



Apache Traffic Control Documentation

Release 6.0.1

Apache Traffic Control

Nov 09, 2021

CONTENTS

1	CDN Basics	3
1.1	CDN Basics	3
2	Traffic Control Overview	7
2.1	Traffic Control Overview	7
3	Administrator's Guide	87
3.1	Administrator's Guide	87
4	Developer's Guide	253
4.1	Developer's Guide	253
5	APIs	365
5.1	Traffic Ops API	365
6	Tools	2057
6.1	Tools	2057
7	FAQ	2093
7.1	FAQ	2093
8	Indices and Tables	2095
8.1	Glossary	2095
	Python Module Index	2109
	Index	2111

The vast majority of today's Internet traffic is media files being sent from a single source to many thousands or even millions of destinations. Content Delivery Networks make that one-to-many distribution possible in an economical way.

Traffic Control is an Open Source implementation of a Content Delivery Network.

The following documentation sections are available:

CDN BASICS

A review of the basic functionality of a Content Delivery Network.

1.1 CDN Basics

Traffic Control is a CDN control plane, see the topics below to familiarize yourself with the basic concepts of a CDN.

1.1.1 Content Delivery Networks

The vast majority of today's Internet traffic is media files (often video or audio) being sent from a single source (the *Content Provider*) to many thousands or even millions of destinations (the *Content Consumers*). CDN (Content Delivery Network)s are the technology that make that one-to-many distribution efficient. A CDN is a distributed system of servers for delivering content over HTTP(S). These servers are deployed in multiple locations with the goal of optimizing the delivery of content to the end users, while minimizing the traffic on the network. A CDN typically consists of the following:

cache servers The *cache server* is a server that both proxies the requests and caches the results for reuse. Traffic Control uses [Apache Traffic Server](#) to provide *cache servers*.

Content Router A *content router* ensures that the end user is connected to the optimal *cache server* for the location of the end user and content availability. Traffic Control uses [Traffic Router](#) as a *content router*.

Health Protocol The [Health Protocol](#) monitors the usage of the *cache servers* and tenants in the CDN.

Configuration Management System In many cases a CDN encompasses hundreds or even thousands of servers across a large geographic area. In such cases, manual configuration of servers becomes impractical, and so a central authority on configuration is used to automate the tasks as much as possible. [Traffic Ops](#) is the Traffic Control configuration management system, which is interacted with via [Traffic Portal](#).

Log File Analysis System Statistics and analysis are extremely important to the management and administration of a CDN. Transaction logs and usage statistics for a Traffic Control CDN are gathered into [Traffic Stats](#).

1.1.2 HTTP/1.1

For a comprehensive look at Traffic Control, it is important to understand basic HTTP/1.1 protocol operations and how *cache servers* function.

See also:

For complete details on HTTP/1.1 see [RFC 2616](#).

What follows is a sequence of events that take place when a client requests content from an HTTP/1.1-compliant server.

1. The client sends a request to the LDNS (Local DNS) server to resolve the name `www.origin.com` to an IP address, then sends an HTTP request to that IP.

Note: A DNS response is accompanied by a TTL (Time To Live) which indicates for how long a name resolution should be considered valid. While longer DNS TTLs of a day (86400 seconds) or more are quite common in other use cases, in CDN use-cases DNS TTLs are often below a minute.

1: A Client Request for `/foo/bar/fun.html` from `www.origin.com`

```
GET /foo/bar/fun.html HTTP/1.1
Host: www.origin.com
```

2. The server at `www.origin.com` looks up the content of the path `/foo/bar/fun.html` and sends it in a response to the client.

2: Server Response

```
HTTP/1.1 200 OK
Content-Type: text/html; charset=UTF-8
Content-Length: 45

<!DOCTYPE html><html><body>This is a fun file</body></html>
```

1.1.3 Cache Control Headers and Revalidation

The HTTP/1.1 specification in [RFC 2616#section-14.9](#) allows for origin servers and clients to influence how caches treat their requests and responses. By default, the Traffic Control CDN will honor cache control headers. Most commonly, origin servers will tell the downstream caches how long a response can be cached.

Note: The terms “content revalidation” and “content invalidation” are often convoluted when referring to the same behavior. Within the context of Traffic Control, the two should be consid-

ered synonymous.

3: This Response may Only be Cached for 86400 Seconds

```
HTTP/1.1 200 OK
Date: Sun, 14 Dec 2014 23:22:44 GMT
Server: Apache/2.2.15 (Red Hat)
Last-Modified: Sun, 14 Dec 2014 23:18:51 GMT
ETag: "1aa008f-2d-50a3559482cc0"
Cache-Control: max-age=86400
Content-Length: 45
Connection: close
Content-Type: text/html; charset=UTF-8

<!DOCTYPE html><html><body>This is a fun file</body></html>
```

The `max-age` directive in the `Cache-Control` header tells downstream caching systems that the maximum time for which they are allowed to cache this response is the specified number of seconds. The origin can also add an `Expires:` header, explicitly telling the cache the time this response is to be expired. When a response is expired it usually doesn't get deleted from the cache, but, when a request comes in that would have hit on this response if it was not expired, the cache *revalidates* the response. In particular, this is the way ATS (Apache Traffic Server) handles content revalidation. Instead of requesting the object again from the origin server, the cache will send a request to the origin indicating what version of the response it has, and asking if it has changed. If it changed, the server will send a `200 OK` response, with the new data. If it has not changed, the origin server will send back a `304 Not Modified` response indicating the response is still valid, and that the cache can reset the timer on the response expiration. To indicate what version the client (cache) has it will add an `If-Not-Modified-Since:` header, or an `If-None-Match:` header. For example, in the `If-None-Match:` case, the origin will have sent an `ETag` header that uniquely identifies the response. The client can then later use that in a revalidation request to check if the `ETag` of the requested content has changed.

4: The Cache Server Sends a Request with the Old ETag Value in the If-None-Match Header

```
GET /foo/bar/fun.html HTTP/1.1
If-None-Match: "1aa008f-2d-50a3559482cc0"
Host: www.origin.com
```

If the content has changed (meaning, the new response would not have had the same `ETag`) the server **MUST** respond with the up-to-date content, usually in the body of a `200 OK` response.

5: The Origin Responds with the Modified Content and a New ETag

```
HTTP/1.1 200 OK
Date: Sun, 18 Dec 2014 3:22:44 GMT
Server: Apache/2.2.15 (Red Hat)
```

(continues on next page)

(continued from previous page)

```
Last-Modified: Sun, 14 Dec 2014 23:18:51 GMT
ETag: "1aa008f-2d-50aa00feadd"
Cache-Control: max-age=604800
Content-Length: 49
Connection: close
Content-Type: text/html; charset=UTF-8

<!DOCTYPE html><html><body>This is NOT a fun file</body></html>
```

If the content did not change (meaning, the response would have had the same ETag) the server SHOULD respond with a 304 Not Modified. In most cases, the server will also send back an ETag header, since the client is allowed to send multiple ETag values in its If-None-Match header to check against multiple cached versions of the content, and the ETag will tell it which specifically is the current plugin version. This is a very rare use case, and ATS will not make use of this feature without a plugin to modify its behavior.

6: The Content has not been Modified so the Server Indicates
the Cached Version is Up-To-Date

```
HTTP/1.1 304 Not Modified
Date: Sun, 18 Dec 2014 3:22:44 GMT
Server: Apache/2.2.15 (Red Hat)
Last-Modified: Sun, 14 Dec 2014 23:18:51 GMT
ETag: "1aa008f-2d-50a3559482cc0"
Cache-Control: max-age=604800
Connection: close
```

TRAFFIC CONTROL OVERVIEW

An introduction to the Traffic Control architecture, components, and their integration.

2.1 Traffic Control Overview

Introduces the Traffic Control architecture, components, and their integration.

2.1.1 Cache Groups

A *Cache Group* is - ostensibly - exactly what it sounds like it is: a group of *cache servers*. More specifically, every server in a Traffic Control CDN must be in a Cache Group (even if they are not actually *cache servers*). Typically a Cache Group is representative of the available *cache servers* within a specific geographical location. Despite that *cache servers* have their own *Physical Locations*, when *cache servers* are chosen to serve content to a client based on geographic location the geographic location actually used for comparisons is that for the Cache Group that contains it, not the geographic location of the *cache server* itself.

The most typical *Types* of Cache Groups are *EDGE_LOC* which contain *Edge-tier cache servers* and *MID_LOC* which contain *Mid-tier cache servers*. The latter are each designated as a *Parent* of one or more of the former to fill out the two-tiered caching hierarchy of an ATC (Apache Traffic Control) CDN.

Consider the example CDN in [Fig. 1](#). Here some country/province/region has been divided into quarters: Northeast, Southeast, Northwest, and Southwest. The arrows in the diagram indicate the flow of requests. If a client in the Northwest, for example, were to make a request to the *Delivery Service*, it would first be directed to some *cache server* in the “Northwest” Edge-tier *Cache Group*. Should the requested content not be in cache, the Edge-tier server will select a parent from the “West” *Cache Group* and pass the request up, caching the result for future use. All Mid-tier *Cache Groups* (usually) answer to a single *Origin* that provides canonical content. If requested content is not in the Mid-tier cache, then the request will be passed up to the *Origin* and the result cached.




Fig. 1: An example CDN that shows the hierarchy between four Edge-tier *Cache Groups*, two Mid-tier *Cache Groups*, and one Origin

Regions, Divisions, and Locations

In addition to being in a Cache Group, all servers have to have a *Physical Location*, which defines their geographic latitude and longitude. Each *Physical Location* is part of a *Region*, and each *Region* is part of a *Division*. For example, Denver could be the name of a *Physical Location* in the Mile High *Region* and that *Region* could be part of the West *Division*. The hierarchy between these terms is illustrated graphically in *Topography Hierarchy*.

To create these structures in Traffic Portal, first make at least one *Division* under *Topology* → *Divisions*. Next enter the desired *Region*(s) in *Topology* → *Regions*, referencing the earlier-entered *Division*(s). Finally, enter the desired *Physical Location*(s) in *Topology* → *Phys Locations*, referencing the earlier-entered *Region*(s).

A Cache Group is a logical grouping of cache servers, that don’t have to be in the same *Physical Location* (in fact, usually a Cache Group is spread across minimally two *Physical Locations* for redundancy purposes), but share geographical coordinates for content routing purposes. There is no strict requirement that *cache servers* in a Cache Group share a *Physical Location*, *Region*, or *Division*. This may be confusing at first as there are a few places in code, interfaces, or even documentation where Cache Groups are referred to as “Cache Locations” or even erroneously as “Physical Locations”.

Properties

Cache Groups are modeled several times over, in the Traffic Ops database, in Traffic Portal forms and tables, and several times for various *Traffic Ops API* versions in the new Go Traffic Ops codebase. Go-specific data structures can be found in the project’s [GoDoc documentation](#). Rather than application-specific definitions, what follows is an attempt at consolidating all of the different properties and names of properties of Cache Group objects throughout the ATC suite. The names of these fields are typically chosen as the most human-readable and/or most commonly-used names for the fields, and when reading please note that in many cases these names will appear camelCased or snake_cased to be machine-readable. Any aliases of these fields that are not merely case transformations of the indicated, canonical names will be noted in a table of aliases.

See also:

The API reference for Cache Group-related endpoints such as *cachegroups* contains definitions of the Cache Group object(s) returned and/or accepted by those endpoints.




Fig. 2: Topography Hierarchy

ASNs

A Cache group can have zero or more ASNs (Autonomous System Numbers) assigned to it, which is used to classify traffic that passes through a CDN. These are typically not represented on a Cache Group object itself, but rather as a separate object indicating the relationship, e.g. in the requests and responses of the *asns* endpoint.

See also:

The [Autonomous System Wikipedia](#) page for an explanation of what an ASN (Autonomous System Number) actually is.

Coordinate

Tip: Normally, one need not interact with this. In most contexts, this property of a Cache Group is not even exposed, but instead the Cache Group's *Latitude* and *Longitude* are exposed and should be directly manipulated.

The *Coordinate* of a Cache Group defines the geographic coordinates of a Cache Group that is used for routing clients based on geographic location. It is also used to determine the “closest” Cache Group to another for the purposes of *Fallback to Closest*.

Typically, this is expressed as an integral, unique identifier for the “Coordinate” object bound to the Cache Group that defines its geographic location, but occasionally it may appear as the name of that “Coordinate” object.

Note: When a new Cache Group is created, it is not necessary to first create a “Coordinate” object where it may reside. Instead, “Coordinates” are created automatically to reflect the *Latitude* and *Longitude* given to the newly created Cache Group. The name of the generated “Coordinate” will conform to the pattern `from_cachegroup_Name` where Name is the Cache Group's *Name*. Because of this, creating new Cache Groups will fail if a “Coordinate” with a name matching that pattern already exists.

Fallbacks

Fallbacks are a group of zero or more Cache Groups to be considered for routing when a Cache Group becomes unavailable due to high load or excessive maintenance. These are normally represented by an array of each Cache Group's *ID*, but may occasionally appear as the *Name* or *Short Name* of each Cache Group.

This set is consulted before *Fallback to Closest* is taken into consideration.

See also:

Health Protocol

Table 1: Aliases

Name	Use(s)	Type(s)
Failover Cache Groups	Traffic Portal forms - but not tables	List or array of <i>Names</i> as strings
backupLoca- tions	In CDN <i>Snapshots</i>	A sub-object called “list” which is a list or array of Cache Group <i>Names</i> as strings
Backup- CacheGroups	Traffic Router source code	A List of strings that are the <i>Names</i> of Cache Groups

Fallback to Closest

This is a boolean field which, when `true` (`True`, `TRUE` etc.) causes routing to “fall back” on the nearest Cache Group - geographically - when this Cache Group becomes unavailable due to high load and/or excessive maintenance.

When this *is* a “true” value, the closest Cache Group will be chosen if and only if any set of *Fallbacks* configured on the Cache Group has already been exhausted and no available Cache Groups were found..

See also:

Health Protocol

Table 2: Aliases

Name	Use(s)	Type(s)
Fallback to Geo Failover	Traffic Portal forms	Unchanged (<code>bool</code> , <code>Boolean</code> etc.)

ID

All Cache Groups have an integral, unique identifier that is mainly used to reference it in the *Traffic Ops API*.

Despite that a Cache Group’s *Name* must be unique, this is the identifier most commonly used to represent a unique Cache Group in most contexts throughout ATC. One notable exception is in CDN *Snapshots* and in routing configuration used by Traffic Router.

Latitude

The Cache Group’s geomagnetic latitude for use in routing and for the purposes of *Fallback to Closest*.

Table 3: Aliases

Name	Use(s)	Type(s)
Geo Magnetic Latitude	Traffic Portal forms	Unchanged (<code>number</code> , <code>float</code> etc.)

Localization Methods

The *Localization Methods* of a Cache Group define the methods by which Traffic Router is allowed to route clients to *cache servers* within this Cache Group. This is a collection of the allowed methods, and the values in the collection are restricted to the following.

- “Coverage Zone File” (alias CZ in source code, database entries, and *Traffic Ops API* requests/responses) allows Traffic Router to direct clients to this Cache Group if they were assigned a geographic location by looking up their IP address in the *Coverage Zone File*.
- “Deep Coverage Zone File” (alias DEEP_CZ in source code, database entries, and *Traffic Ops API* requests/responses) was intended to allow Traffic Router to direct clients to this Cache Group if they were assigned a geographic location by looking up their IP addresses in the *Deep Coverage Zone File*. However, it **has no effect at all**. This option therefore will not appear in Traffic Portal forms.

Warning: In order to make use of “deep caching” for a *Delivery Service*, all that is required is that *Delivery Service* has *Deep Caching* enabled. If that is done and a *cache server* appears in the *Deep Coverage Zone File* then clients can and will be routed using that method. There is no way to disable this behavior on a Cache Group (or otherwise) basis, and the precense or absence of DEEP_CZ in a Cache Group’s Localization Methods has no meaning.

- “Geo-IP Database” (alias GEO in source code, database entries, and *Traffic Ops API* requests/responses) allows Traffic Router direct clients to this Cache Group if the client’s IP was looked up in a provided IP address-to-geographic location mapping database to provide their geographic location.

If none of these localization methods are in the set of allowed methods on a Cache Group, it is assumed that *clients should be allowed to be routed to that Cache Group regardless of the method used to determine their geographic location*.

This property only has meaning for Cache Groups containing *Edge-tier cache servers*. Which is to say (one would hope) that it only has meaning for *EDGE_LOC* Cache Groups.

Table 4: Aliases

Name	Use(s)	Type(s)
Enabled Localization Methods	Traffic Portal forms, Traffic Router source code	Unchanged (Set<String>, Array<string> etc.)

Longitude

The Cache Group’s geomagnetic longitude for use in routing and for the purposes of *Fallback to Closest*.

Table 5: Aliases

Name	Use(s)	Type(s)
Geo Magnetic Longitude	Traffic Portal forms	Unchanged (number, float etc.)

Name

A unique, human-friendly name for the Cache Group, with no special character restrictions or length limit.

Though this property must be unique for all Cache Groups, *ID* is more commonly used as a unique identifier for a Cache Group in most contexts.

Table 6: Aliases

Name	Use(s)	Type(s)
locationID	CDN <i>Snapshots</i>	Unchanged (str, String etc.)

Parent

A Cache Group can have a *parent* Cache Group which has different meanings based on the Cache Group’s *Type*.

- An *EDGE_LOC* Cache Group’s parent must be a *MID_LOC* Cache Group. When configuration files are generated for *Edge-tier cache servers*, their *parents* (different from a Cache Group parent) will be selected from the *Mid-tier cache servers* contained within the Cache Group that is the parent of their containing Cache Group.
- A *MID_LOC* Cache Group’s parent must be an *ORG_LOC* Cache Group. However, if any given *MID_LOC* *either doesn’t have a parent, or does and it’s an ORG_LOC*, then **all *ORG_LOC* Cache Groups - even across CDNs - will be considered the parents of that *MID_LOC* Cache Group.** This parent relationship only has any meaning in the context of “multi-site-origins”, as they are unnecessary in other scenarios.

See also:

Configure Multi-Site Origin

- For all other Cache Group *Types*, parent relationships have no meaningful semantics.

Danger: There is no safeguard in the data model or *Traffic Ops API* that ensures these relationships hold. If they are violated, the resulting CDN behavior is undefined - and almost certainly undesirable.

Parents are typically represented by their *ID*, but may occasionally appear as their *Name*.

See also:

The Apache Traffic Server documentation for the “parent.config” configuration file. ATC parentage relationships boil down to the `parent` field of that configuration file, which sets the *parents* of *cache servers*.

Table 7: Aliases

Name	Use(s)	Type(s)
Parent Cache Group	Traffic Portal forms and tables	Unchanged (str, String etc.)
Parent-CacheGroupID	Traffic Ops database, Traffic Ops Go code, <i>Traffic Ops API</i> requests and responses	Positive integer (int, bigint etc.)
Parent-CacheGroup-Name	Traffic Ops database, Traffic Ops Go code, <i>Traffic Ops API</i> requests and responses	Unchanged (str, String etc.)

Parameters

For unknown reasons, it’s possible to assign *Parameters* to Cache Groups. This has no attached semantics respected by ATC, and exists today only for compatibility purposes.

These are nearly always represented as a collection of *Parameter IDs* but occasionally they can be expressed as full *Parameter* objects.

Table 8: Aliases

Name	Use(s)	Type(s)
cachegroup-Parameters	Certain <i>Traffic Ops API</i> responses, sometimes in internal Go code	Usually a tuple of associative information like a Cache Group ID and a Parameter ID

Secondary Parent

A *secondary parent* of a Cache Group is used for fall-back purposes on a *cache server*-to-*cache server* basis after routing has already occurred (in contrast with *Fallbacks* and *Fallback to Closest* which operate at the routing step on a Cache Group-to-Cache Group basis).

For an explanation of what it means for one Cache Group to be the *Parent* of another, refer to the *Parent* section.

See also:

The Apache Traffic Server documentation for the “parent.config” configuration file. ATC secondary parentage relationships boil down to the `secondary_parent` field of that configuration file, which sets the “secondary parents” of *cache servers*.

Table 9: Aliases

Name	Use(s)	Type(s)
Secondary Parent Cache Group	Traffic Portal forms and tables	Unchanged (str, String etc.)
SecondaryParent-CacheGroupID	Traffic Ops database, Traffic Ops Go code, <i>Traffic Ops API</i> requests and responses	Positive integer (int, bigint etc.)
SecondaryParent-CacheGroupName	Traffic Ops database, Traffic Ops Go code, <i>Traffic Ops API</i> requests and responses	Unchanged (str, String etc.)

Servers

The primary purpose of a Cache Group is to contain servers. In most scenarios it is implied or assumed that the servers are *cache servers*, but this is not required and in fact it is not by any means uncommon for the contained servers to be of some other arbitrary *Type*.

A Cache Group can have zero or more assigned servers, and each server can belong to at most one Cache Group.

Short Name

This is typically an abbreviation of the Cache Group's *Name*. The main difference is that it isn't required to be unique.

Type

A Cache Group's *Type* determines what kind of servers it contains. Note that there's no real restriction on the kinds of servers that a Cache Group can contain, and this *Type* serves as more of a guide in certain contexts. The *Types* available by default are described in this section.

Tip: Because *Types* are mutable, the actual *Types* that can describe Cache Groups cannot be completely or precisely defined. However, there are no good reasons of which this author can think to modify or delete the default *Types* herein described, and honestly the good reasons to even merely add to their ranks are likely few.

Table 10: Aliases

Name	Use(s)	Type(s)
Type ID	Traffic Ops client and server Go code, <i>Traffic Ops API</i> requests and responses	positive integer (int, bigint, etc.)
Type Name	<i>Traffic Ops API</i> requests and responses, Traffic Ops database	unchanged (string, String etc.)

EDGE_LOC

This *Type* of Cache Group contains *Edge-tier cache servers*.

MID_LOC

This *Type* of Cache Group contains *Mid-tier cache servers*.

ORG_LOC

This *Type* of Cache Group contains *Origins*. The primary purpose of these is to group *Origins* for the purposes of “multi-site-origins”, and it’s suggested that if that doesn’t meet your use-case that these be mostly avoided. In general, it’s not strictly necessary to create *Origin servers* in ATC at all, unless you have to support “multi-site-origins”.

See also:

Configure Multi-Site Origin

TC_LOC

A catch-all *Type* of Cache Group that’s meant to house infrastructure servers that gain no special semantics based on the Cache Group containing them, e.g. Traffic Portal instances.

TR_LOC

This *Type* of Cache Group is meant specifically to contain Traffic Router instances.

2.1.2 Delivery Service Requests

A DSR (Delivery Service Request) is a request to create a new *Delivery Service*, delete an existing *Delivery Service*, or modify an existing *Delivery Service*. The model for a DSR is, therefore, somewhat nebulous as it depends on the model of a *Delivery Service*. This concept is not to be confused with *deliveryservices/request*.

See also:

Delivery Service Requests for information about how to use DSRs in

See also:

The API reference for Delivery Service-related endpoints such as *deliveryservice_requests* contains definitions of the Delivery Service object(s) returned and/or accepted by those endpoints.

See also:

The github.com/apache/trafficcontrol/lib/go-tc.DeliveryServiceRequestV30 Go structure documentation.

The model for a DSR in the most recent version of the *Traffic Ops API* is given in *Delivery Service Request as a Typescript Interface* as a Typescript interface.

7: Delivery Service Request as a Typescript Interface

```
interface DeliveryServiceRequest {
  assignee: string | null;
  author: string;
  changeType: 'create' | 'delete' | 'update';
  createdAt: Date; // RFC3339 string - response-only field
  id?: number; // response-only field
  lastEditedBy: string; // response-only field
  lastUpdated: Date; // RFC3339 string - response-only field
  original?: DeliveryService;
  requested?: DeliveryService;
  status: 'draft' | 'pending' | 'submitted' | 'rejected' | 'complete
  →';
}
// Specifically, every DSR will be one of the following more "concrete
  →" types.
interface CreatedSR extends DeliveryServiceRequest {
  changeType: 'create';
  original: undefined;
  requested: DeliveryService;
}
interface DeletedSR extends DeliveryServiceRequest {
  changeType: 'delete';
  original: DeliveryService;
  requested: undefined;
}
interface UpdatedSR extends DeliveryServiceRequest {
  changeType: 'update';
  original: DeliveryService;
  requested: DeliveryService;
}
```

Assignee

Assignee is the username of the user to whom the DSR is assigned. It may be null-typed if there is no assignee for a given DSR.

Table 11: Aliases/Synonyms

Name	Use(s)	Type
assigneeId	older API versions, internally in Traffic Control code	unsigned integer

Author

Author is the username of the user who created the DSR.

Table 12: Aliases/Synonyms

Name	Use(s)	Type
authorId	older API versions, internally in Traffic Control code	unsigned integer

Change Type

This string indicates the action that will be taken in the event that the DSR is fulfilled. It can be one of the following values:

create A new *Delivery Service* will be created

delete An existing *Delivery Service* will be deleted

update An existing *Delivery Service* will be modified

Created At

This is the date and time at which the DSR was created. In the context of the *Traffic Ops API*, it is formatted as an **RFC 3339** date string except where otherwise noted.

ID

An integral, unique identifier for the DSR.

Last Edited By

This is the username of the user by whom the DSR was last edited. Author is the username of the user who created the DSR.

Table 13: Aliases/Synonyms

Name	Use(s)	Type
lastEditedById	older API versions, internally in Traffic Control code	unsigned integer

Original

If this property of a DSR exists, then it represents the original *Delivery Service* before the DSR was/would have been/is fulfilled. This property only exists on DSRs that have a *Change Type* of “update” or “delete”. This is a full representation of a *Delivery Service*, and so in the context of *Traffic Ops API* has the same structure as a request to or response from the *deliveryservices* endpoint, as appropriate for its *Change Type*.

Table 14: Aliases/Synonyms

Name	Use(s)	Type
deliv- eryser- vice	older API versions combined the concepts of Original and <i>Requested</i> into this single field	unchanged (<i>Delivery Service</i> representation)

Requested

If this property of a DSR exists, then it represents the *Delivery Service* the creator wishes to exist - possibly in place of an existing *Delivery Service* that shares its identifying properties. This property only exists on DSRs that have a *Change Type* of “update” or “create”. This is a full representation of a *Delivery Service*, and so in the context of *Traffic Ops API* has the same structure as a request to or response from the *deliveryservices* endpoint, as appropriate for its *Change Type*.

Table 15: Aliases/Synonyms

Name	Use(s)	Type
deliv- eryser- vice	older API versions combined the concepts of <i>Original</i> and Requested into this single field	unchanged (<i>Delivery Service</i> representation)

Status

Status is a string that indicates the point in the DSR workflow lifecycle at which a given DSR is. Generally a DSR may be either “open” - meaning that it is available to be modified, reviewed, and possibly either completed or rejected - or “closed” - meaning that it has been completed or rejected. More specifically, “open” DSRs have one of the following Statuses:

draft The DSR is not yet ready for completion or review that might result in rejection, as it is still being actively worked on.

submitted The DSR has been submitted for review, but has not yet been reviewed.

... while a “closed” DSR has one of these Statuses:

complete The DSR was approved and its declared action was taken.

pending The DSR was approved and the changes are applied, but the new configuration is not yet disseminated to other ATC components - usually meaning that it cannot be considered truly complete until a *Snapshot* is taken or a *Queue Updates* performed.

rejected The DSR was rejected and closed; it cannot be completed.

A “closed” DSR cannot be edited - except to change a “pending” Status to “complete” or “rejected”.

2.1.3 Delivery Services

“Delivery Services” are a very important construct in ATC. At their most basic, they are a source of content and a set of *cache servers* and configuration options used to distribute that content.

Delivery Services are modeled several times over, in the Traffic Ops database, in Traffic Portal forms and tables, and several times for various *Traffic Ops API* versions in the new Go Traffic Ops codebase. Go-specific data structures can be found in [the project’s GoDoc documentation](#). Rather than application-specific definitions, what follows is an attempt at consolidating all of the different properties and names of properties of Delivery Service objects throughout the ATC suite. The names of these fields are typically chosen as the most human-readable and/or most commonly-used names for the fields, and when reading please note that in many cases these names will appear camelCased or snake_cased to be machine-readable. Any aliases of these fields that are not merely case transformations of the indicated, canonical names will be noted in a table of aliases.

See also:

The API reference for Delivery Service-related endpoints such as *deliverservices* contains definitions of the Delivery Service object(s) returned and/or accepted by those endpoints.

See also:

Delivery Service Requests

Active

Whether or not this Delivery Service is active on the CDN and can be served. When a Delivery Service is not “active”, Traffic Router will not be made aware of its existence - i.e. it will not appear in CDN *Snapshots*. Setting a Delivery Service to be “active” (or “inactive”) will require that a new *Snapshot* be taken.

Anonymous Blocking

Enables/Disables blocking of anonymized IP address - proxies, TOR (The Onion Ring) exit nodes, etc - for this Delivery Service. Set to true to enable blocking of anonymous IPs for this Delivery Service.

Table 16: Aliases

Name	Use(s)	Type(s)
anony-mous-Blockin-gEnabled	Traffic Ops client and server Go code, <i>Traffic Ops API</i> requests and responses	usually unchanged (boolean), but sometimes as a string containing a boolean e.g. in the response of a GET request to <i>cdns/{{name}}/snapshot</i>

Note: Anonymous Blocking requires an anonymous IP address database from the Delivery Service’s Geolocation Provider. E.g. [MaxMind’s Anonymous IP Database](#) when MaxMind is used as the Geolocation Provider.

See also:

The *Configure Anonymous Blocking* “Quick-How-To” guide.

Cache URL Expression

Deprecated since version 3.0: This feature is no longer supported by ATS and consequently it will be removed from Traffic Control in the future. Current plans are to remove after ATC 5.X is no longer supported.

Manipulates the cache key of the incoming requests. Normally, the cache key is the *Origin* domain. This can be changed so that multiple services can share a cache key, can also be used to preserve cached content if service origin is changed.

Warning: This field provides access to a feature that was only present in ATS 6.X and earlier. As *cache servers* must now use ATS 7.1.X, this field **must** be blank unless all *cache servers* can be guaranteed to use that older ATS version (**NOT** recommended).

CDN

A CDN to which this Delivery Service belongs. Only *cache servers* within this CDN are available to route content for this Delivery Service. Additionally, only Traffic Routers assigned to this CDN will perform said routing. Most often `cdn/CDN` refers to the *name* of the CDN to which the Delivery Service belongs, but occasionally (most notably in the payloads and/or query parameters of certain *Traffic Ops API* endpoints) it actually refers to the *integral, unique identifier* of said CDN.

Check Path

A request path on the *origin server* which is used to by certain *Traffic Ops Extensions* to indicate the “health” of the *Origin*.

Consistent Hashing Regular Expression

When Traffic Router performs *Consistent Hashing* on a client request to find an *Edge-tier cache server* to which to redirect them, it can optionally first modify the request path by extracting the pieces that match this regular expression.

See also:

Consistent Hashing Patterns

Table 17: Aliases

Name	Use(s)	Type(s)
consisten-tHashRegex	In source code and <i>Traffic Ops API</i> requests and responses	unchanged (regular expression)
pattern-based consistent hashing	documentation and the Traffic Portal UI	unchanged (regular expression), but usually used when discussing the concept rather than the field

Consistent Hashing Query Parameters

When Traffic Router performs *Consistent Hashing* on a client request to find an *Edge-tier cache server* to which to redirect them, it can optionally take into account any number of query parameters. This field defines them, formally as a Set but often represented as an Array/List due to encoding limitations. That is, if the Consistent Hashing Query Parameters on a Delivery Service are `{test}` and a client makes a request for `/?test=something` they will be directed to a different *cache server* than a different client that requests `/?test=somethingElse`, but the *same cache server* as a client that requests `/?test=something&quest=somethingToo`.

Table 18: Aliases

Name	Use(s)	Type(s)
consistentHash-Query-Params	In source code, Traffic Portal, and <i>Traffic Ops API</i> requests and responses	unchanged (Array of strings - should ALWAYS be unique, thus treated as a Set in most contexts)

Deep Caching

Controls the *Deep Caching* feature of Traffic Router when serving content for this Delivery Service. This should always be represented by one of two values:

ALWAYS This Delivery Service will always use *Deep Caching*

NEVER This Delivery Service will never use *Deep Caching*

Implementation Detail

Traffic Ops and Traffic Ops client Go code use an empty string as the name of the enumeration member that represents “NEVER”.

Display Name

The “name” of the Delivery Service. Since nearly any use of a string-based identification method for Delivery Services (e.g. in Traffic Portal tables) uses *xml_id*, this is of limited use. For that reason and for consistency’s sake it is suggested that this be the same as the *xml_id*. However, unlike the *xml_id*, this can contain any UTF-8 characters without restriction.

DNS Bypass CNAME

When the limits placed on this Delivery Service by the *Global Max Mbps* and/or *Global Max Tps* are exceeded, a DNS-*Routed* Delivery Service will direct excess traffic to the host referred to by this CNAME (Canonical Name) record.

Note: IPv6 traffic will be redirected if and only if *IPv6 Routing Enabled* is “true” for this Delivery Service.

DNS Bypass IP

When the limits placed on this Delivery Service by the *Global Max Mbps* and/or *Global Max Tps* are exceeded, a DNS-*Routed* Delivery Service will direct excess IPv4 traffic to this IPv4 address.

DNS Bypass IPv6

When the limits placed on this Delivery Service by the *Global Max Mbps* and/or *Global Max Tps* are exceeded, a DNS-*Routed* Delivery Service will direct excess IPv6 traffic to this IPv6 address.

Note: This requires an accompanying configuration of *IPv6 Routing Enabled* such that IPv6 traffic is allowed at all.

DNS Bypass TTL

When the limits placed on this Delivery Service by the *Global Max Mbps* and/or *Global Max Tps* are exceeded, a DNS-*Routed* Delivery Service will direct excess traffic to their *DNS Bypass IP*, *DNS Bypass IPv6*, or *DNS Bypass CNAME*.

DNS TTL

The TTL on the DNS record for the Traffic Router A and AAAA records. DNS-*Routed* Delivery Services will send this TTL along with their record responses to clients requesting access to this Delivery Service. Setting too high or too low will result in poor caching performance.

Table 19: Aliases

Name	Use(s)	Type(s)
CCR DNS TTL	In Delivery Service objects returned by the <i>Traffic Ops API</i>	unchanged (int, integer etc.)
CCR TTL	Legacy Traffic Ops UI, documentation for older Traffic Control versions	unchanged (int, integer etc.)
ttl	In CDN <i>Snapshot</i> structures, where it is displayed on a per-record-type-basis	map of record type names to integral values

DSCP

The DSCP (Differentiated Services Code Point) which will be used to mark IP packets as they are sent out of the CDN to the client.

See also:

[The Differentiated Services Wikipedia article.](#)

Warning: The DSCP setting in Traffic Portal is *only* for setting traffic towards the client, and gets applied *after* the initial TCP handshake is complete and the HTTP request has been received. Before that the cache can't determine what Delivery Service is being requested, and consequently can't know what DSCP to apply. Therefore, the DSCP feature can not be used for security settings; the IP packets that form the TCP handshake are not going to be DSCP-marked.

Implementation Detail

DSCP settings only apply on *cache servers* that run `APACHE TRAFFIC SERVER`. The implementation uses the [ATS Header Rewrite Plugin](#) to create a rule that will mark traffic bound outward from the CDN to the client.

Edge Header Rewrite Rules

This field in general contains the contents of the a configuration file used by the [ATS Header Rewrite Plugin](#) when serving content for this Delivery Service - on *Edge-tier cache servers*.

Tip: Because this ultimately is the contents of an ATS configuration file, it can make use of the *Strings with Special Meaning to t3c*.

Note: This field cannot be used if the Delivery Service is assigned to a *Topology*.

EDNS0 Client Subnet Enabled

A boolean value that controls whether or not EDNS0 client subnet is enabled on this Delivery Service by Traffic Router. When creating a Delivery Service in Traffic Portal, this will default to “false”.

Example URLs

The Example URLs of a Delivery Service are the scheme/host specifications that clients can use to request content through it. These are determined by Traffic Ops from the Delivery Service's configuration, and are read-only in virtually every context. The only reason a Delivery Service should ever have no Example URLs is if it is an ANY_MAP-*Type* Delivery Service (since they are not routed). For example, a Delivery Service that can deliver HTTP and HTTPS content, has a *Routing Name* of “cdn”, an *xml_id* of “demo1”, and belonging to a *CDN* that is authoritative for the *mycdn.ciab.test* domain would have two Example URLs:

- `https://cdn.demo1.mycdn.ciab.test`
- `http://cdn.demo1.mycdn.ciab.test`

Note that these are irrespective of request path; meaning a client can request e.g. `https://cdn.demo1.mycdn.ciab.test/index.html` through this Delivery Service.

Warning: This list does not consider any *Static DNS Entries* configured on the Delivery Service, those are

Table 20: Aliases

Name	Use(s)	Type(s)
Delivery Service URLs	Traffic Portal forms	unchanged (list of strings)

Fair-Queuing Pacing Rate Bps

The maximum bytes per second a *cache server* will deliver on any single TCP connection. This uses the Linux kernel's Fair-Queuing `setsockopt(2)` (`SO_MAX_PACING_RATE`) to limit the rate of delivery. Traffic exceeding this speed will only be rate-limited and not diverted. This option requires extra configuration on all *cache servers* assigned to this Delivery Service - specifically, the line `net.core.default_qdisc = fq` must exist in `/etc/sysctl.conf`.

See also:

`tc-fq_codel(8)`

See also:

This is implemented using the *ATS fq_pacing plgn*.

Table 21: Aliases

Name	Use(s)	Type(s)
FQPacingRate	Traffic Ops source code, Delivery Service objects returned by the <i>Traffic Ops API</i>	unchanged (int, integer etc.)

First Header Rewrite Rules

This field in general contains the contents of the a configuration file used by the [ATS Header Rewrite Plugin](#) when serving content for this Delivery Service - on *First-tier cache servers*.

Tip: Because this ultimately is the contents of an ATS configuration file, it can make use of the *Strings with Special Meaning to t3c*.

Note: This field can only be used if the Delivery Service is assigned to a *Topology*.

Geo Limit

Limits access to a Delivery Service by geographic location. The only practical difference between this and *Regional Geoblocking* is the configuration method; as opposed to *Regional Geoblocking*, GeoLimit configuration is handled by country-wide codes and the *Coverage Zone File*. When a client is denied access to a requested resource on an HTTP-*Routed* Delivery Service, they will receive a 503 Service Unavailable instead of the usual 302 Found response - unless *Geo Limit Redirect URL* is defined, in which case a 302 Found response pointing to that URL will be returned by Traffic Router. If the Delivery Service is a DNS-*Routed* Delivery Service, the IP address of the *resolver* for the client DNS request is what is checked. If the IP address of this resolver is found to be in a restricted location, the Traffic Router will respond with an NXDOMAIN response, causing the name resolution to fail. This is nearly always an integral, unique identifier for a behavior set to be followed by Traffic Router. The defined values are:

- 0 Geographic access limiting is not enabled, and content served by this Delivery Service will be accessible regardless of the clients geographic location. (Aliased as “0 - None” in Traffic Portal forms)
- 1 A client will be allowed to request content if and only if their IP address is found by Traffic Router within the *Coverage Zone File*. Otherwise, access will be denied. (Aliased as “1 - CZF Only” in Traffic Portal forms)
- 2 A client will be allowed to request content if their IP address is found by Traffic Router within the *Coverage Zone File*, or if looking up the client’s IP address in the Geographic IP mapping database provided by *Geolocation Provider* indicates the client resides in a country that is found in the *Geo Limit Countries* array. (Aliased as “2 - CZF + Country Code(s)” in Traffic Portal forms - formerly was known as “CZF + US” when only the US country code was supported)

Warning: The definitions of each integral, unique identifier are hidden in implementations in each ATC component. Different components will handle invalid values differently, and there’s no actual enforcement that the stored integral, unique identifier actually be within the representable range.

Table 22: Aliases

Name	Use(s)	Type(s)
coverageZoneOnly	In CDN <i>Snapshot</i> structures, especially in <i>Traffic Ops API</i> responses	A boolean which, if <code>true</code> , tells Traffic Router to only service requests when the client IP address is found in the <i>Coverage Zone File</i>

Danger: Geographic access limiting is **not** sufficient to guarantee access is properly restricted. The limiting is implemented by Traffic Router, which means that direct requests to *Edge-tier cache servers* will bypass it entirely.

Geo Limit Countries

When *Geo Limit* is being used with this Delivery Service (and is set to exactly 2), this is optionally a list of country codes to which access to content provided by the Delivery Service will be restricted. Normally, this is a comma-delimited string of said country codes. When creating a Delivery Service with this field or modifying the Geo Limit Countries field on an existing Delivery Service, any amount of whitespace between country codes is permissible, as it will be removed on submission, but responses from the *Traffic Ops API* should never include such whitespace.

Table 23: Aliases

Name	Use(s)	Type(s)
geoEnabled	In CDN <i>Snapshot</i> structures, especially in <i>Traffic Ops API</i> responses	An array of objects each having the key “countryCode” that is a string containing an allowed country code - one should exist for each allowed country code

Geo Limit Redirect URL

If *Geo Limit* is being used with this Delivery Service, this is optionally a URL to which clients will be redirected when Traffic Router determines that they are not in a geographic zone that permits their access to the Delivery Service content. This changes the response from Traffic Router from 503 Service Unavailable to 302 Found with a provided location that will be this URL. There is no restriction on the provided URL; it may even be the path to a resource served by this Delivery Service. In fact, this field need not even be a full URL, it can be a relative path. Both of these cases are handled specially by Traffic Router.

- If the provided URL is a resource served by the Delivery Service (e.g. if the client requests `http://cdn.dsXMLID.somedomain.example.com/index.html` but are denied access by *Geo Limit* and the Geo Limit Redirect URL is something like `http://cdn.dsXMLID.somedomain.example.com/help.php`), Traffic Router will find an appropriate *Edge-tier cache server* and redirect the client, ignoring Geo Limit restrictions *for this request only*.

- If the provided “URL” is actually a relative path, it will be considered *relative to the requested Delivery Service :abbr: FQDN (Fully Qualified Domain Name)*. This means that e.g. if the client requests `http://cdn.dsXMLID.somedomain.example.com/index.html` but are denied access by *Geo Limit* and the Geo Limit Redirect URL is something like `/help.php`, Traffic Router will find an appropriate *Edge-tier cache server* and redirect the client to it as though they had requested `http://cdn.dsXMLID.somedomain.example.com/help.php`, ignoring *Geo Limit* restrictions *for this request only*.

Table 24: Aliases

Name	Use(s)	Type(s)
NGB (National GeoBlock)	Older documentation, in Traffic Router comments and error logs	unchanged(string,String etc.)
geoRedirectURLType	Internally in Traffic Router	<p>A <code>String</code> that describes whether or not the actual Geo Limit Redirect URL is relative to the Delivery Service base FQDN (Fully Qualified Domain Name). Should be one of:</p> <p>INVALID_URL The Geo Limit Redirect URL has not yet been parsed, or an error occurred during parsing</p> <p>DS_URL The Geo Limit Redirect URL is served by this Delivery Service</p> <p>NOT_DS_URL The Geo Limit Redirect URL is external to this Delivery Service</p>

Note: The use of a redirect URL relies on the ability of Traffic Router to redirect the client using HTTP 302 Found responses. As such, this field has no effect on DNS-*Routed* Delivery Services.

Geolocation Provider

This is nearly always the integral, unique identifier of a provider for a database that maps IP addresses to geographic locations. Less frequently, this may be accompanied by the actual name of the provider. Only two values are possible at the time of this writing:

0: MaxMind IP address to geographic location mapping will be provided by a [MaxMind GeoIP2 database](#).

1: Neustar IP address to geographic location mapping will be provided by a [Neustar GeoPoint IP address database](#).

Warning: It's not clear whether Neustar databases are actually supported; this is an old option and compatibility may have been broken over time.

Table 25: Aliases

Name	Use(s)	Type(s)
geo-Provider	Traffic Ops and Traffic Ops client code, <i>Traffic Ops API</i> requests and responses	unchanged (integral, unique identifier)

Geo Miss Default Latitude

Default Latitude for this Delivery Service. When the geographic location of the client cannot be determined, they will be routed as if they were at this latitude.

Table 26: Aliases

Name	Use(s)	Type(s)
missLat	In <i>Traffic Ops API</i> responses and Traffic Ops source code	unchanged (numeric)

Geo Miss Default Longitude

Default Longitude for this Delivery Service. When the geographic location of the client cannot be determined, they will be routed as if they were at this longitude.

Table 27: Aliases

Name	Use(s)	Type(s)
miss-Long	In <i>Traffic Ops API</i> responses and Traffic Ops source code	unchanged (numeric)

Global Max Mbps

The maximum Mbps (Megabits per second) this Delivery Service can serve across all *Edge-tier cache servers* before traffic will be diverted to the bypass destination. For a DNS-*Routed* Delivery Service, the *DNS Bypass IP* or *DNS Bypass IPv6* will be used (depending on whether this was a A or AAAA request), and for HTTP-*Routed* Delivery Services the *HTTP Bypass FQDN* will be used.

Table 28: Aliases

Name	Use(s)	Type(s)
totalKbpsThreshold	In <i>Traffic Ops API</i> re- sponses - most notably <i>cdns/{{name}}/configs/monitoring</i>	unchanged (numeric), but converted from MBPS to KBPS (kilobits per sec- ond)

Global Max TPS

The maximum TPS (Transactions per Second) this Delivery Service can serve across all *Edge-tier cache servers* before traffic will be diverted to the bypass destination. For a DNS-*Routed* Delivery Service, the *DNS Bypass IP* or *DNS Bypass IPv6* will be used (depending on whether this was a A or AAAA request), and for HTTP-*Routed* Delivery Services the *HTTP Bypass FQDN* will be used.

Table 29: Aliases

Name	Use(s)	Type(s)
totalTpsThreshold	In <i>Traffic Ops API</i> responses - most notably <i>cdns/{{name}}/configs/monitoring</i>	unchanged (nu- meric)

HTTP Bypass FQDN

When the limits placed on this Delivery Service by the *Global Max Mbps* and/or *Global Max Tps* are exceeded, an HTTP-*Routed* Delivery Service will direct excess traffic to this FULLY QUALIFIED DOMAIN NAME.

IPv6 Routing Enabled

A boolean value that controls whether or not clients using IPv6 can be routed to this Delivery Service by Traffic Router. When creating a Delivery Service in Traffic Portal, this will default to “true”.

Info URL

This should be a URL (though neither the *Traffic Ops API* nor the Traffic Ops Database in any way enforce the validity of said URL) to which administrators or others may refer for further information regarding a Delivery Service - e.g. a related JIRA ticket.

Initial Dispersion

The number of *Edge-tier cache servers* across which a particular asset will be distributed within each *Cache Group*. For most use-cases, this should be 1, meaning that all clients requesting a particular asset will be directed to 1 *cache server* per *Cache Group*. Depending on the popularity and size of assets, consider increasing this number in order to spread the request load across more than 1 *cache server*. The larger this number, the more copies of a particular asset are stored in a *Cache Group*, which can “pollute” caches (if load distribution is unnecessary) and decreases caching efficiency (due to cache misses if the asset is not requested enough to stay “fresh” in all the caches).

Inner Header Rewrite Rules

This field in general contains the contents of the a configuration file used by the *ATS Header Rewrite Plugin* when serving content for this Delivery Service - on *Inner-tier cache servers*.

Tip: Because this ultimately is the contents of an ATS configuration file, it can make use of the *Strings with Special Meaning to t3c*.

Note: This field can only be used if the Delivery Service is assigned to a *Topology*.

Last Header Rewrite Rules

This field in general contains the contents of the a configuration file used by the *ATS Header Rewrite Plugin* when serving content for this Delivery Service - on *Last-tier cache servers*.

Tip: Because this ultimately is the contents of an ATS configuration file, it can make use of the *Strings with Special Meaning to t3c*.

Note: This field can only be used if the Delivery Service is assigned to a *Topology*.

Logs Enabled

A boolean switch that can be toggled to enable/disable logging for a Delivery Service.

Note: This doesn't actually do anything. It was part of the functionality for a planned Traffic Control component named "Traffic Logs" - which was never created.

Long Description

Free text field that has no strictly defined purpose, but it is suggested that it contain a short description of the Delivery Service and its purpose.

Name	Use(s)	Type(s)
longDesc	Traffic Control source code and <i>Traffic Ops API</i> responses	unchanged (string, String etc.)

Match List

A Match List is a set of regular expressions used by Traffic Router to determine whether a given request from a client should be served by this Delivery Service. Under normal circumstances this field should only ever be read-only as its contents should be generated by Traffic Ops based on the Delivery Service's configuration. These regular expressions can each be one of the following types:

HEADER_REGEX This Delivery Service will be used if an HTTP Header/Value pair can be found in the clients request matching this regular expression.⁴

HOST_REGEX This Delivery Service will be used if the requested host matches this regular expression. The host can be found using the `Host` HTTP Header, or as the requested name in a DNS request, depending on the *Type* of the Delivery Service.

PATH_REGEX This Delivery Service will be used if the request path matches this regular expression.[?]

STEERING_REGEX This Delivery Service will be used if this regular expression matches the *xml_id* of one of this Delivery Service's "targets"

Note: This regular expression type can only exist in the Match List of STEERING-*Type* Delivery Services - and **not** CLIENT_STEERING.

⁴ These regular expression types can only appear in the Match List of HTTP-*Routed* Delivery Services.

Table 30: Aliases

Name	Use(s)	Type(s)
deliveryservice_regex	Traffic database	Ops unique, integral identifier for a regular expression

Max DNS Answers

DNS-routed Delivery Service The maximum number of *Edge-tier cache server* IP addresses that the Traffic Router will include in responses to DNS requests. When provided, the *cache server* IP addresses included are rotated in each response to spread traffic evenly. This number should scale according to the amount of traffic the Delivery Service is expected to serve.

HTTP-routed Delivery Service If the Traffic Router profile parameter “edge.http.limit” is set, setting this to a non-zero value will override that parameter for this delivery service, limiting the number of Traffic Router IP addresses (A records) that are included in responses to DNS requests for this delivery service.

Max Origin Connections

The maximum number of TCP connections individual *Mid-tier cache servers* are allowed to make to the *Origin Server Base URL*. A value of 0 in this field indicates that there is no maximum.

Max Request Header Bytes

The maximum size(in bytes) of the request header that is allowed for this Delivery Service.

Mid Header Rewrite Rules

This field in general contains the contents of the a configuration file used by the *ATS Header Rewrite Plugin* when serving content for this Delivery Service - on *Mid-tier cache servers*.

Tip: Because this ultimately is the contents of an ATS configuration file, it can make use of the *Strings with Special Meaning to t3c*.

Note: This field cannot be used if the Delivery Service is assigned to a *Topology*.

Origin Server Base URL

The Origin Server’s base URL which includes the protocol (http or https). Example: `http://movies.origin.com`. Must not include paths, query parameters, document fragment identifiers, or username/password URL fields.

Table 31: Aliases

Name	Use(s)	Type(s)
orgServer-Fqdn	<i>Traffic Ops API</i> responses and in Traffic Control source code	unchanged (usually <code>str</code> , <code>string</code> etc.)

Origin Shield

An experimental feature that allows administrators to list additional forward proxies that sit between the *Mid-tier* and the *Origin*. In most scenarios, this is represented (and required to be input) as a pipe (|)-delimited string.

Profile

Either the *Name* of a *Profile* used by this Delivery Service, or the *ID* of said *Profile*.

Table 32: Aliases

Name	Use(s)	Type(s)
pro-fileId	In Traffic Control source code and some <i>Traffic Ops API</i> responses dealing with Delivery Services	Unlike the more general “Profile”, this is <i>always</i> an integral, unique identifier
pro-file-Name	In Traffic Control source code and some <i>Traffic Ops API</i> responses dealing with Delivery Services	Unlike the more general “Profile”, this is <i>always</i> a name (<code>str</code> , <code>string</code> , etc.)

Protocol

The protocol with which to serve content from this Delivery Service. This defines the way the Delivery Service will handle client requests that are either HTTP or HTTPS, which is distinct from what protocols are used to direct traffic. For example, this can be used to direct clients to only request content using HTTP, or to allow clients to use either HTTP or HTTPS, etc. Normally, this will be the name of the protocol handling, but occasionally this will appear as the integral, unique identifier of the protocol handling instead. The integral, unique identifiers and their associated names and meanings are:

- 0: HTTP** This Delivery Service will only accept unsecured HTTP requests. Requests made with HTTPS will fail.
- 1: HTTPS** This Delivery Service will only accept secured HTTPS requests. Requests made with HTTP will fail.

2: HTTP AND HTTPS This Delivery Service will accept both unsecured HTTP requests and secured HTTPS requests.

3: HTTP TO HTTPS When this Delivery Service is using HTTP *Content Routing* unsecured HTTP requests will be met with a response that indicates to the client that further requests must use HTTPS.

Note: If any other type of *Content Routing* is used, this functionality cannot be used. In those cases, a protocol setting of 3/"HTTP TO HTTPS" will result in the same behavior as 1/"HTTPS". This behavior is tracked by [GitHub Issue #3221](#)

Warning: The definitions of each integral, unique identifier are hidden in implementations in each ATC component. Different components will handle invalid values differently, and there's no actual enforcement that the stored integral, unique identifier actually be within the representable range.

Table 33: Aliases

Name	Use(s)	Type(s)
Protocol	<p>CDN <i>Snapshots</i> An object containing the key "acceptHttps" that is a string containing a boolean which expresses whether or not Traffic Router should redirect HTTP requests to HTTPS URLs. Optionally, the key "acceptHttp" may also appear, once again a string containing a boolean that expresses whether or not Traffic Router should accept unsecured HTTP requests - this is implicitly treated as "true" by Traffic Router when it is not present.</p>	

Query String Handling

Describes how query strings should be handled by the *Edge-tier cache servers* when serving content for this Delivery Service. This is nearly always expressed as an integral, unique identifier for each behavior, though in Traffic Portal a more descriptive value is typically used, or at least provided in addition to the integral, unique identifier. The allowed values and their meanings are:

- 0 For the purposes of caching, *Edge-tier cache servers* will consider URLs unique if and only if they are unique up to and including any and all query parameters. They will also pass the query parameters in their own requests to *Mid-tier cache servers* (which in turn will exhibit the same caching behavior and pass the query parameters in requests to the *Origin*).

(Aliased as “USE” in Traffic Portal tables, and “0 - use qstring in cache key, and pass up” in Traffic Portal forms)

- 1 For the purposes of caching, neither *Edge-tier* nor *Mid-tier cache servers* will consider the query parameter string when determining if a URL is stored in cache. However, the query string will still be passed in upstream requests to *Mid-tier cache servers* and in turn the *Origin*. (Aliased as “IGNORE” in Traffic Portal tables and “1 - ignore in cache key, and pass up” in Traffic Portal forms)
- 2 The query parameter string will be stripped from URLs immediately when the request is received by an *Edge-tier cache server*. This means it is never considered for the purposes of caching unique URLs and will not be passed in upstream requests. (Aliased as “DROP” in Traffic Portal tables and “2 - drop at edge” in Traffic Portal forms)

Warning: The implementation of dropping query parameter strings at the *Edge-tier* uses a *Regex Remap Expression* and thus Delivery Services with this type of query string handling cannot make use of *Regex Remap Expressions*.

Table 34: Aliases

Name	Use(s)	Type(s)
Qstring Handling	Traffic Portal tables	One of the Traffic Portal value aliases “USE” (0), “IGNORE” (1), “DROP” (2)
qstringIgnore	Traffic Ops code, <i>Traffic Ops API</i> requests/responses	unchanged (integral, unique identifier)

The Delivery Service’s Query String Handling can be set directly as a field on the Delivery Service object itself, or it can be overridden by a *Parameter* on a *Profile* used by this Delivery Service. The special *Parameter* named `psel.qstring_handling` and configuration file `parent.config` will have it’s contents directly inserted into the `parent.config` file on all *cache servers* assigned to this Delivery Service.

Danger: Using the `psel.qstring_handling` *Parameter* is **strongly** discouraged for several reasons. Firstly, at a Delivery Service level it will **NOT** change the configuration of that Delivery Service’s own Query String Handling - which will cause it to appear in Traffic Portal and in *Traffic Ops API* responses as though it were configured one way while actually behaving a different way altogether. Also, no validation is performed on the value given to it. Because it’s inserted verbatim into the `qstring` field of a line in ATS `parent.config configuration file`, a typo or an ignorant user can easily cause ATS instances on all *cache servers* assigned to that Delivery Service to fail to reload their configuration, possibly grinding entire CDNs to a halt.

See also:

When implemented as a *Parameter* (`psel.qstring_handling`), its value must be a valid value for the `qstring` field of a line in the ATS `parent.config` configuration file. For a description of valid values, see the [documentation for parent.config](#)

Range Request Handling

Describes how HTTP “Range Requests” should be handled by the Delivery Service at the *Edge-tier*. This is nearly always an integral, unique identifier for the behavior set required of the *Edge-tier cache servers*. The valid values and their respective meanings are:

0 Do not cache Range Requests at all. (Aliased as “0 - Don’t cache” in Traffic Portal forms)

Note: This is not retroactive - when modifying an existing Delivery Services to have this value for “Range Request Handling”, ranges requested from files that are already cached due to a non-range request will be served out of cache for as long as the Cache-Control headers allow.

- 1** Use the `background_fetch` plugin to service the range request while caching the whole object. (Aliased as “1 - Use background_fetch plugin” in Traffic Portal forms)
- 2** Use the `cache_range_requests` plugin to cache ranges as unique objects. (Aliased as “2 - Use cache_range_requests plugin” in Traffic Portal forms)
- 3** Use the `slice` plugin to slice range based requests into deterministic chunks. (Aliased as “3 - Use slice plugin” in Traffic Portal forms)

New in version ATCv4.1.

Note: Range Request Handling can only be implemented on *cache servers* using ATS because of its dependence on ATS plugins. The value may be set on any Delivery Service, but will have no effect when the *cache servers* that ultimately end up serving the content are e.g. Grove, Nginx, etc.

Warning: The definitions of each integral, unique identifier are hidden in implementations in each ATC component. Different components will handle invalid values differently, and there’s no actual enforcement that the stored integral, unique identifier actually be within the representable range.

Range Slice Request Block Size

The block size in bytes that is used for `slice` plugin.

This can only and must be set if the *Range Request Handling* is set to 3.

Raw Remap Text

For HTTP and DNS-*Routed* Delivery Services, this will be added to the end of a line in the `remap.config` ATS configuration file line on the cache verbatim. For ANY_MAP-*Type* Delivery Services this must be defined.

Tip: Because this ultimately is a raw line of content in a configuration file, it can make use of the *Strings with Special Meaning to t3c*. Of particular note is the *Remap Override* template string.

Note: This field **must** be defined on ANY_MAP-*Type* Delivery Services, but is otherwise optional.

See also:

The Apache Trafficserver documentation for the Regex Remap plugin

Table 35: Aliases

Name	Use(s)	Type(s)
remap-Text	In Traffic Ops source code and <i>Traffic Ops API</i> requests/responses	unchanged (text, string etc.)

Directives “”

The Raw Remap text is ordinarily added at the end of the line, after everything else. However, it may be necessary to add Range Request Handling after the Raw Remap. For example, if you have a plugin which manipulates the Range header. In this case, you can insert the text `__RANGE_DIRECTIVE__` in the Raw Remap text, and the range request handling directives will be added at that point.

For example, if you have an Apache Traffic Server lua plugin which manipulates the range, and are using Slice Range Request Handling which needs to run after your plugin, you can set a Raw Remap, `@plugin=tslua.so @pparam=range.lua __RANGE_DIRECTIVE__`, and the `@plugin=slice.so` range directive will be inserted after your plugin.

Regex Remap Expression

Allows remapping of incoming requests URL using regular expressions to search and replace text. In a more literal sense, this is the raw contents of a configuration file used by the *ATS regex_remap plugin*. At its most basic, the contents of this field should consist of `map` followed by a regular expression and then a “template URL” - all space-separated. The regular expression matches a client’s request *path* (i.e. not a full URL - `/path/to/content` **not** `https://origin.example.com/path/to/content`) and when such a match occurs, the request is transformed into a request for the template URL. The most basic usage of the template URL is to use `$1-$9` to insert the corresponding regular expression capture group. For example, a regular expression of `^/a/(.*)` and a template URL of `https://origin.example.com/b/$1`

maps requests for *Origin* content under path /a/ to the same sub-paths under path b. Note that since it's a full URL, this mapping can be made to another server entirely.

See also:

The [documentation for the regex_remap plugin](#) for ATS

Caution: This field is not validated by Traffic Ops to be correct syntactically, and can cause Traffic Server to not start if invalid. Please use with caution.

Warning: Regex remap expressions are incompatible with *Query String Handling* being set to 2. The behavior of a *cache server* under that configuration is undefined.

Tip: It is, of course, entirely possible to write a Regex Remap Expression that reproduces the desired *Query String Handling* as well as any other desired behavior.

See also:

The [Apache Trafficserver documentation for the Regex Remap plugin](#)

Table 36: Aliases

Name	Use(s)	Type(s)
regexRemap	Traffic Ops source code and database, and <i>Traffic Ops API</i> requests/responses	unchanged (string etc.)

Regional Geoblocking

A boolean value that defines whether or not *Regional Geoblocking* is active on this Delivery Service. The actual configuration of *Regional Geoblocking* is done in the *Profile* used by the Traffic Router serving the Delivery Service. Rules for this Delivery Service may exist, but they will not actually be used unless this field is `true`.

Tip: *Regional Geoblocking* is configured primarily with respect to Canadian postal codes, so unless specifically Canadian regions should be allowed/disallowed to access content, *Geo Limit* is probably a better setting for controlling access to content according to geographic location.

Required Capabilities

New in version ATCv4.

A Delivery Service can be associated with *Server Capabilities* that it requires *cache servers* serving its content to have. When one or more *Server Capability* is required by a Delivery Service, it will block the assignment of *cache servers* to it that do not have those *Server Capabilities*. Additionally, the *Edge-tier cache servers* assigned to a Delivery Service that requires a *Server Capability* will only request content they do not have cached from *Mid-tier cache servers* which also have this *Server Capability*.

Typically, a required *Server Capability* is represented merely by the name of said *Server Capability*. In fact, there's nothing more to a *Server Capability* than its name; it's the responsibility of CDN operators to ensure that they are assigned and required properly. There is no mechanism to detect whether or not a *cache server* has a given *Server Capability*, it must be assigned manually.

Routing Name

A DNS label in the Delivery Service's domain that forms the FQDN that is used by clients to request content. All together, the constructed FQDN looks like: *Delivery Service xml_id.CDN Subdomain.CDN Domain.Top-Level Domain*¹.

Servers

Servers can be assigned to Delivery Services using the *Servers* and *Delivery Services* Traffic Portal sections, or by directly using the *deliveryserviceserver* endpoint. Only *Edge-tier cache servers* can be assigned to a Delivery Service, and once they are so assigned they will begin to serve content for the Delivery Service (after updates are queued and then applied). Any servers assigned to a Delivery Service must also belong to the same *CDN* as the Delivery Service itself. At least one server must be assigned to a Delivery Service in order for it to serve any content.

Service Category

A service category is a tag that describes the type of content being delivered by the Delivery Service. Some example values are: "Linear" and "VOD"

¹ Some things to consider when choosing an *xml_id* and routing name: the name should be descriptive and unique, but as brief as possible to avoid creating a monstrous FQDN. Also, because these are combined to form an FQDN, they should not contain any characters that are illegal for a DNS subdomain, e.g. . (period/dot). Finally, the restrictions on what characters are allowable (especially in *xml_id*) are, in general, **NOT** enforced by the *Traffic Ops API*, so take care that the name is appropriate. See [RFC 1035](#) for exact guidelines.

Signing Algorithm

URLs/URIs may be signed using one of two algorithms before a request for the content to which they refer is sent to the *Origin* (which in practice can be any upstream network). At the time of this writing, this field is restricted within the Traffic Ops Database to one of two values (or NULL/"None", to indicate no signing should be done).

See also:

The `url_sig` [README](#).

See also:

The draft RFC for `uri_signing` - note, however that the current implementation of `uri_signing` uses Draft 12 of that RFC document, **NOT** the latest.

url_sig URL signing will be implemented in this Delivery Service using the `url_sig` [Apache Traffic Server plugin](#). (Aliased as "URL Signature Keys" in Traffic Portal forms)

uri_signing URL signing will be implemented in this Delivery Service using an algorithm based on a work-in-progress RFC specification draft. (Aliased as "URI Signing Keys" in Traffic Portal forms)

Table 37: Aliases

Name	Use(s)	Type(s)
Signed	In all components prior to Traffic Control v2.2. Some endpoints in early versions of the <i>Traffic Ops API</i> will still return this field instead of "signingAlgorithm".	A boolean value where <code>true</code> was the same as "url_sig" in current versions, and <code>false</code> indicated URL signing would not be done for the Delivery Service.

Keys for either algorithm can be generated within *Traffic Portal*.

SSL Key Version

An integer that describes the version of the SSL key(s) - if any - used by this Delivery Service. This is incremented whenever Traffic Portal generates new SSL keys for the Delivery Service.

Warning: This number will not be correct if keys are manually replaced using the API, as the key generation API does not increment it!

Static DNS Entries

Static DNS Entries can be added *under* a Delivery Service’s domain. These DNS records can be configured in the [Delivery Services](#) section of Traffic Portal, and can be any valid CNAME, A or AAAA DNS record - provided the associated hostname falls within the DNS domain for the Delivery Service. For example, a Delivery Service with [xml_id](#) “demo1” and belonging to a [CDN](#) with domain “mycdn.ciab.test” could have Static DNS Entries for hostnames “foo.demo1.mycdn.ciab.test” or “foo.bar.demo1.mycdn.ciab.test” but not “foo.bar.mycdn.ciab.test” or “foo.bar.test”.

Note: The [Routing Name](#) of a Delivery Service is not part of the SOA (Start of Authority) record for the Delivery Service’s domain, and so there is no need to place Static DNS Entries below a domain containing it.

Tenant

The [Tenant](#) who owns this Delivery Service. They (and their parents, if any) are the only ones allowed to make changes to this Delivery Service. Typically, `tenant/Tenant` refers to the *name* of the owning [Tenant](#), but occasionally (most notably in the payloads and/or query parameters of certain [Traffic Ops API](#) requests) it actually refers to the *integral, unique identifier* of said [Tenant](#).

Table 38: Aliases

Name	Use(s)	Type(s)
TenantID	Go code and Traffic Ops API requests/responses	Integral, unique identifier (bigint, int etc.)

TLS Versions

The versions of TLS that can be used in HTTP requests to [Edge-tier cache servers](#) for this Delivery Service’s content can be limited using this property. When a Delivery Service has this property set to anything other than a `null` value, it lists the versions that will be allowed. Any versions can be added to the supported set, so long as they are of the form *Major.Minor*, e.g. 1.1 or 42.0. When this is a `null` value, no restrictions are placed on the TLS versions that may be used for retrieving Delivery Service content.

Implementation Detail

Traffic Ops will accept empty arrays as a synonym for `null` in requests, but will always represent them as `null` in responses. Note that this means it’s impossible to create a Delivery Service that explicitly supports no TLS versions - the proper way to disable HTTPS for a Delivery Service is to set its [Protocol](#) accordingly.

A Delivery Service that has a *Type* of STEERING or CLIENT_STEERING may not legally be set to have a TLS Versions property that is non-null.

Warning: Using this setting may cause old clients that only support archaic TLS versions to break suddenly. Be sure that the security increase is worth this risk.

Topology

A structure composed of *Cache Groups* and parent relationships, which is assignable to one or more *Delivery Services*.

Traffic Router Additional Response Headers

List of HTTP header `{{name}}:{{value}}` pairs separated by `__RETURN__` or simply on separate lines. Listed pairs will be included in all HTTP responses from Traffic Router for HTTP-*Routed* Delivery Services.

Deprecated since version 4.0: The use of `__RETURN__` as a substitute for a real newline is unnecessary and the ability to do so will be removed in the future.

Table 39: Aliases

Name	Use(s)	Type(s)
trResponse-Headers	Traffic Control source code and Delivery Service objects returned by the <i>Traffic Ops API</i>	unchanged (string etc.)

Traffic Router Log Request Headers

List of HTTP header names separated by `__RETURN__` or simply on separate lines. Listed pairs will be logged for all HTTP requests to Traffic Router for HTTP-*Routed* Delivery Services.

Deprecated since version 4.0: The use of `__RETURN__` as a substitute for a real newline is unnecessary and the ability to do so will be removed in the future.

Table 40: Aliases

Name	Use(s)	Type(s)
trRequest-Headers	Traffic Control source code and Delivery Service objects returned by the <i>Traffic Ops API</i>	unchanged (string etc.)

Type

Defines the content routing method used by the Delivery Service. In most cases this is an integral, unique identifier that corresponds to an enumeration of the Delivery Service Types. In other cases, this is the actual name of said type.

The “Type” of a Delivery Service can mean several things. First, it can be used to refer to the “routing type” of Delivery Service. This is one of:

Tip: The only way to get the integral, unique identifier of a *Type* of Delivery Service is to look at the database after it has been generated; these are non-deterministic and cannot be guaranteed to have any particular value, or even consistent values. This can be done directly or, preferably, using the *types* endpoint. Unfortunately, knowing the name of the *Type* is rarely enough for many applications. The `useInColumn` values of these *Types* will be `deliveryservice`.

DNS Delivery Services of this routing type are routed by Traffic Router by providing DNS records that provide the IP addresses of *cache servers* when clients look up the full Delivery Service FQDN.

HTTP The Traffic Router(s) responsible for routing this Delivery Service will still answer DNS requests for the Delivery Service FQDN, but will provide its own IP address. The client then directs its HTTP request to the Traffic Router, which will use an *HTTP redirection response* to direct the client to a *cache server*.

More generally, though, Delivery Services have a Type that defines not only how traffic is routed, but also how content is cached and semantically defines what “content” means in the context of a given Delivery Service.

ANY_MAP This is a special kind of Delivery Service that should only be used when control over the clients is guaranteed, and very fine control over the ATS `remap.config` line for this Delivery Service is required. ANY_MAP is not known to Traffic Router. It is not routed in any way. For Delivery Services of this type, the “Raw Remap Text” field **must** be defined, as it is the only configuration generated by Traffic Control. The only way for a client to utilize delivery through an ANY_MAP service is by knowing in advance the IP address of one or more *Edge-tier cache servers* and make the appropriate request(s).

DNS Uses DNS content routing. Delivers content normally. This is the recommended Type for delivering smaller objects like web page images.

DNS_LIVE³ Uses DNS Content routing, but optimizes caching for live video streaming. Specifically, the configuration generated for *cache servers* responsible for serving content for this Delivery Service will not cache that content on storage disks. Instead, they will make use of RAM block devices dedicated to ATS - as specified by the special `RAM_Drive_Prefix` and `RAM_Drive_Letters` *Parameters*. Also, any *Mid-tier* of caching is bypassed.

DNS_LIVE_NATNL Works exactly the same as DNS_LIVE, but is optimized for delivery of live video content across a wide physical area. What this means is that the *Mid-tier*

³ These Delivery Services Types are vulnerable to what this writer likes to call the “Duplicate Origin Problem”. This problem is tracked by [Issue #3537](#).

of caching is **not** bypassed, unlike DNS_LIVE. The *Mid-tier* will also use block RAM devices.

HTTP Uses HTTP content routing, delivers content normally. This is the recommended Type for delivering larger objects like video streams.

HTTP_LIVE^{Page 45, 3} Uses HTTP Content routing, but optimizes caching for live video streaming. Specifically, the configuration generated for *cache servers* responsible for serving content for this Delivery Service will not cache that content on storage disks. Instead, they will make use of RAM block devices dedicated to ATS - as specified by the special `RAM_Drive_Prefix` and `RAM_Drive_Letters` *Parameters*. Also, any *Mid-tier* of caching is bypassed.

HTTP_LIVE_NATNL Works exactly the same as HTTP_LIVE, but is optimized for delivery of live video content across a wide physical area. What this means is that the *Mid-tier* of caching is **not** bypassed, unlike HTTP_LIVE. The *Mid-tier* will also use block RAM devices.

HTTP_NO_CACHE^{Page 45, 3} Uses HTTP Content Routing, but *cache servers* will not actually cache the delivered content - they act as just proxies. This will bypass any existing *Mid-tier* entirely (as it's totally useless when content is not being cached).

STEERING This is a sort of “meta” Delivery Service. It is used for directing clients to one of a set of Delivery Services, rather than delivering content directly itself. The Delivery Services to which a STEERING Delivery Service routes clients are referred to as “targets”. Targets in general have an associated “value” and can be of several *Types* that define the meaning of the value - these being:

STEERING_ORDER The value of a STEERING_ORDER target sets a strict order of preference. In cases where a response to a client contains multiple Delivery Services, those targets with a lower “value” appear earlier than those with a higher “value”. In cases where two or more targets share the same value, they each have an equal chance of being presented to the client - effectively spreading traffic evenly across them.

STEERING_WEIGHT The values of STEERING_WEIGHT targets are interpreted as “weights”, which define how likely it is that any given client will be routed to a specific Delivery Service - effectively this determines the spread of traffic across each target.

The targets of a Delivery Service may be set using *the appropriate section of Traffic Portal* or via the `steering/{ID}/targets` and `steering/{ID}/targets/{targetID}` *Traffic Ops API* endpoints.

See also:

For more information on setting up a STEERING (or CLIENT_STEERING) Delivery Service, see *Configure Delivery Service Steering*.

See also:

For implementation details about how Traffic Router routes STEERING (and CLIENT_STEERING) Delivery Services, see *Steering Feature*.

CLIENT_STEERING A CLIENT_STEERING Delivery Service is exactly like STEERING except that it provides clients with methods of bypassing the weights, orders, and localizations of targets in order to choose any arbitrary target at will. When utilizing these methods, the client will either directly choose a target immediately or request a list of all available targets from Traffic Router and then choose one to which to send a subsequent request for actual content. CLIENT_STEERING also supports two additional target types:

STEERING_GEO_ORDER These targets behave exactly like STEERING_ORDER targets, but Delivery Services are grouped according to the “locations” of their *Origins*. Before choosing a Delivery Service to which to direct the client, Traffic Router will first create subsets of choices according to these groupings, and order them by physical distance from the client (closest to farthest). Within these subsets, the values of the targets establish a strict precedence ordering, just like STEERING_ORDER targets.

STEERING_GEO_WEIGHT These targets behave exactly like STEERING_WEIGHT targets, but Delivery Services are grouped according to the “locations” of their *Origins*. Before choosing a Delivery Service to which to direct the client, Traffic Router will first create subsets of choices according to these groupings, and order them by physical distance from the client (closest to farthest). Within these subsets, the values of the targets establish the likelihood that any given target within the subset will be chosen for the client - effectively determining the spread of traffic across targets within that subset.

Important: To make use of the STEERING_GEO_ORDER and/or STEERING_GEO_WEIGHT target types, it is first necessary to ensure that at least the “primary” *Origin* of the *Delivery Service* has an associated geographic coordinate pair. This can be done either from the *Origins* page in Traffic Portal, or using the *origins Traffic Ops API* endpoint.

Note: “Steering” is also commonly used to collectively refer to either of the kinds of Delivery Services that can participate in steering behavior (STEERING and CLIENT_STEERING).

Table 41: Aliases

Name	Use(s)	Type(s)
Content Routing Type	Traffic Portal forms	The name of any of the Delivery Service <i>Types</i> (string)
TypeID	In Go code and <i>Traffic Ops API</i> requests/responses	Integral, unique identifier (bigint, int etc.)

Use Multi-Site Origin Feature

A boolean value that indicates whether or not this Delivery Service serves content for an *Origin* that provides content from two or more redundant servers. There are very few good reasons for this to not be false. When true, Traffic Ops will configure *Mid-tier cache servers* to perform load-balancing and other optimizations for redundant *origin servers*.

Naturally, this assumes that each redundant server is exactly identical, from request paths to actual content. If Multi-Site Origin is configured for servers that are *not* identical, the client's experience is undefined. Furthermore, the *origin servers* may have differing IP addresses, but **must** serve content for a single FQDN - as defined by the Delivery Service's *Origin Server Base URL*. These redundant servers **must** be configured as servers (server *Type* ORG) in Traffic Ops - either using the *appropriate section of Traffic Portal* or the *servers* endpoint.

Important: In order for a given *Mid-tier cache server* to support Multi-Site Origins, the value of a *Parameter* named `http.parent_proxy_routing_enable` in configuration file `records.config` must be set to 1 on that server's *Profile*. If using an optional secondary grouping of Multi-Site Origins, the *Parameter* named `url_remap.remap_required` in configuration file `records.config` must also be set to 1 on that *Profile*. These settings must be applied to all *Mid-tier cache servers* that are the *parents* of any *Edge-tier cache server* assigned to this Delivery Service.

See also:

These parameters are described in the ATS documentation sections for [Parent Proxy Configuration](#) and [URL Remap Rules](#), respectively.

Table 42: Aliases

Name	Use(s)	Type(s)
multiSiteOrigin	In Go code and <i>Traffic Ops API</i> requests/responses	unchanged (bool, boolean etc.)
MSO (Multi-Site Origin)	In documentation and used heavily in discussion in Slack, mailing list etc.	unchanged (usually only used where implicitly true)

A Delivery Service *Profile* can have *Parameters* that affect Multi-Site Origin configuration. These are detailed in the *Parameters of a Delivery Service Profile that Affect MSO Configuration* table. All of these *Parameters* should have their Configuration File set to `parent.config`. Each *Parameter* directly corresponds to a field in a line of the ATS *parent.config* file <https://docs.trafficserver.apache.org/en/7.1.x/admin-guide/files/parent.config.en.html> (usually by almost the same name), and documentation for these fields is provided in the form of links to their entries in the ATS documentation.

Table 43: Parameters of a Delivery Service Profile that Affect MSO Configuration

Name	ATS parent.config field	Effect
mso.algorithm	round_robin	Sets the algorithm used to determine from which <i>origin server</i> content will be requested.
mso.max_simple_retries	max_simple_retries	Sets a strict limit on the number of “simple retries” allowed before giving up
mso.max_unavailable_server_retries	max_unavailable_server_retries	Sets a strict limit on the number of times the <i>cache server</i> will attempt to request content from an <i>origin server</i> that has previously been considered “unavailable”.
mso.parent_retry	parent_retry	Sets whether the <i>cache servers</i> will use “simple retries”, “unavailable server retries”, or both.
mso.simple_retry_response_codes	simple_retry_response_codes	UNKNOWN - supposedly defines HTTP response codes from an <i>origin server</i> that necessitate a “simple retry”.
mso.unavailable_server_retry_response_codes	unavailable_server_retry_response_codes	Defines HTTP response codes from an <i>origin server</i> that indicate it is currently “unavailable”.

Warning: The `mso.simple_retry_response_codes` *Parameter* has no apparent, possible use according to the ATS [parent.config documentation](#). Whether or not it has any effect - let alone the *intended* effect - is not known, and its use is therefore strongly discouraged.

See also:

A quick guide on setting up Multi-Site Origins is given in [Configure Multi-Site Origin](#).

See also:

See the [Apache Traffic Server documentation](#) for more information on its implementation of Multi-Site Origins.

xml_id

A text-based unique identifier for a Delivery Service. Many [Traffic Ops API](#) endpoints and internal ATC functions use this to uniquely identify a Delivery Service as opposed to the historically favored “ID”. This string will become a part of the CDN service domain, which all together looks like: *Delivery Service Routing Name.Delivery Service xml_id.CDN Subdomain.CDN Domain.Top-Level Domain*. Must be all lowercase, no spaces or special characters, but may contain dashes/hyphens?

Table 44: Aliases

Name	Use(s)	Type(s)
Key	Traffic Portal tables and forms	unchanged (string)

Delivery Service Parameters

Features which are new, experimental, or not significant enough to be first-class Delivery Service fields are often added as Parameters. To use these, add a Profile to the Delivery Service, with the given Parameter assigned.

parent.config

The following Parameters must have the Config File `parent.config` to take effect.

- `try_all primaries before secondary` - on a Delivery Service Profile, if this exists, try all primary parents before failing over to secondary parents, which may be ideal if objects are unlikely to be in cache. The default behavior is to immediately fail to a secondary, which is ideal if objects are likely to be in cache, as the first consistent-hashed secondary parent will be the primary parent in its own cachegroup and therefore receive requests for that object from clients near its own cachegroup.
- `enable_h2` - on a Delivery Service Profile, if this is `true`, enable HTTP/2 for client requests. Note ATS must also be listening for HTTP/2 in `records.config`, or this will have no effect. Note this setting is not in the `parent.config` config file, but either `ssl_server_name.yaml` in ATS 8 or `sni.yaml` in ATS 9. The Parameter has the “`parent.config`” config file for consistency.
- `tls_versions` - on a Delivery Service Profile, if this exists, enable the given comma-delimited TLS versions for client requests. For example, `1.1, 1.2, 1.3`. Note ATS must also be accepting those TLS versions in `records.config`, or this will have no effect. Note this setting is not in the `parent.config` config file, but either `ssl_server_name.yaml` in ATS 8 or `sni.yaml` in ATS 9. The Parameter has the “`parent.config`” config file for consistency.

Additionally, *Delivery Service Profiles* can have special Parameters with the *Name* “`mso.parent_retry`” to *Configure Multi-Site Origin*.

See also:

To see how the *Values* of these Parameters are interpreted, refer to the [Apache Traffic Server documentation on the parent.config configuration file](#)

2.1.4 Introduction

Traffic Control is a CDN control plane. It is made up of a suite of applications which are used to configure, manage, and direct client traffic to a tiered system of HTTP caching proxy servers (herein referred to as *cache servers*). In principle, a CDN may be implemented with any HTTP caching proxy. The caching software chosen for Traffic Control is [Apache Traffic Server](#). Although the current release supports only ATS as a *cache server* implementation, this may change with future releases.

Traffic Control was first developed at Comcast for internal use and released to Open Source in April of 2015. Traffic Control moved into the Apache Incubator in August of 2016.

Traffic Control implements the elements illustrated in green in the diagram below.




Fig. 3: Apache Traffic Control Hierarchical Diagram

Traffic Ops *Traffic Ops* stores the configuration of *cache servers* and CDN *Delivery Services*. It also serves the *Traffic Ops API* which can be used by tools, scripts, and programs to access and manipulate CDN data.

Traffic Router *Traffic Router* is used to route client requests to the closest healthy *cache server* by analyzing the health, capacity, and state of the *cache servers* according to the *Health Protocol* and relative geographic distance between each *Cache Group* and the client.

Traffic Monitor *Traffic Monitor* does health polling of the *cache servers* on a very short interval to keep track of which servers should be kept in rotation.

See also:

Health Protocol

Traffic Stats *Traffic Stats* collects and stores real-time traffic statistics aggregated from each of the *cache servers*. This data is used by the *Traffic Router* to assess the available capacity of each *cache server* which it uses to balance traffic load and prevent overload.

Traffic Portal *Traffic Portal* is a web interface which uses the *Traffic Ops API* to present CDN data and the controls to manipulate it in a user-friendly interface.

New in version 2.2: As of Traffic Control 2.2, this is the recommended, official UI for the Traffic Control platform. In Traffic Control 3.x, the Traffic Ops UI has been deprecated and disabled by default, and it will be removed with the release of Traffic Control 4.0.

Traffic Vault *Traffic Vault* is used as a secure key/value store for SSL private keys used by other Traffic Control components.

2.1.5 Profiles and Parameters

Profiles are a collection of configuration options, defined partially by the Profile's *Type* (not to be confused with the more general “*Type*” used by many other things in Traffic Control) and partially by the *Parameters* set on them. Mainly, Profiles and Parameters are used to configure *cache servers*, but they can also be used to configure parts of (nearly) any Traffic Control component, and can even be linked with more abstract concepts like *Delivery Services* and *Cache Groups*. The vast majority of configuration done within a Traffic Control CDN must be done through *Profiles* and *Parameters*, which can be achieved either through the *Traffic Ops API* or in the *Profiles* view of Traffic Portal. For ease of use, Traffic Portal allows for duplication, comparison, import and export of *Profiles* including all of their associated *Parameters*.

See also:

For Delivery Service Profile Parameters, see *Delivery Service Parameters*.

Profiles

Properties

Profile objects as represented in e.g. the *Traffic Ops API* or in the *Traffic Portal Profiles view* have several properties that describe their general operation. In certain contexts, the *Parameters* assigned to a Profile (and/or the integral, unique identifiers thereof) may appear as properties of the Profile, but that will not appear in this section as a description of *Parameters* is provided in the section of that name.

CDN

A Profile is restricted to operate within a single CDN. Often, “CDN” (or “cdn”) refers to the integral, unique identifier of the CDN, but occasionally it refers to the *name* of said CDN. It may also appear as e.g. `cdnId` or `cdnName` in *Traffic Ops API* payloads and responses. A Profile may only be assigned to a server, *Delivery Service*, or *Cache Group* within the same CDN as the Profile itself.

Description

Profiles may have a description provided by the creating user (or Traffic Control itself in the case of the *Default Profiles*). The *Traffic Ops API* does not enforce length requirements on the description (though Traffic Portal does), and so it’s possible for Profiles to have empty descriptions, though it is strongly recommended that Profiles have meaningful descriptions.

ID

An integral, unique identifier for the Profile.

Name

Ostensibly this is simply the Profile’s name. However, the name of a Profile has drastic consequences for how Traffic Control treats it. Particularly, the name of a Profile is heavily conflated with its *Type*. These relationships are discussed further in the *Type* section, on a Type-by-Type basis.

The Name of a Profile may not contain spaces.

Changed in version ATCv6: In older versions of ATC, Profile Names were allowed to contain spaces. The *Traffic Ops API* will reject creation or update of Profiles that have spaces in their Names as of ATC version 6, so legacy Profiles will need to be updated to meet this constraint before they can be modified.

Routing Disabled

This property can - and in fact *must* - exist on a Profile of any *Type*, but it only has any meaning on a Profile that has a name matching the constraints placed on the names of ATS_PROFILE-*Type* Profiles. This means that it will also have meaning on Profiles of *Type* UNK_PROFILE that for whatever reason have names beginning with EDGE or MID. When this field is defined as 1 (may be displayed as `true` in e.g. Traffic Portal), Traffic Router will not be informed of any *Delivery Services* to which the *cache server* using this Profile may be assigned. Effectively, this means that client traffic cannot be routed to them, although existing connections would be uninterrupted.

Type

A Profile's *Type* determines how its configured *Parameters* are treated by various components, and often even determine how the object using the Profile is treated (particularly when it is a server). Unlike the more general “*Type*” employed by Traffic Control, the allowed Types of Profiles are set in stone, and they are as follows.

Danger: Nearly all of these Profile Types have strict naming requirements, and it may be noted that some of said requirements are prefixes ending with `_`, while others are either not prefixes or do not end with `_`. This is exactly true; some requirements **need** that `_` and some may or may not have it. It is our suggestion, therefore, that for the time being all prefixes use the `_` notation to separate words, so as to avoid causing headaches remembering when that matters and when it does not.

ATS_PROFILE A Profile that can be used with either an Edge-tier or Mid-tier *cache server* (but not both, in general). This is the only Profile type that will ultimately pass its *Parameters* on to *ORT* in the form of generated configuration files. For this reason, it can make use of the *Strings with Special Meaning to t3c* in the values of some of its *Parameters*.

Warning: For legacy reasons, the names of Profiles of this type *must* begin with EDGE or MID. This is **not** enforced by the *Traffic Ops API* or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise! This includes *caches/stats*.

DS_PROFILE A Profile that, rather than applying to a server, is instead *used by a Delivery Service*.

ES_PROFILE A Profile for *ElasticSearch* servers. This has no known special meaning to any component of Traffic Control, but if ElasticSearch is in use the use of this Profile Type is suggested regardless.

Warning: For legacy reasons, the names of Profiles of this type *must* begin with ELASTICSEARCH. This is **not** enforced by the *Traffic Ops API* or Traffic Portal, but

certain Traffic Control operations/components expect this and will fail to work otherwise!

GROVE_PROFILE A Profile for use with the experimental Grove HTTP caching proxy.

INFLUXDB_PROFILE A Profile used with [InfluxDB](#), which is used by Traffic Stats.

Warning: For legacy reasons, the names of Profiles of this type *must* begin with INFLUXDB. This is **not** enforced by the [Traffic Ops API](#) or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise!

KAFKA_PROFILE A Profile for [Kafka](#) servers. This has no known special meaning to any component of Traffic Control, but if Kafka is in use the use of this Profile Type is suggested regardless.

Warning: For legacy reasons, the names of Profiles of this type *must* begin with KAFKA. This is **not** enforced by the [Traffic Ops API](#) or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise!

LOGSTASH_PROFILE A Profile for [Logstash](#) servers. This has no known special meaning to any component of Traffic Control, but if Logstash is in use the use of this Profile Type is suggested regardless.

Warning: For legacy reasons, the names of Profiles of this type *must* begin with LOGSTASH_. This is **not** enforced by the [Traffic Ops API](#) or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise!

ORG_PROFILE A Profile that may be used by either [origin servers](#) or [Origins](#) (no, they aren't the same thing).

Warning: For legacy reasons, the names of Profiles of this type *must* begin with MSO, or contain either ORG or ORIGIN anywhere in the name. This is **not** enforced by the [Traffic Ops API](#) or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise!

RIAK_PROFILE A Profile used for each [Riak](#) server in a Traffic Stats cluster.

Warning: For legacy reasons, the names of Profiles of this type *must* begin with RIAK. This is **not** enforced by the [Traffic Ops API](#) or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise!

SPLUNK_PROFILE A Profile meant to be used with [Splunk](#) servers. This has no known special meaning to any component of Traffic Control, but if Splunk is in use the use of this Profile Type is suggested regardless.

Warning: For legacy reasons, the names of Profiles of this type *must* begin with SPLUNK. This is **not** enforced by the [Traffic Ops API](#) or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise!

TM_PROFILE A Traffic Monitor Profile.

Warning: For legacy reasons, the names of Profiles of this type *must* begin with RASCAL_ or TM_. This is **not** enforced by the [Traffic Ops API](#) or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise!

TP_PROFILE A Traffic Portal Profile. This has no known special meaning to any Traffic Control component(s) (not even Traffic Portal itself), but its use is suggested for the profiles used by any and all Traffic Portal servers anyway.

TR_PROFILE A Traffic Router Profile.

Warning: For legacy reasons, the names of Profiles of this type *must* begin with CCR_ or TR_. This is **not** enforced by the [Traffic Ops API](#) or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise!

See also:

[The Traffic Router Profile](#)

TS_PROFILE A Traffic Stats Profile.

Caution: For legacy reasons, the names of Profiles of this type *must* be TRAFFIC_STATS. This is **not** enforced by the [Traffic Ops API](#) or Traffic Portal, but certain Traffic Control operations/components expect this and will fail to work otherwise! Furthermore, because Profile names must be unique, this means that only one TS_PROFILE-Type Profile can exist at a time.

UNK_PROFILE A catch-all type that can be assigned to anything without imbuing it with any special meaning or behavior.

Tip: A Profile of the wrong type assigned to a Traffic Control component *will* (in general) cause it to function incorrectly, regardless of the [Parameters](#) assigned to it.

Default Profiles

Traffic Control comes with some pre-installed Profiles for its basic components, but users are free to define their own as needed. Additionally, these default Profiles can be modified or even removed completely. One of these Profiles is *The GLOBAL Profile*, which has a dedicated section.

INFLUXDB A Profile used by InfluxDB servers that store Traffic Stats information. It has a *Type* of UNK_PROFILE and is assigned to the special “ALL” *CDN*.

RIAK_ALL This Profile is used by Traffic Vault, which is, generally speaking, the only instance in Traffic Control as it can store keys for an arbitrary number of CDNs. It has a *Type* of UNK_PROFILE and is assigned to the special “ALL” *CDN*.

TRAFFIC_ANALYTICS A default Profile that was intended for use with the now-unplanned “Traffic Analytics” ATC component. It has a *Type* of UNK_PROFILE and is assigned to the special “ALL” *CDN*.

TRAFFIC_OPS A Profile used by the Traffic Ops server itself. It’s suggested that any and all “mirrors” of Traffic Ops for a given Traffic Control instance be recorded separately and all assigned to this Profile for record-keeping purposes. It has a *Type* of UNK_PROFILE and is assigned to the special “ALL” *CDN*.

TRAFFIC_OPS_DB A Profile used by the PostgreSQL database server that stores all of the data needed by Traffic Ops. It has a *Type* of UNK_PROFILE and is assigned to the special “ALL” *CDN*.

TRAFFIC_PORTAL A Profile used by Traffic Portal servers. This profile name has no known special meaning to any Traffic Control components (not even Traffic Portal itself), but its use is suggested for Traffic Portal servers anyway. It has a *Type* of UNK_PROFILE and is assigned to the special “ALL” *CDN*.

TRAFFIC_STATS This is the **only** Profile used by Traffic Stats (though InfluxDB servers have their own Profile(s)). It has a *Type* of UNK_PROFILE and is assigned to the special “ALL” *CDN*.

In addition to these Profiles, each release of Apache Traffic Control is accompanied by a set of suggested Profiles suitable for import in the *Profiles* view of Traffic Portal. They may be found on [the Profiles Downloads Index page](#). These Profiles are typically built from production Profiles by a company using Traffic Control, and as such are typically highly specific to the hardware and network infrastructure available to them. **None of the Profiles bundled with a release are suitable for immediate use without modification**, and in fact many of them cannot actually be imported directly into a new Traffic Control environment, because Profiles with the same *Names* already exist (as above).

Administrators may alternatively wish to consult the Profiles and *Parameters* available in the *CDN in a Box* environment, as they might be more familiar with them. Furthermore, those Profiles are built with a minimum running Traffic Control system in mind, and thus may be easier to look through. The Profiles and their associated *Parameters* may be found within the [infrastructure/cdn-in-a-box/traffic_ops_data/profiles/](#) directory.

The GLOBAL Profile

There is a special Profile of *Type* UNK_PROFILE that holds global configuration information - its *Name* is “GLOBAL”, its *Type* is UNK_PROFILE and it is assigned to the special “ALL” *CDN*. The *Parameters* that may be configured on this Profile are laid out in the *Global Profile Parameters* Table.

Table 45: Global Profile Parameters

Name	Config File	Value
tm.url	global	The URL at which this Traffic Ops instance services requests.
tm.reverseproxy	global	Not required. The URL where a caching proxy for configuration files generated by Traffic Ops may be found. Requires a minimum <i>ORT</i> version of 2.1. When configured, <i>ORT</i> will request configuration files via this FQDN, which should be set up as a reverse proxy to the Traffic Ops server(s). The suggested cache lifetime for these files is 3 minutes or less. This setting allows for greater scalability of a CDN maintained by Traffic Ops by caching configuration files of profile and CDN scope, as generating these is a very computationally expensive process.
tm.tool	global	The name of the Traffic Ops tool. Usually “Traffic Ops” - this will appear in the comment headers of generated configuration files.
tm.info	global	This is the “for more information go here” URL, which used to be visible in the “About” page of the now-deprecated Traffic Ops UI.
tm.instance	global	The name of the Traffic Ops instance - typically to distinguish instances when multiple are active.
tm.forwardproxy	global	When collecting stats from Traffic Monitor, Traffic Ops will use this forward proxy instead of the actual Traffic Monitor host. Setting this <i>Parameter</i> can significantly lighten the load on the Traffic Monitor system and it is therefore recommended that this be set on a production system.
use_regex_revalidate	global	When this Parameter is present and its <i>Value</i> is exactly “1”, Traffic Ops will separately keep track of <i>cache servers</i> ’ updates and pending content invalidation jobs. This behavior should be enabled by default, and disabling it, while still possible, is EXTREMELY DISCOURAGED .
geo-location.polling.url	CR-Config.json	The location of a geographic IP mapping database for Traffic Router instances to use.
geo-location6.polling.url	CR-Config.json	The location of a geographic IPv6 mapping database for Traffic Router instances to use.
maxmind.default-geoip	CR-Config.json	The destination geographic coordinates to use for client location when the geo-mapping database returns a default location that matches the country code. This parameter can be specified multiple times with different values to support default overrides for multiple countries. The reason for the name “maxmind” is because the default geographic IP mapping database used by Traffic Control is MaxMind’s GeoIP2 database. The format of this <i>Parameter’s Value</i> is: <i>Country Code;Latitude,Longitude</i> , e.g. US;37.751,-97.822
max-duration-days	Regex-Validate.conf	This parameter sets the maximum duration, in days, for which a content invalidation job may run. This is extremely important, as there is currently no way to delete a content invalidation job once it has been created. Furthermore, while there is no restriction placed on creating multiple <i>Parameters</i> with this <i>Name</i> and <i>Config File</i> - potentially with differing <i>Values</i> - this is EXTREMELY DISCOURAGED as any <i>Parameter</i> that has both that <i>Name</i> and <i>Config File</i> might be used when generating any given <i>regex_revalidate.config</i> file for any given <i>cache server</i> and whenever such <i>Parameters</i> exist, the actual maximum duration for content invalidation jobs is undefined, and CAN and WILL differ from server to server, and configuration file to configuration file.

2.1. Traffic Control Overview

Some of these *Parameters* have the *Config File* value *global*, while others have *CRConfig.json*. This is not a typo, and the distinction is that those that use *global* are typically configuration options relating to Traffic Control as a whole or to Traffic Ops itself, whereas *CRConfig.json* is used by configuration options that are set globally, but pertain mainly to routing and are thus communicated to Traffic Routers through *CDN Snapshots* (which historically were called “CRConfig Snapshots” or simply “the CRConfig”). When a *Parameter* has a *Config File* value that *isn’t* one of *global* or *CRConfig.json*, it refers to the global configuration of said *Config File* across all servers that use it across all CDNs configured in Traffic Control. This can be used to easily apply extremely common configuration to a great many servers in one place.

Parameters

A *Parameter* is usually a way to set a line in a configuration file that will appear on the servers using *Profiles* that have said Parameter. More generally, though, a Parameter merely describes some kind of configuration for some aspect of some thing. There are many Parameters that *must* exist for Traffic Control to work properly, such as those on *The GLOBAL Profile* or the *Default Profiles*. Some Traffic Control components can be associated with *Profiles* that only have a few allowed (or actually just meaningful - others are ignored and don’t cause problems) but some can have any number of Parameters to describe custom configuration of things of which Traffic Control itself may not even be aware (most notably *cache servers*). For most Parameters, the meaning of each Parameter’s various properties are very heavily tied to the allowed contents of [Apache Traffic Server configuration files](#).

Properties

When represented in Traffic Portal (in the *Parameters* view) or in *Traffic Ops API* request and/or response payloads, a Parameter has several properties that define it. In some of these contexts, the *Profiles* to which a Parameter is assigned (and/or the integral, unique identifiers thereof) are represented as a property of the Parameter. However, an explanation of this “property” is not provided here, as the *Profiles* section exists for the purpose of explaining those.

Config File

This (usually) names the configuration file to which the Parameter belongs. Note that it is only the *name of* the file and **not** the *full path* to the file - e.g. `remap.config` not `/opt/trafficserver/etc/trafficserver/remap.config`. To define the full path to any given configuration file, Traffic Ops relies on a reserved *Name* value: “*location*”.

See also:

This section is only meant to cover the special handling of Parameters assigned to specific Config File values. It is **not** meant to be a primer on Apache Traffic Server configuration files, nor is it intended to be exhaustive of the manners in which said files may be manipulated by Traffic Control. For more information, consult the documentation for [Apache Traffic Server configuration files](#).

Certain Config Files are handled specially by Traffic Ops's configuration file generation. Specifically, the format of the configuration is tailored to be correct when the syntax of a configuration file is known. However, these configuration files **must** have "*location*" Parameters on the *Profile* of servers, or they will not be generated. The Config File values that are special in this way are detailed within this section. When a *Config File* is none of these special values, each Parameter assigned to given server's *Profile* with the same *Config File* value will create a single line in the resulting configuration file (with the possible exception being when the *Name* is "header")

12M_facts

This legacy file is generated entirely from a *Profile*'s metadata, and cannot be affected by Parameters.

Tip: This Config File serves an unknown and likely historical purpose, so most users/administrators/developers don't need to worry about it.

50-ats.rules

Parameters have no meaning when assigned to this Config File (except "*location*"), but it is affected by Parameters that are on the same *Profile* with the Config File `storage.config` - **NOT this Config File**. For each letter in the special "Drive Letters" Parameter, a line will be added of the form `KERNEL=="PrefixLetter", OWNER="ats"` where *Prefix* is the *Value* of the Parameter with the *Name* "Drive Prefix" and the Config File `storage.config` - but with the first instance of `/dev/` removed -, and *Letter* is the drive letter. Also, if the Parameter with the *Name* "RAM Drive Prefix" exists on the same Profile assigned to the server, a line will be inserted for each letter in the special "RAM Drive Letters" Parameter of the form `KERNEL=="PrefixLetter", OWNER="ats"` where *Prefix* is the *Value* of the "RAM Drive Prefix" Parameter - but with the first instance of `/dev/` removed -, and *Letter* is the drive letter.

Tip: This Config File serves an unknown and likely historical purpose, so most users/administrators/developers don't need to worry about it.

astats.config

This configuration file will be generated with a line for each Parameter with this Config File value on the *cache server*'s *Profile* in the form `Name=Value` where *Name* is the Parameter's *Name* with trailing characters that match `__\d+$` stripped, and *Value* is its *Value*.

bg_fetch.config

This configuration file always generates static contents besides the header, and cannot be affected by any Parameters (besides its “*location*” Parameter).

See also:

For an explanation of the contents of this file, consult [the Background Fetch Apache Traffic Server plugin’s official documentation](#).

cache.config

This configuration is built entirely from *Delivery Service* configuration, and cannot be affected by Parameters.

See also:

[The Apache Traffic Server cache.config documentation](#)

cacheurlanything.config

Config Files that match this pattern - where *anything* is a string of zero or more characters - can only be generated by providing a *location* and their contents will be fully determined by properties of *Delivery Services*.

See also:

[The official documentation for the Cache URL Apache Traffic Server plugin](#).

Deprecated since version ATCv3.0: This configuration file is only used by Apache Traffic Server version 6.x, whose use is deprecated both by that project and Traffic Control. These Config Files will have no special meaning at some point in the future.

chkconfig

This actually isn’t a configuration file at all, kind of. Specifically, it is a valid configuration file for the legacy [chkconfig utility](#) - but it is never written to disk on any *cache server*. Though all Traffic Control-supported systems are now using *systemd(8)*, *ORT* still uses *chkconfig*-style configuration to set the status of services on its host system(s). This means that any Parameter with this Config File value should have a *Name* that is the name of a service on the *cache servers* using the *Profile* to which the Parameter is assigned, and it’s *Value* should be a valid *chkconfig* configuration line for that service.

CRConfig.json

In general, the term “CRConfig” refers to *CDN Snapshots*, which historically were called “CR-Config Snapshots” or simply “the CRConfig”. Parameters with this Config File should be only be on either *The GLOBAL Profile* where they will affect global routing configuration, or on a Traffic Router’s *Profile* where they will affect routing configuration for that Traffic Router only.

See also:

For the available configuration Parameters for a Traffic Router Profile, see *The Traffic Router Profile*.

drop_qstring.config

This configuration file will be generated with a single line that is exactly: `/([^\?]+) $s://$t/$1n` **unless** a Parameter exists on the *Profile* with this Config File value, and the *Name* “content”. In the latter case, the contents of the file will be exactly the Parameter’s *Value* (with terminating newline appended).

global

In general, this Config File isn’t actually handled specially by Traffic Ops when generating server configuration files. However, this is the Config File value typically used for Parameters assigned to *The GLOBAL Profile* for truly “global” configuration options, and it is suggested that this precedent be maintained - i.e. don’t create Parameters with this Config File.

hdr_rw_anything.config

Config Files that match this pattern - where *anything* is zero or more characters - are written specially by Traffic Ops to accommodate the *DSCP* setting of *Delivery Services*.

Tip: The *anything* in those file names is typically a *Delivery Service*’s *xml_id* - though the inability to affect the file’s contents is utterly independent of whether or not a *Delivery Service* with that *xml_id* actually exists.

See also:

For information on the contents of files like this, consult [the Header Rewrite Apache Traffic Server plugin’s documentation](#)

hosting.config

This configuration file is mainly generated based on the assignments of *cache servers* to *Delivery Services* and the *Cache Group* hierarchy, but there are a couple of Parameter *Names* that can affect it when assigned to this Config File. When a Parameter assigned to the `storage.config` Config File - **NOT this Config File** - with the *Name* “RAM_Drive_Prefix” *exists*, it will cause lines to be generated in this configuration file for each *Delivery Service* that is of one of the *Types* DNS_LIVE (only if the server is an *Edge-tier cache server*), HTTP_LIVE (only if the server is an *Edge-tier cache server*), DNS_LIVE_NATNL, or HTTP_LIVE_NATNL to which the *cache server* to which the *Profile* containing that Parameter belongs is assigned. Specifically, it will cause each of them to use `volume=1` **UNLESS** the Parameter with the *Name* “Drive_Prefix” associated with Config File `storage.config` - again, **NOT this Config File** - *also exists*, in which case they will use `volume=2`.

Caution: If a Parameter with Config File `storage.config` and *Name* “RAM_Drive_Prefix” does *not* exist on a *Profile*, then the *cache servers* using that *Profile* will **be incapable of serving traffic for *Delivery Services* of the aforementioned *Types*, even when a “location” Parameter exists.**

See also:

For an explanation of the syntax of this configuration file, refer to the [Apache Traffic Server `hosting.config` documentation](#).

ip_allow.config

This configuration file is mostly generated from various server data, but can be affected by a Parameter that has a *Name* of “purge_allow_ip”, which will cause the insertion of a line with `src_ip=VALUE action=ip_allow method=ALL` where `VALUE` is the Parameter’s *Value*. Additionally, Parameters with *Names* like `coalesce_masklen/number_v4/6` cause Traffic Ops to generate coalesced IP ranges in different ways. In the case that `number` was used, the Parameter’s *Value* sets the the maximum number of IP address that may be coalesced into a single range. If `masklen` was used, the lines that are generated are coalesced into CIDR (Classless Inter-Domain Routing) ranges using mask lengths determined by the *Value* of the parameter (using ‘4’ sets the mask length of IPv4 address coalescing while using ‘6’ sets the mask length to use when coalescing IPv6 addresses). This is not recommended, as the default mask lengths allow for maximum coalescence. Furthermore, if two Parameters on the same *Profile* assigned to a server having Config File values of `ip_allow.config` and *Names* that are both “`coalesce_masklen_v4`” but each has a different *Value*, then the actual mask length used to coalesce IPv4 addresses is undefined (but will be one of the two). All forms of the “coalescence Parameters” have this problem.

Implementation Detail

At the time of this writing, coalescence is implemented through the [the `NetAddr::IP` Perl library](#).

See also:

The Apache Traffic Server `ip_allow.config` documentation explains the syntax and meaning of lines in that file.

logging.config

This configuration file can only be affected by Parameters with specific *Names*. Specifically, for each Parameter assigned to this Config File on the *Profile* used by the *cache server* with the name `LogFormatN.Name` where N is either the empty string or a natural number on the interval [1,9] the text in *Log Format Snippet* will be inserted. In that snippet, NAME is the *Value* of the Parameter with the *Name* `LogFormatN.Name`, and FORMAT is the *Value* of the Parameter with the *Name* `LogFormatN.Format` for the same value of N².

8: Log Format Snippet

```
NAME = format {
    Format = 'FORMAT '
}
```

Tip: The order in which these Parameters are considered is exactly the numerical ordering implied by N (starting with it being empty). However, each section is generated for all values of N before moving on to the next.

Furthermore, for a given value of N - as before restricted to either the empty string or a natural number on the interval [1,9] -, if a Parameter exists on the *cache server*'s *Profile* having this Config File value with the *Name* `LogFilterN.Name`, a line of the format `NAME = filter.TYPE.('FILTER')` will be inserted, where NAME is the *Value* of the Parameter with the *Name* `LogFilterN.Name`, TYPE is the *Value* of the Parameter with the *Name* `LogFilterN.Type`, and FILTER is the *Value* of the Parameter with the name `LogFilterN.Filter`³.

Note: When, for a given value of N, a Parameter with the *Name* `LogFilterN.Name` exists, but a Parameter with the *Name* `LogFilterN.Type` does *not* exist, the value of TYPE will be accept.

Finally, for a given value of N, if a Parameter exists on the *cache server*'s *Profile* having this Config File value with the *Name* `LogObjectN.Filename`, the text in *Log Object Snippet* will be inserted. In that snippet, TYPE is the *Value* of the Parameter with the *Name* `LogObjectN.Type`

² This *Value* may safely contain double quotes (") as they will be backslash-escaped in the generated output.

³ This *Value* may safely contain backslashes (\) and single quotes ('), as they will be backslash-escaped in the generated output.

9: Log Object Snippet

```
log.TYPE {  
    Format = FORMAT,  
    Filename = 'FILENAME',  
}
```

Note: When, for a given value of N a Parameter with the *Name* LogObjectN.Filename exists, but a Parameter with the *Name* LogObjectN.Type does *not* exist, the value of TYPE in *Log Object Snippet* will be `ascii`.

At this point, if the *Value* of the Parameter with the *Name* LogObjectN.Type is **exactly** `pipe`, a line of the format `Filters = FILTERS` will be inserted where FILTERS is the *Value* of the Parameter with the *Name* LogObjectN.Filters, followed by a line containing only a closing “curly brace” (`}`) - *if and only if said Parameter is not empty*. If, however, the *Value* of the Parameter with the *Name* LogObjectN.Type is **not** exactly `pipe`, then the text in *Log Object (not a “pipe”) Snippet* is inserted.

10: Log Object (not a “pipe”) Snippet

```
RollingEnabled = ROLLING,  
RollingIntervalSec = INTERVAL,  
RollingOffsetHr = OFFSET,  
RollingSizeMb = SIZE  
}
```

In this snippet, ROLLING is the *Value* of the Parameter with the *Name* LogObjectN.RollingEnabled, INTERVAL is the *Value* of the Parameter with the *Name* LogObjectN.RollingIntervalSec, OFFSET is the *Value* of the Parameter with the *Name* LogObjectN.RollingOffsetHr, and SIZE is the *Value* of the Parameter with the *Name* LogObjectN.SizeMb - all still having the same value of N, and the Config File value `logging.config`, of course.

Warning: The contents of these fields are not validated by Traffic Control - handle with care!

See also:

The Apache Traffic Server documentation for the `logging.config` configuration file

logging.yaml

This is a YAML-format configuration file used by *cache servers* that use Apache Traffic Server version 8 or higher - for lower versions, users/administrators/developers should instead be configuring `logging.config`. This configuration always starts with (after the header) the single line: `format:.` Afterward, for every Parameter assigned to this Config File with a *Name* like `LogFormatN.Name` where N is either the empty string or a natural number on the interval [1,9], the YAML fragment shown in *Log Format Snippet* will be inserted. In this snippet, *NAME* is the *Value* of the Parameter with the *Name* `LogFormatN.Name`, and for the same value of N *FORMAT* is the *Value* of the Parameter with the *Name* `LogFormatN.Format`.

11: Log Format Snippet

```
- name: NAME
  format: 'FORMAT'
```

Tip: The order in which these Parameters are considered is exactly the numerical ordering implied by N (starting with it being empty). However, each section is generated for all values of N before moving on to the next.

After this, a single line containing only `filters:` is inserted. Then, for each Parameter on the *cache server's Profile* with a *Name* like `LogFilterN.Name` where N is either the empty string or a natural number on the interval [1,9], the YAML fragment in *Log Filter Snippet* will be inserted. In that snippet, *NAME* is the *Value* of the Parameter with the *Name* `LogFilterN.Name`, *TYPE* is the *Value* of the Parameter with the *Name* `LogFilterN.Type` for the same value of N, and *FILTER* is the *Value* of the Parameter with the *Name* `LogFilterN.Filter` for the same value of N.

12: Log Filter Snippet

```
- name: NAME
  action: TYPE
  condition: FILTER
```

Note: When, for a given value of N, a Parameter with the *Name* `LogFilterN.Name` exists, but a Parameter with the *Name* `LogFilterN.Type` does *not* exist, the value of *TYPE* in *Log Filter Snippet* will be accept.

At this point, a single line containing only `logs:` is inserted. Finally, for each Parameter on the *cache server's Profile* assigned to this Config File with a *Name* like `LogObjectN.Filename` where N is once again either an empty string or a natural number on the interval [1,9] the YAML fragment in *Log Object Snippet* will be inserted. In this snippet, for a given value of N *TYPE* is the *Value* of the Parameter with the *Name* `LogObjectN.Type`, *FILENAME* is the *Value* of the Parameter with the *Name* `LogObjectN.Filename`, *FORMAT* is the *Value* of the Parameter with the *Name* `LogObjectN.Format`.

13: Log Object Snippet

```
- mode: TYPE
  filename: FILENAME
  format: FORMAT
  ROLLING_OR_FILTERS
```

Note: When, for a given value of N a Parameter with the *Name* `LogObjectN.Filename` exists, but a Parameter with the *Name* `LogObjectN.Type` does *not* exist, the value of TYPE in *Log Object Snippet* will be `ascii`.

ROLLING_OR_FILTERS will be one of two YAML fragments based on the *Value* of the Parameter with the name `LogObjectN.Type`. In particular, if it is exactly `pipe`, then ROLLING_OR_FILTERS will be `filters: [FILTERS]` where FILTERS is the *Value* of the Parameter assigned to this Config File with the *Name* `LogObjectN.Filters` for the same value of N. If, however, the *Value* of the Parameter with the *Name* `LogObjectN.Type` is **not** exactly `pipe`, ROLLING_OR_FILTERS will have the format given by *Log Object (not a “pipe”) Snippet*. In that snippet, ROLLING is the *Value* of the Parameter with the *Name* `LogObjectN.RollingEnabled`, INTERVAL is the *Value* of the Parameter with the *Name* `LogObjectN.RollingIntervalSec`, OFFSET is the *Value* of the Parameter with the *Name* `LogObjectN.RollingOffsetHr`, and SIZE is the *Value* of the Parameter with the *Name* `LogObjectN.RollingSizeMb` - all for the same value of N and assigned to the `logging.yaml` Config File, obviously.

14: Log Object (not a “pipe”) Snippet

```
rolling_enabled: ROLLING
rolling_interval_sec: INTERVAL
rolling_offset_hr: OFFSET
rolling_size_mb: SIZE
```

See also:

For an explanation of YAML syntax, refer to the [official specification thereof](#). For an explanation of the syntax of a valid Apache Traffic Server `logging.yaml` configuration file, refer to [that project’s dedicated documentation](#).

logs_xml.config

This configuration file is somewhat more complex than most Config Files, in that it generates XML document tree segments¹ for each Parameter on the *cache server’s Profile* rather than simply a plain-text line. Specifically, up to ten of the document fragment shown in *LogFormat Snippet* will be inserted, one for each Parameter with this Config File value on the *cache*

¹ The contents of this file are not valid XML, but are rather XML-like so developers writing procedures that will consume and parse it should be aware of this, and note the actual syntax as specified in the [Apache Traffic Server documentation for logs_xml.config](#)

server's Profile that has a *Name* like `LogFormatN.Name` where N is either the empty string or a natural number on the range [1,9]. In that snippet, the string NAME is actually the *Value* of the Parameter with the *Name* `LogFormatN.Name`. FORMAT is the *Value* of the Parameter with the *Name* `LogFormatN.Format`, where again N is either the empty string or a natural number on the interval [1,9] - same-valued N Parameters are associated.

15: LogFormat Snippet

```
<LogFormat>
  <Name = "NAME"/>
  <Format = "FORMAT"/>
</LogFormat>
```

Tip: The order in which these Parameters are considered is exactly the numerical ordering implied by N (starting with it being empty).

Furthermore, for a given value of N, if a Parameter exists on the *cache server's Profile* having this Config File value with the *Name* `LogObjectN.Filename`, the document fragment shown in *LogObject Snippet* will be inserted. In that snippet, OBJ_FORMAT is the *Value* of the Parameter with the *Name* `LogObjectN.Format`, FILENAME is the *Value* of the Parameter with the *Name* `LogObjectN.Filename`, ROLLING is the *Value* of the Parameter with the *Name* `LogObjectN.RollingEnabled`, INTERVAL is the *Value* of the Parameter with the *Name* `LogObjectN.RollingIntervalSec`, OFFSET is the *Value* of the Parameter with the *Name* `LogObjectN.RollingOffsetHr`, SIZE is the *Value* of the Parameter with the *Name* `LogObjectN.RollingSizeMb`, and HEADER is the *Value* of the Parameter with the *Name* `LogObjectN.Header` - all having the same value of N, and the Config File value `logs_xml.config`, of course.

16: LogObject Snippet

```
<LogObject>
  <Format = "OBJ_FORMAT"/>
  <Filename = "FILENAME"/>
  <RollingEnabled = ROLLING/>
  <RollingInterval = INTERVAL/>
  <RollingOffsetHr = OFFSET/>
  <RollingSizeMb = SIZE/>
  <Header = "HEADER"/>
</LogObject>
```

Warning: The contents of these fields are not validated by Traffic Control - handle with care!

See also:

The [Apache Traffic Control documentation on the logs_xml.config configuration file](#)

Deprecated since version ATCv3.0: This file is only used by Apache Traffic Server version 6.x. The use of Apache Traffic Server version < 7.1 has been deprecated, and will not be supported in the future. Developers are encouraged to instead configure the *logging.config* configuration file.

package

This is a special, reserved Config File that isn't a file at all. When a Parameter's Config File is *package*, then its name is interpreted as the name of a package. *ORT* on the server using the *Profile* that has this Parameter will attempt to install a package by that name, interpreting the Parameter's *Value* as a version string if it is not empty. The package manager used will be *yum(8)*, regardless of system (though the Python version of *ORT* will attempt to use the host system's package manager - *yum(8)*, *apt(8)* and *pacman* are supported) but that shouldn't be a problem because only CentOS 7 and CentOS 8 are supported.

The current implementation of *ORT* will expect Parameters to exist on a *cache server*'s *Profile* with the *Names* *astats_over_http* and *trafficserver* before being run the first time, as both of these are required for a *cache server* to operate within a Traffic Control CDN. It is possible to install these outside of *ORT* - and indeed even outside of *yum(8)* - but such configuration is not officially supported.

packages

This Config File is reserved, and is used by *ORT* to pull bulk information about all of the Parameters with Config File values of *package*. It doesn't actually correspond to any configuration file.

parent.config

This configuration file is generated entirely from *Cache Group* relationships, as well as *Delivery Service* configuration. This file *can* be affected by Parameters on the server's *Profile* if and only if its *Name* is one of the following:

- *algorithm*
- *qstring*
- *psel.qstring_handling*
- *not_a_parent* - unlike the other Parameters listed (which have a 1:1 correspondence with Apache Traffic Server configuration options), this Parameter affects the generation of *parent* relationships between *cache servers*. When a Parameter with this *Name* and Config File exists on a *Profile* used by a *cache server*, it will not be added as a *parent* of any other *cache server*, regardless of *Cache Group* hierarchy. Under ordinary circumstances, there's no real reason for this Parameter to exist.

Additionally, *Delivery Service Profiles* can have special Parameters with the *Name* "mso.parent_retry" to *Configure Multi-Site Origin*.

See also:

To see how the *Values* of these Parameters are interpreted, refer to the [Apache Traffic Server documentation on the parent.config configuration file](#)

plugin.config

For each Parameter with this Config File value on the same *Profile*, a line in the resulting configuration file is produced in the format *NAME VALUE* where *NAME* is the Parameter's *Name* with trailing characters matching the regular expression `__\d+$` stripped out and *VALUE* is the Parameter's *Value*.

Caution: In order for Parameters for Config Files relating to Apache Traffic Server plugins - e.g. *regex_revalidate.config* - to have any effect, a Parameter must exist with this Config File value to instruct Apache Traffic Server to load the plugin. Typically, this is more easily achieved by assigning these Parameters to *The GLOBAL Profile* than on a server-by-server basis.

See also:

The [Apache Traffic server documentation on the plugin.config configuration file](#) explains what *Value* and *Name* a Parameter should have to be valid.

rascal.properties

This Config File is meant to be on Parameters assigned to either Traffic Monitor *Profiles* or *cache server Profiles*. Its allowed *Parameter Names* are all configuration options for Traffic Monitor. The *Names* with meaning are as follows.

See also:

Health Protocol

health.polling.format The *Value* of this Parameter should be the name of a parsing format supported by Traffic Monitor, used to decode statistics when polling for health and statistics. If this Parameter does not exist on a *cache server's Profile*, the default format (astats) will be used. The only supported values are

- *astats* parses the statistics output from the *astats_over_http* plugin.
- *stats_over_http* parses the statistics output from the *stats_over_http* plugin.
- *noop* no statistics are parsed; the *cache servers* using this *Value* will always be considered healthy, but statistics will never be gathered for them.

For more information on Traffic Monitor plug-ins that can expand the parsed formats, refer to *Extensions*.

health.polling.url The *Value* of this Parameter sets the URL requested when Traffic Monitor polls cache servers that have this Parameter in their *Profiles*. Specifically, the *Value* is

interpreted as a template - in a format reminiscent of variable interpolation in double-quoted strings in Bash -, that offers the following substitutions:

- `${hostname}` Replaced by the *IP Address* of the *cache server* being polled, and **not** its (short) hostname. The IP address used will be its IPv4 service address if it has one, otherwise its IPv6 service address. IPv6 addresses are properly formatted when inserted into the template, so the template need not include “square brackets” ([and]) around `${hostname}`s even when they anticipate they will be IPv6 addresses.
- `${interface_name}` Replaced by the name of the network interface that contains the *cache server*’s service address(es). For most cache servers (specifically those using the `stats_over_http` ATS plugin to report their health and statistics) using this in a template won’t be necessary.

If the template doesn’t include a specific port number, the *cache server*’s TCP port will be inserted if the URL uses the HTTP scheme, or its HTTPS Port if the *cache server* uses the the HTTPS scheme.

Table *health.polling.url Value Examples* gives some examples of templates, inputs, and outputs.

Table 46: health.polling.url Value Examples

Template	Chosen Service IP	TCP Port	HTTP Port	Interface Name	Output
<code>http://\${hostname}/_astats?inf.name=\${interface_name}</code>	192.0.2.42	8080	8443	eth0	<code>http://192.0.2.42:8080/_astats?inf.name=eth0</code>
<code>https://\${hostname}/_stats</code>	2001:DB8:0:0:1::1	8080	8443	eth0	<code>https://[2001:DB8:0:0:1::1]/_stats</code>
<code>http://\${hostname}:80/custom/stats/path/\${interface_name}</code>	192.0.2.42	8080	8443	eth0	<code>http://192.0.2.42:80/custom/stats/path/eth0</code>

health.threshold.loadavg The *Value* of this Parameter sets the “load average” above which the associated *Profile*’s *cache server* will be considered “unhealthy”.

See also:

The definition of a “load average” can be found in the documentation for the Linux/Unix command *uptime(1)*.

Caution: If more than one Parameter with this *Name* and Config File exist on the same *Profile* with different *Values*, the actual *Value* used by any given Traffic Monitor instance is undefined (though it will be the *Value* of one of those Parameters).

health.threshold.availableBandwidthInKbps The *Value* of this Parameter sets the amount of bandwidth (in kilobits per second) that Traffic Control will try to keep available on the *cache server* - for all network interfaces. For example a *Value* of “>1500000” indicates that the *cache server* will be marked “unhealthy” if its available remaining bandwidth across all of the network interfaces used by the caching proxy fall below 1.5Gbps.

Caution: If more than one Parameter with this *Name* and Config File exist on the same *Profile* with different *Values*, the actual *Value* used by any given Traffic Monitor instance is undefined (though it will be the *Value* of one of those Parameters).

history.count The *Value* of this Parameter sets the maximum number of collected statistics will retain at a time. For example, if this is “30”, then Traffic Monitor will keep up to the past 30 collected statistics runs for the *cache servers* using the *Profile* that has this Parameter. The minimum history size is 1, and if this Parameter’s *Value* is set below that, it will be treated as though it were 1.

Caution: This **must** be an integer. What happens when the *Value* of this Parameter is *not* an integer is not known to this author; at a guess, in all likelihood it would be treated as though it were 1 and warnings/errors would be logged by Traffic Monitor and/or Traffic Ops. However, this is not known and setting it improperly is potentially dangerous, so *please ensure it is always an integer*.

records.config

For each Parameter with this Config File value on the same *Profile*, a line in the resulting configuration file is produced in the format *NAME VALUE* where *NAME* is the Parameter’s *Name* with trailing characters matching the regular expression `__\d+$` stripped out and *VALUE* is the Parameter’s *Value*.

See also:

[The Apache Traffic Server records.config documentation](#)

regex_remap_anything.config

Config Files matching this pattern - where *anything* is zero or more characters - are generated entirely from *Delivery Service* configuration, which cannot be affected by any Parameters (except “*location*”).

See also:

For the syntax of configuration files for the “Regex Remap” plugin, see [the Regex Remap plugin’s official documentation](#). For instructions on how to enable a plugin, consult, the [plugin.config documentation](#).

regex_revalidate.config

This configuration file can only be affected by the special `maxRevalDurationDays`, which is discussed in the *The GLOBAL Profile* section.

See also:

For the syntax of configuration files for the “Regex Revalidate” plugin, see [the Regex Revalidate plugin’s official documentation](#). For instructions on how to enable a plugin, consult, the [plugin.config documentation](#).

remap.config

This configuration file can only be affected by Parameters on a *Profile* assigned to a *Delivery Service*. Then, for every Parameter assigned to that *Profile* that has the Config File value “`remap.config`” -, a parameter will be added to the line for that *Delivery Service* of the form `@pparam=Value` where Value is the Parameter’s *Value*. Each argument should have its own Parameter. Repeated arguments are allowed, but a warning is issued by *t3c* when processing configuration for cache servers that serve content for the *Delivery Service* with a *Profile* that includes duplicate arguments.

For backwards compatibility, a special case exists for the `cachekey.config` Config File for Parameters on *Delivery Service Profiles* that can also affect this configuration file. This is of the form: `pparam=--Name=Value` where Name is the Parameter’s *Name*, and Value is its *Value*. A warning will be issued by *t3c* when processing configuration for cache servers that serve content for the *Delivery Service* with a *Profile* that uses a Parameter with the Config File `cachekey.config` as well as at least one with the Config File `cachekey.pparam`.

The following plugins have support for adding args with following parameter Config File values.

- `background_fetch.pparam` Note the `--config=bg_fetch.conf` argument is already added to `remap.config` by *t3c*.
- `cachekey.pparam`
- `cache_range_requests.pparam`
- `slice.pparam` Note the `--blocksize=val` plugin parameter is specifiable directly on *Delivery Services* by setting their *Range Slice Request Block Size* property.
- `url_sig.pparam` Note the configuration file for this plugin is already added by *t3c*.

See also:

For more information about these plugin parameters, refer to the [Apache Traffic Server documentation for the background_fetch plugin](#), the [Apache Traffic Server documentation for the cachekey plugin](#), the [Apache Traffic Server documentation for the cache_range_requests plugin](#), the [Apache Traffic Server documentation for the slice plugin](#), and the [Apache Traffic Server documentation for the url_sig plugin](#), respectively.

Deprecated since version ATCv6: `cachekey.config` is deprecated but available for backwards compatibility. `cachekey.config` Parameters will be converted by *t3c* to the “pparam” syntax

with `--` added as a prefix to the *Name*. Any “empty” param value (i.e. separator) will add an extra `=` to the key.

Table 47: Equivalent cachekey.config/cachekey.pparam entries

<i>Name</i>	Config File	<i>Value</i>	Result
remove-all-params	cachekey.config	true	@pparam=--remove-all-params=true
cachekey.pparam	remap.config	--remove-all-params=true	@pparam=--remove-all-params=true
separator	cachekey.config	(empty value)	@pparam=--separator=
cachekey.pparam	remap.config	--separator=	@pparam=--separator=
cachekey.pparam	cachekey.pparam	o	@pparam=-o

See also:

For an explanation of the syntax of this configuration file, refer to [the Apache Traffic Server remap.config documentation](#).

set_dscp_anything.config

Configuration files matching this pattern - where *anything* is a string of zero or more characters is generated entirely from a “*location*” Parameter.

Tip: *anything* in that Config File name only has meaning if it is a natural number - specifically, one of each value of *DSCP* on every *Delivery Service* to which the *cache server* using the *Profile* on which the Parameter(s) exist(s).

ssl_multicert.config

This configuration file is generated from the SSL keys of *Delivery Services*, and is unaffected by any Parameters (except “*location*”)

See also:

[The official ssl_multicert.config documentation](#)

storage.config

This configuration file can only be affected by a handful of Parameters. If a Parameter with the *Name* “Drive Prefix” exists the generated configuration file will have a line inserted in the format *PREFIXLETTER* volume=1 for each letter in the comma-delimited list that is the *Value* of the Parameter on the same *Profile* with the *Name* “Drive Letters”, where *PREFIX* is the *Value* of the Parameter with the *Name* “Drive Prefix”, and *LETTER* is each of the aforementioned letters in turn. Additionally, if a Parameter on the same *Profile* exists with the *Name* “RAM Drive

Prefix” then for each letter in the comma-delimited list that is the *Value* of the Parameter on the same *Profile* with the *Name* “RAM Drive Letters”, a line will be generated in the format *PREFIXLETTER volume=i* where *PREFIX* is the *Value* of the Parameter with the *Name* “RAM Drive Prefix”, *LETTER* is each of the aforementioned letters in turn, and *i* is 1 *if and only if* a Parameter does **not** exist on the same *Profile* with the *Name* “Drive Prefix” and is 2 otherwise. Finally, if a Parameter exists on the same *Profile* with the *Name* “SSD Drive Prefix”, then a line is inserted for each letter in the comma-delimited list that is the *Value* of the Parameter on the same *Profile* with the *Name* “SSD Drive Letters” in the format *PREFIXLETTER volume=i* where *PREFIX* is the *Value* of the Parameter with the *Name* “SSD Drive Prefix”, *LETTER* is each of the aforementioned letters in turn, and *i* is 1 *if and only if both* a Parameter with the *Name* “Drive Prefix” and a Parameter with the *Name* “RAM Drive Prefix” *don’t exist on the same Profile*, or 2 if only **one** of them exists, or otherwise 3.

See also:

The Apache Traffic Server `storage.config` file documentation.

traffic_stats.config

This Config File value is only handled specially when the *Profile* to which it is assigned is of the special `TRAFFIC_STATS` *Type*. In that case, the *Name* of any Parameters with this Config File is restrained to one of “CacheStats” or “DsStats”. When it is “Cache Stats”, the *Value* is interpreted specially based on whether or not it starts with “ats.”. If it does, then what follows must be the name of one of the [core Apache Traffic Server statistics](#). This signifies to Traffic Stats that it should store that statistic for *cache servers* within Traffic Control. Additionally, the special statistics “bandwidth”, “maxKbps” are supported as *Names* - and in fact it is suggested that they exist in every Traffic Control deployment.

When the Parameter *Name* is “DSStats”, the allowed *Values* are:

- kbps
- status_4xx
- status_5xx
- tps_2xx
- tps_3xx
- tps_4xx
- tps_5xx
- tps_total

See also:

For more information on the statistics gathered by Traffic Stats, see [Traffic Stats Administration](#). For information about how these statics are gathered, consult the only known documentation of the “astats_over_http” Apache Traffic Server plugin: [traffic_server/plugins/astats_over_http/README.md](#).

sysctl.config

For each Parameter with this Config File value on the same *Profile*, a line in the resulting configuration file is produced in the format *NAME* = *VALUE* where *NAME* is the Parameter's *Name* with trailing characters matching the regular expression `___\d+$` stripped out and *VALUE* is the Parameter's *Value*.

uri_signing_anything.config

Config Files matching this pattern - where *anything* is zero or more characters - are generated entirely from the URI Signing Keys configured on a *Delivery Service* through either the *Traffic Ops API* or the *Delivery Services* view in Traffic Portal.

See also:

The draft RFC for *uri_signing* - note, however that the current implementation of *uri_signing* uses Draft 12 of that RFC document, **NOT** the latest.

url_sig_anything.config

Config Files that match this pattern - where *anything* is zero or more characters - are mostly generated using the URL Signature Keys as configured either through the *Traffic Ops API* or the *Delivery Services* view in Traffic Portal. However, if no such keys have been configured, they may be provided by fall-back Parameters. In this case, for each Parameter on assigned to this Config File on the same *Profile* a line is inserted into the resulting configuration file in the format *NAME* = *VALUE* where *NAME* is the Parameter's *Name* and *VALUE* is the Parameter's *Value*.

See also:

The Apache Trafficserver documentation for the *url_sig* plugin.

volume.config

This Config File is peculiar in that it depends only on the existence of Parameters, and not each Parameter's actual *Value*. The Parameters that affect the generated configuration file are the Parameters with the *Names* "Drive Prefix", "RAM Drive Prefix", and "SSD Drive Prefix". Each of these Parameters must be assigned to the *storage.config* Config File - **NOT this Config File** - and, of course, be on the same *Profile*. The contents of the generated Config File will be between zero and three lines (excluding headers) where the number of lines is equal to the number of the aforementioned Parameters that actually exist on the same *Profile*. Each line has the format `volume=i scheme=http size=SIZE%` where *i* is a natural number that ranges from 1 to the number of those Parameters that exist. *SIZE* is $100/N$ - where *N* is the number of those special Parameters that exist - truncated to the nearest natural number, e.g. $100/3 = 33$.

See also:

The Apache Traffic Server *volume.config* file documentation.

ID

An integral, unique identifier for a Parameter. Note that Parameters must have a unique combination of *Config File*, *Name*, and *Value*, and so those should be used for identifying a unique Parameter whenever possible.

Implementation Detail

If two *Profiles* have been assigned Parameters that have the same values for *Config File*, *Name*, and *Value* then Traffic Ops actually only stores one Parameter object and merely *links* it to both *Profiles*. This can be seen by inspecting the Parameters' IDs, as they will be the same. There are many cases where a user or developer must rely on this implementation detail, but both are encouraged to do so only when absolutely necessary.

Name

The Name of a Parameter has different meanings depending on the type of any and all *Profiles* to which it is assigned, as well as the *Config File* to which the Parameter belongs, but most generally it is used in *Apache Traffic Server configuration files* as the name of a configuration option in a name/value pair. Traffic Ops interprets the Name and *Value* of a Parameter in intelligent ways depending on the type of object to which the *Profile* using the Parameter is assigned. For example, if *Config File* is `records.config` and the Parameter's *Profile* is assigned to a *cache server*, then a single line is placed in the configuration file specified by *Config File*, and that line will have the contents *Name Value*. However, if the *Config File* of the Parameter is something without special meaning to Traffic Ops e.g. "foo", then a line containing **only** the Parameter's *Value* would be inserted into that file (presuming it also has a Parameter with a Name of "*location*" and a *Config File* of "foo"). Additionally, there are a few Names that are treated specially by Traffic Control.

location The *Value* of this Parameter is to be interpreted as a path under which the configuration file specified by *Config File* shall be found (or written, if not found). Any configuration file that is to exist on a server must have an associated "location" Parameter, even if the contents of the file cannot be affected by Parameters.

Caution: If a single *Profile* has multiple "location" Parameters for the same *Config File* with different *Values*, the actual location of the generated configuration file is undefined (but will be one of those Parameters' *Values*).

header If the *Profile* containing this Parameter is assigned to a server, **and** if the *Config File* is not one of the special values that Traffic Ops uses to determine special syntax formatting, then the *Value* of this Parameter will be used instead of the typical Traffic Ops header - *unless* it is the special string "none", in which case no header will be inserted at all.

Caution: If a single *Profile* has multiple “header” Parameters for the same *Config File* with different *Values*, the actual header is undefined (but will be one of those Parameters’ *Values*).

Secure

When this is ‘true’, a user requesting to see this Parameter will see the value `*****` instead of its actual value if the user’s permission *Role* isn’t ‘admin’.

Value

In general, a Parameter’s *Value* can be anything, and in the vast majority of cases the Value is *in no way validated by Traffic Control*. Usually, though, the Value has a special meaning depending on the values of the Parameter’s *Config File* and/or *Name*.

2.1.6 Traffic Monitor

Traffic Monitor is an HTTP service that monitors the *cache servers* in a CDN for a variety of metrics. These metrics are for use in determining the overall “health” of a given *cache server* and the related *Delivery Services*. A given CDN can operate a number of Traffic Monitors, from a number of geographically diverse locations, to prevent false positives caused by network problems at a given site. Traffic Monitors operate independently, but use the state of other Traffic Monitors in conjunction with their own state to provide a consistent view of CDN *cache server* health to downstream applications such as *Traffic Router*. *Health Protocol* governs the *cache server* and *Delivery Service* availability. Traffic Monitor provides a view into CDN health using several RESTful JSON endpoints, which are consumed by other Traffic Monitors and downstream components such as *Traffic Router*. Traffic Monitor is also responsible for serving the overall CDN configuration to *Traffic Router*, which ensures that the configuration of these two critical components remain synchronized as operational and health related changes propagate through the CDN.

Cache Monitoring

Traffic Monitor polls all *cache servers* configured with a status of REPORTED or ADMIN_DOWN at an interval specified as a configuration parameter in *Traffic Ops*. If the *cache server* is set to ADMIN_DOWN it is marked as unavailable but still polled for availability and statistics. If the *cache server* is explicitly configured with a status of ONLINE or OFFLINE, it is not polled by Traffic Monitor and presented to *Traffic Router* as configured, regardless of actual availability. Traffic Monitor makes HTTP requests at regular intervals to a special URL on each Edge-tier *cache server* and consumes the JSON output. The special URL is served by a plugin running on the ATS *cache servers* called “*astats*”, which is restricted to Traffic Monitor only. The *astats* plugin provides insight into application and system performance, such as:

- Throughput (e.g. bytes in, bytes out, etc).

- Transactions (e.g. number of 2xx, 3xx, 4xx responses, etc).
- Connections (e.g. from clients, to parents, origins, etc).
- Cache performance (e.g.: hits, misses, refreshes, etc).
- Storage performance (e.g.: writes, reads, frags, directories, etc).
- System performance (e.g: load average, network interface throughput, etc).

Many of the application-level statistics are available at the global or aggregate level, some at the *Delivery Service* level. Traffic Monitor uses the system-level performance to determine the overall health of the *cache server* by evaluating network throughput and load against values configured in *Traffic Ops*. Traffic Monitor also uses throughput and transaction statistics at the *Delivery Service* level to determine *Delivery Service* health. If *astats* is unavailable due to a network-related issue or the system statistics have exceeded the configured thresholds, Traffic Monitor will mark the *cache server* as unavailable. If the *Delivery Service* statistics exceed the configured thresholds, the *Delivery Service* is marked as unavailable, and *Traffic Router* will start sending clients to the overflow destinations for that *Delivery Service*, but the *cache server* remains available to serve other content.

See also:

For more information on ATS statistics, see the [ATS documentation](#)

Health Protocol

Optimistic Health Protocol

Redundant Traffic Monitor servers operate independently from each other but take the state of other Traffic Monitors into account when asked for health state information. In *Cache Monitoring*, the behavior of a single Traffic Monitor instance is described. The *Health Protocol* adds another dimension to the health state of the CDN by merging the states of all Traffic Monitors into one, and then taking the *optimistic* approach when dealing with a *cache server* or *Delivery Service* that might have been marked as unavailable by this particular instance or a peer instance of Traffic Monitor. Upon startup or configuration change in *Traffic Ops*, in addition to *cache servers*, Traffic Monitor begins polling its peer Traffic Monitors whose state is set to *ONLINE*. Each *ONLINE* Traffic Monitor polls all of its peers at a configurable interval and saves the peer's state for later use. When polling its peers, Traffic Monitor asks for the raw health state from each respective peer, which is strictly that instance's view of the CDN's health. When any *ONLINE* Traffic Monitor is asked for CDN health by a downstream component, such as *Traffic Router*, the component gets the Health Protocol-influenced version of CDN health (non-raw view). In operation of the Health Protocol, Traffic Monitor takes all health states from all peers, including the locally known health state, and serves an optimistic outlook to the requesting client. This means that, for example, if three of the four Traffic Monitors see a given *cache server* or *Delivery Service* as exceeding its thresholds and unavailable, it is still considered available. Only if all Traffic Monitors agree that the given object is unavailable is that state propagated to downstream components. This optimistic approach to the Health Protocol is counter to the “fail fast” philosophy, but serves well for large networks with complicated geography and/or routing. The optimistic Health Protocol allows network failures or latency to occur without affecting over-

all traffic routing, as Traffic Monitors can and do have a different view of the network when deployed in geographically diverse locations.

Optimistic Quorum

In order to prevent split-brain monitoring scenarios, a minimum of three Traffic Monitors are required to properly monitor a given CDN and the optimistic quorum feature should be enabled. If three or more Traffic Monitors are set to ONLINE, the optimistic quorum can be employed by setting the `peer_optimistic_quorum_min` property in `traffic_monitor.cfg` to a value greater than zero. This value represents the minimum number of peers that must be available in order to participate in the *Optimistic Health Protocol*. If Traffic Monitor detects that the number of available peers is less than this number, Traffic Monitor withdraws itself from participation in the health protocol by serving 503s for cache health state calls until connectivity is restored.

The optimistic quorum prevents invalid state propagation caused by a Traffic Monitor losing connectivity to the network and consequently marking all peers and caches as unavailable. When connectivity is restored, a race between peering recovery and polling from Traffic Routers begins. If Traffic Router were to poll a Traffic Monitor that has no available peers and optimistic quorum is not enabled or cannot be used (i.e.: too few Traffic Monitors), the Traffic Monitor will serve its local state only until peer connectivity is restored. If Traffic Router polls the Traffic Monitor when in this state, that is, prior to regaining peering, negative cache states caused by the lack of connectivity would be consumed and directly impact which caches are available for consideration for routing, until the Traffic Router polls a Traffic Monitor that has good state, or peering is restored. For this reason, it is recommended to run a minimum of three Traffic Monitors, with `peer_optimistic_quorum_min` set to a value of 1 or greater. Note that this value cannot exceed the number of peers of any given Traffic Monitor; that is, a value of 2 is the maximum value that can be used when three Traffic Monitors are in use. If this number exceeds the number of peers, the Traffic Monitor will always serve 503s and an error will be logged.

Protocol Engagement

Short polling intervals of both the *cache servers* and Traffic Monitor peers help to reduce customer impact of outages. It is not uncommon for a *cache server* to be marked unavailable by Traffic Monitor - in fact, it is business as usual for many CDNs. Should a widely requested video asset cause a single *cache server* to get close to its interface capacity, the Health Protocol will “kick in,” and Traffic Monitor marks the *cache server* as unavailable. New clients want to see the same asset, and now *Traffic Router* will send these customers to another *cache server* in the same *Cache Group*. The load is now shared between the two *cache servers*. As clients finish watching the asset on the overloaded *cache server*, it will drop below the threshold and gets marked available again, and new clients will begin to be directed to it once more. It is less common for a *Delivery Service* to be marked unavailable by Traffic Monitor. The *Delivery Service* thresholds are usually used for overflow situations at extreme peaks to protect other *Delivery Services* in the CDN from being impacted.

2.1.7 Traffic Ops

Traffic Ops is the tool for administration (configuration and monitoring) of all components in a Traffic Control CDN. *Traffic Portal* uses the *Traffic Ops API* to manage servers, *Cache Groups*, *Delivery Services*, etc. In many cases, a configuration change requires propagation to several, or even all, *cache servers* and only explicitly after or before the same change propagates to *Traffic Router*. Traffic Ops takes care of this required consistency between the different components and their configuration.

Traffic Ops uses a *PostgreSQL* database to store the configuration information, and a combination of the *Mojolicious* framework and *Go* to provide the *Traffic Ops API*. Not all configuration data is in this database however; for sensitive data like private SSL keys or token-based authentication shared secrets, *Traffic Vault* is used as a separate, key/value store, allowing administrators to harden the *Traffic Vault* server better from a security perspective (i.e only allow Traffic Ops to access it, verifying authenticity with a certificate). The Traffic Ops server, by design, needs to be accessible from all the other servers in the Traffic Control CDN.

Traffic Ops generates all the application-specific configuration files for the *cache servers* and other servers. The *cache servers* and other servers check in with Traffic Ops at a regular interval to see if updated configuration files require application. On *cache servers* this is done by the *ORT* script.

Traffic Ops also runs a collection of periodic checks to determine the operating state of the *cache servers*. These periodic checks are customizable by the Traffic Ops administrative user using *Traffic Ops Extensions*.

Traffic Ops Extension

Traffic Ops Extensions are a way to enhance the basic functionality of Traffic Ops in a custom manner. There are two types of extensions:

Check Extensions Allow you to add custom checks to the *Monitor* → *Cache Checks* view in *Traffic Portal*.

2.1.8 Traffic Portal

Traffic Portal is an [AngularJS 1.x](#) client served from a [Node.js](#) web server designed to consume the *Traffic Ops API*. It is the official replacement for the legacy *Traffic Ops* UI.

Features

- CDN Monitoring
- CDN Administration
- *Delivery Service* Configuration
- *cache server* Maintenance

See also:

See *Traffic Portal - Using* for an overview of the Traffic Portal UI.

2.1.9 Traffic Router

Traffic Router's function is to send clients to the most optimal *cache server*. 'Optimal' in this case is based on a number of factors:

- Distance between the *cache server* and the client (not necessarily measured in physical distance, but quite often in layer 3 network hops). Less network distance between the client and *cache server* yields better performance and lower network load. Traffic Router helps clients connect to the best-performing *cache server* for their location at the lowest network cost.
- Availability of *cache servers* and the system processing/network load on the *cache servers*. A common issue in Internet and television distribution scenarios is having many clients attempting to retrieve the same content at the same time. Traffic Router helps clients route around overloaded or purposely disabled *cache servers*.
- Availability of content on a particular *cache server*. Reusing of content through "cache hits" is the most important performance gain a CDN can offer. Traffic Router sends clients to the *cache server* that is most likely to already have the desired content.

Traffic routing options are often configured at the *Delivery Service* level.

DNS Content Routing

For a DNS *Delivery Service* the client might receive a URL such as `http://video.demo1.mycdn.ciab.test/`. When the LDNS is resolving this `video.demo1.mycdn.ciab.test` hostname to an IP address, it ends at Traffic Router because it is the authoritative DNS server for `mycdn.ciab.test` and the domains below it, and subsequently responds with a list of IP addresses from the eligible *cache servers* based on the location of the LDNS. When responding, Traffic Router does not know the actual client IP address or the path that the client is going to request. The decision on what *cache server* IP address (or list of *cache server* IP

addresses) to return is solely based on the location of the LDNS and the health of the *cache servers*. The client then connects to port 80 (HTTP) or port 443 (HTTPS) on the *cache server*, and sends the `Host: video.demo1.mycdn.ciab.test` header. The configuration of the *cache server* includes the “remap rule” `http://video.demo1.mycdn.ciab.test http://origin.infra.ciab.test` to map the routed name to an *Origin* hostname.

HTTP Content Routing

For an HTTP *Delivery Service* the client might receive a URL such as `http://video.demo1.mycdn.ciab.test/`. The LDNS resolves this `video.demo1.mycdn.ciab.test` to an IP address, but in this case Traffic Router returns its own IP address. The client opens a connection to port 80 (HTTP) or port 443 (HTTPS) on the Traffic Router’s IP address, and sends its request.

17: Example Client Request to Traffic Router

```
GET / HTTP/1.1
Host: video.demo1.mycdn.ciab.test
Accept: */*
```

Traffic Router uses an HTTP 302 Found response to redirect the client to the best *cache server*.

18: Traffic Router Redirect to Edge-tier *cache server*

```
HTTP/1.1 302 Found
Location: http://edge.demo1.mycdn.ciab.test/
Content-Length: 0
Date: Tue, 13 Jan 2015 20:01:41 GMT
```

In this case Traffic Router has access to more information when selecting a *cache server* because it has a full HTTP request instead of just a hostname. Traffic Router can be configured to select a *cache server* based on any of the following parts of the HTTP request:

- The client’s IP address.
- The URL the client is requesting.
- All HTTP/1.1 headers.

The client follows the redirect and performs a DNS request for the IP address for `edge.demo1.mycdn.ciab.test`, and normal HTTP steps follow, except the sending of the `Host:` header when connected to the cache is `Host: edge.demo1.mycdn.ciab.test`, and the configuration of the *cache server* includes the “remap rule” (e.g. `http://edge.demo1.mycdn.ciab.test http://origin.infra.ciab.test`). Traffic Router sends all requests for the same path in a *Delivery Service* to the same *cache server* in a *Cache Group* using consistent hashing, in this case all *cache servers* in a *Cache Group* are not carrying the same content, and there is a much larger combined cache in the *Cache Group*. In many cases DNS content routing is the best possible option, especially in cases where the client is receiving small objects from the CDN like images and web pages. Traffic Router is redundant and horizontally scalable by adding more instances into the DNS hierarchy using NS records.

2.1.10 Traffic Stats

Traffic Stats is a program written in [Go](#) that is used to acquire and store statistics about CDNs controlled by Traffic Control. Traffic Stats mines metrics from the [Traffic Monitor APIs](#) and stores the data in [InfluxDB](#). Data is typically stored in InfluxDB on a short-term basis (30 days or less). The data from InfluxDB is then used to drive graphs created by [Grafana](#) - which are linked to from [Traffic Portal](#) - as well as provide data exposed through the [Traffic Ops API](#). Traffic Stats performs two functions:

- Gathers statistics for Edge-tier *cache servers* and *Delivery Services* at a configurable interval (10 second default) from the [Traffic Monitor APIs](#) and stores the data in InfluxDB
- Summarizes all of the statistics once a day (around midnight UTC) and creates a daily report containing the Max GBPS (Gigabits per second) Served and the Total Bytes Served.

Statistics are stored in three different databases:

- `cache_stats`: Stores data gathered from edge-tier *cache servers*. The [measurements](#) stored by `cache_stats` are:
 - bandwidth
 - maxKbps
 - client_connections (ats.proxy.process.http.current_client_connections).

Cache Data is stored with [tags](#) for hostname, *Cache Group*, and CDN. Data can be queried using tags.

- `deliveryservice_stats`: Stores data for *Delivery Services*. The measurements stored by `deliveryservice_stats` are:
 - kbps
 - status_4xx
 - status_5xx
 - tps_2xx
 - tps_3xx
 - tps_4xx
 - tps_5xx
 - tps_total

Delivery Service statistics are stored with tags for *Cache Group*, CDN, and *Delivery Service xml_id*.

- `daily_stats`: Stores summary data for daily activities. The statistics that are currently summarized are:
 - Max Bandwidth
 - Bytes Served

Daily stats are stored by CDN.

Traffic Stats does not influence overall CDN operation, but is required in order to display charts in *Traffic Portal*.

2.1.11 Traffic Vault

Traffic Vault is a data store used for storing the following types of sensitive information:

- SSL Certificates
 - Private Key
 - Certificate
 - CSR (Certificate Signing Request)
- DNSSEC (DNS Security Extensions) Keys
 - Key Signing Key
 - * private key
 - * public key
 - Zone Signing Key
 - * private key
 - * public key
- URL Signing Keys

As the name suggests, Traffic Vault is meant to be a “vault” of private keys that only certain users are allowed to access. In order to create, add, and retrieve keys a user must have administrative privileges. Keys can be created via the *Traffic Portal* UI, but they can only be retrieved via the *Traffic Ops API*. Currently, the supported data stores used by Traffic Vault are PostgreSQL and Riak (deprecated). Support for Riak may be removed in a future release.

ADMINISTRATOR'S GUIDE

How to deploy and manage a Traffic Control CDN.

3.1 Administrator's Guide

Traffic Control is distributed in source form for the developer, but also as a binary package. This guide details how to install and configure a Traffic Control CDN using the binary packages, as well as how to perform common operations running a CDN.

When installing a complete CDN from scratch, a sample recommended order is:

1. Traffic Ops DB (PostgreSQL)
2. [InfluxDB](#) [Optional]
3. Traffic Vault (PostgreSQL or Riak) [Optional]
4. Fake Origin [Optional]
5. Traffic Ops
6. Traffic Portal
7. Initial Traffic Ops Dataset Setup [if applicable]
8. Traffic Monitor
9. Apache Traffic Server Mid-Tier Caches
10. Apache Traffic Server Edge-Tier Caches
11. Grove [Optional]
12. Traffic Router
13. [InfluxDB-relay](#) [Optional]
14. Traffic Stats [Optional]

Once everything is installed, you will need to configure the servers to talk to each other. You will also need Origin server(s), from which the Mid-Tier Cache(s) will obtain content. An Origin server is simply an HTTP(S) server which serves the content you wish to cache on the CDN.

3.1.1 Traffic Ops

Traffic Ops is quite possibly the single most complex and most important Traffic Control component. It has many different configuration options that affect a wide range of other components and their interactions.

Installing

System Requirements

The user must have the following for a successful minimal install:

- CentOS 7 or later
- Two machines - physical or virtual -, each with at least two (v)CPUs, 4GB of RAM, and 20 GB of disk space
- Access to CentOS Base and EPEL *yum(8)* repositories
- Access to [The Comprehensive Perl Archive Network \(CPAN\)](#)

Guide

1. Install PostgreSQL Database. For a production install it is best to install PostgreSQL on its own server/virtual machine.

See also:

For more information on installing PostgreSQL, see [their documentation](#).

19: Example PostgreSQL Install Procedure

```
yum update -y
yum install -y https://download.postgresql.org/pub/repos/
↳yum/reporepms/EL-7-x86_64/pgdg-redhat-repo-latest.noarch.
↳rpm
yum install -y postgresql13-server
su - postgres -c '/usr/pgsql-13/bin/initdb -A md5 -W' #-W
↳forces the user to provide a superuser (postgres)
↳password
```

2. Edit `/var/lib/pgsql/13/data/pg_hba.conf` to allow the Traffic Ops instance to access the PostgreSQL server. For example, if the IP address of the machine to be used as the Traffic Ops host is `192.0.2.1` add the line `host all all 192.0.2.1/32 md5` to the appropriate section of this file.
3. Edit the `/var/lib/pgsql/13/data/postgresql.conf` file to add the appropriate `listen_addresses` or `listen_addresses = '*'`, set `timezone = 'UTC'`, and start the database

20: Starting PostgreSQL with `systemd`(1)

```
systemctl enable postgresql-13
systemctl start postgresql-13
systemctl status postgresql-13 # Prints the status of the
↳PostgreSQL service, to prove it's running
```

4. Build a `traffic_ops-version string.rpm` file using the instructions under the [Building Traffic Control](#) page - or download a pre-built release from the [Apache Continuous Integration server](#).
5. Install a PostgreSQL client on the Traffic Ops host

21: Installing PostgreSQL Client from a Hosted Source

```
yum install -y https://download.postgresql.org/pub/repos/
↳yum/reporems/EL-7-x86_64/pgdg-redhat-repo-latest.noarch.
↳rpm
```

6. Install the Traffic Ops RPM. The Traffic Ops RPM file should have been built in an earlier step.

22: Installing a Generated Traffic Ops RPM

```
yum install -y ./dist/traffic_ops-3.0.0-xxxx.yyyyyyy.el7.
↳x86_64.rpm
```

Note: This will install the PostgreSQL client, `psql` as a dependency.

7. Login to the Database from the Traffic Ops machine. At this point you should be able to login from the Traffic Ops (hostname `to` in the example) host to the PostgreSQL (hostname `pg` in the example) host

23: Example Login to Traffic Ops Database from Traffic Ops Server

```
to-# psql -h pg -U postgres
Password for user postgres:
psql (13.2)
Type "help" for help.

postgres=#
```

8. Create the user and database. By default, Traffic Ops will expect to connect as the `traffic_ops` user to the `traffic_ops` database.

24: Creating the Traffic Ops User and Database

```
to-# psql -U postgres -h pg -c "CREATE USER traffic_ops_
↳WITH ENCRYPTED PASSWORD 'tcr0cks';"
Password for user postgres:
CREATE ROLE
to-# createdb traffic_ops --owner traffic_ops -U postgres -
↳h pg
Password:
to-#
```

9. Now, run the following command as the root user (or with *sudo(8)*): `/opt/traffic_ops/install/bin/postinstall`. Some additional files will be installed, and then it will proceed with the next phase of the install, where it will ask you about the local environment for your CDN. Please make sure you remember all your answers and verify that the database answers match the information previously used to create the database.

25: Example Output

```
to-# /opt/traffic_ops/install/bin/postinstall
...

===== /opt/traffic_ops/app/conf/production/database.
↳conf=====
Database type [Pg]:
Database type: Pg
Database name [traffic_ops]:
Database name: traffic_ops
Database server hostname IP or FQDN [localhost]: pg
Database server hostname IP or FQDN: pg
Database port number [5432]:
Database port number: 5432
Traffic Ops database user [traffic_ops]:
Traffic Ops database user: traffic_ops
Password for Traffic Ops database user:
Re-Enter Password for Traffic Ops database user:
Writing json to /opt/traffic_ops/app/conf/production/
↳database.conf
Database configuration has been saved
===== /opt/traffic_ops/app/db/dbconf.yml=====
Database server root (admin) user [postgres]:
Database server root (admin) user: postgres
Password for database server admin:
Re-Enter Password for database server admin:
===== /opt/traffic_ops/app/conf/cdn.conf=====
Generate a new secret? [yes]:
```

(continues on next page)

(continued from previous page)

```

Generate a new secret?: yes
Number of secrets to keep? [10]:
Number of secrets to keep?: 10
Not setting up ldap
===== /opt/traffic_ops/install/data/json/users.
↪ json=====
Administration username for Traffic Ops [admin]:
Administration username for Traffic Ops: admin
Password for the admin user:
Re-Enter Password for the admin user:
Writing json to /opt/traffic_ops/install/data/json/users.
↪ json
===== /opt/traffic_ops/install/data/json/openssl_
↪ configuration.json=====
Do you want to generate a certificate? [yes]:
Country Name (2 letter code): US
State or Province Name (full name): CO
Locality Name (eg, city): Denver
Organization Name (eg, company): Super CDN, Inc
Organizational Unit Name (eg, section):
Common Name (eg, your name or your server's hostname):
RSA Passphrase:
Re-Enter RSA Passphrase:
===== /opt/traffic_ops/install/data/json/profiles.
↪ json=====
Traffic Ops url [https://localhost]:
Traffic Ops url: https://localhost
Human-readable CDN Name. (No whitespace, please)↵
↪ [kabletown_cdn]: blue_cdn
Human-readable CDN Name. (No whitespace, please): blue_cdn
DNS sub-domain for which your CDN is authoritative [cdn1.
↪ kabletown.net]: blue-cdn.supercdn.net
DNS sub-domain for which your CDN is authoritative: blue-
↪ cdn.supercdn.net
Writing json to /opt/traffic_ops/install/data/json/
↪ profiles.json

... much SQL output skipped

Starting Traffic Ops
Restarting traffic_ops (via systemctl):
↪ [ OK ]
Waiting for Traffic Ops to restart
Success! Postinstall complete.

```

Table 48: Explanation of the information that needs to be provided:

Field	Description
Database type	This requests the type of database to be used. Answer with the default - 'Pg' to indicate a PostgreSQL database.
Database name	The name of the database Traffic Ops uses to store the configuration information.
Database server host-name IP or FQDN	The hostname of the database server (pg in the example).
Database port number	The database port number. The default value, 5432, should be correct unless you changed it during the setup.
Traffic Ops database user	The username Traffic Ops will use to read/write from the database.
Password for Traffic Ops	The password for the database user that Traffic Ops uses.
Database server root (admin) user name	Privileged database user that has permission to create the database and user for Traffic Ops...
Database server root (admin) user password	The password for the privileged database user.
Traffic Ops URL	The URL to connect to this instance of Traffic Ops, usually <code>https://Traffic Ops host</code>
Human-readable CDN Name	The name of the first CDN which Traffic Ops will be manage.
DNS sub-domain for which your CDN is authoritative	The DNS domain that will be delegated to this Traffic Control CDN.
Administration user-name for Traffic Ops	The Administration (highest privilege) Traffic Ops user to create. Use this user to login for the first time and create other users.
Password for the admin user	The password for the administrative Traffic Ops user.

Deprecated since version ATCv6: The postinstall script is now written in Python. If you run into issues with the postinstall script, you are encouraged to file an issue at <https://github.com/apache/trafficcontrol/issues/new/choose>. The original Perl postinstall script is deprecated and will be removed in a future ATC release. To use the deprecated version anyway, run `/opt/traffic_ops/install/bin/_postinstall.pl` directly instead of `/opt/traffic_ops/install/bin/postinstall`.

The postinstall script can also be run non-interactively using `traffic_ops/install/bin/input.json`

26: Postinstall in Automatic (-a) mode

```
/opt/traffic_ops/install/bin/postinstall -a --cfile /opt/traffic_
↪ops/install/bin/input.json
```

Deprecated since version ATCv6: Once the Perl script is removed, the values in `input.json` for the "hidden" properties will be changed from "1" and "0" to `true` and `false`.

Upgrading

To upgrade from older Traffic Ops versions, stop the service, use `yum(8)` to upgrade to the latest available Traffic Ops package, and use the [admin](#) tool to perform the database upgrade.

Tip: In order to upgrade to the latest version of Traffic Ops, please be sure that you have first upgraded to the latest available minor or patch version of your current release. For example, if your current Traffic Ops version is 3.0.0 and version 3.1.0 is available, you must first upgrade to 3.1.0 before proceeding to upgrade to 4.0.0. (Specifically, this means running all migrations, `traffic_ops/app/db/seeds.sql`, and `traffic_ops/app/db/patches.sql` for the latest of your current major version - which should be handled by the **admin** tool). The latest migration available before the release of 4.0.0 (pending at the time of this writing) was `traffic_ops/app/db/migrations/20180814000625_remove_capabilities_for_reseed.sql`, so be sure that migrations up to this point have been run before attempting to upgrade Traffic Ops.

See also:

[app/db/admin](#) for more details about **admin**.

27: Sample Script for Upgrading Traffic Ops

```
systemctl stop traffic_ops
yum upgrade traffic_ops
pushd /opt/traffic_ops/app/
./db/admin --env production upgrade
popd
```

After this completes, see [Guide](#) for instructions on running the **postinstall** script. Once the **postinstall** script, has finished, run the following command as the root user (or with `sudo(8)`): `systemctl start traffic_ops` to start the service.

Upgrading to 6.0

As of Apache Traffic Control 6.0, Traffic Ops supports PostgreSQL version 13.2. In order to migrate from the prior PostgreSQL version 9.6, it is recommended to use the `pg_upgrade` tool.

Running

While this section contains instructions for running Traffic Ops manually, the only truly supported method is via `systemd(8)`, e.g. `systemctl start traffic_ops` (this method starts the program properly and uses its default configuration file locations).

traffic_ops_golang

```
traffic_ops_golang [--version] [--plugins] [--api-routes] --cfg
CONFIG_PATH --dbcfg DB_CONFIG_PATH [--riakcfg RIAK_CONFIG_PATH]
```

--cfg CONFIG_PATH

This **mandatory** command line flag specifies the absolute or relative path to the configuration file to be used by Traffic Ops - [cdn.conf](#).

--dbcfg DB_CONFIG_PATH

This **mandatory** command line flag specifies the absolute or relative path to a configuration file used by Traffic Ops to establish connections to the PostgreSQL database - [database.conf](#)

--plugins

List the installed plugins and exit.

--api-routes

Print information about all API routes and exit. If also used with the `--cfg` option, also print out the configured routing blacklist information from [cdn.conf](#).

--riakcfg RIAK_CONFIG_PATH

Deprecated since version 6.0: This optional command line flag specifies the absolute or relative path to a configuration file used by Traffic Ops to establish con-

nections to Riak when used as the Traffic Vault backend - [riak.conf](#). Please use "traffic_vault_backend": "riak" and "traffic_vault_config": {...} (with the contents of [riak.conf](#)) instead.

Implementation Detail

The name of this flag is derived from the current database used in the implementation of Traffic Vault - [Riak KV](#).

--version

Print version information and exit.

Configuring

traffic_ops_golang uses several configuration files, but the most important of these is [cdn.conf](#).

Configuration Files

cdn.conf

This file deals with the configuration parameters of running Traffic Ops itself. It is a JSON-format set of options and their respective values. [traffic_ops_golang](#) will use whatever file is specified by its `--cfg` option. The keys of the file are described below.

acme_accounts This is an optional array of objects to define ref:external_account_binding information to an existing ACME (Automatic Certificate Management Environment) account. The *acme_provider* and *user_email* combination must be unique.

New in version 5.1.

acme_provider The certificate provider. This field needs to correlate to the AuthType field for each certificate so the renewal functionality knows which provider to use.

user_email The email used to set up the account with the provider.

acme_url The URL for the ACME.

kid The key ID provided by the ACME provider for ref:external_account_binding.

hmac_encoded The HMAC (Hashed Message Authentication Code) key provided by the ACME provider for ref:external_account_binding. This should be in Base64 URL encoded.

acme_renewal This object contains the information for the automatic renewal script for certificates.

New in version 5.1.

renew_days_before_expiration Set the number of days before expiration date to renew certificates.

summary_email The email address to use for summarizing certificate expiration and renewal status. If it is blank, no email will be sent.

default_certificate_info This is an optional object to define default values when generating a self signed certificate when an HTTPS delivery service is created or updated. If this is an empty object or not present in the *cdn.conf* then the term “Placeholder” will be used for all fields.

business_unit An optional field which, if present, will represent the business unit for which the SSL certificate was generated

city An optional field which, if present, will represent the resident city of the generated SSL certificate

organization An optional field which, if present, will represent the organization for which the SSL certificate was generated

country An optional field which, if present, will represent the resident country of the generated SSL certificate

state An optional field which, if present, will represent the resident state or province of the generated SSL certificate

geniso This object contains configuration options for system ISO generation.

iso_root_path Sets the filesystem path to the root of the ISO generation directory. For default installations, this should usually be set to `/opt/traffic_ops/app/public`.

Deprecated since version ATCv6: The `geniso.iso_root_path` configuration option is unused now that Traffic Ops is rewritten from Perl to Golang and will be removed in a future ATC release.

See also:

Generate ISO

hypnotoad This is a group of options that mainly no longer have any meaning..

group Serves no known purpose anymore.

heartbeat_timeout Serves no known purpose anymore.

listen This must always be an array containing a single string. This very odd string is apparently a URL. The scheme of the URL doesn't matter, as *traffic_ops_golang* ignores that and always uses HTTPS. The host (and optionally port) of the URL used to have a purpose, but no longer does. The “cert” query parameter sets the location of the SSL certificate to use for encrypting connections, while the “key” query parameter is the certificate's

corresponding private key. The default configuration file also has the “verify” query parameter which serves no known purpose anymore.

pid_file Serves no known purpose anymore.

user Serves no known purpose anymore.

workers Serves no known purpose anymore.

inactivity_timeout Serves no known purpose anymore.

influxdb_conf_path An optional field which gives *traffic_ops_golang* the absolute or relative path to an *influxdb.conf* file. Default if not specified is to first check if the *MOJO_MODE* environment variable is set. If it is, then Traffic Ops will look in the current working directory for a subdirectory named *conf/*, then inside that for a subdirectory with the name that is the value of the *MOJO_MODE* variable, and inside that directory for a file named *influxdb.conf*. If *MOJO_MODE* is *not* set, then Traffic Ops will look for a file named *influxdb.conf* in the same directory as this *cdn.conf* file.

New in version 4.0.

Warning: While relative paths are allowed, they are discouraged, as the path will be relative to the working directory of the *traffic_ops_golang* process itself, not relative to the *cdn.conf* configuration file, which can be confusing.

ldap_conf_location An optional field which gives *traffic_ops_golang* the absolute or relative path to an *ldap.conf* file. Default if not specified is a file named *ldap.conf* in the same directory as this *cdn.conf* file.

Warning: While relative paths are allowed, they are discouraged, as the path will be relative to the working directory of the *traffic_ops_golang* process itself, not relative to the *cdn.conf* configuration file, which can be confusing.

lets_encrypt New in version 4.1.

user_email A required email address to create an account with Let’s Encrypt or to receive expiration updates. If this is not included then *rate limits* may apply for the number of certificates.

send_expiration_email A boolean option to send email summarizing certificate expiration status

Deprecated since version 5.1: Future versions of Traffic Ops will not support this legacy configuration option, see *acme_renewal*:
{ summary_email: <string> } instead.

convert_self_signed A boolean option to convert self signed to Let's Encrypt certificates as they expire. This only works for certificates labeled as Self Signed in the Certificate Source field.

renew_days_before_expiration Set the number of days before expiration date to renew certificates.

Deprecated since version 5.1: Future versions of Traffic Ops will not support this legacy configuration option, see `acme_renewal`:
{ `renew_days_before_expiration`: <int> } instead.

environment This specifies which Let's Encrypt environment to use: 'staging' or 'production'. It defaults to 'production'.

portal This section provides information regarding a connected UI with which users interact, so that emails can include links to it.

base_url This URL should be the root and/or landing page of the UI. For Traffic Portal instances, this should include the fragment part of the URL, e.g. `https://trafficportal.infra.ciab.test/#!/.`

docs_url The actual use of this URL is unknown, but supposedly it ought to point to the documentation for the Traffic Control instance. It's hard to imagine a fantastic reason this shouldn't just always be <https://traffic-control-cdn.readthedocs.io>

email_from Most emails sent from the Traffic Ops server will use `to.email_from`, but specifically password reset requests (which contain a link to a fragment under `portal.base_url`) will instead use this as the value of their *From* field.

pass_reset_path A path to be added to `base_url` that is the URL of the UI's password reset interface. For Traffic Portal instances, this should always be set to "user".

user_register_path A path to be added to `base_url` that is the URL of the UI's new user registration interface. For Traffic Portal instances, this should always be set to "user".

secrets This is an array of strings, which cannot be empty. The first secret in the array is used to encrypt Traffic Ops authentication cookies - multiple Traffic Ops instances serving the same CDN need to share secrets in order for users logged into one to be able to use their cookie as authentication with other instances.

smtp This optional section contains options for connecting to and authenticating with an SMTP (Simple Mail Transfer Protocol) server for sending emails. If this section is undefined (or if `enabled` is explicitly `false`), Traffic Ops will not be able to send emails and certain *Traffic Ops API* endpoints that depend on that functionality will fail to operate.

New in version 4.0.

address This is the address of the SMTP which will be used to send emails. Should include the port number, e.g. "localhost:25" for *sendmail(8)* on the Traffic Ops server.

enabled A boolean flag that determines whether or not connection to an SMTP ought to be allowed. Whatever the settings of the other fields in the *smtp* object, email cannot and will not be sent if this is *false*.

password The password to be used when authenticating with the SMTP server.

user The name of the user to be used when authenticating with the SMTP server.

Note: The SMTP integration currently only supports Login Auth.

to Contains information to identify Traffic Ops in a network sense.

base_url This field is used to identify the location for the now-removed Traffic Ops UI. It no longer serves any purpose.

email_from Sets the address that will appear in the *From* field of Emails sent by Traffic Ops.

no_account_found_msg When a password reset is requested for an email address not registered to any known user, this is the message that will be sent to that email address.

traffic_ops_golang This group configuration options is used exclusively by *traffic_ops_golang*.

crconfig_emulate_old_path An optional boolean that controls the value of a part of *Snapshots* that report what *Traffic Ops API* endpoint is used to generate *Snapshots*. If this is *true*, it forces Traffic Ops to report that a legacy, deprecated endpoint is used, whereas if it's *false* Traffic Ops will report the actual, current endpoint. Default if not specified is *false*.

Deprecated since version 3.0: Future versions of Traffic Ops will not support this legacy configuration option, and will always report the current endpoint.

crconfig_snapshot_use_client_request_host An optional boolean which controls the value of the Traffic Ops server's URL as inserted into *Snapshots*. If this is *true*, then the value used will be taken from the *Host* header of the request that generated the *Snapshot*. If it's *false*, then it will instead use the value of the global "tm.url" *Parameter*. Default if not specified is *false*.

Deprecated since version 3.0: Future versions of Traffic Ops will not support this legacy configuration option, and will always use

the global “tm.url” *Parameter*.

db_conn_max_lifetime_seconds An optional field that sets the maximum lifetime in seconds of any given connection to the Traffic Ops Database. If set to zero, connections are held open until explicitly closed. Default if not specified is the value of `DBConnMaxLifetimeSecondsDefault`.

db_max_idle_connections An optional limit on the number of connections to the Traffic Ops Database to keep alive while idle. If this is less than `max_db_connections`, that number will be used instead - *even if this field is unset and using its default*. Default if not specified is the value of `DBMaxIdleConnectionsDefault`.

db_query_timeout_seconds An optional field specifying a timeout on database *transactions* (not actually single queries in most cases) within API route handlers. Effectively this is a timeout on a single handler’s ability to interact with the Traffic Ops Database. Default if not specified is the value of `DefaultDBQueryTimeoutSecs`.

idle_timeout An optional timeout in seconds for idle client connections to Traffic Ops. If set to zero, the value of `read_timeout` will be used instead. If both are zero, then the value of `read_header_timeout` will be used. If all three fields are zero, there is no timeout and connections will be kept alive indefinitely - **not** recommended. Default if not specified is zero.

insecure An optional boolean which, if set to `true` will cause Traffic Ops to skip verification of client certificates whenever necessary/possible. If set to `false`, the normal verification behavior is exhibited. Default if not specified is `false`.

Deprecated since version 5.0: Future versions of Traffic Ops will not support this legacy configuration option, see `tls_config`: { `InsecureSkipVerify`: <bool> } instead

log_location_debug This optional field, if specified, should either be the location of a file to which debug-level output will be logged, or one of the special strings “stdout” which indicates that STDOUT should be used, “stderr” which indicates that STDERR should be used or “null” which indicates that no output of this level should be generated. An empty string (“”) and literally null are equivalent to “null”. Default if not specified is “null”.

log_location_error This optional field, if specified, should either be the location of a file to which error-level output will be logged, or one of the special strings “stdout” which indicates that STDOUT should be used, “stderr” which indicates that STDERR should be used or “null” which indicates that no output of

this level should be generated. An empty string ("") and literally `null` are equivalent to `"null"`. Default if not specified is `"null"`. This field is also used to determine where server profiling statistics are written. Assuming `profiling_enabled` is `true` and `profiling_location` is unset, if this field's value is given as a path to a regular file, a file named `profiling` will be written to the same directory containing the profiling information - overwriting any existing files by that name.

log_location_event This optional field, if specified, should either be the location of a file to which event-level output will be logged, or one of the special strings `"stdout"` which indicates that `STDOUT` should be used, `"stderr"` which indicates that `STDERR` should be used or `"null"` which indicates that no output of this level should be generated. An empty string ("") and literally `null` are equivalent to `"null"`. Default if not specified is `"null"`.

log_location_info This optional field, if specified, should either be the location of a file to which informational-level output will be logged, or one of the special strings `"stdout"` which indicates that `STDOUT` should be used, `"stderr"` which indicates that `STDERR` should be used or `"null"` which indicates that no output of this level should be generated. An empty string ("") and literally `null` are equivalent to `"null"`. Default if not specified is `"null"`.

log_location_warning This optional field, if specified, should either be the location of a file to which warning-level output will be logged, or one of the special strings `"stdout"` which indicates that `STDOUT` should be used, `"stderr"` which indicates that `STDERR` should be used or `"null"` which indicates that no output of this level should be generated. An empty string ("") and literally `null` are equivalent to `"null"`. Default if not specified is `"null"`.

max_db_connections An optional limit on the number of allowed concurrent connections to the Traffic Ops Database. If it is less than or equal to zero, there is no limit. Default if not specified is zero.

oauth_client_secret An optional secret string to be shared with OAuth-capable clients attempting to authenticate via OAuth. The default behavior if this is not defined - or is an empty string ("") or `null` is to disallow authentication via OAuth.

Warning: OAuth support in Traffic Ops is still in its infancy, so most users are advised to avoid defining this field without good cause.

plugins An optional array of enabled plugin names. These names must be unique. Note that a plugin that is installed will not be used unless its name appears in this list - thus “enabling” it. If not specified no plugins will be enabled.

plugin_config This optional object maps plugin names - which **must** appear in the `plugins` array - to arbitrary JSON configurations for said plugins. It is up to the plugins themselves to parse these configurations. The default if not specified is no configuration information, somewhat obviously.

plugin_shared_config This optional object is just an arbitrary JSON object that is converted into a native object and made available to any and all loaded and enabled plugins. A typical use-case for this field is avoiding repetition of identical configuration in `plugin_config`. The default if not specified is `null`.

port Sets the port on which Traffic Ops will listen for incoming connections.

profiling_enabled An optional boolean which, if `true` will enable the gathering of profiling statistics on the Traffic Ops server. Default if not specified is `false`.

profiling_location An optional string which, if set, should be the absolute path (relative paths are allowed but not recommended) to a file where profiling statistics for the Traffic Ops server will be written. If `profiling_enabled` is `true` but this is not specified, or is an empty string (“”) or `null`, then a file named “profiling” will be created or overwritten in the same directory as the file specified in `log_location_error`. If that file is not a regular file, then Traffic ops will instead create a temporary directory and write profiling statistics to a file named “profiling” within that directory.

proxy_keep_alive Serves no known purpose anymore.

proxy_read_handler_timeout Serves no known purpose anymore.

proxy_timeout Serves no known purpose anymore.

proxy_tls_timeout Serves no known purpose anymore.

read_header_timeout An optional timeout in seconds before which Traffic Ops must be able to finish reading the headers of an incoming request or it will drop the connection. If set to zero, there is no timeout. Default if not specified is zero.

read_timeout An optional timeout in seconds before which Traffic Ops must be able to finish reading an entire incoming request (including body) or it will drop the connection. If set to zero, there is no timeout. Default if not specified is zero.

request_timeout An optional timeout in seconds that serves as the

maximum time each Traffic Ops middleware can take to execute. If it is exceeded, the text “server timed out” is served in place of a response. If set to 0, 60 is used instead. Default if not specified is 60.

riak_port An optional field that sets the port on which Traffic Ops will try to contact Traffic Vault for storage and retrieval of sensitive encryption keys.

Deprecated since version 6.0: Please use a “port” field in `traffic_vault_config` instead when using “traffic_vault_backend”: “riak”.

Implementation Detail

The name of this field is derived from the current database used in the implementation of Traffic Vault - [Riak KV](#).

whitelisted_oauth_url An optional array of URLs which are allowed to authenticate Traffic Ops users via OAuth. The default behavior if this field is not defined is to not allow OAuth authentication.

Warning: OAuth support in Traffic Ops is still in its infancy, so most users are advised to avoid defining this field without good cause.

write_timeout An optional timeout in seconds set on handlers. After reading a request’s header, the server will have this long to send back a response. If set to zero, there is no timeout. Default if not specified is zero.

traffic_vault_backend New in version 6.0: Optional. The name of which backend to use for Traffic Vault. Currently, the only supported backend is “riak”.

traffic_vault_config New in version 6.0: Optional. The JSON configuration which is unique to the chosen Traffic Vault backend. See [Traffic Vault Administration](#) for the configuration options for each supported backend.

routing_blacklist Optional configuration for explicitly disabling any routes via `disabled_routes`.

New in version 4.0.

perl_routes Serves no known purpose anymore.

Deprecated since version 6.0: This was used back when Traffic Ops was still in the process of being rewritten

from Perl. It serves no purpose anymore, and will be removed in the future.

disabled_routes A list of API route IDs to disable. Requests matching these routes will receive a 503 response. To find the route ID for a given path you would like to disable, run `./traffic_ops_golang` using the `--api-routes` option to view all the route information, including route IDs and paths.

ignore_unknown_routes If false (default) return an error and prevent startup if unknown route IDs are found. Otherwise, log a warning and continue startup.

tls_config An optional stanza for TLS configuration. The values of which conform to the `crypto/tls.Config` structure.

use_ims New in version 5.0: This is an optional boolean value to enable the handling of the “If-Modified-Since” HTTP request header. Default: false

Example `cdn.conf`

```
{
  "hypnotoad" : {
    "listen" : [
      "https://[::]:60443?cert=/etc/pki/tls/certs/localhost.crt&
→key=/etc/pki/tls/private/localhost.key&verify=0x00&ciphers=AES128-
→GCM-SHA256:HIGH:!RC4:!MD5:!aNULL:!EDH:!ED"
    ],
    "user" : "trafops",
    "group" : "trafops",
    "heartbeat_timeout" : 20,
    "pid_file" : "/var/run/traffic_ops.pid",
    "workers" : 12
  },
  "traffic_ops_golang" : {
    "port" : "443",
    "proxy_timeout" : 60,
    "proxy_keep_alive" : 60,
    "proxy_tls_timeout" : 60,
    "proxy_read_header_timeout" : 60,
    "read_timeout" : 60,
    "request_timeout" : 60,
    "read_header_timeout" : 60,
    "write_timeout" : 60,
    "idle_timeout" : 60,
    "log_location_error": "/var/log/traffic_ops/error.log",
    "log_location_warning": "",
```

(continues on next page)

(continued from previous page)

```

    "log_location_info": "",
    "log_location_debug": "",
    "log_location_event": "/var/log/traffic_ops/access.log",
    "max_db_connections": 20,
    "db_max_idle_connections": 15,
    "db_conn_max_lifetime_seconds": 60,
    "db_query_timeout_seconds": 20,
    "whitelisted_oauth_urls": [],
    "oauth_client_secret": "",
    "traffic_vault_backend": "",
    "traffic_vault_config": {},
    "routing_blacklist": {
        "ignore_unknown_routes": false,
        "disabled_routes": []
    },
    "profiling_enabled": false,
    "supported_ds_metrics": [ "kbps", "tps_total", "tps_2xx", "tps_
→3xx", "tps_4xx", "tps_5xx" ],
    "tls_config": {
        "MinVersion": 769
    }
},
"use_ims": false,
"cors" : {
    "access_control_allow_origin" : "*"
},
"to" : {
    "base_url" : "http://localhost:3000",
    "email_from" : "no-reply@traffic-ops-domain.com",
    "no_account_found_msg" : "A Traffic Ops user account is
→required for access. Please contact your Traffic Ops user
→administrator."
},
"portal" : {
    "base_url" : "https://localhost/#!/",
    "docs_url" : "https://traffic-control-cdn.readthedocs.io/en/
→latest/admin/traffic_portal/usingtrafficportal.html",
    "email_from" : "no-reply@traffic-portal-domain.com",
    "pass_reset_path" : "user",
    "user_register_path" : "user"
},
"secrets" : [
    "mONKEYDmONKEYSEE."
],
"inactivity_timeout" : 60,
"smtp" : {

```

(continues on next page)

(continued from previous page)

```

        "enabled" : false,
        "user" : "",
        "password" : "",
        "address" : ""
    },
    "inactivity_timeout" : 60,
    "lets_encrypt" : {
        "user_email" : "",
        "send_expiration_email": false,
        "convert_self_signed": false,
        "renew_days_before_expiration": 30,
        "environment": "production"
    },
    "acme_renewal": {
        "summary_email": "",
        "renew_days_before_expiration": 30
    },
    "acme_accounts": [
        {
            "acme_provider" : "",
            "user_email" : "",
            "acme_url" : "",
            "kid" : "",
            "hmac_encoded" : ""
        }
    ],
    "default_certificate_info" : {
        "business_unit" : "",
        "city" : "",
        "organization" : "",
        "country" : "",
        "state" : ""
    }
}

```

database.conf

This file deals with configuration of the Traffic Ops Database; in particular it tells Traffic Ops how to connect with the database for its current environment. *traffic_ops_golang* will read this file in from the path pointed to by its *--dbcfg* flag. *database.conf* is encoded as a JSON object, and its keys are described below.

dbname The name of the PostgreSQL database used. Typically different databases are used for different environments, e.g. “trafficops_test”, “trafficops”, etc. Many environments choose to use *traffic_ops*.

description An optional, human friendly description of the database. Generally this should just describe the purpose of the database e.g. “This database is used for integration testing with our toolset”.

hostname The hostname (FQDN) of the server that runs the Traffic Ops Database.

password The password to use when authenticating with the Traffic Ops database. In a typical install process, the `postinstall` script will ask for a password to use for this connection, and this should match that.

port The port number (as a string) on which the Traffic Ops Database is listening for incoming connections. *traffic_ops_golang* ignores this and always uses the default PostgreSQL port (5432).

ssl A boolean that sets whether or not the Traffic Ops Database encrypts its connections with SSL.

type A string that gives the “type” of database pointed to by all the other options. Once upon a time it was possible for this to either be “mysql” or “postgres”, but the only valid value anymore is “postgres” - and *traffic_ops_golang* ignores this field entirely (and in fact doesn’t even care if it’s defined at all) and only supports “postgres” databases.

user The name of the user as whom to connect to the database. In a typical install process, the `postinstall` script will ask for the name of a user to set up for the Traffic Ops Database, and this should match that. Many environments choose to use `traffic_ops`.

Example database.conf

```
{
  "description": "Local PostgreSQL database on port 5432",
  "dbname": "traffic_ops",
  "hostname": "localhost",
  "user": "traffic_ops",
  "password": "password",
  "port": "5432",
  "ssl": false,
  "type": "Pg"
}
```

influxdb.conf

This file deals with configuration of the InfluxDB cluster that serves Traffic Stats; specifically it tells Traffic Ops how to authenticate with the InfluxDB cluster and which measurements to check. *traffic_ops_golang* will look for this file at the path given by the value of `influx_db_conf_path` in *cdn.conf*. This file is encoded as a JSON object, and its keys are described below.

See also:

For more information about InfluxDB, see [the InfluxDB documentation](#).

cache_stats_db_name This field sets the name of the “database” (measurement) used to query for *Cache Group* statistics. *traffic_ops_golang* will default to "cache_stats" if this field is not defined. It is recommended that this field not be defined.

Danger: The **only** valid value for this is "cache_stats", if it is anything else Traffic Stats data for *Cache Group* statistics will be inaccessible through the *Traffic Ops API*.

deliveryservice_stats_db_name This field sets the name of the “database” (measurement) used to query for *Delivery Service* statistics. *traffic_ops_golang* will default to "deliveryservice_stats" if this field is not defined. It is recommended that this field not be defined.

Danger: The **only** valid value for this is "deliveryservice_stats", if it is anything else Traffic Stats data for *Delivery Service* statistics will be inaccessible through the *Traffic Ops API*.

password Sets the password to use when authenticating with InfluxDB clusters.

secure An optional boolean that sets whether or not to use SSL encrypted connections to the InfluxDB cluster (the InfluxDB servers would need to be configured to use SSL). Default if not specified is `false`.

user Sets the user name as whom to authenticate with InfluxDB clusters.

Example influxdb.conf

```
{
  "user": "influxuser",
  "password": "password",
  "deliveryservice_stats_db_name": "deliveryservice_stats",
  "cache_stats_db_name": "cache_stats",
```

(continues on next page)

(continued from previous page)

```
"secure": false
}
```

ldap.conf

This file defines methods of connection to an LDAP (Lightweight Directory Access Protocol) server and semantics for searching for users on it for the purpose of authentication. *trafic_ops_golang* will look for this file at the path given by the value of `ldap_conf_location` in *cdn.conf*. `ldap.conf`'s contents are a JSON-encoded object, the keys of which are detailed below.

See also:

For more information on LDAP see [the LDAP Wikipedia page](#) and [RFC 4511](#).

admin_dn The LDAP DN (Distinguished Name) of the administrative user.

admin_pass The password of the administrative user for the LDAP.

host The full hostname of the LDAP server, preceded by a scheme (only `ldap://` and `ldaps://` are supported), optionally including port number.

insecure A boolean that tells Traffic Ops whether or not to verify the certificate chain of the LDAP server if it uses TLS-encrypted communications.

ldap_timeout_secs Sets a timeout in seconds for connections to the LDAP.

search_base The directory relative to which searches for users should be conducted.

search_query A query to be used to search for users. The string `%s` should appear exactly once in this string, where user names will be inserted procedurally by the handler for LDAP logins.

Example ldap.conf

```
{
  "admin_pass" : "password",
  "search_base" : "dc=prefix,dc=domain,dc=suffix",
  "admin_dn" : "user@prefix.domain.suffix",
  "host" : "ldaps://host:[port]",
  "search_query" : "(&
→(objectCategory=person)(objectClass=user)(userName=%s))",
  "insecure" : false,
  "ldap_timeout_secs" : 20
}
```

riak.conf

Deprecated since version 6.0: The `riak.conf` configuration file and associated `--riakcfg` flag have been deprecated and will be removed from Traffic Control in the future. Please use `"traffic_vault_backend": "riak"` and put the existing contents of `riak.conf` into `"traffic_vault_config": {...}` in `cdn.conf` instead.

This file sets authentication options for connections to Riak when used as the Traffic Vault backend. `traffic_ops_golang` will look for this file at the path given by the value of the `--riakcfg` flag as passed on startup. The contents of `riak.conf` are encoded as a JSON object, the keys of which are described in *Riak (deprecated)*.

Implementation Detail

The name of this file is derived from the current database used in the implementation of Traffic Vault - *Riak KV*.

Installing the SSL Certificate

By default, Traffic Ops runs as an SSL web server (that is, over HTTPS), and a certificate needs to be installed.

Self-signed Certificate (Development)

28: Example Procedure

```
$ openssl genrsa -des3 -passout pass:x -out localhost.pass.key 2048
Generating RSA private key, 2048 bit long modulus
...
$ openssl rsa -passin pass:x -in localhost.pass.key -out localhost.key
writing RSA key
$ rm localhost.pass.key

$ openssl req -new -key localhost.key -out localhost.csr
You are about to be asked to enter information that will be
  → incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or
  → a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [XX]:US<enter>
State or Province Name (full name) []:CO<enter>
```

(continues on next page)

(continued from previous page)

```
Locality Name (eg, city) [Default City]:Denver<enter>
Organization Name (eg, company) [Default Company Ltd]: <enter>
Organizational Unit Name (eg, section) []: <enter>
Common Name (eg, your name or your server's hostname) []: <enter>
Email Address []: <enter>
```

Please enter the following 'extra' attributes
to be sent with your certificate request

A challenge password []: pass<enter>

An optional company name []: <enter>

```
$ openssl x509 -req -sha256 -days 365 -in localhost.csr -signkey_
↳localhost.key -out localhost.crt
```

Signature ok

subject=/C=US/ST=CO/L=Denver/O=Default Company Ltd

Getting Private key

```
$ sudo cp localhost.crt /etc/pki/tls/certs
```

```
$ sudo cp localhost.key /etc/pki/tls/private
```

```
$ sudo chown trafops:trafops /etc/pki/tls/certs/localhost.crt
```

```
$ sudo chown trafops:trafops /etc/pki/tls/private/localhost.key
```

Certificate from Certificate Authority (Production)

Note: You will need to know the appropriate answers when generating the certificate request file `trafficopss.csr`.

29: Example Procedure

```
$ openssl genrsa -des3 -passout pass:x -out trafficops.pass.key 2048
Generating RSA private key, 2048 bit long modulus
...
$ openssl rsa -passin pass:x -in trafficops.pass.key -out trafficops.
↳key
writing RSA key
$ rm localhost.pass.key
```

Generate the CSR file needed for CA (Certificate Authority) request

30: Example Certificate Signing Request File Generation

```
$ openssl req -new -key trafficops.key -out trafficops.csr
You are about to be asked to enter information that will be_
↳incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or_
↳a DN.
```

(continues on next page)

(continued from previous page)

```
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [XX]: <enter country code>
State or Province Name (full name) []: <enter state or province>
Locality Name (eg, city) [Default City]: <enter locality name>
Organization Name (eg, company) [Default Company Ltd]: <enter
→organization name>
Organizational Unit Name (eg, section) []: <enter organizational unit
→name>
Common Name (eg, your name or your server's hostname) []: <enter server
→'s hostname name>
Email Address []: <enter e-mail address>

Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []: <enter challenge password>
An optional company name []: <enter>
$ sudo cp trafficops.key /etc/pki/tls/private
$ sudo chown trafops:trafops /etc/pki/tls/private/trafficops.key
```

You must then take the output file `trafficops.csr` and submit a request to your CA. Once you get approved and receive your `trafficops.crt` file

31: Certificate Installation

```
sudo cp trafficops.crt /etc/pki/tls/certs
sudo chown trafops:trafops /etc/pki/tls/certs/trafficops.crt
```

If necessary, install the CA (CERTIFICATE AUTHORITY) CERTIFICATE's `.pem` and `.crt` files in `/etc/pki/tls/certs`.

You will need to update `cdn.conf` with any necessary changes.

32: Sample ‘listen’ Line When Path to trafficops.crt and trafficops.key are Known

```
'hypnotoad' => ...
  'listen' => 'https://[::]:443?cert=/etc/pki/tls/certs/trafficops.
→ crt&key=/etc/pki/tls/private/trafficops.key&ca=/etc/pki/tls/certs/
→ localhost.ca&verify=0x00&ciphers=AES128-GCM-SHA256:HIGH:!RC4:!MD5:!
→ aNULL:!EDH:!ED'
  ...
```

Managing Traffic Ops Extensions

Traffic Ops supports “*Check Extensions*”, which are analytics scripts that collect and display information as columns in the table under *Monitor* → *Cache Checks* in Traffic Portal.

See also:

Traffic Ops also supports a more involved type of extension in the form of *Go Plugins*.

Check Extensions

Check Extensions are scripts that, after registering with Traffic Ops, have a column reserved in the *Monitor* → *Cache Checks* view and usually run periodically using *cron(8)*. Each extension is a separate executable located in *\$TO_HOME/bin/checks/* on the Traffic Ops server (though all of the default extensions are written in Perl, this is in *no way* a requirement; they can be any valid executable). The currently registered extensions can be listed by running */opt/traffic_ops/app/bin/extensions -a*. Some extensions automatically registered with the Traffic Ops database (to_extension table) at install time (see *traffic_ops/app/db/seeds.sql*). However, *cron(8)* must still be configured to run these checks periodically. The extensions are called like so:

33: Example Check Extension Call

```
$TO_HOME/bin/checks/<name> -c "{\"base_url\": \"https://<traffic_
→ ops_ip>\", \"check_name\": \"<check_name>\"}" -l <log level>
```



name The basename of the extension executable

traffic_ops_ip The IP address or FQDN of the Traffic Ops server

check_name The name of the check e.g. CDU, CHR, DSCP, MTU, etc...

log_level A whole number between 1 and 4 (inclusive), with 4 being the most verbose. Implementation of this field is optional

It is the responsibility of the check extension script to iterate over the servers it wants to check and post the results. An example script might proceed by logging into the Traffic Ops server using the HTTPS base_url provided on the command line. The script is hard-coded with an authentication token that is also provisioned in the Traffic Ops User database. This token allows

the script to obtain a cookie used in later communications with the Traffic Ops API. The script then obtains a list of all *cache servers* to be polled by accessing *servers*. This list is then iterated, running a command to gather the stats from each server. For some extensions, an HTTP GET request might be made to the ATS *astats* plugin, while for others the server might be pinged, or a command might run over *ssh(1)*. The results are then compiled into a numeric or boolean result and the script submits a POST request containing the result back to Traffic Ops using *servercheck*. A check extension can have a column of 's and 's (CHECK_EXTENSION_BOOL) or a column that shows a number (CHECK_EXTENSION_NUM).

Check Extensions Installed by Default

CDU (Cache Disk Usage) This check shows how much of the available total cache disk is in use. A “warm” *cache server* should show 100.00.

CHR (Cache Hit Ratio) The cache hit ratio for the cache in the last 15 minutes (the interval is determined by the *cron(8)* entry).

DSCP Checks if the returning traffic from the cache has the correct DSCP value as assigned in the *Delivery Service*. (Some routers will overwrite DSCP)

MTU (Maximum Transmission Unit) Checks if the Traffic Ops host (if that is the one running the check) can send and receive 8192B packets to the *ip_address* of the server in the server table.

ORT (Operational Readiness Test) The ORT column shows how many changes the *ORT* script would apply if it was run. The number in this column should be 0 for *cache servers* that do not have updates pending.

10G Is the *ip_address* (the main IPv4 address) from the server table ping-able?

ILO (Integrated Lights-Out) Is the *ilo_ip_address* (the lights-out-management IPv4 address) from the server table ping-able?

10G6 Is the *ip6_address* (the main IPv6 address) from the server table ping-able?

FQDN Is the FQDN (the concatenation of *host_name* and *.* and *domain_name* from the server table) ping-able?

RTR (Responds to Traffic Router) Checks the state of each *cache server* as perceived by all Traffic Monitors (via Traffic Router). This extension asks each Traffic Router for the state of the *cache server*. A check failure is indicated if one or more monitors report an error for a *cache server*. A *cache server* is only marked as good if all reports are positive.

Note: This is a pessimistic approach, opposite of how Traffic Monitor marks a *cache server* as up, i.e. “the optimistic approach”.

Example Cron File

The `cron(8)` file should be edited by running `crontab(1)` as the `traffops` user, or with `sudo(8)`. You may need to adjust the path to your `$TO_HOME` to match your system. Edit `$TO_USER` and `$TO_PASS` to match `ORT` input parameters.

34: Example Cron File

```
PERL5LIB=/opt/traffic_ops/app/local/lib/perl5:/opt/traffic_ops/app/lib

# IPv4 ping examples - The 'select: ["hostName","domainName"]' works but,
→ if you want to check DNS resolution use FQDN.
*/15 * * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
→ "base_url\: \"https://localhost\", \"check_name\: \"10G\", \
→ "select\: [\"hostName\", \"domainName\"]}" >> /var/log/traffic_ops/
→ extensionCheck.log 2>&1
*/15 * * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
→ "base_url\: \"https://localhost\", \"check_name\: \"10G\", \
→ "select\: \"ipAddress\"" >> /var/log/traffic_ops/extensionCheck.
→ log 2>&1
*/15 * * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
→ "base_url\: \"https://localhost\", \"check_name\: \"10G\", \"name\
→ \: \"IPv4 Ping\", \"select\: \"ipAddress\", \"syslog_facility\: \
→ "local0\"" > /dev/null 2>&1

# IPv6 ping examples
*/15 * * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
→ "base_url\: \"https://localhost\", \"check_name\: \"10G6\", \"name\
→ \: \"IPv6 Ping\", \"select\: \"ip6Address\", \"syslog_facility\: \
→ "local0\"" >/dev/null 2>&1
*/15 * * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
→ "base_url\: \"https://localhost\", \"check_name\: \"10G6\", \
→ "select\: \"ip6Address\"" >> /var/log/traffic_ops/extensionCheck.
→ log 2>&1

# iLO ping
18 * * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
→ "base_url\: \"https://localhost\", \"check_name\: \"ILO\", \
→ "select\: \"iloIpAddress\"" >> /var/log/traffic_ops/extensionCheck.
→ log 2>&1
18 * * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
→ "base_url\: \"https://localhost\", \"check_name\: \"ILO\", \"name\
→ \: \"ILO ping\", \"select\: \"iloIpAddress\", \"syslog_facility\: \
→ "local0\"" >/dev/null 2>&1

# MTU ping
45 0 * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
→ "base_url\: \"https://localhost\", \"check_name\: \"MTU\", \
→ "select\: \"ipAddress\"" >> /var/log/traffic_ops/extensionCheck.
→ log 2>&1
```

(continues on next page)

(continued from previous page)

```

45 0 * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"MTU\", \
↳ "select\: \"ip6Address\"}" >> /var/log/traffic_ops/extensionCheck.
↳ log 2>&1
45 0 * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"MTU\", \"name\
↳ \": \"Max Trans Unit\", \"select\: \"ipAddress\", \"syslog_facility\
↳ \": \"local0\"}" > /dev/null 2>&1
45 0 * * * root /opt/traffic_ops/app/bin/checks/ToPingCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"MTU\", \"name\
↳ \": \"Max Trans Unit\", \"select\: \"ip6Address\", \"syslog_facility\
↳ \": \"local0\"}" > /dev/null 2>&1

# FQDN
27 * * * * root /opt/traffic_ops/app/bin/checks/ToFQDNCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"FQDN\"\" >> /
↳ var/log/traffic_ops/extensionCheck.log 2>&1
27 * * * * root /opt/traffic_ops/app/bin/checks/ToFQDNCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"FQDN\", \"name\
↳ \": \"DNS Lookup\", \"syslog_facility\: \"local0\"}" > /dev/null 2>&1

# DSCP
36 * * * * root /opt/traffic_ops/app/bin/checks/ToDSCPCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"DSCP\", \"cms_
↳ interface\: \"eth0\"}" >> /var/log/traffic_ops/extensionCheck.log 2>
↳ &1
36 * * * * root /opt/traffic_ops/app/bin/checks/ToDSCPCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"DSCP\", \"name\
↳ \": \:term:Delivery Service\", \"cms_interface\: \"eth0\", \
↳ "syslog_facility\: \"local0\"}" > /dev/null 2>&1

# RTR
10 * * * * root /opt/traffic_ops/app/bin/checks/ToRTRCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"RTR\"}" >> /
↳ var/log/traffic_ops/extensionCheck.log 2>&1
10 * * * * root /opt/traffic_ops/app/bin/checks/ToRTRCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"RTR\", \"name\
↳ \": \"Content Router Check\", \"syslog_facility\: \"local0\"}" > /
↳ dev/null 2>&1

# CHR
*/15 * * * * root /opt/traffic_ops/app/bin/checks/ToCHRCheck.pl -c "{\
↳ "base_url\: \"https://localhost\", \"check_name\: \"CHR\"}" >> /
↳ var/log/traffic_ops/extensionCheck.log 2>&1

# CDU

```

(continues on next page)

(continued from previous page)

```
20 * * * * root /opt/traffic_ops/app/bin/checks/ToCDUCheck.pl -c "{\
→"base_url\: \"https://localhost\", \"check_name\: \"CDU\"}" >> /
→var/log/traffic_ops/extensionCheck.log 2>&1

# ORT
40 * * * * ssh_key_edge_user /opt/traffic_ops/app/bin/checks/
→ToORTCheck.pl -c "{\"base_url\: \"https://localhost\", \"check_name\
→\": \"ORT\", \"to_user\:\"$TO_USER\", \"to_pass\:\"$TO_PASS\"}" >>
→ /var/log/traffic_ops/extensionCheck.log 2>&1
40 * * * * ssh_key_edge_user /opt/traffic_ops/app/bin/checks/
→ToORTCheck.pl -c "{\"base_url\: \"https://localhost\", \"check_name\
→\": \"ORT\", \"name\: \"Operational Readiness Test\", \"syslog_
→facility\: \"local0\", \"to_user\:\"$TO_USER\", \"to_pass\:\"$TO_
→PASS\"}" > /dev/null 2>&1
```

3.1.2 Environment Creation

Apache Traffic Control is a complex set of components to construct a functional CDN. To help users get started more quickly, two paths exist to help based on the audience and needs. These tools are optional and administrators may use whatever means are at their disposal to perform their deployments.

CDN-in-a-Box (CIAB)

Audience for CIAB

- Developers who need a local full-stack to aid in development using Docker
- A common platform for developers to write tests against and executed by a CI system
- New users who are learning how a CDN using Apache Traffic Control works
- Functional demonstrations

CDN in a Box

“CDN in a Box” is a name given to the time-honored tradition of new Traffic Control developers/potential users attempting to set up their own, miniature CDN to just see how it all fits together. Historically, this has been a nightmare of digging through leftover `virsh` scripts and manually configuring pretty hefty networking changes (don’t even get me started on DNS) and just generally having a bad time. For a few years now, different people had made it to various stages of merging the project into Docker for ease of networking, but certain constraints hampered progress - until now. The project has finally reached a working state, and now getting a mock/test CDN running can be a very simple task (albeit rather time-consuming).

Getting Started

Because it runs in Docker, the only true prerequisites are:

- Docker version \geq 17.05.0-ce
- Docker Compose¹ version \geq 1.9.0

Building

The CDN in a Box directory is found within the Traffic Control repository at `infrastructure/cdn-in-a-box/`. CDN in a Box relies on the presence of pre-built `component.rpm` files for the following Traffic Control components:

- Traffic Monitor - at `infrastructure/cdn-in-a-box/traffic_monitor/traffic_monitor.rpm`
- Traffic Ops - at `infrastructure/cdn-in-a-box/traffic_ops/traffic_ops.rpm`
- Traffic Portal - at `infrastructure/cdn-in-a-box/traffic_portal/traffic_portal.rpm`
- Traffic Router - at `infrastructure/cdn-in-a-box/traffic_router/traffic_router.rpm` - also requires an Apache Tomcat RPM at `infrastructure/cdn-in-a-box/traffic_router/tomcat.rpm`

Note: These can also be specified via the `RPM` variable to a direct Docker build of the component - with the exception of Traffic Router, which instead accepts `JDK8_RPM` to specify a Java Development Kit RPM, `TRAFFIC_ROUTER_RPM` to specify a Traffic Router RPM, and `TOMCAT_RPM` to specify an Apache Tomcat RPM.

These can all be supplied manually via the steps in *Building Traffic Control* (for Traffic Control component RPMs) or via some external source. Alternatively, the `infrastructure/cdn-in-a-box/Makefile` file contains recipes to build all of these - simply run `make(1)` from the `infrastructure/cdn-in-a-box/` directory. Once all RPM dependencies have been satisfied, run `docker-compose build --parallel` from the `infrastructure/cdn-in-a-box/` directory to construct the images needed to run CDN in a Box.

Tip: If you have gone through the steps to *Build the RPMs Natively*, you can run `make native` instead of `make` to build the RPMs quickly. Another option is running `make -j4` to build 4 components at once, if your computer can handle it.

Tip: When updating CDN-in-a-Box, there is no need to remove old images before building new ones. Docker detects which files are updated and only reuses cached layers that have not

¹ It is perfectly possible to build and run all containers without Docker Compose, but it's not recommended and not covered in this guide.

changed.

By default, CDN in a Box will be based on CentOS 8. To base CDN in a Box on CentOS 7, set the `RHEL_VERSION` environment variable to 7 (for CDN in a Box, it defaults to 8):

35: Building CDN in a Box to run CentOS 7 instead of CentOS 8

```
export RHEL_VERSION=7
make # Builds RPMs for CentOS 7
docker-compose build --parallel # Builds CentOS 7 CDN in a Box images
```

Usage

In a typical scenario, if the steps in *Building* have been followed, all that's required to start the CDN in a Box is to run `docker-compose up` - optionally with the `-d` flag to run without binding to the terminal - from the `infrastructure/cdn-in-a-box/` directory. This will start up the entire stack and should take care of any needed initial configuration. The services within the environment are by default not exposed locally to the host. If this is the desired behavior when bringing up CDN in a Box the command `docker-compose -f docker-compose.yml -f docker-compose.expose-ports.yml up` should be run. The ports are configured within the `infrastructure/cdn-in-a-box/docker-compose.expose-ports.yml` file, but the default ports are shown in *Service Info*. Some services have credentials associated, which are totally configurable in *variables.env*.

Table 49: Service Info

Service	Ports exposed and their usage	Username	Password
DNS	DNS name resolution on 9353	N/A	N/A
Edge Tier Cache	Apache Trafficserver 8.1 HTTP caching reverse proxy on port 9000	N/A	N/A
Mid Tier Cache	Apache Trafficserver 8.1 HTTP caching forward proxy on port 9100	N/A	N/A
Second Mid-Tier Cache (parent of the first Mid-Tier Cache)	Apache Trafficserver 8.1 HTTP caching forward proxy on port 9100	N/A	N/A
Mock Origin Server	Example web page served on port 9200	N/A	N/A
SMTP Server	Passwordless, cleartext SMTP server on port 25 (no relay) Web interface exposed on port 4443 (port 443 in the container)	N/A	N/A
Traffic Monitor	Web interface and API on port 80	N/A	N/A
Traffic Ops	API endpoints on port 6443	TO_ADMIN_USER in <i>variables.env</i>	TO_ADMIN_PASSWORD in <i>variables.env</i>
Traffic Ops PostgreSQL Database	PostgresQL connections accepted on port 5432 (database name: DB_NAME in <i>variables.env</i>)	DB_USER in <i>variables.env</i>	DB_USER_PASS in <i>variables.env</i>
Traffic Portal	Web interface on 443 (Javascript required)	TO_ADMIN_USER in <i>variables.env</i>	TO_ADMIN_PASSWORD in <i>variables.env</i>
Traffic Router	Web interfaces on ports 3080 (HTTP) and 3443 (HTTPS), with a DNS service on 53 and an API on 3333 (HTTP) and 2222 (HTTPS)	N/A	N/A
Traffic Vault	Riak key-value store on port 8010	TV_ADMIN_USER in <i>variables.env</i>	TV_ADMIN_PASSWORD in <i>variables.env</i>
Traffic Stats	N/A	N/A	N/A
Traffic Stats Influxdb	Influxdbd connections accepted on port 8086 (database name: cache_stats, daily_stats and deliveryservice_stats)	INFLUXDB_ADMIN_USER in <i>variables.env</i>	INFLUXDB_ADMIN_PASSWORD in <i>variables.env</i>

See also:

Traffic Router API and *Traffic Monitor APIs*

While the components may be interacted with by the host using these ports, the true operation of the CDN can only truly be seen from within the Docker network. To see the CDN in action, connect to a container within the CDN in a Box project and use cURL to request the URL `http://video.demo1.mycdn.ciab.test` which will be resolved by the DNS container to the IP of the Traffic Router, which will provide a 302 FOUND response pointing to the Edge-

Tier cache. A typical choice for this is the “enroller” service, which has a very nuanced purpose not discussed here but already has the `curl(1)` command line tool installed. For a more user-friendly interface into the CDN network, see *VNC Server*.

To test the demo1 Delivery Service:

36: Example Command to See the CDN in Action

```
sudo docker-compose exec enroller curl -L "http://video.demo1.mycdn.
→ciab.test"
```

To test the `foo.kabletown.net`. Federation:

37: Query the Federation CNAME using the Delivery Service hostname

```
sudo docker-compose exec trafficrouter dig +short @trafficrouter.infra.
→ciab.test -t CNAME video.demo2.mycdn.ciab.test
```

```
# Expected response:
foo.kabletown.net.
```

When the CDN is to be shut down, it is often best to do so using `sudo docker-compose down -v` due to the use of shared volumes in the system which might interfere with a proper initialization upon the next run.

Readiness Check

In order to check the “readiness” of your CDN, you can optionally start the Readiness Container, which will continually `curl(1)` the *Delivery Services* in your CDN until they all return successful responses before exiting successfully.

38: Example Command to Run the Readiness Container

```
sudo docker-compose -f docker-compose.readiness.yml up
```

Integration Tests

There also exist TP and TO integration tests containers. Both of these containers assume that CDN in a Box is already running on the local system.

39: Running TP Integration Tests

```
sudo docker-compose -f docker-compose.traffic-portal-test.yml up
```

40: Running TO Integration Tests

```
sudo docker-compose -f docker-compose.traffic-ops-test.yml up
```

Note: If all CDN in a Box containers are started at once (example: `docker-compose -f docker-compose.yml -f docker-compose.traffic-ops-test.yml up -d edge enroller dns db smtp trafficops trafficvault integration`), the *Enroller* initial data load is skipped to prevent data conflicts with the *Traffic Ops API tests fixtures*.

variables.env

```
TV_AES_KEY_LOCATION=/opt/traffic_ops/app/conf/aes.key
# Unset TV_BACKEND to use riak as the traffic_vault backend and run
# the traffic_vault image from the optional directory
TV_BACKEND=postgres
TLD_DOMAIN=ciab.test
INFRA_SUBDOMAIN=infra
CDN_NAME=CDN-in-a-Box
CDN_SUBDOMAIN=mycdn
DS_HOSTS='demo1 demo2 demo3'
FEDERATION_CNAME=foo.kabletown.net.
X509_CA_NAME=CIAB-CA
X509_CA_COUNTRY=US
X509_CA_STATE=Colorado
X509_CA_CITY=Denver
X509_CA_COMPANY=NotComcast
X509_CA_ORG=CDN-in-a-Box
X509_CA_ORGUNIT=CDN-in-a-Box
X509_CA_EMAIL=no-reply@infra.ciab.test
X509_CA_DIGEST=sha256
X509_CA_DURATION_DAYS=365
X509_CA_KEYTYPE=rsa
X509_CA_KEYSIZE=4096
X509_CA_UMASK=0000
X509_CA_DIR=/shared/ssl
X509_CA_PERSIST_DIR=/ca
X509_CA_PERSIST_ENV_FILE=/ca/environment
X509_CA_ENV_FILE=/shared/ssl/environment
DB_NAME=traffic_ops
TV_DB_NAME=traffic_vault
DB_PORT=5432
DB_SERVER=db
TV_DB_SERVER=db
```

(continues on next page)

(continued from previous page)

```
DB_USER_PASS=twelve
DB_USER=traffic_ops
TV_DB_USER=traffic_vault
TV_DB_USER_PASS=twelve
TV_DB_PORT=5432
DNS_SERVER=dns
DBIC_TRACE=0
ENROLLER_HOST=enroller
PGPASSWORD=twelve
POSTGRES_PASSWORD=twelve
EDGE_HOST=edge
INFLUXDB_HOST=influxdb
INFLUXDB_PORT=8086
INFLUXDB_ADMIN_USER=influxadmin
INFLUXDB_ADMIN_PASSWORD=influxadminpassword
GRAFANA_ADMIN_USER=grafanaadmin
GRAFANA_ADMIN_PASSWORD=grafanaadminpassword
GRAFANA_PORT=443
MID_01_HOST=mid-01
MID_02_HOST=mid-02
ORIGIN_HOST=origin
SMTP_HOST=smtp
SMTP_PORT=25
TM_HOST=trafficmonitor
TM_PORT=80
TM_EMAIL=tmonitor@cdn.example.com
TM_PASSWORD=jhds1vhdfsuklvfhsuvlhs
TM_USER=tmon
TM_LOG_EVENT=stdout
TM_LOG_ERROR=stdout
TM_LOG_WARNING=stdout
TM_LOG_INFO=stdout
TM_LOG_DEBUG=stdout
TO_ADMIN_PASSWORD=twelve12
TO_ADMIN_USER=admin
TO_ADMIN_FULL_NAME='James Cole'
# Set ENROLLER_DEBUG_ENABLE to true`to debug the enroller with Delve
ENROLLER_DEBUG_ENABLE=false
# To debug a t3c component with Delve in the `edge` container, set T3C_
→DEBUG_COMPONENT_EDGE to t3c-apply, t3c-check, t3c-check-refs, t3c-
→check-reload, t3c-diff, t3c-generate, t3c-request, or t3c-update
T3C_DEBUG_COMPONENT_EDGE=none
# To debug a t3c component with Delve in the `mid-01` container, set
→T3C_DEBUG_COMPONENT_MID_01 to t3c-apply, t3c-check, t3c-check-refs,
→t3c-check-reload, t3c-diff, t3c-generate, t3c-request, or t3c-update
T3C_DEBUG_COMPONENT_MID_01=none
```

(continues on next page)

(continued from previous page)

```
# To debug a t3c component with Delve in the `mid-02` container, set
→T3C_DEBUG_COMPONENT_MID_02 to t3c-apply, t3c-diff, t3c-generate, t3c-
→request, t3c-update, or t3c-verify
T3C_DEBUG_COMPONENT_MID_02=none
# Set TM_DEBUG_ENABLE to true`to debug Traffic Monitor with Delve
TM_DEBUG_ENABLE=false
# Set TO_DEBUG_ENABLE to true`to debug Traffic Ops with Delve
TO_DEBUG_ENABLE=false
# Set TR_DEBUG_ENABLE to true`to debug Traffic Router with with JPDA
TR_DEBUG_ENABLE=false
# Set TS_DEBUG_ENABLE to true`to debug Traffic Stats with Delve
TS_DEBUG_ENABLE=false
TO_EMAIL=cdnadmin@example.com
TO_HOST=trafficops
TO_PORT=443
TO_LOG_ERROR=/var/log/traffic_ops/error.log
TO_LOG_WARNING=/var/log/traffic_ops/warning.log
TO_LOG_INFO=/var/log/traffic_ops/info.log
#TO_LOG_DEBUG=/var/log/traffic_ops/debug.log
TO_LOG_DEBUG=/dev/null
TO_LOG_EVENT=/var/log/traffic_ops/event.log
TP_HOST=trafficportal
TP_EMAIL=tp@cdn.example.com
TR_HOST=trafficrouter
TR_DNS_PORT=53
TR_HTTP_PORT=80
TR_HTTPS_PORT=443
TR_API_PORT=3333
TP_PORT=443
TS_EMAIL=tstats@cdn.example.com
TS_HOST=trafficstats
TS_PASSWORD=trafficstatspassword
TS_USER=tstats
TV_HOST=trafficvault
TV_USER=tvault
TV_PASSWORD=mwL5GP6Ghu_uJpkfjfiBmii3l9vfgLl0
TV_EMAIL=tvault@cdn.example.com
TV_ADMIN_USER=admin
TV_ADMIN_PASSWORD=riakAdmin
TV_RIAK_USER=riakuser
TV_RIAK_PASSWORD=riakPassword
TV_INT_PORT=8087
TV_HTTP_PORT=8098
TV_HTTPS_PORT=8088
ENROLLER_DIR=/shared/enroller
AUTO_SNAPQUEUE_ENABLED=true
```

(continues on next page)

(continued from previous page)

```
AUTO_SNAPQUEUE_SERVERS=trafficops,trafficmonitor,trafficrouter,edge,
↪mid-01,mid-02
AUTO_SNAPQUEUE_POLL_INTERVAL=2
AUTO_SNAPQUEUE_ACTION_WAIT=2
```

Note: While these port settings can be changed without hampering the function of the CDN in a Box system, note that changing a port without also changing the matching port-mapping in `infrastructure/cdn-in-a-box/docker-compose.yml` for the affected service *will* make it unreachable from the host.

X.509 SSL/TLS Certificates

All components in Apache Traffic Control utilize SSL/TLS secure communications by default. For SSL/TLS connections to properly validate within the “CDN in a Box” container network a shared self-signed X.509 Root CA is generated at the first initial startup. An X.509 Intermediate CA is also generated and signed by the Root CA. Additional “wildcard” certificates are generated/signed by the Intermediate CA for each container service and `demo1`, `demo2`, and `demo3` *Delivery Services*. All certificates and keys are stored in the `ca` host volume which is located at `infrastructure/cdn-in-a-box/traffic_ops/ca`⁴.

Table 50: Self-Signed X.509 Certificate List

Filename	Description	X.509 CN/SAN
CIAB-CA-root.crt	Shared Root CA Certificate	N/A
CIAB-CA-intr.crt	Shared Intermediate CA Certificate	N/A
CIAB-CA-fullchain.crt	Shared CA Certificate Chain Bundle ⁵	N/A
infra.ciab.test.crt	Infrastructure Certificate	<code>prefix.infra.ciab.test</code>
demo1.mycdn.ciab.test.crt	Demo1 <i>Delivery Service</i> Certificate	<code>prefix.demo1.mycdn.ciab.test</code>
demo2.mycdn.ciab.test.crt	Demo2 <i>Delivery Service</i> Certificate	<code>prefix.demo2.mycdn.ciab.test</code>
demo3.mycdn.ciab.test.crt	Demo3 <i>Delivery Service</i> Certificate	<code>prefix.demo3.mycdn.ciab.test</code>

⁴ The `ca` volume is not purged with normal `docker volume` commands. This feature is by design to allow the existing shared SSL certificate to be trusted at the system level across restarts. To re-generate all SSL certificates and keys, remove the `infrastructure/cdn-in-a-box/traffic_ops/ca` directory before startup.

⁵ The full chain bundle is a file that contains both the Root and Intermediate CA certificates.

Trusting the Certificate Authority

For developer and testing use-cases, it may be necessary to have full x509 CA validation by HTTPS clients⁶⁷. For x509 validation to work properly, the self-signed x509 CA certificate must be trusted either at the system level or by the client application itself.

Note: HTTP Client applications such as Chromium, Firefox, *curl(1)*, and *wget(1)* can also be individually configured to trust the CA certificate. Review each program's respective documentation for instructions.

Importing the CA Certificate on OSX

1. Copy the CIAB root and intermediate CA certificates from `infrastructure/cdn-in-a-box/traffic_ops/ca/` to the Mac.
2. Double-click the CIAB root CA certificate to open it in Keychain Access.
3. The CIAB root CA certificate appears in login.
4. Copy the CIAB root CA certificate to System.
5. Open the CIAB root CA certificate, expand *Trust*, select *Use System Defaults*, and save your changes.
6. Reopen the CIAB root CA certificate, expand *Trust*, select *:guilabel: 'Always Trust*, and save your changes.
7. Delete the CIAB root CA certificate from login.
8. Repeat the previous steps with the Intermediate CA certificate to import it as well
9. Restart all HTTPS clients (browsers, etc).

Importing the CA certificate on Windows

1. Copy the CIAB root CA and intermediate CA certificates from `infrastructure/cdn-in-a-box/traffic_ops/ca/` to Windows filesystem.
2. As Administrator, start the Microsoft Management Console.
3. Add the Certificates snap-in for the computer account and manage certificates for the local computer.
4. Import the CIAB root CA certificate into *Trusted Root Certification Authorities* → *Certificates*.
5. Import the CIAB intermediate CA certificate into *Trusted Root Certification Authorities* → *Certificates*.

⁶ All containers within CDN-in-a-Box start up with the self-signed CA already trusted.

⁷ The 'demo1' *Delivery Service* X509 certificate is automatically imported into Traffic Vault on startup.

6. Restart all HTTPS clients (browsers, etc).

Importing the CA certificate on CentOS 8 (Linux)

1. Copy the CIAB full chain CA certificate bundle from `infrastructure/cdn-in-a-box/traffic_ops/ca/CIAB-CA-fullchain.crt` to path `/etc/pki/ca-trust/source/anchors/`.
2. Run `update-ca-trust-extract` as the root user or with `sudo(8)`.
3. Restart all HTTPS clients (browsers, etc).

Importing the CA certificate on Ubuntu (Linux)

1. Copy the CIAB full chain CA certificate bundle from `infrastructure/cdn-in-a-box/traffic_ops/ca/CIAB-CA-fullchain.crt` to path `/usr/local/share/ca-certificates/`.
2. Run `update-ca-certificates` as the root user or with `sudo(8)`.
3. Restart all HTTPS clients (browsers, etc).

Advanced Usage

This section will be amended as functionality is added to the CDN in a Box project.

The Enroller

The “enroller” began as an efficient way for Traffic Ops to be populated with data as CDN in a Box starts up. It connects to Traffic Ops as the “admin” user and processes files placed in the docker volume shared between the containers. The enroller watches each directory within the `/shared/enroller` directory for new `filename.json` files to be created there. These files must follow the format outlined in the API guide for the POST method for each data type, (e.g. for a region, follow the guidelines for `POST api/2.0/regions`). Of note, the enroller does not require fields that reference database ids for other objects within the database.

--dir directory

Base directory to watch for data. Mutually exclusive with `--http`.

--http port

Act as an HTTP server for POST requests on this port. Mutually exclusive with `--dir`.

--started filename

The name of a file which will be created in the `--dir` directory when given, indicating service was started (default: “enroller-started”).

The enroller runs within CDN in a Box using `--dir` which provides the above behavior. It can also be run using `--http` to instead have it listen on the indicated port. In this case,

it accepts only POST requests with the JSON provided in the request payload, e.g. `curl -X POST https://enroller/api/2.0/regions -d @newregion.json`. CDN in a Box does not currently use this method, but may be modified in the future to avoid using the shared volume approach.

Auto Snapshot/Queue-Updates

An automatic *Snapshot* of the current Traffic Ops CDN configuration/topology will be performed once the “enroller” has finished loading all of the data and a minimum number of servers have been enrolled. To enable this feature, set the boolean `AUTO_SNAPQUEUE_ENABLED` to `true`⁸. The *Snapshot* and *Queue Updates* actions will not be performed until all servers in `AUTO_SNAPQUEUE_SERVERS` (comma-delimited string) have been enrolled. The current enrolled servers will be polled every `AUTO_SNAPQUEUE_POLL_INTERVAL` seconds, and each action (*Snapshot* and *Queue Updates*) will be delayed `AUTO_SNAPQUEUE_ACTION_WAIT` seconds⁹.

Mock Origin Service

The default “origin” service container provides a basic static file HTTP server as the central repository for content. Additional files can be added to the origin root content directory located at `infrastructure/cdn-in-a-box/origin/content`. To request content directly from the origin directly and bypass the CDN:

- Origin Service URL: <http://origin.infra.ciab.test/index.html>
- Docker Host: <http://localhost:9200/index.html>

Optional Containers

All optional containers that are not part of the core CDN-in-a-Box stack are located in the `infrastructure/cdn-in-a-box/optional` directory.

- `infrastructure/cdn-in-a-box/optional/docker-compose.NAME.yml`
- `infrastructure/cdn-in-a-box/optional/NAME/Dockerfile`

Multiple optional containers may be combined by using a shell alias:

41: Starting Optional Containers with an Alias

```
# From the infrastructure/cdn-in-a-box directory
# (Assuming the names of the optional services are stored in the_
→ `NAME1` and `NAME2` environment variables)
alias mydc="docker-compose -f $PWD/docker-compose.yml -f $PWD/optional/
→ docker-compose.$NAME1.yml -f $PWD/optional/docker-compose.$NAME2.yml
→ "
```

(continues on next page)

⁸ Automatic *Snapshot/Queue Updates* is enabled by default in `variables.env`.

⁹ Server poll interval and delay action wait are defaulted to a value of 2 seconds.

(continued from previous page)

```
docker volume prune -f
mydc build
mydc up
```

VNC Server

The TightVNC optional container provides a basic lightweight window manager (fluxbox), Firefox browser, xterm, and a few other utilities within the CDN-In-A-Box “tcnet” bridge network. This can be very helpful for quick demonstrations of CDN-in-a-Box that require the use of real container network FQDNs and full X.509 validation.

1. Download and install a VNC client. TightVNC client is preferred as it supports window resizing, host-to-vnc copy/pasting, and optimized frame buffer compression.
2. Set your VNC console password by adding the VNC_PASSWD environment variable to `infrastructure/cdn-in-a-box/variables.env`. The password needs to be at least six characters long. The default password is randomized for security.
3. Start up CDN-in-a-Box stack. It is recommended that this be done using a custom bash alias

42: CIAB Startup Using Bash Alias

```
# From infrastructure/cdn-in-a-box
alias mydc="docker-compose "` \
    "-f $PWD/docker-compose.yml "` \
    "-f $PWD/docker-compose.expose-ports.yml "` \
    "-f $PWD/optional/docker-compose.vnc.yml "` \
    "-f $PWD/optional/docker-compose.vnc.expose-ports.yml"
docker volume prune -f
mydc build
mydc kill
mydc rm -fv
mydc up
```

4. Connect with a VNC client to localhost port 5909.
5. When Traffic Portal becomes available, the Firefox within the VNC instance will subsequently be started.
6. An xterm with bash shell is also automatically spawned and minimized for convenience.

Socks Proxy

Dante's socks proxy is an optional container that can be used to provide browsers and other clients the ability to resolve DNS queries and network connectivity directly on the tcnet bridged interface. This is very helpful when running the CDN-In-A-Box stack on OSX/Windows docker host that lacks network bridge/IP-forward support. Below is the basic procedure to enable the Socks Proxy support for CDN-in-a-Box:

1. Start the CDN-in-a-Box stack at least once so that the x.509 self-signed CA is created.
2. On the host, import and Trust the CA for your target Operating System. See [Trusting the Certificate Authority](#)
3. On the host, using either Firefox or Chromium, download the [FoxyProxy browser plugin](#) which enables dynamic proxy support via URL regular expression
4. Once FoxyProxy is installed, click the Fox icon on the upper right hand of the browser window, select *Options*
5. Once in Options Dialog, Click *Add New Proxy* and navigate to the General tab:
6. Fill in the General tab according to the table

Table 51: General Tab Values

Name	Value
Proxy Name	CIAB
Color	Green

7. Fill in the Proxy Details tab according to the table

Table 52: Proxy Details Tab Values

Name	Value
Manual Proxy Configuration	CIAB
Host or IP Address	localhost
Port	9080
Socks Proxy	checked
Socks V5	selected

8. Go to URL Patterns tab, click Add New Pattern, and fill out form according to

Table 53: URL Patters Tab Values

Name	Value
Pattern Name	CIAB Pattern
URL Pattern	*.test/*
Whitelist	selected
Wildcards	selected

9. Enable dynamic 'pre-defined and patterns' mode by clicking the fox icon in the upper right of the browser. This mode only forwards URLs that match the wildcard *.test/*

to the Socks V5 proxy.

10. On the docker host start up CDN-in-a-Box stack. It is recommended that this be done using a custom bash alias

43: CIAB Startup Using Bash Alias

```
# From infrastructure/cdn-in-a-box
alias mydc="docker-compose -f $PWD/docker-compose.yml -f
↪$PWD/optional/docker-compose.socksproxy.yml"
docker volume prune -f
mydc build
mydc kill
mydc rm -fv
mydc up
```

11. Once the CDN-in-a-box stack has started, use the aforementioned browser to access Traffic Portal via the socks proxy on the docker host.

See also:

The official [Docker Compose documentation CLI reference](#) for complete instructions on how to pass service definition files to the `docker-compose` executable.

Static Subnet

Since `docker-compose` will randomly create a subnet and it has a chance to conflict with your network environment, using static subnet is a good choice.

44: CIAB Startup with Static Subnet

```
# From the infrastructure/cdn-in-a-box directory
alias mydc="docker-compose -f $PWD/docker-compose.yml -f $PWD/optional/
↪docker-compose.static-subnet.yml"
docker volume prune -f
mydc build
mydc up
```

VPN Server

This container provides an OpenVPN service. It's primary use is to allow users and developers to easily access CIAB network.

How to use it

1. It is recommended that this be done using a custom bash alias.

45: CIAB Startup with VPN

```
# From infrastructure/cdn-in-a-box
alias mydc="docker-compose -f $PWD/docker-compose.yml -f
↪$PWD/docker-compose.expose-ports.yml -f $PWD/optional/
↪docker-compose.vpn.yml -f $PWD/optional/docker-compose.
↪vpn.expose-ports.yml"
mydc down -v
mydc build
mydc up
```

2. All certificates, keys, and client configuration are stored at `infrastructure/cdn-in-a-box/optional/vpn/vpnca`. You just simply change `REALHOSTIP` and `REALPORT` of `client.ovpn` to fit your environment, and then you can use it to connect to this OpenVPN server.

The proposed VPN client

On Linux, we suggest `openvpn`. On most Linux distributions, this will also be the name of the package that provides it.

46: Install openvpn on ubuntu/debian

```
apt-get update && apt-get install -y openvpn
```

On OSX, it only works with brew installed `openvpn` client, not the *OpenVPN GUI client*.

47: Install openvpn on OSX

```
brew install openvpn
```

If you want a GUI version of VPN client, we recommend [Tunnelblick](#).

Private Subnet for Routing

Since `docker-compose` randomly creates a subnet, this container prepares 2 default private subnets for routing:

- 172.16.127.0/255.255.240.0
- 10.16.127.0/255.255.240.0

The subnet that will be used is determined automatically based on the subnet prefix. If the subnet prefix which `docker-compose` selected is 192. or 10., this container will select 172.16.127.0/255.255.240.0 for its routing subnet. Otherwise, it selects 10.16.127.0/255.255.240.0.

Of course, you can decide which routing subnet by supplying the environment variables `PRIVATE_NETWORK` and `PRIVATE_NETMASK`.

Pushed Settings

Pushed settings are shown as follows:

- DNS
- A routing rule for the CIAB subnet

Note: It will not change your default gateway. That means apart from CDN in a Box traffic and DNS requests, all other traffic will use the standard interface bound to the default gateway.

Grafana

This container provides a Grafana service. It's an open platform for analytics and monitoring. This container has prepared necessary *datasources* and *scripted dashboards*. Please refer to [Configuring Grafana](#) for detailed Settings.

How to start it

It is recommended that this be done using a custom bash alias.

48: CIAB Startup with Grafana

```
# From infrastructure/cdn-in-a-box
alias mydc="docker-compose -f $PWD/docker-compose.yml -f $PWD/optional/
↪docker-compose.grafana.yml -f $PWD/optional/docker-compose.grafana.
↪expose-ports.yml"
mydc down -v
mydc build
mydc up
```

Apart from start Grafana, the above commands also expose port 3000 for it.

Check the charts

There are some *scripted dashboards* can show beautiful charts. You can display different charts by passing in different *query string*

- `https://<grafanaHost>/dashboard/script/traffic_ops_cachegroup.js?which=`. The query parameter *which* in this particular URL should be the **cachegroup**. Take CIAB as an example, it can be filled in with **CDN_in_a_Box_Edge** or **CDN_in_a_Box_Edge**.
- `https://<grafanaHost>/dashboard/script/traffic_ops_deliveryservice.js?which=`. The query parameter *which* in this particular URL should be the **xml_id** of the desired Delivery Service.
- `https://<grafanaHost>/dashboard/script/traffic_ops_server.js?which=`. The query parameter *which* in this particular URL should be the **hostname** (not **FQDN**). It can be filled in with **edge** or **mid** in CIAB.

Debugging

See *Debugging inside CDN-in-a-Box*.

Ansible-based Lab Deployment

Audience for Ansible-based Lab Deployment

- DevOps engineers building more production-like lab environments
- DevOps engineers building an initial greenfield production environment
- Developers who need test environments that cannot be modeled on local resources

Ansible-based Lab Creation

The scope of the Ansible work presented is a set of generic roles an implementor could use to expose the common installation and configuration tasks of each component. Additionally, it provides some suggestions and sample scaffolding on how to divide the full end-to-end lab construction.

Why Ansible?

There are many excellent tools to facilitate application installation and configuration. Ansible is a leading open-source tool in this marketplace backed by major corporate sponsorship and adoption. Most importantly it facilitates the abstractions desired without creating technological conflicts with existing infrastructure management solutions.

What about Security?

Each organization should review the instructions being performed in each Ansible playbook to determine if they satisfy their security requirements. Additionally, each implementor should select and implement their secret store of choice such as the built-in `ansible-vault` or a more advanced secret-as-a-service solution for any sensitive variables.

Lab Implementation Concepts

The basic idea is to separate responsibilities to allow each implementation to use the tools/technologies that are already in use within their organizations.

Provisioning Layer

The provisioning layer deals with the lowest levels of compute/network/storage/load balancer resources. Its objective is to bring systems from nothingness to a functional operating system (at least minimally). Additionally, it is responsible for setting up proper DNS for each system, CDN components, and DNS NS record delegations.

Since DNS is a part of this layer, this unfortunately necessitates a small number of CDN concepts being present in the provisioning configuration. It is expected that upon completion of this layer, a compatible Ansible inventory file is generated and placed in the lab's Ansible inventory directory.

The Provisioning Layer Output

Ansible supports inventory files in several formats such as JSON, YAML, INI, or TOML. An example output is located at `infrastructure/ansible/sample.lab/inventory/provisioning.inventory`.

When creating systems, each will probably be designated for some particular component in the CDN. Ansible groups and hostvars specifying the component name must be provided and will be mapped to server types later on in the dataset loader.

Like the systems being allocated to a particular component name, they must also be assigned to a particular DNS NS Delegation name where relevant or the ALL cdn as needed by the component. The NS Delegation name is what you would find in DNS for Traffic Router to be authoritative for. In this example it's MKGA rather than the CDN Name which is Kabletown2.0.

It is not recommended that an *origin server* be used by more than one *Delivery Service* or it could lead to inconsistent behavior and conflated log data at the *Mid-tier*. As a workaround to this it is better for a lab to create DNS CNAME for each *Delivery Service* pointing at a particular *origin server* and return that set of names as a CSV hostvar `ds_names` on each *origin server*. These names will later be translated to additional inventory hosts used only for the creation of server objects in Traffic Ops and assignment to *Delivery Services*.

Steady-state OS Layer

The steady-state layer deals with the adaptation of a generic OS image to something that meets the organization's requirements. For a CDN lab, it is also important to consider the deployment of necessary SSL data to known locations.

Application Layer

This is the primary area for contribution within Apache Traffic Control. Ansible has built-in variable precedence and role inclusion. Conceptually these playbooks are split into implementation specific driver playbooks versus a generic core.

Implementation Specific Driver Playbook

Generally, this should handle some basic lab variable plumbing as well as any implementation specific tasks not generally useful to other ATC implementations. For example, an implementation might use an internal application as their application alerting engine which wouldn't make sense to others. Sticking with the example of an application alerting engine, even if it were an open implementation such as Nagios it still probably wouldn't be appropriate as not all implementations make use of that tool and maintaining it after contribution would incur ongoing costs.

Generic Core Playbook

This is the important piece for collaboration as it's based on the question, "Is this task/feature/function something all ATC implementations would benefit from?". Typically, the yes answers involve exposing or simplifying application functionality on the part of the lab environment maintainer or developer. Generally, the default values of a generic core role match or improve upon those present inside the RPM of the software.

Lab Implementation Layout

Ansible variable hierarchy

This is a topic better covered by [Ansible documentation](#), but the short version to keep in mind if you follow the sample lab design and markdown readme is:

(Highest precedence) CLI → Lab Vault → Lab Vars → Playbook Vars → Task Vars → Role Defaults (Lowest precedence)

Each of the generic core roles uses a prefix on its variables to avoid collision, and to make life easier it's recommended that you map them on the associated import role task variables. This makes keeping track of what variables were intentionally overwritten from the role defaults clearer.

Sample Driver Playbooks

There are a few sample playbooks located at [infrastructure/ansible/](#). As an implementor develops their implementation specific driver playbooks they should go here.

- [infrastructure/ansible/steady-state.yml](#) is an example of a playbook that can deal with generating SSL certificates and distributing them across a lab as well as dynamically generating a secondary inventory file with additional data.
- [infrastructure/ansible/sample.driver.playbook.yml](#) shows a general skeleton to leverage when building out your implementation's driver playbooks around the generic core roles.
- [infrastructure/ansible/influxdb_relay.yml](#) shows a more advanced example of a driver playbook that involves querying Traffic Ops for supplementary information in a secondary play.
- [infrastructure/ansible/test.urls.yml](#) is just a simple playbook to query a known asset list on all delivery service urls to ensure a basic 200 http response for every asset and url.

The Lab directory

A simple scaffold for a lab directory is included at `infrastructure/ansible/sample.lab`. This directory should encapsulate all pieces that make one environment unique from another. Ideally making new environments is as simple as copy-paste this directory and tweak the variables desired inside.

- The `infrastructure/ansible/sample.lab/ansible` subdirectory should be used to hold variables specific to a particular lab in either `vars.yml` or an encrypted Ansible vault
- The `infrastructure/ansible/sample.lab/inventory` directory is where it's recommended for your provisioning layer to drop a valid Ansible inventory file describing what was allocated. When using Ansible, it's important to point the inventory source to this directory so that it will merge all available inventory files together for you.
- The `infrastructure/ansible/sample.lab/out/ssl` directory is generated with the first run of the lab and holds your local copy of the lab SSL data. The out directory is also handy for holding temporary data from the provisioning or steady-state layers to help triage failures.
- The docker and docker-compose related files are present as an optional wrapper for Linux hosts (doesn't work on OSX) around all the lab plumbing dependencies for Ansible. This is particularly handy for automated systems who perform regular redeployments such as in a CI/CD tool.
- `infrastructure/ansible/sample.lab/manual.run.sh` is a scaffold for the entry-point for performing a lab rebuild from your local system.

Gilt

Traditionally when distributing application playbooks for Ansible, many people use the built-in Ansible Galaxy repository. There is a design limitation to the Ansible Galaxy though in that one git repository may only contain one role. In the case of Apache Traffic Control, there are many components each with their own roles. At the end of the day, the generic core roles must exist in a valid Ansible role directory location. There are many solutions to this problem, but one of the better and easier once that's been run across is using the 3rd-party tool [Gilt](#). As another alternative you can simply extract the roles from an Apache Traffic Control (ATC) source tarball from a build.

The Roles directory

The generic core roles for each component live at `infrastructure/ansible/roles`. Each role contains a README.md with more information, but this is not a replacement for existing documentation on the components themselves. It's very useful to still review the Administrator's Guide in the documentation as you develop your implementation around the component's generic core.

If you're attempting to optimize the wallclock time needed to deploy all the components in parallel, they should be installed like the following:

Ansible Bonuses

These roles don't require a lab environment to be useful to operations (ops) teams.

The `to_api` role

When reviewing the generic core roles, you'll notice that `infrastructure/ansible/roles/to_api` is a little different and doesn't map to an ATC component. This role was developed for Ops teams to integrate around daily workflows if desired.

Using Traffic Ops as an Ansible Dynamic Inventory source

`infrastructure/ansible/dynamic.inventory` contains a python script that is compatible with Ansible as a dynamic inventory. It leverages the python native client in ATC to expose lots of Traffic Ops server related data to the operator to make powerful and precise Ansible host patterns without the need of maintaining static files.

3.1.3 Traffic Portal Administration

Traffic Portal is only supported on CentOS Linux distributions version 7.x and 8.x. It runs on `NodeJS` and requires version 12 or higher.

Installing Traffic Portal

1. Download the Traffic Portal RPM from [Apache Jenkins](#) or build the Traffic Portal RPM from source using the instructions in *Building Traffic Control*.
2. Copy the Traffic Portal RPM to your server
3. Install NodeJS. This can be done by building it from source, installing with `yum(8)` if it happens to be in your available repositories (at version 12+), or using the NodeSource setup script.

49: Installing NodeJS using the NodeSource Setup Script

```
curl --silent --location https://rpm.nodesource.com/setup_
↪12.x | sudo bash -
```

4. Install the Traffic Portal RPM with `yum(8)` or `rpm(8)` e.g. by running `yum install path/to/traffic_portal.rpm` as the root user or with `sudo(8)`.

Configuring Traffic Portal

- update `/etc/traffic_portal/conf/config.js` (if Traffic Portal is being upgraded, reconcile `config.js` with `config.js.rpmnew` and then delete `config.js.rpmnew`)
- update `/opt/traffic_portal/public/traffic_portal_properties.json` (if Traffic Portal is being upgraded, reconcile `traffic_portal_properties.json` with `traffic_portal_properties.json.rpmnew` and then delete `traffic_portal_properties.json.rpmnew`)
- Optional: update `/opt/traffic_portal/public/resources/assets/css/custom.css` to customize Traffic Portal styling.

Configuring OAuth Through Traffic Portal

See *Configure OAuth Login*.

Starting Traffic Portal

The Traffic Portal RPM comes with a `systemd(1)` unit file, so under normal circumstances Traffic Portal may be started with `systemctl(1)`.

50: Starting Traffic Portal

```
systemctl start traffic_portal
```

Stopping Traffic Portal

The Traffic Portal RPM comes with a `systemd(1)` unit file, so under normal circumstances Traffic Portal may be stopped with `systemctl(1)`.

51: Stopping Traffic Portal

```
systemctl stop traffic_portal
```

3.1.4 Traffic Portal - Using

Traffic Portal is the official Traffic Control UI. Traffic Portal typically runs on a different machine than Traffic Ops, and works by using the Traffic Ops API. The following high-level items are available in the Traffic Portal menu.




Fig. 4: Traffic Portal Start Page

Change Logs

At the top-right of every page is a bubble icon and badge count indicating the number of changes made to the CDN since the last viewing. Clicking on this expands a short list, with an option to *See All Change Logs*. Clicking on this will navigate to the “Changelog” page.



Fig. 5: The Changelog Dialog




Fig. 6: The Full Change Logs Page

Sidebar Bottom Buttons

At the bottom of the sidebar, a few action buttons may be found. At the far left, is the *Logout* button.

Clicking on this button will cause the current user session to end; further use of the Traffic Portal UI will require re-authentication. Next to this is the *User Profile* button.




Fig. 7: The Logout Button




Fig. 8: The User Profile Button

Clicking on this button will take the user to his or her user profile page, where much of their information (contact, username etc.) is editable. The next button to the right is the *Release Info* button.




Fig. 9: The Release Info Button

When this button is clicked, a modal window will appear, displaying the Traffic Portal version, the date on which it was built, and the network location of the Traffic Ops server that serves the *Traffic Ops API* used by the Traffic Portal instance. The final button is the *Popout* button.

This button will open the current view in a new browsing context. Most browsers will implement this as a new tab, but can be configured instead to open them in a new window - check your browser's configuration and set it as desired.



Fig. 10: The Popout Button

Dashboard

The Dashboard is the default landing page for Traffic Portal. It provides a real-time view into the main performance indicators of the CDNs managed by Traffic Control. It also displays various statistics about the overall health of your CDN.

Current Bandwidth The current bandwidth of all of your CDNs.

Current Connections The current number of connections to all of your CDNs.

Healthy Caches Displays the number of healthy *cache servers* across all CDNs. Click the link to view the healthy caches on the cache stats page.

Unhealthy Caches Displays the number of unhealthy *cache servers* across all CDNs. Click the link to view the unhealthy caches on the cache stats page.

Online Caches Displays the number of *cache servers* with ONLINE *Status*. Traffic Monitor will not monitor the state of ONLINE servers.

Reported Caches Displays the number of *cache servers* with REPORTED *Status*.

Offline Caches Displays the number of *cache servers* with OFFLINE *Status*.

Admin Down Caches Displays the number of caches with ADMIN_DOWN *Status*.

Each component of this view is updated on the intervals defined in the `traffic_portal/app/src/traffic_portal_properties.json` configuration file.

CDNs

A table of CDNs with the following columns:

Name The name of the CDN

Domain The CDN's TLD (Top-Level Domain)

DNSSEC Enabled 'true' if *DNSSEC* is enabled on this CDN, 'false' otherwise.

CDN management includes the ability to (where applicable):

- create a new CDN
- update an existing CDN
- delete an existing CDN

- *Queue Updates* on all servers in a CDN, or clear such updates
- Compare CDN *Snapshots*
- create a CDN *Snapshot*
- manage a CDN's DNSSEC keys
- manage a CDN's *Federations*
- view *Delivery Services* of a CDN
- view CDN *Profiles*
- view servers within a CDN

Monitor

The *Monitor* section of Traffic Portal is used to display statistics regarding the various *cache servers* within all CDNs visible to the user. It retrieves this information through the *Traffic Ops API* from Traffic Monitor instances.




Fig. 11: The 'Monitor' Menu

Cache Checks

A real-time view into the status of each *cache server*. The *Monitor* → *Cache Checks* page is intended to give an overview of the caches managed by Traffic Control as well as their status.

Warning: Several of these columns may be empty by default - particularly in the *CDN in a Box* environment - and require *Traffic Ops Extensions* to be installed/enabled/configured in order to work.

Hostname The (short) hostname of the *cache server*

Profile The *Name* of the *Profile* used by the *cache server*

Status The *Status* of the *cache server*

See also:

Health Protocol

- UPD** Displays whether or not this *cache server* has configuration updates pending
- RVL** Displays whether or not this *cache server* (or one or more of its *parents*) has content invalidation requests pending
- ILO** Indicates the status of an iLO (Integrated Lights-Out) interface for this *cache server*
- 10G** Indicates whether or not the IPv4 address of this *cache server* is reachable via ICMP “pings”
- FQDN** DNS check that matches what the DNS servers respond with compared to what Traffic Ops has configured
- DSCP** Checks the DSCP value of packets received from this *cache server*
- 10G6** Indicates whether or not the IPv6 address of this *cache server* is reachable via ICMP “pings”
- MTU** Checks the MTU by sending ICMP “pings” from the Traffic Ops server
- RTR** Checks the reachability of the *cache server* from the CDN’s configured Traffic Routers
- CHR** Cache-Hit Ratio (percent)
- CDU** Total Cache-Disk Usage (percent)
- ORT** Uses the *ORT* script on the *cache server* to determine if the configuration in Traffic Ops matches the configuration on *cache server* itself. The user as whom this script runs must have an SSH key on each server.

Cache Stats

A table showing the results of the periodic *Check Extensions* that are run. These can be grouped by *Cache Group* and/or *Profile*.

- Profile** *Name* of the *Profile* applied to the Edge-tier or Mid-tier *cache server*, or the special name “ALL” indicating that this row is a group of all *cache servers* within a single *Cache Group*
- Host** ‘ALL’ for entries grouped by *Cache Group*, or the hostname of a particular *cache server*
- Cache Group** *Name of the Cache Group* to which this server belongs, or the name of the *Cache Group* that is grouped for entries grouped by *Cache Group*, or the special name “ALL” indicating that this row is an aggregate across all *Cache Groups*
- Healthy** True/False as determined by Traffic Monitor
- See also:**
Health Protocol
- Status** Status of the *cache server* or *Cache Group*

Connections Number of currently open connections to this *cache server* or *Cache Group*

MbpsOut Data flow rate outward from the CDN (toward client) in Megabits per second

Services

Services groups the functionality to modify *Delivery Services* - for those users with the necessary permissions - or make *Delivery Service Requests* for such changes - for users without necessary permissions. Delivery Services can also be grouped by *Service Category*.




Fig. 12: The 'Services' Menu

Delivery Services

This page contains a table displaying all *Delivery Services* visible to the user as determined by their *Tenant*.

XML ID (Key)	Tenant	Type	Active	Protocol
testqa	test and utility	HTTP	true	HTTP

Fig. 13: Table of Delivery Services

Use the *Select Columns* menu to select the delivery service columns to view and search. Columns can also be rearranged using drag-and-drop. Available delivery service columns include:

- *Active* (visible by default)
- *Anonymous Blocking*
- *CDN* (visible by default)
- *Check Path*
- *Consistent Hashing Query Parameters*
- *Consistent Hashing Regular Expression*
- *Deep Caching*
- *Display Name*

- *DNS Bypass CNAME*
- *DNS Bypass IP*
- *DNS Bypass IPv6*
- *DNS Bypass TTL*
- *DNS TTL*
- *DSCP* (visible by default)
- *Edge Header Rewrite Rules*
- *Fair-Queuing Pacing Rate Bps*
- *First Header Rewrite Rules*
- *Geo Limit*
- *Geo Limit Countries*
- *Geo Limit Redirect URL*
- *Geolocation Provider*
- *Geo Miss Default Latitude*
- *Geo Miss Default Longitude*
- *Global Max Mbps*
- *Global Max TPS*
- *HTTP Bypass FQDN*
- *Info URL*
- *Initial Dispersion*
- *Inner Header Rewrite Rules*
- *IPv6 Routing Enabled* (visible by default)
- *Last Header Rewrite Rules*
- *Long Description*
- *Max DNS Answers*
- *Max Origin Connections*
- *Mid Header Rewrite Rules*
- *Origin Shield*
- *Origin Server Base URL* (visible by default)
- *Profile*
- *Protocol* (visible by default)
- *Query String Handling* (visible by default)

- *Range Request Handling*
- *Range Slice Request Block Size*
- *Raw Remap Text*
- *Regex Remap Expression*
- *Regional Geoblocking*
- *Routing Name*
- *Signing Algorithm* (visible by default)
- *Tenant* (visible by default)
- *Topology*
- *Traffic Router Additional Response Headers*
- *Traffic Router Log Request Headers*
- *Type* (visible by default)
- *Use Multi-Site Origin Feature*
- *xml_id* (visible by default)

Delivery Service management includes the ability to (where applicable):


- Create a new *Delivery Service*
- Clone an existing *Delivery Service*
- Update an existing *Delivery Service*
- Delete an existing *Delivery Service*
- Compare *Delivery Services*
- Manage *Delivery Service* SSL keys
- Manage *Delivery Service* URL signature keys
- Manage *Delivery Service* URI signing keys
- Manage *Delivery Service* invalidation requests
- Manage *Delivery Service* origins
- Manage *Delivery Service* regular expressions
- *Manage delivery service required server capabilities*
- Manage *Delivery Service* server assignments
- Manage *Delivery Service* steering targets
- Manage *Delivery Service* static DNS records within a *Delivery Service* subdomain
- Test *Consistent Hashing Patterns*

See also:

Configuring Static DNS Entries

Delivery Service Requests

If enabled in the `traffic_portal_properties.json` configuration file, all *Delivery Service* changes (create, update and delete) are captured as a *Delivery Service Request* and must be reviewed before fulfillment/deployment.



Delivery Service	Type	Status	Author
testds010804	create	complete	admin
testds010803	create	complete	admin
testds010802	update	submitted	admin
testds010802	create	complete	admin
testtopods0108	delete	complete	admin
testtopods0108	create	complete	admin

Fig. 14: Table of Delivery Service Requests

Delivery Service: A unique string that identifies the *Delivery Service* with which the request is associated. This unique string is also known (and often referred to within documentation and source code) as a *Delivery Service* key or 'XML ID'/'xml_id'/'xmlid' :**Type:** The type of *Delivery Service Request*: 'create', 'update', or 'delete' according to what was requested :**Status:** The status of the *Delivery Service Request*. Has the following possible values:

- draft** The *Delivery Service Request* is *not* ready for review and fulfillment
- submitted** The *Delivery Service Request* is ready for review and fulfillment
- rejected** The *Delivery Service Request* has been rejected and cannot be modified
- pending** The *Delivery Service Request* has been fulfilled but the changes have yet to be deployed
- complete** The *Delivery Service Request* has been fulfilled and the changes have been deployed
- Author** The user responsible for creating the *Delivery Service Request*
- Assignee** The user responsible for fulfilling the *Delivery Service Request*. Currently, the operations role or above is required to assign *Delivery Service Requests*
- Last Edited By** The last user to edit the *Delivery Service Request*
- Created** Relative time indicating when the *Delivery Service Request* was created
- Actions** Actions that can be performed on a *Delivery Service Request*. The following actions are provided:
 - fulfill** Implement the changes captured in the *Delivery Service Request*
 - reject** Reject the changes captured in the *Delivery Service Request*

delete Delete the *Delivery Service Request*

Delivery Service Request management includes the ability to (where applicable):

- create a new *Delivery Service Request*
- update an existing *Delivery Service Request*
- delete an existing *Delivery Service Request*
- update the status of a *Delivery Service Request*
- assign a *Delivery Service Request*
- reject a *Delivery Service Request*
- fulfill a *Delivery Service Request*
- complete a *Delivery Service Request*

See also:

Delivery Service Requests

Configure

Interfaces for managing the various components of Traffic Control and how they interact are grouped under *Configure*.




Fig. 15: The ‘Configure’ Menu

Servers

A configurable table of all servers (of all kinds) across all *Delivery Services* and CDNs visible to the user.

Host	Domain	CDN	Network IP	Select Columns
foo	bar.com	Kabletown2.0	1.1.1.1	<input type="checkbox"/> Cache Group <input checked="" type="checkbox"/> CDN <input checked="" type="checkbox"/> Domain <input type="checkbox"/> Hash ID <input checked="" type="checkbox"/> Host <input type="checkbox"/> HTTPS Port <input type="checkbox"/> ID <input type="checkbox"/> ILO IP Address <input type="checkbox"/> ILO IP Gateway <input type="checkbox"/> ILO IP Netmask

Fig. 16: Table of Servers

Use the *Quick Search* to search across all table columns or the column filter to apply a more powerful filter to individual columns. Use the *Select Columns* menu to select the server columns to view. Columns can also be rearranged using drag-and-drop. Available server columns include:

Cache Group [Visible by default] The *Name of the Cache Group* to which this server belongs

CDN [Visible by default] The name of the CDN to which the server belongs

Domain [Visible by default] The domain part of the server's FQDN

Hash ID The identifier of the server used in Traffic Router's consistent hashing algorithm.

Host [Visible by default] The (short) hostname of the server

HTTPS Port The port on which the server listens for incoming HTTPS connections/requests

ID An integral, unique identifier for this server

ILO IP Address The IPv4 address of the server's ILO service

See also:

[Hewlett Packard ILO Wikipedia Page](#)

ILO IP Gateway The IPv4 gateway address of the server's ILO service

ILO IP Netmask The IPv4 subnet mask of the server's ILO service

ILO Username The user name for the server's ILO service

Interface Name The name of the primary network interface used by the server

IPv6 Address [Visible by default] The IPv6 address and subnet mask of interfaceName

- IPv6 Gateway** The IPv6 address of the gateway used by `interfaceName`
- Last Updated** The date and time at which this server description was last modified
- Mgmt IP Address** The IPv4 address of some network interface on the server used for ‘management’
- Mgmt IP Gateway** The IPv4 address of a gateway used by some network interface on the server used for ‘management’
- Mgmt IP Netmask** The IPv4 subnet mask used by some network interface on the server used for ‘management’
- IPv4 Gateway** The IPv4 address of the gateway used by `interfaceName`
- IPv4 Address** [Visible by default] The IPv4 address of `interfaceName`
- Network MTU** The Maximum Transmission Unit (MTU) to configured on `interfaceName`
- IPv4 Subnet** The IPv4 subnet mask used by `interfaceName`
- Offline Reason** A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status
- Phys Location** The name of the physical location where the server resides
- Profile** [Visible by default] The *Name* of the *Profile* used by this server
- Rack** A string indicating “server rack” location
- Reval Pending** [Visible by default] A boolean value represented as a clock (content invalidation/revalidation is pending) or green check mark (content invalidation/revalidation is not pending)
- Router Hostname** The human-readable name of the router responsible for reaching this server’s interface
- Router Port** The human-readable name of the port used by the router responsible for reaching this server’s interface
- Status** [Visible by default] The *Status* of the server
- See also:**
- Health Protocol*
- TCP Port** The port on which this server listens for incoming TCP connections
- Type** [Visible by default] The name of the *Type* of this server
- Update Pending** [Visible by default] A boolean value represented as a clock (updates are pending) or green check mark (updates are not pending), typically to be acted upon by Traffic Ops ORT

Server management includes the ability to (where applicable):

- Create a new server
- Update an existing server

- Delete an existing server
- *Queue Updates* on a server, or clear such updates
- Update server status
- View server *Delivery Services*
- Clone *Delivery Service* assignments
- Assign *Delivery Services* to server(s)
- *Manage server capabilities assigned to a server*

Origins

A table of all *Origins*. These are automatically created for the *Origins* served by *Delivery Services* throughout all CDNs, but additional ones can be created at will. The table has the following columns:

Name The name of the *Origin*. If this *Origin* was created automatically for a *Delivery Service*, this will be the *xml_id* of that *Delivery Service*.

Tenant The name of the *Tenant* that owns this *Origin* - this is not necessarily the same as the *Tenant* that owns the *Delivery Service* to which this *Origin* belongs.

Primary Either `true` to indicate that this is the “primary” *Origin* for the *Delivery Service* to which it is assigned, or `false` otherwise.

Delivery Service The *xml_id* of the *Delivery Service* to which this *Origin* is assigned.

FQDN The FQDN of the *Origin*.

IPv4 Address The *Origin*’s IPv4 address, if configured.

IPv6 Address The *Origin*’s IPv6 address, if configured.

Protocol The protocol this *Origin* uses to serve content. One of

- `http`
- `https`

Port The port on which the *Origin* listens for incoming HTTP(S) requests.

Note: If this field appears blank in the table, it means that a default was chosen for the *Origin* based on its Protocol - 80 for “http”, 443 for “https”.

Coordinate The name of the geographic coordinate pair that defines the physical location of this *Origin*. *Origins* created for *Delivery Services* automatically will **not** have associated Coordinates. This can be rectified on the details pages for said *Origins*

Cachegroup The *Name of the Cache Group* to which this *Origin* belongs, if any.

Profile The *Name* of a *Profile* used by this *Origin*.

Origin management includes the ability to (where applicable):

- create a new *Origin*
- update an existing *Origin*
- delete an existing *Origin*

Profiles

A table of all *Profiles*. From here you can see *Parameters*, servers and *Delivery Services* assigned to each *Profile*. Each entry in the table has these fields:

Name The *Name* of the *Profile*

Type The *Type* of this *Profile*, which indicates the kinds of objects to which the *Profile* may be assigned

Routing Disabled The *Routing Disabled* setting of this *Profile*

Description This *Profile*'s *Description*

CDN The *CDN* to which this *Profile* is restricted. To use the same *Profile* across multiple CDNs, clone the *Profile* and change the clone's *CDN* field.

Profile management includes the ability to (where applicable):

- create a new *Profile*
- update an existing *Profile*
- delete an existing *Profile*
- clone a *Profile*
- export a *Profile*
- view *Profile Parameters*
- view *Profile Delivery Services*
- view *Profile* servers

Parameters

This page displays a table of *Parameters* from all *Profiles* with the following columns:

Name The *Name* of the *Parameter*

Config File The *Config File* to which the *Parameter* belongs.

Value The *Value* of the *Parameter*.

Secure Whether or not the *Parameter* is *Secure*

Profiles The number of *Profiles* currently using this *Parameter*

Parameter management includes the ability to (where applicable):

- create a new *Parameter*
- update an existing *Parameter*
- delete an existing *Parameter*
- view *Parameter Profiles*
- manage assignments of a *Parameter* to one or more *Profiles* and/or *Delivery Services*

Types

Types group *Delivery Services*, servers and *Cache Groups* for various purposes. Each entry in the table shown on this page has the following fields:

Name The name of the *Type*

Use In Table States the use of this *Type*, e.g. `server` indicates this is a *Type* assigned to servers

Description A short, usually user-defined, description of the *Type*

Type management includes the ability to (where applicable):

- create a new *Type*
- update an existing *Type*
- delete an existing *Type*
- view *Delivery Services* assigned to a *Type*
- view servers assigned to a *Type*
- view *Cache Groups* assigned to a *Type*

Statuses

This page shows a table of *Statuses* with the following columns:

Name The name of this *Status*

Description A short, usually user-defined, description of this *Status*

Status management includes the ability to (where applicable):

- create a new *Status*
- update an existing *Status*
- delete an existing *Status*
- view *Statuses*

Topology

Topology groups views and functionality that deal with how CDNs and their Traffic Control components are grouped and distributed, both on a logical level as well as a physical level.




Fig. 17: ‘Topology’ Menu

Cache Groups

This page is a table of *Cache Groups*, each entry of which has the following fields:

- Name** The full *Name of this Cache Group*
- Short Name** This *Cache Group’s Short Name*
- Type** This *Cache Group’s Type*
- Latitude** This *Cache Group’s Latitude*
- Longitude** This *Cache Group’s Longitude*

Cache Group management includes the ability to (where applicable):

- create a new *Cache Group*
- update an existing *Cache Group*
- delete an existing *Cache Group*
- *Queue Updates* for all servers in a *Cache Group*, or clear such updates
- view *Cache Group* ASNs

See also:

[The Wikipedia page on Autonomous System Numbers](#)

- view and assign *Cache Group Parameters*
- view *Cache Group* servers

Coordinates

Topology → *Coordinates* allows a label to be given to a set of geographic coordinates for ease of use. Each entry in the table on this page has the following fields:

Name The name of this coordinate pair

Latitude The geographic latitude part of the coordinate pair

Longitude The geographic longitude part of the coordinate pair

Coordination management includes the ability to (where applicable):

- create a new coordinate pair
- update an existing coordinate pair
- delete an existing coordinate pair

Phys Locations

A table of *Physical Locations* which may be assigned to servers and *Cache Groups*, typically for the purpose of optimizing client routing. Each entry has the following columns:

Name The full name of the *Physical Location*

Short Name A shorter, more human-friendly name for this *Physical Location*

Address The *Physical Location*'s street address (street number and name)

City The city within which the *Physical Location* resides

State The state within which the *Physical Location*'s city lies

Region The *Region* to which this *Physical Location* has been assigned

Physical Location management includes the ability to (where applicable):

- create a new *Physical Location*
- update an existing *Physical Location*
- delete an existing *Physical Location*
- view *Physical Location* servers

Divisions

Each entry in the table of *Divisions* on this page has the following fields:

Name The name of the *Division*

Division management includes the ability to (where applicable):

- create a new *Division*
- delete an existing *Division*
- modify an existing *Division*
- view *Regions* within a *Division*

Regions

Each entry in the table of *Regions* on this page has the following fields:

Name The name of this *Region*

Division The *Division* to which this *Region* is assigned

Region management includes the ability to (where applicable):

- create a new *Region*
- update an existing *Region*
- delete an existing *Region*
- view *Physical Locations* within a *Region*

ASNs

Manage ASNs. Each entry in the table on this page has the following fields:

ASN The actual ASN

Cache Group The *Cache Group* to which this ASN is assigned

ASN management includes the ability to (where applicable):

- create a new ASN
- update an existing ASN
- delete an existing ASN

See also:

[Autonomous System \(Internet\) Wikipedia Page](#)

Tools

Tools contains various tools that don't directly relate to manipulating Traffic Control components or their groupings.




Fig. 18: The 'Tools' Menu

Invalidate Content

Here, specific assets can be invalidated in all caches of a *Delivery Service*, forcing content to be updated from the origin. Specifically, this *doesn't* mean that *cache servers* will immediately remove items from their caches, but rather will fetch new copies whenever a request is made matching the 'Asset URL' regular expression. This behavior persists until the Invalidate Content Job's TTL expires. Each entry in the table on this page has the following fields:

Delivery Service: The *Delivery Service* to which to apply this Invalidate Content Job :Asset URL: A URL or regular expression which describes the asset(s) to be invalidated :Parameters: So far, the only use for this is setting a TTL over which the Invalidate Content Job shall remain active :Start: An effective start time until which the job is delayed :Created By: The user name of the person who created this Invalidate Content Job

Invalidate content includes the ability to (where applicable):

- create a new invalidate content job

Generate ISO

Generates a boot-able system image for any of the servers in the Servers table (or any server for that matter). Currently it only supports CentOS 7, but if you're brave and pure of heart you MIGHT be able to get it to work with other Unix-like Operating Systems. The interface is *mostly* self-explanatory, but here is a short explanation of the fields in that form.

See also:

For instructions on setting up the Kickstart ISO generation files, see *Creating the CentOS Kickstart File*.

Copy Server Attributes From Optional. This option lets the user choose a server from the Traffic Ops database and will auto-fill the other fields as much as possible based on that server's properties

OS Version This list is populated by modifying the `osversions.json` file on the Traffic Ops server. This file maps OS names to the name of a directory under *kickstart.files.location* (`/var/www/files` by default).

Hostname The desired hostname of the resultant system

Domain The desired domain name of the resultant system

DHCP If this is ‘no’ the IP settings of the system must be specified, and the following extra fields will appear:

IP Address The resultant system’s IPv4 address

IPv6 Address The resultant system’s IPv6 address

Network Subnet The system’s network subnet mask

Network Gateway The system’s network gateway’s IPv4 address

IPv6 Gateway The system’s network gateway’s IPv6 address

Management IP Address An optional IP address (IPv4 or IPv6) of a “management” server for the resultant system (e.g. for ILO)

Management IP Netmask The subnet mask (IPv4 or IPv6) used by a “management” server for the resultant system (e.g. for ILO) - only needed if the Management IP Address is provided

Management IP Gateway The IP address (IPv4 or IPv6) of the network gateway used by a “management” server for the resultant system (e.g. for ILO) - only needed if the Management IP Address is provided

Management Interface The network interface used by a “management” server for the resultant system (e.g. for ILO) - only needed if the Management IP Address is provided. Must not be the same as “Interface Name”.

Network MTU The system’s network’s MTU. Despite being a text field, this can only be 1500 or 9000 - it should almost always be 1500

See also:

[The Maximum transmission unit Wikipedia Page](#)

Disk for OS Install The disk on which to install the base system. A reasonable default is `sda` (the `/dev/` prefix is not necessary)

Root Password The password to be used for the root user. Input is hashed using MD5 before being written to disk

Confirm Root Password Repeat the ‘Root Password’ to be sure it’s right

Interface Name Optional. The name of the resultant system’s network interface. Typical values are `bond0`, `eth4`, etc. If `bond0` is entered, a Link Aggregation Control Protocol bonding configuration will be written

See also:

[The Link aggregation Wikipedia Page](#)

Stream ISO If this is ‘yes’, then the download will start immediately as the ISO is written directly to the socket connection from Traffic Ops. If this is ‘no’, then the download will begin only *after* the ISO has finished being generated. For almost all use cases, this should be ‘yes’.

Implementation Detail

Traffic Ops uses Red Hat’s *Kickstart* <https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/7/html/installation_guide/chap-kickstart-installations> to create these ISOs, so many configuration options not available here can be tweaked in the [Kickstart configuration file](#).

User Admin

This section offers administrative functionality for users and their permissions.




Fig. 19: The ‘User Admin’ Menu

User

This page lists all the users that are visible to the user (so, for ‘admin’ users, all users will appear here). Each entry in the table on this page has the following fields:

Full Name The user’s full, real name

Username The user’s username

Email The user’s email address

Tenant The user’s *Tenant*

Role The user’s *Role*

User management includes the ability to (where applicable):

- register a new user

- create a new user
- update an existing user
- view *Delivery Services* visible to a user

Note: If OAuth is enabled, the username must exist both here as well as with the OAuth provider. A user's rights are defined by the *Role* assigned to the user in Traffic Ops. Creating/deleting a user here will update the user's *Role* but the user needs to be created/deleted with the OAuth provider as well.

Tenants

Each entry in the table of *Tenants* on this page has the following entries:

Name The name of the *Tenant*

Active If 'true' users of this *Tenant* group are allowed to login and have active *Delivery Services*

Parent The parent of this *Tenant*. The default is the 'root' *Tenant*, which has no users.

Tenant management includes the ability to (where applicable):

- create a new *Tenant*
- update an existing *Tenant*
- delete an existing *Tenant*
- view users assigned to a *Tenant*
- view *Delivery Services* assigned to a *Tenant*

Roles

Each entry in the table of *Roles* on this page has the following fields:

Name The name of the *Role*

Privilege Level The privilege level of this *Role*. This is a whole number that actually controls what a user is allowed to do. Higher numbers correspond to higher permission levels

Description A short description of the *Role* and what it is allowed to do

Role management includes the ability to (where applicable):

- view all *Roles*
- create new *Role*

Note: *Roles* cannot be deleted through the Traffic Portal UI

Other

Custom menu items. By default, this contains only a link to the Traffic Control documentation.




Fig. 20: The ‘Other’ Menu

Docs

This is just a link to [the Traffic Control Documentation](#).

Custom Menu Items

This section is configurable in the `traffic_portal_properties.json` configuration file, in the `customMenu` section.

3.1.5 Traffic Monitor Administration

Installing Traffic Monitor

The following are hard requirements requirements for Traffic Monitor to operate:

- CentOS 7 or later
- Successful install of Traffic Ops (usually on a separate machine)
- Administrative access to the Traffic Ops (usually on a separate machine)

These are the recommended hardware specifications for a production deployment of Traffic Monitor:

- 8 CPUs
- 16GB of RAM
- It is also recommended that you know the geographic coordinates and/or mailing address of the site where the Traffic Monitor machine lives for optimal performance

1. Enter the Traffic Monitor server into Traffic Portal

Note: For legacy compatibility reasons, the ‘Type’ field of a new Traffic Monitor server must be ‘RASCAL’.

2. Make sure the FQDN of the Traffic Monitor is resolvable in DNS.
3. Install Traffic Monitor, either from source or by installing a `traffic_monitor-version.string.rpm` package generated by the instructions in *Building Traffic Control* with `yum(8)` or `rpm(8)`
4. Configure Traffic Monitor according to *Configuring Traffic Monitor*
5. Start Traffic Monitor, usually by starting its `systemd(1)` service
6. Verify Traffic Monitor is running by e.g. opening your preferred web browser to port 80 on the Traffic Monitor host.

Configuring Traffic Monitor

Configuration Overview

Traffic Monitor is configured via two JSON configuration files, `traffic_ops.cfg` and `traffic_monitor.cfg`, by default located in the `conf` directory in the install location. `traffic_ops.cfg` contains Traffic Ops connection information. Specify the URL, username, and password for the instance of Traffic Ops of which this Traffic Monitor is a member. `traffic_monitor.cfg` contains log file locations, as well as detailed application configuration variables such as processing flush times, initial poll intervals, and the polling protocols. Once started with the correct configuration, Traffic Monitor downloads its configuration from Traffic Ops and begins polling *cache server*s. Once every *cache server* has been polled, *Health Protocol* state is available via RESTful JSON endpoints and a web browser UI.

Polling protocol can be set for peers and caches and has 3 options:

ipv4only Traffic Monitor will communicate with the peers or caches only over IPv4

ipv6only Traffic Monitor will communicate with the peers or caches only over IPv6 (use case for peers is if the other Traffic Monitor are only available over IPv6)

both (the default) Traffic Monitor will alternate its communication between IPv4 and IPv6 (note: this does not affect the polling frequency so if polling frequency is 1 second IPv4 will be polled every 2 seconds)

Note: both will poll IPv4 and IPv6 and report on availability based on if the respective IP addresses are defined on the server. So if only an IPv4 address is defined and the protocol is set to both then it will only show the availability over IPv4, but if both addresses are defined then it will show availability based on IPv4 and IPv6.

Peering and Optimistic Quorum

As mentioned in the *Health Protocol* section of the *Traffic Monitor* overview, peering a Traffic Monitor with one or more other Traffic Monitors enables the optimistic health protocol. In order to leverage the optimistic quorum feature along with the optimistic health protocol, a minimum of three Traffic Monitors are required. The optimistic quorum feature allows a Traffic Monitor to withdraw itself from the optimistic health protocol when it loses connectivity to a number of its peers.

To enable the optimistic quorum feature, the `peer_optimistic_quorum_min` property in `traffic_monitor.cfg` should be configured with a value greater than zero that specifies the minimum number of peers that must be available in order to participate in the optimistic health protocol. If at any time the number of available peers falls below this threshold, the local Traffic Monitor will serve 503s whenever the aggregated, optimistic health protocol enabled view of the CDN's health is requested. Traffic Monitor will continue serving 503s and logging errors in `traffic_monitor.log` until the minimum number of peers are available. Once the minimum number of peers are available, the local Traffic Monitor can resume participation in the optimistic health protocol. This prevents negative states caused by network isolation of a Traffic Monitor from propagating to downstream components such as Traffic Router.

Stat and Health Flush Configuration

The Monitor has a health flush interval, a stat flush interval, and a stat buffer interval. Recall that the monitor polls both stats and health. The health poll is so small and fast, a buffer is largely unnecessary. However, in a large CDN, the stat poll may involve thousands of *cache servers* with thousands of stats each, or more, and CPU may be a bottleneck.

The flush intervals, `health_flush_interval_ms` and `stat_flush_interval_ms`, indicate how often to flush stats or health, if results are continuously coming in with no break. This prevents starvation. Ideally, if there is enough CPU, the flushes should never occur. The default flush times are 200 milliseconds, which is suggested as a reasonable starting point; operators may adjust them higher or lower depending on the need to get health data and stop directing client traffic to unhealthy *cache servers* as quickly as possible, balanced by the need to reduce CPU usage.

The stat buffer interval, `stat_buffer_interval_ms`, also provides a temporal buffer for stat processing. Stats will not be processed except after this interval, whereupon all pending stats will be processed, unless the flush interval occurs as a starvation safety. The stat buffer and flush intervals may be thought of as a state machine with two states: the “buffer state” accepts results until the buffer interval has elapsed, whereupon the “flush state” is entered, and results

are accepted while outstanding, and processed either when no results are outstanding or the flush interval has elapsed.

Note that this means the stat buffer interval acts as “bufferbloat,” increasing the average and maximum time a *cache server* may be down before it is processed and marked as unhealthy. If the stat buffer interval is non-zero, the average time a *cache server* may be down before being marked unavailable is half the poll time plus half the stat buffer interval, and the maximum time is the poll time plus the stat buffer interval. For example, if the stat poll time is 6 seconds, and the stat buffer interval is 4 seconds, the average time a *cache server* may be unhealthy before being marked is $\frac{6}{2} + \frac{4}{2} = 6$ seconds, and the maximum time is $6 + 4 = 10$ seconds. For this reason, if operators feel the need to add a stat buffer interval, it is recommended to start with a very low duration, such as 5 milliseconds, and increase as necessary.

It is not recommended to set either flush interval to 0, regardless of the stat buffer interval. This will cause new results to be immediately processed, with little to no processing of multiple results concurrently. Result processing does not scale linearly. For example, processing 100 results at once does not cost significantly more CPU usage or time than processing 10 results at once. Thus, a flush interval which is too low will cause increased CPU usage, and potentially increased overall poll times, with little or no benefit. The default value of 200 milliseconds is recommended as a starting point for configuration tuning.

HTTP Accept Header Configuration

The Accept header sent to caches for stat retrieval can be modified with the `http_polling_format` option. This is a string that will be inserted in to the Accept header of any requests. The default value is `text/json` which is the default value used by the `astats` plugin currently.

However newer versions of `astats` also support CSV output, which can have some CPU savings. To enable that format using `http_polling_format`: `"text/csv"` in `traffic_monitor.cfg` will set the Accept header properly.

Troubleshooting and Log Files

Traffic Monitor log files are in `/opt/traffic_monitor/var/log/`.

Extensions

Traffic Monitor allows extensions to its parsers for the statistics returned by *cache servers* and/or their plugins. The formats supported by Traffic Monitor by default are `astats`, `astats-dsnames` (which is an odd variant of `astats` that probably shouldn't be used), and `stats_over_http`. The format of a *cache server*'s health and statistics reporting payloads must be declared on its *Profile* as the *health.polling.format Parameter*, or the default format (`astats`) will be assumed.

For instructions on how to develop a parsing extension, refer to the github.com/apache/trafficcontrol/traffic_monitor/cache package's documentation.

Importantly, though, a statistics provider *must* respond to HTTP GET requests over either plain HTTP or HTTPS (which is controlled by the *health.polling.url Parameter*), and it *must* provide the following statistics, or enough information to calculate them:

- System “loadavg” (only requires the one-minute value)

See also:

For more information on what “loadavg” is, refer to the *proc(5)* manual page.

- Input bytes, output bytes, and speeds for all monitored network interfaces

When using the `stats_over_http` extension this can be provided by the `system_stats` plugin which will inject that information in to the ATS stats which then get returned by `stats_over_http`. The `system_stats` plugin can be used with any custom implementations as it is already included and built with ATS when building with experimental-plugins enabled.

There are other optional and/or *Delivery Service*-related statistics that may cause Traffic Stats to not have the right information if not provided, but the above are essential for implementing *Health Protocol*.

3.1.6 Traffic Router Administration

Requirements

- CentOS 7 or later
- 4 CPUs
- 8GB of RAM
- Successful install of Traffic Ops (usually on another machine)
- Successful install of Traffic Monitor (usually on another machine)
- Administrative access to Traffic Ops

Note: Hardware requirements are generally doubled if *DNSSEC* is enabled

Installing Traffic Router

1. If no suitable *Profile* exists, create a new *Profile* for Traffic Router via the + button on the *Profiles* page in Traffic Portal

Warning: Traffic Ops will *only* recognize a *Profile* as assignable to a Traffic Router if its *Name* starts with the prefix `ccr-`. The reason for this is a legacy limitation related to the old name for Traffic Router (Comcast Cloud Router), and will (hopefully) be rectified in the future.

2. Enter the Traffic Router server into Traffic Portal on the *Servers* page (or via the *Traffic Ops API*), assign to it a Traffic Router *Profile*, and ensure that its status is set to ONLINE.
3. Ensure the FQDN of the Traffic Router is resolvable in DNS. This FQDN must be resolvable by the clients expected to use this CDN.
4. Install a Traffic Router server package, either from source or using a `traffic_router-version string.rpm` package generated using the instructions in *Building Traffic Control*.

Changed in version 3.0: As of version 3.0, Traffic Router depends upon a package called `tomcat`. This package should have been created when Traffic Router was built. If installing the `traffic_router` produces a dependency error, make sure that the `tomcat` package is available in an accessible `yum(8)` repository.

5. Edit `/opt/traffic_router/conf/traffic_monitor.properties` and specify the correct online Traffic Monitor(s) for your CDN.

See also:

Traffic Router Configuration File Parameters

traffic_monitor.properties URL that should normally point to this file, e.g. `traffic_monitor.properties=file:/opt/traffic_router/conf/traffic_monitor.properties`

traffic_monitor.properties.reload.period Period to wait (in milliseconds) between reloading this file, e.g. `traffic_monitor.properties.reload.period=60000`

6. Start Traffic Router. This is normally done by starting its `systemd(1)` service. `systemctl start traffic_router`, and test DNS lookups against that server to be sure it's resolving properly. with e.g. `dig` or `curl`. Also, because previously taken CDN *Snapshots* will be cached, they need to be removed manually to actually be reloaded. This file should be located at `/opt/traffic_router/db/cr-config.json`. This should be done before starting or restarting Traffic Router.

52: Starting and Testing Traffic Router

```
[root@trafficrouter /]# systemctl start traffic_router
[root@trafficrouter /]# dig @localhost mycdn.ciab.test

; <<>> DiG 9.9.4-RedHat-9.9.4-72.el7 <<>> @localhost mycdn.
↳ciab.test
; (2 servers found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 27109
;; flags: qr aa rd; QUERY: 1, ANSWER: 0, AUTHORITY: 1,↳
↳ADDITIONAL: 0
;; WARNING: recursion requested but not available
```

(continues on next page)

(continued from previous page)

```
;; QUESTION SECTION:
;mycdn.ciab.test.      IN  A

;; AUTHORITY SECTION:
mycdn.ciab.test.      30  IN  SOA trafficrouter.infra.ciab.
↳test. twelve_monkeys.mycdn.ciab.test. 2019010918 28800
↳7200 604800 30

;; Query time: 28 msec
;; SERVER: ::1#53(::1)
;; WHEN: Wed Jan 09 21:27:57 UTC 2019
;; MSG SIZE  rcvd: 104
```

7. Perform a CDN *Snapshot*.

Note: Once the *Snapshot* is taken, live traffic will be sent to the new Traffic Routers provided that their status has been set to ONLINE.

8. Ensure that the parent domain (e.g.: `cdn.local`) for the CDN's top level domain (e.g.: `ciab.cdn.local`) contains a delegation (Name Server records) for the new Traffic Router, and that the value specified matches the FQDN of the Traffic Router.

Configuring Traffic Router

Changed in version 1.5: Many of the configuration files under `/opt/traffic_router/conf` are now only needed to override the default configuration values for Traffic Router. Most of the given default values will work well for any CDN. Critical values that must be changed are hostnames and credentials for communicating with other Traffic Control components such as Traffic Ops and Traffic Monitor. Pre-existing installations that store configuration files under `/opt/traffic_router/conf` will still be used and honored for Traffic Router 1.5 onward.

Changed in version 3.0: Traffic Router 3.0 has been converted to a formal Tomcat instance, meaning that is now installed separately from the Tomcat servlet engine. The Traffic Router installation package contains all of the Traffic Router-specific software, configuration and startup scripts including some additional configuration files needed for Tomcat. These new configuration files can all be found in the `/opt/traffic_router/conf` directory and generally serve to override Tomcat's default settings.

For the most part, the configuration files and *Parameters* used by Traffic Router are used to bring it online and start communicating with various Traffic Control components. Once Traffic Router is successfully communicating with Traffic Control, configuration should mostly be performed in Traffic Portal, and will be distributed throughout Traffic Control via CDN *Snapshot* process.

Table 54: Traffic Router Configuration File Parameters

Con-figu-ration File	Parame-ter Name	Description	Default Value
traf- fic_monitor.properties	traf- fic_monitor.bootstrap_hosts	Semicolon-delimited Traffic Monitor FQDNs with optional port numbers as necessary	N/A
	traf- fic_monitor.bootstrap_files	Use only the Traffic Monitors specified in local bootstrap files	false
	traf- fic_monitor.properties_monitor	Path to file: <code>traffic_monitor.properties</code> ; used internally to monitor the file for changes	/opt/ traffic_router/ traffic_monitor. properties
	traf- fic_monitor.properties_reload_period	The interval in milliseconds for Traffic Router to reparse and reload this configuration file	60000
dns.properties	dns.tcp.port	TCP port that Traffic Router will use for incoming DNS requests	53
	dns.tcp.backlog	Maximum length of the queue for incoming TCP connection requests	0
	dns.tcp.host	IP Address Traffic Router will listen on for incoming TCP DNS requests	0.0.0.0
	dns.udp.host	IP Address Traffic Router will listen on for incoming UDP DNS requests	0.0.0.0
	dns.udp.port	UDP port that Traffic Router will use for incoming DNS requests	53
	dns.max-threads	Maximum number of threads used to process incoming DNS requests	1000
	dns.queue-depth	Maximum number of threads allowed to queue when all workers threads are busy. To disable the queue, set to 0, or to allow an unlimited sized queue, set to -1.	1000
	dns.zones.dir	Path to automatically generated zone files for reference	/opt/ traffic_router/ var/ auto-zones
traf- fic_ops.properties	traf- fic_ops.username	Username with which to access the <i>Traffic Ops API</i> (must have the <i>admin Role</i>)	admin
	traf- fic_ops.password	Password for the user specified in <code>traffic_ops.username</code>	N/A
cache.properties	cache.geolocation_db_path	Full path to the local copy of a geographic IP mapping database (usually MaxMind's GeoIP2)	/opt/ traffic_router/ db/ GeoIP2-City. mmdb
	cache.geolocation_db_refresh_period	The interval in milliseconds for Traffic Router to wait between polling for changes to the GeoIP2 database	604800000
	cache.czmap_path	Full path to the local copy of the coverage zone file	/opt/ traffic_router/ db/czmap. json
170		Chapter 3. Administrator's Guide	
	cache.czmap_db_refresh_period	The interval in milliseconds for Traffic Router to	10800000

The Traffic Router Profile

Much of a Traffic Router’s configuration can be obtained through the *Parameters* on its *Profile*. The *Parameters* of a Traffic Router’s *Profile* that have meaning (others are just ignored) are detailed in the *The Parameters of a Traffic Router Profile*.

Name	Config File	Value Description
location	dns.zone	Location to store the DNS zone files in
location	http-log4j.properties	Location to find the log4j.properties fi
location	dns-log4j.properties	Location to find the dns-log4j.properti
location	geolocation.properties	Location to find the log4j.properties fi
CDN_name	rascal-config.txt	The human readable name of the CDN
CoverageZoneJsonURL	CRConfig.xml	The location (URL) where a <i>Coverage</i>
ecsEnable	CRConfig.json	Boolean value to enable or disable ED
geolocation.polling.url	CRConfig.json	The location (URL) where a geograph
geolocation.polling.interval	CRConfig.json	How often - in milliseconds - Traffic R
coveragezone.polling.interval	CRConfig.json	How often - in milliseconds - Traffic R
coveragezone.polling.url	CRConfig.json	The location (URL) where a <i>Coverage</i>
deepcoveragezone.polling.interval	CRConfig.json	How often - in milliseconds - Traffic R
deepcoveragezone.polling.url	CRConfig.json	The location (URL) where a <i>Deep Cov</i>
client.steering.forced.diversity	CRConfig.json	When this <i>Parameter</i> exists and is exa
strip.special.query.params	CRConfig.json	If “true”, Traffic Router will strip its sp
tld.soa.expire	CRConfig.json	The value for the “expire” field the Tra
tld.soa.minimum	CRConfig.json	The value for the minimum field the T
tld.soa.admin	CRConfig.json	The DNS Start of Authority administr
tld.soa.retry	CRConfig.json	The value for the “retry” field the Traf
tld.soa.refresh	CRConfig.json	The value for the “refresh” field the Tr
tld.ttls.NS	CRConfig.json	The TTL the Traffic Router DNS Serv
tld.ttls.SOA	CRConfig.json	The TTL the Traffic Router DNS Serv
tld.ttls.AAAA	CRConfig.json	The TTL the Traffic Router DNS Serv
tld.ttls.A	CRConfig.json	The TTL the Traffic Router DNS Serv
tld.ttls.DNSKEY	CRConfig.json	The TTL the Traffic Router DNS Serv
tld.ttls.DS	CRConfig.json	The TTL the Traffic Router DNS Serv
api.port	server.xml	The TCP port on which Traffic Router
api.cache-control.max-age	CRConfig.json	The value of the Cache-Control: m
api.auth.url	CRConfig.json	The URL of the authentication endpoi
consistent.dns.routing	CRConfig.json	Control whether <i>DNS-routed Delivery</i>
dnssec.enabled	CRConfig.json	Whether DNSSEC is enabled; this par
dnssec.zone.diffing.enabled	CRConfig.json	If DNSSEC is enabled, enabling this p
dnssec.rrsig.cache.enabled	CRConfig.json	If DNSSEC is enabled, enabling this p
dnssec.allow.expired.keys	CRConfig.json	Allow Traffic Router to use expired DN
dynamic.cache.primer.enabled	CRConfig.json	Allow Traffic Router to attempt to prin
dynamic.cache.primer.limit	CRConfig.json	Limit the number of permutations to p
edge.dns.limit	CRConfig.json	Integer that controls the default numbe

<i>Name</i>	<i>Config File</i>	<i>Value</i> Description
edge.dns.routing	CRConfig.json	Boolean flag to control whether edge r
edge.http.limit	CRConfig.json	Integer that controls the default numbe
edge.http.routing	CRConfig.json	Boolean flag to control whether edge r
keystore.maintenance.interval	CRConfig.json	The interval in seconds which Traffic I
keystore.api.url	CRConfig.json	The URL of the DNSSEC key manage
keystore.fetch.timeout	CRConfig.json	The timeout in milliseconds for reques
keystore.fetch.retries	CRConfig.json	The number of times Traffic Router wi
keystore.fetch.wait	CRConfig.json	The number of milliseconds Traffic Ro
signaturemanager.expiration.multiplier	CRConfig.json	Multiplier used in conjunction with a z
zonemanager.threadpool.scale	CRConfig.json	Multiplier used to determine the numb
zonemanager.cache.maintenance.interval	CRConfig.json	The interval in seconds on which Traff
zonemanager.dynamic.response.expiration	CRConfig.json	A duration (e.g.: “300s”) that defines l
zonemanager.dynamic.concurrencylevel	CRConfig.json	An integer that defines the size of the c
zonemanager.dynamic.initialcapacity	CRConfig.json	An integer that defines the initial size o
zonemanager.init.timeout	CRConfig.json	An integer that defines the number of m
DNSKEY.generation.multiplier	CRConfig.json	Used to determine when new DNSSEC
DNSKEY.effective.multiplier	CRConfig.json	Used when creating an effective date f

Deprecated since version ATCv4.0: The use of “CRConfig.xml” as a *Parameter* “*Config File*” *value* has no known meaning, and its use for configuring Traffic Router is deprecated. All configuration (?) that previously used that value should instead use the equivalent *Parameter* with the *Config File* value “CRConfig.json”.

Consistent Hashing

Traffic Router does special optimization for some requests to ensure that requests for specific content are consistently fetched from a small number (often exactly one, but dependent on *Initial Dispersion*) of *cache servers* - thus ensuring it stays “fresh” in the cache. This is done by performing “consistent hashing” on request paths (when HTTP routing) or names requested for resolution (when DNS routing). To an extent, this behavior is configurable by modifying fields on *Delivery Services*. Consistent hashing acts differently on a *Delivery Service* based on how *Delivery Services* of its *Type* route content.

- **HTTP, HTTP_NO_CACHE, HTTP_LIVE, HTTP_LIVE_NATNL, DNS, DNS_LIVE, and DNS_N**
These *Delivery Service Types* route directly to *cache servers*, so consistent hashing is used to choose a *cache server* to which the client will be redirected.
- **STEERING and CLIENT_STEERING** These *Delivery Service Types* route to “target” *Delivery Services*, so consistent hashing is used to choose a “target” which will service the client request.

See also:

See the [Wikipedia article on consistent hashing](#).

Consistent Hashing Patterns

New in version 4.0.

Regular expressions (“patterns”) can be provided in the *Consistent Hashing Regular Expression* field of an HTTP-*routed* Delivery Service to influence what parts of an HTTP request path are considered when performing consistent hashing. These patterns propagate to Traffic Router through *Snapshots*.

Important: Consistent Hashing Patterns on STEERING-*Type Delivery Services* will be used for Consistent Hashing - the Consistent Hashing Pattern(s) of said *Delivery Service*’s target(s) will **not** be considered. If Consistent Hashing Patterns are important to the routing of content on a STEERING-*Type* or CLIENT_STEERING-*Type Delivery Service*, they **must** be defined on that *Delivery Service* itself, and **not** on its target(s).

How it Works

The supplied *Consistent Hashing Regular Expression* is applied to the request path to extract matching elements to build a new string *before* consistent hashing is done. For example, using the pattern `/. *?(/.*?/). *?(m3u8)` and given the request paths `/test/path/asset.m3u8` and `/other/path/asset.m3u8` the resulting string used for consistent hashing will be `/path/m3u8`

See also:

See Oracle’s [documentation for the java.util.regex.Pattern](#) implementation in Java.

Testing Pattern-Based Consistent Hashing

In order to test this feature without affecting the delivery of traffic through a CDN, there are several test tools in place.

- **Traffic Router API** Several Traffic Router endpoints exist to test regular expression application against a request path, *cache server* selection, and *Delivery Service* selection.
- **Traffic Ops API** The *consistenthash* endpoint will proxy request data through to one of the Traffic Router endpoints in order to test regular expression application against a request path, in the event that direct access to the *Traffic Router API* is not possible and/or desired.
- **Traffic Portal** On the *Delivery Service* creation/modification form in Traffic Portal (under *Delivery Services*), there is a *Test Regex* section that the user can use to validate a regular expression before saving it to a *Delivery Service*.

Consistent Hash Query Parameters

Normally, when performing consistent hashing for an HTTP-routed *Delivery Service*, any query parameters present in the request are ignored. That is, if a client requests `/some/path?key=value` consistent hashing is only performed on the string `/some/path`. However, query parameters that are part of uniquely identifying content can be specified by adding them to the set of *Consistent Hashing Query Parameters* of a *Delivery Service*. For example, suppose that the file `/video.mp4` is available on the *origin server* in different resolutions, which are specified by the `resolution` query parameter. This means that `/video.mp4?resolution=480p` and `/video.mp4?resolution=720p` share a *request path*, but represent different *content*. In that case, adding `resolution` to the *Delivery Service's Consistent Hashing Query Parameters* will cause consistent hashing to be done on e.g. `/video.mp4?resolution=480p` instead of just `/video.mp4` - however if the client requests e.g. `/video.mp4?resolution=480p&bitrate=120kbps` consistent hashing will *only* consider `/video.mp4?resolution=480p`.

Note: *Consistent Hashing Patterns* are applied *before* query parameters are considered - i.e. a pattern cannot match against query parameters, and need not worry about query parameters contaminating matches.

Important: Consistent Hash Query Parameters on the *targets* of *STEERING-Type Delivery Services* will be used for Consistent Hashing - the Consistent Hash Query Parameters of said *Delivery Services* themselves will **not** be considered. If Consistent Hash Query Parameters are important to the routing of content on a *STEERING-Type* or *CLIENT_STEERING-Type Delivery Service*, they **must** be defined *on that Delivery Service's target(s)*, and **not** on the *Delivery Service itself*.

Caution: Certain query parameters are reserved by Traffic Router for its own use, and thus cannot be present in any Consistent Hash Query Parameters. These reserved parameters are:

- `trred`
- `format`
- `fakeClientIPAddress`

DNSSEC

See also:

[The Wikipedia page on Domain Name Security Extensions](#)

Overview

DNSSEC is a set of extensions to DNS that provides a cryptographic mechanism for resolvers to verify the authenticity of responses served by an authoritative DNS server. Several RFCs ([RFC 4033](#), [RFC 4044](#), [RFC 4045](#)) describe the low level details and define the extensions, [RFC 7129](#) provides clarification around authenticated denial of existence of records, and finally [RFC 6781](#) describes operational best practices for administering an authoritative DNSSEC-enabled DNS server. The authenticated denial of existence [RFC 7129](#) describes how an authoritative DNS server responds in NXDOMAIN and NODATA scenarios when DNSSEC is enabled. Traffic Router currently supports DNSSEC with NSEC (Next Secure Record), however, NSEC3 (Next Secure Record version 3) and more configurable options are planned for the future.

Operation

Upon startup or a configuration change, Traffic Router obtains keys from the ‘keystore’ API in Traffic Ops which returns KSK (Key Signing Key)s and ZSK (Zone Signing Key)s for each *Delivery Service* that is a sub-domain of the CDN’s TLD in addition to the keys for the CDN TLD itself. Each key has timing information that allows Traffic Router to determine key validity (expiration, inception, and effective dates) in addition to the appropriate TTL to use for the DNSKEY record(s). All TTLs are configurable *Parameters* in *The Traffic Router Profile*.

Once Traffic Router obtains the key data from the API, it converts each public key into the appropriate record types (DNSKEY, DS) to place in zones and uses the private key to sign zones. DNSKEY records are added to each *Delivery Service*’s zone (e.g.: `demo1.mycdn.ciab.test`) for every valid key that exists, in addition to the CDN TLD’s zone. A DS record is generated from each zone’s KSK and is placed in the CDN TLD’s zone (e.g.: `mycdn.ciab.test`); the DS record for the CDN TLD must be placed in its parent zone, which is not managed by Traffic Control.

The DNSKEY to DS record relationship allows resolvers to validate signatures across zone delegation points. With Traffic Control, we control all delegation points below the CDN’s TLD, **however, the DS record for the CDN TLD must be placed in the parent zone** (e.g.: `ciab.test`), **which is not managed by Traffic Control**. As such, the DS record must be placed in the parent zone prior to enabling DNSSEC, and prior to generating a new CDN KSK. Based on your deployment’s DNS configuration, this might be a manual process or it might be automated. Either way, extreme care and diligence must be taken and knowledge of the management of the upstream zone is imperative for a successful DNSSEC deployment.

To enable DNSSEC for a CDN in Traffic Portal, Go to *CDNs* from the sidebar and click on the desired CDN, then toggle the ‘DNSSEC Enabled’ field to ‘true’, and click on the green *Update* button to save the changes.

Rolling Zone Signing Keys

Traffic Router currently follows the ZSK pre-publishing operational best practice described in [RFC 6781#section-4.1.1.1](#). Once DNSSEC is enabled for a CDN in Traffic Portal, key rolls are triggered by Traffic Ops via the automated key generation process, and Traffic Router selects the active ZSKs based on the expiration information returned from the ‘keystore’ API of Traffic Ops.

Edge Traffic Routing

Overview

Edge Traffic Routing is a feature that enables localization for more DNS record types than just the routing name for DNS delivery services. This feature has two main components: localization of HTTP delivery service routing names and localization for CDN-managed NS records. This allows Traffic Router to scale horizontally more easily, as there is a practical limit to how many records can be in an RRset for NS, A, or AAAA record types. The practical limit is typically an answer size exceeding 512 bytes; we have observed issues where some clients and/or resolvers do not honor larger answer responses, while in some cases, resolvers are unable to use TCP for larger responses. Additionally, this feature allows Traffic Router to serve an RRset containing only Traffic Routers that are near the client (resolver), placing more control over which Traffic Routers a given resolver or client will interact with.

Localizing NS records reduces latency for the resolver, which, due to caching in DNS is of little utility for NS records, but it will force resolvers to use the closest Traffic Routers for all queries. This is important for lookups of CDN routing name records that have very short TTLs, meaning DNS traffic for routing name records is frequent. Like localization for routing names of DNS delivery services, localizing the routing name for HTTP delivery services provides the client (end user) with a list of Traffic Routers that are physically close, reducing latency when the client moves from DNS resolution to the HTTP connection to Traffic Router for the 302 redirect to the edge cache. This feature reduces latency between a resolver and Traffic Router, reduces latency for the client’s HTTP request to Traffic Router, and allows Traffic Control to dictate which Traffic Routers are used in any given location when a client can be localized.

Edge DNS Routing

Edge DNS routing refers to the localization of NS records in Traffic Router. This can be turned on and off via the `edge.dns.routing` parameter; the number of records returned is controlled via `edge.dns.limit` and there is a hardcoded default limit of 4 when this feature is enabled. See [The Traffic Router Profile](#) documentation for parameter details.

Edge HTTP Routing

Edge HTTP routing refers to the localization of A and AAAA records that represent routing names for HTTP delivery services. This can be turned on and off via the `edge.http.routing` parameter; the number of records returned is controlled via `edge.http.limit` and there is a hardcoded default limit of 4 when this feature is enabled. The default or global limit can be overridden by modifying the `maxDnsAnswers` setting on the delivery service. See *The Traffic Router Profile* documentation for parameter details.

Edge Traffic Router Selection

Traffic Router performs localization on client requests in order to determine which Traffic Routers should service a given request. After localization, Traffic Router will perform a consistent hash on the incoming name and will use the value to refine Traffic Router selection. There are two main cases for Traffic Router selection: a localization hit, and a localization miss.

Localization Hit: Consistent Hash (CH)

When a client is localized, Traffic Router selects the nearest Traffic Router Location (cachegroup) based on proximity. Proximity is determined by using the latitude and longitude of the client, regardless of whether it is a coverage zone or geolocation hit, and the latitude and longitude specified on Traffic Router Locations. Once the location is identified, a consistent hash is performed on the incoming name and the list of Traffic Routers is ordered based upon the consistent hash. Once ordered, the list is limited to the appropriate number based on the limit parameter specified by the hardcoded default (4), `edge.dns.limit`, `edge.http.limit`, or `maxDnsAnswers`, depending on the configuration and request being localized. This approach can be thought of as the consistent hash (CH) selection process.

Localization Miss: Consistent Hash + Round Robin (CH + RR)

When a client cannot be localized, Traffic Router still needs to produce a list of Traffic Routers to service the request. Because the number of Traffic Routers in the CDN could far exceed the practical limits of what constitutes a “normal” sized answer, a selection algorithm is applied to select Traffic Routers. Much like the localization hit scenario, the incoming request name is consistent hashed and results size is limited by the same parameters. Because no client location is known, Traffic Router must distribute the load across all Traffic Router Locations. To distribute the load, Traffic Router will order all Traffic Routers at each location based on the consistent hash, selecting a Traffic Router at the *n*th position, incrementing the index, *n*, after iterating over all locations.

For example, with four Traffic Router Locations each containing 10 Traffic Routers and a limit of 6, the algorithm would:

- Consistent hash the incoming name
- Order the Traffic Routers at each location by the consistent hash

- Select the Traffic Router at the first position of each location
- Select the Traffic Router at the second position of each location, stopping after selecting the 6th Traffic Router

Because the algorithm employs consistent hashing, the answers should be consistent as long as the topology remains the same. This approach can be thought of as the consistent hash round robin (CH + RR) selection process.

Example Request Flow

The following is an example of the request flow when a client requests the routing name for an example delivery service, `tr.service.cdn.example.com`. The request flow assumes that the resolver is cold and has yet to build a local cache of lookups, meaning it has to walk the domain hierarchy asking for NS records until it reaches `service.cdn.example.com`. This example starts after the resolver has determined which name servers are authoritative for `cdn.example.com`. Note that the same logic is applied for each of the three queries made by the resolver.

Troubleshooting and log files

Traffic Router log files can be found under `/opt/traffic_router/var/log` and `/opt/tomcat/logs`. Initialization and shutdown logs are in `/opt/tomcat/logs/catalinadata.out`. Application related logging is in `/opt/traffic_router/var/log/traffic_router.log`, while access logs are written to `/opt/traffic_router/var/log/access.log`.

Event Log File Format

Summary

All access events to Traffic Router are logged to the file `/opt/traffic_router/var/log/access.log`. This file grows up to 200MB and gets rolled into older log files, ten log files total are kept (total of up to 2GB of logged events per Traffic Router instance)

Traffic Router logs access events in a format that largely follows ATS [event logging format](#).

Message Format

- Except for the first item, each event that is logged is a series of space-separated key/value pairs.
- The first item is always the Unix epoch in seconds with a decimal field precision of up to milliseconds.
- Each key/value pair is in the form of `unquoted_string="optionally quoted string"`




Fig. 21: Example Request Flow for Edge Traffic Routing. Note this picks up when the resolver hits the CDN managed domain.

- Values that are quoted strings may contain whitespace characters.
- Values that are not quoted should not contains any whitespace characters.

Note: Any value that is a single dash character or a dash character enclosed in quotes represents an empty value

Table 56: Fields Always Present

Name	Description	Data
qtype	Whether the request was for DNS or HTTP	Always “DNS” or “HTTP”
chi	The IP address of the requester	Depends on whether this was a DNS or HTTP request, see other sections
rhi	The IP address of the request source address	Depends on whether this was a DNS or HTTP request, see other sections
ttms	The amount of time in milliseconds it took Traffic Router to process the request	A number greater than or equal to zero
rtype	Routing result type	One of ERROR, CZ, DEEP_CZ, GEO, MISS, STATIC_ROUTE, DS_REDIRECT, DS_MISS, INIT, FED
rloc	GeoLocation of result	Latitude and longitude in degrees as floating point numbers
rdtl	Result details Associated with unusual conditions	One of DS_NOT_FOUND, DS_NO_BYPASS, DS_BYPASS, DS_CZ_ONLY, DS_CZ_BACKUP_CG
rerr	Message about an internal Traffic Router error	String

See also:

If [Regional Geo-Blocking](#) is enabled on the *Delivery Service*, an additional field (rgb) will appear.

Sample Message

Items within brackets are detailed under the HTTP and DNS sections

53: Example Logfile Lines

```
144140678.000 qtype=DNS chi=192.168.10.11 rhi=- ttms=789 [Fields
→Specific to the DNS request] rtype=CZ rloc="40.252611,58.439389"
→rdtl=- rerr="-" [Fields Specific to the DNS result]
144140678.000 qtype=HTTP chi=192.168.10.11 rhi=- ttms=789 [Fields
→Specific to the HTTP request] rtype=GEO rloc="40.252611,58.439389"
→rdtl=- rerr="-" [Fields Specific to the HTTP result]
```

Note: These samples contain fields that are always present for every single access event to Traffic Router

rtype Meanings

- The request was not redirected. This is usually a result of a DNS request to the Traffic Router or an explicit denial for that request

ANON_BLOCK The client's IP matched an *Anonymous Blocking* rule and was blocked

CZ The result was derived from Coverage Zone data based on the address in the `chi` field

DEEP_CZ The result was derived from Deep Coverage Zone data based on the address in the `chi` field

DS_MISS **HTTP Only** No HTTP *Delivery Service* supports either this request's URL path or headers

DS_REDIRECT The result is using the Bypass Destination configured for the matched *Delivery Service* when that *Delivery Service* is unavailable or does not have the requested resource

ERROR An internal error occurred within Traffic Router, more details may be found in the `rerr` field

FED **DNS Only** The result was obtained through federated coverage zone data outside of any *Delivery Services*

GEO The result was derived from geolocation service based on the address in the `chi` field

GEO_REDIRECT The request was redirected based on the National Geo blocking (Geo Limit Redirect URL) configured on the *Delivery Service*

GEO_DS The request was redirected to the Miss Location configured on the *Delivery Service*, because CZF couldn't resolve the client IP, and Maxmind returned the default coordinates of the country code of the client IP

MISS Traffic Router was unable to resolve a DNS request or find a cache for the requested resource

RGALT The request was redirected to the *Regional Geo-Blocking* URL. Regional Geo blocking is enabled on the *Delivery Service* and is configured through the `regional_geoblock.polling.url` *Parameter* on the Traffic Router *Profile*

RGDENY **DNS Only** The result was obtained through federated coverage zone data outside of any *Delivery Service* - the request was regionally blocked because there was no rule for the request made

STATIC_ROUTE **DNS Only** No DNS *Delivery Service* supports the hostname portion of the requested URL

rdt1 Meanings

- The request was not redirected. This is usually a result of a DNS request to the Traffic Router or an explicit denial for that request

DS_BYPASS Used a bypass destination for redirection of the *Delivery Service*

DS_CLIENT_GEO_UNSUPPORTED Traffic Router did not find a resource supported by coverage zone data and was unable to determine the geographic location of the requesting client

DS_CZ_BACKUP_CG Traffic Router found a backup cache via fall-back (through the edgeLocation field of a *Snapshot*) or via coordinates (*Coverage Zone File*) configuration

DS_CZ_ONLY The selected *Delivery Service* only supports resource lookup based on coverage zone data

DS_NO_BYPASS No valid bypass destination is configured for the matched *Delivery Service* and the *Delivery Service* does not have the requested resource

DS_NOT_FOUND Always goes with rtypes STATIC_ROUTE and DS_MISS

GEO_NO_CACHE_FOUND Traffic Router could not find a resource via geographic location data based on the requesting client's location

NO_DETAILS This entry is for a standard request

REGIONAL_GEO_ALTERNATE_WITHOUT_CACHE This goes with the rtype RGDENY. The URL is being regionally blocked

REGIONAL_GEO_NO_RULE The request was blocked because there was no rule in the *Delivery Service* for the request

HTTP Specifics

54: Sample Message

```
1452197640.936 qtype=HTTP chi=69.241.53.218 rhi=- url="http://foo.mm-
→test.jenkins.cdnlab.comcast.net/some/asset.m3u8" cqhm=GET cqhv=HTTP/
→1.1 rtype=GEO rloc="40.252611,58.439389" rdtl=- rerr="-" pssc=302.
→ttms=0 rurl="http://odol-atsec-sim-114.mm-test.jenkins.cdnlab.
→comcast.net:8090/some/asset.m3u8" rh="Accept: */*" rh="myheader:
→asdadasdasfasg"
```

Table 57: Request Fields

Name	Description	Data
url	Requested URL with query string	A URL String
cqhm	Http Method	e.g GET, POST
cqhvh	Http Protocol Version	e.g. HTTP/1.1
rh	One or more of these key value pairs may exist in a logged event and are controlled by the configuration of the matched <i>Delivery Service</i> Key/value pair of the format name : value	

Table 58: Response Fields

Name	Description
rurl	The resulting URL of the resource requested by the client

DNS Specifics

55: Sample Message

```
144140678.000 qtype=DNS chi=192.168.10.11 rhi=- ttms=123 xn=65535
→fqdn=www.example.com. type=A class=IN ttl=12345 rcode=NOERROR
→rtype=CZ rloc="40.252611,58.439389" rdtl=- rerr="-" ans="192.168.1.2
→192.168.3.4 0:0:0:0:0:ffff:c0a8:102 0:0:0:0:0:ffff:c0a8:304"
```

Table 59: Request Fields

Name	Description	Data
xn	The ID from the client DNS request header	a whole number between 0 and 65535 (inclusive)
rhi	The IP address of the resolver when EDNS0 client subnet extensions are enabled.	An IPv4 or IPv6 string, or dash if request is for resolver only and no client subnet is present
fqdn	The qname field from the client DNS request message (i.e. the FQDN the client is requesting be	A series of DNS labels/domains separated by ‘.’ characters and ending with a ‘.’ character
type	The qtype field from the client DNS request message (i.e. the type of resolution that’s requested such as IPv4, IPv6)	Examples are A (IPv4), AAAA (IPv6), NS (Name Service), SOA, and CNAME, (see qtype)
class	The qclass field from the client DNS request message (i.e. the class of resource being requested)	Either IN (Internet resource) or ANY (Traffic Router rejects requests with any other value of class)

Table 60: Response Fields

Name	Description	Data
ttl	The ‘time to live’ in seconds for the answer provided by Traffic Router (clients can reliably use this answer for this long without re-querying traffic router)	A whole number between 0 and 4294967295 (inclusive)
rcode	The result code for the DNS answer provided by Traffic Router	One of NOERROR (success), NOTIMP (request is not NOTIMP (request is not supported), REFUSED (request is refused to be answered), or NXDOMAIN (the domain/name requested does not exist)

Deep Caching

Overview

Deep Caching is a feature that enables clients to be routed to the closest possible “deep” Edge-tier *cache servers* on a per-*Delivery Service* basis. The term “deep” is used in the networking sense, meaning that the Edge-tier *cache servers* are located deep in the network where the number of network hops to a client is as minimal. This deep caching topology is desirable because storing content closer to the client gives better bandwidth savings, and sometimes the cost of bandwidth usage in the network outweighs the cost of adding storage. While it may not be feasible to cache an entire copy of the CDN’s contents in every deep location (for the best possible bandwidth savings), storing just a relatively small amount of the CDN’s most requested content can lead to very high bandwidth savings.

What You Need

1. Edge cache deployed in “deep” locations and registered in Traffic Ops
2. A *Deep Coverage Zone File* mapping these deep cache hostnames to specific network prefixes
3. Deep caching *Parameters* in the Traffic Router *Profile*
 - `deepcoveragezone.polling.interval`
 - `deepcoveragezone.polling.url`

See also:

See *The Traffic Router Profile* for details.

4. Deep Caching enabled on one or more HTTP *Delivery Services* (i.e. ‘Deep Caching’ field on the *Delivery Service* details page (under *Advanced Options*) set to **ALWAYS**)

How it Works

Deep Coverage Zone routing is very similar to that of regular Coverage Zone routing, except that the DCZF (Deep Coverage Zone File) is preferred over the regular CZF (Coverage Zone File) for *Delivery Services* with Deep Caching enabled. If the client requests a Deep Caching-enabled *Delivery Service* and their IP address gets a “hit” in the DCZF, Traffic Router will attempt to route that client to one of the available “deep” *cache servers* in the client’s corresponding zone. If there are no “deep” *cache servers* available for a client’s request, Traffic Router will fall back to the regular CZF and continue regular CZF routing from there.

Steering Feature

Overview

A Steering *Delivery Service* is a *Delivery Service* that is used to route a client to another *Delivery Service*. The *Type* of a Steering *Delivery Service* is either STEERING or CLIENT_STEERING. A Steering *Delivery Service* will have target *Delivery Services* configured for it with weights assigned to them. Traffic Router uses the weights to make a consistent hash ring which it then uses to make sure that requests are routed to a target based on the configured weights. This consistent hash ring is separate from the consistent hash ring used in cache selection.

Special regular expressions - referred to as ‘filters’ - can also be configured for target *Delivery Services* to pin traffic to a specific *Delivery Service*. For example, if the filter `.*news/.*` for a target called `target-ds-1` is created, any requests to Traffic Router with “news” in them will be routed to `target-ds-1`. This will happen regardless of the configured weights.

Some other points of interest

- Steering is currently only available for HTTP *Delivery Services* that are a part of the same CDN.
- A new role called STEERING has been added to the Traffic Ops database. Only users with the Steering *Role* or higher can modify steering assignments for a *Delivery Service*.
- Traffic Router uses the steering endpoints of the *Traffic Ops API* to poll for steering assignments, the assignments are then used when routing traffic.

A couple simple use-cases for Steering are:

- Migrating traffic from one *Delivery Service* to another over time.
- Trying out new functionality for a subset of traffic with an experimental *Delivery Service*.
- Load balancing between *Delivery Services*

The Difference Between STEERING and CLIENT_STEERING

The only difference between the STEERING and CLIENT_STEERING *Delivery Service Types* is that CLIENT_STEERING explicitly allows a client to bypass Steering by choosing a destination *Delivery Service*. A client can accomplish this by providing the X-TC-Steering-Option HTTP header with a value of the `xml_id` of the target *Delivery Service* to which they desire to be routed. When Traffic Router receives this header it will route to the requested target *Delivery Service* regardless of weight configuration. This header is ignored by STEERING *Delivery Services*.

Configuration

The following needs to be completed for Steering to work correctly:

1. Two target *Delivery Services* are created in Traffic Ops. They must both be HTTP *Delivery Services* part of the same CDN.
2. A *Delivery Service* with type STEERING or CLIENT_STEERING is created in Traffic Portal.
3. Target *Delivery Services* are assigned to the Steering *Delivery Service* using Traffic Portal.
4. A user with the role of Steering is created.
5. The Steering user assigns weights to the target *Delivery Services*.
6. If desired, the Steering user can create filters for the target *Delivery Services*.

See also:

For more information see *Configure Delivery Service Steering*.

HTTPS for HTTP Delivery Services

New in version 1.7: Traffic Router now has the ability to allow HTTPS traffic between itself and clients on a per-HTTP *Delivery Service* basis.

Note: As of version 3.0 Traffic Router has been integrated with native OpenSSL. This makes establishing HTTPS connections to Traffic Router much less expensive than previous versions. However establishing an HTTPS connection is more computationally demanding than an HTTP connection. Since each client will in turn get redirected to an ATS instance, Traffic Router is most always creating a new HTTPS connection for all HTTPS traffic. It is likely to mean that an existing Traffic Router may have some decrease in performance if you wish to support a lot of HTTPS traffic. As noted for DNSSEC, you may need to plan to scale Traffic Router vertically and/or horizontally to handle the new load.

The HTTPS set up process is:

1. Select one of '1 - HTTPS', '2 - HTTP AND HTTPS', or '3 - HTTP TO HTTPS' for the *Delivery Service*
2. Generate private keys for the *Delivery Service* using a wildcard domain such as *.my-delivery-service.my-cdn.example.com
3. Obtain and import signed certificate chain
4. Perform a CDN *Snapshot*

Clients may make HTTPS requests to *Delivery Services* only after the CDN *Snapshot* propagates to Traffic Router and it receives the certificate chain from Traffic Ops.

Protocol Options

HTTP Any secure client will get an SSL handshake error. Non-secure clients will experience the same behavior as prior to 1.7

HTTPS Traffic Router will only redirect (send a 302 Found response) to clients communicating with a secure connection, all other clients will receive a 503 Service Unavailable response

HTTP AND HTTPS Traffic Router will redirect both secure and non-secure clients

HTTP TO HTTPS Traffic Router will redirect non-secure clients with a 302 Found response and a location that is secure (i.e. an `https://` URL instead of an `http://` URL), while secure clients will be redirected immediately to an appropriate target or *cache server*.

Certificate Retrieval

Warning: If you have HTTPS *Delivery Services* in your CDN, Traffic Router will not accept **any** connections until it is able to fetch certificates from Traffic Ops and load them into memory. Traffic Router does not persist certificates to the Java Keystore or anywhere else.

Traffic Router fetches certificates into memory:

- At startup time
- When it receives a new CDN *Snapshot*
- Once an hour starting whenever the most recent of the last of the above occurred

Note: To adjust the frequency at which Traffic Router fetches certificates add the *Parameter* `certificates.polling.interval` with the ConfigFile “CRConfig.json” and set it to the desired duration in milliseconds.

Note: Taking a CDN *Snapshot* may be used at times to avoid waiting the entire polling cycle for a new set of certificates.

Warning: If a CDN *Snapshot* is taken that involves a *Delivery Service* missing its certificates, Traffic Router will ignore **ALL** changes in that CDN *Snapshot* until one of the following occurs:

- It receives certificates for that *Delivery Service*
- Another CDN *Snapshot* is taken and the *Delivery Service* without certificates is changed such that its HTTP protocol is set to ‘http’

Certificate Chain Ordering

The ordering of certificates within the certificate bundle matters. It must be:

1. Primary Certificate (e.g. the one created for `*.my-delivery-service.my-cdn.example.com`)
2. Intermediate Certificate(s)
3. Root Certificate from a CA (optional)

Warning: If something is wrong with the certificate chain (e.g. the order of the certificates is backwards or for the wrong domain) the client will get an SSL handshake. Inspection of `/opt/tomcat/logs/catalina.log` is likely to yield information to reveal this.

To see the ordering of certificates you may have to manually split up your certificate chain and use `openssl(1ssl)` on each individual certificate

Automatic Certificate Management Environment

Automatic Certificate Management Environment (ACME) is a protocol for automatically generating, renewing, and revoking SSL certificates. Currently, ACME can be used through [Let's Encrypt](#) or through [External Account Binding](#).

External Account Binding

External account binding allows the user to use an existing account with an ACME provider to obtain, renew, and revoke SSL certificates. To use this functionality, fill in the fields in `cdn.conf` for the ACME provider with which the account is set up. The first time this is used for a specific ACME provider (defined by the `acme_provider` and `user_email` fields) the information will be used to get a private key and account URL from the ACME provider and register the account. These will be stored for later use. External account binding information can only be used once, so after the first time, the private key and URL will be used.

Important: The `acme_provider` and `user_email` combination must be unique. The `acme_provider` field must correlate to the `AuthType` field for each certificate to be renewed using that provider.

External account binding can be set up through `cdn.conf` by updating the following fields:

Table 61: Fields to update for external account binding using ACME protocol under *acme_accounts*

Name	Type	Re- quired	Description
acme_provider	string	Yes	The certificate provider. This field needs to correlate to the AuthType field for each certificate so the renewal functionality knows which provider to use.
user_email	string	Yes	The email used to set up the account with the provider.
acme_url	string	Yes	The URL for the ACME.
kid	string	No	The key ID provided by the ACME provider for external account binding.
hmac_encoded	string	No	The HMAC key provided by the ACME provider for external account binding. This should be in Base64 URL encoded.

Note: The *kid* and *hmac_encoded* fields are required unless the account has already been registered and the information has been stored in the Traffic Ops Database.

Let's Encrypt

Let's Encrypt is a free, automated CA using ACME protocol. Let's Encrypt performs a domain validation before issuing or renewing a certificate. There are several options for domain validation but for this application the DNS challenge is used in order to receive wildcard certificates. Let's Encrypt sends a token to be used as a TXT record at `_acme-challenge.domain.example.com` and after verifying that the token is accessible there, will return the newly generated and signed certificate and key. The basic workflow implemented is:

1. POST to Let's Encrypt and receive the DNS challenge token.
2. Traffic Ops stores the DNS challenge.
3. Traffic Router has a watcher which checks with Traffic Ops for any new challenges or deleted challenges.
4. When a new record appears, Traffic Router temporarily adds a static route for the specified *Delivery Service* with the token from Let's Encrypt at `_acme-challenge.domain.example.com`.
5. Let's Encrypt continuously attempts to resolve it as a TXT record to verify ownership of the domain.

Note: DNSSEC should be turned on for any CDN using Let's Encrypt to guard against a 'Man in the Middle' interference with this transaction.

1. Let's Encrypt returns the signed certificate and key to Traffic Ops.

2. Traffic Ops stores the certificate and key in Traffic Vault and removes the DNS challenge record.
3. The Traffic Router watcher removes the TXT record.

Let's Encrypt can be set up through *cdn.conf* by updating the following fields:

Table 62: Fields to update for Let's Encrypt under *lets_encrypt*

Name	Type	Re- quired	Description
user_email	string	Yes	Email to create account with Let's Encrypt or to receive expiration updates. If this is not included then <i>rate limits</i> may apply for the number of certificates.
send_expiration_email	boolean	No	Option to send email summarizing certificate expiration status
convert_self_signed	boolean	No	Option to convert self signed to Let's Encrypt certificates as they expire. Only works for certificates labeled as Self Signed in the Certificate Source field.
re-new_days_before_expiration	int	No	Number of days before expiration date to renew certificates
environment	string	No	Let's Encrypt environment to use. Options are 'staging' or 'production'. Defaults to 'production'.

Automatic Certificate Renewal

If desired, an automated certificate renewal script is located at `/traffic_ops/etc/cron.d/autorenew_certs`. This job is setup to be run, but the file must be updated with the username and password for Traffic Ops in order to be run. In *cdn.conf* the following fields can be defined in order to alter the number of days in advance to renew and send a summary email after renewal.

Note: In order for this to work, the AuthType field for the certificate must match the ACME provider in the *cdn.conf*.

Important: After the automatic renewal script has run, a queue and snapshot must be run manually in order for the certificates to be used.

Table 63: Fields to update to run the automatic renewal script under *acme_renewal*:

Name	Type	Re- quired	Description
summary_email	boolean	No	The email address to use for summarizing certificate expiration and renewal status. If it is blank, no email will be sent.
re-new_days_before_expiration	int	No	Number of days before expiration date to renew certificates. Default is 30 days.

Table 64: Fields to update for sending emails under *smtp*

Name	Type	Description
enabled	boolean	Enable sending emails through Simple Mail Transfer Protocol (SMTP)
user	string	User for SMTP server access
pass-word	string	Password for SMTP server access
address	string	SMTP server address including port

Suggested Way of Setting up an HTTPS Delivery Service With Let's Encrypt Automation

Assuming you have already created a *Delivery Service* which you plan to modify to use HTTPS, do the following in Traffic Portal:

1. Select one of '1 - HTTPS', '2 - HTTP AND HTTPS', or '3 - HTTP TO HTTPS' for the protocol field of a *Delivery Service* and click the *Update* button
2. Go to *More* → *Manage SSL Keys*
3. Click on *More* → *Generate SSL Keys*
4. Click on the *Use Let's Encrypt* slider, click on the green *Generate Keys* button, then confirm that you want to make these changes
5. Take a new CDN *Snapshot*

Once this is done you should be able to verify that you are being correctly redirected by Traffic Router using e.g. `curl (1)` commands to HTTPS destinations on your *Delivery Service*.

Suggested Way of Setting up an HTTPS Delivery Service With Certificate Authority

Assuming you have already created a *Delivery Service* which you plan to modify to use HTTPS, do the following in Traffic Portal:

1. Select one of '1 - HTTPS', '2 - HTTP AND HTTPS', or '3 - HTTP TO HTTPS' for the protocol field of a *Delivery Service* and click the *Update* button
2. Go to *More* → *Manage SSL Keys*
3. Click on *More* → *Generate SSL Keys*
4. Fill out the form and click on the green *Generate Keys* button, then confirm that you want to make these changes
5. Copy the contents of the Certificate Signing Request field and save it locally
6. Go back and select 'HTTP' for the protocol field of the *Delivery Service* and click *Save* (to avoid preventing other CDN *Snapshot* updates from being blocked by Traffic Router)
7. Follow your standard procedure for obtaining your signed certificate chain from a CA

8. After receiving your certificate chain import it into Traffic Ops
9. Edit the *Delivery Service*
10. Restore your original choice for the protocol field and click *Save*
11. Click *More* → *Manage SSL Keys*
12. Paste your key information into the appropriate fields
13. Click the green *Update Keys* button
14. Take a new CDN *Snapshot*

Once this is done you should be able to verify that you are being correctly redirected by Traffic Router using e.g. `curl(1)` commands to HTTPS destinations on your *Delivery Service*.

Router Load Testing

The Traffic Router load testing tool is located in the [Traffic Control repository under test/router](#). It can be used to simulate a mix of HTTP and HTTPS traffic for a CDN by choosing the number of HTTP *Delivery Services* and the number HTTPS *Delivery Service* the test will exercise.

There are 2 parts to the load test:

- A web server that makes the actual requests and takes commands to fetch data from the CDN, start the test, and return current results.
- A web page that's used to run the test and see the results.

Running the Load Tests

1. First, clone the [Traffic Control repository](#).
2. You will need to make sure you have a CA file on your machine
3. The web server is a Go program, set your GOPATH environment variable appropriately (we suggest \$HOME/go or \$HOME/src)
4. Open a terminal emulator and navigate to the `test/router/server` directory inside of the cloned repository
5. Execute the server binary by running `go run server.go`
6. Using your web browser of choice, open the file `test/router/index.html`
7. Authenticate against a Traffic Ops host - this should be a nearly instantaneous operation - you can watch the output from `server.go` for feedback
8. Enter the Traffic Ops host in the second form and click the button to get a list of CDN's
9. Wait for the web page to show a list of CDN's under the above form, this may take several seconds
10. The List of CDN's will display the number of HTTP- and HTTPS-capable *Delivery Services* that may be exercised

11. Choose the CDN you want to exercise from the drop-down menu
12. Fill out the rest of the form, enter appropriate numbers for each HTTP and HTTPS *Delivery Services*
13. Click *Run Test*
14. As the test runs the web page will occasionally report results including running time, latency, and throughput

Tuning Recommendations

The following is an example of the command line parameters set in `/opt/traffic_router/conf/startup.properties` that has been tested on a multi-core server running under HTTPS load test requests. This is following the general recommendation to use the G1 garbage collector for JVM (Java Virtual Machine) applications running on multi-core machines. In addition to using the G1 garbage collector the `InitiatingHeapOccupancyPercent` was lowered to run garbage collection more frequently which improved overall throughput for Traffic Router and reduced ‘Stop the World’ garbage collection. Note that any environment variable settings in this file will override those set in `/lib/systemd/system/traffic_router.service`.

56: Example CATALINA_OPTS Configuration

```
CATALINA_OPTS="\
-server -Xms2g -Xmx8g \
-Dlog4j.configuration=file://$CATALINA_BASE/conf/log4j.properties \
-Djava.library.path=/usr/lib64 \
-XX:+UseG1GC \
-XX:+UnlockExperimentalVMOptions \
-XX:InitiatingHeapOccupancyPercent=30"
```

3.1.7 Traffic Router - Migrating to 3.0

Contents

- *Traffic Router - Migrating to 3.0*
 - *Release Notes v3.0*
 - *System Requirements*
 - *Upgrade Procedure*
 - *Development Environment Upgrade*

Release Notes v3.0

- Replaced custom Java SNI (Server Name Indication) implementation with a native implementation using tomcat-native, APR (Apache Portable Runtime) and OpenSSL. This should significantly improve the performance of routing HTTPS *Delivery Services*.

See also:

[The Server Name Indication Wikipedia page](#), [The Apache Portable Runtime project site](#) and/or [the OpenSSL project site](#)

- Upgraded to Tomcat 8.5.30
- Separated the Traffic Router installation from the Tomcat deployment and created a new ‘tomcat’ package for installing Tomcat. Traffic Router and Tomcat can now be upgraded independently
- Converted Traffic Router to a *systemd(1)* service
- Modified the development test and deployment processes to be more consistent with production

System Requirements

- Centos 7.9 or CentOS 8.2
- OpenSSL >= 1.0.2 installed
- JDK >= 8.0 installed or available in an accessible *yum(8)* repository
- APR >= 1.4.8-3 installed or available in an accessible *yum(8)* repository
- Tomcat Native >= 1.2.16 installed or available in an accessible *yum(8)* repository
- tomcat >= 8.5-30 installed or available in an accessible *yum(8)* repository (This package is created automatically by the Traffic Router build process)

Upgrade Procedure

- upload the `dist/tomcat-version string.rpm` file generated as a part of the build instructions outlined in *Building Traffic Control* to an accessible *yum(8)* repository
- update the `traffic_router` package with *yum(8)*
- restore property files

Upload tomcat.rpm

The `term-version string.rpm` package should have been created when Traffic Router was built according to the instructions in *Building Traffic Control*. It must either be added to an accessible `yum(8)` repository, or manually copied to the servers where Traffic Router will be installed. It is generally better that it be added to a `yum(8)` repository because then it will be installed automatically when Traffic Router is updated.

Update the traffic_router Package

If `openssl`, `apr`, `tomcat-native`, `java-1.8.0-openjdk`, `java-1.8.0-openjdk-devel` and `tomcat_tr` packages are all in an available `yum(8)` repository then an upgrade can be performed by running `yum update traffic_router` as the root user or with `sudo(8)`. This will first cause the `apr`, `tomcat-native`, `java-1.8.0-openjdk`, `java-1.8.0-openjdk-devel` and `tomcat` packages to be installed. When the `tomcat` package runs, it will cause any older versions of `traffic_router` or `tomcat` to be uninstalled. This is because the previous versions of the `traffic_router` package included an untracked installation of `tomcat`.

Restore Property Files

The install process does not override or replace any of the files in the `/opt/traffic_router/conf` directory. Previous versions of the `traffic_ops.properties`, `traffic_monitor.properties` and `startup.properties` should still be good. On a new install replace the Traffic Router properties files with the correct ones for the CDN.

Development Environment Upgrade

If a development environment is already set up for the previous version of Traffic Router, then `openssl`, `apr` and `tomcat-native` will need to be manually installed with `yum(8)` or `rpm(8)`. Also, whenever either `mvn clean verify` or `TrafficRouterStart` is/are run, the location of the `tomcat-native` libraries will need to be made known to the JVM via command line arguments.

57: Example Commands Specifying a Path to the tomcat-native Library

```
mvn clean verify -Djava.library.path=[tomcat native library path on  
→your box]  
java -Djava.library.path=[tomcat native library path on your box]  
→TrafficRouterStart
```

3.1.8 Traffic Stats Administration

Traffic Stats consists of three separate components: Traffic Stats, InfluxDB, and Grafana. See below for information on installing and configuring each component as well as configuring the integration between the three and Traffic Ops.

Installation

Installing Traffic Stats

- See the [downloads](#) page for Traffic Control to get the latest release.
- Follow the instructions in *Building Traffic Control* to generate an RPM.
- Copy the RPM to your server
- Install the generated Traffic Stats RPM with *yum(8)* or *rpm(8)*

Installing InfluxDB

In order to store Traffic Stats data you will need to install [InfluxDB](#). While not required, it is recommended to use some sort of high availability option like [Influx enterprise](#), [InfluxDB Relay](#), or another [high availability option](#).

Installing Grafana

Grafana is used to display Traffic Stats/InfluxDB data in Traffic Ops. Grafana is typically run on the same server as Traffic Stats but this is not a requirement. Grafana can be installed on any server that can access InfluxDB and can be accessed by Traffic Ops. Documentation on installing Grafana can be found on the [Grafana website](#).

Configuration

Configuring Traffic Stats

Traffic Stats's configuration file can be found in `/opt/traffic_stats/conf/traffic_stats.cfg`. The following values need to be configured:

toUser The user used to connect to Traffic Ops

toPasswd The password to use when connecting to Traffic Ops

toUrl The URL of the Traffic Ops server used by Traffic Stats

influxUser The user to use when connecting to InfluxDB (if configured on InfluxDB, else leave default)

influxPassword That password to use when connecting to InfluxDB (if configured, else leave blank)

pollingInterval The interval at which Traffic Monitor is polled and stats are stored in InfluxDB

statusToMon The status of Traffic Monitor to poll (poll ONLINE or OFFLINE Traffic Monitors)

seelogConfig The absolute path of the seelog configuration file

dailySummaryPollingInterval The interval, in seconds, at which Traffic Stats checks to see if daily stats need to be computed and stored.

cacheRetentionPolicy The default retention policy for cache stats

dsRetentionPolicy The default retention policy for *Delivery Service* statistics

dailySummaryRetentionPolicy The retention policy to be used for the daily statistics

influxUrls An array of InfluxDB hosts for Traffic Stats to write stats to.

Configuring InfluxDB

As mentioned above, it is recommended that InfluxDB be running in some sort of high availability configuration. There are several ways to achieve high availability so it is best to consult the high availability options on the [InfluxDB website](#).

Once InfluxDB is installed and configured, databases and retention policies need to be created. Traffic Stats writes to three different databases: `cache_stats`, `deliveryservice_stats`, and `daily_stats`. More information about the databases and what data is stored in each can be found in the [Traffic Stats Overview](#).

To easily create databases, retention policies, and continuous queries, run **create_ts_databases** from the `/opt/traffic_stats/influxdb_tools` directory on your Traffic Stats server. See the [InfluxDB Tools](#) section for more information.

Configuring Grafana

In Traffic Portal the *Other* → *Grafana* menu item can be configured to display Grafana graphs using InfluxDB data (when not configured, this menu item will not appear). In order for this to work correctly, you will need two things:

1. A *Parameter* with the graph URL (more information below)
2. The graphs created in Grafana. See below for how to create some simple graphs in Grafana. These instructions assume that InfluxDB has been configured and that data has been written to it. If this is not true, you will not see any graphs.

To create a graph in Grafana, you can follow these basic steps:

1. Login to Grafana as an administrative user
2. Click on *Data Sources* → *Add New*
3. Enter the necessary information to configure your data source
4. Click on *Home* → *New* at the bottom
5. Click on “*Collapsed Menu Icon*” *Button* → *Add Panel* → *Graph*
6. Where it says *No Title (click here)* click and choose edit
7. Choose your data source at the bottom
8. You can have Grafana help you create a query, or you can create your own.

58: Sample Query

```
SELECT sum(value)*1000 FROM "monthly"."bandwidth.cdn.1min"
GROUP BY time(60s), cdn;
```

9. Once you have the graph the way you want it, click the *Save Dashboard* button at the top
10. You should now have a new saved graph

In order for Traffic Portal users to see Grafana graphs, Grafana will need to allow anonymous access. Information on how to configure anonymous access can be found on the configuration page of the [Grafana Website](#).

Traffic Portal uses custom dashboards to display information about individual *Delivery Services* or *Cache Groups*. In order for the custom graphs to display correctly, the Javascript files in `traffic_stats/grafana/` need to be in the `/usr/share/grafana/public/dashboards/` directory on the Grafana server. If your Grafana server is the same as your Traffic Stats server the RPM install process will take care of putting the files in place. If your Grafana server is different from your Traffic Stats server, you will need to manually copy the files to the correct directory.

See also:

More information on custom scripted graphs can be found in the [scripted dashboards](#) section of the Grafana documentation.

Configuring Traffic Portal for Traffic Stats

- The InfluxDB servers need to be added to Traffic Portal with a *Profile* that has the *Type* InfluxDB. Make sure to use port 8086 in the configuration.
- The traffic stats server should be added to Traffic Ops with a *Profile* that has the *Type* TRAFFIC_STATS.
- *Parameters* for which stats will be collected are added with the release, but any changes can be made via *Parameters* that are assigned to the Traffic Stats *Profile*.

Configuring Traffic Portal to use Grafana Dashboards

To configure Traffic Portal to use Grafana Dashboards, you need to enter the following *Parameters* and assign them to the special GLOBAL *Profile*. This assumes you followed instructions in the *Installation*, *Configuring Traffic Stats*, *Configuring InfluxDB*, and *Configuring Grafana* sections.

Table 65: Traffic Stats Parameters

parameter name	parameter value
all_graph_url	https://grafanaHost/dashboard/db/deliveryservice-stats-dashboard
cachegroup_graph_url	https://grafanaHost/dashboard/script/traffic_ops_cachegroup.js?which=
deliveryservice_graph_url	https://grafanaHost/dashboard/script/traffic_ops_deliveryservice.js?which=
server_graph_url	https://grafanaHost/dashboard/script/traffic_ops_server.js?which=
visual_status_panel_cdn	https://grafanaHost/dashboard-solo/db/cdn-stats-dashboard?panelId=2&fullscreen&from=now-24h&to=now-60s
visual_status_panel_delivery	https://grafanaHost/dashboard-solo/db/cdn-stats-dashboard?panelId=1&fullscreen&from=now-24h&to=now-60s
daily_bw_url	https://grafanaHost/dashboard-solo/db/daily-summary-dashboard?panelId=1&fullscreen&from=now-3y&to=now
daily_served_url	https://grafanaHost/dashboard-solo/db/daily-summary-dashboard?panelId=2&fullscreen&from=now-3y&to=now

where

grafanaHost is the FQDN of the Grafana server (again, usually the same as the Traffic Stats server),

cdn-stats-dashboard is the name of the Dashboard providing CDN-level statistics,

deliveryservice-stats-dashboard is the name of the Dashboard providing *Delivery Service*-level statistics, and

daily-summary-dashboard is the name of the Dashboard providing a daily summary of general statistics that would be of interest to administrators using Traffic Portal

InfluxDB Tools

Under the Traffic Stats source directory there is a directory called `influxdb_tools`. These tools are meant to be used as one-off scripts to help a user quickly get new databases and continuous queries setup in InfluxDB. They are specific for Traffic Stats and are not meant to be generic to InfluxDB. Below is a brief description of each script along with how to use it.

`create/create_ts_databases.go`

This program creates all [databases](#), [retention policies](#), and [continuous queries](#) required by Traffic Stats.

Pre-Requisites

- Go 1.7 or later
- Configured `$GOPATH` environment variable

Options and Arguments

`--help`

(Optional) Print usage information and exit (with a failure exit code for some reason)

`--password` password

The password that will be used by the user defined by `--user` to authenticate.

`--replication` N

(Optional) The number of nodes in the cluster (default: 3)

`--url` URL

The InfluxDB server's root URL - including port number, if required (default: `http://localhost:8086`)

`--user` username

The name of the user to use when connecting to InfluxDB

sync/sync_ts_databases.go

This program is used to sync one InfluxDB environment to another. Only data from continuous queries is synced as it is down-sampled data and much smaller in size than syncing raw data. Possible use cases are syncing from production to development or syncing a new cluster once brought online.

Pre-Requisites

- Go 1.7 or later
- Configured `$GOPATH` environment variable

Options and Arguments

- database** database_name
(Optional) Specify the name of a specific database to sync (default: all databases)
- days** N
The number of days in the past to sync. 0 means ‘all’
- help**
(Optional) Print usage information and exit
- source-password** password
The password of the user named by *--source-user*
- source-url** URL
(Optional) The URL of the InfluxDB instance *_from_* which data will be copied (default: `http://localhost:8086`)
- source-user** username
The name of the user as whom the utility will connect to the source InfluxDB instance
- target-password** password
The password of the user named by *--target-user*
- target-url** URL
(Optional) The URL of the InfluxDB instance *_to_* which data will be copied (default: `http://localhost:8086`)
- target-user** username
The name of the user as whom the utility will connect to the target InfluxDB instance

3.1.9 Traffic Server Administration

Installing Traffic Server

1. Build the Traffic Server RPM. The best way to do this is to follow the [Apache Traffic Server documentation](#).
2. Build the astats RPM using the appropriate version number - ours are built [here](#)

Note: The astats plugin is bundled as a part of Apache Traffic Server as of version 7.2.

3. Install Traffic Server and astats

59: Apache Traffic Server Installation Using *yum*(8)

```
yum -y install trafficserver-*.rpm astats_over_http*.rpm
```

4. Add the server using the Traffic Portal UI:
 1. Go to *Configure* → *Servers*
 2. Click on the + button at the top of the page.
 3. Complete the form. Be sure to fill out all fields marked ‘Required’
 - Set ‘Interface Name’ to the name of the network interface device from which Apache Traffic Server delivers content.
 - Set ‘Type’ to ‘MID’ or ‘EDGE’.
 - If you wish for the server to immediately be polled by the *Health Protocol*, set ‘Status’ to ‘REPORTED’.
 4. Click on the *Create* button to submit the form.
 5. Verify that the server status is now listed as **Reported**
5. Install the *t3c* script and run it in ‘badass’ mode to create the initial configuration

See also:

Configuring Traffic Server

6. Start ATS

60: Starting ATS with *systemd*(1)

```
systemctl start trafficserver
```

7. (Optional) Configure ATS to start automatically when the system powers on

61: Configuring ATS to Start Automatically Using *systemd(1)*

```
systemctl enable trafficserver
```

8. Verify that the installation is working

1. Make sure that the service is running

62: Checking that ATS is Running Using *systemd(1)*

```
systemctl status trafficserver
```

2. Assuming a Traffic Monitor is already installed somewhere, check the “Cache States” table in its Web UI to verify that the ATS server appears.

Configuring Traffic Server

All of the ATS application configuration files are generated by Traffic Ops and installed by *t3c*. The *t3c* file should be installed on all *cache servers* (See *Installing the Cache Config Tool*), usually in `/opt/ort`. It is used to do the initial install of the configuration files when the *cache server* is being deployed, and to keep the configuration files up-to-date when the *cache server* is already in service.

Cache Config File Generation

In the past, ATS config files were generated by Traffic Ops. Cache config generation is now performed on cache servers themselves, via a library for generic use, and an application which uses the library and resides on the cache server. That application, *t3c*, is in the process of being rewritten as many small POSIX-style applications which will behave similar to the *git* ecosystem.

The library, `lib/go-atscfg`, allows users to write their own applications and servers, if they wish to generate ATS configuration files and deploy them to caches via other means. For example, if you wish to generate config files with an additional service, or continue generating config files on Traffic Ops itself via a plugin or local service.

The app `atstccfg` is installed by the cache config RPM alongside *t3c*. This app is a helper to *t3c* and does not have a stable interface, and should never need to be called directly by Traffic Control administrators.

The cache-side config generation provides several benefits. Primarily, it reduces the overhead and risk of the monolithic Traffic Ops installation and upgrade process, and allows operators to canary-test config changes one cache at a time, and in the event of an error, only rolling back a few canary caches rather than the entire Traffic Ops instance.

Installing the Cache Config Tool

1. Build the RPM by following the instructions in *Building Traffic Control* and install it with `rpm(8)` or `yum(8)`.
2. Install modules required by the RPM if needed
3. For initial configuration or when major changes (like a *Profile* change) need to be made, run the script in “badass” mode. All required RPM packages will be installed, all ATS configuration files will be fetched and installed, and (if needed) the ATS service will be restarted.

Note: The first run gives a lot of state errors that are expected. The “badass” mode fixes these issues. If you run it a second time, this should be cleaner. Also, note that many “ERROR” messages emitted by *t3c* are actually information messages. Do not panic. We are in the process of converting legacy “ERROR” messages to informational logs.

4. Create a `cron(8)` entry for running *t3c* in “syncds” mode every 15 minutes. This makes Traffic Control check periodically if the server has updates pending, and if so get the updated configuration.

Note: By default, running *t3c* on an Edge-tier *cache server* will cause it to first wait for its parents (usually Mid-tier *cache server* s) to download their configuration before downloading its own configuration. Because of this, scheduling *t3c* for running every 15 minutes (with 5 minutes default dispersion) means that it might take up to ~35 minutes for queued updates to affect all *cache server* s. To customize this dispersion time, use the command line option `--dispersion=x` where `x` is the number of seconds for the dispersion period. Servers will select a random number from within this dispersion period to being downloading configuration files from Traffic Ops. Another option, `--login_dispersion=x` can be used to create a dispersion period after the job begins during which *t3c* will wait before logging in and checking Traffic Ops for updates to the server. This defaults to 0. If `use_reval_pending`, a.k.a. “Rapid Revalidate” is enabled, Edge-tier *cache servers* will **not** wait for their parents to download their configuration before downloading their own.

Note: In “syncds” mode, the *t3c* app updates only configurations that might be changed as part of normal operations, such as:

- *Delivery Services*
- SSL certificates
- Traffic Monitor IP addresses
- Logging configuration

- Revalidation requests (By default - if “Rapid Revalidate” is enabled, this will only be checked by using a separate revalidate command in *t3c*)

5. If “Rapid Revalidate” is enabled in Traffic Ops, create a second *cron*(8) job for revalidation checks by running *t3c* in “revalidate” mode. *t3c* will not check revalidation files if “Rapid Revalidate” is enabled. This setting allows for a separate check to be performed every 60 seconds to verify if a revalidation update has been made.

Strings with Special Meaning to t3c

When processing configuration files, if `traffic_ops_or` encounters any of the strings in the *Replacement Strings* table it will perform the indicated replacement. This means that these strings can be used to create templates in *Profile Parameters* and certain *Delivery Service* configuration fields.

Table 66: Replacement Strings

String	Replaced With
<code>__CACHE_IPv4</code>	The IPv4 address of the <i>cache server</i> on which <i>t3c</i> is running.
<code>__FULL_HOSTNAME</code>	hostname (i.e. including the full domain to which it belongs) of the <i>cache server</i> on which <i>t3c</i> is running.
<code>__HOSTNAME</code>	The (short) hostname of the <i>cache server</i> on which <i>t3c</i> is running.
<code>__RETURN</code>	A newline character (<code>\n</code>).
<code>__SERVER_TCP_PORT</code>	The <i>cache server</i> on which <i>t3c</i> is being run has a TCP port configured to something besides <code>80</code> , this will be replaced with that TCP port value. <i>If it is set to ``80``, this string will simply be removed, NOT replaced with ANYTHING.</i>
<code>##OVERRIDE##</code>	This string is only valid in the content of files named “remap.config”. It is further described in <i>Remap Override</i>

Deprecated since version ATCv4.0: The use of `__RETURN__` in lieu of a true newline character is (finally) no longer necessary, and the ability to do so will be removed in the future.

Note: There is currently no way to indicate that a server’s IPv6 address should be inserted - only IPv4 is supported.

Remap Override

Warning: The `ANY_MAP ##OVERRIDE##` special string is a temporary solution and will be deprecated once Delivery Service Versioning is implemented. For this reason it is suggested that it not be used unless absolutely necessary.

The `##OVERRIDE##` template string allows the *Delivery Service Raw Remap Text* field to override to fully override the *Delivery Service*’s line in the `remap.config` ATS configuration file, gen-

erated by Traffic Ops. The end result is the original, generated line commented out, prepended with `##OVERRIDDEN##` and the `##OVERRIDE##` rule is activated in its place. This behavior is used to incrementally deploy plugins used in this configuration file. Normally, this entails cloning the *Delivery Service* that will have the plugin, ensuring it is assigned to a subset of the *cache servers* that serve the *Delivery Service* content, then using this `##OVERRIDE##` rule to create a `remap.config` rule that will use the plugin, overriding the normal rule. Simply grow the subset over time at the desired rate to slowly deploy the plugin. When it encompasses all *cache servers* that serve the original *Delivery Service*'s content, the "override *Delivery Service*" can be deleted and the original can use a non-`##OVERRIDE##` *Raw Remap Text* to add the plugin.

63: Example of Remap Override

```
# This is the original line as generated by Traffic Ops
map http://from.example.com/ http://to.example.com/

# This is the raw remap text as configured on the delivery service
##OVERRIDE## map http://from.example.com/ http://to.example.com/ some_
→plugin.so

# The resulting content is what actually winds up in the remap.config_
→file:
##OVERRIDE##
map http://from.example.com/ http://to.example.com/ some_plugin.so
##OVERRIDDEN## map http://from.example.com/ http://to.example.com/
```

Warning: The "from" URL must exactly match for this to properly work (e.g. including trailing URL '/'), otherwise ATS may fail to initialize or reload while processing `remap.config`.

Tip: To assist in troubleshooting, it is strongly recommended that any `##OVERRIDE##` rules in use should be documented on the original *Delivery Service*.

3.1.10 Traffic Vault Administration

Currently, the supported backends for Traffic Vault are PostgreSQL and Riak, but Riak support is deprecated and may be removed in a future release. More backends may be supported in the future.

PostgreSQL

In order to use the PostgreSQL backend for Traffic Vault, you will need to set the `traffic_vault_backend` option to "postgres" and include the necessary configuration in the `traffic_vault_config` section in `cdn.conf`. The `traffic_vault_config` options for the PostgreSQL backend are as follows:

dbname The name of the database to use

hostname The hostname of the database server to connect to

password The password to use when connecting to the database

port The port number that the database listens for new connections on (NOTE: the PostgreSQL default is 5432)

user The username to use when connecting to the database

aes_key_location The location on-disk for a base64-encoded AES key used to encrypt secrets before they are stored. It is highly recommended to backup this key to a safe, secure storage location, because if it is lost, you will lose access to all your Traffic Vault data. Either this option or `hashicorp_vault` must be used.

hashicorp_vault This group of configuration options is for fetching the base64-encoded AES key from [HashiCorp Vault](#). This uses the [AppRole authentication method](#).

address The address of the HashiCorp Vault server, e.g. `http://localhost:8200`

role_id The RoleID of the AppRole.

secret_id The SecretID issued against the AppRole.

secret_path The URI path where the secret AES key is located, e.g. `/v1/secret/data/trafficvault`. The secret should be stored using the [KV Secrets Engine](#) with a key of `traffic_vault_key` and value of a base64-encoded AES key, e.g. `traffic_vault_key='WoFc86CisM1aXo8D5GvDnq2h9kjULuIP4upaqX15SRc='`.

login_path Optional. The URI path used to login with the AppRole method. Default: `/v1/auth/approle/login`

timeout_sec Optional. The timeout (in seconds) for requests. Default: 30

insecure Optional. Disable server certificate verification. This should only be used for testing purposes. Default: false

conn_max_lifetime_seconds Optional. The maximum amount of time (in seconds) a connection may be reused. If negative, connections are not closed due to a connection's age. If 0 or unset, the default of 60 is used.

max_connections Optional. The maximum number of open connections to the database. Default: 0 (unlimited)

max_idle_connections Optional. The maximum number of connections in the idle connection pool. If negative, no idle connections are retained. If 0 or unset, the default of 30 is used.

query_timeout_seconds Optional. The duration (in seconds) after which database queries will time out and be cancelled. Default: 30

ssl Optional. Whether or not to use SSL to connect to the database. Default: false

Example `cdn.conf` snippet:

```
{
  "traffic_ops_golang": {
    "traffic_vault_backend": "postgres",
    "traffic_vault_config": {
      "dbname": "tv_development",
      "hostname": "localhost",
      "user": "traffic_vault",
      "password": "twelve",
      "port": 5432,
      "ssl": false,
      "conn_max_lifetime_seconds": 60,
      "max_connections": 500,
      "max_idle_connections": 30,
      "query_timeout_seconds": 10,
      "aes_key_location": "/opt/traffic_ops/app/conf/tv.key"
    }
  }
}
```

Administration of the PostgreSQL database for Traffic Vault

Similar to administering the Traffic Ops database, the *admin* tool should be used for administering the PostgreSQL Traffic Vault backend.

`app/db/reencrypt/reencrypt`

The **reencrypt** binary is used to re-encrypt all data in the Postgres Traffic Vault with a new base64-encoded AES key.

Note: For proper resolution of configuration files, it's recommended that this binary be run from the `app/db/reencrypt` directory.

Usage

```
./reencrypt [options]
```

Options and Arguments

--new-key NEW_KEY

(Optional) The file path for the new base64-encoded AES key. Default is `/opt/traffic_ops/app/conf/new.key`.

--previous-key PREVIOUS_KEY

(Optional) The file path for the previous base64-encoded AES key. Default is `/opt/traffic_ops/app/conf/aes.key`.

--cfg CONFIG_FILE

(Optional) The path for the configuration file. Default is `./reencrypt.conf`.

--help

(Optional) Print usage information and exit.

64: Example Usage

```
./reencrypt --new-key ~/exampleNewKey.txt --previous-key ~/
↪ exampleOldKey.txt
```

reencrypt.conf

This file deals with configuration of the Traffic Vault Database to be used with the **reencrypt** tool.

dbname The name of the PostgreSQL database used.

hostname The hostname (FQDN) of the server that runs the Traffic Vault Database.

password The password to use when authenticating with the Traffic Vault database.

port The port number on which the Traffic Vault Database is listening for incoming connections (NOTE: the PostgreSQL default is 5432).

ssl A boolean that sets whether or not the Traffic Vault Database encrypts its connections with SSL.

user The name of the user as whom to connect to the database.

Riak (deprecated)

Deprecated since version ATCv6: The Riak Traffic Vault backend is deprecated and support may be removed in a future release. It is highly recommended to use the PostgreSQL Traffic Vault backend instead.

In order to use the Riak backend for Traffic Vault, you will need to set the `traffic_vault_backend` option to `"riak"` and include the necessary configuration in the `traffic_vault_config` section in `cdn.conf`. The `traffic_vault_config` options for the Riak backend are as follows:

password The password to use when authenticating with Riak

user The username to use when authenticating with Riak

port The Riak protobuf port to connect to. Default: 8087

tlsConfig Optional. Certain TLS options from [the `tls.Config` struct options](#) may be included here, such as `insecureSkipVerify: true` to disable certificate validation in order to use self-signed certificates for test/development purposes.

MaxTLSVersion Optional. This is the highest TLS version that Traffic Ops is allowed to use to connect to Traffic Vault. Valid values are `"1.0"`, `"1.1"`, `"1.2"`, and `"1.3"`. The default is `"1.1"`.

Note: Enabling TLS 1.1 in Riak itself is required for Traffic Ops to communicate with Riak. See [Enabling TLS 1.1](#) for details.

Example `cdn.conf` snippet:

```
{
  "traffic_ops_golang": {
    "traffic_vault_backend": "riak",
    "traffic_vault_config": {
      "user": "riakuser",
      "password": "password",
      "MaxTLSVersion": "1.1",
      "port": 8087
    }
  }
}
```

Installing the Riak backend for Traffic Vault

In order to successfully store private keys you will need to install Riak. The latest version of Riak can be downloaded on [the Riak website](#). The installation instructions for Riak can be found [here](#). Based on experience, version 2.0.5 of Riak is recommended, but the latest version should suffice.

Configuring Riak

Follow these steps to configure Riak in a production environment.

Self Signed Certificate configuration

Note: Self-signed certificates are not recommended for production use. Intended for development or learning purposes only. Modify subject as necessary.

65: Self-Signed Certificate Configuration

```
cd ~
mkdir certs
cd certs
openssl genrsa -out ca-bundle.key 2048
openssl req -new -key ca-bundle.key -out ca-bundle.csr -subj "/C=US/
→ST=CO/L=DEN/O=somecompany/OU=CDN/CN=somecompany.net/
→emailAddress=someuser@somecompany.net"
openssl x509 -req -days 365 -in ca-bundle.csr -signkey ca-bundle.key -
→out ca-bundle.crt
openssl genrsa -out server.key 2048
openssl req -new -key server.key -out server.csr -subj "/C=US/ST=CO/
→L=DEN/O=somecompany/OU=CDN/CN=somecompany.net/
→emailAddress=someuser@somecompany.net"
openssl x509 -req -days 365 -in server.csr -CA ca-bundle.crt -CAkey ca-
→bundle.key -CAcreateserial -out server.crt
mkdir /etc/riak/certs
mv -f server.crt /etc/riak/certs/.
mv -f server.key /etc/riak/certs/.
mv -f ca-bundle.crt /etc/pki/tls/certs/.
```

Riak Configuration File

The following steps need to be performed on each Riak server in the cluster:

1. Log into Riak server as root
2. Update the following in `riak.conf` to reflect your IP, hostname, and CDN domains and sub-domains:
 - `nodename = riak@a-host.sys.kabletown.net`
 - `listener.http.internal = a-host.sys.kabletown.net:8098` (port can be 80 - This endpoint will not work over HTTPS)
 - `listener.protobuf.internal = a-host.sys.kabletown.net:8087` (can be different port if you want)
 - `listener.https.internal = a-host.sys.kabletown.net:8088` (port can be 443)
3. Update the following in `riak.conf` file to point to your SSL certificate files
 - `ssl.certfile = /etc/riak/certs/server.crt`
 - `ssl.keyfile = /etc/riak/certs/server.key`
 - `ssl.cacertfile = /etc/pki/tls/certs/ca-bundle.crt`

Enabling TLS 1.1 (required)

1. Add a line at the bottom of the `riak.conf` for TLSv1.1 by setting `tls_protocols.tls1.1 = on`
2. Once the configuration file has been updated restart Riak
3. Consult the [Riak documentation](#) for instructions on how to verify the installed service

riak-admin Configuration

`riak-admin` is a command line utility used to configure Riak that needs to be run as root on a server in the Riak cluster.

See also:

The [riak-admin documentation](#)

66: Traffic Vault Setup with `riak-admin`

```
# This script need only be run on any *one* Riak server in the cluster

# Enable security and secure access groups
riak-admin security enable
riak-admin security add-group admins
```

(continues on next page)

(continued from previous page)

```
riak-admin security add-group keysusers

# User name and password should be stored in the traffic_vault_config_
→section in
# /opt/traffic_ops/app/conf/cdn.conf on the Traffic Ops server (with_
→traffic_vault_backend = riak)
# In this example, we assume the usernames 'admin' and 'riakuser' with
# respective passwords stored in the ADMIN_PASSWORD and RIAK_USER_
→PASSWORD
# environment variables
riak-admin security add-user admin password=$ADMIN_PASSWORD_
→groups=admins
riak-admin security add-user riakuser password=$RIAK_USER_PASSWORD_
→groups=keysusers
riak-admin security add-source riakuser 0.0.0.0/0 password
riak-admin security add-source admin 0.0.0.0/0 password

# Grant privileges to the admins group for everything
riak-admin security grant riak_kv.list_buckets,riak_kv.list_keys,riak_
→kv.get,riak_kv.put,riak_kv.delete on any to admins

# Grant privileges to keysusers group for SSL, DNSSEC, and url_sig_
→keys buckets only
riak-admin security grant riak_kv.get,riak_kv.put,riak_kv.delete on_
→default ssl to keysusers
riak-admin security grant riak_kv.get,riak_kv.put,riak_kv.delete on_
→default dnssec to keysusers
riak-admin security grant riak_kv.get,riak_kv.put,riak_kv.delete on_
→default url_sig_keys to keysusers
riak-admin security grant riak_kv.get,riak_kv.put,riak_kv.delete on_
→default cdn_uri_sig_keys to keysusers
```

See also:

For more information on security in Riak, see the [Riak Security documentation](#).

Traffic Ops Configuration

Before a fully set-up Riak instance may be used as the Traffic Vault backend, it must be added as a server to Traffic Ops. The easiest way to accomplish this is via Traffic Portal at *Configure* → *Servers*, though *servers* may also be used by low-level tools and/or scripts. The Traffic Ops configuration file `/opt/traffic_ops/app/conf/cdn.conf` must be updated to set `traffic_vault_backend` to "riak" and the `traffic_vault_config` to include the correct username and password for accessing the Riak database.

Configuring Riak Search

In order to more effectively support retrieval of SSL certificates by Traffic Router and *ORT*, the Riak backend for Traffic Vault uses *Riak search*. Riak Search uses *Apache Solr* for indexing and searching of records. This section explains how to enable, configure, and validate Riak Search.

Riak Configuration

On each Traffic Vault server follow these steps.

1. If Java (JDKv1.8+) is not already installed on your Riak server, install Java

67: Check if Java is Installed, Then Install if Needed

```
# Ensure that this outputs a Java version that is at least
↪1.8
java -version

# If it didn't, or produced an error because `java` doesn't
↪exist,
# install the correct version
# (OpenJDK is used here because of its permissive license,
↪though OracleJDK
# should work with some tinkering)

# On CentOS/RedHat/Fedora (recommended)
yum install -y java-1.8.0-openjdk java-1.8.0-openjdk-devel

# On Ubuntu/Debian/Linux Mint
apt install -y openjdk-8-jdk

# Arch/Manjaro
pacman -Sy jdk8-openjdk
```

2. Enable search in `riak.conf` by changing the `search = off` setting to `search = on`
3. Restart Riak to propagate configuration changes

68: Restarting Riak on *systemd(1)* Systems

```
systemctl restart riak
```

One-time Configuration

After Riak has been configured to use Riak Search, permissions still need need to be updated to allow users to utilize this feature. Unlike actually setting up Riak Search, the permissions step need only be done on any *one* of the Riak servers in the cluster.

1. Use `riak-admin` to grant `search.admin` permissions to the “admin” user and `search.query` permissions to **both** the “admin” user and the “riakuser” user. The “admin” user will also require `search.admin` permissions on the `schema` (in addition to `index`) and `riak_core.set_bucket` permissions on any.

69: Setting up Riak Search Permissions

```
riak-admin security grant search.admin on schema to admin
riak-admin security grant search.admin on index to admin
riak-admin security grant search.query on index to admin
riak-admin security grant search.query on index sslkeys to_
↳admin
riak-admin security grant search.query on index to riakuser
riak-admin security grant search.query on index sslkeys to_
↳riakuser
riak-admin security grant riak_core.set_bucket on any to_
↳admin
```

2. Add the search schema to Riak. This schema is a simple Apache Solr configuration file which will index all records on CDN, hostname, and *Delivery Service*. The file can be found at `traffic_ops/app/config/misc/riak_search/sslkeys.xml` in the Traffic Control repository.

70: Adding the GitHub-hosted Search Schema to Riak

```
# Obtain the configuration file - in this example by_
↳downloading it from GitHub
wget https://raw.githubusercontent.com/apache/
↳trafficcontrol/master/traffic_ops/app/conf/misc/riak_
↳search/sslkeys.xml

# Upload the schema to the Riak server using its API
# Note that the assumptions made here are that the "admin"
↳user's password is "pass"
# and the server is accessible at port 8088 on the_
↳hostname "trafficvault.infra.ciab.test"
curl --tlsv1.1 --tls-max 1.1 -kvsX PUT "https://
↳admin:pass@trafficvault.infra.ciab.test:8088/indexes/
↳schema/sslkeys" -H "Content-Type: application/xml" -d_
↳@sslkeys.xml
```

(Continues on next page)

(continued from previous page)

3. Add the search index to Riak.

71: Adding the Search Index to Riak Via its API

```
# Note that the assumptions made here are that the "admin"
↪user's password is "pass"
# and the server is accessible at port 8088 on the
↪hostname "trafficvault.infra.ciab.test"
curl --tlsv1.1 --tls-max 1.1 -kvsX PUT "https://
↪admin:pass@trafficvault.infra.ciab.test:8088/search/
↪index/sslkeys" -H 'Content-Type: application/json' -d '{
↪"schema":"sslkeys"}'
```

4. Associate the sslkeys index to the ssl bucket in Riak

72: Using the Riak API to Create an Index-to-Bucket Association for sslkeys

```
# Note that the assumptions made here are that the "admin"
↪user's password is "pass"
# and the server is accessible at port 8088 on the
↪hostname "trafficvault.infra.ciab.test"
curl --tlsv1.1 --tls-max 1.1 -kvs -XPUT "https://
↪admin:pass@trafficvault.infra.ciab.test:8088/buckets/ssl/
↪props" -H'content-type:application/json' -d'{"props":{"
↪"search_index":"sslkeys"}}'
```

5. To validate the search is working run a query against the Riak database server, or use the Traffic Ops API endpoint: `cdns/name/{{name}}/sslkeys`

73: Validate Riak Search is Working

```
# Note that the assumptions made here are that the "admin"
↪user's password is
# "pass", the Traffic Vault server's Riak database is
↪accessible at port 8088 on
# the hostname "trafficvault.infra.ciab.test", $COOKIE
↪contains a valid
# Mojolicious cookie for a Traffic Ops user with proper
↪permissions, and the
# Traffic Ops server is available at the hostname
↪"trafficops.infra.ciab.test"

# Verify by querying Riak directly
curl --tlsv1.1 --tls-max 1.1 -kvs "https://
↪admin:password@trafficvault.infra.ciab.test:8088/search/
↪query/sslkeys?wt=json&q=cdn:CDN-in-a-Box" (continues on next page)
```

(continued from previous page)

```
# Verify using the Traffic Ops API
curl -Lvs -H "Cookie: $COOKIE" https://trafficops.infra.
ciab.test/api/2.0/cdns/name/mycdn/sslkeys
```

3.1.11 Quick How To Guides

Traffic Control is a complicated system, and documenting it is not trivial. Sometimes a picture says more than a thousand words, so here are some screenshot-based tutorials on how to use some of the more involved features.

Configure Anonymous Blocking

Note: Anonymous Blocking is only supported for HTTP delivery services. You will need access to a database that provides anonymous IP statistics ([Maxmind's database](#) is recommended, as this functionality was built specifically to work with it.)

1. Prepare the Anonymous Blocking configuration file. Anonymous Blocking uses a configuration file in JSON format to define blocking rules for *Delivery Services*. The file needs to be put on an HTTP server accessible to Traffic Router.

74: Example Configuration JSON

```
{
  "customer": "YourCompany",
  "version": "1",
  "date" : "2017-05-23 03:28:25",
  "name": "Anonymous IP Blocking Policy",

  "anonymousIp": { "blockAnonymousVPN": true,
    "blockHostingProvider": true,
    "blockPublicProxy": true,
    "blockTorExitNode": true},

  "ip4Whitelist": ["192.168.30.0/24", "10.0.2.0/24", "10.
1.1.1/32"],
  "ip6Whitelist": ["2001:550:90a::/48", "::1/128"],
  "redirectUrl": "http://youvebeenblocked.com"
}
```

anonymousIp Contains the types of IPs which can be checked against the Anonymous IP Database. There are 4 types of IPs which can be checked: VPN (Virtual Private Network)s, Hosting Providers, Public Proxies, and TOR “Exit Nodes”. Each type of IP can be enabled or disabled. If the

value is true, IPs matching this type will be blocked when the feature is enabled in the *Delivery Service*. If the value is false, IPs which match this type will not be blocked. If an IP matches more than 1 type and any type is enabled, the IP will be blocked.

redirectUrl The URL that will be returned to the blocked clients. Without a *redirectUrl*, the clients will receive an HTTP response code 403 Forbidden. With a *redirectUrl*, the clients will be redirected with an HTTP response code 302 Found.


ipWhiteList An optional element. It includes a list of CIDR blocks indicating the IPv4 and IPv6 subnets that are allowed by the rule. If this list exists and the value is not null, client IPs will be matched against the CIDR list, and if there is any match, the request will be allowed. If there is no match in the white list, further anonymous blocking logic will continue.

2. Add the following three Anonymous Blocking *Parameters* in Traffic Portal with the “CR-Config.json” *Config File*, and ensure they are assigned to all of the Traffic Routers that should perform Anonymous Blocking:


anonymousip.policy.configuration The URL of the Anonymous Blocking configuration file. Traffic Router will fetch the file from this URL.

anonymousip.polling.url The URL of the Anonymous IP Database. Traffic Router will fetch the file from this URL.


anonymousip.polling.interval The interval that Traffic Router polls the Anonymous Blocking configuration file and Anonymous IP Database.



3. Enable Anonymous Blocking for a *Delivery Service* using the *Delivery Services view* in *Traffic Portal* (don't forget to save changes!)



4. Go to *the Traffic Portal CDNs view*, click on *Diff CDN Config Snapshot*, and click *Perform Snapshot*.



Traffic Router Access Log

Anonymous Blocking extends the field of `rtype` and adds a new field `ANON_BLOCK` in the Traffic Router `access.log` file to help monitor this feature. If the `rtype` in an access log is `ANON_BLOCK` then the client's IP was found in the Anonymous IP Database and was blocked.

See also:

Troubleshooting and log files

Configure Cache Group Fallbacks

See also:

Cache Groups

1. Go to 'Topology', click on *Cache Groups*, and click on your desired *Cache Group* or click the + button to create a new *Cache Group*.




Fig. 22: Cache Groups Page

2. Verify that the *Cache Group* is of type `EDGE_LOC`. *Cache Group* Failovers only apply to `EDGE_LOC` *Cache Groups*.

Fig. 23: Cache Group Details Page

- Once `EDGE_LOC` is selected, the Failover Cache Groups section will appear at the bottom of the page. If you are editing an existing *Cache Group*, then the current Failovers will be listed. If creating a new *Cache Group*, the Fallback to Geo Failover box will default to be checked.

Fig. 24: Failover Cache Groups Section of Cache Group Details Page

- To add a new Failover to the list, select the “Add Failover *Cache Group*” drop down and choose which *Cache Group* you would like. While in the drop down, you can also type in order to search.

Fig. 25: Add New Failover Cache Group Section of Cache Group Details Page

- The order of the Failovers is important. If you want to reorder the Failovers, you can drag and drop them into a new position. A red line will appear to show where the Failover will be dropped.
- To remove a Failover, click the trash can symbol on the right hand side of the list.
- Click the *Update* button (if editing existing *Cache Group*) or the *Create* button (if creating new *Cache Group*) in order to save the Failovers to the *Cache Group*.




Fig. 26: Failover Cache Groups Section Drag and Drop Functionality




Fig. 27: Failover Cache Groups Delete

Forcing Content Invalidation

Invalidating content on the [CDN](#) is sometimes necessary when the *Origin* was mis-configured and something is cached in the CDN that needs to be removed.

Implementation Detail

Given the size of a typical Traffic Control CDN and the amount of content that can be cached in it, removing the content from all the caches may take a long time. To speed up content invalidation, Traffic Control does not try to remove the content from the caches, but it makes the content inaccessible using the [regex_revalidate plugin](#) for [Apache Traffic Server](#). This forces a “re-validation” of the content.

Note: This method forces *cache servers* to “re-validate” content, so in order to work properly the *Origin* needs to support revalidation according to section 13 of [RFC 2616](#).

To invalidate content for a specific *Delivery Service*, follow these steps:

1. Select the desired *Delivery Service* from the *Delivery Services* view of Traffic Portal




Fig. 28: The Traffic Portal Delivery Services view

2. From the *More* drop-down menu, select *Manage Invalidation Requests*




Fig. 29: Select ‘Manage Invalidation Requests’

- Click/tap on the + button to open the submission form for a new content invalidation. Fill out this form. The “Path Regex” field should be a [PCRE](#)-compatible regular expression that matches all content that must be invalidated - and should **not** match any content that must *not* be invalidated. “TTL (hours)” specifies the number of hours for which the invalidation should remain active. Best practice is to set this to the same as the content’s cache lifetime (typically set in the *Origin*’s Cache-Control response header).

Fig. 30: The ‘new content invalidation submission’ Form

- Click on the *Create* button to finalize the content invalidation.

Configure DNSSEC

In order to support [DNSSEC](#) in Traffic Router, Traffic Portal provides some actions for managing DNSSEC keys for a CDN and associated *Delivery Services*. DNSSEC keys consist of a KSK which is used to sign other DNSKEY records as well as a ZSK which is used to sign other records. DNSSEC keys are stored in Traffic Vault and should only be accessible to Traffic Ops. Other applications needing access to this data, such as Traffic Router, must use the *Traffic Ops API* to retrieve this information.

See also:

[DNSSEC](#)

Note: DNSSEC is only supported for DNS-Routed *Delivery Services*.

Creating Keys

Note: In order for Traffic Ops to successfully store keys in Traffic Vault, at least one Traffic Vault server needs to be configured in Traffic Ops.

1. Go to *CDNs* and click on the desired CDN.




Fig. 31: CDNs Page

2. Click on *More* → *Manage DNSSEC Keys*.




Fig. 32: CDN Details Page

3. Click on the *Generate DNSSEC Keys* button.
4. A modal will pop up asking you to confirm that you want to proceed.
5. Input the required information (reasonable defaults should be generated for you). When done, click on the green *Generate* button.

Note: Depending upon the number of *Delivery Services* in the CDN, generating DNSSEC keys may take several seconds.




Fig. 33: DNSSEC Key Management Page




Fig. 34: Confirmation Modal




Fig. 35: DNSSEC Key Generation Page

- You will be prompted to confirm the changes by typing the name of the CDN into a text box. After doing so, click on the red *Confirm* button.

Fig. 36: DNSSEC Key Change Confirmation

- In order for DNSSEC to work properly, the DS (Delegation of Signing) Record information needs to be added to the parent zone of the CDN's domain (e.g. If the CDN's domain is 'ciab.cdn.local' the parent zone is 'cdn.local'). If you control your parent zone you can enter this information yourself, otherwise you will need to work with your DNS team to get the DS Record added to the parent zone.

Enabling and Disabling DNSSEC on a CDN

- Once DS Record information has been added to the parent zone, DNSSEC needs to be activated for the CDN so that Traffic Router will sign responses. Go to the CDN details page for this CDN, and set the 'DNSSEC Enabled' field to 'true' (or 'false' to disable DNSSEC), then click the green *Update* button.

Fig. 37: Change 'DNSSEC Enabled' to 'true'

- DNSSEC should now be active (or inactive, if disabled) on your CDN and Traffic Router should be signing responses. This should be tested e.g. with this *dig(1)* command: `dig edge.cdn.local. +dnssec`.

Regenerating KSKs

When KSK expiration is approaching (default 365 days), it is necessary to manually generate a new KSK for the TLD and add the DS Record to the parent zone. In order to avoid signing errors, it is suggested that an effective date is chosen which allows time for the DS Record to be added to the parent zone before the new KSK becomes active.


Regenerating Keys

It's also possible to re-do the generation of DNSSEC keys once they have already been generated. This can be done at any point after [Creating Keys](#) by clicking on the then-enabled *Regenerate Keys* button on the CDN's details page.

Delivery Service Requests

When enabled in `traffic_portal_properties.json`, Delivery Service Requests are created when *all* users attempt to create, update or delete a [Delivery Service](#). This allows users with higher level permissions (“operations” or “admin”) to review the changes for completeness and accuracy before deploying the changes. In addition, most [Delivery Service](#) changes require configuration updates (i.e. [Queue Updates](#)) and/or a CDN [Snapshot](#). Both of these actions are reserved for users with elevated permissions.

A list of the Delivery Service requests associated with your [Tenant](#) can be found under *Services* → *Delivery Service Requests*



Delivery Service	Type	Status	Author
testds010804	create	complete	admin
testds010803	create	complete	admin
testds010802	update	submitted	admin
testds010802	create	complete	admin
testtopods0108	delete	complete	admin
testtopods0108	create	complete	admin

Fig. 38: Example Delivery Service Request Listing

Who Can Create a Delivery Service Request and How?

Users with the Portal [Role](#) (or above) can create Delivery Service Requests by doing one of three things:

- Creating a new [Delivery Service](#)
- Updating an existing [Delivery Service](#)
- Deleting an exiting [Delivery Service](#)

By performing one of these actions, a Delivery Service Request will be created for you with a status of ‘draft’ or ‘submitted’. You determine the status of your request upon submission.

Only change the status of your request to ‘submitted’ once the request is ready for review and deployment.

Who Can Fulfill a Delivery Service Request and How?

Users with elevated permissions (Operations or above) can fulfill (apply the changes) or reject the Delivery Service Request. In fact, they can do all of the following:

Update the contents of the Delivery Service Request This will update the “Last Edited By” field to indicate who last updated the request.

Assign or Unassign the Delivery Service Request Assignment is currently limited to current user. This is optional as fulfillment will auto-assign the request to the user doing the fulfillment.

Reject the Delivery Service Request Rejecting a Delivery Service Request will set status to ‘rejected’ and the request can no longer be modified. This will auto-assign the request to the user doing the rejection.

Fulfill the Delivery Service Request Fulfilling a Delivery Service Request will show the requested changes and, once committed, will apply the desired changes and set status to ‘pending’. The request is pending because many types of changes will require *cache server* configuration updates (i.e. *Queue Updates*) and/or a CDN *Snapshot*. Once *Queue Updates* and/or CDN *Snapshot* is complete, the request should be marked ‘complete’.

Complete the Delivery Service Request Only after the Delivery Service Request has been fulfilled and the changes have been applied can a Delivery Service Request be marked as ‘complete’. Marking a Delivery Service Request as ‘complete’ is currently a manual step because some changes require *cache server* configuration updates (i.e. *Queue Updates*) and/or a CDN *Snapshot*. Once that is done and the changes have been deployed, the request status should be changed from ‘pending’ to ‘complete’.

Note: Only the user that fulfilled the delivery service request can mark a delivery service as ‘complete’. This prevents other users from interfering in the process and marking delivery services as ‘complete’ when further action is required for the changes to truly be deployed. However, in `traffic_portal_properties.json`, users with the ‘overrideRole’ are given the ability to mark any delivery service requests as ‘complete’.

Delete the Delivery Service request Delivery Service Requests with a status of ‘draft’ or ‘submitted’ can always be deleted entirely if appropriate.

Configure Federations

1. Create a user with a federations role (*User Admin* → *Users* → '+' button). This user will need the ability to:
 - Create/edit/delete federations
 - Add IPV4 resolvers
 - Add IPV6 resolvers

The screenshot shows a web form titled "Add User". On the left, there is a list of fields with asterisks indicating required fields: Full Name, Username, Email, Password, Confirm Password, Role, Phone Number, Company, Address Line 1, Address Line 2, City, State or Province, Postal Code, Country, UID, GID, and Last Updated. On the right, the corresponding input fields are shown. "Full Name" contains "Federation User", "Username" contains "federation_user1", "Email" contains "federation_user@mega-cdn.net", "Password" and "Confirm Password" are masked with dots, and "Role" is a dropdown menu currently showing "federation". The remaining fields are empty. At the bottom of the form, there are two buttons: "Add User" and "Close".

2. As a user with administrative privileges, create a Federation Mapping by going to *Services* → *:term: 'Delivery Services' → More → Federations`* and then clicking *Add Federation Mapping*.
3. Choose the *Delivery Service* to which the federation will be mapped and assign it to the Federation-role user; click *Add*.
4. After the Federation is added, Traffic Ops will display the Federation. Changes can be made at this time or the Federation can be deleted. Notice that no resolvers have been added to the Federation yet. This can only be done by the Federation-role user to whom the Federated *Delivery Service* was assigned. If no further action is necessary, the *Close* button will close the window and display the list of all Federations.

Add Federation Mapping

* CNAME:

Description:

* TTL:

* Role:

* Delivery Services:

* User:

5. The federation user logs into either the Traffic Ops API or the Traffic Portal UI and stores the Mojolicious cookie. The Mojolicious cookie can be obtained manually using the debug tools on a web browser or via a command line utility like *curl* (1).

75: Example cURL Command

```
curl -i -XPOST "http://localhost:3000/api/2.0/user/login" -
-H "Content-Type: application/json" -d '{ "u":
"federation_user1", "p": "password" }'
```

Federation Mapping

Successfully added Federation!

* CNAME

img.mega-cdn.net.

Description

Federation Mapping for img.mega-cdn.

* TTL

30

* Role

federation

* Delivery Services

images-c1

* User

Federation User (federation_user1) -

Resolvers

Delete

Save

Close

76: Example API Response

```
HTTP/1.1 200 OK
Date: Wed, 02 Dec 2015 21:12:06 GMT
Content-Length: 65
Access-Control-Allow-Credentials: true
Content-Type: application/json
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov
↳2019 17:40:54 GMT; Max-Age=3600; HttpOnly
X-Server-Name: traffic_ops_golang/
Access-Control-Allow-Headers: Origin, X-Requested-With,
↳Content-Type, Accept
Cache-Control: no-cache, no-store, max-age=0, must-
↳revalidate
Connection: keep-alive
Access-Control-Allow-Origin: http://localhost:8080

{"alerts":[{"level":"success","text":"Successfully logged
↳in."}]}
```

6. The federation user sends a request to Traffic Ops to add IPV4 and/or IPV6 resolvers

77: Example cURL Command

```
curl -ki -H "Cookie:
↳mojolicious=eyJleHBpcmVzIjoxNDQ5MTA1MTI2LCJhdXRoX2RhdGEiOiJmZWRLcmF0aW9uX
↳--06b4f870d809d82a91433e92eae8320875c3e8b0;" -XPUT
↳'http://localhost:3000/api/2.0/federations' -d '
{"federations": [
  { "deliveryService": "images-c1",
    "mappings":
      { "resolve4": [ "8.8.8.8/32", "8.8.4.4/32" ],
        "resolve6": ["2001:4860:4860::8888/128",
↳"2001:4860:4860::8844"]
      }
    }
}]}'
```

78: Example API Response

```
HTTP/1.1 200 OK
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov
↳2019 17:40:54 GMT; Max-Age=3600; HttpOnly
X-Server-Name: traffic_ops_golang/
Date: Wed, 02 Dec 2015 21:25:42 GMT
Content-Length: 74
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Credentials: true
Content-Type: application/json
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Cache-Control: no-cache, no-store, max-age=0, must-
    ↪revalidate
Access-Control-Allow-Origin: http://localhost:8080
Connection: keep-alive
Access-Control-Allow-Headers: Origin, X-Requested-With,
    ↪Content-Type, Accept

{"response": "federation_user1 successfully created,
    ↪federation resolvers."}
```

7. The resolvers added by the Federation-user will now visible in Traffic Portal.

Federation Mapping

* CNAME:

Description:

* TTL:

* Role:

* Delivery Services:

* User:

Resolvers

- ▼ resolve4
 - 8.8.8.8/32
 - 8.8.4.4/32
- ▼ resolve6
 - 2001:4860:4860::8888/128
 - 2001:4860:4860::8844/128

Any requests made from a client that resolves to one of the federation resolvers will now be given a CNAME Record from Traffic Router.

79: Example DNS request (via dig)

```
dig @tr.kabletown.net foo.images-c1.kabletown.net
```

80: Example Resolver Response

```
; <<>> DiG 9.7.3-RedHat-9.7.3-2.el6 <<>> @tr.kabletown.net.
; →foo.images-c1.kabletown.net
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 45110
;; flags: qr rd; QUERY: 1, ANSWER: 1, AUTHORITY: 0,
; →ADDITIONAL: 0
;; WARNING: recursion requested but not available

;; QUESTION SECTION:
;foo.images-c1.kabletown.net.    IN A

;; ANSWER SECTION:
foo.images-c1.kabletown.net.    30 IN CNAME img.mega-cdn.net.

;; Query time: 9 msec
;; SERVER: 10.10.10.10#53(10.10.10.10)
;; WHEN: Wed Dec  2 22:05:26 2015
;; MSG SIZE rcvd: 84
```

Creating the CentOS Kickstart File

The Kickstart file is a text file, containing a list of items, each identified by a keyword. This file can be generated using the [Red Hat Kickstart Configurator application](#), or it can be written from scratch. The Red Hat Enterprise Linux installation program also creates a sample Kickstart file based on the options selected during installation. It is written to the file `/root/anaconda-ks.cfg` in this case. This file is editable using most text editors.

Generating a System Image

1. Create a Kickstart file.
2. Create a boot media with the Kickstart file or make the Kickstart file available on the network.
3. Make the installation tree available.
4. Start the Kickstart installation.

81: Creating a New System Image Definition Tree from an Existing One

```
# Starting from the Kickstart root directory (`/var/www/files` by default)
mkdir newdir
cd newdir/

# In this example, the pre-existing system image definition tree is for CentOS 7.4 located in `centos74`
cp -r ../centos74/* .
vim ks.src
vim isolinux/isolinux.cfg
cd ..
vim osversions.json
```

`ks.src` is a standard, Kickstart-formatted file that will be used to create the Kickstart (`ks.cfg`) file for the install whenever a system image is generated from the source tree. `ks.src` is a template - it will be overwritten by any information set in the form submitted from *Tools* → *Generate ISO* in Traffic Portal. Ultimately, the two are combined to create the final Kickstart file (`ks.cfg`).

Note: It is highly recommended for ease of use that the system image source trees be kept under 1GB in size.

See also:

For in-depth instructions, please see [Kickstart Installation](#) in the Red Hat documentation.

kickstart.files.location

The Kickstart root directory used by *Traffic Ops* (`/var/www/files` by default) can be changed by setting the `kickstart.files.location` *Parameter*.

Configure Multi-Site Origin

The following steps will take you through the procedure of setting up an MSO. #. Create *Cache Groups* for the origin locations, and assign the appropriate parent-child relationship between the Mid-tier *Cache Group*(s) and origin *Cache Groups*. Each Mid-tier *Cache Group* can be assigned a primary and secondary origin parent *Cache Group*. When the *Cache Group* parent configuration is generated, origins in the primary *Cache Groups* will be listed first, followed by origins in the secondary *Cache Group*. Origin servers assigned to the *Delivery Service* that are assigned to neither the primary nor secondary *Cache Groups* will be listed last.

Health	Delivery Services	Servers	Parameters	Tools	Misc	Change Log	Help	UTC: 20:52:58
Search: <input type="text" value="orig"/>								
Name	Short Name	Type	Magnet Latitude	Magnet Longitude	Parent Loc	Last Updated	Cache Groups	
mid-east	east	MID_LOC	0	0	origin-east	2015-06-25 20:52:37		
mid-west	west	MID_LOC	0	0	origin-west	2015-06-25 20:52:37		
origin-east	org-east	ORG_LOC	0	0		2015-06-25 20:52:37		
origin-west	org-west	ORG_LOC	0	0		2015-06-25 20:52:37		

Showing 1 to 4 of 4 entries (Filtered from 12 total entries)

[Add Cache Group](#)

1. Create a profile to assign to each of the origins:

Health	Delivery Services	Servers	Parameters	Tools	Misc	Change Log	Help	UTC: 20:53:46
Search: <input type="text" value="ORG"/>								
Profile name	Parameter name	Config file name	Value					
ORG1_CDN1	domain_name	CRConfig.xml	cdn1.kabletown.net					
ORG1_CDN1	GeoLocationURL	CRConfig.xml	http://www.cdnlab.kabletown.net:8080/GeoLocCity.dat.gz					
ORG1_CDN1	weight	parent.config	1.0					
ORG2_CDN1	domain_name	CRConfig.xml	cdn1.kabletown.net					
ORG2_CDN1	GeoLocationURL	CRConfig.xml	http://www.cdnlab.kabletown.net:8080/GeoLocCity.dat.gz					
ORG2_CDN1	weight	parent.config	1.0					

Showing 1 to 6 of 6 entries (Filtered from 3,996 total entries)

[Add Parameter](#)

2. Create server entries for the origination vips:

Health	Delivery Services	Servers	Parameters	Tools	Misc	Change Log	Help	UTC: 20:54:14
Search: <input type="text" value="ORG"/>								
Host Name	Domain Name	Cache group	Location	IPAddr	IPv6 Addr	Status	Profile	BLD
org1	kabletown.net	origin-east	plocation-nyc-1	10.11.10.2		CCR_IGNORE	ORG1_CDN1	
org2	kabletown.net	origin-west	plocation-nyc-1	10.11.12.2		CCR_IGNORE	ORG2_CDN1	

Showing 1 to 2 of 2 entries (Filtered from 83 total entries)

[Add Server](#)

3. Check the multi-site check box in the *Delivery Service* screen:
4. Assign the org servers to the *Delivery Service* that will have the multi site feature. Origin servers assigned to a *Delivery Service* with multi-site checked will be assigned to be the origin servers for this *Delivery Service*.

Note: “Origin Server Base URL” uniqueness: In order to enable Mid-tier *Cache Group* to distinguish *Delivery Services* by different MSO algorithms while performing parent fail-over, it requires that OSBU (Origin Server Base URL) for each MSO-enabled *Delivery Service* is unique. This means that the OSBU of an MSO-enabled *Delivery Service* should be different from the OSBUs of any other *Delivery Service*, regardless of whether they are MSO-enabled or not. The exceptions to this rule are:

- If there are multiple CDNs created on the same Traffic Ops, *Delivery Services* across different CDNs may have the same OSBU configured.
- If several *Delivery Services* in the same CDN have the same MSO algorithm configured, they may share the same OSBU.
- If delivery services are assigned with different Mid-tier *Cache Groups* respectively, they can share the same OSBU.
- This OSBU must be valid - ATS will perform a DNS lookup on this FQDN even if IPs, not DNS, are used in the `parent.config`.

* CDN	cdn1
* Content Routing Type	HTTP
* Protocol	http
* DSCP Tag	0 - Best Effort
Signed URLs	No
Query String Handling	0 - use qstring in cache key, and pass up
Geo Limit?	None
Bypass FQDN	
Initial Dispersion	1 - Off
IPv6 Routing Enabled?	No
Range Request Handling	0 - Don't cache
Delivery Service DNS TTL	3600
* Origin Server Base URL	http://movies.origin.kabletown.net
* Use Multi Site Origin Feature	Yes

Delivery Service Server Assignments for movies-c1 (http://movies.origin.kabletown.net)

EDGE1_CDN1_421_SSL

us-ca-losangeles

us-co-denver

us-il-chicago

atsec-chi-00

atsec-chi-01

atsec-chi-02

atsec-chi-03

good-host

us-ny-newyork

us-pa-philadelphia

us-tx-houston

Save

Close

- The OSBU entered as the “Origin Server Base URL” will be sent to the origins as a host header. All origins must be configured to respond to this host.

5. Create a delivery service profile. This must be done to set the MSO algorithm. Also, as of ATS 6.x, multi-site options must be set as parameters within the `parent.config`. Header rewrite parameters will be ignored. See [ATS parent.config](#) for more details. These *Parameters* are now handled by the creation of a *Delivery Service Profile*.

- a) Create a *Profile* of the *Type* DS_PROFILE for the *Delivery Service* in question.

- b) Click *Show profile parameters* to bring up the *Parameters* screen for the *Profile*. Create the following *Parameters*:

Parameter Name	Config File Name	Value	ATS parent.config value
mso.algorithm	parent.config	true, false, strict, consistent_hash	round_robin
mso.parent_retry	parent.config	simple_retry, both, unavailable_server_retry	parent_retry
mso.unavailable_server_retry_response_codes	parent.config	list of response codes, eg “500,502,503”	defaults to the value in records.config when unused.
mso.max_simple_retries	parent.config	Number of retries made after a 4xx error	defaults to the value in records.config when unused.
mso.max_unavailable_server_retries	parent.config	Number of retries made after a 5xx error	defaults to the value in records.config when unused.

- c) In the *Delivery Service* page, select the newly created DS_PROFILE and save the *Delivery Service*.

6. Turn on `parent_proxy_routing` in the MID *Profile*.

Profile name	Parameter name	Config file name	Value	Secure
DS_example	msa.algorithm	parent.config	false	no
DS_example	msa.parent_retry	parent.config	both	no
DS_example	msa.unavailable_server_retry_responses	parent.config	"500,502,503"	no

Note: Support for multisite configurations with single-layer CDNs is now available. If a *Cache Groups* defined parents are either blank or of the type ORG_LOC, that *cache server's* parent.config will be generated as a top layer cache, even if it is an edge. In the past, parent.config generation was strictly determined by cache type. The new method examines the parent *Cache Group* definitions and generates the parent.config accordingly.

Configure OAuth Login

An opt-in configuration for SSO using OAuth is supported and can be configured through the /opt/traffic_portal/public/traffic_portal_properties.json and /opt/traffic_ops/app/conf/cdn.conf files. OAuth uses a third party provider to authenticate the user. If enabled, the Traffic Portal Login page will still accept username and password for local accounts but will also allow authentication using OAuth. This will redirect to the oAuthUrl from /opt/traffic_portal/public/traffic_portal_properties.json which will authenticate the user then redirect to the new /sso page with an authorization code. The new /sso page will then construct the full URL to exchange the authorization code for a JSON Web Token, and POST this information to the *user/login/oauth* API endpoint. The *user/login/oauth* API endpoint will POST to the URL provided and receive JSON Web Token. The *user/login/oauth* API endpoint will decode the token, validate that it is between the issued time and the expiration time, and validate that the public key set URL is allowed by the list of whitelisted URLs read from /opt/traffic_ops/app/conf/cdn.conf. It will then authorize the user from the database and return a mojolicious cookie as per the normal login workflow.

Note: Ensure that the user names in the Traffic Ops database match the value returned in the *sub* field in the response from the OAuth provider when setting up with the OAuth provider. The *sub* field is used to reference the roles in the Traffic Ops database in order to authorize the user.

Note: OAuth providers sometimes do not return the public key set URL but instead require a locally stored key. This functionality is not currently supported and will require further development.

Note: The POST from the API to the OAuth provider to exchange the code for a token expects the response to have the token in JSON format with *access_token* as the desired field (and can include other fields). It also supports a response with just the token itself as the body. Further development work will need to be done to allow other response forms or other response fields.

Note: Users must exist in both Traffic Ops as well as in the OAuth provider's system. The user's rights are defined by the *Role* assigned to the user.

To configure OAuth login:

- Set up authentication with a third party OAuth provider.
- Update `/opt/traffic_portal/public/traffic_portal_properties.json` and ensure the following properties are set up correctly:

Table 67: OAuth Configuration Property Definitions In traffic_portal_properties.json

Name	Type	Description
enabled	boolean	Allow OAuth SSO login
oAuthUrl	string	URL to your OAuth provider
redirectUri-ParameterOverride	string	Query parameter override if the oAuth provider requires a different key for the redirect_uri parameter, defaults to <code>redirect_uri</code>
clientId	string	Client id registered with OAuth provider, passed in with <code>client_id</code> parameter
oAuth-CodeTo-tokenUrl	string	URL to your OAuth provider's endpoint for exchanging the code (from oAuthUrl) for a token

82: Example OAuth Configuration Properties In traffic_portal_properties.json

```
{
  "oAuth": {
    "_comment": "Opt-in OAuth properties for SSO login.
    ↪ See http://traffic-control-cdn.readthedocs.io/en/
    ↪ release-4.0.0/admin/quick_howto/oauth_login.html for
    ↪ more details. redirectUriParameterOverride defaults to
    ↪ redirect_uri if left blank.",
    "enabled": true,
    "oAuthUrl": "example.oauth.com",
    "redirectUriParameterOverride": "",
    "clientId": "",
    "oAuthCodeTokenUrl": "example.oauth.com/oauth/token
    ↪ "
  }
}
```

- Update `/opt/traffic_ops/app/conf/cdn.conf` property `traffic_ops_golang.whitelisted_oauth_urls` to contain all allowed domains for the JSON key set (Use `*` for wildcard):

Table 68: OAuth Configuration Property Definitions In cdn.conf

Name	Type	Description
whitelisted_oauth_urls	Array of strings	List of whitelisted URLs for the JSON public key set returned by OAuth provider. Can contain * wild-cards.
oauth_client_secret	string	Client secret registered with OAuth provider to verify client, passed in with <i>client_secret</i> parameter

83: Example OAuth Configuration Properties In cdn.conf

```
{
  "traffic_ops_golang": {
    "whitelisted_oauth_urls": [
      "oauth.example.com",
      ".*example.com"
    ],
    "oauth_client_secret": "secret"
  }
}
```

Compare Profiles

In Traffic Portal *all* users can compare the *Parameters* of any 2 *Profiles* side-by-side, and users with a higher level *Role* (“operations” or “admin”) can easily add or remove parameters from each profile as necessary.

The ability to compare 2 profiles can be found under *Configure* → *Profiles* → *More* → *Compare Profiles*




Fig. 39: The “Compare Profiles” menu item

Once you have selected the *Compare Profiles* menu item, you will be asked to choose 2 profiles to compare.

All parameters exclusively assigned to one profile but not the other will be displayed by default with their profile membership displayed side-by-side. In addition, by selecting the *Show Shared Params* link, the user can see a superset of all parameters (shared and not shared) across the 2 profiles. Both views provide users with higher level permissions (“operations” or “admin”) the ability to easily remove or add parameters for each profile and persist the final state of both profiles (or restore the original state and discard changes). As the user makes changes, a blue shadow is added to all modified checkboxes.




Fig. 40: The “Compare Profiles” dialog

Name	Config File	Value	PROFILE_1	PROFILE_2
edge.http.routing	CRCConfig.json	true	<input checked="" type="checkbox"/>	<input type="checkbox"/>
edge.http.limit	CRCConfig.json	12	<input checked="" type="checkbox"/>	<input type="checkbox"/>
CONFIG.proxy.config.temp_dir	records.config	STRING /tmp	<input type="checkbox"/>	<input checked="" type="radio"/>
neustar.polling.interval	CRCConfig.json	86400000	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Fig. 41: The “Compare Profiles” table

Configure Regional Geo-blocking (RGB)

Note: RGB (Regional Geographic-based Blocking) is only supported for HTTP *Delivery Services*.

1. Prepare an RGB configuration file. RGB uses a configuration file in JSON format to define regional geographic blocking rules for *Delivery Services*. The file needs to be put on an HTTP server accessible to Traffic Router.

84: Example Configuration File

```
{
  "deliveryServices":
  [
    {
      "deliveryServiceId": "hls-live",
      "urlRegex": ".*live4\\.m3u8",
      "geoLocation": {"includePostalCode": ["NØH",
↪ "L9V", "L9W"],
      "coordinateRange": [{"minLat": ↪
↪ -12, "maxLat": 13, "minLon" : 55, "maxLon": 56}, {
↪ "minLat" : -13, "maxLat": 14, "minLon" : 55, "maxLon": ↪
↪ 56}]},
      "redirectUrl": "http://third-party.com/blacked_
↪ out.html"
```

(continues on next page)

(continued from previous page)

```

    },
    {
      "deliveryServiceId": "hls-live",
      "urlRegex": ".*live5\\.m3u8",
      "ipWhiteList": ["185.68.71.9/22", "142.232.0.79/
↪24"],
      "geoLocation": {"excludePostalCode": ["NOH",
↪"L9V"]},
      "redirectUrl": "/live5_low_bitrate.m3u8",
      "isSteeringDS": "false"
    },
    {
      "deliveryServiceId": "linear-steering",
      "urlRegex": ".*live3\\.m3u8",
      "ipWhiteList": ["185.68.71.9/22", "142.232.0.79/
↪24"],
      "geoLocation": {"excludePostalCode": ["NOH",
↪"L9V"]},
      "redirectUrl": "http://ip-slate.cdn.example.
↪com/slate.m3u8",
      "isSteeringDS": "true"
    }
  ]
}

```

deliveryServiceId Should be equal to the ID or `xml_id` field of the intended *Delivery Service* as configured in Traffic Portal

urlRegex A regular expression to be used to determine to what URLs the rule shall apply; a URL that matches it is subject to the rule

geoLocation An object that currently supports only the keys `includePostalCode`, `excludePostalCode` (mutually exclusive) and `coordinateRange`. When the `includePostalCode` key is used, only the clients whose FSA (Forward Sortation Areas)s - the first three postal characters of Canadian postal codes - are in the `includePostalCode` list are able to view the content at URLs matched by the `urlRegex`. When `excludePostalCode` is used, any client whose FSA is not in the `excludePostalCode` list will be allowed to view the content. The `coordinateRange` key is used to specify a list of latitude and longitude ranges. This is used in regional geo blocking, in case the client does not have a postal code associated with it.

redirectUrl The URL that will be returned to the blocked clients. Without a domain name in the URL, the URL will still be served in the same *Delivery Service*. Thus Traffic Router will redirect the client to a chosen *cache server* assigned to the *Delivery Service*. If the URL includes a domain name, Traffic Router simply redirects the client to the defined


URL. In the latter case, the redirect URL must not match the `urlRegex` value, or an infinite loop of HTTP 302 Found responses will occur at the Traffic Router. *Steering-Type Delivery Services* must contain an FQDN as the re-redirect or Traffic Router will return a DENIED to the client. This is because steering services do not have caches associated to them, so a relative `redirectURL` can not be turned into a FQDN.

ipWhiteList An optional element that is an array of CIDR blocks indicating the IPv4 and/or IPv6 subnets that are allowed by the rule. If this list exists and the value is not empty, client IP will be matched against the CIDR list, bypassing the value of `geoLocation`. If there is no match in the white list, Traffic Router defers to the value of `geoLocation` to determine if content ought to be blocked.


2. Add RGB *Parameters* in Traffic Portal to the *Delivery Service*'s Traffic Router(s)'s *Profile(s)*. The *Config File* value should be set to `CRConfig.json`, and the following two *Parameter Name/Value* pairs need to be specified:

regional_geoblock.polling.url The URL of the RGB configuration file. Traffic Router will fetch the file from this URL using an HTTP GET request.

regional_geoblock.polling.interval The interval on which Traffic Router polls the RGB configuration file.



3. Enable RGB for a *Delivery Service* using the *Delivery Services* view in *Traffic Portal* (don't forget to save changes!)



4. Go to *the Traffic Portal CDNs view*, click on *Diff CDN Config Snapshot*, and click *Perform Snapshot*.



Traffic Router Access Log

See also:

Troubleshooting and log files

RGB extends the `rtype` field and adds a new field `rgb` in Traffic Router access.log to help to monitor this feature. A value of `RGALT` in the `rtype` field indicates that a request is redirected to an alternate URL by RGB; a value of `RGDENY` indicates that a request is denied by RGB because there is no matching rule in the RGB configuration file for this request. When RGB is enabled, the `rgb` field will be non-empty with following format:

```
{FSA}:{allowed/disallowed}:{include/exclude postal}:{fallback
config}:{allowed by whitelist}
```

FSA FSA part of the client's postal code, which is retrieved from a geographic location database. If this field is empty, a dash ("-") is filled in.

allowed/disallowed This flag shows if a request was allowed or disallowed by RGB (1 for yes, and 0 for no).

include/exclude postal This shows that when a rule in JSON is matched for a request, it's value is "I" if the rule matched because of an `includePostalCode` rule, "X" if the rule matched because of an `excludePostalCode` rule, or "-" if no rule matched.

fallback config When Traffic Router fails to parse an RGB configuration file as JSON, Traffic Router will handle requests with latest valid configuration that it had, but will set the `fallback config` flag to 1. If no fall-back occurred, then the flag is set to 0.

allowed by whitelist If a request is allowed by a `whitelist` field in the configuration, this flag is set to 1; for all other cases, it is 0.

85: Example

```
1446442214.685 qtype=HTTP chi=129.100.254.79 url="http://foo.geo2.cdn.
→com/live5.m3u8" cqhm=GET cqhv=HTTP/1.1 rtype=GEO rloc="-" rdtl=-
→rerr="-" rgb="N6G:1:X:0:0" pssc=302 ttms=3 rurl=http://cent6-44.geo2.
→cdn.com/live5.m3u8 rh="-"

1446442219.181 qtype=HTTP chi=184.68.71.9 url="http://foo.geo2.cdn.com/
→live5.m3u8" cqhm=GET cqhv=HTTP/1.1 rtype=RGALT rloc="-" rdtl=- rerr=
→"-" rgb="-:0:X:0:0" pssc=302 ttms=3 rurl=http://cent6-44.geo2.cdn.
→com/low_bitrate.m3u8 rh="-"
```

(continues on next page)


(continued from previous page)

```
1446445521.677 qtype=HTTP chi=24.114.29.79 url="http://foo.geo2.cdn.
→com/live51.m3u8" cqhm=GET cqhv=HTTP/1.1 rtype=RGDENY rloc="-" rdtl=-
→rerr="-" rgb="L4S:0:-:0:0" pssc=520 ttms=3 rurl="-" rh="-"
```

Manage Server Capabilities

Server capabilities are designed to enable users with the Operations or Admin *Role* to control the flow of *Delivery Service* traffic through only the *cache servers* (*Edge* or *Mid*) that have the required capabilities. For example, *Delivery Services* designed to serve large binary files should only have requests routed to *cache servers* with sufficient disk cache. Currently, this can be controlled at the *Edge-tier* where system operators can explicitly assign only *Edge-tier caches* with sufficient disk cache to the *Delivery Service*. However, operators do not have control of *Mid-tier cache* assignments and cannot dictate which *Mid-tier caches* are qualified to serve these large binary files. This will cause a problem if a *Mid-tier cache* with insufficient disk cache is asked to serve the *Delivery Services*' large binary files.

A list of the server capabilities can be found under *Configure* → *Server Capabilities*. Users with a higher-level *Role* ("operations" or "admin") can create or delete server capabilities. Server capabilities can only be deleted if they are not currently being used by a *cache server* or required by a *Delivery Service*.



Name	Capabilities
CACHE_MEMORY	
CACHE_DISK	

Fig. 42: Example Server Capabilities Listing

Manage server capabilities assigned to a server

Users with the Operations or Admin *Role* can associate one or more server capabilities with a *cache servers* (*Edge* or *Mid*) by navigating to a server via *Configure* → *Servers* and using the context menu for the server table and selecting *Manage Capabilities* or by navigating to *Configure* → *Servers* → *Server* → *More* → *Manage Capabilities*.



Name	Capabilities
CACHE_MEMORY	

Fig. 43: Example Server Capabilities for a Server Listing

Manage delivery service required server capabilities

Users with the Operations or Admin *Role* can associate one or more required server capabilities with a *Delivery Service* by navigating to a *Delivery Service* via *Services* → *Delivery Services* and using the context menu for the *Delivery Services* table and selecting *Manage Required Server Capabilities* or by navigating to *Services* → *Delivery Services* → *Delivery Service* → *More* → *Manage Required Server Capabilities*.

Adding a required server capability to a *Delivery Service* will ensure two things:

1. Only *Edge-tier caches* with the required capability can be assigned to the *Delivery Service*
2. Only *Mid-tier caches* with the required capability will handle requests of the *Delivery Service* (if applicable)




Fig. 44: Example Required Server Capabilities for a Delivery Service Listing

Configuring Static DNS Entries

Static DNS records (historically “entries”) can be configured within the DNS subdomain of a given *Delivery Service*. In a typical scenario, the *Delivery Service* will have DNS records automatically generated based on its “xml_id” and “routing name”, and the name and subdomain of the CDN to which it belongs. For example, in the *CDN in a Box* default environment, the “demo1” *Delivery Service* has an automatically generated DNS record for `video.demo1.mycdn.ciab.test`. Configuring a static DNS record allows for further extension of this, for example, one could create an A record that enforces lookups of the name `foo.demo1.mycdn.ciab.test` resolve to the IPv4 address `192.0.2.1`.

Note: It’s only possible to create static DNS records within a *Delivery Service*’s subdomain. That is, one could not create an A record for `foo.bar.mycdn.ciab.test` on the *CDN in a Box Delivery Service* “demo1”, since “demo1”’s subdomain is `demo1.mycdn.ciab.test`.

See also:

This guide covers how to set up static DNS records using Traffic Portal. It’s also possible to do so directly using the *Traffic Ops API* endpoint *staticdnsentries*.

Example

To set up the aforementioned rule, follow these steps.

1. In Traffic Portal, expand the *Services* sidebar menu and select *Delivery Services*.
2. From the now-displayed table of *Delivery Services*, select the desired one for static DNS record configuration.
3. From the *More* drop-down menu, select *Static DNS Entries*. The displayed table will probably be empty.




Fig. 45: The Static DNS Entries Table Page

4. Click on the blue + button to add a new static DNS Entry
5. Fill in all of the fields.

Host This is the lowest-level DNS label that will be used in the DNS record. In the *CDN in a Box* scenario, for example, entering `foo` here will result in a full DNS name of `foo.demo1.mycdn.ciab.test`.


Type Indicates the type of DNS record that will be created. The available types are

- A
- AAAA
- CNAME
- TXT

TTL The TTL of the DNS record, after which clients will be expected to re-request name resolution.

Address The meaning of this field depends on the value of the “Type” field.

- If the “Type” is **A**, this must be a valid IPv4 address
- If the “Type” is **AAAA**, this must be a valid IPv6 address
- If the “Type” is **CNAME**, this must be a valid DNS name - **not** an IP address at all
- If the “Type” is **TXT**, no restrictions are placed on the content whatsoever



The screenshot shows the 'TRAFFIC PORTAL' interface. On the left is a dark sidebar with a menu including Dashboard, CDNs, Monitor, Services (expanded), Delivery Services (selected), Delivery Service Requests, Configure, Topology, Tools, User Admin, and Other. The main content area has a breadcrumb trail: 'Delivery Services / demo1 / Static DNS Entries / New'. Below this is a form with four fields: 'Host' (text input with 'foo'), 'Type' (dropdown menu with 'A_RECORD'), 'TTL' (text input with '42' and increment/decrement buttons), and 'Address' (text input with '192.0.2.1'). A green 'Create' button is at the bottom right of the form. The top right of the portal shows user 'admin' and a notification icon.

Fig. 46: An Example Static DNS Entry Form


6. Click on the green *Create* button to finalize the changes.
7. At this point, although the static DNS record has been created, it will have no effect until a new CDN *Snapshot* is taken. Once that is done (and enough time has passed for Traffic Router to poll for the changes), the new DNS record should be usable through the CDN’s designated Traffic Router.

86: Example DNS Query to Test a New Static DNS Entry within *CDN in a Box*

```
$ docker exec cdnabox_enroller_1 dig +noall +answer foo.
demo1.mycdn.ciab.test
foo.demo1.mycdn.ciab.test. 42    IN    A    192.0.2.1
```

Configure Delivery Service Steering

1. Create two target *Delivery Services* in Traffic Portal. They must both be HTTP *Delivery Services* that are part of the same CDN.




The screenshot shows the 'TRAFFIC PORTAL' interface with a sidebar menu on the left. The main content area is titled 'Delivery Services' and displays a table with two entries. The table has columns for Key (DNS ID), Tenant, Origin, Active, Type, Protocol, CDN, IPv6 Enabled, DISC, Signing Algorithm, Query Handling, Last Updated, and Actions. The first entry has Key '1', Tenant 'root', Origin 'http://origin1.cdn.local', and is active. The second entry has Key '2', Tenant 'root', Origin 'http://origin2.cdn.local', and is also active. Both are of Type 'HTTP' and Protocol 'HTTP', using the 'ciab' CDN.

Key (DNS ID)	Tenant	Origin	Active	Type	Protocol	CDN	IPv6 Enabled	DISC	Signing Algorithm	Query Handling	Last Updated	Actions
1	root	http://origin1.cdn.local	true	HTTP	HTTP	ciab	true	0		USE	2 minutes ago	
2	root	http://origin2.cdn.local	true	HTTP	HTTP	ciab	true	0		USE	a minute ago	

Fig. 47: Target *Delivery Services*


2. Create a *Delivery Service* with Type STEERING or CLIENT_STEERING in Traffic Ops.



The screenshot shows the 'TRAFFIC PORTAL' interface with a sidebar menu on the left. The main content area is titled 'Delivery Services / New' and contains a form for creating a new delivery service. The form fields include: Active (set to true), Content Routing Type (set to STEERING), Key (DNS ID) (set to 3), Display Name (set to steering-deliveryservice), Tenant (set to root), CDN (set to ciab), Protocol (set to HTTP), Long Description (set to A STEERING service), Long Description 2, and Long Description 3. There are 'View Details' links for Tenant, CDN, and Protocol. At the bottom right, there are 'Show Advanced' and 'Create' buttons.

Fig. 48: Creating a STEERING *Delivery Service*

3. Click *More* → *View Targets* and then use the blue + button to assign targets.
4. If desired, a ‘steering’ *Role* user can create filters for the target *Delivery Services* using *steering/{{ID}}/targets*



Delivery Service	Target	Type	Value
3	2	STEERING_WEIGHT	1
3	1	STEERING_WEIGHT	1

Fig. 49: STEERING Targets

Note: This is only available via the *Traffic Ops API*; no functionality for manipulating steering targets is offered by Traffic Portal. This feature has been requested and is tracked by [GitHub Issue #2811](#)

- Any requests to Traffic Router for the steering *Delivery Service* should now be routed to target *Delivery Services* based on configured weight or order.

Note: This example assumes that the Traffic Ops instance is running at `to.cdn.local` and the administrative username and password are `admin` and `twelve`, respectively. This is *not* recommended in production, but merely meant to replicate the default *CDN in a Box* environment!

DEVELOPER'S GUIDE

A guide to the various internal and external APIs, and an introduction for the Traffic Control developer.

4.1 Developer's Guide

Use this guide to start developing applications that consume the Traffic Control APIs, to create extensions to Traffic Ops, or work on Traffic Control itself.

4.1.1 API Guidelines

This section lays out guidelines to be considered by API endpoint authors. What follows are not *strictly* hard-and-fast rules, but there should be a very convincing argument accompanying endpoints that do not follow them.

Legacy API versions don't, in general, adhere to these principles. This section is not meant as a proposal for altering them to be compliant, but merely a set of guidelines for future work.

Response Bodies

All valid API responses will be in the form of some serialized object. The main data that represents the result of the client's request **MUST** appear in the `response` property of that object. If a warning, error message, success message, or informational message is to be issued by the server, then they **MUST** appear in the `alerts` property of the response. Some endpoints may return ancillary statistics such as the total number of objects when pagination occurs, which should be placed in the `summary` property of the response.

Response

The `response` property of a serialized response object **MUST** only contain object representations as requested by the client. In particular, it **MUST NOT** contain admonitions, success messages, informative messages, or statistic summaries beyond the scope requested by the client.

Equally unacceptable API responses are shown in *Success Message as Response Object* and *Illegal Top-Level Property*.

87: Success Message as Response Object

```
{
  "response": "Thing was successfully created."
}
```

88: Illegal Top-Level Property

```
{
  "response": {"foo": "bar"},
  "someOtherField": {"someOtherObject"}
}
```

When requests are serviced by Traffic Ops that pass data asking that the returned object list be filtered, the `response` property **MUST** be a filtered array of those objects (assuming the request may be successfully serviced). This is true even if filtering is being done according to a uniquely identifying property - e.g. a numeric ID. The `response` field of an object returned in response to a request to create, update, or delete one or more resources may be either a single object representation or an array thereof according to the number of objects created, updated, or deleted. However, if a handler is *capable* of creating, updating, or deleting more than one object at a time, the `response` field **SHOULD** consistently be represented as an array - even if its length would only be 1.

The proper value of an empty collection is an empty collection. If a Foo can have zero or more Bars, then the representation of a Foo with no Bars **MUST** be an empty array/list/set, and in particular **MUST NOT** be either missing from the representation or represented as the “Null” value of the representation format. That is, if Fools have no other property than their Bars, then a Foo with no Bars may be represented in JSON encoding as `{"bars": []}`, but not as `{"bars": null}` or `{}`. Similarly, an empty string field is properly represented as an empty string - e.g. `{"bar": ""}` not `{"bar": null}` or `{}` - and the “zero-value” of numbers is zero itself - e.g. `{"bar": 0}` not `{"bar": null}` or `{}`. Note that “null” values *are allowed* when appropriate, but “null” values represent the *absence* of a value rather than the “zero-value” of a property. If a property is *missing* from an object representation it indicates the absence of that property, and because of that there must be a *very convincing* argument if and when that is the case.

As a special case, endpoints that report statistics including minimums, maximums and arithmetic means of data sets **MUST** use the property names `min`, `max`, and `mean`, respectively, to express those concepts. These **SHOULD** be properties of response directly whenever that makes sense.

Alerts

Alerts should be presented as an array containing objects which each conform to the object definition laid out by [github.com/apache/trafficcontrol/tree/master lib/go-tc#Alert](https://github.com/apache/trafficcontrol/tree/master/lib/go-tc#Alert)'s `Alert` structure. The allowable levels of an `Alert` are:

- **error** - This level **MUST** be used to indicate conditions that caused a request to fail. Because of this, this level **MUST NOT** appear in the `alerts` array of responses with any HTTP response code less than 400 (except when used for asynchronous tasks as discussed in [202 Accepted](#)). Details of server workings and/or failing components **MUST NOT** be exposed in this message, which should otherwise be as descriptive as possible.
- **info** - This level **SHOULD** be used to convey supplementary information to a user that is not directly the result of their request. This **SHOULD NOT** carry information indicating whether or not the request succeeded and why/why not, as that is best left to the **error** and **success** levels.
- **success** - This level **MUST** be used to convey success messages to the client. In general, it is expected that the message will be directly displayed to the user by the client, and therefore can be used to add human-friendly details about a request beyond the response payload. This level **MUST NOT** appear in the `alerts` array of responses with an HTTP response code that is not between 200 and 399 (inclusive).
- **warning** - This level is used to warn clients of potentially dangerous conditions when said conditions have not caused a request to fail. The best example of this is deprecation warnings, which should appear on all API routes that have been deprecated.

Summary

The `summary` object is used to provide summary statistics about object collections. In general the use of `summary` is left to be defined by API endpoints (subject to some restrictions). However, its use is not appropriate in cases where the user is specifically requesting summary statistics, but should rather be used to provide supporting information - pre-calculated - about a set of objects or data that the client *has* requested.

Endpoints **MUST** use the following, reserved properties of `summary` for their described purposes (when use of `summary` is appropriate) rather than defining new `summary` or `response` properties to suit the same purpose:

- **count** - Count contains an unsigned integer that defines the total number of results that could possibly be returned given the non-pagination query parameters supplied by the client.

HTTP Request Methods

RFC 7231#section-4 defines the semantics of HTTP/1.1 request methods. Authors should conform to that set of standards whenever possible, but for convenience the methods recognized by Traffic Ops and their meanings in that context are herein defined.

GET

HTTP GET requests are issued by clients who want some data in response. In the context of Traffic Ops, this generally means a serialized representation of some object. GET requests **MUST NOT** alter the state of the server. An example of an API endpoint created in API version 1 that violates this restriction is `cdns/name/name/dnsseckey/delete`.

This is the standard method to be used by all read-only operations, and as such handlers for this method should generally be accessible to users with the “read-only” *Role*.

All endpoints dealing with the manipulation or fetching representations of “Traffic Control Objects” **MUST** support this method.

POST

POST requests ask the server to process some provided data. Most commonly, in Traffic Ops, this means creating an object based on the serialization of said object contained in the request body, but it can also be used virtually whenever no other method is appropriate. When an object *is* created, the response body **MUST** contain a representation of the newly created object. POST requests do not need to be *idempotent*, unlike PUT requests.

PUT

PUT is used to replace existing data with new data that is provided in the request body. **RFC 2616#section-9.1.2** lists PUT as an “idempotent” request method, which means that subsequent identical requests should ensure the same state is maintained on the server. What this means is that a client that PUTs an object representation to Traffic Ops expects that if they then GET a representation of that object, do the same PUT again and GET another representation, the two retrieved representations should be identical. Effectively, the `lastUpdated` field that is common to objects in the *Traffic Ops API* violates this, but the other properties of objects - which can actually be defined - generally obey this restriction. In general, fulfilling this restriction means that handlers will need to require the entirety of an object be defined in the request body.

When an object is replaced, the response body **MUST** contain a representation of the object after replacement. While **RFC 2616** states that servers **MAY** create objects for the passed representations if they do not already exist, *Traffic Ops API* endpoint authors **MUST** instead use POST handlers for object creation.

All endpoints that support the PUT request method **MUST** also support the *If-Unmodified-Since* HTTP header.

PATCH

At the time of this writing, no *Traffic Ops API* endpoints handle the PATCH request method. PATCH requests that the server's stored data be mutated in some way using data provided in the request body. Unlike PUT, PATCH is not *idempotent*, which essentially means that it can be used to change only part of a stored object. When an object is modified, the response body **MUST** contain a representation of the object after modification, and that representation **SHOULD** fully describe the modified object, even the parts that were not modified.

Handlers that implement PATCH in the *Traffic Ops API* **MUST** use conditional requests to ensure that race conditions are not a problem, specifically they **MUST** support using *ETag* and *If-Match*, and **SHOULD** also support *If-Unmodified-Since*.

Clients **SHOULD** use PATCH requests rather than PUT requests for modifying existing resources whenever it is supported.

DELETE

DELETE destroys an object stored on the server. Typically the request will contain identifying information for the object(s) to be destroyed either in the request URI or in the request's body. *Traffic Ops API* endpoint authors **MUST** use this request method whenever an object identified by the request URI is being destroyed. When such deletion successfully occurs, the response body **MUST** contain a representation of the destroyed object.

HTTP Response Codes

Proper use of HTTP response codes can significantly improve user interfaces built on top of the API. What follows is a (non-exhaustive) set of response codes and their appropriate use in the context of Traffic Ops. For more complete information, refer to [the Mozilla Developer Network's HTTP Response Code list](#).

200 OK

This indicates the request succeeded, with no additional semantics. This **MUST** be the exact response status code of successful GET requests. This is also the default “success” response code for any other request.

201 Created

This indicates that a resource was successfully created on the server. This **MUST** be the response status code of POST requests that create a new object or objects on the server, and in that case the response **SHOULD** also include a *Location* header that provides a URI where a representation of the newly created object may be requested.

202 Accepted

202 Accepted **MUST** be used when the server is performing some task asynchronously (e.g. refreshing DNSSEC keys) but the status of that task cannot be ascertained at the current time. Ideally in this case, when the task completes - either successfully or by failing - the Traffic Ops changelog will be updated to indicate that status, along with information to uniquely identify the task (e.g. username and date/time when the task started).

Endpoints that create asynchronous jobs **SHOULD** provide a URI to which the client may send GET requests to obtain a representation of the job’s current state in the *Location* HTTP header. They **MAY** also provide an *info*-level Alert that provides the same or similar information in a more human-friendly manner.

The responses to such GET requests are subject to the same restrictions as any other API endpoint, but have the added restriction that the response objects sent **MUST** have the *status* property, which is a string limited to one of the following values and having the associated semantics:

PENDING This means the job has been started but is not yet completed.

SUCCEEDED This means that the asynchronous job has completed and encountered no errors.

FAILED The task encountered errors and was unable to continue, and thus has been terminated.

Note that the response code of the response carrying this information **MUST NOT** depend on the value of *status*. In particular, a response that successfully reports the status of a **FAILED** asynchronous task is still successfully servicing a client’s GET request, and therefore **MUST** have the **200 OK** response status code. However, a response encoding a **FAILED** status **MUST** be accompanied by one or more *error*-level Alerts that explain (to the greatest degree of detail allowable securely) why the job failed.

These responses **MUST** also include the *startTime* and *endTime* properties which indicate, respectively, the time at which the asynchronous job started and the time at which it concluded.

A job that has not started **MUST** have a Null-valued `startTime` and likewise a job that has yet to conclude **MUST** have a Null-value `endTime`.

400 Bad Request

In general this is used when there's something syntactically wrong with the client's request. For example, Traffic Ops **MUST** respond with this code when the request body was improperly encoded. In most cases, this is also the proper response code when the client submits data that is not semantically correct. For example, dates/times represented as timestamp strings in an unsupported format should trigger this response code.

This is also the default "client failure" response code for any other request.

The response body **MUST** include an entry in the `alerts` array that describes to the client what was wrong with the request.

401 Unauthorized

This **MUST** be the response code when a client without valid authorization information in the HTTP headers requests a resource which cannot be accessed without first authorizing. Which should be everything except `/ping` and endpoints that provide authorization.

403 Forbidden

This **MUST** be used whenever the client is logged-in, but still does not have access to the resource they are requesting. It **MUST** also be used when they have some access to the resource, but not with the specific request method they used. This can pertain to restricted access on the basis of *Role*, User Permissions, as well as *Tenancy*.

The response body **MUST NOT** disclose any information regarding why the user was denied access.

404 Not Found

This **MUST** be the returned status code when the client requests a path that does not exist on the server. Note that a *path* does not include a *query string*; in the URL `http://example.test/some/path?query#frag` the *path* consists of only `/some/path`.

409 Conflict

This SHOULD be used when the request cannot be completed because the current state of the server is fundamentally incompatible with the request. For example, creating a new user with an email that is already in use should result in this response.

Additionally, this MAY be used instead of *404 Not Found* when the client is requesting a link between an object identified by the request URI and some other object (e.g. when assigning a *cache server* to a *Delivery Service*) when the other object does not exist. If the request URI identifies an object that does not exist, the response MUST use *404 Not Found* instead.

This is also the proper response status code when the conditions of a request cannot be met, e.g. when a client submits a PATCH request for a resource with an *If-Match* header that does not match the stored object's *ETag*.

The response body MUST indicate what the conflict is that prevented the request from being fulfilled via one or more **error-level** alerts.

500 Internal Server Error

When the Traffic Ops server encounters some error - through no fault of the client or their request - that renders it incapable of servicing the client's request, it MUST return this status code if no other code is more appropriate. The response body in this case SHOULD indicate that an error occurred, but MUST NOT divulge details about what data was being processed, what (if any) other components are not functioning properly, or what process failed. Generally it is advisable that the resultant alerts array entry just say "Internal Server Error" and nothing else.

501 Not Implemented

This is the response code used when the client requests an API version not implemented by the server. It SHOULD NOT be used in any other case.

502 Bad Gateway

This code indicates that some other service on which the endpoint's processes depend has given back improper data or an error response. It MAY be used (with caution) by plugin developers, but SHOULD NOT be used by authors of proper API endpoints, as that divulges information about failing connected systems and potentially gives an attacker information about Traffic Control's weak points. API endpoint authors should instead use *500 Internal Server Error*.

504 Gateway Timeout

This code indicates that a connection timeout occurred when attempting to contact some other service on which the endpoint's processes depend. It MAY be used (with caution) by plugin developers, but SHOULD NOT be used by authors of proper API endpoints, as that divulges information about failing connected systems and potentially gives an attacker information about Traffic Control's weak points. API endpoint authors should instead use *500 Internal Server Error*.

Documentation

All endpoints MUST be properly documented. For guidelines for writing API documentation, refer to *Documenting API Routes*.

Passing Request Data

Request data may be passed in the request body or as a *application/x-www-form-urlencoded*-encoded query string in the request URI, or as a part of the request path. Request data MUST NOT be passed through a portion of the request path unless it uniquely identifies a resource with which the client may interact. For example, */foos/ID* is an acceptable path for dealing with the particular "Foo" object that has some identifier ID, but *logs/Number of Days/days* is unacceptable because reasonable default behavior can be provided if no number of days is given in the query string parameters, and that doesn't help uniquely identify a resource. Request path parameters should use double "curly-braces" (*{* and *}*) to call out variable components of the request path in documentation and references. Request path parameters MUST NOT be used for data that is optional to the request (somewhat obviously). Note that all endpoints dealing with the manipulation of "Traffic Control Objects" MUST support the GET HTTP request method.

When accepting data in the request body of requests, the endpoint MUST properly document the object representations (properties and their types) it accepts and MUST reject semantically invalid data with a *400 Bad Request* response code. For example, if an endpoint specifies it accepts a representation of a Foo object, assuming Foo objects possess only the Bar property which is an arbitrary string, then the endpoint MUST accept *{"bar": "testquest"}* as semantically valid (The data may be rejected for other reasons, e.g. if a Foo with such a Bar property already exists and Bars must be unique among all Foos) and MUST reject *{"bar": "testquest", "someOtherProperty": 10}* as semantically invalid. This is in contrast to the API's behavior at the time of this writing, which silently ignores unrecognized properties of request body objects.

The decision to pass data in the request body or query string is mainly up to the author, but some helpful tips:

- GET and DELETE requests do not typically provide request bodies.
- Query parameters should nearly always be optional. If data is required by an endpoint, consider requiring it in the request body. If the data identifies a resource, it ought to be a path parameter.

- Request body data often represents objects that are being created or updated. If an object is being created or updated, it ought to be defined in the request body, and if any additional data is (possibly optionally) required then it ought to be passed in the query string to separate it from the object definition.
- The following query parameters are reserved for special use by Traffic Ops endpoint handlers, and may not be used for any purpose other than their prescribed functions.
 - `limit`
 - `newerThan`
 - `offset`
 - `olderThan`
 - `orderBy`
 - `page`
 - `sortOrder`

Duplicate Endpoints

No two endpoints should serve the same purpose. While it's fine to overlap a bit, an endpoint like `/foo_bars` should not exist solely to edit the `Bars` property of `Foo` objects (which can ostensibly be edited just fine on the object itself), for example. Ideally, there should be exactly one way to accomplish something through the API.

A caveat, though, is object relationships. For example, a *Delivery Service* has zero or more *cache servers* assigned to it, and in turn *cache servers* may be assigned to zero or more *Delivery Services* (a “has-and-belongs-to-many” relationship). Thus it is permissible to be able to edit the *Delivery Services* property of a *cache server* using the `/cache_servers` API endpoint as well as to be able to edit the *cache servers* property of a *Delivery Service* using the `/delivery_services` API endpoint - though they arguably provide equivalent functionality in that way (although at the time of this writing the former endpoint doesn't exist and the latter doesn't offer that functionality - this is just an example).

Date/Time Format

Dates MUST be represented in either **RFC 3339** (with or without nanosecond precision) or as integers indicating the number of nanoseconds past the Unix epoch at which the date/time occurs. In either case, Dates included in responses from Traffic Ops MUST be in UTC. Wherever date/times are accepted as input, *Traffic Ops API* endpoints MUST accept either format and SHOULD NOT accept anything else.

Traffic Ops endpoints MUST return dates and times in **RFC 3339** format with nanosecond precision. Endpoints MAY provide ways for the client to specify alternate representations, but these SHOULD be restricted to only Unix epoch timestamps in nanoseconds.

Age Filtering

Whenever object age is a property of that object (which is quite often in the form of `lastUpdated`), Traffic Ops endpoint handlers that respond to requests for object representations (i.e. GET requests) **SHOULD** support filtering by age. If age filtering is implemented, it **MUST** be made available using the query parameters in the table below.

Table 69: Age Filtering Query Parameters

Parameter	Meaning
<code>newerThan</code>	Timestamp to be used as the lower limit on an object's age. Objects older than this MUST NOT appear in the response body. That is, the response will be the set of all objects in the collection with a modification date that is greater than <i>or equal to</i> this value.
<code>olderThan</code>	Timestamp to be used as the upper limit an object's age. Objects newer than this MUST NOT appear in the response body. That is, the response will be the set of all objects in the collection with a modification date that is less than <i>or equal to</i> this value.

The format of these timestamps - in accordance with the [Date/Time Format](#) section - **MUST** be accepted as Unix epoch timestamps in nanoseconds, **and** in the form of [RFC 3339](#) date/time strings.

Endpoints **MAY** return errors when a client request gives these parameters improper or invalid values, but **MUST** at least provide a warning. When ambiguity or errors in age filtering controls render age filtering impossible, the handler **MUST NOT** perform age filtering.

Tenancy

When a client requests access to a set of stored objects that are “tenantable” inevitably some of them will be inaccessible to the user on the basis of their [Tenant](#). Traffic Ops endpoint handlers that respond to requests for such object representations (i.e. GET requests) **MUST** filter their results implicitly according to the requesting Tenant's access. Any request that would modify, create, or destroy an object to which the requesting [Tenant](#) does not have access **MUST NOT** be fulfilled by the server (obviously) and in that case the response status code **MUST** be [403 Forbidden](#). Furthermore, if a request for a representation of a [Tenant](#)-inaccessible object is made *explicitly for said object* (e.g. GET `/foos/ID` rather than GET `/foos?id=ID`) the response status code **MUST** be [403 Forbidden](#).

Naming Conventions

The names of properties of objects as they appear in said objects' serializations ought to conform to “camelCase” naming. Initialisms, abbreviations, and acronyms that appear in property names should be capitalized unless they are at the very beginning of the name. For example, `myIPAddress` and `someProperty` are both well-formed property names, while `IPAddress`, `someproperty` and `SomeProperty` are not.

Query string parameters **MUST** also follow “camelCase” naming.

API endpoints themselves should have a name that conveys their purpose. For example, `/cdns` is an endpoint that deals with manipulating, creating, destroying, or retrieving representations of CDNs. Request paths **MUST** use “snake_case” to separate words whenever necessary, and **MUST** never include the action being performed by the handler; instead that is decided by the request *method*. For example, `/myObject/delete` is a poor request path name for both of those reasons. Furthermore, when an endpoint deals with an object type of which there are typically multiple, the request path should be plural, e.g. `/cdns` is better than `/cdn`.

API endpoints **MAY** support trailing slashes (/) in the request path, but **MUST NOT** include suffixes that indicate a particular encoding (“file extensions”); that's what the *Content-Type* header is for. For example, in API version 1.x, `/foos` and `/foos.json` are both equally valid ways to access the `/foos` endpoint handlers - this is no longer allowed!

Relationships as Objects

Relationships **SHOULD NOT** be represented through the API as objects in their own right. For example, instead of an endpoint like `/delivery_service_servers` used to manipulate assignments of *cache servers* to *Delivery Services*, a *Delivery Service* itself should have *Servers* as a property. Thus assignments are manipulated by manipulating that property. So the only endpoints necessary for fully defining and dealing with such relationships are `/delivery_services` and `/servers`.

Change Logging

All manipulations of objects (i.e. any operation that is not merely “reading” data) **MUST** add a Change Log entry indicating what was changed.

4.1.2 Environment Variables

Various ATC components and tools use specific environment variables to modify their behavior - in some cases they're even mandatory. What follows is a (hopefully) exhaustive list of the environment variables used in multiple places throughout the project - variables used by only a single tool or component can be found in the usage/development documentation for that tool or component. Developers are encouraged to expand the usage of variables mentioned here rather than create new ones to serve the same purpose in a different tool.

Tip: As environment variables can be set by any parent process, possibly unknown to the user or merely forgotten, they should generally have the lowest precedence of setting any given configuration (when multiple exist, e.g. configuration file parameters or command-line arguments) and should not be required if possible. It can be confusing to a user if `some-tool --to-url="http://to.infra.ciab.test"` actually uses some Traffic Ops URL other than the one they can see and specified explicitly. The suggested precedence order is:

1. Command-line arguments
 2. Configuration file entries/parameters/lines
 3. Environment variables
-

MOJO_MODE

This is a legacy environment variable only used for compatibility's sake - new tools should not need to use it for anything, in general. It refers to the environment or "mode" of the Traffic Ops server from back in the old Perl days. Effectively, this chooses the set of configuration files it will consult. The default value is "development", and the possible values are:

- development
- integration
- production
- test

admin sets this to the value of the environment as specified by `admin --env` (Default: development)

TO_PASSWORD

This is used - typically in concert with `TO_PASSWORD` and `TO_USER` - to provide a password for a user as whom to authenticate with some Traffic Ops instance. This generally should not be validated, to avoid having to update validation to match the *Traffic Ops API*'s own validation - because in general this will/should end up in the payload of an authentication request to *user/login*.

Caution: For security reasons, the contents of this environment variable should not be stored anywhere for any length of time that isn't strictly necessary.

The following list details which components/tools use this variable, how, and what, if any, restrictions they place upon its content.

- `infrastructure/cdn-in-a-box/traffic_ops/to-access.sh` expects this password to authenticate the administrative-level user given by `TO_USER`.
- `atstccfg` uses this variable to authenticate the user used for fetching configuration information.

- *toaccess* uses this variable to authenticate with the Traffic Ops instance before sending requests.

TO_URL

This is used - typically in concert with *TO_USER* and *TO_PASSWORD* - to identify a Traffic Ops instance for some purpose. In general, this should be able to handle the various ways to identify a network location, and need not be restricted to strictly a URL - for example, an FQDN without a scheme should be acceptable, with or without port. When ports are not given, but scheme is, the port to use should be trivially deducible from a given supported scheme - 80 for `http://` and 443 for `https://`. When the scheme is not given but the port is, the reverse assumptions should be made. When neither are given, or the port is non-standard, then `https://` and port 443 (if applicable) should be assumed.

There are cases in the repository today where that is not true. The following list details the components/tools that use this variable and their restrictions and expected formats for it, if they differ from the description above.

- `infrastructure/cdn-in-a-box/traffic_ops/to-access.sh` uses this variable to connect to the *CDN in a Box* Traffic Ops instance. It is passed directly to `curl(1)` after path portions are appended, and so is subject to the restrictions and assumptions thereof.
- The Traffic Ops *Go Tests* for integration with the Go client use this to define the URL at which the Traffic Ops instance is running. It will override configuration file settings that specify the instance location.
- *atstccfg* uses this variable to specify the Traffic Ops instance used to fetch configuration information.
- *toaccess* uses this variable to identify the Traffic Ops instance to which requests will be sent.

TO_USER

This is used - typically in concert with *TO_PASSWORD* and *TO_USER* - to provide a user name as whom to authenticate with some Traffic Ops instance. This generally should not be validated, to avoid having to update validation to match the *Traffic Ops API*'s own validation - because in general this will/should end up in the payload of an authentication request to *user/login*.

The following list details which components/tools use this variable, how, and what, if any, restrictions they place upon its content.

- `infrastructure/cdn-in-a-box/traffic_ops/to-access.sh` expects this to be the name of an administrative-level user.
- *atstccfg* uses this variable to name the user as whom to authenticate for fetching configuration information.
- *toaccess* uses this variable to authenticate with the Traffic Ops instance before sending requests.

4.1.3 Building Traffic Control

The build steps for Traffic Control components are all pretty much the same, despite that they are written in a variety of different languages and frameworks. This is accomplished by using Docker.

Note: Currently, both listed methods of building Traffic Control components will produce *.rpm files, meaning that the support of these components is limited to RedHat-based distributions - and none of them are currently tested (or guaranteed to work) outside of CentOS 7 and CentOS 8, specifically.

Downloading Traffic Control

If any local work on Traffic Monitor, Traffic Router Golang, Grove or Traffic Ops is to be done, it is **highly** recommended that [the Traffic Control repository](#) be downloaded inside the \$GOPATH directory. Specifically, the best location is \$GOPATH/src/github.com/apache/trafficcontrol. Cloning the repository outside of this location will require either linking the actual directory to that point, or moving/copying it there.

See also:

The Golang project's GOPATH [wiki page](#)

Build Using pkg

This is the easiest way to build all the components of Traffic Control; all requirements are automatically loaded into the image used to build each component. The pkg command can be found at the root of the Traffic Control [repository](#).

Requirements

- [Docker](#)
- [Docker Compose](#)¹

¹ This is optional, but recommended. If a docker-compose executable is not available the pkg script will automatically download and run it using a container. This is noticeably slower than running it natively.

Usage

```
./pkg [options] [projects]
```

Note: The `pkg` script often needs to be run as `sudo`, as certain privileges are required to run Docker containers

Options

-7	Build RPMs targeting CentOS 7 (default)
-8	Build RPMs targeting CentOS 8
-b	Build builder Docker images before building projects
-d	Disable compiler optimizations for debugging.
-l	List available projects.
-p	Pull builder Docker images, do not build them (default)
-q	Quiet mode. Suppresses output. (default)
-v	Verbose mode. Lists all build output.

If present, `projects` should be one or more project names. When no specific project or project list is given the default projects will be built. Valid projects:

- docs
- grove_build²
- grovetccfg_build
- source²
- traffic_monitor_build²
- traffic_ops_build²
- cache-config_build²
- traffic_portal_build²
- traffic_router_build²
- traffic_stats_build²
- weasel

Output `component-version.rpm` files, build logs and source tarballs will be output to the `dist/` directory at the root of the Traffic Control repository directory.

² This is a default project, which will be built if `pkg` is run with no `projects` argument

Build Using docker-compose

If the `pkg` script fails, `docker-compose` can still be used to build the projects directly. The compose file can be found at `infrastructure/docker/build/docker-compose.yml` under the repository's root directory. It can be passed directly to `docker-compose`, either from the `infrastructure/docker/build/` directory or by explicitly passing a path to the `infrastructure/docker/build/docker-compose.yml` file via `-f`. It is recommended that between builds `docker-compose down -v` is run to prevent caching of old build steps. The service names are the same as the project names described above in *Usage*, and similar to the `pkg` script, the build results, logs and source tarballs may all be found in the `dist` directory after completion.

Note: Calling `docker-compose` in the way described above will build `_all_` projects, not just the default projects.

See also:

[The Docker Compose command line reference](#)

Build the RPMs Natively

A developer may end up building the RPMs several times to test or *debug* code changes, so it can be desirable to build the RPMs quickly for this purpose. Natively building the RPMs has the lowest build time of any building method.

Install the Dependencies

Table 70: Build dependencies for Traffic Control

	Common dependencies	Traffic Monitor	Traffic Ops	Traffic Portal	Traffic Router	Traffic Stats	Grove	Grove TC Config (grovetc-cfg)	Docs
macOS (homebrew) ³	• rpm	• go	• go	• npm • grunt-cli	• maven	• go	• go	• go	• python3
CentOS/Red Hat/Fedora (yum) ⁴	• git • rpm-build • rsync			• epel-release • npm • nodejs-grunt-cli • ruby-devel • gcc • make	• java-1.8.0-openjdk • maven			• python3-devel • gcc • make	
Arch Linux (pacman)	• git • rpm-tools • diff • rsync	• go	• go	• npm • make • grunt-cli • ruby • gcc	• jdk8-openjdk • maven	• go	• go	• go	• python-pip • python-sphinx • make
Windows (cygwin) ⁵	• git			• ruby-devel	• curl				
270	• rpm-build			• make					
	•			•					
Chapter 4. Developer's Guide									

After installing the packages using your platform's package manager,

- Install the *global NPM packages* and *Compass* to build Traffic Portal.
- Install the Python 3 modules used to *build the documentation*.

Run `build/clean_build.sh` directly

In a terminal, navigate to the root directory of the repository. You can run `build/clean_build.sh` with no arguments to build all components.

89: `build/clean_build.sh` with no arguments

```
build/clean_build.sh
```

This is the equivalent of running

90: `build/clean_build.sh` with all components

```
build/clean_build.sh tarball traffic_monitor traffic_ops traffic_
↪portal traffic_router traffic_stats grove grove/grovetccfg docs
```

If any component fails to build, no further component builds will be attempted.

By default, the RPMs will be built targeting CentOS 7. CentOS 8 is also a supported build target. You can choose which CentOS version to build for (7, 8, etc.) by setting the `RHEL_VERSION` environment variable:

³ If you are on macOS, you additionally need to *Get OpenJDK 8 on macOS*.

⁴ If you are on CentOS, you need to *download Go directly* instead of using a package manager in order to get the latest Go version. For most users, the desired architecture is AMD64/x86_64.

⁵ If you are on Windows, you need to install both the Cygwin packages and the Chocolatey packages in order to build the Apache Traffic Control RPMs natively.

91: Building RPMs that target CentOS 8 without the build host needing to be CentOS 8

```
export RHEL_VERSION=8
```

Warning: Although there are no known issues with natively-built RPMs, the official, supported method of building the RPMs is by using *pkg* or *docker-compose*. Use natively-built RPMs at your own risk.

Building Individual Components

Each Traffic Control component can be individually built, and the instructions for doing so may be found in their respective component's development documentation.

Building This Documentation

See instructions for *building the documentation*.

4.1.4 Debugging inside CDN-in-a-Box

Some CDN-in-a-Box components can be used with a debugger to step through lines of code, set breakpoints, see the state of all variables in each scope, etc. at runtime. Components that support debugging:

- *Enroller*
- *t3c on Caches*
 - *t3c on Edge Cache*
 - *t3c on Mid 01 Cache*
 - *t3c on Mid 02 Cache*
- *Traffic Monitor*
- *Traffic Ops*
- *Traffic Router*
- *Traffic Stats*

Enroller

- In `infrastructure/cdn-in-a-box`, open `variables.env` and set `ENROLLER_DEBUG_ENABLE` to `true`.
- Stop CDN-in-a-Box if it is running and remove any existing volumes. Build/rebuild the `enroller-debug` image each time you have changed `infrastructure/cdn-in-a-box/enroller/enroller.go`. Then, start CDN-in-a-Box.

92: docker-compose command for debugging the CDN in a Box Enroller

```
alias mydc='docker-compose -f docker-compose.yml -f docker-compose.
↪expose-ports.yml -f optional/docker-compose.debugging.yml'
mydc down -v
mydc build enroller
mydc up
```

- Install an IDE that supports `delve` and create a debugging configuration over port 2343. If you are using VS Code, the configuration should look like this:

93: VS Code launch.json for debugging the CDN in a Box Enroller

```
{
  "version": "0.2.0",
  "configurations": [
    {
      "name": "Enroller",
      "type": "go",
      "request": "attach",
      "mode": "remote",
      "port": 2343,
      "cwd": "${workspaceRoot}/",
      "remotePath": "/go/src/github.com/apache/trafficcontrol/",
    }
  ]
}
```

- Use the debugging configuration you created to start debugging the Enroller. It should connect without first breaking at any line.

For an example of usage, set a breakpoint at the `toSession.CreateDeliveryServiceV30()` call in `enrollDeliveryService()`, then wait for the Enroller to process a file from `/shared/enroller/deliveryservices/` (only exists within the Docker container).

t3c on Caches

t3c on Edge Cache

- Navigate to the `infrastructure/cdn-in-a-box` directory. Remove `infrastructure/cdn-in-a-box/cache/trafficcontrol-cache-config.rpm` because it contains release Go binaries that do not include useful debugging information. Rebuild the RPM with no optimization, for debugging:

94: Remove release RPMs, then build debug RPMs

```
make very-clean
make debug cache/trafficcontrol-cache-config.rpm
```

Tip: If you have gone through the steps to *Build the RPMs Natively*, you can run `make debug native cache/trafficcontrol-cache-config.rpm` instead of `make debug cache/trafficcontrol-cache-config.rpm` to build the RPM quickly.

- **Still in `infrastructure/cdn-in-a-box`, open `variables.env` and set `T3C_DEBUG_COMPONENT_E`**
 - `t3c-apply`
 - `t3c-check`
 - `t3c-check-refs`
 - `t3c-check-reload`
 - `t3c-diff`
 - `t3c-generate`
 - `t3c-request`
 - `t3c-update`

- Stop CDN-in-a-Box if it is running and remove any existing volumes. Build the edge-debug image to make sure it uses our fresh `trafficcontrol-cache-config.rpm`. Then, start CDN-in-a-Box:

95: docker-compose command for debugging t3c running on the Edge Cache

```
alias mydc='docker-compose -f docker-compose.yml -f docker-compose.
↪expose-ports.yml -f optional/docker-compose.debugging.yml'
mydc down -v
mydc build edge
mydc up -d
mydc logs -f trafficmonitor
```

- Install an IDE that supports delve and create a debugging configuration over port 2347. If you are using VS Code, the configuration should look like this:

96: VS Code launch.json for debugging t3c on the Edge
Cache

```
{
  "version": "0.2.0",
  "configurations": [
    {
      "name": "t3c on Edge",
      "type": "go",
      "request": "attach",
      "mode": "remote",
      "port": 2347,
      "cwd": "${workspaceRoot}",
      "remotePath": "/tmp/go/src/github.com/apache/trafficcontrol",
    },
  ]
}
```

Wait for Traffic Monitor to start, which will indicate that the SSL keys have been generated. Because T3C_DEBUG_COMPONENT_EDGE is set to the name of one of the t3c binaries, t3c will *not* run automatically every minute. Start it manually:

97: Run t3c-apply with debugging enabled

```
[user@computer cdn-in-a-box]$ mydc exec edge t3c apply --run-
mode=badass --traffic-ops-url=https://trafficops.infra.ciab.test --
traffic-ops-user=admin --traffic-ops-password=twelve12 --git=yes --
dispersion=0 --log-location-error=stdout --log-location-
warning=stdout --log-location-info=stdout all
API server listening at: [::]:2347
```

The *API server listening* message is from dlvs, indicating it is ready to accept a connection from your IDE. Note that, unlike the other components, execution of t3c does not begin until your IDE connects to dlvs.

For this example, set a breakpoint at the assignment of “`##OVERRIDDEN##`” + str to newstr in `torequest.processRemapOverrides()`.

Use the debugging configuration you created to connect to dlvs and start debugging t3c.

t3c on Mid 01 Cache

- Navigate to the `infrastructure/cdn-in-a-box` directory. Remove `infrastructure/cdn-in-a-box/cache/trafficcontrol-cache-config.rpm` because it contains release Go binaries that do not include useful debugging information. Rebuild the RPM with no optimization, for debugging:

98: Remove release RPMs, then build debug RPMs

```
make very-clean
make debug cache/trafficcontrol-cache-config.rpm
```

Tip: If you have gone through the steps to *Build the RPMs Natively*, you can run `make debug native cache/trafficcontrol-cache-config.rpm` instead of `make debug cache/trafficcontrol-cache-config.rpm` to build the RPM quickly.

- Still in `infrastructure/cdn-in-a-box`, open `variables.env` and set `T3C_DEBUG_COMPONENT_M`
 - `t3c-apply`
 - `t3c-check`
 - `t3c-check-refs`
 - `t3c-check-reload`
 - `t3c-diff`
 - `t3c-generate`
 - `t3c-request`
 - `t3c-update`
- Stop CDN-in-a-Box if it is running and remove any existing volumes. Build the mid-debug image to make sure it uses our fresh `trafficcontrol-cache-config.rpm`. Then, start CDN-in-a-Box:

99: docker-compose command for debugging t3c running on the Mid 01 Cache

```
alias mydc='docker-compose -f docker-compose.yml -f docker-compose.
↪expose-ports.yml -f optional/docker-compose.debugging.yml '
mydc down -v
mydc build mid-01
mydc up -d
mydc logs -f trafficmonitor
```

- Install an IDE that supports `delve` and create a debugging configuration over port 2348. If you are using VS Code, the configuration should look like this:

100: VS Code launch.json for debugging t3c on the Mid 01
Cache

```
{
  "version": "0.2.0",
  "configurations": [
    {
      "name": "t3c on Mid 01",
      "type": "go",
      "request": "attach",
      "mode": "remote",
      "port": 2348,
      "cwd": "${workspaceRoot}",
      "remotePath": "/tmp/go/src/github.com/apache/trafficcontrol
→",
    }
  ]
}
```

Wait for Traffic Monitor to start, which will indicate that the SSL keys have been generated. Because T3C_DEBUG_COMPONENT_MID_01 is set to the name of one of the t3c binaries, t3c will *not* run automatically every minute. Start it manually:

101: Run t3c-apply with debugging enabled

```
[user@computer cdn-in-a-box]$ mydc exec mid-01 t3c apply --run-
→mode=badass --traffic-ops-url=https://trafficops.infra.ciab.test --
→traffic-ops-user=admin --traffic-ops-password=twelve12 --git=yes --
→dispersion=0 --log-location-error=stdout --log-location-
→warning=stdout --log-location-info=stdout all
API server listening at: [::]:2348
```

The *API server listening* message is from dlvs, indicating it is ready to accept a connection from your IDE. Note that, unlike the other components, execution of t3c does not begin until your IDE connects to dlvs.

For this example, set a breakpoint at the assignment of “`##OVERRIDDEN##`” + str to newstr in `torequest.processRemapOverrides()`.

Use the debugging configuration you created to connect to dlvs and start debugging t3c.

t3c on Mid 02 Cache

- Navigate to the `infrastructure/cdn-in-a-box` directory. Remove `infrastructure/cdn-in-a-box/cache/trafficcontrol-cache-config.rpm` because it contains release Go binaries that do not include useful debugging information. Rebuild the RPM with no optimization, for debugging:

102: Remove release RPMs, then build debug RPMs

```
make very-clean
make debug cache/trafficcontrol-cache-config.rpm
```

Tip: If you have gone through the steps to *Build the RPMs Natively*, you can run `make debug native cache/trafficcontrol-cache-config.rpm` instead of `make debug cache/trafficcontrol-cache-config.rpm` to build the RPM quickly.

- Still in `infrastructure/cdn-in-a-box`, open `variables.env` and set `T3C_DEBUG_COMPONENT_M`
 - `t3c-apply`
 - `t3c-check`
 - `t3c-check-refs`
 - `t3c-check-reload`
 - `t3c-diff`
 - `t3c-generate`
 - `t3c-request`
 - `t3c-update`
- Stop CDN-in-a-Box if it is running and remove any existing volumes. Build the mid-debug image to make sure it uses our fresh `trafficcontrol-cache-config.rpm`. Then, start CDN-in-a-Box:

103: docker-compose command for debugging t3c running on the Mid 02 Cache

```
alias mydc='docker-compose -f docker-compose.yml -f docker-compose.
↪expose-ports.yml -f optional/docker-compose.debugging.yml '
mydc down -v
mydc build mid-02
mydc up -d
mydc logs -f trafficmonitor
```

- Install an IDE that supports `delve` and create a debugging configuration over port 2349. If you are using VS Code, the configuration should look like this:

104: VS Code launch.json for debugging t3c on the Mid 02
Cache

```
{
  "version": "0.2.0",
  "configurations": [
    {
      "name": "t3c on Mid 02",
      "type": "go",
      "request": "attach",
      "mode": "remote",
      "port": 2349,
      "cwd": "${workspaceRoot}",
      "remotePath": "/tmp/go/src/github.com/apache/trafficcontrol
→",
    }
  ]
}
```

Wait for Traffic Monitor to start, which will indicate that the SSL keys have been generated. Because T3C_DEBUG_COMPONENT_MID_02 is set to the name of one of the t3c binaries, t3c will *not* run automatically every minute. Start it manually:

105: Run t3c-apply with debugging enabled

```
[user@computer cdn-in-a-box]$ mydc exec mid-02 t3c apply --run-
→mode=badass --traffic-ops-url=https://trafficops.infra.ciab.test --
→traffic-ops-user=admin --traffic-ops-password=twelve12 --git=yes --
→dispersion=0 --log-location-error=stdout --log-location-
→warning=stdout --log-location-info=stdout all
API server listening at: [::]:2349
```

The *API server listening* message is from dlvs, indicating it is ready to accept a connection from your IDE. Note that, unlike the other components, execution of t3c does not begin until your IDE connects to dlvs.

For this example, set a breakpoint at the assignment of “`##OVERRIDDEN##`” + str to newstr in `torequest.processRemapOverrides()`.

Use the debugging configuration you created to connect to dlvs and start debugging t3c.

Traffic Monitor

- Navigate to the `infrastructure/cdn-in-a-box` directory. Remove the existing RPMs because they contain release Go binaries do not include useful debugging information. Rebuild the RPMs with no optimization, for debugging:

106: Remove release RPMs, then build debug RPMs

```
make very-clean
make debug traffic_monitor/traffic_monitor.rpm
```

Tip: If you have gone through the steps to *Build the RPMs Natively*, you can run `make debug native traffic_monitor/traffic_monitor.rpm` instead of `make debug traffic_monitor/traffic_monitor.rpm` to build the RPM quickly.

- Still in `infrastructure/cdn-in-a-box`, open `variables.env` and set `TM_DEBUG_ENABLE` to `true`.
- Stop CDN-in-a-Box if it is running and remove any existing volumes. Build the `trafficmonitor-debug` image to make sure it uses our fresh `traffic_monitor.rpm`. Then, start CDN-in-a-Box:

107: docker-compose command for debugging Traffic Monitor

```
alias mydc='docker-compose -f docker-compose.yml -f docker-compose.
→expose-ports.yml -f optional/docker-compose.debugging.yml'
mydc down -v
mydc build trafficmonitor
mydc up
```

- Install an IDE that supports `delve` and create a debugging configuration over port 2344. If you are using VS Code, the configuration should look like this:

108: VS Code launch.json for debugging Traffic Monitor

```
{
  "version": "0.2.0",
  "configurations": [
    {
      "name": "Traffic Monitor",
      "type": "go",
      "request": "attach",
      "mode": "remote",
      "port": 2344,
      "cwd": "${workspaceRoot}",
      "remotePath": "/tmp/go/src/github.com/apache/trafficcontrol
→",
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```
}
]
}
```

- Use the debugging configuration you created to start debugging Traffic Monitor. It should connect without first breaking at any line.

For an example of usage, set a breakpoint at the `o.m.RLock()` call in `ThreadsafeEvents.Get()`, then visit <http://trafficmonitor.infra.ciab.test/publish/EventLog> (see *Traffic Monitor APIs: /publish/EventLog*).

Traffic Ops

- Navigate to the `infrastructure/cdn-in-a-box` directory. Remove the existing RPMs because they contain release Go binaries do not include useful debugging information. Rebuild the RPMs with no optimization, for debugging:

109: Remove release RPMs, then build debug RPMs

```
make very-clean
make debug traffic_stats/traffic_stats.rpm
```

Tip: If you have gone through the steps to *Build the RPMs Natively*, you can run `make debug native traffic_stats/traffic_stats.rpm` instead of `make debug traffic_stats/traffic_stats.rpm` to build the RPM quickly.

- Still in `infrastructure/cdn-in-a-box`, open `variables.env` and set `TO_DEBUG_ENABLE` to true.
- Stop CDN-in-a-Box if it is running and remove any existing volumes. Build the `trafficops-debug` image to make sure it uses our fresh `traffic_ops.rpm`. Then, start CDN-in-a-Box:

110: docker-compose command for debugging Traffic Ops

```
alias mydc='docker-compose -f docker-compose.yml -f docker-compose.
↪expose-ports.yml -f optional/docker-compose.debugging.yml'
mydc down -v
mydc build trafficops
mydc up
```

- Install an IDE that supports delve and create a debugging configuration over port 2345. If you are using VS Code, the configuration should look like this:

111: VS Code launch.json for debugging Traffic Ops

```
{
  "version": "0.2.0",
  "configurations": [
    {
      "name": "Traffic Ops",
      "type": "go",
      "request": "attach",
      "mode": "remote",
      "port": 2345,
      "cwd": "${workspaceRoot}",
      "remotePath": "/tmp/go/src/github.com/apache/trafficcontrol",
    },
  ]
}
```

- Use the debugging configuration you created to start debugging Traffic Ops. It should connect without first breaking at any line.

For an example of usage, set a breakpoint at the `log.Debugln()` call in `TOPProfile.Read()`, then visit <https://trafficportal.infra.ciab.test/api/4.0/profiles> (after logging into *Traffic Portal*).

Traffic Router

- Navigate to the `infrastructure/cdn-in-a-box` directory.
- In `variables.env`, set `TR_DEBUG_ENABLE` to `true`.
- Install a debugging-capable Java IDE or text editor of your choice. If unsure, install IntelliJ IDEA Community Edition.
- At the base of the repository (not in the `cdn-in-a-box` directory), open the `traffic_router` directory in your IDE.
- Add a new “Remote” (Java) debug configuration. Use port 5005.
- Start CDN-in-a-Box, including the “expose ports” “debugging” compose files:

112: docker-compose command for debugging Traffic Router

```
alias mydc='docker-compose -f docker-compose.yml -f docker-compose.
→expose-ports.yml -f optional/docker-compose.debugging.yml'
mydc down -v
mydc build trafficrouter
mydc up -d
mydc logs --follow trafficrouter
```

- Watch the trafficrouter container's log. After DNS and certificate operations, the enroller, and Traffic Monitor, Traffic Router will start. Look for Listening for transport dt_socket at address: 5005 in the example log below:

113: Log of the Docker container for Traffic Router

```
Warning:
The JKS keystore uses a proprietary format. It is recommended.
→to migrate to PKCS12 which is an industry standard format using
→"keytool -importkeystore -srckeystore /opt/traffic_router/conf/
→keyStore.jks -destkeystore /opt/traffic_router/conf/keyStore.jks -
→deststoretype pkcs12".
Certificate stored in file <trafficrouter.infra.ciab.test.crt>

Warning:
The JKS keystore uses a proprietary format. It is recommended.
→to migrate to PKCS12 which is an industry standard format using
→"keytool -importkeystore -srckeystore /opt/traffic_router/conf/
→keyStore.jks -destkeystore /opt/traffic_router/conf/keyStore.jks -
→deststoretype pkcs12".
Waiting for enroller initial data load to complete....
Waiting for enroller initial data load to complete....
Waiting for enroller initial data load to complete....
Waiting for enroller initial data load to complete....
Waiting for enroller initial data load to complete....
Waiting for enroller initial data load to complete....
Waiting for enroller initial data load to complete....
Waiting for enroller initial data load to complete....
Waiting for enroller initial data load to complete....
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
```

(continues on next page)

(continued from previous page)

```

Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
Waiting for Traffic Monitor to start...
tail: cannot open '/opt/tomcat/logs/catalina.log' for reading:
→No such file or directory
tail: cannot open '/opt/tomcat/logs/catalina.2020-02-21.log'
→for reading: No such file or directory
==> /opt/traffic_router/var/log/traffic_router.log <==

==> /opt/traffic_router/var/log/access.log <==
Tomcat started.
tail: '/opt/tomcat/logs/catalina.log' has appeared; following
→end of new file
tail: '/opt/tomcat/logs/catalina.2020-02-21.log' has appeared;
→ following end of new file

==> /opt/traffic_router/var/log/traffic_router.log <==
INFO 2020-02-21T05:16:07.557 [Thread-3] org.apache.traffic_
→control.traffic_router.protocol.LanguidPoller - Waiting for state
→from mbean path traffic-router:name=languidState
INFO 2020-02-21T05:16:07.557 [Thread-4] org.apache.traffic_
→control.traffic_router.protocol.LanguidPoller - Waiting for state
→from mbean path traffic-router:name=languidState
INFO 2020-02-21T05:16:07.558 [Thread-5] org.apache.traffic_
→control.traffic_router.protocol.LanguidPoller - Waiting for state
→from mbean path traffic-router:name=languidState
INFO 2020-02-21T05:16:07.559 [Thread-6] org.apache.traffic_
→control.traffic_router.protocol.LanguidPoller - Waiting for state
→from mbean path traffic-router:name=languidState

==> /opt/tomcat/logs/catalina.log <==
Listening for transport dt_socket at address: 5005

Watch for the line that mentions port 5005 -----^^^

==> /opt/tomcat/logs/catalina.2020-02-21.log <==
21-Feb-2020 05:16:07.359 WARNING [main] org.apache.traffic_
→control.traffic_router.protocol.LanguidNioProtocol.<clinit> Adding
→BouncyCastle provider
21-Feb-2020 05:16:07.452 WARNING [main] org.apache.traffic_
→control.traffic_router.protocol.LanguidNioProtocol.<init> Serving
→wildcard certs for multiple domains

```

(continues on next page)

(continued from previous page)

```
21-Feb-2020 05:16:07.459 WARNING [main] org.apache.traffic_
→control.traffic_router.protocol.LanguidNioProtocol.<init> Serving_
→wildcard certs for multiple domains
21-Feb-2020 05:16:07.459 WARNING [main] org.apache.traffic_
→control.traffic_router.protocol.LanguidNioProtocol.<init> Serving_
→wildcard certs for multiple domains
21-Feb-2020 05:16:07.461 INFO [main] org.apache.traffic_
→control.traffic_router.protocol.LanguidNioProtocol.
→setSslImplementationName setSslImplementation: org.apache.traffic_
→control.traffic_router.protocol.RouterSslImplementation
```

- When you see that Tomcat is listening for debugger connections on port 5005, start debugging using the debug configuration that you created.

Traffic Stats

- Navigate to the `infrastructure/cdn-in-a-box` directory. Remove the existing RPMs because they contain release Go binaries do not include useful debugging information. Rebuild the RPMs with no optimization, for debugging:

114: Remove release RPMs, then build debug RPMs

```
make very-clean
make debug traffic_ops/traffic_ops.rpm
```

Tip: If you have gone through the steps to *Build the RPMs Natively*, you can run `make debug native traffic_ops/traffic_ops.rpm` instead of `make debug traffic_ops/traffic_ops.rpm` to build the RPMs quickly.

- Still in `infrastructure/cdn-in-a-box`, open `variables.env` and set `TS_DEBUG_ENABLE` to `true`.
- Stop CDN-in-a-Box if it is running and remove any existing volumes. Build the `trafficstats-debug` image to make sure it uses our fresh `traffic_stats.rpm`. Then, start CDN-in-a-Box:

115: docker-compose command for debugging Traffic Stats

```
alias mydc='docker-compose -f docker-compose.yml -f docker-compose.
→expose-ports.yml -f optional/docker-compose.debugging.yml'
mydc down -v
mydc build trafficstats
mydc up
```

- Install an IDE that supports `delve` and create a debugging configuration over port 2346. If you are using VS Code, the configuration should look like this:

116: VS Code launch.json for debugging Traffic Stats

```
{
  "version": "0.2.0",
  "configurations": [
    {
      "name": "Traffic Stats",
      "type": "go",
      "request": "attach",
      "mode": "remote",
      "port": 2346,
      "cwd": "${workspaceRoot}",
      "remotePath": "/tmp/go/src/github.com/apache/trafficcontrol
    },
  ]
}
```

- Use the debugging configuration you created to start debugging Traffic Stats. It should connect without first breaking at any line.

For an example of usage, set a breakpoint at the `http.Get()` call in `main.getURL()`, then wait 10 seconds for the breakpoint to be hit.

Troubleshooting

- If you are debugging a Golang project and you don't see the values of all variables, or stepping to the next line puts you several lines ahead, rebuild the Docker image with an RPM built using `make debug`.

4.1.5 Documentation Guidelines

The Apache Traffic Control documentation is written in RST (reStructuredText) and uses the [Sphinx documentation build system](#) to convert these into the desired output document format. This collection of guidelines does **not** aim to be a primer in RST, but merely a style guide regarding how the components of the document ought to be formatted and structured. It may also point out some features of the markup language of which a writer may not be aware.

See also:

[The docutils RST reference](#).

Building

This documentation uses the [Sphinx documentation build system](#), and as such requires a Python3 version that is at least 3.4.1. It also has dependency on Sphinx, and Sphinx extensions and themes. All of these can be easily installed using *pip* by referencing the requirements file like so:

117: Run from the Repository's Root Directory

```
python3 -m pip install --user -r docs/source/requirements.txt
```

Once all dependencies have been satisfied, build using the Makefile at docs/Makefile.

Alternatively, it is also possible to *Build Using pkg* or to *Build Using docker-compose*, both of which will output a documentation “tarball” to dist/.

Writing

When writing documentation, the most important things to remember are:

- **Spell Check.** Most text editors have this built-in (e.g. F6 in Sublime Text) or have plugins that will do this for you.
- **Proof-Read.** Spell-checkers won't catch grammatical errors or poor wording, so it's very important to actually proof-read all documentation *before* submitting it in a Pull Request.
- **Make Sure the Documentation Actually Builds.** Please actually verify the documentation not only builds, but builds *correctly*. That means there probably shouldn't be any warnings, no malformed tables etc. and it also means that new documentation is actually accessible once built. It's not enough to create a new *something.rst* file, that file must actually be linked to from some other, already included document. Some warnings may be considered acceptable, but do be prepared to defend them.
- **Traffic Ops UI is Dead.** Do not ever create documentation that references or includes images of the Traffic Ops UI. That is officially dead now, and if the documentation being created is best made with references to a user-friendly UI, such references, examples and/or images should all be to/of Traffic Portal.

Formatting

Whenever possible, avoid specifying manual line breaks, except as required by RST syntax. Extremely long lines will be wrapped by the user-agent, compiler, or output format as necessary. A single blank line may be used to separate paragraphs. This means that the ‘flow break’ character should never need to be used, i.e. no line in the documentation should ever match the regular expression `^\|`.

Abbreviations

When using an abbreviation, acronym or initialism for the first time on a page, it **must** be named fully and followed by the abbreviation in parentheses e.g. “Fully Qualified Domain Name (FQDN)”. Strictly speaking, the *best* way to create an abbreviation is to always fully name it in parentheses immediately following the abbreviation using the `:abbr:` RST text role e.g. `:abbr:`FQDN (Fully Qualified Domain Name)``, but it’s not reasonable to expect that of everyone. Some abbreviations can be assumed to be understood by the documentation’s target audience, and do not need full naming; they are general, basic networking and computing terms including (though not strictly limited to):

- API
- CSS
- DNS
- HTML
- HTTP
- HTTPS
- IP/IPv4/IPv6
- ISO
- JPG
- JSON
- PDF
- PNG
- RPM
- SQL
- SSL
- SVG
- TCP
- TLS
- UDP
- URL
- URI
- XML
- YAML

Please do **not** abbreviate Traffic Control terms e.g. *Cache Group*, *Delivery Service*. See *Terms* for the proper way to use these terms.

Floating Objects

“Floating objects” are images, tables, source code listings, and equations. These may not be placed relative to other content exactly as shown in the source RST document, as it may be necessary to move them for e.g. page breaks in PDF documents so they are not split across pages.

Figures

Images should *always* be included inside of a `.. figure` directive. **Always** caption figures to make their purpose clear, as well as to make them directly link-able inside of the document and include them in figure listings. Though not syntactically required, figures should, in general be sized explicitly. The size should not be *absolute*, however; i.e. use `70%` not `540px`. Figures should, in general, be centered on the page. When drawings, graphs, or diagrams are included they should ideally be provided in both SVG and PNG formats, and included using globbing as `filename.*`. This will use the appropriate format for the output type.

Source Code Listings

Do not ever use the double-colon (`::`) directive to mark a section of text as a source code listing. This not only doesn’t support direct linking or provide a caption, but also uses the default “domain” - which is Python - for syntax highlighting. Instead, use `.. code-block` to include source code in the documentation. Source code must always be left-aligned, so do not provide any configuration options that would alter the default.

118: Example Usage of the code-block Directive

```
.. code-block:: syntax
   :caption: A short, meaningful caption
   :linenos:

   ``:linenos:`` is an optional field which will include line numbers.
   ↳in the listing. 'syntax'
      should be the name of a valid Pygments syntax.
```

Tables

Tables should be included in `.. table` directive bodies, **never** as a floating, block-quoted tabular environment. This ensures that all tables will be captioned, which makes their purpose clear and makes them directly link-able in the output as well as includes them in table listings. Tables should avoid wrapping lines until they reach 215 characters in width in the source RESTRUCTUREDTEXT document (including indentation which should be counted as 4 characters per TAB). No table may ever exceed 215 characters in width. Tables should, in general be left-aligned (which is the default configuration). For the usage or command-line flags or options of a utility, use an “option list” or the `.. program` and `.. option` directives instead of a table.

Indentation

Firstly, indentation of a text paragraph is rarely required. Doing so does not “link” the text with a heading in any way, text falls beneath a section or sub-section purely by being literally *beneath* that heading. When placing source code into a source code listing, any indentation may be used for the source code (typically should represent the actual preferred indentation of the code’s respective project were it included in the repository), but to avoid ambiguity in indentation used in the documentation versus indentation used in the source code, all documentation indentation should be done using *one (1) TAB character* and **never spaces**.

Lists

When making a list, consider first what *kind* of list it is. A list only needs to be enumerated if the enumeration has meaning e.g. a list of hierarchically ordered data or a sequential list of steps to accomplish a task or desired state. When enumerating list items, use `#.` instead of literal numbers, as this will enumerate automatically which makes modification of the list much easier at a later date. Unordered lists may use `-` or `*` for each item. Lists do not need to be indented beyond the current paragraph level. If a list is an unordered list of terms and their definitions, use a “definition list” instead of any other kind of list. If a list is a list of fields in a document or object, use a “field list” instead of any other kind of list. If a list is a list of parameters, arguments, or flags used by a command-line utility, use an “option list” instead of any other kind of list.

Notes and Footnotes

Instead of `**NOTE**` or similar, consider using the `.. note` directive, or one of the appropriate admonitions supported by RST:

attention The default admonition that calls attention to something without any specific semantics or attached context. Use when none of the others seem appropriate.

caution Includes cautionary information. Should be used when advising the reader that the containing section includes instructions or information that frequently confuse people/trip people up, and how to avoid these pitfalls.

danger Advises the reader of potential security risks or system damage that could occur as a result of following instructions in the containing section, or as a result of making assumptions about and/or improperly utilizing information in the containing section.

error Denotes an error. This has limited uses in the ATC documentation.

hint Offers a hint to nudge readers in the direction of a solution. This has limited uses in the ATC documentation.

impl-detail Contains information describing the details of an implementation of a feature described in the containing section. For an example, see [the DSCP section of the Delivery Services page](#).

Note: This is an *extension* provided by the ATC documentation build system, and will not appear in the Sphinx project documentation nor the reStructuredText standard.

important Contains information that is important to consider while reading the containing section. Typically content that is related to a section's content in an important way should appear as content of that section, but if a section is in danger of readers "skimming" it for information this can be useful to catch their eye.

note Used to segregate content that is only tangentially related to the containing section, but is noteworthy nonetheless. Historically the most used admonition, containing caveats, exceptions etc.

tip Provides the reader with information that can be helpful - particularly to users/administrators/developers new to ATC - but not strictly necessary to understand the containing section.

warning Warns the reader about possible unintended consequences of following instructions/utilizing information in the containing section. If the behavior warned about constitutes a security risk and/or serious damage to one or more systems - including clients and origins - please use `.. danger` instead.

In a similar vein, instead of e.g. "(See also: some-link-or-reference)" please use the special `.. seealso` admonition. If the same admonition is required more than twice on the same page, it most likely ought to be a footnote instead. Footnotes should ideally use human-readable labels or, failing that, be labeled sequentially in the order of appearance. Footnotes should appear at the end of the major section in which they first or last appear. In practice, however, placement of the footnote is left to the writer's discretion.

Section Headings

When deciding on the name of a section heading, it is important to select a name that both accurately reflects the content it contains and is suitable for reference later e.g. "Health Protocol" is good, but "Configuring Multi-Site Origin" as the title of a page which not only explains MSO configuration but also the concept is not good. Section headings follow a hierarchy, and for consistency's sake should follow this particular hierarchy:

1. Document title. There should only be one of these per page, and it should be the first heading on the page. This will also make the contained text the "Page Title" in HTML output (i.e. `<title>Page Title</title>` in the `<head>`).

119: Document Title

```
*****
Document Title
*****
```

2. Section header. This should represent a main topic of the page

120: Section Header

Section Header
=====

3. Subsection header. This should represent a key piece of a main topic on the page

121: Subsection Header

Subsection Header

4. Sub-Subsection header. This represents a group of content logically separate from the rest of the subsection but still related to the content thereof. It is also acceptable to use this as an “aside” containing information only tangentially related to the subsection content.

122: Sub-Subsection Header

Sub-Subsection Header
.....

5. Aside or Sub-Sub-Subsection header. This is the lowest denomination of header, and should almost always be used exclusively for “asides” which contain information only tangentially related to the sub-subsection content.

123: Aside

Aside
.....

Section headings should *always* follow this order exactly, and **never** skip levels (which will generally cause a failure to compile properly). These can be thought of as the equivalents of the HTML tags <h1> through <h5>, respectively. Sectioning should never require more specificity than can be provided by an “Aside”. Please do not use **bold text** in lieu of a proper section heading. When referencing information in another section on the same page, please do not refer to the current placement of the referenced content relative to the referencing content. For example, instead of “as discussed below”, use “as discussed in *Terms*”.

Terms

Please always spell out the entire name of any Traffic Control terms used in the definition. For example, a collection of *cache servers* associated with a certain physical location is called a “Cache Group”, not a “CG”, “cachegroup”, “cache location” etc. A subdomain and collection of *cache servers* responsible collectively for routing traffic to a specific origin is called a *Delivery Service*, not a “DS”, “deliveryservice” etc. Similarly, always use *full* permissions role names e.g. “operations” not “oper”. This will ensure the *Glossary* is actually helpful. To link a term to the glossary, use the `:term:` role. This should be done for virtually every use of a Traffic Control term, e.g. `:term:`Cache Group`` will render as: *Cache Group*. Generally speaking,

be wary of using the word “cache”. To most people that means the *actual* cache on a hard disk somewhere. This word is frequently confused with “*cache server*”, which - when accurate - is always preferred over “cache”.

Documenting API Routes

Follow all of the formatting conventions in *Formatting*. Maintain the structural format of the API documentation as outlined in the *Traffic Ops API* section. API routes that have variable paths e.g. *profiles/{ID}* should use *mustache templates* **not** the Mojolicious-specific `:param` syntax. This keeps the templates generic, familiar, and reflects the inability of a request path to contain procedural instructions or program logic. Please do not include the `/api/2.x/` part of the request path for Traffic Ops API endpoints. If an endpoint is unavailable prior to a specific version, use the `.. versionadded` directive to indicate that version. Likewise, do not make a new page for an endpoint when it changes across versions, instead call out the changes using the `.. versionchanged` directive. If an endpoint should not be used because newer endpoints provide the same functionality in a better way, use the `.. deprecated` directive to link to them and explain why they are better.

When documenting an API route, be sure to include *all* methods, request/response JSON payload fields, path parameters, and query parameters, whether they are optional or not. When describing a field in a JSON payload, remember that JSON does not have “hashes” it has “objects” or even “maps”. When documenting path parameters such as *Profile ID* in *profiles/{ID}*, consider that the endpoint path cannot be formed without defining **all** path parameters, and so to label them as “required” is superfluous.

The “Response Example” must **always** exist. “TODO” is **not** an acceptable Response Example for new endpoints. The “Request Example” must only exist if the request requires data in the body (most commonly this will be for PATCH, POST and PUT methods). It is, however, strongly advised that a request example be given if the endpoint takes Query Parameters or Path Parameters, and it is required if the Response Example is a response to a request that used a query or path parameter. If the Request Example *is* present, then the Response Example **must** be the appropriate response **to that request**. When generating Request/Response Examples, attempt to use the *CDN in a Box* environment whenever possible to provide a common basis and familiarity to new users who likely set up “CDN in a Box” as a primer for understanding CDNs/Traffic Control. Responses are sometimes hundreds of lines long, and in those cases only as much as is required for an understanding of the structure needs to be included in the example - along with a note mentioning that the output was trimmed. Also always attempt to place structure explanations before any example so that the content of the example can be understood by the reader (though in general the placement of a floating environment like a code listing is not known at compile-time). Whenever possible, the Request and Response examples should include the *complete HTTP stack*, which captures behavior like Query Parameters, Path Parameters and HTTP cookie operations like those used by e.g. *logs*. A few caveats to the “include all headers” rule:

- The `Host` header ought to reflect the actual hostname of the Traffic Ops server - which should be “trafficops.infra.ciab.test” for the CDN in a Box environment. This can be polluted when requests are made to a remotely running CDN in a Box on a different server.

- The “mojolicious” cookie is extremely long and potentially insecure to publicly show. As such, a placeholder should be used for its value, preferably “...”.
- The Content-Type header sent by `curl(1)` (and possibly others) is always `application/x-www-form-urlencoded` regardless of the actual content (unless overridden). Virtually all payloads accepted by the API must be JSON, so this should be modified to reflect that when appropriate e.g. `application/json`.
- API output is often beautified by inserting line breaks and indentation, which will make the Content-Length header (if any) incorrect. Don’t worry about fixing that - just try to leave the output as close as possible to what will actually be returned by leaving it the way it is.

File names should reflect the request path of the endpoint, e.g. a file for an endpoint of the Traffic Ops API `/api/2.0/foo/{{fooID}}/bar/{{barID}}` should be named `foo_fooID_bar_barID.rst`. Similarly, reference labels linking to the document title for API route pages should follow the convention: `<component>-api-<path>` in all lowercase where `<component>` is an abbreviated Traffic Control component name e.g. `to` and `<path>` is the request path e.g. `foo_bar`. So a label for an endpoint of the Traffic Ops API at `/api/2.0/foo_bar/{{ID}}` should be `to-api-foo_bar-id`.

Extension

The ATC documentation provides an extension to the standard roles and directives offered by Sphinx, located at `docs/source/_ext/atc.py`. It provides the following roles and directives:

impl-detail An admonition directive used to contain implementation-specific notes on a subject.

124: Example impl-detail usage

```
.. impl-detail:: Implementation-specific information here.
```

This example usage renders like so:

Implementation Detail

Implementation-specific information here.

atc-file Creates a link to the specified file on the master branch of the ATC repository. For example, “`:atc-file:`docs/source/development/documentation_guidelines``” renders as a link to the source of this documenting section like so: [docs/source/development/documentation_guidelines](#). You can also link to directories as well as files.

issue A text role that can be used to easily link to GitHub Issues for the ATC repository. For example, “`:issue:`1``” renders as: [Issue #1](#).

pr A text role that can be used to easily link to GitHub Pull Requests for the ATC repository. For example, “`:pr:`1``” renders as [Pull Request 1](#).

pull-request A synonym for `pr`

godoc A text role that can be used to easily link to the documentation for any Go package, type, or function/method (grouped constants/variables not supported). For example, “:godoc:`net/http.HandlerFunc`” renders as [net/http.HandlerFunc](#).

atc-godoc This is provided for convenience, and is identical to `:godoc:` except that it is assumed to be relative to the Apache Traffic Control project. For example, `:atc-godoc:`lib/go-rfc.MimeType.Quality`` renders as [github.com/apache/trafficcontrol/lib/go-rfc.MimeType.Quality](#).

to-godoc This is provided for convenience, and is identical to `:godoc:` except that it is assumed to be relative to the [github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang](#) package. For example, `:to-godoc:`api.APIInfo`` renders as [github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/api.APIInfo](#).

4.1.6 Godocs

Linking to Godocs

As mentioned in *Documentation Guidelines*, you can use the `:godoc:` role, the `:atc-godoc:` role, and the `:to-godoc:` role to link to Godocs from the ATC documentation.

Keeping pkg.go.dev from hiding the Apache Traffic Control Godocs

If less than 75% of ATC’s `LICENSE` file contains OSS licenses according to [pkg.go.dev](#) license detection system `pkg.go.dev` will hide all of ATC’s Godocs for that particular ATC version, saying “Documentation not displayed due to license restrictions.”. Example: <https://pkg.go.dev/github.com/apache/trafficcontrol@v5.1.0+incompatible/lib/go-tc>

When listing a dependency in the `LICENSE` file as part of [bundling a new dependency](#), make sure that the license “pointer” adheres to this format:

125: The `atc-dependency.lre` license exception from [golang.org/x/pkg/site](#)

```
This product bundles __4__, which
(( is || are ))
available under
(( a || an ))
(( Apache-2.0 || BSD-2-Clause || BSD-3-Clause || MIT ))
license.
__15__
(( /* || .css || .js || .scss ))
(( ./licenses/__4__ || ./vendor/__16__/LICENSE
(( .libyaml || .md || .txt ))??
```

(continues on next page)

(continued from previous page)

```
))
Refer to the above license for the full text.
```

Example:

126: An example of a bundled dependency license pointer

```
This product bundles go-acme/lego, which is available under an MIT_
→license.
@vendor/github.com/go-acme/lego/*
./vendor/github.com/go-acme/lego/LICENSE
Refer to the above license for the full text.
```

The ATC repository includes a GitHub Actions workflow ([.github/workflows/license-file-coverage.yml](#)) to verify that changes to the LICENSE file will not result in pkg.go.dev hiding the Apache Traffic Control Godocs.

4.1.7 Traffic Monitor

Introduction

Traffic Monitor is an HTTP service application that monitors *cache servers*, provides health state information to Traffic Router, and collects statistics for use in tools such as Traffic Portal and Traffic Stats. The health state provided by Traffic Monitor is used by Traffic Router to control which *cache servers* are available on the CDN.

Software Requirements

To work on Traffic Monitor you need a Unix-like (MacOS and Linux are most commonly used) environment that has a working install of Go version 1.7+.

Project Tree Overview

traffic_monitor/ - base directory for Traffic Monitor.

- cache/ - Handler for processing cache results.
- config/ - Application configuration; in-memory objects from `traffic_monitor.cfg`.
- crconfig/ - data structure for deserializing the CDN *Snapshot* (historically named “CR-Config”) from JSON.
- deliveryservice/ - aggregates *Delivery Service* data from cache results.
- deliveryservicedata/ - *Delivery Service* data structures. This exists separate from `deliveryservice` to avoid circular dependencies.
- enum/ - enumerations and name alias types.

- `health/` - functions for calculating *cache server* health, and creating health event objects.
- `manager/` - manager goroutines (microthreads).
 - `health.go` - Health request manager. Processes health results, from the health poller -> fetcher -> manager. The health poll is the “heartbeat” containing a small amount of stats, primarily to determine whether a *cache server* is reachable as quickly as possible. Data is aggregated and inserted into shared thread-safe objects.
 - `manager.go` - Contains `Start` function to start all pollers, handlers, and managers.
 - `monitorconfig.go` - Monitor configuration manager. Gets data from the monitor configuration poller, which polls Traffic Ops for changes to which caches are monitored and how.
 - `opsconfig.go` - Ops configuration manager. Gets data from the ops configuration poller, which polls Traffic Ops for changes to monitoring settings.
 - `peer.go` - Peer manager. Gets data from the peer poller -> fetcher -> handler and aggregates it into the shared thread-safe objects.
 - `stat.go` - Stat request manager. Processes stat results, from the stat poller -> fetcher -> manager. The stat poll is the large statistics poll, containing all stats (such as HTTP response status codes, transactions, *Delivery Service* statistics, and more). Data is aggregated and inserted into shared thread-safe objects.
 - `statecombiner.go` - Manager for combining local and peer states, into a single combined states thread-safe object, for serving the `CrStates` endpoint.
- `datareq/` - HTTP routing, which has thread-safe health and stat objects populated by stat and health managers.
- `peer/` - Manager for getting and populating peer data from other Traffic Monitors
- `srvhttp/` - HTTP(S) service. Given a map of endpoint functions, which are lambda closures containing aggregated data objects. If HTTPS, the HTTP service will redirect to HTTPS.
- `static/` - Web interface files (markup, styling and scripting)
- `threadsafe/` - Thread-safe objects for storing aggregated data needed by multiple goroutines (typically the aggregator and HTTP server)
- `todata/` - Data structure for fetching and storing Traffic Ops data needed from the CDN *Snapshot*. This is primarily mappings, such as *Delivery Service* servers, and server types.
- `trafficopswrapper/` - Thread-safe wrapper around the Traffic Ops client. The client used to not be thread-safe, however, it mostly (possibly entirely) is now. But, the wrapper also serves to overwrite the Traffic Ops `monitoring.json` values, which are live, with values from the CDN *Snapshot*.

Architecture

At the highest level, Traffic Monitor polls *cache server*s, aggregates their data and availability, and serves it at HTTP endpoints in JSON format. In the code, the data flows through microthread (goroutine) pipelines. All stages of the pipeline are independently running microthreads¹. The pipelines are:

stat poll Polls caches for all statistics data. This should be a slower poll, which gets a lot of data.

health poll Polls caches for a tiny amount of data, typically system information. This poll is designed to be a heartbeat, determining quickly whether the *cache server* is reachable. Since it's a small amount of data, it should poll more frequently.

peer poll Polls Traffic Monitor peers for their availability data, and aggregates it with its own availability results and that of all other peers.

monitor config Polls Traffic Ops for the list of Traffic Monitors and their info.

ops config Polls for changes to the Traffic Ops configuration file `traffic_ops.cfg`, and sends updates to other pollers when the configuration file has changed.

- The ops config manager also updates the shared Traffic Ops client, since it's the actor which becomes notified of configuration changes requiring a new client.
- The ops config manager also manages, creates, and recreates the HTTP server, since Traffic Ops configuration changes necessitate restarting the HTTP server.

All microthreads in the pipeline are started by `manager/manager.go:Start()`.




Fig. 50: Pipeline Overview

¹ Technically, some stages which are one-to-one simply call the next stage as a function. For example, the Fetcher calls the Handler as a function in the same microthread. But this isn't architecturally significant.

Stat Pipeline




Fig. 51: The Stats Pipeline

poller `common/poller/poller.go:HttpPoller.Poll()`. Listens for configuration changes (from the Ops Configuration Manager), and starts its own, internal microthreads - one for each cache to poll. These internal microthreads call the Fetcher at each cache's poll interval.

fetcher `common/fetcher/fetcher.go:HttpFetcher.Fetch()`. Fetches the given URL, and passes the returned data to the Handler, along with any errors.

handler `traffic_monitor/cache/cache.go:Handler.Handle()`. Takes the given result and does all data computation possible with the single result. Currently, this computation primarily involves processing the de-normalized ATS data into Go structs, and processing System data into 'OutBytes', KBPS, etc. Precomputed data is then passed to its result channel, which is picked up by the Manager.

manager `traffic_monitor/manager/stat.go:StartStatHistoryManager()`. Takes preprocessed results, and aggregates them. Aggregated results are then placed in shared data structures. The major data aggregated are *Delivery Service* statistics, and *cache server* availability data. See *Aggregated Stat Data* and *Aggregated Availability Data*.

Health Pipeline




Fig. 52: The Health Pipeline

poller `common/poller/poller.go:HttpPoller.Poll()`. Same poller type as the Stat Poller pipeline, with a different handler object.

fetcher `common/fetcher/fetcher.go:HttpFetcher.Fetch()`. Same fetcher type as the Stat Poller pipeline, with a different handler object.

handler `traffic_monitor/cache/cache.go:Handler.Handle()`. Same handler type as the Stat Poller pipeline, but constructed with a flag to not pre-compute anything. The health endpoint is of the same form as the stat endpoint, but doesn't return all stat data. So, it doesn't pre-compute like the Stat Handler, but only processes the system data, and passes the processed result to its result channel, which is picked up by the Manager.

manager `traffic_monitor/manager/health.go:StartHealthResultManager()`.

Takes preprocessed results, and aggregates them. For the Health pipeline, only health availability data is aggregated. Aggregated results are then placed in shared data structures (`lastHealthDurationsThreadsafe`, `lastHealthEndTimes`, etc). See [Aggregated Availability Data](#).

Peer Pipeline




Fig. 53: The Peers Pipeline

poller `common/poller/poller.go:HttpPoller.Poll()`. Same poller type as the Stat and Health Poller pipelines, with a different handler object. Its configuration changes come from the Monitor Configuration Manager, and it starts an internal microthread for each peer to poll.

fetcher `common/fetcher/fetcher.go:HttpFetcher.Fetch()`. Same fetcher type as the Stat and Health Poller pipeline, with a different handler object.

handler `traffic_monitor/cache/peer.go:Handler.Handle()`. Decodes the JSON result into an object, and without further processing passes to its result channel, which is picked up by the Manager.

manager `traffic_monitor/manager/peer.go:StartPeerManager()`. Takes JSON peer Traffic Monitor results, and aggregates them. The availability of the Peer Traffic Monitor itself, as well as all [cache server](#) availability from the given peer result, is stored in the shared `peerStates` object. Results are then aggregated via a call to the `combineState()` lambda, which signals the State Combiner microthread (which stores the combined availability in the shared object `combinedStates`; See [State Combiner](#)).

Monitor Config Pipeline




Fig. 54: The Monitor Configuration Pipeline

poller `common/poller/poller.go:MonitorConfigPoller.Poll()`. The Monitor Configuration poller, on its interval, polls Traffic Ops for the Monitor configuration, and writes the polled value to its result channel, which is read by the Manager.

manager `traffic_monitor/manager/monitorconfig.go:StartMonitorConfigManager()`. Listens for results from the poller, and processes them. Cache changes are written to channels read by the Health, Stat, and Peer pollers. In the Shared Data objects, this also sets the list of new *Delivery Services* and removes ones which no longer exist, and sets the list of peer Traffic Monitors.

Ops Config Pipeline




Fig. 55: The Ops Configuration Pipeline

poller `common/poller/poller.go:FilePoller.Poll()`. Polls for changes to the Traffic Ops configuration file `traffic_ops.cfg`, and writes the changed configuration to its result channel, which is read by the Handler.

handler `common/handler/handler.go:OpsConfigFileHandler.Listen()`. Takes the given raw configuration, un-marshals the JSON into an object, and writes the object to its channel, which is read by the Manager, along with any error.

manager `traffic_monitor/manager/monitorconfig.go:StartMonitorConfigManager()`. Listens for new configurations, and processes them. When a new configuration is received, a new HTTP dispatch map is created via `traffic_monitor/datareq/datareq.go:MakeDispatchMap()`, and the HTTP server is restarted with the new dispatch map. The Traffic Ops client is also recreated, and stored in its shared data object. The Ops Configuration change subscribers and Traffic Ops Client change subscribers (the Monitor Configuration poller) are also passed the new Traffic Ops configuration and new Traffic Ops client.

Events

The events shared data object is passed to each pipeline microthread which needs to signal events. Most of them do. Events are then logged, and visible in the UI as well as an HTTP JSON endpoint. Most events are *cache server* becoming available or unavailable, but include other things such as peer availability changes.

State Combiner

The State Combiner is a microthread started in `traffic_monitor/manager/manager.go:Start()` via `traffic_monitor/manager/statecombiner.go:StartStateCombiner()`, which listens for signals to combine states. It should be signaled by any pipeline which updates the local or peer availability shared data objects, `localStates` and `peerStates`. It holds the thread-safe shared data objects for local states and peer states, so no data is passed or returned, only a signal. When a signal is received, it combines the local and peer states optimistically. That is, if a *cache server* is marked available locally or by any peer, that *cache server* is marked available in the combined states. There exists a variable to combine pessimistically, which may be set at compile time (it's unusual for a CDN to operate well with pessimistic *cache server* availability). Combined data is stored in the thread-safe shared data object `combinedStates`.

Aggregated Stat Data

The Stat pipeline Manager is responsible for aggregating stats from all *Edge-tier cache servers*, into *Delivery Services* statistics. This is done via a call to `traffic_monitor/deliveryservice/stat.go:CreateStats()`.

Aggregated Availability Data

Both the Stat and Health pipelines aggregate availability data received from caches. This is done via a call to `traffic_monitor/deliveryservice/health.go:CalcAvailability()` followed by a call to `combineState()`. The `CalcAvailability` function calculates the availability of each *cache server* from the result of polling it, that is, local availability. The `combineState()` function is a lambda passed to the Manager, which signals the State Combiner microthread, which will combine the local and peer Traffic Monitor availability data, and insert it into the shared data `combinedStates` object.

HTTP Data Requests

Data is provided to HTTP requests via the thread-safe shared data objects (see [Shared Data](#)). These objects are closed in lambdas created via `traffic_monitor/datareq/datareq.go:MakeDispatchMap()`. This is called by the Ops Configuration Manager when it recreates the HTTP(S) server. Each HTTP(S) endpoint is mapped to a function which closes around the shared data objects it needs, and takes the request data it needs (such as query parameters). Each endpoint function resides in its own file in `traffic_monitor/datareq/`. Because each Go HTTP routing function must be a `http.HandlerFunc`, wrapper functions take the endpoint functions and return `http.HandlerFunc` functions which call them, and which are stored in the dispatch map, to be registered with the HTTP(S) server.

Shared Data

Processed and aggregated data must be shared between the end of the stat and health processing pipelines, and HTTP requests. The CSP (Communicating Sequential Processes) paradigm of idiomatic Go does not work efficiently with storing and sharing state. While not idiomatic Go, shared mutexed data structures are faster and simpler than CSP manager microthreads for each data object. Traffic Monitor has many thread-safe shared data types and objects. All shared data objects can be seen in `manager/manager.go:Start()`, where they are created and passed to the various pipeline stage microthreads that need them. Their respective types all include the word `Threadsafe`, and can be found in `traffic_monitor/threadsafe/` as well as, for dependency reasons, various appropriate directories. Currently, all thread-safe shared data types use mutexes. In the future, these could be changed to lock-free or wait-free structures, if the performance needs outweighed the readability and correctness costs. They could also easily be changed to internally be manager microthreads and channels, if being idiomatic were deemed more important than readability or performance.

Disk Backup

The *Traffic Monitor configuration* and *CDN Snapshot* (see [Snapshots](#)) are both stored as backup files (`tmconfig.backup` and `crconfig.backup` or whatever you set the values to in the configuration file). This allows the monitor to come up and continue serving even if Traffic Ops is down. These files are updated any time a valid configuration is received from Traffic Ops, so if Traffic Ops goes down and Traffic Monitor is restarted it can still serve the previous data. These files can also be manually edited and the changes will be reloaded into Traffic Monitor so that if Traffic Ops is down or unreachable for an extended period of time manual updates can be done. If on initial startup Traffic Ops is unavailable then Traffic Monitor will continue through its exponential back-off until it hits the max retry interval, at that point it will create an unauthenticated Traffic Ops session and use the data from disk. It will still poll Traffic Ops for updates though and if it successfully gets through then it will login at that point.

Formatting Conventions

Go code should be formatted with `gofmt`. See also `CONTRIBUTING.md`.

Installing The Developer Environment

To install the Traffic Monitor Developer environment:

1. Install [Go](#) version 1.7 or greater
2. Clone the [Traffic Control repository](#) using `git`, into `$GOPATH/src/github.com/apache/trafficcontrol`
3. Change directories into `$GOPATH/src/github.com/apache/trafficcontrol/traffic_monitor`
4. Run `./build.sh`

Test Cases

Tests can be executed by running `go test ./...` at the root of the `traffic_monitor` project.

API

Traffic Monitor APIs

Traffic Monitor APIs

The Traffic Monitor URLs below allow certain query parameters for use in controlling the data returned.

Note: Unlike *Traffic Ops API endpoints*, no authentication is required for any of these, and as such there can be no special role requirements for a user.

`/publish/EventLog`

Gets a log of recent changes in the availability of polled caches.

GET

Response Type Array (key 'events' contains an array of all data)

Response Structure

event an entry in the top-level events array

description A string containing short description of the event

hostname A string containing the server's full hostname

index A serial integer that is incremented for each sequential event

isAvailable A boolean value indicating whether the server is available following this event

name The server's short hostname as a string

time A UNIX timestamp as an integer

type The type of the server as a string

127: Example Response

```
{ "events": [
  {
    "time": 1538417713,
    "index": 67848,
    "description": "REPORTED - loadavg too high (36.37 \u003e 25.
    ↳00) (health)",
    "name": "edge",
    "hostname": "edge",
    "type": "EDGE",
    "isAvailable": false
  }
]}
```

/publish/CacheStats

Statistics gathered for each cache.

GET

Response Type Object

Request Structure

Table 71: Request Query Parameters

Parameter	Type	Description
hc	integer	The history count, number of items to display.
stats	string	A comma separated list of stats to display.
wildcard	boolean	Controls whether specified stats should be treated as partial strings.

128: Example Request

```
GET /publish/CacheStats HTTP/1.1
Accept: */*
Content-Type: application/json
```

Response Structure

pp Stores any provided request parameters provided as a string

date A ctime-like string representation of the time at which the response was served

caches An object with keys that are the names of monitored *cache servers*

<server name> Each server's object is a collection of keys that are the names of statistics

<interface name> The name of the network interface under the same sever

<statistic name> The name of the statistic which this array represents. Each value in the array is one (and usually only one) object with the following structure:

value The statistic's value. This is *always* a string, even if that string only contains a number.

time An integer UNIX timestamp indicating the start time for this value of this statistic

span The span of time - in milliseconds - for which this value is valid. This is deter-

mined by the polling interval for the statistic

129: Example Response

```

HTTP/1.1 200 OK
Content-Type: application/json
Date: Thu, 14 May 2020 15:48:55 GMT
Transfer-Encoding: chunked

{
  "pp": "",
  "date": "Thu May 14 15:48:55 UTC 2020",
  "caches": {
    "mid": {
      "eth0": {
        "ats.proxy.process.ssl.cipher.user_agent.PSK-AES256-
→GCM-SHA384": [
          {
            "value": "0",
            "time": 1589471325624,
            "span": 99
          }
        ]
      },
      "aggregate": {
        "ats.proxy.process.http.milestone.server_begin_write":
→[
          {
            "value": "174",
            "time": 1589471325624,
            "span": 1
          }
        ]
      },
      "lo": {
        "ats.proxy.node.http.transaction_counts_avg_10s.miss_
→changed": [
          {
            "value": "0",
            "time": 1589471325624,
            "span": 99
          }
        ]
      },
      "edge": {
        "eth0": {

```

(continues on next page)

(continued from previous page)

```

    "ats.proxy.process.ssl.cipher.user_agent.PSK-AES256-
    ↪GCM-SHA384": [
        {
            "value": "0",
            "time": 1589471325624,
            "span": 99
        }
    ],
    "aggregate": {
        "ats.proxy.process.http.milestone.server_begin_write": ↪
    ↪[
        {
            "value": "174",
            "time": 1589471325624,
            "span": 1
        }
    ],
    "lo": {
        "ats.proxy.node.http.transaction_counts_avg_10s.miss_
    ↪changed": [
        {
            "value": "0",
            "time": 1589471325624,
            "span": 99
        }
    ]
    }
}

```

`publish/CacheStats/{{cache}}`

Statistics gathered for only a single cache.

GET

Response Type Object

Request Structure

Table 72: Request Path Parameters

Parameter	Type	Description
cache	string	The name of the cache to inspect

Table 73: Request Query Parameters

Parameter	Type	Description
hc	integer	The history count, number of items to display.
stats	string	A comma separated list of stats to display.
wildcard	boolean	Controls whether specified stats should be treated as partial strings.

130: Example Request

```
GET /api/CacheStats/mid HTTP/1.1
Accept: */*
Content-Type: application/json
```

Response Structure

pp Stores any provided request parameters provided as a string

date A ctime-like string representation of the time at which the response was served

caches An object with keys that are the names of monitored *cache servers* - only the cache named by the cache request path parameter will be shown

<server name> The requested server's object is a collection of keys that are the names of statistics

<interface name> The name of the network interface under the same sever

<statistic name> The name of the statistic which this array represents. Each value in the array is one (and usually only one) object with the following structure:

value The statistic's value. This is *always* a string, even if that string only contains a number.

time An integer UNIX timestamp indicating the start time for this value of this statistic

span The span of time - in milliseconds - for which this value is valid. This is determined by the polling interval for the statistic

131: Example Response

```
HTTP/1.1 200 OK
Content-Type: application/json
Date: Thu, 14 May 2020 15:54:35 GMT
Transfer-Encoding: chunked

{
  "pp": "",
  "date": "Thu May 14 15:48:55 UTC 2020",
  "caches": {
    "mid": {
      "eth0": {
        "ats.proxy.process.ssl.cipher.user_agent.PSK-AES256-
→GCM-SHA384": [
          {
            "value": "0",
            "time": 1589471325624,
            "span": 99
          }
        ],
      },
      "aggregate": {
        "ats.proxy.process.http.milestone.server_begin_write":
→[
          {
            "value": "174",
            "time": 1589471325624,
```

(continues on next page)

(continued from previous page)

```

    "span": 1
  }
],
},
"lo": {
  "ats.proxy.node.http.transaction_counts_avg_10s.miss_
→changed": [
    {
      "value": "0",
      "time": 1589471325624,
      "span": 99
    }
  ]
}
}
}
}
```

/publish/DsStats

Statistics gathered for *Delivery Services*

GET

Response Type Object

Request Structure

Table 74: Request Query Parameters

Parameter	Type	Description
hc	int	The history count, number of items to display.
stats	string	A comma separated list of stats to display.
wildcard	boolean	Controls whether specified stats should be treated as partial strings.

Response Structure

TODO

`/publish/DsStats/{{deliveryService}}`

Statistics gathered for this *Delivery Service* only.

GET

Response Type ?

Request Structure

Table 75: Request Path Parameters

Parameter	Type	Description
deliveryService	string	The name of the <i>Delivery Service</i> to inspect

Table 76: Request Query Parameters

Parameter	Type	Description
hc	integer	The history count, number of items to display.
stats	string	A comma separated list of stats to display.
wildcard	boolean	Controls whether specified stats should be treated as partial strings.

Response Structure

TODO

`/publish/CrStates`

The current state of this CDN per the ref:*health-proto*.

GET

Response Type ?

Response Structure

TODO

..???? raw

The current state of this CDN per this Traffic Monitor only.

[/publish/CrConfig](#)

The CDN *Snapshot* (historically named a “CRConfig”) served to and consumed by Traffic Router.

GET

Response Type ?

Response Structure

TODO

[/publish/PeerStates](#)

The health state information from all peer Traffic Monitors.

GET

Response Type ?

Request Structure

Table 77: Request Query Parameters

Parameter	Type	Description
hc	integer	The history count, number of items to display.
stats	string	A comma separated list of stats to display.
wildcard	boolean	Controls whether specified stats should be treated as partial strings.

Response Structure

TODO

`/publish/Stats`

The general statistics about Traffic Monitor.

GET

Response Type ?

Response Structure

TODO

`/publish/StatSummary`

The summary of *cache server* statistics.

GET

Response Type ?

Request Structure

Table 78: Request Query Parameters

Parameter	Type	Description
<code>startTime</code>	number	Window start. The number of milliseconds since the epoch.
<code>endTime</code>	number	Window end. The number of milliseconds since the epoch.
<code>hc</code>	integer	The history count, number of items to display.
<code>stats</code>	string	A comma separated list of stats to display.
<code>wildcard</code>	boolean	Controls whether specified stats should be treated as partial strings.
<code>cache</code>	string	Summary statistics for just this cache.

Response Structure

TODO

`/publish/ConfigDoc`

The overview of configuration options.

GET

Response Type ?

Response Structure

TODO

4.1.8 Traffic Ops

At one point, Traffic Ops was a collection of Perl scripts, and while the current program is written in Go, many of its tools and utilities are still written in Perl.

Introduction

Traffic Ops at its core is mainly a PostgreSQL database used to store configuration information for ATC, and a set of RESTful API endpoints for interacting with and manipulating that information. It also serves as the single point of authentication for ATC components (that is, when one hears “user” in an ATC context it nearly always means a “user” as configured in Traffic Ops) and provides interfaces to other ATC components by proxy. Additionally, there is some miscellaneous, at times obscure functionality to Traffic Ops, such as generating arbitrary Linux system images.

Software Requirements

Traffic Ops is only supported on CentOS 7+ systems (although many developers do use Mac OS with some success). Here are the requirements:

- [PostgreSQL 13.2](#) - the machine where Traffic Ops is running must have the client tool set (e.g. `psql(1)`), but the actual database can be run anywhere so long as it is accessible.

Note: Prior to version 13.2, Traffic Ops used version 9.6. For upgrading an existing Mac OS Homebrew-based PostgreSQL instance, you can use [Homebrew](#) to easily upgrade from 9.6 to 13.2:

```
brew services stop postgresql
brew upgrade postgresql
brew postgresql-upgrade-database
brew cleanup postgresql@9.6
brew services start postgresql
```

- *openssl(1SSL)* is recommended to generate server certificates, though not strictly required if certificates can be obtained by other means.
- Some kind of SMTP server is required for certain *Traffic Ops API* endpoints to work, but for purposes unrelated to them an SMTP server is not required. *CDN in a Box* comes with a relayless SMTP server for testing (you can view the emails that Traffic Ops sends, but they aren't sent anywhere outside CDN-in-a-Box).

Tip: Alternatively, development and testing can be done using *CDN in a Box* - albeit somewhat more slowly.

Perl Script Requirements

Not much code is still in Perl, but for the scripts the following are needed:

- Perl 5.10.1
- libpcap and libpcap development library - usually `libpcap-dev` or `libpcap-devel` in your system's native package manager.
- libpq and libpq development library - usually `libpq-dev` or `libpq-devel` in your system's native package manager.
- The *JSON Perl pod* from CPAN
- The *JSON::PP Perl pod* from CPAN
- Developers should use *Perltidy* to format their Perl code.

132: Example Perltidy Configuration (usually in *HOME/.perltidycrc*)

```
-l=156
-et=4
-t
-ci=4
-st
-se
-vt=0
-cti=0
-pt=1
```

(continues on next page)

(continued from previous page)

```
-bt=1
-sbt=1
-bbt=1
-nsfs
-nolq
-otr
-aws
-wls="= + - / * ."
-wrs="\ "= + - / * .\"
-wbb="% + - * / x != == >= <= =~ < > | & **= += *= &= <
↪<= &&= -= /= |= + >>= ||= .= %= ^= x="
```

Go Program Requirements

- [Go 1.17](#) or later
- If the system’s Go compiler doesn’t provide it implicitly, also note that all Go code in the ATC repository should be formatted using [gofmt](#)

All Go code dependencies are managed through the [go.mod](#), [go.sum](#), and [vendor/modules.txt](#) files. With the exception of [golang.org/x](#) packages (see [below](#)), module dependencies in [vendor/](#) are tracked in Git and should thus be available without any extra work - and any new dependencies should be properly “vendored” into that same, top-level directory. No other [vendor/](#) directories exist, as Go modules only supports a single vendor directory.

Per the Go language standard’s authoritative source’s recommendation, all sub-packages of [golang.org/x](#) are treated as a part of the compiler, and so need not ever be “vendored” as though they were an external dependency. These dependencies are not listed explicitly here, so it is strongly advised that they be fetched using [go-get\(1\)](#) rather than downloaded by hand.

Tip: All new dependencies need to be subject to community review to ensure necessity (because it will be added in its entirety to the repository, after all) and license compliance via [the developer mailing list](#).

Traffic Ops Project Tree Overview

- [traffic_ops/](#) - The root of the Traffic Ops project
 - [app/](#) - Holds most of the Perl code base, though many of the files contained herein are also used by the Go implementation

Note: This directory is home to many things that no longer work as intended or have been superseded by other things.

- * bin/ - Directory for scripts and tools, *cron(8)* jobs, etc.
 - checks/ - Contains the *Check Extensions* scripts that are provided by default
 - db/ - Contains scripts that manipulate the database beyond the scope of setup, migration, and seeding
 - tests/ - Integration and unit test scripts for automation purposes - in general this has been superseded by *traffic_ops/testing/api/*
- * conf/ - Aggregated configuration for Traffic Ops. For convenience, different environments for the *app/db/admin* tool are already set up
 - development/ - Configuration files for the “development” environment
 - integration/ - Configuration files for the “integration” environment
 - misc/ - Miscellaneous configuration files.
 - production/ - Configuration files for the “production” environment
 - test/ - Configuration files for the “test” environment
- * db/ - Database setup, seeding, and upgrade/downgrade helpers
 - migrations/ - Database migration files
 - tools/ - Contains helper scripts for easing upgrade transitions when selective data manipulation must be done to achieve a desirable state
- * script/ - Mojolicious bootstrap/startup scripts.
- * templates/ - Mojolicious Embedded Perl (*template name.ep*) files for the now-removed Traffic Ops UI
- build/ - Contains files that are responsible for packaging Traffic Ops into an RPM file - and also for doing the same with *ORT*
- etc/ - Configuration files for various systems associated with running production instances of Traffic Ops, which are installed under */etc* by the Traffic Ops RPM
 - * cron.d/ - Holds specifications for *cron(8)* jobs that need to be run periodically on Traffic Ops servers

Note: At least one of these jobs expects itself to be run on a server that has the Perl implementation of Traffic Ops installed under */opt/traffic_ops/*. Nothing terrible will happen if

that's not true, just that it/they won't work. Installation using the RPM will set up all of these kinds of things up automatically.

- * `init.d/` - Contains the old, `initscripts`-based job control for Traffic Ops
- * `logrotate.d/` - Specifications for the Linux `logrotate(8)` utility for Traffic Ops log files
- * `profile.d/traffic_ops.sh` - Sets up common environment variables for working with Traffic Ops
- `install/` - Contains all of the resources necessary for a full install of Traffic Ops
 - * `bin/` - Binaries related to installing Traffic Ops, as well as installing its prerequisites, certificates, and database
 - * `data/` - Contains things that need to be accessible by the running server for certain functionality - typically installed to `/var/www/data` by the RPM (hence the name).
 - * `etc/` - This directory left empty; it's used to contain post-installation extensions and resources
 - * `lib/` - Contains libraries used by the various installation binaries
- `ort/` - Contains *ORT* and ATS configuration file-generation logic and tooling
- `testing/` - Holds utilities for testing the *Traffic Ops API*
 - * `api/` - Integration testing for the *Traffic Ops Go client* and Traffic Ops
- `traffic_ops_golang/` - The root of the Go implementation's code-base

Note: The vast majority of subdirectories of `traffic_ops/traffic_ops_golang/` contain handlers for the *Traffic Ops API*, and are named according to the endpoint they handle. What follows is a list of subdirectories of interest that have a special role (i.e. don't handle a *Traffic Ops API* endpoint).

See also:

The *GoDoc* documentation for this package

- * `api/` - A library for use by *Traffic Ops API* handlers that provides helpful utilities for common tasks like obtaining a database transaction handle or accessing Traffic Ops configuration
- * `auth/` - Contains definitions of privilege levels and access control code used in routing and provides a library for dealing with password and token-based authentication
- * `config/` - Defines configuration structures and methods for reading them in from files

- * dbhelpers/ - Assorted utilities that provide functionality for common database tasks, e.g. “Get a user by email”
 - * plugin/ - The Traffic Ops plugin system, with examples
 - * trafficvault/ - This package provides the Traffic Vault interface and associated backend implementations for other handlers to interact with Traffic Vault.
 - * routing/ - Contains logic for mapping all of the *Traffic Ops API* endpoints to their handlers, as well as proxying requests back to the Perl implementation and managing plugins, and also provides some wrappers around registered handlers that set common HTTP headers and connection options
 - * swaggerdocs/ A currently abandoned attempt at defining the *Traffic Ops API* using *Swagger* - it may be picked up again at some point in the (distant) future
 - * tenant/ - Contains utilities for dealing with *Tenantable* resources, particularly for checking for permissions
 - * tocookie/ - Defines the method of generating the *mojolicious* cookie used by Traffic Ops for authentication
 - * vendor/ - contains “vendored” Go packages from third party sources
- v1-client - The official Traffic Ops Go client package for working with the version 1 *Traffic Ops API*.
 - v2-client - The official Traffic Ops Go client package for working with the version 2 *Traffic Ops API*.
 - v3-client - The official Traffic Ops Go client package for working with the version 3 *Traffic Ops API*.
 - v4-client - The official Traffic Ops Go client package for working with the version 4 *Traffic Ops API*.
 - vendor/ - contains “vendored” Go packages from third party sources

app/db/admin

The **app/db/admin** binary is for use in managing the Traffic Ops (and Traffic Vault PostgreSQL backend) database tables. This essentially serves as a front-end for *Migrate*, though *dbconf.yml* comes from *Goose*, which Traffic Ops used to use before switching to *Migrate*.

Note: For proper resolution of configuration and SQL statement files, it’s recommended that this binary be run from the **app** directory

Usage

db/admin [options] command

Options and Arguments

--env ENVIRONMENT

An optional environment specification that causes the database configuration to be read out of the corresponding section of the `app/db/dbconf.yml` configuration file. One of:

- development
- integration
- production
- test

admin sets `MOJO_MODE` to the value of the environment as specified by this option. (Default: development)

--trafficvault

When used, commands will be run against the Traffic Vault PostgreSQL backend database as specified in the `app/db/trafficvault/dbconf.yml` configuration file.

command

The `command` specifies the operation to be performed on the database. It must be one of:

createdb Creates the database for the current environment

create_migration Creates a pair of timestamped up/down migrations titled NAME.

create_user Creates the user defined for the current environment

dbversion Displays the database version that results from the current sequence of migrations

down Rolls back a single migration from the current version

drop Drops the database for the current environment

drop_user Drops the user defined for the current environment

load_schema Sets up the database for the current environment according to the SQL statements in `app/db/create_tables.sql` or `app/db/trafficvault/create_tables.sql` if the `--trafficvault` option is used

migrate Runs a migration on the database for the current environment

patch Patches the database for the current environment using the SQL statements from the `app/db/patches.sql`. This command is not supported when using the `--trafficvault` option

redo Rolls back the most recently applied migration, then run it again

reset Creates the user defined for the current environment, drops the database for the current environment, creates a new one, loads the schema into it, and runs a single migration on it

seed Executes the SQL statements from the `app/db/seeds.sql` file for loading static data. This command is not supported when using the `--trafficvault` option

show_users Displays a list of all users registered with the PostgreSQL server

status Deprecated, `status` is now an alias for `dbversion` and will be removed in a future Traffic Control release.

upgrade Performs a migration on the database for the current environment, then seeds it and patches it using the SQL statements from the `app/db/patches.sql` file

133: Example Usage

```
db/admin --env=test reset
```

The environments are defined in the `traffic_ops/app/db/dbconf.yml` file, and the name of the database generated will be the name of the environment for which it was created. If the `--trafficvault` option is used, the `app/db/trafficvault/dbconf.yml` file defines this information.

Resolving Migration Failures

If you encounter an error running a migration, you will see a message like

134: db/admin error example

```
[root@trafficops app]# db/admin -env production migrate
Error running migrate up: migration failed: syntax error at or near
↳ "This_is_a_syntax_error" (column 1) in line 18: /*
```

That means that the migration timestamp in the version column of the `schema_migrations` table has been updated to the version of the migration that failed, but the `dirty` column is also set, and if you try to run another migration (either up or down), you will see

135: db/admin error migrating when the database version is dirty

```
[root@trafficops app]# db/admin -env production migrate
Error running migrate up: Dirty database version 20210708000000000. Fix
↳ and force version.
```

You will need to manually fix the database. When you are sure that it is fixed, you can unset the `dirty` column manually using an SQL client.

Installing The Developer Environment

To install the Traffic Ops Developer environment:

1. Clone the [Traffic Control repository](#) from GitHub. In most cases it is best to clone this directly into `GOPATH/src/github.com/apache/trafficcontrol`, as otherwise the Go implementation will not function properly.
2. Install any required Go dependencies - the suggested method is using `go-get(1)`.

136: Install Go Development Dependencies

```
# assuming current working directory is the repository
↳ root
go mod vendor -v
```

3. Set up a role (user) in PostgreSQL

See also:

PostgreSQL instructions on setting up a database.

4. Use the reset and upgrade *commands* of **admin** (see [app/db/admin](#) for usage) to set up the `traffic_ops` database(s) and optionally with the `--trafficvault` option to set up the `traffic_vault` database(s).
5. Run the `traffic_ops/install/bin/postinstall` script, it will prompt for information like the default user login credentials.
6. To run Traffic Ops, follow the instructions in [Running](#).

app/db/traffic_vault_migrate

The `traffic_vault_migrate` tool - located at `traffic_ops/app/db/traffic_vault_migrate/traffic_vault_migrate.go` in the [Apache Traffic Control repository](#) - is used to transfer TV keys between database servers. It interfaces directly with each backend so Traffic Ops/Vault being available is not a requirement. The tool assumes that the schema for each backend is already setup as according to the [admin setup](#).

Usage

```
traffic_vault_migrate [-cdhmr] [-e value] [-f value] [-g value] [-i value] [-l value] [-o value] [-t value]
```

-c, --compare

Compare ‘to’ and ‘from’ backend keys. Will fetch keys from the dbs of both ‘to’ and ‘from’, sorts them by cdn/ds/version and does a deep comparison.

Note: Mutually exclusive with `-r/--dry`

-d, --dump

Write keys (from ‘from’ server) to disk in the folder ‘dump’ with the unix permissions 0640.

Warning: This can write potentially sensitive information to disk, use with care.

Note: Mutually exclusive with `-l/--fill`

-e LEVEL, --logLevel=LEVEL

Print everything at above specified log level (error|warning|info|debug|event) [info]

Note: Mutually exclusive with *-l/--logCfg*

- f** CFG, **--fromCfgPath**=CFG
From server config file ["riak.json"]
- g** CFG, **--toCfgPath**=CFG
To server config file ["pg.json"]
- h, --help**
Displays usage information
- i** DIR, **--fill** DIR
Insert data into *to* server with data in this directory

Note: Mutually exclusive with *-d/--dump*

- l** CFG, **--logCfg** CFG
Log configuration file

Note: Mutually exclusive with *-e/--logLevel*

- o** TYPE, **--toType**=TYPE
From server types (Riak|PG) [PG]
- m, --noConfirm**
Don't require confirmation before inserting records
- r, --dry**
Do not perform writes. Will do a basic output of the keys on the 'from' backend.

Note: Mutually exclusive with *-c/--compare*

- t** TYPE, **--fromType**=TYPE
From server types (Riak|PG) [Riak]

Riak

riak.json

user The username used to log into the Riak server.

password The password used to log into the Riak server.

host The hostname for the Riak server.

port The port for which the Riak server is listening for protobuf connections.

timeout The number of seconds to wait for each operation.

insecure (Optional) Determines whether to verify insecure certificates.

tlsVersion (Optional) Max TLS version supported. Valid values are “10”, “11”, “12”, “13”.

Postgres

traffic_vault_migrate will properly handle both encryption and decryption of postgres data as that is done on the client side.

pg.json

user The username used to log into the PG server.

password The password for the user to log into the PG server.

database The database to connect to.

port The port on which the PG server is listening.

host The hostname of the PG server.

sslmode The ssl settings for the client connection, [explanation here](#). Options are ‘disable’, ‘allow’, ‘prefer’, ‘require’, ‘verify-ca’ and ‘verify-full’

aesKey The base64 encoding of a 16, 24, or 32 bit AES key.

Logging

The log configuration file has the structure:

error_log Where to output error messages (stderr|stdout|null)

warning_log Where to output warning messages (stderr|stdout|null)

info_log Where to output info messages (stderr|stdout|null)

debug_log Where to output error messages (stderr|stdout|null)

event_log Where to output error messages (stderr|stdout|null)

Adding a Migration Backend

To add a plugin, implement the `traffic_vault_migrate.go:TVBackend` interface and add the backend to the returned values in github.com/apache/trafficcontrol/traffic_ops/app/db/traffic_vault_migrate.supportBackends.

Test Cases

Go Tests

Many (but not all) endpoint handlers and utility packages in the Go code-base define Go unit tests that can be run with `go-test(1)`. There are integration tests for the Traffic Ops Go client in `traffic_ops/testing/api/`.

137: Sample Run of Go Unit Tests

```
cd traffic_ops/traffic_ops_golang

# run just one test
go test ./about

# run all of the tests
go test ./...
```

There are a few prerequisites to running the Go client integration tests:

- A PostgreSQL server must be accessible and have a Traffic Ops database schema set up (though not necessarily populated with anything).
- A running Traffic Ops Go implementation instance must be accessible - it shouldn't be necessary to also be running the Perl implementation.

Note: For testing purposes, SSL certificates are not verified, so self-signed certificates will work fine.

Note: It is *highly* recommended that the Traffic Ops instance be run on the same machine as the integration tests, as otherwise network latency can cause the tests to exceed their threshold time limit of ten minutes.

The integration tests are run using `go-test(1)`, with two configuration options available.

Note: It should be noted that the integration tests will output thousands of lines of highly repetitive text not directly related to the tests its running at the time - even if the `-v` flag is not passed to `go-test(1)`. This problem is tracked by [Issue #4017](#).

Warning: Running the tests will wipe the connected database clean, so do not **ever** run it on an instance of Traffic Ops that holds meaningful data.

--cfg CONFIG

Specify the path to the *Test Configuration File*. If not specified, it will attempt to read a file named `traffic-ops-test.conf` in the working directory.

See also:

Configuring the Integration Tests for a detailed explanation of the format of this configuration file.

--fixtures FIXTURES

Specify the path to a file containing static data for the tests to use. This should almost never be used, because many of the tests depend on the data having a certain content and structure. If not specified, it will attempt to read a file named `tc-fixtures.json` in the working directory.

--includeSystemTests ``no``/``yes``

Specify whether to run tests that depend on additional components like an SMTP server or a Traffic Vault server. Default: no

Configuring the Integration Tests

Configuration is mainly done through the configuration file passed as **--cfg**, but is also available through the following environment variables.

In addition to the variables described here, the integration tests support identifying the network location of the Traffic Ops instance via *TO_URL*.

SESSION_TIMEOUT_IN_SECS

Sets the timeout of requests made to the Traffic Ops instance, in seconds.

TODB_DESCRIPTION

An utterly cosmetic variable which, if set, gives a description of the PostgreSQL database to which the tests will connect. This has no effect except possibly changing one line of debug output.

TODB_HOSTNAME

If set, will define the FQDN at which the PostgreSQL server to be used by the tests resides¹.

TODB_NAME

If set, will define the name of the database to which the tests will connect^{Page 298, 1}.

TODB_PASSWORD

If set, defines the password to use when authenticating with the PostgreSQL server.

TODB_PORT

If set, defines the port on which the PostgreSQL server listens^{Page 298, 1}.

¹ The Traffic Ops instance *must* be using the same PostgreSQL database that the tests will use.

TODB_SSL

If set, must be one of the following values:

true The PostgreSQL server to which the tests will connect uses SSL on the port on which it will be contacted.

false The PostgreSQL server to which the tests will connect does not use SSL on the port on which it will be contacted.

TODB_TYPE

If set, tells the database driver used by the tests the kind of SQL database to which they are connecting^{Page 298, 1}. This author has no idea what will happen if this is set to something other than Pg, but it's possible the tests will fail to run. Certainly never do it.

TODB_USER

If set, defines the user as whom to authenticate with the PostgreSQL server.

TO_USER_ADMIN

If set, will define the name of a user with the “admin” *Role* that will be created by the tests².

TO_USER_DISALLOWED

If set, will define the name of a user with the “disallowed” *Role* that will be created by the tests².

TO_USER_EXTENSION

If set, will define the name of a user with the “extension” *Role* that will be created by the tests².

Caution: Due to legacy constraints, the only truly safe value for this is `extension` - anything else could cause the tests to fail.

TO_USER_FEDERATION

If set, will define the name of a user with the “federation” *Role* that will be created by the tests².

TO_USER_OPERATIONS

If set, will define the name of a user with the “operations” *Role* that will be created by the tests².

TO_USER_PASSWORD

If set, will define the password used by all users created by the tests. This does not need to be the password of any pre-existing user.

TO_USER_PORTAL

If set, will define the name of a user with the “portal” *Role* that will be created by the tests².

TO_USER_READ_ONLY

If set, will define the name of a user with the “read-only” *Role* that will be created by the tests².

² This does not need to match the name of any pre-existing user.

Test Configuration File

The configuration file for the tests (defined by `--cfg`) is a JSON-encoded object with the following properties.

Warning: Many of these configuration options are overridden by variables in the execution environment. Where this is a problem, there is an associated warning. In general, this issue is tracked by [Issue #3975](#).

default An object containing sub-objects relating to default configuration settings for connecting to external resources during testing

logLocations An object containing key/value pairs where the keys are log levels and each associated value is the file location to which logs of that level will be written. The allowed values respect the [reserved special names used by the github.com/apache/trafficcontrol/lib/go-log package](#). Omitted keys are treated as though their values were null, in which case that level is written to `/dev/null`. The allowed keys are:

- debug
- error
- event
- info
- warning

session An object containing key/value pairs that define the default settings used by Traffic Ops “session” connections

timeoutInSecs At the time of this writing this is the only meaningful configuration option that may be present under `session`. It specifies the timeouts used by client connections during testing as an integer number of seconds. The default if not specified (or overridden) is 0, meaning no limit.

Warning: This configuration is overridden by `SESSION_TIMEOUT_IN_SECS`.

trafficOps An object containing information that defines the running Traffic Ops instance to use in testing.

password This password will be used for all created users used by the test suite - it does not need to be the password of any pre-existing user. The default if not specified (or overridden) is an empty string, which may or may not cause problems.

Warning: This is overridden by `TO_USER_PASSWORD`.

URL The network location of the running Traffic Ops server, including schema, hostname and optionally port number e.g. `https://localhost:6443`.

Warning: This is overridden by `TO_URL`.

users An object containing key-value pairs where the keys are the names of *Roles* and the values are the usernames of users that will be created with the associated *Role* for testing purposes. *There are very few good reasons why the values should not just be the same as the keys.* The default for any missing (and not overridden) key is the empty string which is *won't* work so please don't leave any undefined. The allowed keys are:

- admin

Warning: The value of this key is overridden by `TO_USER_ADMIN`.

- disallowed

Warning: The value of this key is overridden by `TO_USER_DISALLOWED`.

- extension

Warning: The value of this key is overridden by `TO_USER_EXTENSION`.

- federation

Warning: The value of this key is overridden by *TO_USER_FEDERATION*.

- operations

Warning: The value of this key is overridden by *TO_USER_OPERATIONS*.

- portal

Warning: The value of this key is overridden by *TO_USER_PORTAL*.

- readOnly

Warning: The value of this key is overridden by *TO_USER_READ_ONLY*.

trafficOpsDB An object containing information that defines the database to use in testing^{Page 298, 1}.

dbname The name of the database to which the tests will connect^{Page 298, 1}.

Warning: This is overridden by *TODB_NAME*.

description An utterly cosmetic option that need not exist at all which, if set, gives a description of the database to which the tests will connect. This has no effect except possibly changing one line of debug output.

Warning: This is overridden by *TODB_DESCRIPTION*

hostname The FQDN of the server on which the database is running^{Page 298, 1}

Warning: This is overridden by `TODB_HOSTNAME`.

password The password to use when authenticating with the database

Warning: This is overridden by `TODB_PASSWORD`.

port The port on which the database listens for connections^{Page 298, 1} - as a **string**

Warning: This is overridden by `TODB_PORT`.

type The “type” of database being used^{Page 298, 1}. This should **never** be set to anything besides “Pg”, anything else results in undefined behavior (although it’s equally possible that it simply won’t have any effect).

Warning: This is overridden by `TODB_TYPE`.

ssl An optional boolean value that defines whether or not the database uses SSL encryption for its connections - default if not specified (or overridden) is `false`

Warning: This is overridden by `TODB_SSL`.

user The name of the user as whom to authenticate with the database

Warning: This is overridden by `TODB_USER`.

Writing New Endpoints

Note: Most new endpoints are accompanied by database schema changes which necessitate a new migration under `traffic_ops/app/db/migrations` and database best-practices are not discussed in this section.

See also:

This section contains a quick overview of API endpoint development; for the full guidelines for API endpoints, consult [API Guidelines](#).

The first thing to consider when writing a new endpoint is what the requests it will serve will look like. It's recommended that new endpoints avoid using "path parameters" when possible, and instead try to utilize request bodies and/or query string parameters. For example, instead of `/foos/{ID}` consider simply `/foos` with a supported `id` query parameter. The request *methods* should be restricted to the following, and respect each method's associated meaning.

DELETE Removes a resource or one or more of its representations from the server. This should **always** be the method used when deleting objects.

GET Retrieves a representation of some resource. This should *always* be used for read-only operations and note that the requesting client **never** expects the state of the server to change as a result of a request using the GET method.

POST Requests that the server process some passed data. This is used most commonly to create new objects on the server, but can also be used more generally e.g. with a request for regenerating encryption keys. Although this isn't strictly creating new API resources, it does change the state of the server and so this is more appropriate than GET.

PUT Places a new representation of some resource on the server. This is typically used for updating existing objects. For creating *new* representations/objects, use POST instead. When using PUT note that clients expect it to be *idempotent*, meaning that subsequent identical PUT requests should result in the same server state. What this means is that it's standard to require that *all* of the information defining a resource be provided for each request even if the vast majority of it isn't changing.

The HEAD and OPTIONS request methods have default implementations for any properly defined [Traffic Ops API](#) route, and so should almost never be defined explicitly. Other request methods (e.g. CONNECT) are currently unused and ought to stay that way for the time being.

Note: Utilizing the PATCH method is unfeasible at the time of this writing but progress toward supporting it is being made, albeit slowly in the face of other priorities.

See also:

The MDN (Mozilla Developer Network)'s [documentation on the various HTTP request methods](#).

The final step of creating any [Traffic Ops API](#) endpoint is to write documentation for it. When doing so, be sure to follow *all* of the guidelines laid out in [Documentation Guidelines](#). *If documentation doesn't exist for new functionality then it has accomplished nothing because no one using Traffic Control will know it exists.* Omitted documentation is how a project winds up with a dozen different API endpoints that all do essentially the same thing.

Framework Options

The Traffic Ops code base offers two basic frameworks for defining a new endpoint. Either one may be used at the author's discretion (or even neither if desired and appropriate - though that seems unlikely).

Generic “CRUDer”

The “Generic ‘CRUDer’”, as it's known, is a pattern of API endpoint development that principally involves defining a type that implements the github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/api.CRUDEr interface. A description of what that entails is best left to the actual GoDoc documentation.

See also:

The github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/api.GenericCreate, github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/api.GenericDelete, github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/api.GenericRead, and github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/api.GenericUpdate helpers are often used to provide the default operations of creating, deleting, reading, and updating objects, respectively. When the API endpoint being written is only meant to perform these basic operations on an object or objects stored in the database, these should be totally sufficient.

This method offers a lot of functionality “out-of-the-box” as compared to the [APIInfo](#) method, but because of that is also restrictive. For example, it is not possible to write an endpoint that returns data not encoded as JSON using this method. That's an uncommon use-case, but not unheard-of.

This method is best used for basic creation, reading, update, and deletion operations performed on simple objects with no structural differences across API versions.

APIInfo

Endpoint handlers can also be defined by simply implementing the [net/http.HandlerFunc](https://golang.org/pkg/net/http/#HandlerFunc) interface. The [net/http.Request](https://golang.org/pkg/net/http/#Request) reference passed into such handlers provides identifying information for the authenticated user (where applicable) in its context.

To easily obtain the information needed to identify a user and their associated permissions, as well as server configuration information and a database transaction handle, authors should use the github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/api.NewInfo function which will return all of that information in a single structure as well as any errors encountered during the process and an appropriate HTTP response code in case of such errors.

This method offers fine control over the endpoint's logic, but tends to be much more verbose than the endpoints written using the [Generic “CRUDer”](#) method. For example, a handler for retrieving an object from the database and returning it to the requesting client encoded as JSON can be twenty or more lines of code, whereas a sin-

gle call to github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/api.GenericCreate provides equivalent functionality.

This method is best used when requests are meant to have extensive side-effects, are performed on unusually structured objects, need fine control of the HTTP headers/options, or operate on objects that have different structures or meanings across API versions.

Extensions

What’s typically meant by “extension” in the context of Traffic Ops is a *Check Extensions* which provides data for server “checks” which can be viewed in Traffic Portal under *Monitor* → *Cache Checks*. This type of extension need not know nor even care which implementation it is being used with, as it interacts with Traffic Ops through the *Traffic Ops API*.

Traffic Ops supports overrides or new definitions for non-standard *Traffic Ops API* routes. This type of “extension” is typically referred to as a “plugin,” and they are described in *Go Plugins*.

Go Plugins

A plugin is defined by a Go source file in the [traffic_ops/traffic_ops_golang/plugin](https://github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/plugin) directory, which is expected to be named *plugin name.go*. A plugin is registered to Traffic Ops by a call to github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/plugin.AddPlugin in the source file’s special `init` function.

A plugin is only enabled at runtime if its name is present in the *cdn.conf* file’s `traffic_ops_golang.plugins` array.

Each plugin may also define any, all, or none of the lifecycle hooks provided: `load`, `startup`, and `onRequest`

load The `load` function of a plugin, if defined, needs to implement the github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/plugin.LoadFunc interface, and will be run when the server starts and after configuration has been loaded. It will be passed the plugin’s own configuration as it was defined in the *cdn.conf* file’s `traffic_ops_golang.plugin_config` map.

onRequest The `onRequest` function of a plugin, if defined, needs to implement the github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/plugin.OnRequestFunc interface, and will be called on **every** request made to the *Traffic Ops API*. Because of this, it’s imperative that the function exit as soon as possible. Note that once one plugin reports that it has served the request, no others will be tried. The order in which plugins are tried is defined by their order in the `traffic_ops_golang.plugins` array of the *cdn.conf* configuration file.

See also:

It’s very common for this function to behave like a *Traffic Ops API* endpoint, so when writing a plugin it may be useful to review *Writing New Endpoints*.

startup Like `load`, the `startup` function of a plugin, if defined, will be called when the server starts and after configuration has been loaded. *Unlike* `load`, however, this function should implement the `github.com/apache/trafficcontrol/traffic_ops/traffic_ops_golang/plugin.StartupFunc` interface and will be passed in the entirety of the server's configuration, including its own configuration and any shared plugin configuration data as defined in the `cdn.conf` file's `traffic_ops_golang.plugin_shared_config` map.

Example

An example “Hello World” plugin that serves the `/_hello` request path by just writing “Hello World” in the body of a 200 OK response back to the client is provided in `traffic_ops/traffic_ops_golang/plugin/hello_world.go`:

```

1 package plugin
2
3 /*
4  Licensed under the Apache License, Version 2.0 (the "License");
5  you may not use this file except in compliance with the License.
6  You may obtain a copy of the License at
7
8  http://www.apache.org/licenses/LICENSE-2.0
9
10  Unless required by applicable law or agreed to in writing, software
11  distributed under the License is distributed on an "AS IS" BASIS,
12  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
13  →implied.
14  See the License for the specific language governing permissions and
15  limitations under the License.
16 */
17 import (
18     "strings"
19 )
20
21 func init() {
22     AddPlugin(10000, Funcs{onRequest: hello}, "example HTTP plugin",
23     →"1.0.0")
24 }
25
26 const HelloPath = "/_hello"
27
28 func hello(d OnRequestData) IsRequestHandled {
29     if !strings.HasPrefix(d.R.URL.Path, HelloPath) {
30         return RequestUnhandled
31     }
32     d.W.Header().Set("Content-Type", "text/plain")

```

(continues on next page)

(continued from previous page)

```

32     d.W.Write([]byte("Hello, World!"))
33     return RequestHandled
34 }

```

Check Extensions

Check Extensions allow you to add custom checks to the *Monitor* → *Cache Checks* view.

Extensions are managed using the `$TO_HOME/bin/extensions` command line script

See also:

For more information see *Managing Traffic Ops Extensions*.

4.1.9 Traffic Portal

Introduction

Traffic Portal is an [AngularJS](#) client served from a [Node.js](#) web server designed to consume the *Traffic Ops API*. Traffic Portal is the official replacement for the legacy Traffic Ops UI.

Software Requirements

To work on Traffic Portal you need a *nix (MacOS and Linux are most commonly used) environment that has the following installed:

- [Ruby Devel 2.0.x](#) or above
- [Compass 1.0.x](#) or above
- [Node.js 12.0.x](#) or above
- [Grunt CLI 1.2.0](#) or above
- Access to a working instance of Traffic Ops

Install Global NPM Packages

Grunt CLI can be installed using NPM.

138: Install Grunt CLI

```
npm -g install grunt-cli
```

Install Compass

Compass can be installed using `gem` manually, or by using `bundle`

Tip: Bundle will automatically install the correct version of the gems.

1. `brew install ruby`/`apt-get install ruby`/`yum install ruby`
2. `gem update --system`
3. At this point, you can either manually install the gems or use `bundler`
 1. For manually: `gem install sass compass`
 2. For automatically: `gem install bundle && bundle install`

Note: Bundle requires ruby versions > 2.3.0, so if you're using a version of ruby < 2.3.0 then this will not work.

4. Make sure that `compass` and `sass` are part of your `PATH` environment variable.
5. **If not, you can see where `gem` installs `compass` and `sass` by running:** `gem environment`
6. **In there, you can see where ruby is installing all the gems. Add that path to your `PATH` environment**
For example, it is `/usr/local/lib/ruby/gems/2.7.0/gems/compass-1.0.3/bin/` for this test setup.
7. **Once you have installed `compass` successfully, make sure you can reach it by typing:**
`compass version` This should give a valid output. For example, for the test setup, the output is:

139: Compass version output

```
Compass 1.0.3 (Polaris)
Copyright (c) 2008-2020 Chris Eppstein
Released under the MIT License.
Compass is charityware.
Please make a tax deductible donation for a worthy cause: http://umdf.
→org/compass
```

Traffic Portal Project Tree Overview

- **traffic_control/traffic_portal/app/src** - contains HTML, JavaScript and SCSS (Sassy CSS) source files.

Installing The Traffic Portal Developer Environment

1. Clone the [Traffic Control Repository](#)
2. Navigate to the `traffic_portal` subdirectory of your cloned repository.
3. Run `npm install` to install application dependencies into `traffic_portal/node_modules`. Only needs to be done the first time unless `traffic_portal/package.json` changes.
4. Make sure that compass is installed and functioning correctly by running `compass version`. If compass is not available, then it can be installed following the instructions under [Install Compass](#).
5. **Modify `traffic_portal/conf/configDev.js`:**
 1. Valid SSL certificates and keys are needed for Traffic Portal to run. Generate these (e.g. using [this SuperUser answer](#)) and update `ssl`.
 2. Modify `api.base_url` to point to your Traffic Ops API endpoint.
6. Run `grunt` to package the application into `traffic_portal/app/dist`, start a local HTTPS server (Express), and start a file watcher.
7. Navigate to `http(s)://localhost:[port|sslPort]` defined in `traffic_portal/conf/configDev.js`

Note: The Traffic Portal consumes the Traffic Ops API. Modify `traffic_portal/conf/configDev.js` to specify the location of Traffic Ops.

4.1.10 Traffic Router

Introduction

Traffic Router is a Java Tomcat application that routes clients to the closest available cache on the CDN using both HTTP and DNS. Cache server availability is determined by Traffic Monitor; consequently Traffic Router polls Traffic Monitor for its configuration and *cache server* health state information, and uses this data to make routing decisions. HTTP routing is performed by localizing the client based on the request's source IP address (IPv4 or IPv6), and issues an HTTP 302 response to redirect to the nearest *cache server*. HTTP routing utilizes consistent hashing on request URLs to optimize cache performance and request distribution. DNS routing is performed by localizing clients, resolvers in most cases, requesting A and AAAA records for a configurable name such as `foo.deliveryservice.somecdn.net`. Traffic Router is comprised of seven separate Maven modules:

- shared - A reusable utility JAR for defining *Delivery Service* Certificates
- configuration - A reusable JAR defining the ConfigurationListener interface
- connector - A JAR that overrides Tomcat's standard Http11Protocol Connector class and allows Traffic Router to delay opening listen sockets until it is in a state suitable for routing traffic
- geolocation - Submodule for defining geolocation services
- neustar - A JAR that provides a bean "neustarGeolocationService" that implements the GeolocationService interface defined in the geolocation maven submodule, which can optionally be added to the build of Traffic Router
- core - Services DNS and HTTP requests, performs localization on routing requests, and is deployed as a WAR to a Service (read: connector/listen port) within Tomcat which is separate from the API
- build - A simple Maven project which gathers the artifacts from the modules and builds an RPM

Software Requirements

To work on Traffic Router you need a *nix (MacOS and Linux are most commonly used) environment that has the following installed:

- Eclipse >= Kepler SR2 (or another Java IDE)
- Maven >= 3.3.1
- JDK >= 8.0 (OpenJDK suggested, but not required)
- OpenSSL >= 1.0.2
- APR >= 1.4.8-3
- Tomcat Native >= 1.2.23

- Not Tomcat - You do not need a Tomcat installation for development. An embedded version is launched for development testing instead.

Get OpenJDK 8 on macOS

If you are on macOS, OpenJDK 8 is not available from Homebrew by default, but it can still be installed using Homebrew with little effort.

Using Homebrew, add the [AdoptOpenJDK](#) tap and install the `adoptopenjdk8` cask

140: Install OpenJDK 8 on macOS

```
brew tap AdoptOpenJDK/openjdk
brew cask install adoptopenjdk8
```

Next, set the `JAVA_HOME` environment variable. Add this line to your `~/.bash_profile`:

141: Set `JAVA_HOME` environment variable

```
export JAVA_HOME=$(/usr/libexec/java_home -v1.8)
```

Traffic Router Project Tree Overview

- `traffic_control/traffic_traffic_router/` - base directory for Traffic Router
 - `connector/` - Source code for Traffic Router Connector;
 - * `src/main/java` - Java source directory for Traffic Router Connector
 - `core/` - Source code for Traffic Router Core, which is built as its own deployable WAR file and communicates with *Traffic Router API* using JMX
 - * `src/main` - Main source directory for Traffic Router Core
 - `lib/systemd/system/traffic_router.service` - Unit script for launching the Traffic Router with Tomcat
 - `conf/` - All of the required configuration files for running the `traffic_router` web application, including those needed for Tomcat
 - `java/` - Java source code for Traffic Router Core
 - `resources/` - Resources pulled in during an RPM build
 - `scripts/` - Scripts used by the RPM build process
 - `webapp/` - Java “webapp” resources
 - `var/log/` - location of all the Traffic Router runtime logs
 - * `src/test` - Test source directory for Traffic Router Core
 - `conf/` - Minimal Configuration files that make it possible to run JUnit tests

- `db/` - Files downloaded by unit tests
- `java/` - JUnit-based unit tests for Traffic Router Core
- `resources/` - Example data files used by junit tests
- `var/auto-zones` - BIND formatted zone files generated by Traffic Router Core during unit testing

Java Formatting Conventions

None at this time. The codebase will eventually be formatted per Java standards.

Installing The Developer Environment

To install the Traffic Router Developer environment:

1. Clone the `traffic_control` repository using Git.
2. Change directories into `traffic_control/traffic_router`.
3. Set the environment variable `TRAFFIC_MONITOR_HOSTS` to be a semicolon delimited list of Traffic Monitors that can be accessed during integration tests OR install the `traffic_monitor.properties` file.
4. Additional configuration is set using the below files:
 - copy `core/src/main/conf/dns.properties` to `core/src/test/conf/`
 - copy `core/src/main/conf/http.properties` to `core/src/test/conf/`
 - copy `core/src/main/conf/log4j.properties` to `core/src/test/conf/`
 - copy `core/src/main/conf/traffic_monitor.properties` to `core/src/test/conf/` and then edit the `traffic_monitor.bootstrap.hosts` property
 - copy `core/src/main/conf/traffic_ops.properties` to `core/src/test/conf/` and then edit the credentials as appropriate for the Traffic Ops instance you will be using.
 - Default configuration values now reside in `core/src/main/webapp/WEB-INF/applicationContext.xml`

Note: These values may be overridden by creating and/or modifying the property files listed in `core/src/main/resources/applicationProperties.xml`

Note: Pre-existing properties files are still honored by Traffic Router. For example `traffic_monitor.properties` may contain the FQDN and port of the Traffic Monitor instance(s), separated by semicolons as necessary (do not include scheme e.g. `http://`)

5. Import the existing git repository as projects into your IDE (Eclipse):
 - a. *File* → *Import* → *Git* → *Projects from Git*; *Next*
 - b. *Existing local repository*; *Next*
 - c. *Add* - browse to find `traffic_control`; *Open*
 - d. Select `traffic_control`; *Next*
 - e. Ensure *Import existing projects* is selected, expand `traffic_control`, select `traffic_router`; *Next*
 - f. Ensure `traffic_router_api`, `traffic_router_connector`, and `traffic_router_core` are checked; *Finish* (this step can take several minutes to complete)
 - g. Ensure `traffic_router_api`, `traffic_router_connector`, and `traffic_router_core` have been opened by Eclipse after importing
6. From the terminal or your IDE, run `mvn clean verify` from the `traffic_router` directory. This will run a series of integration tests and will temporarily start and embedded version of Traffic Router and a ‘fake’ simulated instance of Traffic Monitor.
7. Start the embedded Tomcat instance for Core from within your IDE by following these steps:
 - a. In the package explorer, expand `traffic_router_core`
 - b. Expand `src/test/java`
 - c. Expand the package `org.apache.traffic_control.traffic_router.core`
 - d. Open and run `TrafficRouterStart.java`

Note: If an error is displayed in the Console, run `mvn clean verify` from the `traffic_router` directory

Once running, the *Traffic Router API* is available over HTTP at <http://localhost:3333> and over HTTPS at <https://localhost:3443>, the HTTP routing interface is available on <http://localhost:8888> and HTTPS is available on <http://localhost:8443>. The DNS server and routing interface is available on `localhost:53` via TCP and UDP.

Manual Testing

Look up the URL for a test HTTP *Delivery Service* in Traffic Ops and then make a request. When Traffic Router is running and used as a resolver for the host in the *Delivery Service* URL, the requested origin content should be found through an Edge-tier *cache server*.

142: Example Test for an HTTP *Delivery Service*

```
root@enroller:/shared/enroller# curl -skvL http://video.demo1.mycdn.
→ciab.test/
* Trying fc01:9400:1000:8::60...
* TCP_NODELAY set
* Connected to video.demo1.mycdn.ciab.test (fc01:9400:1000:8::60) port.
→80 (#0)
> GET / HTTP/1.1
> Host: video.demo1.mycdn.ciab.test
> User-Agent: curl/7.52.1
> Accept: */*
>
< HTTP/1.1 302 Found
< Location: http://edge.demo1.mycdn.ciab.test/
< Content-Length: 0
< Date: Wed, 16 Jan 2019 21:52:14 GMT
<
* Curl_http_done: called premature == 0
* Connection #0 to host video.demo1.mycdn.ciab.test left intact
* Issue another request to this URL: 'http://edge.demo1.mycdn.ciab.
→test/'
* Trying fc01:9400:1000:8::100...
* TCP_NODELAY set
* Connected to edge.demo1.mycdn.ciab.test (fc01:9400:1000:8::100) port.
→80 (#1)
> GET / HTTP/1.1
> Host: edge.demo1.mycdn.ciab.test
> User-Agent: curl/7.52.1
> Accept: */*
>
< HTTP/1.1 200 OK
< Content-Type: text/html
< Accept-Ranges: bytes
< ETag: "1473249267"
< Last-Modified: Wed, 07 Nov 2018 13:53:57 GMT
< Cache-Control: public, max-age=300
< Access-Control-Allow-Origin: *
< Access-Control-Allow-Headers: Accept, Origin, Content-Type
< Access-Control-Allow-Methods: GET, POST, PUT, OPTIONS
< Content-Length: 1881
< Date: Wed, 16 Jan 2019 21:52:15 GMT
```

(continues on next page)

(continued from previous page)

```
< Server: ATS/7.1.4
< Age: 1
< Via: http/1.1 mid.infra.ciab.test (ApacheTrafficServer/7.1.4
→[uScMsSfWpSeN:t cCMi p sS]), http/1.1 edge.infra.ciab.test
→(ApacheTrafficServer/7.1.4 [uScMsSfWpSeN:t cCMi pSs ])
< Connection: keep-alive
<
<!DOCTYPE html>
<!-- Licensed to the Apache Software Foundation (ASF) under one
or more contributor license agreements. See the NOTICE file
distributed with this work for additional information
regarding copyright ownership. The ASF licenses this file
to you under the Apache License, Version 2.0 (the
"License"); you may not use this file except in compliance
with the License. You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing,
software distributed under the License is distributed on an
"AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
KIND, either express or implied. See the License for the
specific language governing permissions and limitations
under the License. -->
<html lang="en">
<head>
    <title>CDN In a Box</title>
    <meta charset="utf-8"/>
    <meta charset="utf-8"/>
    <meta name="viewport" content="width=device-width; height=device-
→height; initial-scale=1"/>
    <link rel="shortcut-icon" href="/tc_logo.svg"/>
    <meta name="author" content="Apache"/>
    <meta name="creator" content="Apache"/>
    <meta name="publisher" content="Apache"/>
    <meta name="description" content="A simple test origin for Apache
→Traffic Control"/>
    <style type="text/css">
        html {
            height: 100vh;
            width: 100vw;
        }

        body {
            text-align: center;
            background-image: url(/tc_logo.svg);
```

(continues on next page)

(continued from previous page)

```
        background-color: black;
        background-position: center;
        background-repeat: no-repeat;
        background-size: 25%;
        font-family: "Ubuntu Mono","Consolas",sans-serif;
        color: white;
        margin: 0;
        padding-top: 0.67em;
        max-width: 100%;
    }

    h1 {
        margin-top: 0.67em;
    }

    p {
        text-align: left;
        width: 80vw;
        min-width: 320px;
        margin: auto;
    }
</style>
</head>
<body>
    <h1>Test Origin</h1>
    <p>This is a test "origin" server for Apache Traffic Control</p>
</body>
</html>
* Curl_http_done: called premature == 0
* Connection #1 to host edge.demo1.mycdn.ciab.test left intact
```

Test Cases

- Unit tests can be executed using Maven by running `mvn test` at the root of the `traffic_router` project.
- Unit and Integration tests can be executed using Maven by running `mvn verify` at the root of the `traffic_router` project.

Debugging Unit Tests

In order to write tests or understand why a test is failing, a developer may want to debug the unit tests. In order to stop at breakpoints, you should run the tests without forking processes. Even once you have specified for Surefire not to fork tests, the debugging connection will disconnect several times while the tests are running, so you should - Have JVM act as the debugging client and have your IDE act as the debugging server, even if you are remote debugging - In your IDE's debugging configuration for the Traffic Router unit tests, enable "auto restart", meaning that, once the debugging client running on JVM has disconnected because a particular test is over, your IDE's debugging server will exit (unavoidable) but will immediately restart in time for the next test.

Note: If you run the tests with debugging enabled and with JVM acting as the debugging client but your IDE is not actively listening for debugging connections, the unit tests *will* fail.

Command for running the tests with debugging enabled:

143: Run the Traffic Router unit tests with debugging enabled

```
mvn '-Dmaven.surefire.debug=-agentlib:jdwp=transport=dt_socket,
    ↪server=n,suspend=n,address=localhost:8000 -DforkCount=0 -
    ↪DreuseForks=false' test -Djava.library.path=/usr/share/java
```

Debugging Unit Tests in Docker

In order to run the unit tests in a controlled, well-defined environment, you may prefer to run them from within Docker. A Docker environment for running the Traffic Router unit tests exists in the repository at `/traffic_router/tests`, and it supports debugging. In order to enable debugging, set `DEBUG_ENABLE` to `'true'` in `docker-compose.yml`. As mentioned in [Debugging Unit Tests](#), - Have your IDE act as the debugging server. In IntelliJ, this debug mode is called *Listen to remote JVM*. - Enable *auto-restart* in your IDE's debugging configuration for the Traffic Router unit tests so your IDE doesn't stop listening for connections after the first test ends - Set the port to 8000 (debugging port is specified in the Dockerfile)

Additionally, you will need to make sure that `host.docker.internal` resolves to the Docker host's IP address (NOT the Docker container's IP address). If you are using Docker Desktop for Mac or Docker Desktop for Windows, this is already set up for you. If you are on Linux, you will need to either figure out how to make `host.docker.internal` resolve to the `docker0` network interface's IP address, or, in `docker-compose.yml`, change the value of the `DEBUG_HOST` environment variable to the IP address of the `docker0` interface.

Note: If you run the tests with debugging enabled and with JVM (in Docker) acting as the debugging client but your IDE is not actively listening for debugging connections, the unit tests *will* fail.

Once your IDE is listening for debugging connections, start the unit tests:

144: Run the Traffic Router unit tests in Docker, with or without debugging enabled

```
docker-compose up
```

RPM Packaging

Running `mvn package` on a Linux-based distribution will trigger the build process to create the Traffic Router RPM and the Traffic Router `.war` file, but will not run the integration tests, so it is a good way to update those artifacts quickly during development. But the preferred way to build the Traffic Router RPMs is by following the instructions in *Building Traffic Control*

API

Traffic Router API

Traffic Router API

By default, Traffic Router serves its API via HTTP (not HTTPS) on port 3333. This can be configured in `/opt/traffic_router/conf/server.xml` or by setting a *Parameter* with the *Name* “api.port”, and the *Config File* “server.xml” on the Traffic Router’s *Profile*.

The API can be configured via HTTPS on port 3443 in `/opt/traffic_router/conf/server.xml` or by setting a *Parameter* named `secure.api.port` with configFile `server.xml` on the Traffic Router’s *Profile*. The post install script will generate self signed certificates at `/opt/traffic_router/conf/`, create a new Java Keystore named `/opt/traffic_router/conf/keyStore.jks`, and add the new certificate to the Keystore. The password for the Java Keystore and the Keystore location are stored in `/opt/traffic_router/conf/https.properties`. To override the self signed certificates with new ones from a certificate authority, update the properties for the Keystore location and password at `/opt/traffic_router/conf/https.properties`.

The API can be configured via HTTPS on port 3443 in `/opt/traffic_router/conf/server.xml` or by setting a *Parameter* named `secure.api.port` with configFile `server.xml` on the Traffic Router’s *Profile*. When `systemctl start traffic_router` is run, it will generate self signed certificates at `/opt/traffic_router/conf/`, create a new Java Keystore named `/opt/traffic_router/conf/keyStore.jks`, and add the new certificate to the Keystore. The password for the Java Keystore and the Keystore location are stored in `/opt/traffic_router/conf/https.properties`. To override the self signed certificates with new ones from a certificate authority, either replace the Java Keystore in the default location or update the properties for the new Keystore location and password at `/opt/traffic_router/conf/https.properties` and then restart the Traffic Router using `systemctl`.

Traffic Router API endpoints only respond to GET requests.

/crs/stats

General stats.

Request Structure

145: Request Example

```
GET /crs/stats HTTP/1.1
Host: trafficrouter.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
```

Response Structure

146: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Tue, 15 Jan 2019 21:02:09 GMT

{ "app": {
  "buildTimestamp": "2019-01-10",
  "name": "traffic_router",
  "deploy-dir": "/opt/traffic_router",
  "git-revision": "437e9df81",
  "version": "3.0.0"
},
"stats": {
  "dnsMap": {},
  "httpMap": {
    "video.demo1.mycdn.ciab.test": {
      "czCount": 0,
      "geoCount": 0,
      "deepCzCount": 0,
      "missCount": 0,
      "dsrCount": 0,
      "errCount": 0,
      "staticRouteCount": 0,
      "fedCount": 0,
      "regionalDeniedCount": 0,
      "regionalAlternateCount": 0
    }
  }
},
```

(continues on next page)

(continued from previous page)

```

"totalDnsCount": 0,
"totalHttpCount": 1,
"totalDsMissCount": 0,
"appStartTime": 1547584831677,
"averageDnsTime": 0,
"averageHttpTime": 1547584863270,
"updateTracker": {
  "lastHttpsCertificatesCheck": 1547586068932,
  "lastGeolocationDatabaseUpdaterUpdate": 1547584858917,
  "lastCacheStateCheck": 1547586128932,
  "lastCacheStateChange": 1547584867102,
  "lastNetworkUpdaterUpdate": 1547584857484,
  "lastHttpsCertificatesUpdate": 1547586071079,
  "lastSteeringWatcherUpdate": 1547584923514,
  "lastConfigCheck": 1547586127344,
  "lastConfigChange": 1547584863406,
  "lastNetworkUpdaterCheck": 1547584857465,
  "lastGeolocationDatabaseUpdaterCheck": 1547584858906,
  "lastFederationsWatcherUpdate": 1547584863433,
  "lastHttpsCertificatesFetchSuccess": 1547586069070,
  "lastSteeringWatcherCheck": 1547586124630,
  "lastFederationsWatcherCheck": 1547586124584,
  "lastHttpsCertificatesFetchAttempt": 1547586068932
}
}}
```

/crs/stats/ip/{{IP}}

Geolocation information for an IPv4 or IPv6 address.

Request Structure

Table 79: Request Path Parameters

Name	Description
IP	The IP address for which statics will be returned. May be IPv4 or IPv6

147: Request Example

```

GET /crs/stats/ip/255.255.255.255 HTTP/1.1
Host: trafficrouter.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
```

Response Structure

148: Response Example

```
HTTP/1.1 200 OK
Content-Disposition: inline;filename=f.txt
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Tue, 15 Jan 2019 21:06:09 GMT

{ "locationByGeo": {
  "city": "Woodridge",
  "countryCode": "US",
  "latitude": "41.7518",
  "postalCode": "60517",
  "countryName": "United States",
  "longitude": "-88.0489"
},
"locationByFederation": "not found",
"requestIp": "69.241.118.34",
"locationByCoverageZone": "not found",
"locationByDeepCoverageZone": "not found"
}
```

/crs/locations

A list of configured *Cache Groups* to which the Traffic Router is capable of routing client traffic.

Request Structure

149: Request Example

```
GET /crs/locations HTTP/1.1
Host: trafficrouter.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
```

Response Structure

locations An array of strings that are the *Names of Cache Groups* to which this Traffic Router is capable of routing client traffic

150: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json; charset=UTF-8
Transfer-Encoding: chunked
Date: Tue, 15 Jan 2019 21:12:17 GMT

{ "locations": [
  "CDN_in_a_Box_Edge"
]}
```

/crs/locations/caches

A mapping of caches to cache groups and their current health state.

Request Structure

151: Request Example

```
GET /crs/locations/caches HTTP/1.1
Host: trafficrouter.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
```

Response Structure

152: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Tue, 15 Jan 2019 21:15:53 GMT

{ "locations": {
  "CDN_in_a_Box_Edge": [
    {
      "cacheId": "edge",
      "fqdn": "edge.infra.ciab.test",
      "ipAddresses": [
        "172.16.239.100",
        "fc01:9400:1000:8:0:0:0:100"
      ],
      "port": 0,
      "adminStatus": null,
      "lastUpdateHealthy": false,
      "lastUpdateTime": 0,
      "connections": 0,
      "currentBW": 0,
      "availBW": 0,
      "cacheOnline": true
    }
  ]
}}
```

/crs/locations/{{cachegroup}}/caches

A list of *cache servers* for this *Cache Group* only.

Request Structure

Table 80: Request Path Parameters

Name	Description
cachegroup	The <i>Name of a Cache Group</i> of which a list of constituent <i>cache servers</i> will be retrieved

153: Request Example

```
GET /crs/locations/CDN_in_a_Box_Edge/caches HTTP/1.1
Host: trafficrouter.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
```

Response Structure

154: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json; charset=UTF-8
Transfer-Encoding: chunked
Date: Tue, 15 Jan 2019 21:18:25 GMT

{ "caches": [
  {
    "cacheId": "edge",
    "fqdn": "edge.infra.ciab.test",
    "ipAddresses": [
      "172.16.239.100",
      "fc01:9400:1000:8:0:0:0:100"
    ],
    "port": 0,
    "adminStatus": null,
    "lastUpdateHealthy": false,
    "lastUpdateTime": 0,
    "connections": 0,
    "currentBW": 0,
    "availBW": 0,
    "cacheOnline": true
  }
]
```

(continues on next page)

(continued from previous page)

```
}
[]}
```

/crs/consistenthash/cache/coveragezone

The resulting cache of the consistent hash using coverage zone file for a given client IP, *Delivery Service*, and request path.

Request Structure

Table 81: Request Query Parameters

Name	Re-quired	Description
ip	yes	The IP address of a potential client
delivery-ServiceId	yes	The integral, unique identifier?/?xml_id'?/name? of a <i>Delivery Service</i> served by this Traffic Router
requestPath	yes	The... request path?

Response Structure

TBD

/crs/consistenthash/cache/deep/coveragezone

The resulting cache of the consistent hash using deep coverage zone file (deep caching) for a given client IP, *Delivery Service*, and request path.

Request Structure

Table 82: Request Query Parameters

Name	Re-quired	Description
ip	yes	The IP address of a potential client
delivery-ServiceId	yes	The integral, unique identifier?/?xml_id'?/name? of a <i>Delivery Service</i> served by this Traffic Router
requestPath	yes	The... request path?

Response Structure

TBD

/crs/consistenthash/cache/geolocation

The resulting cache of the consistent hash using geographic location for a given client IP, *Delivery Service*, and request path.

Request Structure

Table 83: Request Query Parameters

Name	Re-quired	Description
ip	yes	The IP address of a potential client
delivery-ServiceId	yes	The integral, unique identifier?/?xml_id'?/name? of a <i>Delivery Service</i> served by this Traffic Router
requestPath	yes	The... request path?

Response Structure

TBD

/crs/consistenthash/deliveryservice/

The resulting *Delivery Service* of the consistent hash for a given *Delivery Service* and request path – used to test STEERING *Delivery Services*.

Request Structure

Table 84: Request Query Parameters

Name	Re-quired	Description
delivery-ServiceId	yes	The integral, unique identifier?/?xml_id'?/name? of a <i>Delivery Service</i> served by this Traffic Router
requestPath	yes	The... request path?

155: Request Example

```
GET /crs/consistenthash/deliveryservice?deliveryServiceId=demo1&
→requestPath=/ HTTP/1.1
Host: trafficrouter.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
```

Response Structure

156: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json; charset=UTF-8
Transfer-Encoding: chunked
Date: Tue, 15 Jan 2019 21:40:51 GMT

{ "id": "demo1",
  "coverageZoneOnly": false,
  "geoRedirectUrl": null,
  "geoRedirectFile": null,
  "geoRedirectUrlType": "INVALID_URL",
  "routingName": "video",
  "missLocation": {
    "latitude": 42,
    "longitude": -88,
    "postalCode": null,
    "city": null,
    "countryCode": null,
    "countryName": null,
    "defaultLocation": false,
    "properties": {
      "city": null,
      "countryCode": null,
      "latitude": "42.0",
      "postalCode": null,
      "countryName": null,
      "longitude": "-88.0"
    }
  },
  "dispersion": {
    "limit": 1,
    "shuffled": true
  },
  "ip6RoutingEnabled": true,
```

(continues on next page)

(continued from previous page)

```
"responseHeaders": {},
"requestHeaders": [],
"regionalGeoEnabled": false,
"geolocationProvider": "maxmindGeolocationService",
"anonymousIpEnabled": false,
"sslEnabled": true,
"acceptHttp": true,
"deepCache": "NEVER",
"dns": false,
"locationLimit": 0,
"maxDnsIps": 0,
"sslReady": true,
"available": true
}
```

/crs/coveragezone/caches

A list of caches for a given *Delivery Service* and *Cache Group*.

Request Structure

Table 85: Request Query Parameters

Name	Re- quired	Description
delivery-ServiceId	yes	The integral, unique identifier?'/xml_id'/?/name? of a <i>Delivery Service</i> served by this Traffic Router
cacheLocationId	yes	The <i>Name of a Cache Group</i> to which this Traffic Router is capable of routing client traffic

Response Structure

TBD

/crs/coveragezone/cachelocation

The resulting *Cache Group* for a given client IP and *Delivery Service*.

Request Structure

Table 86: Request Query Parameters

Name	Re-quired	Description
ip	yes	The IP address of a potential client
delivery-ServiceId	yes	The integral, unique identifier?/'xml_id'/?/name? of a <i>Delivery Service</i> served by this Traffic Router

Response Structure

TBD

/crs/deepcoveragezone/cachelocation

The resulting *Cache Group* using the *Deep Coverage Zone File* (deep caching) for a given client IP and *Delivery Service*.

Request Structure

Table 87: Request Query Parameters

Name	Re-quired	Description
ip	yes	The IP address of a potential client
delivery-ServiceId	yes	The integral, unique identifier?/'xml_id'/?/name? of a <i>Delivery Service</i> served by this Traffic Router

Response Structure

TBD

/crs/consistenthash/patternbased/regex

The resulting path that will be used for consistent hashing when the given regex is applied to the given request path.

Request Structure

Table 88: Request Query Parameters

Name	Re-quired	Description
regex	yes	The (URI encoded) regular expression to be used to test pattern based consistent hashing
request-Path	yes	The (URI encoded) request path to use to test pattern based consistent hashing

157: Request Example

```
GET /crs/consistenthash/patternbased/regex?regex=%2F.*%3F%28%2F.*%3F%2F
→%29.*%3F%28%5C.m3u8%29&requestPath=%2Ftext1234%2Fname%2Fasset.m3u8
→HTTP/1.1
Host: localhost:3333
User-Agent: curl/7.54.0
Accept: */*
```

Response Structure

158: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Fri, 15 Feb 2019 22:06:53 GMT

{
  "resultingPathToConsistentHash": "/name/.m3u8",
  "consistentHashRegex": "/.*?(/.*?/).*(\\..m3u8)",
  "requestPath": "/text1234/name/asset.m3u8"
}
```

/crs/consistenthash/patternbased/deliveryservice

The resulting path that will be used for consistent hashing for the given delivery service and the given request path.

Request Structure

Table 89: Request Query Parameters

Name	Re-quired	Description
requestPath	yes	The (URI encoded) request path to use to test pattern based consistent hashing
delivery-ServiceId	yes	The integral, unique identifier?/'xml_id'?/name? of a <i>Delivery Service</i> served by this Traffic Router

159: Request Example

```
GET /crs/consistenthash/patternbased/deliveryservice?
→deliveryServiceId=asdf&requestPath=%2Fsometext1234%2Fstream_name
→%2Fasset_name.m3u8 HTTP/1.1
Host: localhost:3333
User-Agent: curl/7.54.0
Accept: */*
```

Response Structure

160: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Transfer-Encoding: chunked
Date: Fri, 15 Feb 2019 22:12:38 GMT

{
  "resultingPathToConsistentHash": "/sometext1234/stream_name/asset_name.
→m3u8",
  "deliveryServiceId": "asdf",
  "requestPath": "/sometext1234/stream_name/asset_name.m3u8"
}
```

/crs/consistenthash/cache/coveragezone/steering

The resulting cache of the consistent hash using coverage zone for a given client IP, delivery service and, request path – used to test cache selection for steering delivery services.

Request Structure

Table 90: Request Query Parameters

Name	Re-quired	Description
requestPath	yes	The (URI encoded) request path to use to test pattern based consistent hashing
delivery-ServiceId	yes	The integral, unique identifier?'/xml_id'/?/name? of a <i>Delivery Service</i> served by this Traffic Router
ip	yes	The IP address of a potential client

Response Structure

TBD

4.1.11 Traffic Stats

Introduction

Traffic Stats is a utility written in [Go](#) that is used to acquire and store statistics about CDNs controlled by Traffic Control. Traffic Stats mines metrics from the [Traffic Monitor APIs](#) and stores the data in [InfluxDB](#). Data is typically stored in InfluxDB on a short-term basis (30 days or less) and is used to drive graphs created by [Grafana](#) which are linked from Traffic Ops. Traffic Stats also calculates daily statistics from InfluxDb and stores them in the Traffic Ops database.

Software Requirements

- A *nix (MacOS and Linux are most commonly used) environment
- [Go 1.7.x or above](#)
- Access to a working instance of Traffic Ops
- Access to a working instance of Traffic Monitor
- [InfluxDB version 1.0.0 or greater](#)

Traffic Stats Project Tree Overview

- `traffic_stats/` - contains Go source files and files used to create the Traffic Stats RPM.
 - `grafana/` - contains a javascript file which is installed on the Grafana server. This allows Traffic Ops to create custom dashboards for [Delivery Services](#), `:term:cache server`s`, etc.
 - `influxdb_tools/` - contains [sync/sync_ts_databases.go](#) and [create/create_ts_databases.go](#) which are helpful if you have multiple instances and they get out of sync with data.

Go Formatting Conventions

In general [Go fmt](#) is the standard for formatting Go code. It is also recommended to use [Go lint](#).

Installing The Developer Environment

1. Clone the `traffic_control` repository using Git into a location accessible by your `$GOPATH`
2. Navigate to the `traffic_ops/client` directory of your cloned repository. (This is the directory containing Traffic Ops client code used by Traffic Stats)
3. From the `traffic_ops/client` directory run `go test` to test the client code. This will run all unit tests for the client and return the results. If there are missing dependencies you will need to run `go mod vendor -v` to get the dependencies
4. Once the tests pass, run `go install` to build and install the Traffic Ops client package. This makes it accessible to Traffic Stats.
5. Navigate to your cloned repository under Traffic Stats
6. Run `go build traffic_stats.go` to build `traffic_stats`. You will need to run `go mod vendor -v` for any missing dependencies.

A guide to external RESTful APIs for Traffic Ops

5.1 Traffic Ops API

The Traffic Ops API provides programmatic access to read and write Traffic Control data which allows for the monitoring of CDN performance and configuration of Traffic Control settings and parameters.

5.1.1 How to Read this Documentation

Each endpoint for each version is on its own page, titled with the request path. The request paths shown on each endpoint's page are - unless otherwise noted - only usable by being appended to the request path prefix `/api/<version>/` where `<version>` is the API version being requested. The API versions officially supported as of the time of this writing are 1.1, 1.2, 1.3, 1.4, 1.5, 2.0. All endpoints are documented as though they were being used in version 1.5 in the version 1 documentation and version 2.0 in the version 2 documentation. If an endpoint or request method of an endpoint is only available after a specific version, that will be noted next to the method or endpoint name. If changes were made to the structure of an endpoint's input or output, the version number and nature of the change will be noted.

Every endpoint is documented with a section for each method, containing the subsections "Request Structure" and "Response Structure" which identify all properties and structure of the Request to and Response from the endpoint. Before these subsections, three key pieces of information will be provided:

Auth. Required This will either be 'Yes' to indicate that a user must be authenticated (or "logged-in") via e.g. [user/login](#) to use this method of the endpoint, or 'No' to indicate that this is not required.

Roles Required Any permissions roles that are allowed to use this method of the endpoint will be listed here. Users with roles not listed here will be unable to properly use these endpoints

Response Type Unless otherwise noted, all responses are JSON objects. See [Response Structure](#) for more information.

The methods of endpoints that require/accept data payloads - unless otherwise noted - always interpret the content of the payload as a JSON object, regardless of the request's `Content-Type` header. Because of this, all payloads are - unless otherwise noted - JSON objects. The Request Structure and Response Structure subsections will contain explanations of the fields before any examples like e.g.

foo A constant field that always contains “foo”

bar An array of objects that each represent a “bar” object

name The bar's name

value The bar's value (an integer)

All fields are mandatory in a request payload, or always present in a response payload unless otherwise noted in the field description.

In most cases, JSON objects have been “pretty-printed” by inserting line breaks and indentation. This means that the `Content-Length` HTTP header does not, in general, accurately portray the length of the content displayed in Request Examples and Response Examples. Also, the Traffic Ops endpoints will ignore any content negotiation, meaning that the `Content-Type` header of a request is totally meaningless. A utility may choose to pass the data as e.g. *application/x-www-form-urlencoded* (cURL's default `Content-Type`) when constructing a Request Example, but the example itself will most often show *application/json* in order for syntax highlighting to properly work.

Response Structure

Unless otherwise noted, all response payloads come as JSON objects.

161: Response Structure

```
{
  "response": "<JSON object with main response>",
}
```

To make the documentation easier to read, only the `<JSON object with main response>` is documented, even though the response endpoints may return other top-level objects (most commonly the `"alerts"` object). The field definitions listed in the Response Structure subsection of an endpoint method are the elements of this object. Sometimes the `response` object is a string, sometimes it's an object that maps keys to values, sometimes it's an array that contains many arbitrary objects, and sometimes it isn't present at all. For ease of reading, the field lists delegate the distinction to be made by the `Response Type` field directly under the request method heading.

Response Type Meanings

Array The fields in the field list refer to the keys of the objects in the `response` array.

Object The fields in the field list refer to the keys of the `response` object.

undefined No `response` object is present in the response payload. Unless the format is otherwise noted, this means that there should be no field list in the “Response Structure” subsection.

Summary

The top-level `summary` object is used to provide summary statistics about object collections. In general the use of `summary` is left to be defined by API endpoints (subject to some restrictions). When an endpoint uses the `summary` object, its fields will be explained in a subsection of the “Response Structure” named “Summary Fields”.

The following, reserved properties of `summary` are guaranteed to always have their herein-described meaning.

count `count` contains an unsigned integer that defines the total number of results that could possibly be returned given the non-pagination query parameters supplied by the client.

Traffic Ops's Custom Date/Time Format

Traffic Ops will often return responses from its API that include dates. As of the time of this writing, the vast majority of those dates are written in a non-`rfc:3339` format (this is tracked by [Issue #5911](#)). This is most commonly the case in the `last_updated` properties of objects returned as JSON-encoded documents. The format used is `YYYY-MM-DD hh:mm:ss±ZZ`, where `YYYY` is the 4-digit year, `MM` is the two-digit (zero padded) month, `DD` is the two-digit (zero padded) day of the month, `hh` is the two-digit (zero padded) hour of the day, `mm` is the two-digit (zero padded) minute of the hour, `ss` is the two-digit (zero padded) second of the minute, and

ZZ is the two-digit (zero padded) timezone offset in hours of the date/time's local timezone from UTC (the offset can be positive or negative as indicated by a + or a - directly before it, where the sample has a \pm).

Note: In practice, all Traffic Ops API responses use the UTC timezone (offset +00), but do note that this custom format is not capable of representing all timezones.

162: Example Date/Timestamp

2021-06-07 08:01:02+00

5.1.2 Using API Endpoints

1. Authenticate with valid Traffic Control user account credentials (the same used by Traffic Portal).
2. Upon successful user authentication, note the Mojolicious cookie value in the response headers¹.

Note: Many tools have methods for doing this without manual intervention - a web browser for instance will automatically remember and properly handle cookies. Another common tool, cURL, has command line switches that will also accomplish this. Most high-level programming language libraries will implement a cookie-handling method as well.

3. Pass the Mojolicious cookie value, along with any subsequent calls to an authenticated API endpoint.

Note: Although many endpoints in API version 1.x supported a `.json` suffix, API version 2.x does not support it at all. Even when using API version 1.x using the `.json` suffix should be avoided at all costs, because there's no real consistency regarding when it may be used, and the output of API endpoints, in general, are not capable of representing POSIX-compliant files (as a 'file extension' might imply).

¹ A cookie obtained by logging in through Traffic Portal can be used to access API endpoints under the Traffic Portal domain name - since it will proxy such requests back to Traffic Ops. This is not recommended in actual deployments, however, because it will involve an extra network connection which could be avoided by simply using the Traffic Ops domain itself.

Example Session

A user makes a request to the `/api/2.0/asns` endpoint.

```
GET /api/2.0/asns HTTP/1.1
Accept: application/json
Host: trafficops.infra.ciab.test
User-Agent: example
```

The response JSON indicates an authentication error.

```
HTTP/1.1 401 UNAUTHORIZED
Content-Length: 68
Content-Type: application/json
Date: Tue, 02 Oct 2018 13:12:30 GMT

{ "alerts": [
  {
    "level": "error",
    "text": "Unauthorized, please log in."
  }
]}
```

To authenticate, the user sends a POST request containing their login information to the `/api/2.0/user/login` endpoint.

```
POST /api/2.0/user/login HTTP/1.1
User-Agent: example
Host: trafficops.infra.ciab.test
Accept: application/json
Content-Length: 32
Content-Type: application/x-www-form-urlencoded
```

Traffic Ops responds with a Mojolicious cookie to be used for future requests, and a message indicating the success or failure (in this case success) of the login operation.

```
HTTP/1.1 200 OK
Connection: keep-alive
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Content-Type: application/json
Date: Tue, 02 Oct 2018 12:53:32 GMT
Access-Control-Allow-Credentials: true
Content-Length: 81
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

```
{ "alerts": [
  {
    "level": "success",
    "text": "Successfully logged in."
  }
]}
```

Using this cookie, the user can now access their original target - the `/api/2.0/asns` endpoint...

```
GET /api/2.0/asns HTTP/1.1
Accept: application/json
Cookie: mojolicious=...;
Host: trafficops.infra.ciab.test
User-Agent: Example
```

... and the Traffic Ops server will now happily service this request.

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Connection: keep-alive
Content-Encoding: gzip
Content-Length: 48
Content-Type: application/json
Date: Tue, 02 Oct 2018 12:55:57 GMT
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-SHA512: u+Q5X7z/DMTc/
→VzRGaFlJBA8btA8EC...dnA85HCYTm8vVwsQCvle+uVc1nA==
X-Server-Name: traffic_ops_golang/

{ "response": {
  "asns": [
    {
      "lastUpdated": "2012-09-17 21:41:22",
      "id": 27,
      "asn": 7015,
      "cachegroup": "us-ma-woburn",
      "cachegroupId": 2
    },
    {
      "lastUpdated": "2012-09-17 21:41:22",
```

(continues on next page)

(continued from previous page)

```

        "id": 28,
        "asn": 7016,
        "cachegroup": "us-pa-pittsburgh",
        "cachegroupID": 3
      }
    ]
  }
}
```

5.1.3 API Errors

If an API endpoint has something to say besides the actual response (usually an error message), it will add a top-level object to the response JSON with the key "alerts". This will be an array of objects that represent messages from the server, each with the following string fields:

level "success", "info", "warning" or "error" as appropriate

text The alert's actual message

The most common errors returned by Traffic Ops are:

401 Unauthorized When a "mojolicious" cookie is supplied that is invalid or expired, or the login credentials are incorrect the server responds with a **401 UNAUTHORIZED** response code.

163: Example of a Response to a Login Request with Bad Credentials

```

HTTP/1.1 401 Unauthorized
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-
  ↳Type, Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Whole-Content-Sha512: xRKu2Q7Yj07UA6A6SyxMnmCBpuBcW2/
  ↳bzuK05eTZ2y4V27rXfP/5bSkNPesomJbi00+xSmiybDsHlcl3P+pzpg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 02 Oct 2018 13:28:30 GMT
Content-Length: 69

{ "alerts": [
  {
    "text": "Invalid username or password.",
    "level": "error"
  }
]}
```

404 Not Found When the requested resource (path) doesn't exist, Traffic Ops returns a 404 NOT FOUND response code.

164: Example Response to GET /not/an/api/path
HTTP/1.1 with Proper Cookies

```
HTTP/1.1 404 Not Found
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-
→Type, Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: text/html;charset=UTF-8
Date: Tue, 02 Oct 2018 13:58:56 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019_
→17:40:54 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: Ff5h08ZUNUMbwCW0mBuUlsvrSmm/
→Giijq703uLivLZ6V0u6eGom4Jag6UqlBbbDBnP6AG7l1Szdt74TT6NidA==
Transfer-Encoding: chunked

{ "alerts": [
  {
    "level": "error",
    "text": "Resource not found."
  }
]}
```

500 Internal Server Error When a server-side error occurs, the API will return a 500 INTERNAL SERVER ERROR response.

165: Example Response to GET /api/2.0/servers.
(when a server error such as a postgres failure occurred)

```
HTTP/1.1 500 Internal Server Error
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-
→Type, Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Length: 93
Content-Type: application/json
Date: Tue, 02 Oct 2018 17:29:42 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019_
→17:40:54 GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Vary: Accept-Encoding
Whole-Content-Sha512:↵
↵gFa4NYFmofCbV7YqgwyFRzKk90+KNgoZu6p2Nx98J4Gy7/
↵2j55tYknvk53WXuMdMKKrgYMop4uiY0la1k1ozQQ==

{ "alerts": [
  {
    "level": "error",
    "text": "An error occurred. Please contact your↵
↵administrator."
  }
]}
```

The rest of the API documentation will only document the 200 OK case, where no errors have occurred.

5.1.4 TrafficOps Native Client Libraries

TrafficOps client libraries are available in Java, Go and Python. You can read (very little) more about them in the client README at [traffic_control/clients](#).

5.1.5 API V2 Routes

API routes available in version 2.

Deprecated since version ATCv6: Traffic Ops API version 2 is deprecated in favor of version 3.

about

GET

Returns info about the Traffic Ops build that is currently running, generated at startup. The output will be the same until the Traffic Ops *version changes*.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

166: Request Example

```
GET /api/2.0/about HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

commitHash The [Git](#) commit hash that Traffic Ops was built at.

commits The number of commits in the branch of the commit that Traffic Ops was built at, including that commit. Calculated by running `git rev-list HEAD | wc -l`.

goVersion The version of [Go](#) that was used to build Traffic Ops.

release The major version of CentOS or Red Hat Enterprise Linux that the build environment was running.

name The human-readable name of the [RPM](#) file.

RPMVersion The entire name of the RPM file, excluding the file extension.

Version The version of ATC that this version of Traffic Control belongs to.

167: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 19:35:28
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳7SVQsddCUVRs+sineziRGR60yMli7XLZbjxyMQgW6E506bh5thM0uttPFT7aJckDcgT45PlhexycwlApO
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 18:35:28 GMT
Content-Length: 145
```

(continues on next page)

(continued from previous page)

```
{
  "commitHash": "1c9a2e9c",
  "commits": "10555",
  "goVersion": "go1.11.13",
  "release": "el7",
  "name": "traffic_ops",
  "RPMVersion": "traffic_ops-4.0.0-10555.1c9a2e9c.el7",
  "Version": "4.0.0"
}
```

api_capabilities

Deals with the capabilities that may be associated with API endpoints and methods. These capabilities are assigned to *Roles*, of which a user may have one or more. Capabilities support “wildcarding” or “globbing” using asterisks to group multiple routes into a single capability

GET

Get all API-capability mappings.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 91: Request Query Parameters

Name	Required	Type	Description
capability	no	string	Capability name

168: Request Example

```
GET /api/2.0/api_capabilities?capability=types-write HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

capability Capability name

httpMethod An HTTP request method, practically one of:

- GET
- POST
- PUT
- PATCH
- DELETE

httpRoute The request route for which this capability applies - relative to the Traffic Ops server's URL

id An integer which uniquely identifies this capability

lastUpdated The time at which this capability was last updated, in *Traffic Ops's Custom Date/Time Format*

169: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 01 Nov 2018 14:45:24 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: wptErtIop/AfTTQ+1MZdA2YpPXEOuLFfrPQvvaHqO/
→uX5fRruOVYW+7p8JTrtH1xg1WN+x6FnjQnSHuWwcpyJg==
Content-Length: 393
```

(continues on next page)

(continued from previous page)

```
{ "response": [
  {
    "httpMethod": "POST",
    "lastUpdated": "2018-11-01 14:10:22.794114+00",
    "httpRoute": "types",
    "id": 261,
    "capability": "types-write"
  },
  {
    "httpMethod": "PUT",
    "lastUpdated": "2018-11-01 14:10:22.795917+00",
    "httpRoute": "types/*",
    "id": 262,
    "capability": "types-write"
  },
  {
    "httpMethod": "DELETE",
    "lastUpdated": "2018-11-01 14:10:22.799748+00",
    "httpRoute": "types/*",
    "id": 263,
    "capability": "types-write"
  }
]}
```

asns

See also:

The [Autonomous System Wikipedia](#) page for an explanation of what an ASN actually is.

GET

List all ASNs.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 92: Request Query Parameters

Parameter	Required	Description
cache-group-id	no	The <i>ID</i> of a <i>Cache Group</i> - only ASNs for this <i>Cache Group</i> will be returned.
order-by	no	The integral, unique identifier of the desired ASN-to- <i>Cache Group</i> association
sortOrder	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
limit	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
offset	no	Choose the maximum number of results to return
page	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
	no	Return the <i>n</i> th page of results, where “ <i>n</i> ” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

170: Request Example

```
GET /api/2.0/asns HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cache-group** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cache-groupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops’s Custom Date/Time Format*

171: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 22:51:14
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳F2NmDbTpXqrIQDX7IBKH9+1drtTL4XedSfJv6klMgLEZwbLCkddIXuSLpmgVCID6kTVqy3fTKjZS3U+HJ
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 21:51:14 GMT
Content-Length: 128

{ "response": [
  {
    "asn": 1,
    "cachegroup": "TRAFFIC_ANALYTICS",
    "cachegroupId": 1,
    "id": 1,
    "lastUpdated": "2019-12-02 21:49:08+00"
  }
]}
```

POST

Creates a new ASN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

asn The value of the new ASN

cachegroup An optional field which, if present, is a string that specifies the *Name* of a *Cache Group* to which this ASN will be assigned

Note: While this endpoint accepts the `cachegroup` field, sending this in the request payload has no effect except that the response will (erroneously) name the *Cache Group* to which the ASN was assigned. Any subsequent requests will reveal that, in fact, the *Cache Group* is set entirely by the `cachegroupId` field, and so the actual *Name* may differ from what was in the request.

cachegroupId An integer that is the *ID* of a *Cache Group* to which this ASN will be assigned

172: Request Example

```
POST /api/2.0/asns HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 29

{"asn": 1, "cachegroupId": 1}
```

Response Structure

asn An ASN as specified by IANA for identifying a service provider

cachegroup A string that is the *Name* of the *Cache Group* that is associated with this ASN

cachegroupId An integer that is the *ID* of the *Cache Group* that is associated with this ASN

id An integral, unique identifier for this association between an ASN and a *Cache Group*

lastUpdated The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

173: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 22:49:08
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mx8b2GTYoJz4QtMxXCMoQyZogCB504vs0yv6WGly4dwM81W3XiejWNuUwchRBYyi8QHawsMZ3DaiGGfQi,
    ↳8Giw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 21:49:08 GMT
Content-Length: 150

{ "alerts": [
  {
    "text": "asn was created.",
    "level": "success"
  }
],
"response": {
  "asn": 1,
  "cachegroup": null,
  "cachegroupId": 1,
  "id": 1,
  "lastUpdated": "2019-12-02 21:49:08+00"
}}
```

PUT

Updates an existing ASN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

asn The value of the new ASN.

cachegroup A string that specifies the *Name* of a *Cache Group* to which this ASN will be assigned. If you do not pass this field, the cachegroup will be null.

cachegroupId The integral, unique identifier of the status of the *Cache Group*.

174: Request Example

```
PUT /api/2.0/asns?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 53

{
  "asn": 1,
  "cachegroup": "TRAFFIC_OPS",
  "cachegroupId": 2
}
```

Response Structure

asn An ASN as specified by IANA for identifying a service provider

cachegroup A string that is the *Name* of the *Cache Group* that is associated with this ASN

cachegroupId An integer that is the *ID* of the *Cache Group* that is associated with this ASN

id An integral, unique identifier for this association between an ASN and a *Cache Group*

lastUpdated The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

175: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 07:21:10 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: MjvwJg6AFbdqGPlAhK+2pfiN+VFjzgeNnhXoMVbh6+fRQYKeej6CCj3x09hw0l4uhp9d9RySrE/CQ3+L1b2VGQ==
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 06:21:10 GMT
Content-Length: 164

{
  "alerts": [
    {
      "text": "asn was updated.",
      "level": "success"
    }
  ],
  "response": {
    "asn": 1,
    "cachegroup": "TRAFFIC_OPS",
    "cachegroupId": 2,
    "id": 1,
    "lastUpdated": "2020-02-25 06:21:10+00"
  }
}
```

DELETE

Deletes an existing ASN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

176: Request Example

```
DELETE /api/2.0/asns?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
```

(continues on next page)

(continued from previous page)

```
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

177: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 08:27:33
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Woz8NSHIYVpX4V5X4xZWZIX1hvGL2uian7nUhjZ8F23Nb9RWQRMIG/cc+1vXEzkT/
    ↳ehKV9t11FKRLX+avSae0g==
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 07:27:33 GMT
Content-Length: 83

{
  "alerts": [
    {
      "text": "asn was deleted.",
      "level": "success"
    }
  ]
}
```


`asns/{{id}}`

See also:

The [Autonomous System Wikipedia](#) page for an explanation of what an ASN actually is.

PUT

Allows user to edit an existing ASN-to-*Cache Group* association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

asn The new ASN which will be associated with the identified *Cache Group* - must not conflict with existing associations

cachegroup An optional field which, if present, is a string that specifies the *Name* of a *Cache Group* to which this ASN will be assigned

Note: While this endpoint accepts the `cachegroup` field, sending this in the request payload has no effect except that the response will (erroneously) name the *Cache Group* to which the ASN was assigned. Any subsequent requests will reveal that, in fact, the *Cache Group* is set entirely by the `cachegroupId` field, and so the actual *Name* may differ from what was in the request.

cachegroupId An integer that is the *ID* of a *Cache Group* to which this ASN will be assigned - must not conflict with existing associations

Table 93: Request Path Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the desired ASN-to- <i>Cache Group</i> as- sociation

178: Request Example

```
PUT /api/2.0/asns/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

(continues on next page)

(continued from previous page)

```
Content-Length: 29
Content-Type: application/x-www-form-urlencoded

{"asn": 2, "cachegroupId": 1}
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cachegroup** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cachegroupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

179: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: /83P4LJVsrQx9BKHfxo5pbhQm1B4o3a9v3PpkspyOJcpNx1S/
→GJhCPpiANBki547sbY+0vTq76IriHZ4GYp8bA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 08 Nov 2018 14:37:39 GMT
Content-Length: 160

{ "alerts": [
  {
    "text": "asn was updated.",
    "level": "success"
  }
],
"response": {
  "asn": 2,
  "cachegroup": null,
```

(continues on next page)

(continued from previous page)

```
"cachegroupId": 1,
"id": 1,
"lastUpdated": "2018-11-08 14:37:39+00"
}}
```

DELETE

Deletes an association between an ASN and a *Cache Group*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 94: Request Path Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the desired ASN-to- <i>Cache Group</i> as- sociation

180: Request Example

```
DELETE /api/2.0/asns/1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

181: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 23:06:24.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→6t3WA+DOcfPJB5UnvDpzEVx5ySfmJgEV9wgk071U5k32L1VXpxcaTdDVLNGgDD19sdNftmYnKXf5jpfWU
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 22:06:24 GMT
Content-Length: 81

{ "alerts": [
  {
    "text": "asn was deleted.",
    "level": "success"
  }
]}
```

cache_stats

Retrieves detailed, aggregated statistics for caches in a specific CDN.

See also:

This gives an aggregate of statistics for *all caches* within a particular CDN and time range. For statistics basic statistics from all caches regardless of CDN and at the current time, use *caches/stats*.

GET

Retrieves statistics about the caches within the CDN

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 95: Request Query Parameters

Name	Required	Description
cdnName	yes	The name of a CDN. Results will represent caches within this CDN
end-Date	yes	The date and time until which statistics shall be aggregated in RFC 3339 format (with or without sub-second precision), the number of nanoseconds since the Unix Epoch, or in the same, proprietary format as the <code>lastUpdated</code> fields prevalent throughout the Traffic Ops API
exclude	no	Either “series” to omit the data series from the result, or “summary” to omit the summary data from the result - directly corresponds to fields in the Response Structure
interval	no	Specifies the interval within which data will be “bucketed”; e.g. when requesting data from 2019-07-25T00:00:00Z to 2019-07-25T23:59:59Z with an interval of “1m”, the resulting data series (assuming it is not excluded) should contain $24 \frac{\text{hours}}{\text{day}} \times 60 \frac{\text{minutes}}{\text{hour}} \times 1 \text{day} \times 1 \frac{\text{minute}}{\text{datapoint}} = 1440$ data points The allowed values for this parameter are valid InfluxQL duration literal strings matching <code>^d+[mhdw]\$</code>
limit	no	A natural number indicating the maximum amount of data points should be returned in the <code>series</code> object
metric-Type	yes	The metric type being reported - one of: ‘connections’, ‘bandwidth’, ‘maxkbits’
offset	no	A natural number of data points to drop from the beginning of the returned data set
orderby	no	Though one struggles to imagine why, this can be used to specify “time” to sort data points by their “time” (which is the default behavior)
start-Date	yes	The date and time from which statistics shall be aggregated in RFC 3339 format (with or without sub-second precision), the number of nanoseconds since the Unix Epoch, or in the same, proprietary format as the <code>lastUpdated</code> fields prevalent throughout the Traffic Ops API

182: Request Example

```
GET /api/2.0/cache_stats?cdnName=CDN&endDate=2019-10-28T20:49:00Z&
→metricType=bandwidth&startDate=2019-10-28T20:45:00Z HTTP/1.1
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: application/json;timestamp=unix, application/json;
→timestamp=rfc;q=0.9, application/json;q=0.8, */*;q=0.7
Connection: keep-alive
Cookie: mojolicious=...
```

Content Format

It's important to note in *Request Example* the use of a complex “Accept” header. This endpoint accepts two special media types in the “Accept” header that instruct it on how to format the timestamps associated with the returned data. Specifically, Traffic Ops will recognize the special, optional, non-standard parameter of *application/json: timestamp*. The values of this parameter are restricted to one of

rfc Returned timestamps will be formatted according to **RFC 3339** (no sub-second precision).

unix Returned timestamps will be formatted as the number of nanoseconds since the Unix Epoch (midnight on January 1st 1970 UTC).

Implementation Detail

The endpoint passes back nanoseconds, specifically, because that is the form used both by InfluxDB, which is used to store the data being served, and Go's standard library. Clients may need to convert the value to match their own standard libraries - e.g. the `Date()` class in Javascript expects milliseconds.

The default behavior - when only e.g. *application/json* or **/** is given - is to use **RFC 3339** formatting. It will, however, respect quality parameters. It is suggested that clients request timestamps they can handle specifically, rather than relying on this default behavior, as it is **subject to change** and is in fact **expected to invert in the next major release** as string-based time formats become deprecated.

See also:

For more information on the “Accept” HTTP header, consult [its dedicated page on MDN](#).

Response Structure

series An object containing the actual data series and information necessary for working with it.

columns This is an array of names of the columns of the data contained in the “values” array - should always be `["time", "sum_count"]`

count The number of data points contained in the “values” array

name The name of the data set. Should always match `metric.ds.1min` where `metric` is the requested `metricType`

values The actual array of data points. Each represents a length of time specified by the `interval` query parameter

time The time at which the measurement was taken. This corresponds to the *beginning* of the interval. This time comes in the format of either an [RFC 3339](#)-formatted string, or a number containing the number of nanoseconds since the Unix Epoch depending on the “Accept” header sent by the client, according to the rules outlined in [Content Format](#).

value The value of the requested `metricType` at the time given by `time`. This will always be a floating point number, unless no data is available for the data interval, in which case it will be `null`

summary A summary of the data contained in the “series” object

average The arithmetic mean of the data’s values

count The number of measurements taken within the requested timespan. This is, in general, **not** the same as the `count` field of the `series` object, as it reflects the number of underlying, un-“bucketed” data points, and is therefore dependent on the implementation of Traffic Stats.

fifthPercentile Data points with values less than or equal to this number constitute the “bottom” 5% of the data set

max The maximum value that can be found in the requested data set

min The minimum value that can be found in the requested data set

ninetyEighthPercentile Data points with values greater than or equal to this number constitute the “top” 2% of the data set

ninetyFifthPercentile Data points with values greater than or equal to this number constitute the “top” 5% of the data set

183: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: p4asf1n7fXGtgpW/
    ↳dWgolJWdXjwDcCjyvJOPFqkckbgoXGUHEj5/
    ↳wlz7brlQ48t3ZnOWCq0lbsu2eSiBssBtUQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 28 Oct 2019 20:49:51 GMT

{ "response": {
  "series": {
    "columns": [
      "time",
      "sum_count"
    ],
    "count": 4,
    "name": "bandwidth.cdn.1min",
    "tags": {
      "cdn": "CDN-in-a-Box"
    },
    "values": [
      [
        1572295500000000000,
        null
      ],
      [
        1572295560000000000,
        113.66666666666666
      ],
      [
        1572295620000000000,
        108.83333333333334
      ]
    ]
  }
}
```

(continues on next page)

(continued from previous page)

```

        ],
        [
            15722956800000000000,
            113
        ]
    ],
    },
    "summary": {
        "average": 111.83333333333333,
        "count": 3,
        "fifthPercentile": 0,
        "max": 113.66666666666666,
        "min": 108.83333333333334,
        "ninetyEighthPercentile": 113.66666666666666,
        "ninetyFifthPercentile": 113.66666666666666
    }
}
}

```

cachegroupparameters

Deprecated since version ATCv6.

GET

Extract information about the *Parameters* associated with *Cache Groups*.

Auth. Required Yes

Roles Required None

Response Type Object

Response Structure

Table 96: Request Query Parameters

Name	Required	Description
cache-group	no	Show only the <i>Parameters</i> with the <i>Cache Group</i> identified by this integral, unique identifier
parameter	no	Show only the <i>Parameters</i> with the <i>Parameter</i> identified by this integral, unique identifier
order-by	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

cacheGroupParameters An array of identifying information for the *Parameters* of *Cache Groups*

cacheGroup A string containing the *Name* of the *Cache Group*

last_updated Date and time of last modification in *Traffic Ops’s Custom Date/Time Format*

parameter An integer that is the *Parameter’s ID*

184: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 18:24:12 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
➔GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Vary: Accept-Encoding
Whole-Content-Sha512: PZyh09NeYYy4sXSv+Bfov0v32EuEk/1y7/
↪B+4fyvhbcPxWQ650NXBDpAe8IsmYZQYVRB03xlBtc33bo3Ixunbg==
Content-Length: 124

{ "response": {
  "cachegroupParameters": [
    {
      "parameter": 124,
      "last_updated": "2018-11-14 18:23:40.488853+00",
      "cachegroup": "test"
    }
  ]
}}
```

Deprecated since version ATCv6.

POST

Assign *Parameter*(s) to *Cache Group*(s).

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

This endpoint accepts two formats for the request payload:

Single Object Format For assigning a single *Parameter* to a single *Cache Group*

Array Format For making multiple assignments of *Parameters* to *Cache Groups* simultaneously

Single Object Format

cacheGroupId An integer that is the *ID* of the *Cache Group* to which a *Parameter* is being assigned

parameterId An integer that is the *ID* of the *Parameter* being assigned

185: Request Example

```
POST /api/2.0/cachegrouponparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 39
Content-Type: application/json

{
  "cacheGroupId": 8,
  "parameterId": 124
}
```

Array Format

cacheGroupId An integer that is the *ID* of the *Cache Group* to which a *Parameter* is being assigned

parameterId An integer that is the *ID* of the *Parameter* being assigned

186: Request Example

```
POST /api/2.0/cachegrouponparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 39
Content-Type: application/json

[
  {
    "cacheGroupId": 8,
    "parameterId": 124
  },
  {
    "cacheGroupId": 8,
    "parameterId": 125
  }
]
```

Response Structure

cacheGroupId An integer that is the *ID* of the *Cache Group* to which a *Parameter* has been assigned

parameterId An integer that is the *ID* of the *Parameter* which has been assigned

187: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 15:47:49 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: wCv388wFaSjgFLCnI9dchlcyGxaVr8IhBAG25F+rpI2/
→azCswEYTcVBSlYOg6NxTQRzGkluMvn67jI6rV+vNsQ==
Content-Length: 136

{ "alerts": [
  {
    "level": "success",
    "text": "Cachegroup parameter associations were created."
  }
],
"response": [
  {
    "cacheGroupId": 8,
    "parameterId": 124
  }
]}
```

`cachegroupparameters/{ID}/{parameterID}`

Deprecated since version ATCv6.

DELETE

Dissociate a *Parameter* with a *Cache Group*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 97: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Cache Group</i> which will have the <i>Parameter</i> association deleted
parameterID	The <i>ID</i> of the <i>Parameter</i> which will be removed from a <i>Cache Group</i>

188: Request Example

```
DELETE /api/2.0/cachegroupparameters/8/124 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

189: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 18:26:40 GMT
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: CuJ+ZPAKsDLp4FpbJDCwsWY0yVQAI1Um1CWraeTIQEMlyJSBEm17oKQWDjzTrvqqV8Prhu3gzlcHoVPzE
Content-Length: 84

{ "alerts": [
  {
    "level": "success",
    "text": "cachegroup parameter was deleted."
  }
]}
```

cachegroups

GET

Extract information about *Cache Groups*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 98: Request Query Parameters

Name	Required	Description
id	no	Return the only <i>Cache Group</i> that has this id
type	no	Return only <i>Cache Groups</i> that are of the <i>Type</i> identified by this integral, unique identifier
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

190: Request Example

```
GET /api/2.0/cachegroups?type=23 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

fallbacks An array of strings that are *Cache Group names* that are registered as *Fallbacks* for this *Cache Group*¹

fallbackToClosest A boolean value that defines the *Fallback to Closest* behavior of this *Cache Group*^{Page 368, 1}

id An integer that is the *ID* of the *Cache Group*

lastUpdated The time and date at which this entry was last updated in *Traffic Ops's Custom Date/Time Format*

latitude A floating-point *Latitude* for the *Cache Group*

localizationMethods An array of *Localization Methods* as strings

longitude A floating-point *Longitude* for the *Cache Group*

name A string containing the *Name* of the *Cache Group*

parentCachegroupId An integer that is the *ID* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

parentCachegroupName A string containing the *Name* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

secondaryParentCachegroupId An integer that is the *ID* of this *Cache Group's Secondary Parent* - or null if it doesn't have a *Secondary Parent*

secondaryParentCachegroupName A string containing the *Name* of this *Cache Group's Secondary Parent Cache Group* - or null if it doesn't have a *Secondary Parent*

shortName A string containing the *Short Name* of the *Cache Group*

typeId An integral, unique identifier for the 'Type' of the *Cache Group*

typeName A string that names the *Type* of this *Cache Group*

¹ Traffic Router will first check for a *fallbacks* array and, when that is empty/unset/all the *Cache Groups* in it are also unavailable, will subsequently check for *fallbackToClosest*. If that is *true*, then it falls back to the geographically closest *Cache Group* capable of serving the same content or, when it is *false*/no such *Cache Group* exists/said *Cache Group* is also unavailable, will respond to clients with a failure response indicating the problem.

Note: The default value of `fallbackToClosest` is 'true', and if it is 'null' Traffic Control components will still interpret it as 'true'.

191: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳oV6ifEgoFy+v049tVjSsRdWQf4bxjrUvIYfDdgpUtlxiC7gzCv31m5bXQ8EUBW4eg2hfYM+BsGvJpnNDZ
X-Server-Name: traffic_ops_golang/
Date: Wed, 07 Nov 2018 19:46:36 GMT
Content-Length: 379

{ "response": [
  {
    "id": 7,
    "name": "CDN_in_a_Box_Edge",
    "shortName": "ciabEdge",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "parentCachegroupName": "CDN_in_a_Box_Mid",
    "parentCachegroupId": 6,
    "secondaryParentCachegroupName": null,
    "secondaryParentCachegroupId": null,
    "fallbackToClosest": [],
    "localizationMethods": [],
    "typeName": "EDGE_LOC",
    "typeId": 23,
    "lastUpdated": "2018-11-07 14:45:43+00",
    "fallbacks": []
  }
]}
```

POST

Creates a *Cache Group*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

fallbacks An optional field which, when present, should contain an array of strings that are the *Names* of other *Cache Groups* which will be the *Fallbacks*^{Page 368, 1}

fallbackToClosest A boolean that sets the *Fallback to Closest* behavior of the *Cache Group*^{Page 368, 1}

Note: The default value of `fallbackToClosest` is `true`, and if it is `null` Traffic Control components will still interpret it as though it were `true`.

latitude An optional field which, if present, should be a floating-point number that will define the *Latitude* for the *Cache Group*²

localizationMethods Array of *Localization Methods* (as strings)

Tip: This field has no defined meaning if the *Type* identified by `typeId` is not “EDGE_LOC”.

longitude An optional field which, if present, should be a floating-point number that will define the *Longitude* for the *Cache Group*[?]

name The *Name* of the *Cache Group*

parentCachegroupId An optional field which, if present, should be an integer that is the *ID* of a *Parent* for this *Cache Group*.

secondaryParentCachegroupId An optional field which, if present, should be an integral, unique identifier for this *Cache Group*’s secondary parent

shortName An abbreviation of the name

typeId An integral, unique identifier for the *Cache Group*’s *Type*

Note: The actual, integral, unique identifiers for these *Types* must first be obtained, generally via *types*.

² While these fields are technically optional, note that if they are not specified many things may break. For this reason, Traffic Portal requires them when creating or editing *Cache Groups*.

192: Request Example

```
POST /api/2.0/cachegroups HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 252
Content-Type: application/json

{
  "name": "test",
  "shortName": "test",
  "latitude": 0,
  "longitude": 0,
  "fallbackToClosest": true,
  "localizationMethods": [
    "DEEP_CZ",
    "CZ",
    "GEO"
  ],
  "typeId": 23,
}
```

Response Structure

fallbacks An array of strings that are *Cache Group names* that are registered as *Fallbacks* for this *Cache Group*^{Page 368, 1}

fallbackToClosest A boolean value that defines the *Fallback to Closest* behavior of this *Cache Group*^{Page 368, 1}

id An integer that is the *ID* of the *Cache Group*

lastUpdated The time and date at which this entry was last updated in *Traffic Ops's Custom Date/Time Format*

latitude A floating-point *Latitude* for the *Cache Group*

localizationMethods An array of *Localization Methods* as strings

longitude A floating-point *Longitude* for the *Cache Group*

name A string containing the *Name* of the *Cache Group*

parentCachegroupId An integer that is the *ID* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

parentCachegroupName A string containing the *Name* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

secondaryParentCachegroupId An integer that is the *ID* of this *Cache Group*'s *Secondary Parent* - or null if it doesn't have a *Secondary Parent*

secondaryParentCachegroupName A string containing the *Name* of this *Cache Group*'s *Secondary Parent Cache Group* - or null if it doesn't have a *Secondary Parent*

shortName A string containing the *Short Name* of the *Cache Group*

typeId An integral, unique identifier for the '*Type*' of the *Cache Group*

typeName A string that names the *Type* of this *Cache Group*

193: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳YvZlh3rpf13nBq6SbNVhbkt3IvckbB9amqGW2JhLxWK9K3cxjBq5JJ2sIHB UhrLKUhE9afpxtvaYrLRxjt
    ↳YMQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 07 Nov 2018 22:11:50 GMT
Content-Length: 379

{ "alerts": [
  {
    "text": "cachegroup was created.",
    "level": "success"
  }
],
"response": {
  "id": 8,
  "name": "test",
  "shortName": "test",
  "latitude": 0,
  "longitude": 0,
  "parentCachegroupName": null,
  "parentCachegroupId": null,
  "secondaryParentCachegroupName": null,
  "secondaryParentCachegroupId": null,
  "fallbackToClosest": true,
  "localizationMethods": [
    "DEEP_CZ",
```

(continues on next page)

(continued from previous page)

```

        "CZ",
        "GEO"
    ],
    "typeName": "EDGE_LOC",
    "typeId": 23,
    "lastUpdated": "2019-12-02 22:21:08+00",
    "fallbacks": []
  }}

```

cachegroups/{ID}

PUT

Update *Cache Group*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 99: Request Path Parameters

Parameter	Description
ID	The <i>ID</i> of a <i>Cache Group</i>

fallbacks An optional field which, when present, should contain an array of strings that are the *Names* of other *Cache Groups* which will be the *Fallbacks*¹

fallbackToClosest A boolean that sets the *Fallback to Closest* behavior of the *Cache Group*^{Page 368, 1}

Note: The default value of `fallbackToClosest` is `true`, and if it is `null` Traffic Control components will still interpret it as though it were `true`.

latitude An optional field which, if present, should be a floating-point number that will define the *Latitude* for the *Cache Group*²

¹ Traffic Router will first check for a `fallbacks` array and, when that is empty/unset/all the *Cache Groups* in it are also unavailable, will subsequently check for `fallbackToClosest`. If that is `true`, then it falls back to the geographically closest *Cache Group* capable of serving the same content or, when it is `false`/no such *Cache Group* exists/said *Cache Group* is also unavailable, will respond to clients with a failure response indicating the problem.

² While these fields are technically optional, note that if they are not specified many things may break. For this reason, Traffic Portal requires them when creating or editing *Cache Groups*.

localizationMethods Array of *Localization Methods* (as strings)

Tip: This field has no defined meaning if the *Type* identified by typeId is not “EDGE_LOC”.

longitude An optional field which, if present, should be a floating-point number that will define the *Longitude* for the *Cache Group*?

name The *Name* of the *Cache Group*

parentCachegroupId An optional field which, if present, should be an integer that is the *ID* of a *Parent* for this *Cache Group*.

secondaryParentCachegroupId An optional field which, if present, should be an integral, unique identifier for this *Cache Group*’s secondary parent

shortName An abbreviation of the name

typeId An integral, unique identifier for the *Cache Group*’s *Type*

Note: The actual, integral, unique identifiers for these *Types* must first be obtained, generally via *types*.

194: Request Example

```
PUT /api/2.0/cachegroups/8 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 118
Content-Type: application/json

{
  "latitude": 0.0,
  "longitude": 0.0,
  "name": "test",
  "fallbacks": [],
  "fallbackToClosest": true,
  "shortName": "test",
  "typeId": 23,
  "localizationMethods": ["GEO"]
}
```

Response Structure

fallbacks An array of strings that are *Cache Group names* that are registered as *Fallbacks* for this *Cache Group*^{Page 368, 1}

fallbackToClosest A boolean value that defines the *Fallback to Closest* behavior of this *Cache Group*^{Page 368, 1}

id An integer that is the *ID* of the *Cache Group*

lastUpdated The time and date at which this entry was last updated in *Traffic Ops's Custom Date/Time Format*

latitude A floating-point *Latitude* for the *Cache Group*

localizationMethods An array of *Localization Methods* as strings

longitude A floating-point *Longitude* for the *Cache Group*

name A string containing the *Name* of the *Cache Group*

parentCachegroupId An integer that is the *ID* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

parentCachegroupName A string containing the *Name* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

secondaryParentCachegroupId An integer that is the *ID* of this *Cache Group's Secondary Parent* - or null if it doesn't have a *Secondary Parent*

secondaryParentCachegroupName A string containing the *Name* of this *Cache Group's Secondary Parent Cache Group* - or `null` if it doesn't have a *Secondary Parent*

shortName A string containing the *Short Name* of the *Cache Group*

typeId An integral, unique identifier for the '*Type*' of the *Cache Group*

typeName A string that names the *Type* of this *Cache Group*

195: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: t1W65/2kj25QyHt0Ib0xpBaAR2sXu2k0sRZ49WjKZp/
    ↳AK5S1YWhX7VNWCUUGiN1VNM4QRNqODC/7ewhYDFUncA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 19:14:28 GMT
Content-Length: 385

{ "alerts": [
  {
    "text": "cachegroup was updated.",
    "level": "success"
  }
],
"response": {
  "id": 8,
  "name": "test",
  "shortName": "test",
  "latitude": 0,
  "longitude": 0,
  "parentCachegroupName": null,
  "parentCachegroupId": null,
  "secondaryParentCachegroupName": null,
  "secondaryParentCachegroupId": null,
  "fallbacks": [],
  "fallbackToClosest": true,
  "localizationMethods": [
    "GEO"
  ],
  "typeName": "EDGE_LOC",
```

(continues on next page)

(continued from previous page)

```
"typeId": 23,
"lastUpdated": "2018-11-14 19:14:28+00"
}}
```

DELETE

Delete a *Cache Group*. A *Cache Group* which has assigned servers or is the *Parent* of one or more other *Cache Groups* cannot be deleted.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 100: Request Path Parameters

Parameter	Description
ID	The <i>ID</i> of a <i>Cache Group</i> to be deleted

196: Request Example

```
DELETE /api/2.0/cacheGroups/42 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

197: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 5jZBg07h1eNF70J/cmlbi3Hf9KJPx+WLMb1H/pSKF3FWb/
→10GUHIN35ZOB+1N5LZYCkmk3izGbTFkiruG8I41Q==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:31:04 GMT
Content-Length: 57

{ "alerts": [
  {
    "text": "cachegroup was deleted.",
    "level": "success"
  }
]}
```

cachegroups/{{ID}}/deliveryservices

POST

Assigns all of the “assignable” servers within a *Cache Group* to one or more *Delivery Services*.

Note: “Assignable” here means all of the *Cache Group’s servers* that have a *Type* that matches one of the glob patterns `EDGE*` or `ORG*`. If even one server of any *Type* exists within the *Cache Group* that is not assigned to the same CDN as the *Delivery Service* to which an attempt is being made to assign them, the request will fail.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

deliveryServices The integral, unique identifiers of the *Delivery Services* to which the *Cache Group’s servers* are being assigned

198: Request Example

```
POST /api/2.0/cachegroups/8/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 25
Content-Type: application/json

{"deliveryServices": [2]}
```

Response Structure

deliveryServices An array of integral, unique identifiers for *Delivery Services* to which the *Cache Group's servers* have been assigned

id An integer that is the *Cache Group's ID*

serverNames An array of the (short) hostnames of all of the *Cache Group's* “assignable” *Servers*

199: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: j/yH0gvJoaGjiLZU/
→0MA8o5He2004aJ5wh1eF9ex6F6IB01liM9Wk9RkWCw7sdiUHoy13/
→mf7gDntisZwzP7yw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 19:54:17 GMT
Content-Length: 183

{ "alerts": [
  {
    "text": "Delivery services successfully assigned to all the
→servers of cache group 8.",
    "level": "success"
  }
],
"response": {
  "id": 8,
  "serverNames": [
    "foo"
  ],
  "deliveryServices": [
    2
  ]
}}
```

cachegroups/{ID}/parameters

Deprecated since version ATCv6.

GET

Gets all of a *Cache Group's parameters*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 101: Request Query Parameters

Name	Re-quired	Description
pa-ram-e-terId	no	Show only the <i>Parameter</i> with the given <i>ID</i>
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
off-set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page .

Table 102: Request Path Parameters

Parameter	Description
ID	The <i>ID</i> of a <i>Cache Group</i>

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name of the Parameter*

secure A boolean value describing whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

200: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 19:56:23 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: DfqPtySzVMpnBYqVt/45sSRG/
    ↳1pRTlQdIcYuQZ0CQt79QSHLzU5e4TbDqht6ntvNP041LimKsj5RzPlPX1n6tg==
Content-Length: 135

{ "response": [
  {
    "lastUpdated": "2018-11-14 18:22:43.754786+00",
    "value": "foobar",
    "secure": false,
    "name": "foo",
    "id": 124,
    "configFile": "bar"
  }
]}
```

cachegroups/{ID}/queue_update

POST

Queue or “dequeue” updates for all of a *Cache Group’s servers*, limited to a specific CDN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 103: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Cache Group</i> for which updates are being <i>Queued</i> /dequeued

action The action to perform; one of “queue” or “dequeue”

cdn The full name of the CDN in need of *Queue Updates*, or a “dequeue” thereof¹

cdnId The integral, unique identifier for the CDN in need of *Queue Updates*, or a “dequeue” thereof^{Page 368, 1}

201: Request Example

```
POST /api/2.0/cachegroups/8/queue_update HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 42
Content-Type: application/json

{"action": "queue", "cdn": "CDN-in-a-Box"}
```

Response Structure

action The action processed, one of “queue” or “dequeue”

cachegroupId An integer that is the *ID* of the *Cache Group* for which *Queue Updates* was performed or cleared

cachegroupName The name of the *Cache Group* for which updates were queued/dequeued

cdn The name of the CDN to which the queue/dequeue operation was restricted

¹ Either ‘cdn’ or ‘cdnID’ *must* be in the request data (but not both).

serverNames An array of the (short) hostnames of the *Cache Group's servers* which are also assigned to the CDN specified in the "cdn" field

202: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳UAcP7LrflU1RnfR4UqbQrJczlk5rkrcLOtTXJTFvIUxxK1Ek1ZkHkE4vewjDaVIhJJ6YQg8jmPGQpr+x1
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:19:46 GMT
Content-Length: 115

{ "response": {
  "cachegroupName": "test",
  "action": "queue",
  "serverNames": [
    "foo"
  ],
  "cdn": "CDN-in-a-Box",
  "cachegroupID": 8
}}
```

caches/stats

An API endpoint that returns cache statistics using the *Traffic Monitor APIs*.

See also:

This gives a set of basic statistics for *all cache servers* at the current time. For statistics from time ranges and/or aggregated over a specific CDN, use *cache_stats*.

GET

Retrieves cache stats from Traffic Monitor. Also includes rows for aggregates.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

Response Structure

cachegroup A string that is the *Name* of the *Cache Group* to which this *cache server* belongs

connections Current number of TCP connections maintained by the *cache server*

healthy true if Traffic Monitor has marked the *cache server* as “healthy”, false otherwise

See also:

Health Protocol

hostname The (short) hostname of the *cache server*

ip The IP address of the *cache server*

kbps The *cache server*’s upload speed (to clients) in Kilobits per second

profile The *Name* of the *Profile* in use by this *cache server*

status The status of the *cache server*

203: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 20:25:01 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
↪GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Vary: Accept-Encoding
Whole-Content-Sha512: DqbLgitanS8q81/
→qKC1i+ImMiEMF+SW4G9rb79FWdeWcgwFjL810t1TRp1nNNfHV+tajgjyK+wMHobqVyaNEfA==
Content-Length: 133

{ "response": [
  {
    "profile": "ALL",
    "connections": 0,
    "ip": null,
    "status": "ALL",
    "healthy": true,
    "kbps": 0,
    "hostname": "ALL",
    "cachegroup": "ALL"
  }
]}
```

capabilities

GET

Get all capabilities.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 104: Request Query Parameters

Name	Re-quired	Description
name	no	Return only the capability that has this name
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

204: Request Example

```
GET /api/2.0/capabilities?name=test HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

name Name of the capability

description Describes the permissions covered by the capability.

lastUpdated Date and time of the last update made to this capability, in *Traffic Ops’s Custom Date/Time Format*

205: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Vary: Accept-Encoding
Transfer-Encoding: chunked
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: c18+GtX2ZI8PoCSwuAzBhl+6w3vDpKQTa/
→cDJC0WHxdpguOL378KBxGWW5PCSyZfJUUb7wPyOL5qKMn6NNTufhg==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Aug 2019 17:20:20 GMT
Content-Length: 161

{ "response": [
  {
    "description": "This is only a test. If this were a real_
→capability, it might do something",
    "lastUpdated": "2019-08-15 17:18:03+00",
    "name": "test"
  }
]}
```

cdns

Extract information about all CDNs

GET

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 105: Request Query Parameters

Parameter	Required	Description
domainName	no	Return only the CDN that has this domain name
dnssecEnabled	no	Return only the CDNs that are either dnssec enabled or not
id	no	Return only the CDN that has this id
name	no	Return only the CDN that has this name
orderBy	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Response Structure

dnssecEnabled true if DNSSEC is enabled on this CDN, otherwise false

domainName Top Level Domain name within which this CDN operates

id The integral, unique identifier for the CDN

lastUpdated Date and time when the CDN was last modified in *Traffic Ops’s Custom Date/Time Format*

name The name of the CDN

206: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→z9P1NkxGebPncUhaChDHtYKYI+XVZfhE6Y84TuwoASZFIMfISELwADLpvpPTN+wwnzBfREksLYn+0313Q
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:46:57 GMT
Content-Length: 237

{ "response": [
  {
    "dnssecEnabled": false,
    "domainName": "-",
    "id": 1,
    "lastUpdated": "2018-11-14 18:21:06+00",
    "name": "ALL"
  },
  {
    "dnssecEnabled": false,
    "domainName": "mycdn.ciab.test",
    "id": 2,
    "lastUpdated": "2018-11-14 18:21:14+00",
    "name": "CDN-in-a-Box"
  }
]}

```

POST

Allows user to create a CDN

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

dnssecEnabled If true, this CDN will use DNSSEC, if false it will not

domainName The top-level domain (TLD) belonging to the new CDN

name Name of the new CDN

207: Request Structure

```
POST /api/2.0/cdns HTTP/1.1
Host: trafficops.infra.ciab.test

```

(continues on next page)

(continued from previous page)

```
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 63
Content-Type: application/json

{"name": "test", "domainName": "quest", "dnssecEnabled": false}
```

Response Structure

dnssecEnabled true if the CDN uses DNSSEC, false otherwise

domainName The top-level domain (TLD) assigned to the newly created CDN

id An integral, unique identifier for the newly created CDN

name The newly created CDN's name

208: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→1rZRL0fQioGRrEb4nCfjGGx7y3Ub2h7BZ4z6NbhcY4acPslKSUNM8QLjWTVwLU4WpkfJNxc0oy8NlKULF
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:49:28 GMT
Content-Length: 174

{ "alerts": [
  {
    "text": "cdn was created.",
    "level": "success"
  }
],
"response": {
  "dnssecEnabled": false,
  "domainName": "quest",
  "id": 3,
  "lastUpdated": "2018-11-14 20:49:28+00",
```

(continues on next page)

(continued from previous page)

```
"name": "test"
}}
```

cdns/capacity

GET

Retrieves the aggregate capacity percentages of all *Cache Groups* for a given CDN.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

availablePercent The percent of available (unused) bandwidth to 64 bits of precision¹

unavailablePercent The percent of unavailable (used) bandwidth to 64 bits of precision¹

utilizedPercent The percent of bandwidth currently in use to 64 bits of precision¹

maintenancePercent The percent of bandwidth being used for administrative or analytical processes internal to the CDN to 64 bits of precision¹

209: Response Example

```
{ "response": {
  "availablePercent": 89.0939840205533,
  "unavailablePercent": 0,
  "utilizedPercent": 10.9060020300395,
  "maintenancePercent": 0.0000139494071146245
}}
```

¹ Following IEEE 754

cdns/dnsseckey/generate

POST

Generates ZSK and KSK keypairs for a CDN and all associated *Delivery Services*.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

effectiveDate An optional string containing the date and time at which the newly-generated ZSK and KSK become effective, in **RFC 3339** format. Defaults to the current time if not specified.

key Name of the CDN

kskExpirationDays Expiration (in days) for the KSKs (Key-Signing Keys)

ttl Time, in seconds, for which the keypairs shall remain valid

zskExpirationDays Expiration (in days) for the ZSKs (Zone-Signing Keys)

210: Request Example

```
POST /api/2.0/cdns/dnsseckey/generate HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 130

{
  "key": "CDN-in-a-Box",
  "kskExpirationDays": 1095,
  "ttl": 3600,
  "zskExpirationDays": 1095
}
```

Response Structure

211: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 19:42:15
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 09SPWzeMNFgg6I/PPeXittBIhdh3/
  ↳zUKK1NwNlYIM9SszSrK0h/Dfz7tnwgnA7h/s6M4eYBJxykDpCfVC7xpeg==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 18:42:15 GMT
Content-Length: 89

{
  "response": "Successfully created dnssec keys for CDN-in-a-Box"
}
```

cdns/dnsseckey/refresh

GET

Refresh the DNSSEC keys for all CDNs. This call initiates a background process to refresh outdated keys, and immediately returns a response that the process has started.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

No parameters available

Response Structure

212: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 21:37:30 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
  ↳Uw1+924m6Ye3NraFP+RBp1dkhcNTTDyXHZbzRaYV95p9tP56Z61gcKeKSr1oQIkNXjXcCsDN5Dmum7Zk1
Content-Length: 69

{
  "response": "Checking DNSSEC keys for refresh in the background"
}
```

cdns/domains

GET

Gets a list of domains and their related Traffic Router *Profiles* for all CDNs.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

Response Structure

domainName The TLD assigned to this CDN

parameterId The *ID* for the *Parameter* that sets this TLD on the Traffic Router

profileDescription A short, human-readable description of the Traffic Router's profile

profileId The *ID* of the *Profile* assigned to the Traffic Router responsible for serving domainName

profileName The *Name* of the *Profile* assigned to the Traffic Router responsible for serving domainName

213: Response Example

```
{ "response": [
  {
    "profileId": 12,
    "parameterId": -1,
    "profileName": "CCR_CIAB",
    "profileDescription": "Traffic Router for CDN-In-A-Box",
    "domainName": "mycdn.ciab.test"
  }
]}
```

cdns/health

Extract health information from all *Cache Groups* across all CDNs

See also:

Health Protocol

GET

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available

Response Structure

cachegroups An array of objects describing the health of each Cache Group

name The name of the Cache Group

offline The number of OFFLINE caches in the Cache Group

online The number of ONLINE caches in the Cache Group

totalOffline Total number of OFFLINE caches across all Cache Groups which are assigned to any CDN

totalOnline Total number of ONLINE caches across all Cache Groups which are assigned to any CDN

214: Response Example

```
{ "response": {
  "totalOffline": 0,
  "totalOnline": 1,
  "cachegroups": [
    {
      "offline": 0,
      "name": "CDN_in_a_Box_Edge",
      "online": 1
    }
  ]
}}
```

`cdns/{ID}`

PUT

Allows a user to edit a specific CDN

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 106: Request Path Parameters

Name	Description
ID	Integral, unique identifier for the CDN to update

dnssecEnabled If `true`, this CDN will use DNSSEC, if `false` it will not

domainName The top-level domain (TLD) belonging to the CDN

name Name of the new CDN

215: Request Example

```
PUT /api/2.0/cdns/3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 63
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
```

```
{"name": "quest", "domainName": "test", "dnssecEnabled": false}
```

Response Structure

dnssecEnabled true if the CDN uses DNSSEC, false otherwise

domainName The top-level domain (TLD) assigned to the newly created CDN

id An integral, unique identifier for the newly created CDN

name The newly created CDN's name

216: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: sI1hzBwG+/
    ↳VAzoFY20kqGFA2RgrU0ThtMeeJqk0ZxH3TRxTWuA8BetACct/
    ↳XICC3n7hPDLlRVpwckEyBdyJkXg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:54:33 GMT
Content-Length: 174

{ "alerts": [
  {
    "text": "cdn was updated.",
    "level": "success"
  }
],
"response": {
  "dnssecEnabled": false,
  "domainName": "test",
  "id": 4,
  "lastUpdated": "2018-11-14 20:54:33+00",
  "name": "quest"
}}
```

DELETE

Allows a user to delete a specific CDN

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 107: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the CDN to delete

Response Structure

217: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Zy4cJN6BEct4ltFLN4e296mM8XnzOs0EQ3/
    ↳jp4TA3L+g8qtkI0WrL+ThcFq4xbJPU+KHVDSi+b0JBav3xsYPqQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:51:23 GMT
Content-Length: 58

{ "alerts": [
  {
    "text": "cdn was deleted.",
    "level": "success"
  }
]}
```

cdns/{ID}/queue_update

POST

Queue or “dequeue” updates for all servers assigned to a specific CDN.

- Auth. Required** Yes
- Roles Required** “admin” or “operations”
- Response Type** Object

Request Structure

Table 108: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the CDN on which to (de)queue updates

action One of “queue” or “dequeue” as appropriate

218: Request Example

```
POST /api/2.0/cdns/2/queue_update HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 19
Content-Type: application/json

{"action": "queue"}
```

Response Structure

- action** The action processed, either "queue" or "dequeue"
- cdnId** The integral, unique identifier for the CDN on which *Queue Updates* was performed or cleared

219: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→rBpFfrrP+9IFkwsRloEM+v+I8MuBZDXqFu+WUTGtRGypnAn2gHooPoNQRYVvJGjyIQrLXLvqjEtve+lH2
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:02:07 GMT
Content-Length: 41

{ "response": {
  "action": "queue",
  "cdnId": 2
}}
```

`cdns/{{name}}/configs/monitoring`

See also:

Health Protocol

GET

Retrieves information concerning the monitoring configuration for a specific CDN.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 109: Request Path Parameters

Name	Description
name	The name of the CDN for which monitoring configuration will be fetched

Response Structure

cacheGroups An array of objects representing each of the *Cache Groups* being monitored within this CDN

coordinates An object representing the geographic location of this *Cache Group*

latitude This *Cache Group's latitude* as a floating-point number

longitude This *Cache Group's longitude* as a floating-point number

name A string that is this *Cache Group's name*

config A collection of parameters used to configure the monitoring behaviour of Traffic Monitor

health.polling.interval An interval in milliseconds on which to poll for health statistics

tm.polling.interval The interval at which to poll for configuration updates

deliveryServices An array of objects representing each *Delivery Service* provided by this CDN

status The *Delivery Service's* status

totalKbpsThreshold A threshold rate of data transfer this *Delivery Service* is configured to handle, in Kilobits per second

totalTpsThreshold A threshold amount of transactions per second that this *Delivery Service* is configured to handle

xmlId A string that is the *Delivery Service's XMLID*

profiles An array of the *Profiles* in use by the *cache servers* and *Delivery Services* belonging to this CDN

name A string that is the *Profile's Name*

parameters An array of the *Parameters* in this *Profile* that relate to monitoring configuration. This can be null if the servers using this *Profile* cannot be monitored (e.g. Traffic Routers)

health.connection.timeout A timeout value, in milliseconds, to wait before giving up on a health check request

health.polling.url A URL to request for polling health. Substitutions can be made in a shell-like syntax using

the properties of an object from the "trafficServers" array

health.threshold.availableBandwidthInKbps

The total amount of bandwidth that servers using this profile are allowed, in Kilobits per second. This is a string and using comparison operators to specify ranges, e.g. ">10" means "more than 10 kbps"

health.threshold.loadavg The UNIX load-avg at which the server should be marked "unhealthy"

See also:

uptime(1)

health.threshold.queryTime The highest allowed length of time for completing health queries (after connection has been established) in milliseconds

history.count The number of past events to store; once this number is reached, the oldest event will be forgotten before a new one can be added

type A string that names the *Profile's Type*

trafficMonitors An array of objects representing each Traffic Monitor that monitors this CDN (this is used by Traffic Monitor's "peer polling" function)

fqdn An FQDN that resolves to the IPv4 (and/or IPv6) address of the server running this Traffic Monitor instance

hostname The hostname of the server running this Traffic Monitor instance

ip6 The IPv6 address of this Traffic Monitor - when applicable

ip The IPv4 address of this Traffic Monitor

port The port on which this Traffic Monitor listens for incoming connections

profile A string that is the *Name* of the *Profile* assigned to this Traffic Monitor

status The status of the server running this Traffic Monitor instance

trafficServers An array of objects that represent the *cache servers* being monitored within this CDN

- cacheGroup** The *Cache Group* to which this *cache server* belongs
- fqdn** An FQDN that resolves to the *cache server*'s IPv4 (or IPv6) address
- hashId** The (short) hostname for the *cache server* - named "hashId" for legacy reasons
- hostName** The (short) hostname of the *cache server*
- interfacename** The name of the network interface device being used by the *cache server*'s HTTP proxy
- ip6** The *cache server*'s IPv6 address - when applicable
- ip** The *cache server*'s IPv4 address
- port** The port on which the *cache server* listens for incoming connections
- profile** A string that is the *Name* of the *Profile* assigned to this *cache server*
- status** The status of the *cache server*
- type** A string that names the *Type* of the *cache server* - should (ideally) be either EDGE or MID

220: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳uLR+tRoqR8SY038j3DV9wQ+IkJ7Kf+MCoFkcWZtsgbpLJ+0S6f+IiI8laNVeDgrM/
    ↳P23MAQ6BSepm+EJRl1AXQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:09:31 GMT
Transfer-Encoding: chunked

{ "response": {
  "trafficServers": [
    {
      "profile": "ATS_EDGE_TIER_CACHE",
      "status": "REPORTED",
      "ip": "172.16.239.100",

```

(continues on next page)

(continued from previous page)

```

        "ip6": "fc01:9400:1000:8::100",
        "port": 80,
        "cachegroup": "CDN_in_a_Box_Edge",
        "hostname": "edge",
        "fqdn": "edge.infra.ciab.test",
        "interfacename": "eth0",
        "type": "EDGE",
        "hashid": "edge"
    },
    {
        "profile": "ATS_MID_TIER_CACHE",
        "status": "REPORTED",
        "ip": "172.16.239.120",
        "ip6": "fc01:9400:1000:8::120",
        "port": 80,
        "cachegroup": "CDN_in_a_Box_Mid",
        "hostname": "mid",
        "fqdn": "mid.infra.ciab.test",
        "interfacename": "eth0",
        "type": "MID",
        "hashid": "mid"
    }
],
"trafficMonitors": [
    {
        "profile": "RASCAL-Traffic_Monitor",
        "status": "ONLINE",
        "ip": "172.16.239.40",
        "ip6": "fc01:9400:1000:8::40",
        "port": 80,
        "cachegroup": "CDN_in_a_Box_Edge",
        "hostname": "trafficmonitor",
        "fqdn": "trafficmonitor.infra.ciab.test"
    }
],
"cacheGroups": [
    {
        "name": "CDN_in_a_Box_Mid",
        "coordinates": {
            "latitude": 38.897663,
            "longitude": -77.036574
        }
    },
    {
        "name": "CDN_in_a_Box_Edge",
        "coordinates": {

```

(continues on next page)

(continued from previous page)

```

        "latitude": 38.897663,
        "longitude": -77.036574
    }
}
],
"profiles": [
    {
        "name": "CCR_CIAB",
        "type": "CCR",
        "parameters": null
    },
    {
        "name": "ATS_EDGE_TIER_CACHE",
        "type": "EDGE",
        "parameters": {
            "health.connection.timeout": 2000,
            "health.polling.url": "http://${hostname}/_astats?
→application=&inf.name=${interface_name}",
            "health.threshold.availableBandwidthInKbps": ">1750000
→",
            "health.threshold.loadavg": "25.0",
            "health.threshold.queryTime": 1000,
            "history.count": 30
        }
    },
    {
        "name": "ATS_MID_TIER_CACHE",
        "type": "MID",
        "parameters": {
            "health.connection.timeout": 2000,
            "health.polling.url": "http://${hostname}/_astats?
→application=&inf.name=${interface_name}",
            "health.threshold.availableBandwidthInKbps": ">1750000
→",
            "health.threshold.loadavg": "25.0",
            "health.threshold.queryTime": 1000,
            "history.count": 30
        }
    }
]
},
"deliveryServices": [],
"config": {
    "health.polling.interval": 6000,
    "heartbeat.polling.interval": 3000,
    "peers.polling.interval": 3000,
    "tm.polling.interval": 2000
}

```

(continues on next page)

(continued from previous page)

```
}  
}}
```

`cdns/{{name}}/dnsseckey/ksk/generate`

POST

Generates a new KSK for a specific CDN.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

Table 110: Request Path Parameters

Name	Required	Description
name	yes	The name of the CDN for which the KSK will be generated

expirationDays The integral number of days until the newly generated KSK expires

effectiveDate An optional string containing the date and time at which the newly generated KSK becomes effective, in **RFC 3339** format. Defaults to the current time if not specified

Response Structure

221: Response Example

```
{ "response": "Successfully generated ksk dnssec keys for my-cdn-name" }
```

`cdns/{{name}}/federations`

GET

Retrieves a list of federations in use by a specific CDN.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 111: Request Path Parameters

Name	Description
name	The name of the CDN for which federations will be listed

Table 112: Request Query Parameters

Name	Description
id	Return only the federation that has this id
orderby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

222: Request Example

```
GET /api/2.0/cdns/CDN-in-a-Box/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

cname The Canonical Name (CNAME) used by the federation

deliveryService An object with keys that provide identifying information for the *Delivery Service* using this federation

id The integral, unique identifier for the *Delivery Service*

xmlId The *Delivery Service*’s uniquely identifying ‘xml_id’

description An optionally-present field containing a description of the field

Note: This key will only be present if the description was provided when the federation was created. Refer to the POST method of this endpoint to see

how federations can be created.

lastUpdated The date and time at which this federation was last modified, in *Traffic Ops's Custom Date/Time Format*

ttl Time to Live (TTL) for the cname, in hours

223: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
→SJA7G+7G5KcOfCtnE3Dq5DCobWtGRUKSppiDkflZoG5+paq4E1aZGqUb6vGVsd+TpPg75MLlhyqfdfCHnl
→g==
x-server-name: traffic_ops_golang/
content-length: 170
date: Wed, 05 Dec 2018 00:35:40 GMT

{ "response": [
  {
    "id": 1,
    "cname": "test.quest.",
    "ttl": 48,
    "description": "A test federation",
    "lastUpdated": "2018-12-05 00:05:16+00",
    "deliveryService": {
      "id": 1,
      "xmlId": "demo1"
    }
  }
]}
```

POST

Creates a new federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 113: Request Path Parameters

Name	Description
name	The name of the CDN for which a new federation will be created

cname The Canonical Name (CNAME) used by the federation

Note: The CNAME must end with a “.”

description An optional description of the federation

ttl Time to Live (TTL) for the name record used for **cname**

224: Request Example

```
POST /api/2.0/cdns/CDN-in-a-Box/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 72
Content-Type: application/json

{
  "cname": "test.quest.",
  "ttl": 48,
  "description": "A test federation"
}
```

Response Structure

cname The Canonical Name (CNAME) used by the federation

description An optionally-present field containing a description of the field

Note: This key will only be present if the description was provided when the federation was created

lastUpdated The date and time at which this federation was last modified, in *Traffic Ops's Custom Date/Time Format*

ttl Time to Live (TTL) for the **cname**, in hours

225: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
    ↳rRsWAIhXzVlj8Hy+8aFjp4Jo1QGTK49m0N1AP5QDyyAZ1TfNIdgtcgiuehu7FiN1IPWRFiv6D9CygFYKG
x-server-name: traffic_ops_golang/
content-length: 192
date: Wed, 05 Dec 2018 00:05:16 GMT

{ "alerts": [
  {
    "text": "cdnfederation was created.",
    "level": "success"
  }
],
"response": {
  "id": 1,
  "cname": "test.quest.",
  "ttl": 48,
  "description": "A test federation",
  "lastUpdated": "2018-12-05 00:05:16+00"
}}
```

cdns/{name}/federations/{ID}

PUT

Updates a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 114: Request Path Parameters

Name	Description
name	The name of the CDN for which the federation identified by ID will be inspected
ID	An integral, unique identifier for the federation to be inspected

cname The Canonical Name (CNAME) used by the federation

Note: The CNAME must end with a “.”

description An optional description of the federation

ttl Time to Live (TTL) for the name record used for **cname**

226: Request Example

```
PUT /api/2.0/cdns/CDN-in-a-Box/federations/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 33
Content-Type: application/json

{
  "cname": "foo.bar.",
  "ttl": 48
}
```

Response Structure

cname The Canonical Name (CNAME) used by the federation

description An optionally-present field containing a description of the field

Note: This key will only be present if the description was provided when the federation was created

lastUpdated The date and time at which this federation was last modified, in *Traffic Ops's Custom Date/Time Format*

ttl Time to Live (TTL) for the **cname**, in hours

227: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
    ↳qcjfQ+gDjNxYQ1aq+dlddgrkFWnkFYxsFF+SHDqqH0uVHBVksmU0aTFgltozek/
    ↳u6wbrGoR1LFf9Fr1C1SbigA==
x-server-name: traffic_ops_golang/
content-length: 174
date: Wed, 05 Dec 2018 01:03:40 GMT

{ "alerts": [
    {
        "text": "cdnfederation was updated.",
        "level": "success"
    }
],
"response": {
    "id": 1,
    "cname": "foo.bar.",
    "ttl": 48,
    "description": null,
    "lastUpdated": "2018-12-05 01:03:40+00"
}}
```

DELETE

Deletes a specific federation.

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 115: Request Path Parameters

Name	Description
name	The name of the CDN for which the federation identified by ID will be inspected
ID	An integral, unique identifier for the federation to be inspected

228: Request Example

```
DELETE /api/2.0/cdns/CDN-in-a-Box/federations/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

229: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512: Cnkfj6dmzTD3if9oiDq33tqf7CnAflKK/
→SPgqJyfu6HUf0jLJ0gKIZvkcs2wWY6EjLVdw5qsatsd4FPoCyjvcw==
x-server-name: traffic_ops_golang/
content-length: 68
date: Wed, 05 Dec 2018 01:17:24 GMT

{ "alerts": [
  {
    "text": "cdnfederation was deleted.",
    "level": "success"
  }
]}
```

`cdns/{{name}}/health`

GET

Retrieves the health of all *Cache Groups* for a given CDN.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 116: Request Path Parameters

Name	Description
name	The name of the CDN for which health will be reported

230: Request Example

```
GET /api/2.0/cdns/CDN-in-a-Box/health HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

cachegroups An array of objects describing the health of each *Cache Group*

name A string that is the *Cache Group's Name*

offline The number of OFFLINE *cache servers* in the *Cache Group*

online The number of ONLINE *cache servers* in the *Cache Group*

totalOffline Total number of OFFLINE *cache servers* across all *Cache Groups* which are assigned to the CDN defined by the name request path parameter

totalOnline Total number of ONLINE *cache servers* across all *Cache Groups* which are assigned to the CDN defined by the name request path parameter

231: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Encoding: gzip
Content-Length: 108
Content-Type: application/json
Date: Tue, 03 Dec 2019 21:33:59 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; expires=Wed, 04 Dec 2019 01:33:59 GMT;
    ↳path=/; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳KpXViXeAgch58ueQqdyU8NuINBw1EUedE6Rv2ewcLUajJp6kowdbVynpwW7XiSvAyHdtClIOuT30khImq

{ "response": {
  "totalOffline": 0,
  "totalOnline": 1,
  "cachegroups": [
    {
      "offline": 0,
      "name": "CDN_in_a_Box_Edge",
      "online": 1
    }
  ]
}}
```

`cdns/name/{name}}`

DELETE

Allows a user to delete a CDN by name

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 117: Request Path Parameters

Name	Description
name	The name of the CDN to be deleted

Response Structure

232: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Zy4cJN6BEct4ltFLN4e296mM8XnzOs0EQ3/
    ↳jp4TA3L+g8qtkI0WrL+ThcFq4xbJPU+KHVDSi+b0JBav3xsYPqQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:59:22 GMT
Content-Length: 58

{ "alerts": [
  {
    "text": "cdn was deleted.",
    "level": "success"
  }
]}
```

cdns/name/{{name}}/dnsseckey

GET

Gets a list of DNSSEC keys for CDN and all associated *Delivery Services*. Before returning response to user, this will make sure DNSSEC keys for all *Delivery Services* exist and are not expired. If they don't exist or are expired, they will be (re-)generated.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 118: Request Path Parameters

Name	Description
name	The name of the CDN for which keys will be fetched

Response Structure

name The name of the CDN or *Delivery Service* to which the enclosed keys belong

zsk The short-term ZSK

expirationDate A Unix epoch timestamp (in seconds) representing the date and time whereupon the key will expire

inceptionDate A Unix epoch timestamp (in seconds) representing the date and time when the key was created

name The name of the domain for which this key will be used

private Encoded private key

public Encoded public key

ttd The time for which the key should be trusted by the client

ksk The long-term KSK

dsRecord An optionally present object containing information about the algorithm used to generate the key

algorithm The name of the algorithm used to generate the key

digest A hash of the DNSKEY record

digestType The type of hash algorithm used to create the value of digest

expirationDate A Unix epoch timestamp (in seconds) representing the date and time whereupon the key will expire

inceptionDate A Unix epoch timestamp (in seconds) representing the date and time when the key was created

name The name of the domain for which this key will be used

private Encoded private key

public Encoded public key

ttl The time for which the key should be trusted by the client

233: Response Example

```
{ "response": {
  "cdn1": {
    "zsk": {
      "ttl": "60",
      "inceptionDate": "1426196750",
      "private": "zsk private key",
      "public": "zsk public key",
      "expirationDate": "1428788750",
      "name": "foo.kabletown.com."
    },
    "ksk": {
      "name": "foo.kabletown.com.",
      "expirationDate": "1457732750",
      "public": "ksk public key",
      "private": "ksk private key",
      "inceptionDate": "1426196750",
      "ttl": "60",
      "dsRecord": {
        "algorithm": "5",
        "digestType": "2",
        "digest": "abc123def456"
      }
    }
  },
  "ds-01": {
    "zsk": {
      "ttl": "60",
      "inceptionDate": "1426196750",
      "private": "zsk private key",
      "public": "zsk public key",
      "expirationDate": "1428788750",
      "name": "ds-01.foo.kabletown.com."
    },
    "ksk": {
```

(continues on next page)

(continued from previous page)

```

        "name": "ds-01.foo.kabletown.com.",
        "expirationDate": "1457732750",
        "public": "ksk public key",
        "private": "ksk private key",
        "inceptionDate": "1426196750"
    }
}
}}
```

DELETE

Delete DNSSEC keys for a CDN and all associated *Delivery Services*.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

Table 119: Request Path Parameters

Name	Description
name	The name of the CDN for which DNSSEC keys will be deleted

Response Structure

234: Response Example

```

{
  "response": "Successfully deleted dnssec keys for test"
}
```

cdns/name/{name}}/sslkeys

GET

Returns SSL certificates for all *Delivery Services* that are a part of the CDN.

Auth. Required Yes

Roles Required “admin”

Response Type Array

Request Structure

Table 120: Request Path Parameters

Name	Description
name	The name of the CDN for which keys will be fetched

Response Structure

certificate An object representing The SSL keys used for the *Delivery Service* identified by `deliveryservice`

key Base 64-encoded private key for SSL certificate

crt Base 64-encoded SSL certificate

deliveryservice A string that is the *xml_id* of the *Delivery Service* using the SSL key within `certificate`

235: Response Example

```
{ "response": [
  {
    "deliveryservice": "ds1",
    "certificate": {
      "crt": "base64encodedcrt1",
      "key": "base64encodedkey1"
    }
  },
  {
    "deliveryservice": "ds2",
    "certificate": {
      "crt": "base64encodedcrt2",
      "key": "base64encodedkey2"
    }
  }
]}
```

`cdns/{{name}}/snapshot`

Caution: This page is a stub! Much of it may be missing or just downright wrong - it needs a lot of love from people with the domain knowledge required to update it.

GET

Retrieves the *current Snapshot* for a CDN, which represents the current *operating state* of the CDN, **not** the current *configuration* of the CDN. The contents of this *Snapshot* are currently used by Traffic Monitor and Traffic Router.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 121: Request Path Parameters

Name	Description
name	The name of the CDN for which a <i>Snapshot</i> shall be returned

236: Request Example

```
GET /api/2.0/cdns/CDN-in-a-Box/snapshot HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

config An object containing basic configurations on the actual CDN object

api.cache-control.max-age A string containing an integer which specifies the value of `max-age` in the `Cache-Control` header of some HTTP responses, likely the *Traffic Router API* responses

certificates.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for updated SSL certificates

consistent.dns.routing A string containing a boolean which indicates whether DNS routing will use a consistent hashing method or “round-robin”

“false” The “round-robin” method will be used to define DNS routing

“true” A consistent hashing method will be used to define DNS routing

coveragezone.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should check for a new Coverage Zone file

coveragezone.polling.url The URL where a *Coverage Zone File* may be requested by Traffic Routers

dnssec.dynamic.response.expiration A string containing a number and unit suffix that specifies the length of time for which dynamic responses to DNSSEC lookup queries should remain valid

dnssec.dynamic.concurrencylevel An integer that defines the size of the concurrency level (threads) of the Guava cache used by ZoneManager to store zone material

dnssec.dynamic.initialcapacity An integer that defines the initial size of the Guava cache, default is 10000. Too low of a value can lead to expensive resizing

dnssec.init.timeout An integer that defines the number of minutes to allow for zone generation, this bounds the zone priming activity

dnssec.enabled A string that tells whether or not the CDN uses DNSSEC; one of:

“false” DNSSEC is not used within this CDN

“true” DNSSEC is used within this CDN

domain_name A string that is the TLD served by the CDN

federationmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new federation mappings

federationmapping.polling.url The URL where Traffic Control components can request federation mappings

geolocation.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new IP-to-geographic-location mapping databases

geolocation.polling.url The URL where Traffic Control components can request IP-to-geographic-location mapping database files

keystore.maintenance.interval A string containing an integer which specifies the interval, in seconds, on which Traffic

Routers should refresh their zone caches

neustar.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new “Neustar” databases

neustar.polling.url The URL where Traffic Control components can request “Neustar” databases

soa An object defining the SOA for the CDN’s TLD (defined in `domain_name`)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: **RFC 1035** dictates that this should always be less than `refresh`.

See also:

[The Wikipedia page on Start of Authority records.](#)

steeringmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which

Traffic Control components should check for new steering mappings

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

zonemanager.cache.maintenance.interval A configuration option for the ZoneManager Java class of Traffic Router

zonemanager.threadpool.scale A configuration option for the ZoneManager Java class of Traffic Router

contentRouters An object containing keys which are the (short) hostnames of the Traffic Routers that serve requests for *Delivery Services* in this CDN

api.port A string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTP

secure.api.port An optionally present string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTPS

fqdn This Traffic Router's FQDN

httpsPort The port number on which this Traffic Router listens for incoming HTTPS requests

ip This Traffic Router's IPv4 address

ip6 This Traffic Router's IPv6 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Router belongs

port The port number on which this Traffic Router listens for incoming HTTP requests

profile The *Name* of the *Profile* used by this Traffic Router

status The health status of this Traffic Router

See also:

Health Protocol

contentServers An object containing keys which are the (short) hostnames of the *Edge-tier cache servers* in the CDN; the values corresponding to those keys are routing information for said servers

cacheGroup A string that is the *Name* of the *Cache Group* to which the server belongs

deliveryServices An object containing keys which are the names of *Delivery Services* to which this *cache server* is assigned; the values corresponding to those keys are arrays

of FQDNs (Fully Qualified Domain Names) that resolve to this *cache server*

Note: Only *Edge-tier cache servers* can be assigned to a *Delivery Service*, and therefore this field will only be present when `type` is "EDGE".

fqdn The server's FQDN

hashCount The number of servers to be placed into a single "hash ring" in Traffic Router

hashId A unique string to be used as the key for hashing servers - as of version 3.0.0 of Traffic Control, this is always the same as the server's (short) hostname and only still exists for legacy compatibility reasons

httpsPort The port on which the *cache server* listens for incoming HTTPS requests

interfaceName The name of the main network interface device used by this *cache server*

ip6 The server's IPv6 address

ip The server's IPv4 address

locationId This field is exactly the same as `cacheGroup` and only exists for legacy compatibility reasons

port The port on which this *cache server* listens for incoming HTTP requests

profile The *Name* of the *Profile* used by the *cache server*

routingDisabled An integer representing the boolean concept of whether or not Traffic Routers should route client traffic to this *cache server*; one of:

0 Do not route traffic to this server

1 Route traffic to this server normally

status This *cache server*'s status

See also:

Health Protocol

type The *Type* of this *cache server*; which ought to be one of (but in practice need not be in certain special circumstances):

EDGE This is an *Edge-tier cache server*

MID This is a *Mid-tier cache server*

deliveryServices An object containing keys which are the *xml_ids* of all of the *Delivery Services* within the CDN

anonymousBlockingEnabled A string containing a boolean that tells whether or not *Anonymous Blocking* is set on this *Delivery Service*; one of:

“true” Anonymized IP addresses are blocked by this *Delivery Service*

“false” Anonymized IP addresses are not blocked by this *Delivery Service*

See also:

Configure Anonymous Blocking

consistentHashQueryParameters A set of query parameters that Traffic Router should consider when determining a consistent hash for a given client request.

consistentHashRegex An optional regular expression that will ensure clients are consistently routed to a *cache server* based on matches to it.

coverageZoneOnly A string containing a boolean that tells whether or not this *Delivery Service* routes traffic based only on its *Coverage Zone File*

See also:

Geo Limit

deepCachingType A string that defines the *Deep Caching* setting of this *Delivery Service*

dispersion An object describing the “dispersion” - or number of *cache servers* within a single *Cache Group* across which the same content is spread - within the *Delivery Service*

limit The maximum number of *cache servers* in which the response to a single request URL will be stored

Note: If this is greater than the number of *cache servers* in the *Cache Group* chosen to service the request, then content will be spread across all of them. That is, it causes no problems.

shuffled A string containing a boolean that tells whether the *cache servers* chosen

for content dispersion are chosen randomly or based on a consistent hash of the request URL; one of:

“false” *cache servers* will be chosen consistently

“true” *cache servers* will be chosen at random

domains An array of domains served by this *Delivery Service*

ecsEnabled A string containing a boolean from *EDNS0 Client Subnet Enabled* that tells whether EDNS0 client subnet is enabled on this *Delivery Service*; one of:

“false” EDNS0 client subnet is not enabled on this *Delivery Service*

“true” EDNS0 client subnet is enabled on this *Delivery Service*

geolocationProvider The name of a provider for IP-to-geographic-location mapping services - currently the only valid value is "maxmindGeolocationService"

ip6RoutingEnabled A string containing a boolean that defines the *IPv6 Routing Enabled* setting for this *Delivery Service*; one of:

“false” IPv6 traffic will not be routed by this *Delivery Service*

“true” IPv6 traffic will be routed by this *Delivery Service*

matchList An array of methods used by Traffic Router to determine whether or not a request can be serviced by this *Delivery Service*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

setNumber An integral, unique identifier for the set of types to which the **type** field belongs

type The name of the *Type* of match performed using **pattern** to determine whether or not to use this *Delivery Service*

HOST_REGEX Use the *Delivery Service* if **pattern** matches the *Host* HTTP header of an HTTP

request, or the name requested for resolution in a DNS request

HEADER_REGEX Use the *Delivery Service* if `pattern` matches an HTTP header (both the name and value) in an HTTP request¹

PATH_REGEX Use the *Delivery Service* if `pattern` matches the request path of this *Delivery Service*'s URL Page 423, 1

STEERING_REGEX Use the *Delivery Service* if `pattern` matches the `xml_id` of one of this *Delivery Service*'s “Steering” target *Delivery Services*

missLocation An object representing the default geographic coordinates to use for a client when lookup of their IP has failed in both the *Coverage Zone File* (and/or possibly the *Deep Coverage Zone File*) and the IP-to-geographic-location database

lat Geographic latitude as a floating point number

long Geographic longitude as a floating point number

protocol An object that describes how the *Delivery Service* ought to handle HTTP requests both with and without TLS encryption

acceptHttps A string containing a boolean that tells whether HTTPS requests should be normally serviced by this *Delivery Service*; one of:

“false” Refuse to service HTTPS requests

“true” Service HTTPS requests normally

redirectToHttps A string containing a boolean that tells whether HTTP requests ought to be re-directed to use HTTPS; one of:

“false” Do not redirect unencrypted traffic; service it normally

¹ These only apply to HTTP-routed *Delivery Services*

“true” Respond to HTTP requests with instructions to use HTTPS instead

See also:

Protocol

regionalGeoBlocking A string containing a boolean that defines the *Regional Geoblocking* setting of this *Delivery Service*; one of:

“false” Regional Geographic Blocking is not used by this *Delivery Service*

“true” Regional Geographic Blocking is used by this *Delivery Service*

See also:

Configure Regional Geo-blocking (RGB)

routingName A string that is this *Delivery Service’s Routing Name*

soa An object defining the SOA record for the *Delivery Service’s* TLDs (Top-Level Domains) (defined in **domains**)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to re-

quest the serial number from the master
if the master does not respond

Note: [RFC 1035](#) dictates that this
should always be less than `refresh`.

See also:

The [Wikipedia page on Start of Authority records](#).

sslEnabled A string containing a boolean that tells whether this
Delivery Service uses SSL; one of:

“false” SSL is not used by this *Delivery Service*

“true” SSL is used by this *Delivery Service*

See also:

Protocol

ttls An object that contains keys which are types of DNS records
that have values which are strings containing integers that
specify the time for which a response to the specific type
of record request should remain valid

Note: This overrides `config.ttls`.

edgeLocations An object containing keys which are the names of Edge-Tier *Cache Groups* within the CDN

backupLocations An object that describes this *Cache Group's Fallbacks*

fallbackToClosest A string containing a
boolean which defines the *Fallback to Closest*
behavior of this *Cache Group*;
one of:

“false” Do not fall back on the closest
available *Cache Group*

“true” Fall back on the closest avail-
able *Cache Group*

list If this *Cache Group* has any *Fallbacks*,
this key will appear and will be an ar-
ray of those *Cache Groups' Names*

latitude A floating point number that defines this *Cache Group's Latitude*

localizationMethods An array of strings that represents this *Cache Group's Localization Methods*

longitude A floating point number that defines this *Cache Group's Longitude*

monitors An object containing keys which are the (short) hostnames of Traffic Monitors within this CDN

fqdn The FQDN of this Traffic Monitor

httpsPort The port number on which this Traffic Monitor listens for incoming HTTPS requests

ip6 This Traffic Monitor's IPv6 address

ip This Traffic Monitor's IPv4 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Monitor belongs

port The port number on which this Traffic Monitor listens for incoming HTTP requests

profile A string which is the *Name* of the *Profile* used by this Traffic Monitor

Note: For legacy reasons, this must always start with "RASCAL-".

status The health status of this Traffic Monitor

See also:

Health Protocol

stats An object containing metadata information regarding the CDN

CDN_name The name of this CDN

date The UNIX epoch timestamp date in the Traffic Ops server's own timezone

tm_host The FQDN of the Traffic Ops server

tm_path A path relative to the root of the Traffic Ops server where a request may be replaced to have this *Snapshot* overwritten by the current *configured state* of the CDN .. deprecated:: ATCv6

This information should never be used; instead all tools and (especially) components **must** use the documented API. This field was removed in APIv4

tm_user The username of the currently logged-in user

tm_version The full version number of the Traffic Ops server, including release number, git commit hash, and supported Enterprise Linux version

trafficRouterLocations An object containing keys which are the *names of Cache Groups* within the CDN which contain Traffic Routers

backupLocations An object that describes this *Cache Group's Fallbacks*

fallbackToClosest A string containing a boolean which defines this *Cache Group's Fallback to Closest* setting; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

latitude A floating point number that defines this *Cache Group's Latitude*

localizationMethods An array of strings that represents this *Cache Group's Localization Methods*

longitude A floating point number that defines this *Cache Group's Longitude*

237: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 220bc4XXwaj+s7ODd3QAF5leGj06lnApiN5E8H/
→B2RgxSphnQIfnwy6WWbBDjonWXPV1IWDCjBMO+rR+lAabMg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 12 Dec 2018 17:36:25 GMT
Transfer-Encoding: chunked

{ "response": {
  "config": {
    "api.cache-control.max-age": "10",
    "certificates.polling.interval": "300000",
    "consistent.dns.routing": "true",
```

(continues on next page)

(continued from previous page)

```

    "coveragezone.polling.interval": "3600000",
    "coveragezone.polling.url": "https://trafficops.infra.ciab.
→test:443/coverage-zone.json",
    "dnssec.dynamic.response.expiration": "300s",
    "dnssec.enabled": "false",
    "domain_name": "mycdn.ciab.test",
    "federationmapping.polling.interval": "60000",
    "federationmapping.polling.url": "https://${toHostname}/api/2.
→0/federations",
    "geolocation.polling.interval": "86400000",
    "geolocation.polling.url": "https://trafficops.infra.ciab.
→test:443/GeoLite2-City.mmdb.gz",
    "keystore.maintenance.interval": "300",
    "neustar.polling.interval": "86400000",
    "neustar.polling.url": "https://trafficops.infra.ciab.test:443/
→neustar.tar.gz",
    "soa": {
        "admin": "twelve_monkeys",
        "expire": "604800",
        "minimum": "30",
        "refresh": "28800",
        "retry": "7200"
    },
    "steeringmapping.polling.interval": "60000",
    "ttls": {
        "A": "3600",
        "AAAA": "3600",
        "DNSKEY": "30",
        "DS": "30",
        "NS": "3600",
        "SOA": "86400"
    },
    "zonemanager.cache.maintenance.interval": "300",
    "zonemanager.threadpool.scale": "0.50"
},
"contentServers": {
    "edge": {
        "cacheGroup": "CDN_in_a_Box_Edge",
        "fqdn": "edge.infra.ciab.test",
        "hashCount": 999,
        "hashId": "edge",
        "httpsPort": 443,
        "interfaceName": "eth0",
        "ip": "172.16.239.100",
        "ip6": "fc01:9400:1000:8::100",
        "locationId": "CDN_in_a_Box_Edge",

```

(continues on next page)

(continued from previous page)

```

    "port": 80,
    "profile": "ATS_EDGE_TIER_CACHE",
    "status": "REPORTED",
    "type": "EDGE",
    "deliveryServices": {
      "demo1": [
        "edge.demo1.mycdn.ciab.test"
      ]
    },
    "routingDisabled": 0
  },
  "mid": {
    "cacheGroup": "CDN_in_a_Box_Mid",
    "fqdn": "mid.infra.ciab.test",
    "hashCount": 999,
    "hashId": "mid",
    "httpsPort": 443,
    "interfaceName": "eth0",
    "ip": "172.16.239.120",
    "ip6": "fc01:9400:1000:8::120",
    "locationId": "CDN_in_a_Box_Mid",
    "port": 80,
    "profile": "ATS_MID_TIER_CACHE",
    "status": "REPORTED",
    "type": "MID",
    "routingDisabled": 0
  }
},
"contentRouters": {
  "trafficrouter": {
    "api.port": "3333",
    "secure.api.port": "3443",
    "fqdn": "trafficrouter.infra.ciab.test",
    "httpsPort": 443,
    "ip": "172.16.239.60",
    "ip6": "fc01:9400:1000:8::60",
    "location": "CDN_in_a_Box_Edge",
    "port": 80,
    "profile": "CCR_CIAB",
    "status": "ONLINE"
  }
},
"deliveryServices": {
  "demo1": {
    "anonymousBlockingEnabled": "false",
    "coverageZoneOnly": "false",

```

(continues on next page)

(continued from previous page)

```
"dispersion": {
  "limit": 1,
  "shuffled": "true"
},
"domains": [
  "demo1.mycdn.ciab.test"
],
"geolocationProvider": "maxmindGeolocationService",
"matchsets": [
  {
    "protocol": "HTTP",
    "matchlist": [
      {
        "regex": ".*\\.demo1\\.\\.\\.*",
        "match-type": "HOST"
      }
    ]
  }
],
"missLocation": {
  "lat": 42,
  "long": -88
},
"protocol": {
  "acceptHttps": "false",
  "redirectToHttps": "false"
},
"regionalGeoBlocking": "false",
"soa": {
  "admin": "traffic_ops",
  "expire": "604800",
  "minimum": "30",
  "refresh": "28800",
  "retry": "7200"
},
"sslEnabled": "false",
"tls": {
  "A": "",
  "AAAA": "",
  "NS": "3600",
  "SOA": "86400"
},
"ip6RoutingEnabled": "true",
"ecsEnabled": "false",
"routingName": "video",
"deepCachingType": "NEVER"
```

(continues on next page)

(continued from previous page)

```

    }
  },
  "edgeLocations": {
    "CDN_in_a_Box_Edge": {
      "latitude": 38.897663,
      "longitude": -77.036574,
      "backupLocations": {
        "fallbackToClosest": "true"
      },
      "localizationMethods": [
        "GEO",
        "CZ",
        "DEEP_CZ"
      ]
    }
  },
  "trafficRouterLocations": {
    "CDN_in_a_Box_Edge": {
      "latitude": 38.897663,
      "longitude": -77.036574,
      "backupLocations": {
        "fallbackToClosest": "false"
      },
      "localizationMethods": [
        "GEO",
        "CZ",
        "DEEP_CZ"
      ]
    }
  },
  "monitors": {
    "trafficmonitor": {
      "fqdn": "trafficmonitor.infra.ciab.test",
      "httpsPort": 443,
      "ip": "172.16.239.40",
      "ip6": "fc01:9400:1000:8::40",
      "location": "CDN_in_a_Box_Edge",
      "port": 80,
      "profile": "RASCAL-Traffic_Monitor",
      "status": "ONLINE"
    }
  },
  "stats": {
    "CDN_name": "CDN-in-a-Box",
    "date": 1544635937,
    "tm_host": "trafficops.infra.ciab.test",

```

(continues on next page)

(continued from previous page)

```

    "tm_path": "/api/2.0/snapshot/CDN-in-a-Box",
    "tm_user": "admin",
    "tm_version": "traffic_ops-3.0.0-9813.8ad7bd8e.e17"
  }
}
```

`cdns/{name}/snapshot/new`

GET

Retrieves the *pending Snapshot* for a CDN, which represents the current *configuration* of the CDN, **not** the current *operating state* of the CDN. The contents of this *Snapshot* are currently used by Traffic Monitor and Traffic Router.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 122: Request Path Parameters

Name	Description
name	The name of the CDN for which a <i>Snapshot</i> shall be returned

238: Request Example

```

GET /api/2.0/cdns/CDN-in-a-Box/snapshot/new HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

config An object containing basic configurations on the actual CDN object

api.cache-control.max-age A string containing an integer which specifies the value of `max-age` in the *Cache-Control* header of some HTTP responses, likely the *Traffic Router API* responses

certificates.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for updated SSL certificates

consistent.dns.routing A string containing a boolean which indicates whether DNS routing will use a consistent hashing method or “round-robin”

“false” The “round-robin” method will be used to define DNS routing

“true” A consistent hashing method will be used to define DNS routing

coveragezone.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should check for a new Coverage Zone file

coveragezone.polling.url The URL where a *Coverage Zone File* may be requested by Traffic Routers

dnssec.dynamic.response.expiration A string containing a number and unit suffix that specifies the length of time for which dynamic responses to DNSSEC lookup queries should remain valid

dnssec.dynamic.concurrencylevel An integer that defines the size of the concurrency level (threads) of the Guava cache used by ZoneManager to store zone material

dnssec.dynamic.initialcapacity An integer that defines the initial size of the Guava cache, default is 10000. Too low of a value can lead to expensive resizing

dnssec.init.timeout An integer that defines the number of minutes to allow for zone generation, this bounds the zone priming activity

dnssec.enabled A string that tells whether or not the CDN uses DNSSEC; one of:

“false” DNSSEC is not used within this CDN

“true” DNSSEC is used within this CDN

domain_name A string that is the TLD served by the CDN

federationmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new federation mappings

federationmapping.polling.url The URL where Traffic Control components can request federation mappings

geolocation.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new IP-to-geographic-location mapping databases

geolocation.polling.url The URL where Traffic Control components can request IP-to-geographic-location mapping database files

keystore.maintenance.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should refresh their zone caches

neustar.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new “Neustar” databases

neustar.polling.url The URL where Traffic Control components can request “Neustar” databases

soa An object defining the SOA for the CDN’s TLD (defined in `domain_name`)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: [RFC 1035](#) dictates that this should always be less than `refresh`.

See also:

[The Wikipedia page on Start of Authority records.](#)

steeringmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Control components should check for new steering mappings

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

zonemanager.cache.maintenance.interval A configuration option for the ZoneManager Java class of Traffic Router

zonemanager.threadpool.scale A configuration option for the ZoneManager Java class of Traffic Router

contentRouters An object containing keys which are the (short) hostnames of the Traffic Routers that serve requests for *Delivery Services* in this CDN

api.port A string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTP

secure.api.port An optionally present string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTPS

fqdn This Traffic Router's FQDN

httpsPort The port number on which this Traffic Router listens for incoming HTTPS requests

ip This Traffic Router's IPv4 address

ip6 This Traffic Router's IPv6 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Router belongs

port The port number on which this Traffic Router listens for incoming HTTP requests

profile The *Name* of the *Profile* used by this Traffic Router

status The health status of this Traffic Router

See also:

[Health Protocol](#)

contentServers An object containing keys which are the (short) hostnames of the *Edge-tier cache servers* in the CDN; the values corresponding to those keys are routing information for said servers

cacheGroup A string that is the *Name* of the *Cache Group* to which the server belongs

deliveryServices An object containing keys which are the names of *Delivery Services* to which this *cache server* is assigned; the values corresponding to those keys are arrays of FQDNs that resolve to this *cache server*

Note: Only *Edge-tier cache servers* can be assigned to a *Delivery Service*, and therefore this field will only be present when *type* is "EDGE".

fqdn The server's FQDN

hashCount The number of servers to be placed into a single "hash ring" in Traffic Router

hashId A unique string to be used as the key for hashing servers - as of version 3.0.0 of Traffic Control, this is always the same as the server's (short) hostname and only still exists for legacy compatibility reasons

httpsPort The port on which the *cache server* listens for incoming HTTPS requests

interfaceName The name of the main network interface device used by this *cache server*

ip6 The server's IPv6 address

ip The server's IPv4 address

locationId This field is exactly the same as *cacheGroup* and only exists for legacy compatibility reasons

port The port on which this *cache server* listens for incoming HTTP requests

profile The *Name* of the *Profile* used by the *cache server*

routingDisabled An integer representing the boolean concept of whether or not Traffic Routers should route client traffic to this *cache server*; one of:

0 Do not route traffic to this server

1 Route traffic to this server normally

status This *cache server*'s status

See also:

Health Protocol

type The *Type* of this *cache server*; which ought to be one of (but in practice need not be in certain special circumstances):

EDGE This is an *Edge-tier cache server*

MID This is a *Mid-tier cache server*

deliveryServices An object containing keys which are the *xml_ids* of all of the *Delivery Services* within the CDN

anonymousBlockingEnabled A string containing a boolean that tells whether or not *Anonymous Blocking* is set on this *Delivery Service*; one of:

“true” Anonymized IP addresses are blocked by this *Delivery Service*

“false” Anonymized IP addresses are not blocked by this *Delivery Service*

See also:

Configure Anonymous Blocking

consistentHashQueryParameters A set of query parameters that Traffic Router should consider when determining a consistent hash for a given client request.

consistentHashRegex An optional regular expression that will ensure clients are consistently routed to a *cache server* based on matches to it.

coverageZoneOnly A string containing a boolean that tells whether or not this *Delivery Service* routes traffic based only on its *Coverage Zone File*

See also:

Geo Limit

deepCachingType A string that defines the *Deep Caching* setting of this *Delivery Service*

dispersion An object describing the “dispersion” - or number of *cache servers* within a single *Cache Group* across which the same content is spread - within the *Delivery Service*

limit The maximum number of *cache servers* in which the response to a single request URL will be stored

Note: If this is greater than the number of *cache servers* in the *Cache Group* chosen to service the request, then content will be spread across all of them. That is, it causes no problems.

shuffled A string containing a boolean that tells whether the *cache servers* chosen for content dispersion are chosen randomly or based on a consistent hash of the request URL; one of:

“false” *cache servers* will be chosen consistently

“true” *cache servers* will be chosen at random

domains An array of domains served by this *Delivery Service*

ecsEnabled A string containing a boolean from *EDNS0 Client Subnet Enabled* that tells whether EDNS0 client subnet is enabled on this *Delivery Service*; one of:

“false” EDNS0 client subnet is not enabled on this *Delivery Service*

“true” EDNS0 client subnet is enabled on this *Delivery Service*

geolocationProvider The name of a provider for IP-to-geographic-location mapping services - currently the only valid value is "maxmindGeolocationService"

ip6RoutingEnabled A string containing a boolean that defines the *IPv6 Routing Enabled* setting for this *Delivery Service*; one of:

“false” IPv6 traffic will not be routed by this *Delivery Service*

“true” IPv6 traffic will be routed by this *Delivery Service*

matchList An array of methods used by Traffic Router to determine whether or not a request can be serviced by this *Delivery Service*

pattern A regular expression - the use of this pattern is dependent on the *type* field (backslashes are escaped)

setNumber An integral, unique identifier for the set of types to which the *type* field

belongs

type The name of the *Type* of match performed using *pattern* to determine whether or not to use this *Delivery Service*

HOST_REGEX Use the *Delivery Service* if *pattern* matches the *Host* HTTP header of an HTTP request, or the name requested for resolution in a DNS request

HEADER_REGEX Use the *Delivery Service* if *pattern* matches an HTTP header (both the name and value) in an HTTP request¹

PATH_REGEX Use the *Delivery Service* if *pattern* matches the request path of this *Delivery Service*'s URL^{Page 423, 1}

STEERING_REGEX Use the *Delivery Service* if *pattern* matches the *xml_id* of one of this *Delivery Service*'s "Steering" target *Delivery Services*

missLocation An object representing the default geographic coordinates to use for a client when lookup of their IP has failed in both the *Coverage Zone File* (and/or possibly the *Deep Coverage Zone File*) and the IP-to-geographic-location database

lat Geographic latitude as a floating point number

long Geographic longitude as a floating point number

protocol An object that describes how the *Delivery Service* ought to handle HTTP requests both with and without TLS encryption

acceptHttps A string containing a boolean that tells whether HTTPS requests should be normally serviced by this *Delivery Service*; one of:

"false" Refuse to service HTTPS requests

¹ These only apply to HTTP-routed *Delivery Services*

“true” Service HTTPS requests normally

redirectToHttps A string containing a boolean that tells whether HTTP requests ought to be re-directed to use HTTPS; one of:

“false” Do not redirect unencrypted traffic; service it normally

“true” Respond to HTTP requests with instructions to use HTTPS instead

See also:

Protocol

regionalGeoBlocking A string containing a boolean that defines the *Regional Geoblocking* setting of this *Delivery Service*; one of:

“false” Regional Geographic Blocking is not used by this *Delivery Service*

“true” Regional Geographic Blocking is used by this *Delivery Service*

See also:

Configure Regional Geo-blocking (RGB)

routingName A string that is this *Delivery Service’s Routing Name*

soa An object defining the SOA record for the *Delivery Service’s* TLDs (defined in domains)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: [RFC 1035](#) dictates that this should always be less than `refresh`.

See also:

[The Wikipedia page on Start of Authority records.](#)

sslEnabled A string containing a boolean that tells whether this *Delivery Service* uses SSL; one of:

“false” SSL is not used by this *Delivery Service*

“true” SSL is used by this *Delivery Service*

See also:

Protocol

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

Note: This overrides `config.ttls`.

edgeLocations An object containing keys which are the names of Edge-Tier *Cache Groups* within the CDN

backupLocations An object that describes this *Cache Group's* *Fallbacks*

fallbackToClosest A string containing a boolean which defines the *Fallback to Closest* behavior of this *Cache Group*; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

list If this *Cache Group* has any *Fallbacks*, this key will appear and will be an array of those *Cache Groups’ Names*

latitude A floating point number that defines this *Cache Group’s Latitude*

localizationMethods An array of strings that represents this *Cache Group’s Localization Methods*

longitude A floating point number that defines this *Cache Group’s Longitude*

monitors An object containing keys which are the (short) hostnames of Traffic Monitors within this CDN

fqdn The FQDN of this Traffic Monitor

httpsPort The port number on which this Traffic Monitor listens for incoming HTTPS requests

ip6 This Traffic Monitor’s IPv6 address

ip This Traffic Monitor’s IPv4 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Monitor belongs

port The port number on which this Traffic Monitor listens for incoming HTTP requests

profile A string which is the *Name* of the *Profile* used by this Traffic Monitor

Note: For legacy reasons, this must always start with “RASCAL-“.

status The health status of this Traffic Monitor

See also:

Health Protocol

stats An object containing metadata information regarding the CDN

CDN_name The name of this CDN

date The UNIX epoch timestamp date in the Traffic Ops server’s own timezone

tm_host The FQDN of the Traffic Ops server

tm_path A path relative to the root of the Traffic Ops server where a request may be replaced to have this *Snapshot* overwritten by the current *configured state* of the CDN

Deprecated since version ATCv6: This information should never be used; instead all tools and (especially) components **must** use the documented API. This field was removed in APIv4

tm_user The username of the currently logged-in user

tm_version The full version number of the Traffic Ops server, including release number, git commit hash, and supported Enterprise Linux version

trafficRouterLocations An object containing keys which are the *names of Cache Groups* within the CDN which contain Traffic Routers

backupLocations An object that describes this *Cache Group's Fallbacks*

fallbackToClosest A string containing a boolean which defines this *Cache Group's Fallback to Closest* setting; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

latitude A floating point number that defines this *Cache Group's Latitude*

localizationMethods An array of strings that represents this *Cache Group's Localization Methods*

longitude A floating point number that defines this *Cache Group's Longitude*

239: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
➔GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
➔MWzgAYngmU1IEIxRa0C6VfY+MMuu7T90CiIj1Aul58pA7J7DiS6r8wjVRVW8W2Eu2V9BC70EacR1fQyu.
(continues on next page)
```

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Wed, 12 Dec 2018 21:41:48 GMT
Transfer-Encoding: chunked

{ "response": {
  "config": {
    "api.cache-control.max-age": "10",
    "certificates.polling.interval": "3000000",
    "consistent.dns.routing": "true",
    "coveragezone.polling.interval": "36000000",
    "coveragezone.polling.url": "https://trafficops.infra.ciab.
→test:443/coverage-zone.json",
    "dnssec.dynamic.response.expiration": "300s",
    "dnssec.enabled": "false",
    "domain_name": "mycdn.ciab.test",
    "federationmapping.polling.interval": "60000",
    "federationmapping.polling.url": "https://${toHostname}/api/2.
→0/federations",
    "geolocation.polling.interval": "86400000",
    "geolocation.polling.url": "https://trafficops.infra.ciab.
→test:443/GeoLite2-City.mmdb.gz",
    "keystore.maintenance.interval": "300",
    "neustar.polling.interval": "86400000",
    "neustar.polling.url": "https://trafficops.infra.ciab.test:443/
→neustar.tar.gz",
    "soa": {
      "admin": "twelve_monkeys",
      "expire": "604800",
      "minimum": "30",
      "refresh": "28800",
      "retry": "7200"
    },
    "steeringmapping.polling.interval": "60000",
    "ttls": {
      "A": "3600",
      "AAAA": "3600",
      "DNSKEY": "30",
      "DS": "30",
      "NS": "3600",
      "SOA": "86400"
    },
    "zonemanager.cache.maintenance.interval": "300",
    "zonemanager.threadpool.scale": "0.50"
  },
  "contentServers": {
    "edge": {
```

(continues on next page)

(continued from previous page)

```

    "cacheGroup": "CDN_in_a_Box_Edge",
    "fqdn": "edge.infra.ciab.test",
    "hashCount": 999,
    "hashId": "edge",
    "httpsPort": 443,
    "interfaceName": "eth0",
    "ip": "172.16.239.100",
    "ip6": "fc01:9400:1000:8::100",
    "locationId": "CDN_in_a_Box_Edge",
    "port": 80,
    "profile": "ATS_EDGE_TIER_CACHE",
    "status": "REPORTED",
    "type": "EDGE",
    "deliveryServices": {
      "demo1": [
        "edge.demo1.mycdn.ciab.test"
      ]
    },
    "routingDisabled": 0
  },
  "mid": {
    "cacheGroup": "CDN_in_a_Box_Mid",
    "fqdn": "mid.infra.ciab.test",
    "hashCount": 999,
    "hashId": "mid",
    "httpsPort": 443,
    "interfaceName": "eth0",
    "ip": "172.16.239.120",
    "ip6": "fc01:9400:1000:8::120",
    "locationId": "CDN_in_a_Box_Mid",
    "port": 80,
    "profile": "ATS_MID_TIER_CACHE",
    "status": "REPORTED",
    "type": "MID",
    "routingDisabled": 0
  }
},
"contentRouters": {
  "trafficrouter": {
    "api.port": "3333",
    "secure.api.port": "3443",
    "fqdn": "trafficrouter.infra.ciab.test",
    "httpsPort": 443,
    "ip": "172.16.239.60",
    "ip6": "fc01:9400:1000:8::60",
    "location": "CDN_in_a_Box_Edge",

```

(continues on next page)

(continued from previous page)

```

        "port": 80,
        "profile": "CCR_CIAB",
        "status": "ONLINE"
    },
    },
    "deliveryServices": {
        "demo1": {
            "anonymousBlockingEnabled": "false",
            "coverageZoneOnly": "false",
            "dispersion": {
                "limit": 1,
                "shuffled": "true"
            },
        },
        "domains": [
            "demo1.mycdn.ciab.test"
        ],
        "geolocationProvider": "maxmindGeolocationService",
        "matchsets": [
            {
                "protocol": "HTTP",
                "matchlist": [
                    {
                        "regex": ".*\\.demo1\\.\\.\\.\"",
                        "match-type": "HOST"
                    }
                ]
            }
        ],
        "missLocation": {
            "lat": 42,
            "long": -88
        },
        "protocol": {
            "acceptHttps": "false",
            "redirectToHttps": "false"
        },
        "regionalGeoBlocking": "false",
        "soa": {
            "admin": "traffic_ops",
            "expire": "604800",
            "minimum": "30",
            "refresh": "28800",
            "retry": "7200"
        },
        "sslEnabled": "false",
        "ttls": {

```

(continues on next page)

(continued from previous page)

```

        "A": "",
        "AAAA": "",
        "NS": "3600",
        "SOA": "86400"
    },
    "ip6RoutingEnabled": "true",
    "ecsEnabled": "false",
    "routingName": "video",
    "deepCachingType": "NEVER"
}
},
"edgeLocations": {
    "CDN_in_a_Box_Edge": {
        "latitude": 38.897663,
        "longitude": -77.036574,
        "backupLocations": {
            "fallbackToClosest": "true",
            "list": [
                "test"
            ]
        },
    },
    "localizationMethods": [
        "GEO",
        "CZ",
        "DEEP_CZ"
    ]
},
},
"trafficRouterLocations": {
    "CDN_in_a_Box_Edge": {
        "latitude": 38.897663,
        "longitude": -77.036574,
        "backupLocations": {
            "fallbackToClosest": "false"
        },
    },
    "localizationMethods": [
        "GEO",
        "CZ",
        "DEEP_CZ"
    ]
},
},
"monitors": {
    "trafficmonitor": {
        "fqdn": "trafficmonitor.infra.ciab.test",
        "httpsPort": 443,
    },
},

```

(continues on next page)

(continued from previous page)

```

        "ip": "172.16.239.40",
        "ip6": "fc01:9400:1000:8::40",
        "location": "CDN_in_a_Box_Edge",
        "port": 80,
        "profile": "RASCAL-Traffic_Monitor",
        "status": "ONLINE"
    }
},
"stats": {
    "CDN_name": "CDN-in-a-Box",
    "date": 1544650908,
    "tm_host": "ipcdn-cache-51.cdnlab.comcast.net:6443",
    "tm_path": "api/2.0/snapshot/CDN-in-a-Box",
    "tm_user": "admin",
    "tm_version": "traffic_ops-3.0.0-9813.8ad7bd8e.el7"
}
}}
```

cdns/routing

GET

Retrieves the aggregated routing percentages across all CDNs. This is accomplished by polling stats from all online Traffic Routers via the `/crs/stats` route.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available

Response Structure

cz The percent of requests to online Traffic Routers that were satisfied by a *Coverage Zone File*

deepCz The percent of requests to online Traffic Routers that were satisfied by a *Deep Coverage Zone File*

dsr The percent of requests to online Traffic Routers that were satisfied by sending the client to an overflow *Delivery Service*

- err** The percent of requests to online Traffic Routers that resulted in an error
- fed** The percent of requests to online Traffic Routers that were satisfied by sending the client to a federated CDN
- geo** The percent of requests to online Traffic Routers that were satisfied using 3rd party geographic IP mapping
- miss** The percent of requests to online Traffic Routers that could not be satisfied
- regionalAlternate** The percent of requests to online Traffic Routers that were satisfied by sending the client to the alternate, Regional Geo-blocking URL
- regionalDenied** The percent of requests to online Traffic Routers that were denied due to geographic location policy
- staticRoute** The percent of requests to online Traffic Routers that were satisfied with *Static DNS Entries*

240: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 21:29:32 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳7LjytwKyRzSKM4cRIol40MIJxApFpTWJaSK73rbtUIQdASZjI64XxLVzZP00GRU7XeJ22YKUyQ30qbKHDI
Content-Length: 130

{ "response": {
  "cz": 79,
  "deepCz": 0.50,
  "dsr": 0,
  "err": 0,
  "fed": 0.25,
  "geo": 20,
  "miss": 0.25,
  "regionalAlternate": 0,
  "regionalDenied": 0,
  "staticRoute": 0
}}
```

consistenthash

Test Pattern-Based Consistent Hashing for a *Delivery Service* using a regular expression and a request path

POST

Queries database for an active Traffic Router on a given CDN and sends GET request to get the resulting path to consistent hash with a given regex and request path.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

regex The regular expression to apply to the request path to get a resulting path that will be used for consistent hashing

requestPath The request path to use to test the regular expression against

cdnId The unique identifier of a CDN that will be used to query for an active Traffic Router

241: Request Example

```
POST /api/2.0/consistenthash HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.54.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 80
Content-Type: application/x-www-form-urlencoded

{"regex":"/.*?(/.*?/).*(m3u8)","requestPath":"/test/path/asset.m3u8",
↪ "cdnId":2}
```

Response Structure

resultingPathToConsistentHash The resulting path that Traffic Router will use for consistent hashing

consistentHashRegex The regex used by Traffic Router derived from POST 'regex' parameter

requestPath The request path used by Traffic Router to test regex against

242: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳QMDFOOnUfqH4TcZ4YnUQyqnXDier0YiUMIfwBGDcT7ySjw9uASBGsLQW35lpnKFi4as0vYlHuSSGpe4hHG
X-Server-Name: traffic_ops_golang/
Date: Tue, 12 Feb 2019 21:32:05 GMT
Content-Length: 142

{ "response": {
  "resultingPathToConsistentHash":"/path/m3u8",
  "consistentHashRegex":"/.*?(/.*?/).*(m3u8)",
  "requestPath":"/test/path/asset.m3u8"
}}
```

coordinates

GET

Gets a list of all coordinates in the Traffic Ops database

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 123: Request Query Parameters

Name	Required	Description
id	no	Return only coordinates that have this integral, unique identifier
name	no	Return only coordinates with this name
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

id Integral, unique, identifier for this coordinate pair

lastUpdated The time and date at which this entry was last updated, in a ctime-like format

latitude Latitude of the coordinate

longitude Longitude of the coordinate

name The name of the coordinate - typically this just reflects the name of the Cache Group for which the coordinate was created

243: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Y2vxC3hpxIg6aRNBBT7i2hbAViIJp+dJoqHIzu3acFM+vGay/
  ↳I5E+eZYOC9RY8hcJPrKNXysZOD8DOb9KsFgaw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:32:28 GMT
```

(continues on next page)

(continued from previous page)

Content-Length: 942

```
{ "response": [
  {
    "id": 1,
    "name": "from_cachegroup_TRAFFIC_ANALYTICS",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 2,
    "name": "from_cachegroup_TRAFFIC_OPS",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 3,
    "name": "from_cachegroup_TRAFFIC_OPS_DB",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 4,
    "name": "from_cachegroup_TRAFFIC_PORTAL",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 5,
    "name": "from_cachegroup_TRAFFIC_STATS",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 6,
    "name": "from_cachegroup_CDN_in_a_Box_Mid",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  }
]
```

(continues on next page)

(continued from previous page)

```
    "id": 7,  
    "name": "from_cachegroup_CDN_in_a_Box_Edge",  
    "latitude": 38.897663,  
    "longitude": -77.036574,  
    "lastUpdated": "2018-10-24 16:07:05+00"  
  }  
]}
```

POST

Creates a new coordinate pair

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the new coordinate

latitude The desired latitude of the new coordinate (must be on the interval [-180, 180])

longitude The desired longitude of the new coordinate (must be on the interval [-90, 90])

244: Request Example

```
POST /api/2.0/coordinates HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 47
Content-Type: application/json

{"name": "test", "latitude": 0, "longitude": 0}
```

Response Structure

- id** Integral, unique, identifier for the newly created coordinate pair
- lastUpdated** The time and date at which this entry was last updated, in a ctime-like format
- latitude** Latitude of the newly created coordinate
- longitude** Longitude of the newly created coordinate
- name** The name of the coordinate

245: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 7pWdeZyIIXE1P7o/
→JVon+5eSCbDw+FGamAzdXzWHXJ8IhF+Vh+/
→tWfCkzHYw3rP2kBVwZu+gqLffjQpBCMjt7A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 17:48:55 GMT
Content-Length: 165

{ "alerts": [
  {
    "text": "coordinate was created.",
    "level": "success"
  }
]}
```

(continues on next page)

(continued from previous page)

```
],
"response": {
  "id": 9,
  "name": "test",
  "latitude": 0,
  "longitude": 0,
  "lastUpdated": "2018-11-15 17:48:55+00"
}}
```

PUT

Updates a coordinate

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 124: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the coordinate to edit

name The name of the new coordinate

latitude The desired new latitude of the coordinate (must be on the interval [-180, 180])

longitude The desired new longitude of the coordinate (must be on the interval [-90, 90])

246: Request Example

```
PUT /api/2.0/coordinates?id=9 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 48
Content-Type: application/json

{"name": "quest", "latitude": 0, "longitude": 0}
```

Response Structure

- id** Integral, unique, identifier for the coordinate pair
- lastUpdated** The time and date at which this entry was last updated, in a ctime-like format
- latitude** Latitude of the coordinate
- longitude** Longitude of the coordinate
- name** The name of the coordinate

247: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳zd03Uvbnv8EbSZZ75Xp5tnnYStZsZTdyPxXnoqK4QZ5WhELLPL8iHlRf0aiLTbrUWUeJ8ue2HRz6aBS/
    ↳iXCCGA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 17:54:30 GMT
Content-Length: 166

{ "alerts": [
  {
    "text": "coordinate was updated.",
    "level": "success"
  }
],
"response": {
  "id": 9,
  "name": "quest",
  "latitude": 0,
  "longitude": 0,
  "lastUpdated": "2018-11-15 17:54:30+00"
}}
```

DELETE

Deletes a coordinate

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 125: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the coordinate to delete

Response Structure

248: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 82x/Wdckqgk4LN5LI1ZfBJ26xkDrUVUGDjs5QFa/
→Lzap7dU30Zkjbv8XW41xeFYj8PDmxHIpb7hiV0bvLaxnEDA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 17:57:42 GMT
Content-Length: 65

{ "alerts": [
  {
    "text": "coordinate was deleted.",
    "level": "success"
  }
]}

```


current_stats

An API endpoint that returns current statistics for each CDN and an aggregate across them all.

GET

Retrieves current stats for each CDN. Also includes aggregate stats across them.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

249: Request Example

```
GET /api/2.0/current_stats HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

cdn The name of the CDN

connections Current number of TCP connections maintained

capacity 85 percent capacity of the CDN in Gps

bandwidth The total amount of bandwidth in Gbs

Note: If **cdn** name is total and capacity is omitted it represents the aggregate stats across CDNs

250: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=; Path=/; HttpOnly
Whole-Content-Sha512: ↵
  ↵Rs3wgd7v5dP0b0Qs4I3J1q6mnWIMSM2AKSAWirK1kymvDY0oFISArF7Kkypgy10I34yn7FtFdMh6U7ABa
X-Server-Name: traffic_ops_golang/
Date: Thu, 14 Nov 2019 15:35:31 GMT
Content-Length: 138

{"response": {
  "currentStats": [
    {
      "bandwidth": null,
      "capacity": null,
      "cdn": "ALL",
      "connections": null
    },
    {
      "bandwidth": 0.000104,
      "capacity": 17,
      "cdn": "CDN-in-a-Box",
      "connections": 4
    },
    {
      "bandwidth": 0.000104,
      "cdn": "total",
      "connections": 4
    }
  ]
}}
```

dbdump

Caution: This is an extremely dangerous thing to do, as it exposes the entirety of the database, including possibly sensitive information. Administrators and systems engineers are advised to instead use database-specific tools to make server transitions more securely.

Dumps the Traffic Ops database as an SQL script that should recreate its schema and contents exactly.

Implementation Detail

The script is output using the *pg_dump(1)* utility, and is thus compatible for use with the

`pg_restore(1)` utility.

GET

Fetches the database dump.

Auth. Required Yes

Roles Required “admin”

Response Type undefined - outputs an SQL script, not JSON

Request Structure

No parameters available

251: Request Example

```
GET /api/2.0/dbdump HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

252: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/sql
Content-Disposition: attachment
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳YwvPB0ZToyzT8ilBnDlWWdwV+E3f2Xgus10KrkNaipQqgrw5zGwq0rC1U9TZ8Zl6kAGcRZgCYnr1EWfHX
X-Server-Name: traffic_ops_golang/
Date: Mon, 09 Sep 2019 21:08:28 GMT
Transfer-Encoding: chunked

-- Actual text omitted - it's huge
```

deliveryservice_request_comments

GET

Gets delivery service request comments.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 126: Request Query Parameters

Name	Re-quired	Description
author	no	Filter for <i>Delivery Service Request</i> comments submitted by the user identified by this username
authorId	no	Filter for <i>Delivery Service Request</i> comments submitted by the user identified by this integral, unique identifier
deliveryServiceRequestId	no	Filter for <i>Delivery Service Request</i> comments submitted for the delivery service identified by this integral, unique identifier
id	no	Filter for the <i>Delivery Service Request</i> comment identified by this integral, unique identifier

253: Request Example

```
GET /api/2.0/deliveryservice_request_comments HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

author The username of the user who created the comment.

authorId The integral, unique identifier of the user who created the comment.

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

id The integral, unique identifier of the *DSR* comment.

lastUpdated The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*

value The text of the comment that was posted.

xmlId This is the xmlId value that you provided in the request.

254: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:00:26
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳RaJZS1XFJ4oIxVKyyDjTuoQY7gPOmm5EuIL4AgHpyQpuaaNviw0XhGC4V/AKf/
    ↳Ws6zXLgIUc40yvMsTxnrilww==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:00:26 GMT
Content-Length: 207

{
  "response": [
    {
      "authorId": 2,
      "author": "admin",
      "deliveryServiceRequestId": 2,
      "id": 3,
      "lastUpdated": "2020-02-24 19:59:46+00",
      "value": "Changing to a different origin for now.",
      "xmlId": "demo1"
    },
    {
      "authorId": 2,
      "author": "admin",
      "deliveryServiceRequestId": 2,
      "id": 4,
      "lastUpdated": "2020-02-24 19:59:55+00",
      "value": "Using HTTPS.",
      "xmlId": "demo1"
    }
  ]
}
```

POST

Allows user to create a *Delivery Service Request* comment.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

deliveryServiceRequestId The integral, unique identifier of the delivery service that you are commenting on.

value The comment text itself.

xmlId This can be any string. It is not validated or used, though it is returned in the response.

255: Request Example

```
POST /api/2.0/deliveryservice_request_comments HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 111

{
  "deliveryServiceRequestId": 2,
  "value": "Does anyone have time to review my delivery service_
→request?"
}
```

Response Structure

author The username of the user who created the comment.

authorId The integral, unique identifier of the user who created the comment.

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

id The integral, unique identifier of the *DSR* comment.

lastUpdated The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*

value The text of the comment that was posted.

xmlId This is the xmlId value that you provided in the request.

256: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:02:20
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳LiakFP6L7PrnF05kLXftx7WQoKn3bGpIJT5N15PvNG2sHridRMV3k23eRJM66ET0LcRfMOrQgRiydE+Xg
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:02:20 GMT
Content-Length: 223

{
  "alerts": [
    {
      "text": "deliveryservice_request_comment was created.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": 2,
    "author": null,
    "deliveryServiceRequestId": 2,
    "id": 6,
    "lastUpdated": "2020-02-24 20:02:20+00",
    "value": "Does anyone have time to review my delivery service
    ↳request?",
    "xmlId": null
  }
}
```

PUT

Updates a delivery service request comment.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

value The comment text itself.

xmlId This can be any string. It is not validated or used, though it is returned in the response.

Table 127: Request Query Parameters

Parameter	Required	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> comment that you wish to update.

257: Request Example

```
PUT /api/2.0/deliveryservice_request_comments?id=6 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 166

{
  "deliveryServiceRequestId": 2,
  "value": "Update: We no longer need this, feel free to reject.\n\
  ↪nDoes anyone have time to review my delivery service request?"
}
```

Response Structure

author The username of the user who created the comment.

authorId The integral, unique identifier of the user who created the comment.

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

id The integral, unique identifier of the *DSR* comment.

lastUpdated The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*

value The text of the comment that was posted.

xmlId This is the xmlId value that you provided in the request.

258: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type, ↪
  ↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:05:46 ↪
  ↪GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ↪
  ↪RalS34imPw7c42nlnu5eTuv6FSxuGcAvxEdeIyNma1zpE3ZojAMFbhj8qi1s+hOVDYybfFPzMz82c+xc1
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

```
Date: Mon, 24 Feb 2020 20:05:46 GMT
Content-Length: 255

{
  "alerts": [
    {
      "text": "deliveryservice_request_comment was updated.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": null,
    "author": null,
    "deliveryServiceRequestId": 2,
    "id": 6,
    "lastUpdated": "2020-02-24 20:05:46+00",
    "value": "Update: We no longer need this, feel free to reject.\n\nDoes anyone have time to review my delivery service request?",
    "xmlId": null
  }
}
```

DELETE

Deletes a delivery service request comment.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type undefined

Request Structure

Table 128: Request Query Parameters

Parameter	Required	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> comment that you wish to delete.

259: Request Example

```
DELETE /api/2.0/deliveryservice_request_comments?id=6 HTTP/1.1
User-Agent: python-requests/2.22.0
```

(continues on next page)

(continued from previous page)

```
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

260: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:07:40
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 10pGzqeIh/1JAx85mz3MI/
    ↳5A1i1g5beTSLtfvgcfQmCjNKQvOMs/4TLviuVzOCRRrEIPmNcjy35tmvfxwlv7RMQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:07:40 GMT
Content-Length: 101

{
  "alerts": [
    {
      "text": "deliveryservice_request_comment was deleted.",
      "level": "success"
    }
  ]
}
```

deliveryservice_requests

GET

Retrieves *Delivery Service Requests*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 129: Request Query Parameters

Name	Re-quired	Description
as-signee	no	Filter for <i>Delivery Service Requests</i> that are assigned to the user identified by this username.
as-signeeId	no	Filter for <i>Delivery Service Requests</i> that are assigned to the user identified by this integral, unique identifier
author	no	Filter for <i>Delivery Service Requests</i> submitted by the user identified by this username
authorId	no	Filter for <i>Delivery Service Requests</i> submitted by the user identified by this integral, unique identifier
changeType	no	Filter for <i>Delivery Service Requests</i> of the change type specified. Can be create , update , or delete .
createdAt	no	Filter for <i>Delivery Service Requests</i> created on a certain date/time. Value must be RFC 3339 compliant. Eg. 2019-09-19T19:35:38.828535Z
id	no	Filter for the <i>Delivery Service Request</i> identified by this integral, unique identifier.
status	no	Filter for <i>Delivery Service Requests</i> whose status is the status specified. The status can be draft , submitted , pending , rejected , or complete .
xmlId	no	Filter for <i>Delivery Service Requests</i> that have the given <i>xml_id</i> .
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

New in version ATCv6: The `createdAt` query parameter was added to this in endpoint across all API versions in ATC version 6.0.0.

261: Request Example

```
GET /api/2.0/deliveryservice_requests?status=draft HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

- author** The username of the user who created the Delivery Service Request.
- authorId** The integral, unique identifier assigned to the author
- changeType** The change type of the *DSR*. It can be create, update, or delete....
- createdAt** The date and time at which the *DSR* was created, in *Traffic Ops's Custom Date/Time Format*.
- deliveryService** The delivery service that the *DSR* is requesting to update.
 - active** A boolean that defines *Active*.
 - anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
 - cacheurl** A *Cache URL Expression*
 - Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
 - ccrDnsTtl** The *DNS TTL* - named "ccrDnsTtl" for legacy reasons
 - cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
 - cdnName** Name of the *CDN* to which the *Delivery Service* belongs
 - checkPath** A *Check Path*
 - consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
 - consistentHashRegex** A *Consistent Hashing Regular Expression*
 - deepCachingType** The *Deep Caching* setting for this *Delivery Service*
 - displayName** The *Display Name*
 - dnsBypassCname** A *DNS Bypass CNAME*
 - dnsBypassIp** A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*¹

geoLimitRedirectUrl A *Geo Limit Redirect URL* Page 423, 1

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

longDesc2 An optional field containing the 3rd long description of this *Delivery Service*

matchList The *Delivery Service's Match List*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

¹ These fields must be defined if and only if **geoLimit** is non-zero

- setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
- type** The type of match performed using pattern.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*

- signed** true if and only if `signingAlgorithm` is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- lastEditedBy** The username of user who last edited this *DSR*
- lastEditedById** The integral, unique identifier assigned to the user who last edited this *DSR*
- lastUpdated** The date and time at which the *DSR* was last updated, in *Traffic Ops's Custom Date/Time Format*.
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

262: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:14:07.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UBp3nklJr2x2cAW/
→TKbhXMVJH6+OduxUaEBGbX4P7IahDk3VkaTd9LsQj01zgFEnZLwHriKpwHm10032RApZ0A==
```


(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:14:07 GMT
Content-Length: 872

{
  "response": [
    {
      "authorId": 2,
      "author": "admin",
      "changeType": "update",
      "createdAt": "2020-02-24 19:11:12+00",
      "id": 1,
      "lastEditedBy": "admin",
      "lastEditedById": 2,
      "lastUpdated": "2020-02-24 19:11:12+00",
      "deliveryService": {
        "active": false,
        "anonymousBlockingEnabled": false,
        "cacheurl": null,
        "ccrDnsTtl": null,
        "cdnId": 2,
        "cdnName": "CDN-in-a-Box",
        "checkPath": null,
        "displayName": "Demo 1",
        "dnsBypassCname": null,
        "dnsBypassIp": null,
        "dnsBypassIp6": null,
        "dnsBypassTtl": null,
        "dscp": 0,
        "edgeHeaderRewrite": null,
        "geoLimit": 0,
        "geoLimitCountries": null,
        "geoLimitRedirectURL": null,
        "geoProvider": 0,
        "globalMaxMbps": null,
        "globalMaxTps": null,
        "httpBypassFqdn": null,
        "id": 1,
        "infoUrl": null,
        "initialDispersion": 1,
        "ipv6RoutingEnabled": true,
        "lastUpdated": "0001-01-01 00:00:00+00",
        "logsEnabled": true,
        "longDesc": "Apachecon North America 2018",
        "longDesc1": null,
        "longDesc2": null,
      }
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```

"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
  "http://video.demo1.mycdn.ciab.test",
  "https://video.demo1.mycdn.ciab.test"
],
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": "root",
"trResponseHeaders": null,
"trRequestHeaders": null,
"consistentHashRegex": null,
"consistentHashQueryParams": [
  "abc",
  "pdq",
  "xxx",
  "zyx"
]

```

(continues on next page)

(continued from previous page)

```

        ],
        "maxOriginConnections": 0,
        "ecsEnabled": false
    },
    "status": "draft"
}
]
}

```

POST

Note: This route does NOT do the same thing as *POST deliveryservices/request*.

Creates a new *Delivery Service Request*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

changeType The action that you want to perform on the delivery service. It can be “create”, “update”, or “delete”.

status The status of your request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

deliveryService The *Delivery Service* that you have submitted for review as part of this request.

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

consistentHashRegex A *Consistent Hashing Regular Expression*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*^{Page 423, 1}

geoLimitRedirectUrl A *Geo Limit Redirect URL*^{Page 423, 1}

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

- lastUpdated** The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** An optional field containing the 2nd long description of this *Delivery Service*
- longDesc2** An optional field containing the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using pattern.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

routingName The *Routing Name* of this *Delivery Service*

signed true if and only if *signingAlgorithm* is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*

sslKeyVersion This integer indicates the *SSL Key Version*

tenant The name of the *Tenant* who owns this *Origin*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

263: Request Example

```
POST /api/2.0/deliveryservice_requests HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 1979

{
  "changeType": "update",
  "status": "draft",
  "deliveryService": {
    "active": false,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "Demo 1",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 1,
    "infoUrl": null,
    "initialDispersion": 1,
    "ipv6RoutingEnabled": true,
    "lastUpdated": "2020-02-13 16:43:54+00",
    "logsEnabled": true,
    "longDesc": "Apachecon North America 2018",
    "longDesc1": null,
    "longDesc2": null,
    "matchList": [
      {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
      }
    ],
  },
}
```

(continues on next page)

(continued from previous page)

```
    "maxDnsAnswers": null,
    "midHeaderRewrite": null,
    "missLat": 42,
    "missLong": -88,
    "multiSiteOrigin": false,
    "originShield": null,
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": 2,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": 1,
    "tenantId": 1,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false
}
```


Response Structure

- author** The username of the user who created the Delivery Service Request.
- authorId** The integral, unique identifier assigned to the author
- changeType** The change type of the *DSR*. It can be create, update, or delete....
- createdAt** The date and time at which the *DSR* was created, in *Traffic Ops's Custom Date/Time Format*.
- deliveryService** The delivery service that the *DSR* is requesting to update.
 - active** A boolean that defines *Active*.
 - anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
 - cacheurl** A *Cache URL Expression*
 Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
 - ccrDnsTtl** The *DNS TTL* - named "ccrDnsTtl" for legacy reasons
 - cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
 - cdnName** Name of the *CDN* to which the *Delivery Service* belongs
 - checkPath** A *Check Path*
 - consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
 - consistentHashRegex** A *Consistent Hashing Regular Expression*
 - deepCachingType** The *Deep Caching* setting for this *Delivery Service*
 - displayName** The *Display Name*
 - dnsBypassCname** A *DNS Bypass CNAME*
 - dnsBypassIp** A *DNS Bypass IP*
 - dnsBypassIp6** A *DNS Bypass IPv6*
 - dnsBypassTtl** The *DNS Bypass TTL*
 - dscp** A *DSCP* to be used within the *Delivery Service*
 - ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*
- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*
- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*^{Page 423, 1}
- geoLimitRedirectUrl** A *Geo Limit Redirect URL*^{Page 423, 1}
- geoProvider** The *Geolocation Provider*
- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*
- httpBypassFqdn** A *HTTP Bypass FQDN*
- id** An integral, unique identifier for this *Delivery Service*
- infoUrl** An *Info URL*
- initialDispersion** The *Initial Dispersion*
- ipv6RoutingEnabled** A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*
- lastUpdated** The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** An optional field containing the 2nd long description of this *Delivery Service*
- longDesc2** An optional field containing the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

- type** The type of match performed using pattern.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*

- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service's xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- lastEditedBy** The username of user who last edited this *DSR*
- lastEditedById** The integral, unique identifier assigned to the user who last edited this *DSR*
- lastUpdated** The date and time at which the *DSR* was last updated, in *Traffic Ops's Custom Date/Time Format*.
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

264: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:11:12
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: aWIrFTwUGnLq56WNZPL/FgOi/
    ↳NwAVUtOy4iqjFPwx4gj7RMZ6+nd++bQKIiasBl8ytAY0WmFvNnmm30Fq9mLpA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:11:12 GMT
Content-Length: 901

{

```

(continues on next page)

(continued from previous page)

```
"alerts": [
  {
    "text": "deliveryservice_request was created.",
    "level": "success"
  }
],
"response": {
  "authorId": 2,
  "author": null,
  "changeType": "update",
  "createdAt": null,
  "id": 1,
  "lastEditedBy": null,
  "lastEditedById": 2,
  "lastUpdated": "2020-02-24 19:11:12+00",
  "deliveryService": {
    "active": false,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "Demo 1",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 1,
    "infoUrl": null,
    "initialDispersion": 1,
    "ipv6RoutingEnabled": true,
    "lastUpdated": "0001-01-01 00:00:00+00",
    "logsEnabled": true,
    "longDesc": "Apachecon North America 2018",
    "longDesc1": null,
    "longDesc2": null,
```

(continues on next page)

(continued from previous page)

```

    "matchList": [
      {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.*"
      }
    ],
    "maxDnsAnswers": null,
    "midHeaderRewrite": null,
    "missLat": 42,
    "missLong": -88,
    "multiSiteOrigin": false,
    "originShield": null,
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": 2,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": 1,
    "tenantId": 1,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
      "http://video.demo1.mycdn.ciab.test",
      "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
      "abc",
      "pdq",
      "xxx",
      "zyx"
    ]

```

(continues on next page)

(continued from previous page)

```

    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false
  },
  "status": "draft"
}

```

PUT

Updates an existing *Delivery Service Request*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

author The username of the user who created the Delivery Service Request.

authorId The integral, unique identifier assigned to the author

changeType The change type of the *DSR*. It can be create, update, or delete....

deliveryService The delivery service that the *DSR* is requesting to update.

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

consistentHashRegex A *Consistent Hashing Regular Expression*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*^{Page 423, 1}

geoLimitRedirectUrl A *Geo Limit Redirect URL*^{Page 423, 1}

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** An optional field containing the 2nd long description of this *Delivery Service*
- longDesc2** An optional field containing the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using **pattern**.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

Table 130: Request Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> that you want to update.

265: Request Example

```
PUT /api/2.0/deliveryservice_requests?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 2256
```

```
{
  "authorId": 2,
  "author": "admin",
  "changeType": "update",
  "createdAt": "2020-02-24 19:11:12+00",
  "id": 1,
  "lastEditedBy": "admin",
  "lastEditedById": 2,
  "lastUpdated": "2020-02-24 19:33:26+00",
  "deliveryService": {
    "active": false,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "Demo 1",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 1,
    "infoUrl": null,
    "initialDispersion": 1,
    "ipv6RoutingEnabled": true,
    "lastUpdated": "0001-01-01 00:00:00+00",
```

(continues on next page)

(continued from previous page)

```

"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"longDesc1": null,
"longDesc2": null,
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
  "http://video.demo1.mycdn.ciab.test",
  "https://video.demo1.mycdn.ciab.test"
],
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": "root",
"trResponseHeaders": "",
"trRequestHeaders": null,
"consistentHashRegex": null,
"consistentHashQueryParams": [

```

(continues on next page)

(continued from previous page)

```

        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false
},
"status": "submitted"
}

```

Response Structure

- author** The username of the user who created the Delivery Service Request.
- authorId** The integral, unique identifier assigned to the author
- changeType** The change type of the *DSR*. It can be create, update, or delete....
- createdAt** The date and time at which the *DSR* was created, in *Traffic Ops's Custom Date/Time Format*.
- deliveryService** The delivery service that the *DSR* is requesting to update.
 - active** A boolean that defines *Active*.
 - anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
 - cacheurl** A *Cache URL Expression*
 Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
 - ccrDnsTtl** The *DNS TTL* - named "ccrDnsTtl" for legacy reasons
 - cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
 - cdnName** Name of the *CDN* to which the *Delivery Service* belongs
 - checkPath** A *Check Path*
 - consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
 - consistentHashRegex** A *Consistent Hashing Regular Expression*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*^{Page 423, 1}

geoLimitRedirectUrl A *Geo Limit Redirect URL*^{Page 423, 1}

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

longDesc2 An optional field containing the 3rd long description of this *Delivery Service*

matchList The *Delivery Service*'s *Match List*

pattern A regular expression - the use of this pattern is dependent on the *type* field (backslashes are escaped)

setNumber An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

type The type of match performed using pattern.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service's xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- lastEditedBy** The username of user who last edited this *DSR*
- lastEditedById** The integral, unique identifier assigned to the user who last edited this *DSR*
- lastUpdated** The date and time at which the *DSR* was last updated, in *Traffic Ops's Custom Date/Time Format*.
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

266: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:36:16.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +W0vFm96yFkZUJqa0GAX7uzIpRKh/
→ohyBm0uH3egpiERTcxy50fVVtoP3h8Ee2teLu8KFooDYXJ6rpQg6UhbnQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:36:16 GMT
Content-Length: 913
```

```
{
  "alerts": [
    {
      "text": "deliveryservice_request was updated.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": 0,
    "author": "admin",
    "changeType": "update",
    "createdAt": "0001-01-01 00:00:00+00",
    "id": 1,
    "lastEditedBy": "admin",
    "lastEditedById": 2,
    "lastUpdated": "2020-02-24 19:36:16+00",
    "deliveryService": {
      "active": false,
      "anonymousBlockingEnabled": false,
      "cacheurl": null,
      "ccrDnsTtl": null,
      "cdnId": 2,
      "cdnName": "CDN-in-a-Box",
      "checkPath": null,
      "displayName": "Demo 1",
      "dnsBypassCname": null,
      "dnsBypassIp": null,
      "dnsBypassIp6": null,
      "dnsBypassTtl": null,
      "dscp": 0,
      "edgeHeaderRewrite": null,
      "geoLimit": 0,
      "geoLimitCountries": null,
      "geoLimitRedirectURL": null,
    }
  }
}
```

(continues on next page)

(continued from previous page)

```

"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"ipv6RoutingEnabled": true,
"lastUpdated": "0001-01-01 00:00:00+00",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"longDesc1": null,
"longDesc2": null,
"matchList": [
    {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
    "http://video.demo1.mycdn.ciab.test",
    "https://video.demo1.mycdn.ciab.test"
]

```

(continues on next page)

(continued from previous page)

```

    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": "",
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false
  },
  "status": "submitted"
}

```

DELETE

Deletes a *Delivery Service Request*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type undefined

Request Structure

Table 131: Request Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> that you want to delete.

267: Request Example

```

DELETE /api/2.0/deliveryservice_requests?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate

```

(continues on next page)

(continued from previous page)

```
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

268: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:48:55
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳jNCbNo8Tw+JMMaWpAYQgntSXPq2Xuj+n2zSEVRaDQFWMV1SYbT9djes6SPdwiBoKq6W0lNE04h0E92jBV
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:48:55 GMT
Content-Length: 96

{
  "alerts": [
    {
      "text": "deliveryservice_request was deleted.",
      "level": "success"
    }
  ]
}
```

deliveryservice_requests/{{ID}}/assign

Assign a *Delivery Service Request* to a user.

PUT

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

id The integral, unique identifier assigned to the *DSR*

assignee The username of the user to whom the *Delivery Service Request* is assigned.

269: Request Example

```
PUT /api/2.0/deliveryservice_requests/1/assign HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 28

{
  "id": 1,
  "assigneeId": 2
}
```

Response Structure

assignee The username of the user to whom the *Delivery Service Request* is assigned.

author The author of the *Delivery Service Request*

authorId The integral, unique identifier assigned to the author

changeType The change type of the *DSR*. It can be create, update, or delete....

createdAt The date and time at which the *DSR* was created, in *Traffic Ops’s Custom Date/Time Format*.

deliveryService The delivery service that the *DSR* is requesting to update.

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

consistentHashRegex A *Consistent Hashing Regular Expression*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*¹

¹ These fields must be defined if and only if `geoLimit` is non-zero

- geoLimitRedirectUrl** A *Geo Limit Redirect URL* Page 423, 1
- geoProvider** The *Geolocation Provider*
- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*
- httpBypassFqdn** A *HTTP Bypass FQDN*
- id** An integral, unique identifier for this *Delivery Service*
- infoUrl** An *Info URL*
- initialDispersion** The *Initial Dispersion*
- ipv6RoutingEnabled** A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*
- lastUpdated** The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** An optional field containing the 2nd long description of this *Delivery Service*
- longDesc2** An optional field containing the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using pattern.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*

- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

id The integral, unique identifier assigned to the *DSR*

lastEditedBy The username of user who last edited this *DSR*

lastEditedById The integral, unique identifier assigned to the user who last edited this *DSR*

lastUpdated The date and time at which the *DSR* was last updated, in *Traffic Ops's Custom Date/Time Format*.

status The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

270: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 14:45:51
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→h7uBZHLQtRYbOSOR5AtQQRZ4uMeEWivWNT74fCf6WtLbAMwGpRrMjNmBYKduv48DEnRqG6WVM/
→4nBu3AkCUqPw==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 13:45:51 GMT
Content-Length: 931

{
  "alerts": [
    {
      "text": "deliveryservice_request was updated.",
      "level": "success"
    }
  ],
  "response": {
    "assigneeId": 2,
```

(continues on next page)

(continued from previous page)

```

"assignee": "admin",
"authorId": 2,
"author": "admin",
"changeType": "update",
"createdAt": "2020-02-23 11:06:00+00",
"id": 1,
"lastEditedBy": "admin",
"lastEditedById": 2,
"lastUpdated": "2020-02-23 13:45:51+00",
"deliveryService": {
  "active": true,
  "anonymousBlockingEnabled": false,
  "cacheurl": null,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "checkPath": null,
  "displayName": "Demo 2",
  "dnsBypassCname": null,
  "dnsBypassIp": null,
  "dnsBypassIp6": null,
  "dnsBypassTtl": null,
  "dscp": 0,
  "edgeHeaderRewrite": null,
  "geoLimit": 0,
  "geoLimitCountries": null,
  "geoLimitRedirectURL": null,
  "geoProvider": 0,
  "globalMaxMbps": null,
  "globalMaxTps": null,
  "httpBypassFqdn": null,
  "id": 1,
  "infoUrl": null,
  "initialDispersion": 1,
  "ipv6RoutingEnabled": true,
  "lastUpdated": "0001-01-01 00:00:00+00",
  "logsEnabled": true,
  "longDesc": "Apachecon North America 2018",
  "longDesc1": null,
  "longDesc2": null,
  "matchList": [
    {
      "type": "HOST_REGEX",
      "setNumber": 0,
      "pattern": ".*\\.demo1\\.\\.\\.*"
    }
  ]
}

```

(continues on next page)

(continued from previous page)

```

    ],
    "maxDnsAnswers": null,
    "midHeaderRewrite": null,
    "missLat": 42,
    "missLong": -88,
    "multiSiteOrigin": false,
    "originShield": null,
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": 2,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": null,
    "tenantId": 1,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false
},
"status": "submitted"
}

```

(continues on next page)

(continued from previous page)

```
}

```

deliveryservice_requests/{ID}/status

Sets the status of a *Delivery Service Request*.

PUT

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

id The integral, unique identifier assigned to the *DSR*

status The status of the *DSR* <*Delivery Service Request*>. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

271: Request Example

```
PUT /api/2.0/deliveryservice_requests/1/status HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 28

{
  "id": 1,
  "status": "rejected"
}
```

Response Structure

assignee The username of the user to whom the *Delivery Service Request* is assigned.

assigneeId The integral, unique identifier of the user to whom the *Delivery Service Request* is assigned.

author The author of the *Delivery Service Request*

- authorId** The integral, unique identifier assigned to the author
- changeType** The change type of the *DSR*. It can be create, update, or delete....
- createdAt** The date and time at which the *DSR* was created, in *Traffic Ops's Custom Date/Time Format*.
- deliveryService** The delivery service that the *DSR* is requesting to update.
- active** A boolean that defines *Active*.
- anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
- cacheurl** A *Cache URL Expression*
- Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
- ccrDnsTtl** The *DNS TTL* - named “ccrDnsTtl” for legacy reasons
- cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
- cdnName** Name of the *CDN* to which the *Delivery Service* belongs
- checkPath** A *Check Path*
- consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
- consistentHashRegex** A *Consistent Hashing Regular Expression*
- deepCachingType** The *Deep Caching* setting for this *Delivery Service*
- displayName** The *Display Name*
- dnsBypassCname** A *DNS Bypass CNAME*
- dnsBypassIp** A *DNS Bypass IP*
- dnsBypassIp6** A *DNS Bypass IPv6*
- dnsBypassTtl** The *DNS Bypass TTL*
- dscp** A *DSCP* to be used within the *Delivery Service*
- ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*
- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*

- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*
- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*¹
- geoLimitRedirectUrl** A *Geo Limit Redirect URL* Page 423, 1
- geoProvider** The *Geolocation Provider*
- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*
- httpBypassFqdn** A *HTTP Bypass FQDN*
- id** An integral, unique identifier for this *Delivery Service*
- infoUrl** An *Info URL*
- initialDispersion** The *Initial Dispersion*
- ipv6RoutingEnabled** A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*
- lastUpdated** The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** An optional field containing the 2nd long description of this *Delivery Service*
- longDesc2** An optional field containing the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using pattern.

¹ These fields must be defined if and only if `geoLimit` is non-zero

- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*

- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- lastEditedBy** The username of user who last edited this *DSR*
- lastEditedById** The integral, unique identifier assigned to the user who last edited this *DSR*
- lastUpdated** The date and time at which the *DSR* was last updated, in *Traffic Ops's Custom Date/Time Format*.
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

272: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 15:54:53
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳C8Nhciy1jv5X7CGgHwAnLp1qmLIzHq+4dv1AApb3cFSz5V2dABl7+N1Z4ndzB7GertB7rNLP31pVcat8v
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 14:54:53 GMT
Content-Length: 930

{
  "alerts": [
    {
      "text": "deliveryservice_request was updated.",

```

(continues on next page)

(continued from previous page)

```

        "level": "success"
    }
],
"response": {
    "assigneeId": 2,
    "assignee": "admin",
    "authorId": 2,
    "author": "admin",
    "changeType": "update",
    "createdAt": "2020-02-23 11:06:00+00",
    "id": 1,
    "lastEditedBy": "admin",
    "lastEditedById": 2,
    "lastUpdated": "2020-02-23 14:54:53+00",
    "deliveryService": {
        "active": true,
        "anonymousBlockingEnabled": false,
        "cacheurl": null,
        "ccrDnsTtl": null,
        "cdnId": 2,
        "cdnName": "CDN-in-a-Box",
        "checkPath": null,
        "displayName": "Demo 2",
        "dnsBypassCname": null,
        "dnsBypassIp": null,
        "dnsBypassIp6": null,
        "dnsBypassTtl": null,
        "dscp": 0,
        "edgeHeaderRewrite": null,
        "geoLimit": 0,
        "geoLimitCountries": null,
        "geoLimitRedirectURL": null,
        "geoProvider": 0,
        "globalMaxMbps": null,
        "globalMaxTps": null,
        "httpBypassFqdn": null,
        "id": 1,
        "infoUrl": null,
        "initialDispersion": 1,
        "ipv6RoutingEnabled": true,
        "lastUpdated": "0001-01-01 00:00:00+00",
        "logsEnabled": true,
        "longDesc": "Apachecon North America 2018",
        "longDesc1": null,
        "longDesc2": null,
        "matchList": [

```

(continues on next page)

(continued from previous page)

```

        {
            "type": "HOST_REGEX",
            "setNumber": 0,
            "pattern": ".*\\.demo1\\..*"
        }
    ],
    "maxDnsAnswers": null,
    "midHeaderRewrite": null,
    "missLat": 42,
    "missLong": -88,
    "multiSiteOrigin": false,
    "originShield": null,
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": 2,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": null,
    "tenantId": 1,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    ],

```

(continues on next page)

(continued from previous page)

```

        "maxOriginConnections": 0,
        "ecsEnabled": false
    },
    "status": "rejected"
}

```

deliveryservice_stats

GET

Retrieves time-aggregated statistics on a specific *Delivery Service*.

Auth. Required Yes

Roles Required None¹

Response Type Object

¹ This endpoint respects *Tenancy*, and users whose *Tenant* does not have access to a *Delivery Service* will be unable to view the statistics of said *Delivery Service*.

Request Structure

Table 132: Request Query Parameters

Name	Required	Description
deliveryService	yes ²	Either the <i>xml_id</i> of a <i>Delivery Service</i> for which statistics will be aggregated or the integral, unique identifier of said <i>Delivery Service</i>
deliveryServiceName	yes [?]	The <i>xml_id</i> of the <i>Delivery Service</i> for which statistics will be aggregated
endDate	yes	The date and time until which statistics shall be aggregated in RFC 3339 format (with or without sub-second precision), the number of nanoseconds since the Unix Epoch, or in the same, proprietary format as the <code>lastUpdated</code> fields prevalent throughout the Traffic Ops API
exclude	no	Either “series” to omit the data series from the result, or “summary” to omit the summary data from the result - directly corresponds to fields in the <i>Response Structure</i>
interval	no	Specifies the interval within which data will be “bucketed”; e.g. when requesting data from 2019-07-25T00:00:00Z to 2019-07-25T23:59:59Z with an interval of “1m”, the resulting data series (assuming it is not excluded) should contain $24 \frac{\text{hours}}{\text{day}} \times 60 \frac{\text{minutes}}{\text{hour}} \times 1 \text{day} \times 1 \frac{\text{minute}}{\text{datapoint}} = 1440 \text{data points}$ The allowed values for this parameter are valid InfluxQL duration literal strings matching <code>^d+[mhdw]\$</code>
limit	no	A natural number indicating the maximum amount of data points should be returned in the series
metricType	yes	The metric type being reported - one of: kbps The total traffic rate

273: Request Example

```
GET /api/2.0/deliveryservice_stats?deliveryServiceName=demo1&
→startDate=2019-07-22T17:55:00Z&endDate=2019-07-22T17:56:00.000Z&
→metricType=tps_total HTTP/1.1
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: application/json;timestamp=unix, application/json;
→timestamp=rfc;q=0.9, application/json;q=0.8, */*;q=0.7
Connection: keep-alive
Cookie: mojolicious=...
```

Content Format

It's important to note in *Request Example* the use of a complex “Accept” header. This endpoint accepts two special media types in the “Accept” header that instruct it on how to format the timestamps associated with the returned data. Specifically, Traffic Ops will recognize the special, optional, non-standard parameter of *application/json: timestamp*. The values of this parameter are restricted to one of

rfc Returned timestamps will be formatted according to **RFC 3339** (no sub-second precision).

unix Returned timestamps will be formatted as the number of nanoseconds since the Unix Epoch (midnight on January 1st 1970 UTC).

Implementation Detail

The endpoint passes back nanoseconds, specifically, because that is the form used both by InfluxDB, which is used to store the data being served, and Go's standard library. Clients may need to convert the value to match their own standard libraries - e.g. the `Date()` class in Javascript expects milliseconds.

The default behavior - when only e.g. *application/json* or **/** is given - is to use **RFC 3339** formatting. It will, however, respect quality parameters. It is suggested that clients request timestamps they can handle specifically, rather than relying on this default behavior, as it **is subject to change** and is in fact **expected to invert in the next major release** as string-based time formats become deprecated.

See also:

For more information on the “Accept” HTTP header, consult [its dedicated page on MDN](#).

² Either `deliveryServiceName` or `deliveryService` *must* be present, but if both are `deliveryServiceName` will be used and `deliveryService` will be ignored.

Response Structure

series An object containing the actual data series and information necessary for working with it.

columns This is an array of names of the columns of the data contained in the “values” array - should always be `["time", "sum_count"]`

count The number of data points contained in the “values” array

name The name of the data set. Should always match `metric.ds.1min` where `metric` is the requested `metricType`

values The actual array of data points. Each represents a length of time specified by the `interval` query parameter

time The time at which the measurement was taken. This corresponds to the *beginning* of the interval. This time comes in the format of either an [RFC 3339](#)-formatted string, or a number containing the number of nanoseconds since the Unix Epoch depending on the “Accept” header sent by the client, according to the rules outlined in [Content Format](#).

value The value of the requested `metricType` at the time given by `time`. This will always be a floating point number, unless no data is available for the data interval, in which case it will be `null`

summary An object containing summary statistics describing the data series

average The arithmetic mean of the data’s values

count The number of measurements taken within the requested timespan. This is, in general, **not** the same as the `count` field of the `series` object, as it reflects the number of underlying, un-“bucketed” data points, and is therefore dependent on the implementation of Traffic Stats.

fifthPercentile Data points with values less than or equal to this number constitute the “bottom” 5% of the data set

max The maximum value that can be found in the requested data set

min The minimum value that can be found in the requested data set

ninetyEighthPercentile Data points with values greater than or equal to this number constitute the “top” 2% of the data set

ninetyFifthPercentile Data points with values greater than or equal to this number constitute the “top” 5% of the data set

totalKiloBytes When the `metricType` requested is `kbps`, this will contain the total number of kilobytes transferred by the *Delivery Service* within the requested time window. Note that fractional amounts are possible, as the data transfer rate will almost certainly not be cleanly divided by the requested time range.

totalTransactions When the `metricType` requested is **not** `kbps`, this will contain the total number of transactions completed by the *Delivery Service* within the requested time window. Note that fractional amounts are possible, as the transaction rate will almost certainly not be cleanly divided by the requested time range.

274: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: zXJGjcYuu6HxWINVp8HA1gL31J3ukry5wCsTDNxtP/
→waC6rSD8h10KJ9jEAtrZJ9owOSVPvKaA/2bRu/QeuCpQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 22 Jul 2019 17:57:14 GMT
Transfer-Encoding: chunked

{ "response": {
  "series": {
    "columns": [
      "time",
      "sum_count"
    ],
    "count": 2,
    "name": "tps_total.ds.1min",
    "tags": {
      "cachegroup": "total"
    }
  }
}
```

(continues on next page)

(continued from previous page)

```

    },
    "values": [
      [
        15638181000000000000,
        0
      ],
      [
        15638181600000000000,
        0
      ]
    ]
  },
  "source": "TrafficStats",
  "summary": {
    "average": 0,
    "count": 2,
    "fifthPercentile": 0,
    "max": 0,
    "min": 0,
    "ninetyEighthPercentile": 0,
    "ninetyFifthPercentile": 0,
    "totalKiloBytes": null,
    "totalTransactions": 0
  },
  "version": "1.2"
}}

```

deliveryservices

GET

Retrieves *Delivery Services*

Auth. Required Yes

Roles Required None¹

Response Type Array

¹ Only those *Delivery Services* assigned to *Tenants* that are the requesting user's *Tenant* or children thereof will appear in the output of a GET request, and the same constraints are placed on the allowed values of the `tenantId` field of a POST request to create a new *Delivery Service*

Request Structure

Table 133: Request Query Parameters

Name	Re-quired	Description
cdn	no	Show only the <i>Delivery Services</i> belonging to the <i>CDN</i> identified by this integral, unique identifier
id	no	Show only the <i>Delivery Service</i> that has this integral, unique identifier
logsEnabled	no	Show only the <i>Delivery Services</i> that have <i>Logs Enabled</i> set or not based on this boolean
profile	no	Return only <i>Delivery Services</i> using the <i>Profile</i> that has this <i>ID</i>
tenant	no	Show only the <i>Delivery Services</i> belonging to the <i>Tenant</i> identified by this integral, unique identifier
type	no	Return only <i>Delivery Services</i> of the <i>Delivery Service Type</i> identified by this integral, unique identifier
accessibleTo	no	Return the <i>Delivery Services</i> accessible from a <i>Tenant</i> or it's children identified by this integral, unique identifier
xmlId	no	Show only the <i>Delivery Service</i> that has this text-based, unique identifier
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*

geoLimitRedirectUrl A *Geo Limit Redirect URL*

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 The 2nd long description of this *Delivery Service*

longDesc2 the 3rd long description of this *Delivery Service*

matchList The *Delivery Service*'s *Match List*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

setNumber An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

type The type of match performed using **pattern**.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId The *ID* of the *Profile* with which this *Delivery Service* is associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

signed true if and only if **signingAlgorithm** is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or `null` to indicate URL/URI signing is not implemented on this *Delivery Service*

rangeSliceBlockSize An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if `rangeRequestHandling` is set to 3.

sslKeyVersion This integer indicates the *SSL Key Version*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service's* `xml_id`

275: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: mCLMjvACRKHNGP/
→OSx4javkOtxxyiDdQzsV78IamUhVmvyKyKaCeOKRmpsG69w+nhh30kPZ6e9MMeJpcJSKCA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 19:04:29 GMT
Transfer-Encoding: chunked

{ "response": [{
  "active": true,
  "anonymousBlockingEnabled": false,
  "cacheurl": null,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "checkPath": null,
  "displayName": "Demo 1",
  "dnsBypassCname": null,
  "dnsBypassIp": null,
  "dnsBypassIp6": null,
```

(continues on next page)

(continued from previous page)

```
"dnsBypassTtl": null,
"dscp": 0,
"edgeHeaderRewrite": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"ipv6RoutingEnabled": true,
"lastUpdated": "2019-05-15 14:32:05+00",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"longDesc1": null,
"longDesc2": null,
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": null,
"tenantId": 1,
```

(continues on next page)

(continued from previous page)

```

"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
    "http://video.demo1.mycdn.ciab.test",
    "https://video.demo1.mycdn.ciab.test"
],
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": "root",
"trResponseHeaders": null,
"trRequestHeaders": null,
"consistentHashRegex": null,
"consistentHashQueryParams": [
    "abc",
    "pdq",
    "xxx",
    "zyx"
],
"maxOriginConnections": 0,
"ecsEnabled": false,
"rangeSliceBlockSize": null
}]]}

```

POST

Allows users to create *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 423, 1}

Response Type Array

Request Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*²

geoLimitRedirectUrl A *Geo Limit Redirect URL*[?]

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

² These fields must be defined if and only if `geoLimit` is non-zero

- longDesc2** An optional field containing the 3rd long description of this *Delivery Service*
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if *rangeRequestHandling* is set to 3. It can only be between (inclusive) 262144 (256KB) - 33554432 (32MB).
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

276: Request Example

```
POST /api/2.0/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 761
Content-Type: application/json

{
  "active": false,
  "anonymousBlockingEnabled": false,
  "cdnId": 2,
  "deepCachingType": "NEVER",
  "displayName": "test",
  "dscp": 0,
  "ecsEnabled": true,
  "geoLimit": 0,
  "geoProvider": 0,
  "initialDispersion": 1,
  "ipv6RoutingEnabled": false,
  "logsEnabled": true,
  "longDesc": "A Delivery Service created expressly for API_
↪documentation examples",
  "missLat": 0,
  "missLong": 0,
  "maxOriginConnections": 0,
  "multiSiteOrigin": false,
  "orgServerFqdn": "http://origin.infra.ciab.test",
  "protocol": 0,
  "qstringIgnore": 0,
  "rangeRequestHandling": 0,
  "regionalGeoBlocking": false,
  "routingName": "test",
  "signed": false,
  "tenant": "root",
  "tenantId": 1,
  "typeId": 1,
  "xmlId": "test"
}
```

Response Structure

- active** A boolean that defines *Active*.
- anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
- cacheurl** A *Cache URL Expression*
 Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
- ccrDnsTtl** The *DNS TTL* - named “ccrDnsTtl” for legacy reasons
- cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
- cdnName** Name of the *CDN* to which the *Delivery Service* belongs
- checkPath** A *Check Path*
- consistentHashRegex** A *Consistent Hashing Regular Expression*
- consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
- deepCachingType** The *Deep Caching* setting for this *Delivery Service*
- displayName** The *Display Name*
- dnsBypassCname** A *DNS Bypass CNAME*
- dnsBypassIp** A *DNS Bypass IP*
- dnsBypassIp6** A *DNS Bypass IPv6*
- dnsBypassTtl** The *DNS Bypass TTL*
- dscp** A *DSCP* to be used within the *Delivery Service*
- ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*
- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*
- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*
- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*
- geoLimitRedirectUrl** A *Geo Limit Redirect URL*
- geoProvider** The *Geolocation Provider*
- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*
- httpBypassFqdn** A *HTTP Bypass FQDN*

- id** An integral, unique identifier for this *Delivery Service*
- infoUrl** An *Info URL*
- initialDispersion** The *Initial Dispersion*
- ipv6RoutingEnabled** A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*
- lastUpdated** The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** The 2nd long description of this *Delivery Service*
- longDesc2** the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
 - pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using **pattern**.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** The *ID* of the *Profile* with which this *Delivery Service* is associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- signed** true if and only if `signingAlgorithm` is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if `rangeRequestHandling` is set to 3.
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*

277: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: SVveQ5hGwfPv8N5APUskwLOzwrTUVA+z8wuFLsSLCr1/
    ↳vVnFJJ0VQOGMUctg1NbqhAuQ795MJmuuAaAwR8dSOQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 19 Nov 2018 19:45:49 GMT
Content-Length: 1404
```

(continues on next page)

(continued from previous page)

```
{ "alerts": [
  {
    "text": "Deliveryservice creation was successful.",
    "level": "success"
  }
],
"response": [
  {
    "active": false,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "test",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 2,
    "infoUrl": null,
    "initialDispersion": 1,
    "ipv6RoutingEnabled": false,
    "lastUpdated": "2018-11-19 19:45:49+00",
    "logsEnabled": true,
    "longDesc": "A Delivery Service created expressly for API_
→documentation examples",
    "longDesc1": null,
    "longDesc2": null,
    "matchList": [
      {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.test\\..*"
      }
    ]
  }
],
```

(continues on next page)

(continued from previous page)

```

    "maxDnsAnswers": null,
    "maxOriginConnections": 0,
    "midHeaderRewrite": null,
    "missLat": -1,
    "missLong": -1,
    "multiSiteOrigin": false,
    "originShield": null,
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": 0,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "test",
    "signed": false,
    "sslKeyVersion": null,
    "tenantId": 1,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "test",
    "exampleURLs": [
        "http://test.test.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "signingAlgorithm": null,
    "tenant": "root",
    "ecsEnabled": true,
    "rangeSliceBlockSize": null
}
]]

```

`deliveryservices/{{ID}}`

PUT

Allows users to edit an existing *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”¹

¹ Only those *Delivery Services* assigned to *Tenants* that are the requesting user’s *Tenant* or children thereof will appear in the output of a GET request, and the same constraints are placed on the allowed values of the `tenantId`

Response Type NOT PRESENT - Despite returning a 200 OK response (rather than e.g. a 204 NO CONTENT response), this endpoint does **not** return a representation of the modified resource in its payload, and instead returns nothing - not even a success message.

Request Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*²

geoLimitRedirectUrl A *Geo Limit Redirect URL*[?]

field of a PUT request to update a new *Delivery Service*. Furthermore, the only *Delivery Services* a user may delete are those assigned to a *Tenant* that is either the same *Tenant* as the user's *Tenant*, or a descendant thereof.

² These fields must be defined if and only if `geoLimit` is non-zero

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

longDesc2 An optional field containing the 3rd long description of this *Delivery Service*

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileId An optional *ID* of the *Profile* with which this *Delivery Service* will be associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

routingName The *Routing Name* of this *Delivery Service*

signed true if and only if **signingAlgorithm** is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*

rangeSliceBlockSize An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if **rangeRequestHandling** is set to 3. It can only be between (inclusive) 262144 (256KB) - 33554432 (32MB).

sslKeyVersion This integer indicates the *SSL Key Version*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

Note: While this field **must** be present, it is **not** allowed to change; this must be the same as the *xml_id* the *Delivery Service* already has. This should almost never be different from the *Delivery Service*'s *displayName*.

278: Request Example

```
PUT /api/2.0/deliveryservices/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 761
Content-Type: application/json

{
  "active": true,
  "anonymousBlockingEnabled": false,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "deepCachingType": "NEVER",
  "displayName": "demo",
  "dscp": 0,
  "ecsEnabled": true,
```

(continues on next page)

(continued from previous page)

```

    "geoLimit": 0,
    "geoProvider": 0,
    "initialDispersion": 1,
    "ipv6RoutingEnabled": false,
    "lastUpdated": "2018-11-14 18:21:17+00",
    "logsEnabled": true,
    "longDesc": "A Delivery Service created expressly for API_
→documentation examples",
    "missLat": -1,
    "missLong": -1,
    "multiSiteOrigin": false,
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "protocol": 0,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regionalGeoBlocking": false,
    "routingName": "video",
    "signed": false,
    "tenant": "root",
    "tenantId": 1,
    "typeId": 1,
    "xmlId": "demo1"
}

```

Response Structure

279: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: z4PhNX7vuL3xVChQ1m2AB9Yg5AULVxXcg/
    ↳SpIdNs6c5H0NE8XYXysP+DGNKHfuwvY7kxvUdBeoGl0DJ6+SfaPg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 20 Nov 2018 14:12:25 GMT
Content-Length: 0
Content-Type: text/plain; charset=utf-8
```

DELETE

Deletes the target *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 423, 1}

Response Type undefined

Request Structure

Table 134: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> to be deleted

280: Request Example

```
DELETE /api/2.0/deliveryservices/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

281: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: w9NlQpJJEl56r6iYq/
→fk8o5WfAXeUS5XR9yDHvKUgPO8lYEo8YyftaSF0MPFseeOk60dk6kQo+MLYTDIAhhRxw==
X-Server-Name: traffic_ops_golang/
Date: Tue, 20 Nov 2018 14:56:37 GMT
Content-Length: 57

{ "alerts": [
  {
    "text": "ds was deleted.",
    "level": "success"
  }
]}
```

`deliveryservices/{{ID}}/capacity`

See also:

Health Protocol

GET

Retrieves the usage percentages of a servers associated with a *Delivery Service*

Auth. Required Yes

Roles Required None¹

Response Type Object

Request Structure

Table 135: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the <i>Delivery Service</i> of interest

Response Structure

availablePercent The percent of servers assigned to this *Delivery Service* that is available - the allowed traffic level in terms of data per time period for all *cache servers* that remains unused

unavailablePercent The percent of servers assigned to this *Delivery Service* that is unavailable - the allowed traffic level in terms of data per time period for all *cache servers* that can't be used because the servers are deemed unhealthy

utilizedPercent The percent of servers assigned to this *Delivery Service* that is currently in use - the allowed traffic level in terms of data per time period that is currently devoted to servicing requests

maintenancePercent The percent of servers assigned to this *Delivery Service* that is unavailable due to server maintenance - the allowed traffic level in terms of data per time period that is unavailable because servers have intentionally been marked offline by administrators

282: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
```

(continues on next page)

¹ Users will only be able to see capacity details for the *Delivery Services* their *Tenant* is allowed to see.

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 14:41:27 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→++dFR9V1c60CHGNwMjX6JSFEjHreXcL4QnhT03hiv04ByY379aLpL40rOzX2bPgJgpR94+f6jZ0+iDIyT
Content-Length: 134

{ "response": {
  "availablePercent": 99.9993696969697,
  "unavailablePercent": 0,
  "utilizedPercent": 0.00063030303030303,
  "maintenancePercent": 0
}}
```

deliveryservices/{{ID}}/health

See also:

Health Protocol

GET

Retrieves the health of all *Cache Groups* assigned to a particular *Delivery Service*

Auth. Required Yes

Roles Required None¹

Response Type Object

¹ Users will only be able to see *Cache Group* health details for the *Delivery Services* their *Tenant* is allowed to see.

Request Structure

Table 136: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the Delivery service for which <i>Cache Groups</i> will be displayed

Response Structure

cachegroups An array of objects that represent the health of each *Cache Group* assigned to this *Delivery Service*

name A string that is the *name of the Cache Group* represented by this object

offline The number of OFFLINE *cache servers* within this *Cache Group*

online The number of ONLINE *cache servers* within this *Cache Group*

totalOffline Total number of OFFLINE *cache servers* assigned to this *Delivery Service*

totalOnline Total number of ONLINE *cache servers* assigned to this *Delivery Service*

283: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 14:43:43 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→KpXViXeAgch58ueQqdyU8NuINBw1EUedE6Rv2ewcLUajJp6kowdbVynpwW7XiSvAyHdtClIOuT30khIm
Content-Length: 115

{ "response": {
  "totalOffline": 0,
```

(continues on next page)

(continued from previous page)

```

    "totalOnline": 1,
    "cachegroups": [
      {
        "offline": 0,
        "name": "CDN_in_a_Box_Edge",
        "online": 1
      }
    ]
  }
}
```

deliveryservices/{{ID}}/regexes

GET

Retrieves routing regular expressions for a specific *Delivery Service*.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 137: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected

Table 138: Request Query Parameters

Name	Re- quired	Description
id	no	Show only the <i>Delivery Service</i> regular expression that has this integral, unique identifier
limit	no	Choose the maximum number of results to return
off- set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>n</i> th page of results, where “ <i>n</i> ” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

¹ Users will only be able to view and create regular expressions for the *Delivery Services* their *Tenant* is allowed to see.

284: Request Example

```
GET /api/2.0/deliveryservices/1/regexes HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- id** The integral, unique identifier of this regular expression
- pattern** The actual regular expression - \s are escaped
- setNumber** The order in which the regular expression is evaluated against requests
- type** The integral, unique identifier of the *Type* of this regular expression
- typeName** The *Type* of regular expression - determines that against which it will be evaluated

285: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: fw9Fde4WRpp2ShRAC41P9s/PhU71LI/
↳SEzHgYjGqfzhk45wq0kpaWy76JvPfLpowY8eDTp8Y8TL5rNGEc+bM+A==
X-Server-Name: traffic_ops_golang/
Date: Tue, 27 Nov 2018 20:56:43 GMT
Content-Length: 100

{ "response": [
  {
    "id": 1,
    "type": 31,
    "typeName": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
]
}]
```

POST

Creates a routing regular expression for a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 423, 1}

Response Type Object

Request Structure

Table 139: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected

pattern The actual regular expression

Warning: Be sure that \s are escaped, or the expression may not work as intended!

setNumber The order in which this regular expression should be checked

type The integral, unique identifier of a routing regular expression type

286: Request Example

```
POST /api/2.0/deliveryservices/1/regexes HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 55
Content-Type: application/json

{
  "pattern": ".*\\.foo-bar\\.\\.\\.\"",
  "type": 31,
  "setNumber": 1
}
```

Response Structure

- id** The integral, unique identifier of this regular expression
- pattern** The actual regular expression - \s are escaped
- setNumber** The order in which the regular expression is evaluated against requests
- type** The integral, unique identifier of the type of this regular expression
- typeName** The type of regular expression - determines that against which it will be evaluated

287: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: kS5dRzAhFKE7vfzHK7XVIwpMOjztk9MU+qtj5YU/
  ↳1oxVHmqNbJ12Fe00IJsZJCXbYlnBS04sCI95Sz5wed1Q==
X-Server-Name: traffic_ops_golang/
Date: Wed, 28 Nov 2018 17:00:42 GMT
Content-Length: 188

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

        "text": "Delivery service regex creation was successful.",
        "level": "success"
    }
],
"response": {
    "id": 2,
    "type": 31,
    "typeName": "HOST_REGEX",
    "setNumber": 1,
    "pattern": ".*\\.foo-bar\\.\\.\\.*"
}}

```

deliveryservices/{{ID}}/regexes/{{rID}}

PUT

Updates a routing regular expression.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type Object

Request Structure

Table 140: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected
rID	The integral, unique identifier of the routing regular expression being inspected

pattern The actual regular expression

Warning: Be sure that \s are escaped, or the expression may not work as intended!

setNumber The order in which this regular expression should be checked

type The integral, unique identifier of a routing regular expression type

¹ Users will only be able to view, delete and update regular expressions for the *Delivery Services* their *Tenant* is allowed to see.

288: Request Example

```
PUT /api/2.0/deliveryservices/1/regexes/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 55
Content-Type: application/json

{
  "pattern": ".*\\.foo-bar\\.\\.\\.\"",
  "type": 33,
  "setNumber": 1
}
```

Response Structure

- id** The integral, unique identifier of this regular expression
- pattern** The actual regular expression - \s are escaped
- setNumber** The order in which the regular expression is evaluated against requests
- type** The integral, unique identifier of the type of this regular expression
- typeName** The type of regular expression - determines that against which it will be evaluated

289: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: kS5dRzAhFKE7vfzHK7XVIwpMOjztksk9MU+qtj5YU/
  ↳1oxVHmqNbJ12Fe00IJsZJCXbYlnBS04sCI95Sz5wed1Q==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 17:54:58 GMT
Content-Length: 188

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

        "text": "Delivery service regex creation was successful.",
        "level": "success"
    }
],
"response": {
    "id": 2,
    "type": 33,
    "typeName": "PATH_REGEX",
    "setNumber": 1,
    "pattern": ".*\\.foo-bar\\.\\.*"
}}

```

DELETE

Deletes a routing regular expression.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 423, 1}

Response Type undefined

Request Structure

Table 141: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected
rID	The integral, unique identifier of the routing regular expression being inspected

290: Request Example

```
DELETE /api/2.0/deliveryservices/1/regexes/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

291: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 8oEa78x7f/o39LIS98W6G+UqE6cX/
    ↳Iw4v3mMHvbAsliWHALuDYRz3V0tA6jzfGQKpB040m8qaVG+zWRrBVoCmQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 18:44:00 GMT
Content-Length: 76

{ "alerts": [
  {
    "text": "deliveryservice_regex was deleted.",
    "level": "success"
  }
]}
```

deliveryservices/{{ID}}/routing

GET

Retrieves the aggregated routing percentages for a given *Delivery Service*. This is accomplished by polling stats from all online Traffic Routers via the */crs/stats* route.

Auth. Required Yes

Roles Required None¹

¹ Users will only be able to view routing details for the *Delivery Services* their *Tenant* is allowed to see.

Response Type Object

Note: Only HTTP or DNS *Delivery Services* can be requested.

Request Structure

Table 142: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the <i>Delivery Service</i> of interest

292: Request Example

```
GET /api/2.0/deliveryservices/1/routing HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cz** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by a *Coverage Zone File*
- deepCz** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by a *Deep Coverage Zone File*
- dsr** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by sending the client to an overflow *Delivery Service*
- err** The percent of requests to online Traffic Routers for this *Delivery Service* that resulted in an error
- fed** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by sending the client to a federated CDN
- geo** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied using 3rd party geographic IP mapping
- miss** The percent of requests to online Traffic Routers for this *Delivery Service* that could not be satisfied
- regionalAlternate** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by sending the client to the alternate, Regional Geo-blocking URL
- regionalDenied** The percent of requests to online Traffic Routers for this *Delivery Service* that were denied due to geographic location policy

staticRoute The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied with *Static DNS Entries*

293: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Fri, 30 Nov 2018 15:08:07 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: UgPziRC/5u4+CfkZ9xm0EkEzjjJVu6cwBrFd/n3xH/
→ZmlkaXkQaa1y4+B7DyE46vxFLYE0OD0cQchyn7JkoQOg==
Content-Length: 132

{ "response": {
  "cz": 79,
  "deepCz": 0.50,
  "dsr": 0,
  "err": 0,
  "fed": 0.25,
  "geo": 20,
  "miss": 0.25,
  "regionalAlternate": 0,
  "regionalDenied": 0,
  "staticRoute": 0
}}
```

deliveryservices/{{ID}}/safe

PUT

Allows a user to edit metadata fields of a *Delivery Service*.

Auth. Required Yes

Roles Required None¹

Response Type Array

¹ Only those *Delivery Services* assigned to *Tenants* that are the requesting user's *Tenant* or children thereof may be modified with this endpoint.

Request Structure

Table 143: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being modified

displayName A string that is the *Display Name*

infoUrl An optional² string containing the *Info URL*

longDesc An optional² string containing the *Long Description* of this *Delivery Service*

longDesc1 An optional² string containing the 2nd long description of this *Delivery Service*

294: Request Example

```
PUT /api/2.0/deliveryservices/1/safe HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 132

{
  "displayName": "test",
  "infoUrl": "this is not even a real URL",
  "longDesc": "longDesc1 is implicitly set to null in this example"
}
```

Response Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

² If these fields are not present in the request body they are *implicitly set to null*.

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*

geoLimitRedirectUrl A *Geo Limit Redirect URL*

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 The 2nd long description of this *Delivery Service*

longDesc2 the 3rd long description of this *Delivery Service*

matchList The *Delivery Service*'s *Match List*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

setNumber An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

type The type of match performed using pattern.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId The *ID* of the *Profile* with which this *Delivery Service* is associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

signed true if and only if **signingAlgorithm** is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*

rangeSliceBlockSize An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if `rangeRequestHandling` is set to 3.

sslKeyVersion This integer indicates the *SSL Key Version*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service's* *xml_id*

295: Response Example

```
HTTP/1.1 200 OK
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 10 Feb 2020 16:33:03 GMT; Max-Age=3600; HttpOnly
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Feb 2020 15:33:03 GMT
Content-Length: 853

{ "alerts": [
  {
    "text": "Delivery Service safe update successful.",
    "level": "success"
  }
],
"response": [
  {
    "active": true,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "test",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
```

(continues on next page)

(continued from previous page)

```

    "dscp": 0,
    "edgeHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 1,
    "infoUrl": "this is not even a real URL",
    "initialDispersion": 1,
    "ipv6RoutingEnabled": true,
    "lastUpdated": "2020-02-10 15:33:03+00",
    "logsEnabled": true,
    "longDesc": "longDesc1 is implicitly set to null in this_
→example",
    "longDesc1": null,
    "longDesc2": null,
    "matchList": [
      {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
      }
    ],
    "maxDnsAnswers": null,
    "midHeaderRewrite": null,
    "missLat": 42,
    "missLong": -88,
    "multiSiteOrigin": false,
    "originShield": null,
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": 2,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": 1,
    "tenantId": 1,

```

(continues on next page)

(continued from previous page)

```

    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false,
    "rangeSliceBlockSize": null
  }
}]

```

`deliveryservices/{{ID}}/servers`

Caution: It's often much easier to use `deliveryservices/{{xml_id}}/servers` instead

GET

Retrieves properties of Edge-Tier servers assigned to a *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 144: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the Delivery service for which servers will be displayed

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId An integral, unique identifier the CDN to which the server belongs

cdnName The name of the CDN to which the server belongs

domainName The domain name part of the FQDN of the server

guid Optionally represents an identifier used to uniquely identify the server

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS requests - 443 in most cases

id An integral, unique identifier for the server

iloIpAddress The IPv4 address of the lights-out-management port¹

iloIpGateway The IPv4 gateway address of the lights-out-management port^{Page 423, 1}

iloIpNetmask The IPv4 subnet mask of the lights-out-management port^{Page 423, 1}

iloPassword The password of the of the lights-out-management user - displays as ***** unless the requesting user has the ‘admin’ role)^{Page 423, 1}

iloUsername The user name for lights-out-management^{Page 423, 1}

interfaceMtu The MTU to configure for **interfaceName**

See also:

[The Wikipedia article on Maximum Transmission Unit](#)

interfaceName The network interface name used by the server

ip6Address The IPv6 address and subnet mask of the server - applicable for the interface **interfaceName**

¹ See [the Wikipedia article on Out-of-Band Management](#) for more information.

ip6Gateway The IPv6 gateway address of the server - applicable for the interface `interfaceName`

ipAddress The IPv4 address of the server- applicable for the interface `interfaceName`

ipGateway The IPv4 gateway of the server- applicable for the interface `interfaceName`

ipNetmask The IPv4 subnet mask of the server- applicable for the interface `interfaceName`

lastUpdated The time and date at which this server was last updated, in *Traffic Ops's Custom Date/Time Format*

mgmtIpAddress The IPv4 address of the server's management port

mgmtIpGateway The IPv4 gateway of the server's management port

mgmtIpNetmask The IPv4 subnet mask of the server's management port

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status (will be empty if not offline)

physLocation The name of the *Physical Location* at which the server resides

physLocationId An integral, unique identifier for the *Physical Location* at which the server resides

profile The *Name* of the *Profile* assigned to this server

profileDesc A *Description* of the *Profile* assigned to this server

profileId The *ID* of the *Profile* assigned to this server

rack A string indicating "rack" location

routerHostName The human-readable name of the router

routerPortName The human-readable name of the router port

status The Status of the server

See also:

Health Protocol

statusId An integral, unique identifier for the status of the server

See also:

Health Protocol

tcpPort The default port on which the main application listens for incoming TCP connections - 80 in most cases

type The name of the type of this server

typeId An integral, unique identifier for the type of this server

updPending true if the server has updates pending, false otherwise

296: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: MaIva080Sjysr4bCkuXFEMf3o6mOqga1aM4IHN/
    ↳tcP2aaliXEmA5IrHB7DaqNX/2vGHLXvN+01FEAR/lRNqr1w==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:28:23 GMT
Content-Length: 891
```

```
{ "response": [
  {
    "cachegroup": "CDN_in_a_Box_Edge",
    "cachegroupId": 7,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "domainName": "infra.ciab.test",
    "guid": null,
    "hostName": "edge",
    "httpsPort": 443,
    "id": 10,
    "iloIpAddress": "",
    "iloIpGateway": "",
    "iloIpNetmask": "",
    "iloPassword": "",
    "iloUsername": "",
    "interfaceMtu": 1500,
    "interfaceName": "eth0",
    "ip6Address": "fc01:9400:1000:8::100",
    "ip6Gateway": "fc01:9400:1000:8::1",
    "ipAddress": "172.16.239.100",
    "ipGateway": "172.16.239.1",
    "ipNetmask": "255.255.255.0",
    "lastUpdated": "2018-11-14 21:08:44+00",
    "mgmtIpAddress": "",
    "mgmtIpGateway": "",
    "mgmtIpNetmask": "",
    "offlineReason": "",
    "physLocation": "Apachecon North America 2018",
    "physLocationId": 1,
```

(continues on next page)

(continued from previous page)

```

    "profile": "ATS_EDGE_TIER_CACHE",
    "profileDesc": "Edge Cache - Apache Traffic Server",
    "profileId": 9,
    "rack": "",
    "routerHostName": "",
    "routerPortName": "",
    "status": "REPORTED",
    "statusId": 3,
    "tcpPort": 80,
    "type": "EDGE",
    "typeId": 11,
    "updPending": false
  }
}]

```

deliveryservices/{{ID}}/servers/eligible

Caution: This endpoint may not work as advertised, and its use is therefore discouraged!

GET

Retrieves properties of *Edge-tier cache servers* eligible for assignment to a particular *Delivery Service*. Eligibility is determined based on the following properties:

- The name of the server's *Type* must match one of the glob patterns `EDGE*`, `ORG*`
- The server and *Delivery Service* must belong to the same CDN
- If the *Delivery Service* has *Required Capabilities*, an *Edge-tier cache server* must have all of those defined capabilities

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 145: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the Delivery service for which servers will be displayed

Response Structure

cachegroup A string which is the *Name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId An integral, unique identifier the CDN to which the server belongs

cdnName The name of the CDN to which the server belongs

domainName The domain name part of the FQDN of the server

guid Optionally represents an identifier used to uniquely identify the server

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS requests - 443 in most cases

id An integral, unique identifier for the server

iloIpAddress The IPv4 address of the lights-out-management port¹

iloIpGateway The IPv4 gateway address of the lights-out-management port^{Page 423, 1}

iloIpNetmask The IPv4 subnet mask of the lights-out-management port^{Page 423, 1}

iloPassword The password of the of the lights-out-management user - displays as ***** unless the requesting user has the 'admin' role)^{Page 423, 1}

iloUsername The user name for lights-out-management^{Page 423, 1}

interfaceMtu The MTU to configure for `interfaceName`

See also:

[The Wikipedia article on Maximum Transmission Unit](#)

interfaceName The network interface name used by the server

ip6Address The IPv6 address and subnet mask of the server - applicable for the interface `interfaceName`

ip6Gateway The IPv6 gateway address of the server - applicable for the interface `interfaceName`

ipAddress The IPv4 address of the server- applicable for the interface `interfaceName`

ipGateway The IPv4 gateway of the server- applicable for the interface `interfaceName`

ipNetmask The IPv4 subnet mask of the server- applicable for the interface `interfaceName`

¹ See [the Wikipedia article on Out-of-Band Management](#) for more information.

lastUpdated The time and date at which this server was last updated, in *Traffic Ops's Custom Date/Time Format*

mgmtIpAddress The IPv4 address of the server's management port

mgmtIpGateway The IPv4 gateway of the server's management port

mgmtIpNetmask The IPv4 subnet mask of the server's management port

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status (will be empty if not offline)

physLocation The name of the *Physical Location* at which the server resides

physLocationId An integral, unique identifier for the *Physical Location* at which the server resides

profile The *Name* of the *Profile* assigned to this server

profileDesc A *Description* of the *Profile* assigned to this server

profileId The *ID* of the *Profile* assigned to this server

rack A string indicating "rack" location

routerHostName The human-readable name of the router

routerPortName The human-readable name of the router port

status The Status of the server

See also:

Health Protocol

statusId An integral, unique identifier for the status of the server

See also:

Health Protocol

tcpPort The default port on which the main application listens for incoming TCP connections - 80 in most cases

type The name of the *Type* of this server

typeId An integral, unique identifier for the *Type* of this server

updPending true if the server has updates pending, false otherwise

297: Response Example

```
{ "response": [
  {
    "cachegroup": "CDN_in_a_Box_Edge",
    "cachegroupId": 7,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "domainName": "infra.ciab.test",
```

(continues on next page)

(continued from previous page)

```
"guid": null,
"hostname": "edge",
"httpsPort": 443,
"id": 10,
"iloIpAddress": "",
"iloIpGateway": "",
"iloIpNetmask": "",
"iloPassword": "",
"iloUsername": "",
"interfaceMtu": 1500,
"interfaceName": "eth0",
"ip6Address": "fc01:9400:1000:8::100",
"ip6Gateway": "fc01:9400:1000:8::1",
"ipAddress": "172.16.239.100",
"ipGateway": "172.16.239.1",
"ipNetmask": "255.255.255.0",
"lastUpdated": "2018-10-30 16:01:12+00",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_EDGE_TIER_CACHE",
"profileDesc": "Edge Cache - Apache Traffic Server",
"profileId": 9,
"rack": "",
"routerHostName": "",
"routerPortName": "",
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "EDGE",
"typeId": 11,
"updPending": false
}
}}
```

`deliveryservices/{{ID}}/urlkeys`

GET

See also:

`deliveryservices/xmlId/{{xmlid}}/urlkeys`

Retrieves URL signing keys for a *Delivery Service*.

Caution: This method will return the *Delivery Service*'s **PRIVATE** URL signing keys! Be wary of using this endpoint and **NEVER** share the output with anyone who would be unable to see it on their own.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 146: Request Path Parameters

Name	Description
id	Filter for the <i>Delivery Service</i> identified by this integral, unique identifier

298: Request Example

```
GET /api/2.0/deliveryservices/1/urlkeys HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

key<N> The private URL signing key for this *Delivery Service* as a base-64-encoded string, where <N> is the “generation” of the key e.g. the first key will always be named "key0". Up to 16 concurrent generations are retained at any time (<N> is always on the interval [0,15])

299: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 16:34:56
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: cTc5OPE3hM+CiyQPCy36zD2tsQcfkvIqQ7/
    ↳D82WGMWHm+ACW3YbcKhgPnSQU6+Tuj4jya52Kx9+nw5+OonFvPQ==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 15:34:56 GMT
Content-Length: 533

{
  "response": {
    "key0": "...",
    "key1": "...",
    "key2": "...",
    "key3": "...",
    "key4": "...",
    "key5": "...",
    "key6": "...",
    "key7": "...",
    "key8": "...",
    "key9": "...",
    "key10": "...",
    "key11": "...",
    "key12": "...",
    "key13": "...",
    "key14": "...",
    "key15": "...",
  }
}

```


deliveryservices_regexes

GET

Retrieves routing regular expressions for all *Delivery Services*.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

No parameters available

Response Structure

dsName The name of the *Delivery Service* represented by this object

regexes An array of objects that represent various routing regular expressions used by dsName

pattern The actual regular expression - \s are escaped

setNumber The order in which the regular expression is evaluated against requests

type The type of regular expression - determines that against which it will be evaluated

300: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +2MI+Q/NJqTizlMR/MhPAL+yu6/z/
  ↳Yqvo5fDO8F593RM0mK6dX/Al4wARbEG+HQAjNgSCRPSiLVATusrmnnCMA==
X-Server-Name: traffic_ops_golang/
Date: Tue, 27 Nov 2018 19:22:59 GMT
Content-Length: 110
```

(continues on next page)

¹ If tenancy is used, then users (regardless of role) will only be able to see the routing regular expressions used by *Delivery Services* their tenant has permissions to see.

(continued from previous page)

```
{ "response": [
  {
    "regexes": [
      {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
      }
    ],
    "dsName": "demo1"
  }
]}
```

deliveryservices/request

Note: This route does NOT do the same thing as *POST deliveryservice_requests*.

Deprecated since version ATCv6: This endpoint does not appear in Traffic Ops API version 4.0 - released with Apache Traffic Control version 6.0 - or later.

POST

Submits an emailed requesting that a *Delivery Service* be created.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type undefined

Request Structure

details An object describing the actual parameters for the Delivery Service request

customer Name of the customer associated with the *Delivery Service* - must only contain alphanumeric characters and the characters @, !, #, \$, %, ^, &, *, (,), [,], ., :kbd:`, and :kbd:-`

Changed in version ATCv6: Prior to ATC version 6, this field had no restrictions.

deepCachingType An optional string describing when to do Deep Caching for this *Delivery Service* - one of:

NEVER Never use deep caching (default)

ALWAYS Always use deep caching

deliveryProtocol The protocol used to retrieve content from the CDN - one of:

- http
- https
- http/https

hasNegativeCachingCustomization true if any customization is required for negative caching, false otherwise

hasOriginACLWhitelist true if access to the origin is restricted using an Access Control List (ACL or “whitelist”) of IP addresses

hasOriginDynamicRemap If true, this *Delivery Service* can dynamically map to multiple origin URLs

hasSignedURLs If true, this *Delivery Service*’s URLs are signed

headerRewriteEdge An optional string containing a header rewrite rule to be used at the Edge tier

headerRewriteMid An optional string containing a header rewrite rule to be used at the Mid tier

headerRewriteRedirectRouter An optional string containing a header re-write rule to be used by the Traffic Router

maxLibrarySizeEstimate A special string that describes the estimated size of the sum total of content available through this *Delivery Service*

negativeCachingCustomizationNote A note remarking on the use, customization, or complications associated with negative caching for this *Delivery Service*

notes An optional string containing additional instructions or notes regarding the Request

originHeaders An optional, comma-separated string of header values that must be passed to requests to the *Delivery Service*’s origin

originTestFile A URL path to a test file available on the *Delivery Service*’s origin server

originURL The URL of the *Delivery Service*’s origin server

otherOriginSecurity An optional string describing any and all other origin security measures that need to be considered

for access to the *Delivery Service*'s origin

overflowService An optional string containing the IP address or URL of an overflow point (used if rate limits are met or exceeded)

peakBPSEstimate A special string describing the estimated peak data transfer rate of the *Delivery Service* in Bytes Per Second (BPS)

peakTPSEstimate A special string describing the estimated peak transaction rate of the *Delivery Service* in Transactions Per Second (TPS)

queryStringHandling A special string describing how the *Delivery Service* should treat URLs containing query parameters

rangeRequestHandling A special string describing how the *Delivery Service* should handle range requests

rateLimitingGBPS An optional field which, if defined, should contain the maximum allowed data transfer rate for the *Delivery Service* in GigaBytes Per Second (GBPS)

rateLimitingTPS An optional field which, if defined, should contain the maximum allowed transaction rate for the *Delivery Service* in Transactions Per Second (TPS)

routingName An optional field which, if defined, should contain the routing name for the *Delivery Service*, e.g. `SomeRoutingName.DeliveryService_xml_id.CDNName.com`

routingType The *Delivery Service*'s routing type, should be one of:

HTTP The Traffic Router re-directs clients to *cache servers* using the HTTP 302 REDIRECT response code

DNS The Traffic Router responds to requests for name resolution of the *Delivery Service*'s routing name with IP addresses of *cache servers*

STEERING This *Delivery Service* routes clients to other *Delivery Services* - which will in turn (generally) route them to clients

ANY_MAP Some kind of undocumented black magic is used to get clients to... content, probably?

serviceAliases An optional array of aliases for this *Delivery Service*

serviceDesc A description of the *Delivery Service*

emailTo The email to which the Delivery Service request will be sent

301: Request Example

```
{ "emailTo": "foo@bar.com",
  "details": {
    "customer": "XYZ Corporation",
    "contentType": "static",
    "deepCachingType": "NEVER",
    "deliveryProtocol": "http",
    "routingType": "http",
    "routingName": "demo1",
    "serviceDesc": "service description goes here",
    "peakBPSEstimate": "less-than-5-Gbps",
    "peakTPSEstimate": "less-than-1000-TPS",
    "maxLibrarySizeEstimate": "less-than-200-GB",
    "originURL": "http://myorigin.com",
    "hasOriginDynamicRemap": false,
    "originTestFile": "http://origin.infra.ciab.test",
    "hasOriginACLWhitelist": false,
    "originHeaders": "",
    "otherOriginSecurity": "",
    "queryStringHandling": "ignore-in-cache-key-and-pass-up",
    "rangeRequestHandling": "range-requests-not-used",
    "hasSignedURLs": false,
    "hasNegativeCachingCustomization": false,
    "negativeCachingCustomizationNote": "",
    "serviceAliases": [],
    "rateLimitingGBPS": 50,
    "rateLimitingTPS": 5000,
    "overflowService": null,
    "headerRewriteEdge": "",
    "headerRewriteMid": "",
    "headerRewriteRedirectRouter": "",
    "notes": ""
  }
}
```

Response Structure

302: Response Example

```
{ "alerts": [{
  "level": "success",
  "text": "Delivery Service request sent to foo@bar.com."
}]}
```

deliveryservices_required_capabilities

GET

Gets all associations of *Server Capability* to *Delivery Services*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 147: Request Query Parameters

Name	Re-quired	Description
delivery-Servi-ceID	no	Filter <i>Server Capability</i> associations by <i>Delivery Service</i> integral, unique identifier
xml-ID	no	Filter <i>Server Capability</i> associations by <i>Delivery Service xml_id</i>
re-quired-Capa-bility	no	Filter <i>Server Capability</i> associations by <i>Server Capability</i> name
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

303: Request Example

```
GET /api/2.0/deliveryservices_required_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

deliveryServiceID The associated *Delivery Service*'s integral, unique identifier

xmlID The associated *Delivery Service*'s *xml_id*

lastUpdated The date and time at which this association between the *Delivery Service* and the *Server Capability* was last updated, in *Traffic Ops's Custom Date/Time Format*

requiredCapability The *Server Capability*'s name

304: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
→jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
→DbBwhMAOJoeqDImoDlrLnrVjQG04AooA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 396

{
  "response": [
    {
      "deliveryServiceID": 1,
      "lastUpdated": "2019-10-07 22:05:31+00",
      "requiredCapability": "ram",
      "xmlId": "example_ds-1"
    },
    {
      "deliveryServiceID": 2,
      "lastUpdated": "2019-10-07 22:05:31+00",
      "requiredCapability": "disk",
      "xmlId": "example_ds-2"
    }
  ]
}
```

POST

Associates a *Server Capability* with a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Note: A *Server Capability* can only be made required on a *Delivery Service* if its associated Servers already have that *Server Capability* assigned.

Request Structure

deliveryServiceID The integral, unique identifier of the *Delivery Service* to be associated

requiredCapability The name of the *Server Capability* to be associated

305: Request Example

```
POST /api/2.0/deliveryservices_required_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "deliveryServiceID": 1,
  "requiredCapability": "disk"
}
```

Response Structure

deliveryServiceID The newly associated *Delivery Service*’s integral, unique identifier

lastUpdated The date and time at which this association between the *Delivery Service* and the *Server Capability* was last updated, in *Traffic Ops’s Custom Date/Time Format*

requiredCapability The newly associated *Server Capability*’s name

306: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳eQrl48zWids0kDpfCYmntYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
    ↳Cfh2X9i3G+MQ36eH95gukJq0BOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 287

{
  "alerts": [
    {
      "level": "success",
      "text": "deliveryservice.RequiredCapability was created."
    }
  ],
  "response": {
    "deliveryServiceID": 1,
    "lastUpdated": "2019-10-07 22:15:11+00",
    "requiredCapability": "disk"
  }
}
```

DELETE

Dissociate a *Server Capability* from a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

deliveryServiceID The integral, unique identifier of the *Delivery Service* from which a *Server Capability* will be dissociated

requiredCapability The name of the *Server Capability* to dissociate

307: Request Example

```
POST /api/2.0/deliveryservices_required_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "deliveryServiceID": 1,
  "requiredCapability": "disk"
}
```

Response Structure

308: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳eQrl48zWids0kDpfCYmmtYMpegjnFxfOVvlBYxxLSfp7P7p6oWX4uiC+/
  ↳Cfh2X9i3G+MQ36eH95gukJqOBOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 127

{
  "alerts": [
    {
      "level": "success",
      "text": "deliveryservice.RequiredCapability was deleted."
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```

    }
  ]
}
```

deliveryservices/sslkeys/add

See also:

In most cases it is preferable to allow Traffic Ops to generate the keys via [deliveryservices/sslkeys/generate](#), rather than uploading them manually using this endpoint.

POST

Allows user to upload an SSL certificate, csr, and private key for a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

cdn The name of the CDN to which the *Delivery Service* belongs

certificate An object that contains the actual components of the SSL key

crt The certificate for the *Delivery Service* identified by key

csr The csr file for the *Delivery Service* identified by key

key The private key for the *Delivery Service* identified by key

key The *xml_id* of the *Delivery Service* to which these keys will be assigned

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

309: Request Example

```

POST /api/2.0/deliveryservices/sslkeys/add HTTP/1.1
Host: trafficops.infra.ciab.test
Content-Type: application/json

{
  "key": "ds-01",
  "version": "1",
```

(continues on next page)

(continued from previous page)

```
"certificate": {
  "key": "some_key",
  "csr": "some_csr",
  "crt": "some_crt"
}
```

Response Structure

310: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "response": "Successfully added ssl keys for ds-01"
}
```

deliveryservices/sslkeys/generate

POST

Generates an SSL certificate, csr, and private key for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

city An optional field which, if present, will represent the resident city of the generated SSL certificate

country An optional field which, if present, will represent the resident country of the generated SSL certificate

hostname The desired hostname of the *Delivery Service*

Note: In most cases, this must be the same as the *Delivery Service* URL’

key The *xml_id* of the *Delivery Service* for which keys will be generated

organization An optional field which, if present, will represent the organization for which the SSL certificate was generated

state An optional field which, if present, will represent the resident state or province of the generated SSL certificate

businessUnit An optional field which, if present, will represent the business unit for which the SSL certificate was generated

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

311: Request Example

```
POST /api/2.0/deliveryservices/sslkeys/generate HTTP/1.1
Content-Type: application/json

{
  "key": "ds-01",
  "businessUnit": "CDN Engineering",
  "version": "3",
  "hostname": "tr.ds-01.ott.kabletown.com",
  "country": "US",
  "organization": "Kabletown",
  "city": "Denver",
  "state": "Colorado"
}
```

Response Structure

312: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": "Successfully created ssl keys for ds-01" }
```

deliveryservices/sslkeys/generate/letsencrypt

POST

Generates an SSL certificate and private key using Let’s Encrypt for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

key The *xml_id* of the *Delivery Service* for which keys will be generated¹

deliveryservice The *xml_id* of the *Delivery Service* for which keys will be generated^{Page 609, 1}

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

hostname The desired hostname of the *Delivery Service*

Note: In most cases, this must be the same as the *Example URLs*.

cdn The name of the CDN of the *Delivery Service* for which the certs will be generated

313: Request Example

```
POST /api/2.0/deliveryservices/sslkeys/generate/letsencrypt HTTP/1.1
Content-Type: application/json

{
  "key": "ds-01",
  "deliveryservice": "ds-01",
  "version": "3",
  "hostname": "tr.ds-01.ott.kabletown.com",
  "cdn": "test-cdn"
}
```

Response Structure

¹ Either the key or the deliveryservice field must be provided. If both are provided, then they must match.

314: Response Example

```
{ "alerts": [{
  "level": "success",
  "text": "Beginning async ACME call for demo1 using Lets Encrypt.
→ This may take a few minutes. Status updates can be found here: /api/
→ 4.0/async_status/1"
}]}
```

deliveryservices/{xml_id}/servers

POST

Assigns *cache servers* to a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type Object

Request Structure

Table 148: Request Path Parameters

Name	Description
xml_id	The ‘xml_id’ of the <i>Delivery Service</i> whose server assignments are being edited

serverNames An array of hostname of *cache servers* to assign to this *Delivery Service*

315: Request Example

```
POST /api/2.0/deliveryservices/test/servers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 24
Content-Type: application/json

{ "serverNames": [ "edge" ] }
```

¹ Users can only assign servers to *Delivery Services* that are visible to their *Tenant*.

Response Structure

xml_id The *xml_id* of the *Delivery Service* to which the servers in **serverNames** have been assigned

serverNames An array of hostnames of *cache servers* assigned to *Delivery Service* identified by **xml_id**

316: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳zTpLrWiLM4xRsm8mlBQFB5KzT478AjloSyXHgtyWhebCv1YIwWltnmkjr0HFgc3GMGZODt+fyzk0Yy5Zl/
    ↳yBtJw==
X-Server-Name: traffic_ops_golang/
Date: Tue, 20 Nov 2018 15:21:50 GMT
Content-Length: 52

{ "response": {
  "serverNames": [
    "edge"
  ],
  "xmlId": "test"
}}
```

deliveryservices/{xml_id}/urisignkeys

DELETE

Deletes URISigning objects for a *Delivery Service*.

Auth. Required Yes

Roles Required admin¹

Response Type undefined

¹ URI Signing Keys can only be created, viewed, deleted, or modified on *Delivery Services* that either match the requesting user's *Tenant* or are descendants thereof.

Request Structure

Table 149: Request Path Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Response Structure

TBD

GET

Retrieves one or more URISigning objects for a delivery service.

Auth. Required Yes

Roles Required admin Page 609, 1

Response Type undefined

Request Structure

Table 150: Request Route Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Response Structure

Issuer a string describing the issuer of the URI signing object. Multiple URISigning objects may be returned in a response, see example

renewal_kid a string naming the jwt key used for renewals

keys json array of jwt symmetric keys

alg this parameter repeats for each jwt key in the array and specifies the jwa encryption algorithm to use with this key, **RFC 7518**

kid this parameter repeats for each jwt key in the array and specifies the unique id for the key as defined in **RFC 7516**

key this parameter repeats for each jwt key in the array and specifies the key type as defined in **RFC 7516**

k this parameter repeats for each jwt key in the array and specifies the base64 encoded symmetric key see **RFC 7516**

317: Response Example

```
{ "Kabletown URI Authority": {
  "renewal_kid": "Second Key",
  "keys": [
    {
      "alg": "HS256",
      "kid": "First Key",
      "kty": "oct",
      "k": "Kh_RkUMj-fzbD37qBnDf_3e_RvQ3RP9PaSmVEpE24AM"
    },
    {
      "alg": "HS256",
      "kid": "Second Key",
      "kty": "oct",
      "k": "fZBpDBNbk2GqhwoB_DGBAsBxqQZVix04rIoLJ7p_RlE"
    }
  ]
}}
```

POST

Assigns URISigning objects to a delivery service.

Auth. Required Yes

Roles Required admin Page 609, 1

Response Type undefined

Request Structure

Table 151: Request Path Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Request Structure

Issuer a string describing the issuer of the URI signing object. Multiple URISigning objects may be returned in a response, see example

renewal_kid a string naming the jwt key used for renewals

keys json array of jwt symmetric keys

- alg** this parameter repeats for each jwt key in the array and specifies the jwa encryption algorithm to use with this key, [RFC 7518](#)
- kid** this parameter repeats for each jwt key in the array and specifies the unique id for the key as defined in [RFC 7516](#)
- kt** this parameter repeats for each jwt key in the array and specifies the key type as defined in [RFC 7516](#)
- k** this parameter repeats for each jwt key in the array and specifies the base64 encoded symmetric key see [RFC 7516](#)

318: Request Example

```
{ "Kabletown URI Authority": {
  "renewal_kid": "Second Key",
  "keys": [
    {
      "alg": "HS256",
      "kid": "First Key",
      "kty": "oct",
      "k": "Kh_RkUMj-fzbD37qBnDf_3e_RvQ3RP9PaSmVEpE24AM"
    },
    {
      "alg": "HS256",
      "kid": "Second Key",
      "kty": "oct",
      "k": "fZBpDBNbk2GqhwoB_DGBAsBxqQZVix04rIoLJ7p_RlE"
    }
  ]
}}
```

PUT

updates URISigning objects on a delivery service.

Auth. Required Yes

Roles Required admin Page 609, 1

Response Type undefined

Request Structure

Table 152: Request Path Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Request Structure

Issuer a string describing the issuer of the URI signing object. Multiple URISigning objects may be returned in a response, see example

renewal_kid a string naming the jwt key used for renewals

keys json array of jwt symmetric keys

alg this parameter repeats for each jwt key in the array and specifies the jwa encryption algorithm to use with this key, [RFC 7518](#)

kid this parameter repeats for each jwt key in the array and specifies the unique id for the key as defined in [RFC 7516](#)

kty this parameter repeats for each jwt key in the array and specifies the key type as defined in [RFC 7516](#)

k this parameter repeats for each jwt key in the array and specifies the base64 encoded symmetric key see [RFC 7516](#)

319: Request Example

```
{ "Kabletown URI Authority": {
  "renewal_kid": "Second Key",
  "keys": [
    {
      "alg": "HS256",
      "kid": "First Key",
      "kty": "oct",
      "k": "Kh_RkUMj-fzbD37qBnDf_3e_RvQ3RP9PaSmVEpE24AM"
    },
    {
      "alg": "HS256",
      "kid": "Second Key",
      "kty": "oct",
      "k": "fZBpDBNbk2GqhwoB_DGBAsBxqQZVix04rIoLJ7p_RlE"
    }
  ]
}}
```

`deliveryservices/xmlId/{XMLID}/sslkeys`

GET

Retrieves SSL keys for a *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 153: Request Path Parameters

Name	Description
XMLID	The ‘xml_id’ of the desired <i>Delivery Service</i>

Table 154: Request Query Parameters

Name	Re-quired	Description
ver-sion	no	The version number of the SSL keys to retrieve
de-code	no	If <code>true</code> , the returned keys will be decoded - if <code>false</code> , they will not be decoded

Caution: There’s almost certainly no good reason to request the private key! Even when “base 64-encoded” do not let **ANYONE** see this who would be unable to request it themselves!

Response Structure

businessUnit An optional field which, if present, contains the business unit entered by the user when generating the SSL certificate¹

certificate An object containing the actual generated key, certificate, and signature of the SSL keys

crt Base 64-encoded (or not if the decode query parameter was given and `true`) certificate for the *Delivery Service* identified by `deliveryservice`

¹ These optional fields will be present in the response if and only if they were specified during key generation; they are optional during key generation and thus cannot be guaranteed to exist or not exist.

csr Base 64-encoded (or not if the decode query parameter was given and true) csr file for the *Delivery Service* identified by deliveryservice

key Base 64-encoded (or not if the decode query parameter was given and true) private key for the *Delivery Service* identified by deliveryservice

Caution: There's almost certainly no good reason to request the private key! Even when "base 64-encoded" do not let **ANYONE** see this who would be unable to request it themselves!

cdn The CDN of the *Delivery Service* for which the certs were generated

city An optional field which, if present, contains the city entered by the user when generating the SSL certificate^{Page 629, 1}

country An optional field which, if present, contains the country entered by the user when generating the SSL certificate^{Page 629, 1}

deliveryservice The 'xml_id' of the *Delivery Service* for which the certificate was generated

hostname The hostname generated by Traffic Ops that is used as the common name when generating the certificate - this will be a FQDN for DNS *Delivery Services* and a wildcard URL for HTTP *Delivery Services*

organization An optional field which, if present, contains the organization entered by the user when generating certificate^{Page 629, 1}

state An optional field which, if present, contains the state entered by the user when generating certificate^{Page 629, 1}

version An integer that defines the "version" of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

expiration The expiration date of the certificate for the *Delivery Service* in **RFC 3339** format

320: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json
```

```
{ "response": {
  "certificate": {
    "crt": "crt",
    "key": "key",
    "csr": "csr"
  },

```

(continues on next page)

(continued from previous page)

```

"deliveryservice": "my-ds",
"cdn": "qa",
"businessUnit": "CDN_Eng",
"city": "Denver",
"organization": "KableTown",
"hostname": "foober.com",
"country": "US",
"state": "Colorado",
"version": "1",
"expiration": "2020-08-18T13:53:06Z"
}}

```

DELETE

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 155: Request Path Parameters

Name	Required	Description
xmlId	yes	The <i>xml_id</i> of the desired <i>Delivery Service</i>

Table 156: Request Query Parameters

Name	Required	Description
version	no	The version number of the SSL keys that shall be retrieved

Response Structure

321: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip

```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 18 Mar 2020 17:36:10 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Pj+zCoOXg19nGNxcSkjib2iDjG062Y3RcEEV+0YnwbGIsLcpa0BKZleY/qJOKT5DkSoX2qQkckUxUqdDxjVorQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 18 Mar 2020 16:36:10 GMT
Content-Length: 79

{
  "response": "Successfully deleted ssl keys for demo1"
}
```

`deliveryservices/xmlId/{xmlid}/urlkeys`

GET

See also:

deliveryservices/{ID}/urlkeys

Retrieves URL signing keys for a *Delivery Service*.

Caution: This method will return the *Delivery Service*'s **PRIVATE** URL signing keys! Be wary of using this endpoint and **NEVER** share the output with anyone who would be unable to see it on their own.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 157: Request Path Parameters

Name	Description
xmlid	The 'xml_id' of the desired <i>Delivery Service</i>

Response Structure

key<N> The private URL signing key for this *Delivery Service* as a base-64-encoded string, where <N> is the “generation” of the key e.g. the first key will always be named **key0**. Up to 16 concurrent generations are retained at any time (<N> is always on the interval [0,15])

322: Response Example

```
{ "response": {
  "key9": "ZvVQNYpPVQWQV8tjQnUl6osm4y7xK4zD",
  "key6": "JhGdpw5X9o8TqHfgezCm0bqb9SQPASWL",
  "key8": "ySXdp1T8IeDEE10CMftzZb9EIw_20wwq",
  "key0": "D4AYzJ1AE2nYisA9MxMtY03TPDCHji9C",
  "key3": "W90YHlGc_kYlYw5_I0LrkpV9J0zSIneI",
  "key12": "ZbtMb3mrKqfS8hnx9_xWBIP_OPWlUpzc",
  "key2": "0qgEoD07sUsugIQemZbwmMt0tNCwB1sf",
  "key4": "aFJ2Gb7atmxVB8uv7T9S60aDml3ycpGf",
  "key1": "wnWNR1mCz104C7EFPtcqHd0xUMQyNFhA",
  "key11": "k6HMz1BH1x6htKkypRFfWQhAndQqe50e",
  "key10": "zYONfdD7fGYKj4kLvIj4U0918csuZ00d",
  "key15": "3360cGaIip_layZMc_0hI2teJbazxTQh",
  "key5": "SIwv3G0hWN7EE9wSwPFj18qE4M07sFxF",
  "key13": "SqQKBR6LqE0zp8AewZUCVtBcW_8YFc1g",
  "key14": "DtXsu8nsw04YhT0kNoKBhu2G3P9WRpQJ",
  "key7": "cmKoIIxXGAxUMdCsWvnGLoIMGmNiuT5I"
}}
```

deliveryservices/xmlId/{xml_id}/urlkeys/copyFromXmlId/
{{copyFrom_xml_id}}

POST

Allows a user to copy URL signing keys from a specified *Delivery Service* to another *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 158: Request Path Parameters

Name	Description
xml_id	The <i>xml_id</i> of the <i>Delivery Service</i> to which keys will be copied
copyFrom_xml_id	The <i>xml_id</i> of the <i>Delivery Service</i> from which keys will be copied

Response Structure

323: Response Example

```
{
  "response": "Successfully copied and stored keys"
}
```

deliveryservices/xmlId/{xml_id}/urlkeys/generate

POST

Generates URL signing keys for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 159: Request Path Parameters

Name	Description
xml_id	The <i>xml_id</i> of the desired <i>Delivery Service</i>

Response Structure

324: Response Example

```
{
  "response": "Successfully generated and stored keys"
}
```

deliveryserviceserver

GET

Retrieve information about the assignment of servers to *Delivery Services*

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 160: Request Query Parameters

Name	Re-quired	Default	Description
page	no	0	The page number for use in pagination - 0 means “no pagination”
limit	no	20	Limits the results to a maximum of this number - if pagination is used, this defines the number of results per page
or-derby	no	“deliv-eryser-vice”	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array

325: Request Example

```
GET /api/2.0/deliveryserviceserver?page=1&limit=2&orderby=lastUpdated.
→HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

Unlike most API endpoints, this will return a JSON response body containing both a “response” object as well as other, top-level fields (besides the optional “alerts” field). For this reason, this section contains a “response” key, which normally is implicit.

See also:

Response Structure

limit The maximum size of the response array, also indicative of the number of results per page using the pagination requested by the query parameters (if any) - this should be the same as the `limit` query parameter (if given)

¹ While no roles are required, this endpoint *does* respect tenancy permissions (pending [GitHub Issue #2978](#)).

orderby A string that names the field by which the elements of the response array are ordered - should be the same as the `orderby` request query parameter (if given)

response An array of objects, each of which represents a server's *Delivery Service* assignment

deliveryService The integral, unique identifier of the *Delivery Service* to which the server identified by `server` is assigned

lastUpdated The date and time at which the server's assignment to a *Delivery Service* was last updated

server The integral, unique identifier of a server which is assigned to the *Delivery Service* identified by `deliveryService`

size The page number - if pagination was requested in the query parameters, else 0 to indicate no pagination - of the results represented by the response array. This is named "size" for legacy reasons

326: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: J7sK8PohQWyTpTrMjJrWdlJwPj+Zyep/
    ↳xutM25uVosL6cHgi30nXa6VMYOC5Y3vd9r5KLES8rTgR+qUQcZcJ/A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 01 Nov 2018 14:27:45 GMT
Content-Length: 129

{ "orderby": "lastUpdated",
  "response": [
    {
      "server": 8,
      "deliveryService": 1,
      "lastUpdated": "2018-11-01 14:10:38+00"
    }
  ],
  "size": 1,
  "limit": 2
}
```

POST

Assign a set of one or more servers to a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”²

Response Type Object

Request Structure

dsId The integral, unique identifier of the *Delivery Service* to which the servers identified in the `servers` array will be assigned

replace If true, any existing assignments for a server identified in the `servers` array will be overwritten by this request

servers An array of integral, unique identifiers for servers which are to be assigned to the *Delivery Service* identified by `deliveryService`

327: Request Example

```
POST /api/2.0/deliveryserviceserver HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 46
Content-Type: application/x-www-form-urlencoded

dsId=1&replace=true&servers=12
```

Response Structure

dsId The integral, unique identifier of the *Delivery Service* to which the servers identified by the elements of the `servers` array have been assigned

replace If true, any existing assignments for a server identified in the `servers` array have been overwritten by this request

servers An array of integral, unique identifiers for servers which have been assigned to the *Delivery Service* identified by `deliveryService`

² Users with the “admin” or “operations” roles will be able to modify ALL server-to-Delivery-Service assignments, whereas all other users can only assign servers to the *Delivery Services* their Tenant has permissions to edit.

328: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳D+HhGhozxaxvka9vZIStoa0ZUpX23nz7zZnMbpFHNRO3MawyEaSb3GVUHQyCv6sDgwhpZZjRggDmctGCw
X-Server-Name: traffic_ops_golang/
Date: Thu, 01 Nov 2018 14:12:49 GMT
Content-Length: 123

{ "alerts": [
  {
    "text": "server assignments complete",
    "level": "success"
  }
],
"response": {
  "dsId": 1,
  "replace": false,
  "servers": [ 12 ]
}}
```

`deliveryserviceserver/{{DSID}}/{{serverID}}`

DELETE

Removes a *cache server* from a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type undefined

¹ Users with the “admin” or “operations” roles will be able to delete *any Delivery Service*, whereas other users will only be able to delete *Delivery Services* that their tenant has permissions to delete.

Request Structure

Table 161: Request Path Parameters

Name	Required	Description
dsId	yes	An integral, unique identifier for a <i>Delivery Service</i>
serverID	yes	An integral, unique identifier for a server

Note: The server identified by serverID must be a *cache server*, or the assignment will fail.

Response Structure

329: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: rGD2sOMHYF0sga1zuTytyLHCUkkc3ZwQRKvZ/
    ↳HuPzObOP4WztKTOVXB4uhs3iJqBg9zRB2TucMxONHN+3/yShQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 01 Nov 2018 14:24:34 GMT
Content-Length: 80

{ "alerts": [
  {
    "text": "Server unlinked from delivery service.",
    "level": "success"
  }
]}
```

divisions

GET

Returns a JSON representation of all configured *Divisions*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 162: Request Query Parameters

Name	Description
id	Filter for <i>Divisions</i> having this integral, unique identifier
name	Filter for <i>Divisions</i> with this name
orderby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

id An integral, unique identifier for this Division

lastUpdated The date and time at which this Division was last modified, in *Traffic Ops’s Custom Date/Time Format*

name The Division name

330: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→SLKi9RHa67sGoSz62IDcQsk7KZjTXKfonqMoCUFPXGcNUdhBssvUjc1G7KkWK8X1Ny16geMx2BN8Hm/
→3dQ75GA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 19:44:03 GMT
Content-Length: 139

{ "response": [
  {
    "id": 1,
    "lastUpdated": "2018-11-29 18:38:28+00",
    "name": "Quebec"
  },
  {
    "id": 2,
    "lastUpdated": "2018-11-29 18:38:28+00",
    "name": "USA"
  }
]}
```

POST

Creates a new Division.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the new Division

331: Request Example

```
POST /api/2.0/divisions HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 16
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
{"name": "test"}
```

Response Structure

id An integral, unique identifier for this Division

lastUpdated The date and time at which this Division was last modified, in *Traffic Ops's Custom Date/Time Format*

name The Division name

332: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +pJm4c30+JTaSXNt+LP+u240Ba/
→SsvSSDOQ4rDc6hcyZ0FIL+iY/WWrMHhpLulRGKGY88bM4YPCMaxGn3FZ9yQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 19:52:06 GMT
Content-Length: 136

{ "alerts": [
  {
    "text": "division was created.",
    "level": "success"
  }
],
"response": {
  "id": 3,
  "lastUpdated": "2018-11-29 19:52:06+00",
  "name": "test"
}}
```

`divisions/{ID}`

PUT

Updates a specific Division

Auth. Required Yes

Roles Required “admin” or “operations”

Request Structure

Table 163: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the requested Division

name The new name of the Division

333: Request Example

```
PUT /api/2.0/divisions/3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 17
Content-Type: application/json

{"name": "quest"}
```

Response Structure

id An integral, unique identifier for this Division

lastUpdated The date and time at which this Division was last modified, in *Traffic Ops's Custom Date/Time Format*

name The Division name

334: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: yBd8MzBR/Qbc/
→xTs44WEIFRTrqeMKZwUe2ufpm6JH6frh1UjFmYRs3/
→B7E5FTruFWRTuvEIlx5EpDmp3f9LjzA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 20:10:36 GMT
Content-Length: 137

{ "alerts": [
  {
    "text": "division was updated.",
    "level": "success"
  }
],
"response": {
  "id": 3,
  "lastUpdated": "2018-11-29 20:10:36+00",
  "name": "quest"
}}
```

federation_resolvers

GET

Retrieves *Federation* Resolvers.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 164: Request Query Parameters

Name	Re-quired	Description
id	no	Return only the Federation Resolver identified by this integral, unique identifier
ipAd- dress	no	Return only the Federation Resolver(s) that has/have this IP Address
type	no	Return only the Federation Resolvers of this <i>Type</i>
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
off- set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

335: Request Example

```
GET /api/2.0/federation_resolvers?type=RESOLVE6 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.63.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

id The integral, unique identifier of the resolver

ipAddress The IP address or CIDR-notation subnet of the resolver - may be IPv4 or IPv6

lastUpdated The date and time at which this resolver was last updated, in *Traffic Ops’s Custom Date/Time Format*

type The *Type* of the resolver

336: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→4TLkULAOAuap47H+hpwyf2lHjDbHbSNQHLmj7BCTHtps2CQxCuq7mwctbwqmPdmAjLOUXAIRsHmvSuAp4
X-Server-Name: traffic_ops_golang/
Date: Wed, 06 Nov 2019 00:03:56 GMT
Content-Length: 101

{ "response": [
  {
    "id": 1,
    "ipAddress": "::1/1",
    "lastUpdated": "2019-11-06 00:00:40+00",
    "type": "RESOLVE6"
  }
]}
```

POST

Creates a new federation resolver.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

ipAddress The IP address of the resolver - may be IPv4 or IPv6

typeId The integral, unique identifier of the *Type* of resolver being created

Caution: This field should only ever be an identifier for one of the *Types* “RESOLVE4” or “RESOLVE6”, but there is **no protection for this built into Traffic Ops** and therefore **any valid *Type* identifier will be silently accepted by Traffic Ops** and so care should be taken to ensure that these *Types* are properly identified. If any *Type* besides “RESOLVE4” or “RESOLVE6” is identified, the resulting resolver *will not work*.

See also:

types is the endpoint that can be used to determine the identifier for various

Types

337: Request Example

```
POST /api/2.0/federation_resolvers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.63.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 36
Content-Type: application/json

{
  "ipAddress": "::1/1",
  "typeId": 37
}
```

Response Structure

id The integral, unique identifier of the resolver

ipAddress The IP address or CIDR-notation subnet of the resolver - may be IPv4 or IPv6

type The *Type* of the resolver

typeId The integral, unique identifier of the *Type* of the resolver

338: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳e9D8JNrQb64xpuDwoBwbISSWUkDGCL2l37NuDXsXsPYof2EqmeHondD8NzxDSwWNJ8d9B9DXpZDbRUtgd
X-Server-Name: traffic_ops_golang/
Date: Wed, 06 Nov 2019 00:00:40 GMT
Content-Length: 153

{ "alerts": [
  {
    "text": "Federation Resolver created [ IP = ::1/1 ] with id: 1
  },
```

(continues on next page)

(continued from previous page)

```

        "level": "success"
      }
    ],
    "response": {
      "id": 1,
      "ipAddress": "::1/1",
      "type": "RESOLVE6",
      "typeId": 37
    }
  }
}
```

DELETE

Deletes a federation resolver.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 165: Request Query Parameters

Name	Required	Description
id	yes	Integral, unique identifier for the federation resolver to be deleted

339: Request Example

```
DELETE /api/2.0/federation_resolvers?id=4 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

id The integral, unique identifier of the resolver

ipAddress The IP address or CIDR-notation subnet of the resolver - may be IPv4 or IPv6

type The *Type* of the resolver

340: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; HttpOnly
Whole-Content-Sha512:
→2v4LYQdRVhaFJVd86Iv1BWVYzNPSlzpQ222bUB7Zz+Ss8A48FNyHZjPlq5a+a4g9KAQCTUIytWnIQk+L1
X-Server-Name: traffic_ops_golang/
Date: Fri, 08 Nov 2019 23:19:01 GMT
Content-Length: 161

{ "alerts": [
  {
    "text": "Federation resolver deleted [ IP = 1.2.6.4/22 ] with
→id: 4",
    "level": "success"
  }
],
"response": {
  "id": 4,
  "ipAddress": "1.2.6.4/22",
```

(continues on next page)

(continued from previous page)

```
"type": "RESOLVE6"
}}
```

federations

GET

Retrieves a list of *Federation* mappings (i.e. *Federation* Resolvers) for the current user.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Array

Request Structure

No parameters available.

Response Structure

deliveryService The `xml_id` that uniquely identifies the *Delivery Service* that uses the federation mappings in `mappings`

mappings An array of objects that represent the mapping of a *Federation*’s CNAME to one or more Resolvers

cname The actual CNAME used by the *Federation*

resolve4 An array of IPv4 addresses (or subnets in CIDR notation) capable of resolving the *Federation*’s CNAME

resolve6 An array of IPv6 addresses (or subnets in CIDR notation) capable of resolving the *Federation*’s CNAME

ttd The TTL of the CNAME in hours

341: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512:↵
↵d6Llm5qNc2sfgVH9IimW7hA4wvtBUq6EzUmpJf805kB0k6v2WysNgFEWK4hBXNdAYkr8hYuKPrwDy3tCx
X-Server-Name: traffic_ops_golang/
Date: Mon, 03 Dec 2018 17:19:13 GMT
Content-Length: 136

{ "response": [
  {
    "mappings": [
      {
        "ttl": 300,
        "cname": "blah.blah.",
        "resolve4": [
          "0.0.0.0/32"
        ],
        "resolve6": [
          "::/128"
        ]
      }
    ],
    "deliveryService": "demo1"
  }
]}
```

POST

Allows a user to create *Federation* Resolvers for *Delivery Services*, providing the *Delivery Service* is within a CDN that has some associated *Federation*.

Warning: Confusingly, this method of this endpoint does **not** create a new *Federation*; to do that, the *cdns/{name}/federations* endpoint must be used. Furthermore, the *Federation* must properly be assigned to a *Delivery Service* using the *federations/{ID}/deliveryservices* and assigned to the user creating Resolvers using *federations/{ID}/users*.

See also:

The *federations/{ID}/federation_resolvers* endpoint duplicates this functionality.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

The request payload is an array of objects that describe Delivery Service *Federation* Resolver mappings. Each object in the array must be in the following format.

deliveryService The *xml_id* of the *Delivery Service* which will use the *Federation* Resolvers specified in mappings

mappings An object containing two arrays of IP addresses (or subnets in CIDR notation) to use as *Federation* Resolvers

resolve4 An array of IPv4 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service's Federation*

resolve6 An array of IPv6 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service's Federation*

342: Request Example

```
POST /api/2.0/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 118
Content-Type: application/json

[{"deliveryService": "demo1",
  "mappings": {
    "resolve4": ["127.0.0.1", "0.0.0.0/32"],
    "resolve6": ["::1", "5efa::ff00/128"]
  }
}]
```

Response Structure

343: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: B7TSUOYZPRPyi3mVy+CuxiXR5k/
→d0s07w4i6kYzpWS+YL79juEfkusqfedayG/kMA809XbjkWRjcBAdxOVrdTQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 23 Oct 2019 22:28:02 GMT
Content-Length: 152

{ "alerts": [
  {
    "text": "admin successfully created federation resolvers.",
    "level": "success"
  }
],
"response": "admin successfully created federation resolvers."
}
```

DELETE

Deletes **all** *Federation* Resolvers associated with the logged-in user's *Federations*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

No parameters available

344: Request Example

```
DELETE /api/2.0/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

345: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳fd7P45mIiHuYqZZW6+8K+YjY1Pe504Aaw4J4Zp9AhrqLX72ERYtTqWtAp1msutzNSRUdUSC72+odNPtpv
X-Server-Name: traffic_ops_golang/
Date: Wed, 23 Oct 2019 23:34:53 GMT
Content-Length: 184

{ "alerts": [
  {
    "text": "admin successfully deleted all federation resolvers:
    ↳[ 8.8.8.8 ]",
    "level": "success"
  }
],
"response": "admin successfully deleted all federation resolvers: [ 8.
    ↳8.8.8 ]"
}
```

PUT

Replaces **all** *Federations* associated with a user's *Delivery Service*(s) with those defined inside the request payload.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

The request payload is an array of objects that describe Delivery Service *Federation* Resolver mappings. Each object in the array must be in the following format.

deliveryService The *xml_id* of the *Delivery Service* which will use the *Federation* Resolvers specified in **mappings**

mappings An object containing two arrays of IP addresses (or subnets in CIDR notation) to use as *Federation* Resolvers

resolve4 An array of IPv4 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service*'s *Federation*

resolve6 An array of IPv6 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service*'s *Federation*

346: Request Example

```
PUT /api/2.0/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 95
Content-Type: application/json

[{"mappings": {
  "resolve4": ["8.8.8.8"],
  "resolve6": []
},
"deliveryService": "demo1"
}]
```

Response Structure

347: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dQ5AvQULhc254zQwgUpBl1/CHbLr/
→clKtkbs0Ju9f1BM4xIfbb03puFNN9zaEaZ1iz0lBvHFp/PgfUqisD3QHA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 23 Oct 2019 23:22:03 GMT
Content-Length: 258
Content-Type: application/json

{ "alerts": [
  {
    "text": "admin successfully deleted all federation resolvers:
→[ 8.8.8.8 ]",
    "level": "success"
  },
  {
    "text": "admin successfully created federation resolvers.",
    "level": "success"
  }
]
```

(continues on next page)

(continued from previous page)

```
}
],
"response": "admin successfully created federation resolvers."
}
```

federations/all

GET

Retrieves a list of *Federation* mappings (also called *Federation* Resolvers) for the current user.

Auth. Required Yes

Roles Required “admin”

Response Type Array

Request Structure

No parameters available.

348: Request Example

```
GET /api/2.0/federations/all HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

deliveryService The *xml_id* of the delivery service.

mappings An array of objects that represent the mapping of a *Federation*’s CNAME to one or more Resolvers

cname The actual CNAME used by the *Federation*

ttd The TTL of the CNAME in hours

349: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 21:38:06.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→UQBlGVPJytYMkv0V42EAIoJUnXjBTCXnOGp0berxte6TtnX63LTAKFfD2LejBVYXkKtnCdkBbs+SzhA0H.
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 20:38:06 GMT
Content-Length: 138
```

```
{
  "response": [
    {
      "mappings": [
        {
          "ttl": 60,
          "cname": "img1.mcdn.ciab.test."
        },
        {
          "ttl": 60,
          "cname": "img2.mycdn.ciab.test."
        }
      ],
      "deliveryService": "demo1"
    },
    {
      "mappings": [
        {
          "ttl": 60,
          "cname": "static.mycdn.ciab.test."
        }
      ],
      "deliveryService": "demo2"
    }
  ]
}
```

federations/{{ID}}/deliveryservices

GET

Retrieves *Delivery Services* assigned to a *Federation*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 166: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation to be inspected

Table 167: Request Query Parameters

Name	Required	Description
dsID	no	Show only the <i>Delivery Service</i> identified by this integral, unique identifier
order-by	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

350: Request Example

```
GET /api/2.0/federations/1/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cdn** The CDN to which this *Delivery Service* Belongs
- id** The integral, unique identifier for the *Delivery Service*
- type** The routing type used by this *Delivery Service*
- xmlId** The 'xml_id' which uniquely identifies this *Delivery Service*

351: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:44:13 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:44:13 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: 7Y9Q/
→qHeXfbjJduvucRCR85wf4VRfyYhlK59sNRkzIJuwnsMhFcEfYfNqrvELwfexOum/
→VEX2f/1oa+I/edGfw==
content-length: 74

{ "response": [
  {
    "xmlId": "demo1",
    "cdn": "CDN-in-a-Box",
    "type": "HTTP",
    "id": 1
  }
]}
```

POST

Assigns one or more *Delivery Services* to a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 168: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation to be inspected

dsIds An array of integral, unique identifiers for *Delivery Services* which will be assigned to this federation

replace An optional boolean (default: `false`) which, if `true`, will cause any conflicting assignments already in place to be overridden by this request

Note: If `replace` is not given (and/or not `true`), then any conflicts with existing assignments will cause the entire operation to fail.

352: Request Example

```
POST /api/2.0/federations/1/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 32
Content-Type: application/json

{
  "dsIds": [1],
  "replace": true
}
```

Response Structure

dsIds An array of integral, unique identifiers for *Delivery Services* which are now assigned to this federation

replace An optional boolean (default: false) which, if true, means any conflicting assignments already in place were overridden by this request

353: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
→rVd0nx8G3bRI8ub1zw6FTdmwQ7jer4zoqzOZf5tC1ckrR0HEIOH1Azdcmvv0FVE5I0omCHVnrYbzab7tU
x-server-name: traffic_ops_golang/
content-length: 137
date: Wed, 05 Dec 2018 00:34:06 GMT

{ "alerts": [
  {
    "text": "1 delivery service(s) were assigned to the federation.
→1",
    "level": "success"
  }
],
```

(continues on next page)

(continued from previous page)

```
"response": {
  "dsIds": [
    1
  ],
  "replace": true
}}
```

`federations/{{ID}}/deliveryservices/{{dsID}}`

DELETE

Removes a *Delivery Service* from a federation. A *Delivery Service* cannot be removed from a federation if it is the only *Delivery Service* assigned to said federation

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 169: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the federation from which the <i>Delivery Service</i> identified by dsID will be removed
dsID	The integral, unique identifier of the <i>Delivery Service</i> which will be removed from the federation identified by ID

354: Request Example

```
DELETE /api/2.0/federations/1/deliveryservices/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

355: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 01:06:51 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 05:06:51 GMT;
    ↳path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: NqAZuZYlF1UW0aazbj/
    ↳j4gWX7ye0kGGakRRFEkK6ShxqXvCxEOdCTyu75qiLPN2wSgr3FGQnp2Sq345sE7In9g==
content-length: 98

{ "alerts": [
  {
    "level": "success",
    "text": "federation deliveryservice was deleted."
  }
]}
```

federations/{{ID}}/federation_resolvers

GET

Retrieves federation resolvers assigned to a federation.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 170: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation for which resolvers will be retrieved

356: Request Example

```
GET /api/2.0/federations/1/federation_resolvers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

id The integral, unique identifier of this federation resolver

ipAddress The IP address of the federation resolver - may be IPv4 or IPv6

type The type of resolver - one of:

RESOLVE4 This resolver is for IPv4 addresses (and **ipAddress** is IPv4)

RESOLVE6 This resolver is for IPv6 addresses (and **ipAddress** is IPv6)

357: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:49:50 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:49:50 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: csC18kE3YjiILHP1wmJg7V4h/
→XWY8HUMKyPuZWnde2g7HJ4gTY51HfjCSqhyKvIJQ8Rl7uEqshF3Ey6xIMOX4A==
content-length: 63
```

(continues on next page)

(continued from previous page)

```
{ "response": [
  {
    "ipAddress": "0.0.0.0",
    "type": "RESOLVE4",
    "id": 1
  }
]}
```

POST

Assigns one or more resolvers to a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 171: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation for which resolvers will be retrieved

fedResolverIds An array of integral, unique identifiers for federation resolvers

replace An optional boolean (default: `false`) which, if `true`, will cause any conflicting assignments already in place to be overridden by this request

Note: If `replace` is not given (and/or not `true`), then any conflicts with existing assignments will cause the entire operation to fail.

358: Request Example

```
POST /api/2.0/federations/1/federation_resolvers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 41
Content-Type: application/json

{
```

(continues on next page)

(continued from previous page)

```
"fedResolverIds": [1],
"replace": true
}
```

Response Structure

fedResolverIds An array of integral, unique identifiers for federation resolvers

replace An optionally-present boolean (default: `false`) which, if `true`, any conflicting assignments already in place were overridden by this request

359: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:47:47 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:47:47 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: +JDcRByS3H06pMg3Gzkvn0w7/
→v5oRu19e+RxyFIOKJKNH0kZILyQBS+PJpxDeCgwI19+0poW5dyHPPR9SwbNCA==
content-length: 148

{ "alerts": [
  {
    "level": "success",
    "text": "1 resolver(s) were assigned to the test.quest.
→federation"
  }
],
"response": {
  "replace": true,
  "fedResolverIds": [
    1
  ]
}}
```

`federations/{{ID}}/users`

GET

Retrieves users assigned to a federation.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 172: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the federation for which users will be retrieved

Table 173: Request Query Parameters

Name	Re-quired	Description
userId	no	Show only the user that has this integral, unique identifier
role	no	Show only the users that have this role
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Response Structure

company The company to which the user belongs

email The user’s email address

fullName The user’s full name

id An integral, unique identifier for the user

role The user’s highest role

username The user’s short “username”

360: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:31:34 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:31:34 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: eQQoF2xlbK2I2oTja7zrt/
→FlkLzCgwpU2zb2+rmIjHbHJ3MnmsSczSamIAAyTzs5gDaqcuUX1G35ZB8d7Bj82g==
content-length: 101

{ "response": [
  {
    "fullName": null,
    "email": null,
    "id": 2,
    "role": "admin",
    "company": null,
    "username": "admin"
  }
]}
```

POST

Assigns one or more users to a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

userIds An array of integral, unique identifiers for users which will be assigned to this federation

replace An optional boolean (default: `false`) which, if `true`, will cause any conflicting assignments already in place to be overridden by this request

Note: If `replace` is not given (and/or not `true`), then any conflicts with existing assignments will cause the entire operation to fail.

361: Request Example

```
POST /api/2.0/federations/1/users HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 34
Content-Type: application/json

{
  "userIds": [2],
  "replace": true
}
```

Response Structure

userIds An array of integral, unique identifiers for users which have been assigned to this federation

replace An optional boolean (default: `false`) which, if `true`, caused any conflicting assignments already in place to be overridden by this request

362: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
➔Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:29:19 GMT
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

```
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:29:19 GMT;␣
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512:␣
→MvPmgOAs58aSOgVh+iEilflgOexbaexg+qE2IPrQZX0H4iSX4JvEys9adbGE9a9yaLj9uUMxg77N6ZyDhV
content-length: 137

{ "alerts": [
  {
    "level": "success",
    "text": "1 user(s) were assigned to the test.quest. federation"
  }
],
"response": {
  "userIds": [
    2
  ],
  "replace": true
}}
```

`federations/{{ID}}/users/{{userID}}`

DELETE

Removes a user from a federation.

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 174: Request Path Parameters

Name	Description
ID	An integral, unique identifier for the federation from which the user identified by <code>userID</code> will be removed
userID	An integral, unique identifier for the user who will be removed from the federation identified by ID

363: Request Structure

```
DELETE /api/2.0/federations/1/users/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

364: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 01:14:04 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 05:14:04 GMT;
    ↳path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512:
    ↳xdF6l7jdd2t8au6lh4pFtDqYxTfehake2aDBuytL7I74hK9KCT7ssLuYbfvD8ejdqqF3+jiBiFk7neQ8c
content-length: 93

{ "alerts": [
  {
    "level": "success",
    "text": "Removed user [ admin ] from federation [ foo.bar. ]"
  }
]}
```

isos

POST

Generates an ISO from the requested ISO source.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined - ISO image as a streaming download

Request Structure

dhcp A string that specifies whether the generated system image will use DHCP IP address leasing; one of:

yes DHCP will be used, and other network configuration keys need not be present in the request (and are ignored if they are)

no DHCP will not be used, and the desired network configuration **must** be specified manually in the request body

disk An optional string that names the block device (under /dev/) used for the boot media, e.g. “sda”

domainName The domain part of the system image’s Fully Qualified Domain Name (FQDN)

hostName The host name part of the system image’s FQDN

interfaceMtu A number that specifies the Maximum Transmission Unit (MTU) for the system image’s network interface card - the only valid values of which I’m aware are 1500 or 9000, and this should almost always just be 1500

interfaceName An optional string naming the network interface to be used by the generated system image e.g. “bond0”, “eth0”, etc. If the special name “bond0” is used, an LACP (Link Aggregation Control Protocol) binding configuration will be created and included in the system image

See also:

[The Link Aggregation Wikipedia page.](#)

ip6Address An optional string containing the IPv6 address of the generated system image

ip6Gateway An optional string specifying the IPv6 address of the generated system image’s network gateway - this will be ignored if **ipGateway** is specified

ipAddress An optional¹ string containing the IP address of the generated system image

ipGateway An optional¹ string specifying the IP address of the generated system image’s network gateway

ipNetmask An optional¹ string specifying the subnet mask of the generated system image

osversionDir The name of the directory containing the ISO source

See also:

[osversions](#)

¹ This optional key is required if and only if **dhcp** is “no”.

rootPass The password used by the generated system image's root user

365: Request Example

```
POST /api/2.0/isos HTTP/1.1
Host: some.trafficops.host
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 334
Content-Type: application/json

{
  "osversionDir": "centos72",
  "hostName": "test",
  "domainName": "quest",
  "rootPass": "twelve",
  "dhcp": "no",
  "interfaceMtu": 1500,
  "ipAddress": "1.3.3.7",
  "ipNetmask": "255.255.255.255",
  "ipGateway": "8.0.0.8",
  "ip6Address": "1::3:3:7",
  "ip6Gateway": "8::8",
  "interfaceName": "eth0",
  "disk": "hda"
}
```

Response Structure

ISO image as a streaming download.

366: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Connection: keep-alive
Content-Disposition: attachment; filename="test-centos72_centos72-
↳netinstall.iso"
Content-Encoding: gzip
Content-Type: application/download
Date: Wed, 05 Feb 2020 21:59:15 GMT
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 05 Feb 2020 22:59:11
↳GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Transfer-Encoding: chunked
Whole-Content-sha512: sLSVQGrLCQ4hGQhv2reragQHWNi2aKMcz2c/
↪HMAH45tLcZ1LenPy0zWRcRfHUNbV4PEEK0oiTfwE2H1A+WtRIQ==
X-Server-Name: traffic_ops_golang/
```

jobs

GET

Retrieve content invalidation jobs.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 175: Request Query Parameters

Name	Re-quired	Description
assetUrl	no	Return only invalidation jobs that operate on URLs by matching this regular expression
createdBy	no	Return only invalidation jobs that were created by the user with this username
delivery-Service	no	Return only invalidation jobs that operate on the <i>Delivery Service</i> with this <i>xml_id</i>
dsId	no	Return only invalidation jobs pending on the <i>Delivery Service</i> identified by this integral, unique identifier
id	no	Return only the single invalidation job identified by this integral, unique identifier
keyword	no	Return only invalidation jobs that have this “keyword” - only “PURGE” should exist
userId	no	Return only invalidation jobs created by the user identified by this integral, unique identifier

¹ When viewing content invalidation jobs, only those jobs that operate on a *Delivery Service* visible to the requesting user’s *Tenant* will be returned. Likewise, creating a new content invalidation job requires that the target *Delivery Service* is modifiable by the requesting user’s *Tenant*. However, when modifying or deleting an existing content invalidation job, the operation can be completed if and only if the requesting user’s *Tenant* is the same as the job’s *Delivery Service*’s *Tenant* or a descendant thereof, **and** if the requesting user’s *Tenant* is the same as the *Tenant* of the user who initially created the job or a descendant thereof.

367: Request Example

```
GET /api/2.0/jobs?id=3&dsId=1&userId=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

368: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: gH41oEi2zrd3y8yo+wfohn4/
→oHU098RpyPnqBzU7H1LUDkMOPKjAZnamcYqfdy7yDCFDUcgqkvbFAvnljxyb8w==
X-Server-Name: traffic_ops_golang/
Date: Tue, 18 Jun 2019 19:47:30 GMT
Content-Length: 186
```

(continues on next page)

(continued from previous page)

```
{ "response": [{
  "assetUrl": "http://origin.infra.ciab.test/.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
  "parameters": "TTL:2h",
  "startTime": "2019-06-18 21:28:31+00"
}]}
```

POST

Creates a new content invalidation job.

Caution: Creating a content invalidation job immediately triggers a CDN-wide revalidation update. In the case that the global *Parameter* `use_reval_pending` has a value of exactly `"0"`, this will instead trigger a CDN-wide “Queue Updates”. This means that content invalidation jobs become active **immediately** at their `startTime` - unlike most other configuration changes they do not wait for a *Snapshot* or a “Queue Updates”. Furthermore, if the global *Parameter* `use_reval_pending` is `"0"`, this will cause all pending configuration changes to propagate to all *cache servers* in the CDN. Take care when using this endpoint.

Auth. Required Yes

Roles Required “operations” or “admin”^{Page 673, 1}

Response Type Object

Request Structure

deliveryService This should either be the integral, unique identifier of a *Delivery Service*, or a string containing an *xml_id*

startTime This can be a string in the legacy YYYY-MM-DD HH:MM:SS format, or a string in **RFC 3339** format, or a string representing a date in the same non-standard format as the `last_updated` fields common in other API responses, or finally it can be a number indicating the number of milliseconds since the Unix Epoch (January 1, 1970 UTC). This date must be in the future.

regex A regular expression that will be used to match the path part of URIs for content stored on *cache servers* that service traffic for the *Delivery Service* identified by `deliveryService`.

ttl Either the number of hours for which the content invalidation job should remain active, or a “duration” string, which is a sequence of numbers followed by units. The accepted units are:

- **h** gives a duration in hours
- **m** gives a duration in minutes
- **s** gives a duration in seconds
- **ms** gives a duration in milliseconds
- **us** (or **µs**) gives a duration in microseconds
- **ns** gives a duration in nanoseconds

These durations can be combined e.g. `2h45m` specifies a TTL of two hours and forty-five minutes - however note that durations are always rounded up to the nearest hour so that e.g. `121m` becomes three hours. TTLs cannot ever be negative, obviously.

369: Request Example

```
POST /api/2.0/jobs HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 80
Content-Type: application/json

{
  "deliveryService": "demo1",
  "startTime": 1560893311219,
  "regex": "/.*",
  "ttl": "121m"
}
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

370: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Location: https://trafficops.infra.ciab.test/api/2.0/jobs?id=3
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳nB2xg2IqO56rLT8dI4+KZgxOsTe5ShctG1U8epRsY9NyyMIpx8TZYt5MrO2QikuYh+NnyoR6V0VICCnGCI
X-Server-Name: traffic_ops_golang/
Date: Tue, 18 Jun 2019 19:37:06 GMT
Content-Length: 238

{
  "alerts": [
    {
      "text": "Invalidation Job creation was successful",
      "level": "success"
    }
  ],
  "response": {
    "assetUrl": "http://origin.infra.ciab.test/.*",
    "createdBy": "admin",
    "deliveryService": "demo1",
    "id": 3,
    "keyword": "PURGE",
    "parameters": "TTL:2h",
    "startTime": "2019-06-18 21:28:31+00"
  }
}
```

PUT

Replaces an existing content invalidation job with a new one provided in the request. This method of editing a content invalidation job does not prevent the requesting user from changing fields that normally only have one value. Use with care.

Caution: Modifying a content invalidation job immediately triggers a CDN-wide revalidation update. In the case that the global *Parameter* `use_reval_pending` has a value of exactly "0", this will instead trigger a CDN-wide “Queue Updates”. This means that content invalidation jobs become active **immediately** at their `startTime` - unlike most other configuration changes they do not wait for a *Snapshot* or a “Queue Updates”. Furthermore, if the global *Parameter* `use_reval_pending` is "0", this will cause all pending configuration changes to propagate to all *cache servers* in the CDN. Take care when using this endpoint.

Auth. Required Yes

Roles Required “operations” or “admin”^{Page 673, 1}

Response Type Object

Request Structure

Table 176: Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the content invalidation job being modified

assetUrl A regular expression - matching URLs will be operated upon according to keyword

Note: Unlike in the payloads of *POST* requests to this endpoint, this must be a **full** URL regular expression, as it is **not** combined with the *Origin Server Base URL* of the *Delivery Service* identified by `deliveryService`.

createdBy The username of the user who initiated the job²

deliveryService The *xml_id* of the *Delivery Service* on which this job operates[?] - unlike *POST* request payloads, this cannot be an integral, unique identifier

id An integral, unique identifier for this job[?]

keyword A keyword that represents the operation being performed by the job. It can have any (string) value, but the only value with any meaning to Traffic

² This field must exist, but it must *not* be different than the same field of the existing job (i.e. as seen in a *GET* response)

Control is:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing space-separated key/value pairs - delimited by colons (`:`s) representing parameters associated with the job. In practice, any string can be passed as a job's `parameters`, but the only value with meaning is a single key/value pair indicated a TTL in hours in the format `TTL:hoursh`, and any other type of value may cause components of Traffic Control to work improperly or not at all.

startTime This can be a string in the legacy `YYYY-MM-DD HH:MM:SS` format, or a string in [RFC 3339](#) format, or a string representing a date in the same non-standard format as the `last_updated` fields common in other API responses, or finally it can be a number indicating the number of milliseconds since the Unix Epoch (January 1, 1970 UTC). This **must** be in the future, but only by no more than two days.

371: Request Example

```
PUT /api/2.0/jobs?id=3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 188
Content-Type: application/json

{
  "assetUrl": "http://origin.infra.ciab.test/*.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
  "parameters": "TTL:360h",
  "startTime": "2019-06-20 18:33:40+00"
}
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

372: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→+P1PTav4ZBoiQcCqQnUqf+J0dCfQgVj8mzzKtUCA69mWYulya9Bjf6BUd8Aro2apmpgPBkCEA5sITJV1t
X-Server-Name: traffic_ops_golang/
Date: Wed, 19 Jun 2019 13:38:59 GMT
Content-Length: 234

{ "alerts": [{
  "text": "Content invalidation job updated",
  "level": "success"
}],
"response": {
  "assetUrl": "http://origin.infra.ciab.test/.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
  "parameters": "TTL:360h",
  "startTime": "2019-06-20 18:33:40+00"
```

(continues on next page)

(continued from previous page)

```
}}
```

DELETE

Deletes a content invalidation job.

Tip: Content invalidation jobs that have passed their TTL are not automatically deleted - for record-keeping purposes - so use this to clean up old jobs that are no longer useful.

Caution: Deleting a content invalidation job immediately triggers a CDN-wide revalidation update. In the case that the global *Parameter* `use_reval_pending` has a value of exactly "0", this will instead trigger a CDN-wide "Queue Updates". This means that content invalidation jobs become active **immediately** at their `startTime` - unlike most other configuration changes they do not wait for a *Snapshot* or a "Queue Updates". Furthermore, if the global *Parameter* `use_reval_pending` is "0", this will cause all pending configuration changes to propagate to all *cache servers* in the CDN. Take care when using this endpoint.

Auth. Required Yes

Roles Required "operations" or "admin"^{Page 673, 1}

Response Type Object

Request Structure

Table 177: Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the content invalidation job being modified

373: Request Example

```
DELETE /api/2.0/jobs?id=3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

374: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: FqfziXJYYwHb84Fac9+p4NEY3EsklYxe94wg/
→V0mlXk4R6l4SaPSh015CChPt/yT72MsWSETnIuRD9KtoK4I+w==
X-Server-Name: traffic_ops_golang/
Date: Tue, 18 Jun 2019 22:55:15 GMT
Content-Length: 234

{ "alerts": [
  {
    "text": "Content invalidation job was deleted",
    "level": "success"
  }
],
"response": {
  "assetUrl": "http://origin.infra.ciab.test/.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
```

(continues on next page)

(continued from previous page)

```
"parameters": "TTL:36h",
"startTime": "2019-06-20 18:33:40+00"
}}
```

letsencrypt/autorenew

POST

Generates an SSL certificate and private key using Let's Encrypt for a *Delivery Service*

Auth. Required Yes

Roles Required "admin" or "operations"

Response Type Object

Request Structure

No parameters available

Response Structure

375: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "alerts": [
  {
    "text": "This endpoint is deprecated, please use letsencrypt/
→autorenew instead",
    "level": "warning"
  },
  {
    "text": "Beginning async call to renew certificates. This may
→take a few minutes.",
    "level": "success"
  }
]}
```

letsencrypt/dnsrecords

GET

Gets DNS challenge records for Let's Encrypt DNS challenge for a specified FQDN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

Table 178: Request Query Parameters

Name	Required	Description
fqdn	no	Return only DNS challenge records for the specified FQDN

376: Request Example

```
GET /api/2.0/letsencrypt/dnsrecord?fqdn=_acme-challenge.demo1.example.
→com. HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

fqdn The FQDN for the TXT record location to complete the DNS challenge

record The record provided by Let's Encrypt to complete the DNS challenge

377: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": [
  {
    "fqdn": "_acme-challenge.demo1.example.com.",
    "record": "testRecord"
  }
]}
```

logs

Note: This endpoint's responses will contain a cookie (`last_seen_log`) that is used by `logs/newcount` to determine the time of last access. Be sure your client uses cookies properly if you intend to use `logs/newcount` in concert with this endpoint!

GET

Fetches a list of changes that have been made to the Traffic Control system

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 179: Request Query Parameters

Name	Re- quired	Description
days	no	An integer number of days of change logs to return, by default there is no limit applied
limit	no	The number of records to which to limit the response, if there is no limit query params, it limits to 1000
off- set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.
user- name	no	A name to which to limit the response too

New in version ATCv6: The username, page, offset query parameters were added to this in endpoint across across all API versions in ATC version 6.0.0.

378: Request Example

```
GET /api/2.0/logs?days=1&limit=2&username=admin HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- id** Integral, unique identifier for the Log entry
- lastUpdated** Date and time at which the change was made, in *Traffic Ops's Custom Date/Time Format*
- level** Log categories for each entry, e.g. 'UICHANGE', 'OPER', 'APICHANGE'
- message** Log detail about what occurred
- ticketNum** Optional field to cross reference with any bug tracking systems
- user** Name of the user who made the change

379: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 15:11:38 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: last_seen_log="2018-11-15% 15:11:38"; path=/; Max-
→Age=604800
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→40dV+azaZ3b6F30y6YHVbV3H2a3ekZrdoxICupwaxQnj62pwYfb7YCM7Qhe30AItmB77Tbg9INy27ymaz
Content-Length: 357

{ "response": [
  {
    "ticketNum": null,
    "level": "APICHANGE",
    "lastUpdated": "2018-11-14 21:40:06.493975+00",
    "user": "admin",
    "id": 444,
    "message": "User [ test ] unlinked from deliveryservice [ 1 |
→demo1 ] ."
  },
  {
    "ticketNum": null,
    "level": "APICHANGE",
    "lastUpdated": "2018-11-14 21:37:30.707571+00",
```

(continues on next page)

(continued from previous page)

```

    "user": "admin",
    "id": 443,
    "message": "1 delivery services were assigned to test"
  }
}],
  "summary": {
    "count": 2
  }
}
```

Summary Fields

The summary object returned by this method of this endpoint uses only the count *standard property*.

logs/newcount

GET

Gets the number of new changes made to the Traffic Control system - “new” being defined as the last time the client requested either *logs*

Note: This endpoint’s functionality is implemented by the *logs* endpoint’s response setting cookies for the client to use when requesting `_this_` endpoint. Take care that your client respects cookies!

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available

Response Structure

newLogcount The integer number of new changes

380: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 15:17:35 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: Ugdqe8GXKSOExphwbDX/
    ↳Gli+2vBpubttbpfYMbJaCP7adox3MzmVRi2RxTDL5kwPewrcL1C088zGITskh0sc9g==
Content-Length: 30

{ "response": {
  "newLogcount": 4
}}
```

origins

GET

Gets all requested *Origins*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 180: Request Query Parameters

Name	Required	Description
cacheGroup	no	Return only <i>Origins</i> within the <i>Cache Group</i> that has this <i>ID</i>
co-ordinate	no	Return only <i>Origins</i> located at the geographic coordinates identified by this integral, unique identifier
delivery-service	no	Return only <i>Origins</i> that belong to the <i>Delivery Service</i> identified by this integral, unique identifier
id	no	Return only the <i>Origin</i> that has this integral, unique identifier
name	no	Return only <i>Origins</i> by this name
profileId	no	Return only <i>Origins</i> which use the <i>Profile</i> that has this <i>ID</i>
primary	no	If <code>true</code> , return only <i>Origins</i> which are the the primary <i>Origin</i> of the <i>Delivery Service</i> to which they belong - if <code>false</code> return only <i>Origins</i> which are <i>not</i> the primary <i>Origin</i> of the <i>Delivery Service</i> to which they belong
tenant	no	Return only <i>Origins</i> belonging to the tenant identified by this integral, unique identifier
orderBy	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “ n ” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Note: Several fields of origin definitions which are filterable by Query Parameters are allowed to be `null`. `null` values in these fields will be filtered *out* appropriately by such Query Parameters, but do note that `null` is not a valid value accepted by any of these Query Parameters, and attempting to pass it will result in an error.

381: Request Example

```
GET /api/2.0/origins?name=demo1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cachegroup** A string that is the *name of the Cache Group* to which the *Origin* belongs
- cachegroupId** An integer that is the *ID of the Cache Group* to which the *Origin* belongs
- coordinate** The name of a coordinate pair that defines the origin's geographic location
- coordinateId** An integral, unique identifier for the coordinate pair that defines the *Origin's* geographic location
- deliveryService** A string that is the *xml_id* of the *Delivery Service* to which the *Origin* belongs
- deliveryServiceId** An integral, unique identifier for the *Delivery Service* to which the *Origin* belongs
- fqdn** The FQDN of the *Origin*
- id** An integral, unique identifier for this *Origin*
- ip6Address** The IPv6 address of the *Origin*
- ipAddress** The IPv4 address of the *Origin*
- isPrimary** A boolean value which, when `true` specifies this *Origin* as the 'primary' *Origin* served by `deliveryService`
- lastUpdated** The date and time at which this *Origin* was last modified
- name** The name of the *Origin*
- port** The TCP port on which the *Origin* listens
- profile** The *Name* of the *Profile* used by this *Origin*
- profileId** The *ID* of the *Profile* used by this *Origin*
- protocol** The protocol used by this origin - will be one of 'http' or 'https'
- tenant** The name of the *Tenant* that owns this *Origin*
- tenantId** An integral, unique identifier for the *Tenant* that owns this *Origin*

382: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳sm8DpvdvrfdSVLtmXTdfjsZbTlbc+pI40Gy0aj00XIURTPfFXuv/
    ↳4LgHb6A3r92iybBRHvFrH6qdB2g97U2sBg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 15:43:41 GMT
Content-Length: 376
```

```
{ "response": [
  {
    "cachegroup": null,
    "cachegroupId": null,
    "coordinate": null,
    "coordinateId": null,
    "deliveryService": "demo1",
    "deliveryServiceId": 1,
    "fqdn": "origin.infra.ciab.test",
    "id": 1,
    "ip6Address": null,
    "ipAddress": null,
    "isPrimary": true,
    "lastUpdated": "2018-12-10 19:11:32+00",
    "name": "demo1",
    "port": null,
    "profile": null,
    "profileId": null,
    "protocol": "http",
    "tenant": "root",
    "tenantId": 1
  }
]}
```

POST

Creates a new origin definition.

Warning: At the time of this writing it is possible to create and/or modify origin definitions assigned to STEERING and CLIENT_STEERING *Delivery Services* - despite that an origin has no meaning in those contexts. In these cases, the API responses may give incorrect output - see [GitHub Issue #3107](#) for details and updates.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cachegroupId An optional, integer which, if present, should be the *Cache Group ID* that identifies a *Cache Group* to which the new *Origin* shall belong

coordinateId An optional, integral, unique identifier of a coordinate pair that shall define the *Origin*’s geographic location

deliveryServiceId The integral, unique identifier of the *Delivery Service* to which the new *Origin* shall belong

fqdn The FQDN of the *Origin*

ip6Address An optional string containing the IPv6 address of the *Origin*

ipAddress An optional string containing the IPv4 address of the *Origin*

isPrimary An optional boolean which, if `true` will set this *Origin* as the ‘primary’ *Origin* served by the *Delivery Service* identified by `deliveryServiceID`

Note: Though not specifying this field in this request will leave it as `null` in the output, Traffic Ops will silently coerce that to its default value: `false`.

name A human-friendly name of the *Origin*

port An optional port number on which the *Origin* listens for incoming TCP connections

profileId An optional *ID* of a *Profile* that shall be used by this *Origin*

protocol The protocol used by the origin - must be one of ‘http’ or ‘https’

tenantId An optional¹, integral, unique identifier for the *Tenant* which shall own the new *Origin*

¹ The `tenantId` field is required if and only if tenancy is enabled within Traffic Ops.

383: Request Example

```
POST /api/2.0/origins HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 114
Content-Type: application/json

{
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "name": "example",
  "port": 80,
  "protocol": "http",
  "tenantId": 1
}
```

Response Structure

- cachegroup** A string that is the *name of the Cache Group* to which the *Origin* belongs
- cachegroupId** An integer that is the *ID of the Cache Group* to which the *Origin* belongs
- coordinate** The name of a coordinate pair that defines the origin's geographic location
- coordinateId** An integral, unique identifier for the coordinate pair that defines the *Origin's* geographic location
- deliveryService** The 'xml_id' of the *Delivery Service* to which the *Origin* belongs
- deliveryServiceId** An integral, unique identifier for the *Delivery Service* to which the *Origin* belongs
- fqdn** The FQDN of the *Origin*
- id** An integral, unique identifier for this *Origin*
- ip6Address** The IPv6 address of the *Origin*
- ipAddress** The IPv4 address of the *Origin*
- isPrimary** A boolean value which, when **true** specifies this *Origin* as the 'primary' *Origin* served by deliveryService
- lastUpdated** The date and time at which this *Origin* was last modified
- name** The name of the *Origin*

- port** The TCP port on which the *Origin* listens
- profile** The *Name* of the *Profile* used by this *Origin*
- profileId** The *ID* the *Profile* used by this *Origin*
- protocol** The protocol used by this origin - will be one of 'http' or 'https'
- tenant** The name of the *Tenant* that owns this *Origin*
- tenantId** An integral, unique identifier for the *Tenant* that owns this *Origin*

384: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳z4gp0MaqYu+gSRORhKT2e0bVBuVDVx1rdteRaN5kRL9uJ3hNzUCi4dSKIt0rgNgOEDt6x/
    ↳iTyrMvhr/TSHYtmA==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 15:14:27 GMT
Content-Length: 418

{ "alerts": [
  {
    "text": "origin was created.",
    "level": "success"
  }
],
"response": {
  "cachegroup": null,
  "cachegroupId": null,
  "coordinate": null,
  "coordinateId": null,
  "deliveryService": null,
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "id": 2,
  "ip6Address": null,
  "ipAddress": null,
  "isPrimary": null,
  "lastUpdated": "2018-12-11 15:14:27+00",
  "name": "example",
```

(continues on next page)

(continued from previous page)

```
"port": 80,
"profile": null,
"profileId": null,
"protocol": "http",
"tenant": null,
"tenantId": 1
}}
```

PUT

Updates an *Origin* definition.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 181: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Origin</i> definition being edited

cachegroupId An optional, integer which, if present, should be the *Cache Group ID* that identifies a *Cache Group* to which the new *Origin* shall belong

coordinateId An optional, integral, unique identifier of a coordinate pair that shall define the *Origin*’s geographic location

deliveryServiceId The integral, unique identifier of the *Delivery Service* to which the *Origin* shall belong

fqdn The FQDN of the *Origin*

ip6Address An optional string containing the IPv6 address of the *Origin*

ipAddress An optional string containing the IPv4 address of the *Origin*

isPrimary An optional boolean which, if `true` will set this *Origin* as the ‘primary’ origin served by the *Delivery Service* identified by `deliveryServiceID`

name A human-friendly name of the *Origin*

port An optional port number on which the *Origin* listens for incoming TCP connections

profileId An optional *ID* of the *Profile* that shall be used by this *Origin*

protocol The protocol used by the *Origin* - must be one of ‘http’ or ‘https’

tenantId An optional^{Page 694, 1}, integral, unique identifier for the *Tenant* which shall own the new *Origin*

385: Request Example

```
PUT /api/2.0/origins?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 135
Content-Type: application/json

{
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "isprimary": true,
  "name": "example",
  "port": 443,
  "protocol": "https",
  "tenantId": 1
}
```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the *Origin* belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the *Origin* belongs

coordinate The name of a coordinate pair that defines the origin's geographic location

coordinateId An integral, unique identifier for the coordinate pair that defines the *Origin's* geographic location

deliveryService The 'xml_id' of the *Delivery Service* to which the *Origin* belongs

deliveryServiceId An integral, unique identifier for the *Delivery Service* to which the *Origin* belongs

fqdn The FQDN of the *Origin*

id An integral, unique identifier for this *Origin*

ip6Address The IPv6 address of the *Origin*

ipAddress The IPv4 address of the *Origin*

isPrimary A boolean value which, when true specifies this *Origin* as the 'primary' *Origin* served by deliveryService

lastUpdated The date and time at which this *Origin* was last modified

name The name of the *Origin*

port The TCP port on which the *Origin* listens

profile The *Name* of the *Profile* used by this *Origin*

profileId The *ID* the *Profile* used by this *Origin*

protocol The protocol used by this origin - will be one of 'http' or 'https'

tenant The name of the *Tenant* that owns this *Origin*

tenantId An integral, unique identifier for the *Tenant* that owns this *Origin*

386: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Zx7j0a7UAQxRtDenYodvGQSoooPj4m0yY0AIEUpbdelmYMiNdPYtW82BCmMesFXkmP74nV4HbTUyDHVMu.
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 15:40:53 GMT
Content-Length: 420

{ "alerts": [
  {
    "text": "origin was updated.",
    "level": "success"
  }
],
"response": {
  "cachegroup": null,
  "cachegroupId": null,
  "coordinate": null,
  "coordinateId": null,
  "deliveryService": null,
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "id": 2,
  "ip6Address": null,
  "ipAddress": null,
  "isPrimary": true,
```

(continues on next page)

(continued from previous page)

```
"lastUpdated": "2018-12-11 15:40:53+00",
"name": "example",
"port": 443,
"profile": null,
"profileId": null,
"protocol": "https",
"tenant": null,
"tenantId": 1
}}
```

DELETE

Deletes an *Origin* definition.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 182: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Origin</i> definition being deleted

387: Request Example

```
DELETE /api/2.0/origins?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

388: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: fLaY4/
→nh0yR38xq5weBKYg02+aQV6Z1Zro0q9UqUCHLMMrH1NMyhOHx+EphPq7JxkjmGY04WCt6VvDyjGWcgfQ==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 17:04:14 GMT
Content-Length: 61

{ "alerts": [
  {
    "text": "origin was deleted.",
    "level": "success"
  }
]}

```

osversions

See also:

Generate ISO

GET

Gets all available OS (Operating System) versions for ISO generation, as well as the name of the directory where the “kickstarter” files are found.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

This endpoint has no constant keys in its response. Instead, each key in the response object is the name of an OS, and the value is a string that names the directory where the ISO source can be found. These directories sit under `/var/www/files/` on the Traffic Ops host machine by default, or at the location defined by the `kickstart.files.location` *Parameter* of the Traffic Ops server's *Profile*, if it is defined.

389: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳RxbRY2DZ+1Y0dTzzUETEZ3wtLBiD2BwXMVuaZjhe4a4cwgcZKRBWxZ6Qy5YYujFe1+UBiTG4sML/
    ↳Amn27F4AVg==
X-Server-Name: traffic_ops_golang/
Date: Fri, 30 Nov 2018 19:14:36 GMT
Content-Length: 38

{ "response": {
  "CentOS 7.2": "centos72"
}}
```

Configuration File

The data returned from the endpoint comes directly from a configuration file. By default, the file is located at `/var/www/files/osversions.json`. The **directory** of the file can be changed by creating a specific *Parameter* named `kickstart.files.location` in configuration file `mkisofs`.

The format of the file is a JSON object as described in *Response Structure*.

390: Example osversions.json file

```
{
  "CentOS 7.2": "centos72"
}
```

The legacy Perl Traffic Ops used a Perl configuration file located by default at `/var/www/files/osversions.cfg`. A Perl script is provided to convert the legacy configuration file to the new JSON format. The script is located within the Traffic Control repository at

traffic_ops/app/bin/osversions-convert.pl.

391: Example usage of conversion script

```
./osversions-convert.pl < /var/www/files/osversions.cfg > /var/www/
→files/osversions.json
```

parameterprofile

POST

Create one or more *Parameter/Profile* assignments.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

paramId The *ID* of the *Parameter* to be assigned to the *Profiles* identified within the profileIds array

profileIds An array of *Profile IDs* to which the *Parameter* identified by paramId shall be assigned

replace An optional boolean (default: false) which, if true, will cause any conflicting *Profile/Parameter* assignments to be overridden.

392: Request Example

```
POST /api/2.0/parameterprofile HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 38
Content-Type: application/json

{
  "paramId": 4,
  "profileIds": [18]
}
```

Response Structure

paramId The *ID* of the *Parameter* which has been assigned to the *Profiles* identified within the `profileIds` array

profileIds An array of *Profile IDs* to which the *Parameter* identified by `paramId` has been assigned

replace An optional boolean (default: false) which, if true, caused any conflicting *Profile/Parameter* assignments to be overridden.

393: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳N2ahnhEnfZ0UqnjylN6Vu3HaOZk340YuiuyiqkhTbk0pENp+kwBPYu4Z/
    ↳sqBAloCfXSQaWlJzaeXw4uOD5heWw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 15:18:23 GMT
Content-Length: 147

{ "alerts": [
  {
    "text": "2 parameters were assigned to the 18 profile",
    "level": "success"
  }
],
"response": {
  "profileId": 18,
  "paramIds": [
    2,
    3
  ],
  "replace": false
}}
```


parameters

GET

Gets all *Parameters* configured in Traffic Ops

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 183: Request Query Parameters

Name	Re- quired	Description
con- fig- File	no	Filter <i>Parameters</i> by <i>Config File</i>
id	no	Filters <i>Parameters</i> by <i>ID</i>
name	no	Filter <i>Parameters</i> by <i>Name</i>
value	no	Filter <i>Parameters</i> by <i>Value</i>
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the <i>nth</i> page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

New in version ATCv6: The value query parameter was added to all API versions in ATC version 6.0.

394: Request Example

```
GET /api/2.0/parameters?configFile=records.config&name=location HTTP/1.
↪1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name of the Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

395: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
→jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
→DbBwhMAOJoeqDImoDlrLnrVjQGO4AooA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 18:23:39 GMT
Content-Length: 212

{ "response": [
  {
    "configFile": "records.config",
    "id": 29,
    "lastUpdated": "2018-12-05 17:51:02+00",
    "name": "location",
    "profiles": [
      "ATS_EDGE_TIER_CACHE",
      "ATS_MID_TIER_CACHE"
    ],
    "secure": false,
    "value": "/etc/trafficserver/"
  }
]}
```

POST

Creates one or more new *Parameters*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

The request body may be in one of two formats, a single *Parameter* object or an array of *Parameter* objects. Each *Parameter* object shall have the following keys:

configFile The *Parameter*’s *Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*’s *Value*

396: Request Example - Single Object Format

```
POST /api/2.0/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 84
Content-Type: application/json

{
  "name": "test",
  "value": "quest",
  "configFile": "records.config",
  "secure": false
}
```

397: Request Example - Array Format

```
POST /api/2.0/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 180
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
[{
  "name": "test",
  "value": "quest",
  "configFile": "records.config",
  "secure": false
},
{
  "name": "foo",
  "value": "bar",
  "configFile": "records.config",
  "secure": false
}]
```

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name of the Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

398: Response Example - Single Object Format

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→eQrl48zWids0kDpfCYmntYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
→Cfh2X9i3G+MQ36eH95gukJqOBOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:18:21 GMT
Content-Length: 212
```

(continues on next page)

(continued from previous page)

```
{ "alerts": [
  {
    "text": "param was created.",
    "level": "success"
  }
],
"response": {
  "configFile": "records.config",
  "id": 124,
  "lastUpdated": "2018-12-05 19:18:21+00",
  "name": "test",
  "profiles": null,
  "secure": false,
  "value": "quest"
}}
```

parameters/{{ID}}

PUT

Replaces a *Parameter*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 184: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Parameter</i> which will be deleted

configFile The *Parameter*’s *Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*’s *Value*

399: Request Example

```
PUT /api/2.0/parameters/124 HTTP/1.1
Host: trafficops.infra.ciab.test
```

(continues on next page)

(continued from previous page)

```
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 81
Content-Type: application/json

{
  "name": "foo",
  "value": "bar",
  "configFile": "records.config",
  "secure": false
}
```

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name of the Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

400: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: DMxS2gKceFVKRtezON/
→vsnrC+zI8onASSHaGv5i3wwvUvyt9KEe72gxQd6ZgVcSq3K8ZpkH6g3UI/WtEfdp5vA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 20:21:07 GMT
Content-Length: 209

{ "alerts": [
```

(continues on next page)

(continued from previous page)

```
{
  "text": "param was updated.",
  "level": "success"
},
"response": {
  "configFile": "records.config",
  "id": 125,
  "lastUpdated": "2018-12-05 20:21:07+00",
  "name": "foo",
  "profiles": null,
  "secure": false,
  "value": "bar"
}}
```

DELETE

Deletes the specified *Parameter*. If, however, the *Parameter* is associated with one or more *Profiles*, deletion will fail.

Auth. Required Yes

Roles Required “admin” or “operations”

Response TType undefined

Request Structure

Table 185: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Parameter</i> which will be deleted

401: Request Example

```
DELETE /api/2.0/parameters/124 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

402: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: hJjQq2Seg7sqWt+jKgp6gwRxUtoVU34PFoc9wEaweXdaIBTn/
    ↳BscoUuyw2/n+V8GZPqpeQcihZE50/0oQhdtHw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:20:30 GMT
Content-Length: 60

{ "alerts": [
  {
    "text": "param was deleted.",
    "level": "success"
  }
]}
```

phys_locations

GET

Retrieves *Physical Locations*

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 186: Request Query Parameters

Name	Description
id	Filter by integral, unique identifier
re-gion	Filter by integral, unique identifier of containing <i>Region</i>
name	Filter by name
or-derby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

403: Request Example

```
GET /api/2.0/phys_locations?name=CDN_in_a_Box HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- address** The physical location’s street address
- city** The name of the city in which the physical location lies
- comments** Any and all human-readable comments
- email** The email address of the physical location’s poc
- id** An integral, unique identifier for the physical location
- lastUpdated** The date and time at which the physical location was last updated, in *Traffic Ops’s Custom Date/Time Format*
- name** The name of the physical location
- phone** A phone number where the the physical location’s poc might be reached
- poc** The name of a “point of contact” for the physical location
- region** The name of the region within which the physical location lies

regionId An integral, unique identifier for the region within which the physical location lies

shortName An abbreviation of the name

state An abbreviation of the name of the state or province within which this physical location lies

zip The zip code of the physical location

404: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳0g4b3W1AwXytCnBo8TReQQij2v9oHA17MG9KuwMig5V4sFcMM5qP8dgPsFTunFr00DPI20c7BpUbZsvJts
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 22:19:52 GMT
Content-Length: 275

{ "response": [
  {
    "address": "1600 Pennsylvania Avenue NW",
    "city": "Washington",
    "comments": "",
    "email": "",
    "id": 2,
    "lastUpdated": "2018-12-05 17:50:58+00",
    "name": "CDN_in_a_Box",
    "phone": "",
    "poc": "",
    "regionId": 1,
    "region": "Washington, D.C",
    "shortName": "ciab",
    "state": "DC",
    "zip": "20500"
  }
]}
```

POST

Creates a new physical location

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

address The physical location’s street address

city The name of the city in which the physical location lies

comments An optional string for containing any and all human-readable comments

email An optional string containing email address of the physical location’s poc

name An optional name of the physical location

phone An optional string containing the phone number where the the physical location’s poc might be reached

poc The name of a “point of contact” for the physical location

region An optional string naming the region that contains this physical location¹

regionId An integral, unique identifier for the region within which the physical location lies¹

shortName An abbreviation of the name

state An abbreviation of the name of the state or province within which this physical location lies

zip The zip code of the physical location

405: Request Example

```
POST /api/2.0/phys_locations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 326
Content-Type: application/json
```

(continues on next page)

¹ The only “region” key that actually matters in the request body is **regionId**; **region** is not validated and has no effect - particularly not the effect of re-naming the region - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the region. Note that if **region** is not present in the request body it will be null in the response, but again further requests will show the true region name.

(continued from previous page)

```
{
  "address": "Buckingham Palace",
  "city": "London",
  "comments": "Buckingham Palace",
  "email": "steve.kingstone@royal.gsx.gov.uk",
  "name": "Great_Britain",
  "phone": "0-843-816-6276",
  "poc": "Her Majesty The Queen Elizabeth Alexandra Mary Windsor II",
  "regionId": 3,
  "shortName": "uk",
  "state": "Westminster",
  "zip": "SW1A 1AA"
}
```

Response Structure

- address** The physical location's street address
- city** The name of the city in which the physical location lies
- comments** Any and all human-readable comments
- email** The email address of the physical location's poc
- id** An integral, unique identifier for the physical location
- lastUpdated** The date and time at which the physical location was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the physical location
- phone** A phone number where the the physical location's poc might be reached
- poc** The name of a "point of contact" for the physical location
- region** The name of the region within which the physical location lies
- regionId** An integral, unique identifier for the region within which the physical location lies
- shortName** An abbreviation of the name
- state** An abbreviation of the name of the state or province within which this physical location lies
- zip** The zip code of the physical location

406: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: GZ/
    ↳BC+AgGpOQNfd9oiZy19jtsD8MP0deyi7PVdz+9YSiLYP44gmn5K+Xi1yS0l59yjHf70+C1loVQPS1IeP9
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 00:14:47 GMT
Content-Length: 443

{ "alerts": [
  {
    "text": "physLocation was created.",
    "level": "success"
  }
],
"response": {
  "address": "Buckingham Palace",
  "city": "London",
  "comments": "Buckingham Palace",
  "email": "steve.kingstone@royal.gsx.gov.uk",
  "id": 3,
  "lastUpdated": "2018-12-06 00:14:47+00",
  "name": "Great_Britain",
  "phone": "0-843-816-6276",
  "poc": "Her Majesty The Queen Elizabeth Alexandra Mary Windsor II",
  "regionId": 3,
  "region": null,
  "shortName": "uk",
  "state": "Westminster",
  "zip": "SW1A 1AA"
}}
```

`phys_locations/{ID}`

PUT

Updates a *Physical Location*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

Table 187: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Physical Location</i> being modified

address The physical location’s street address

city The name of the city in which the physical location lies

comments An optional string for containing any and all human-readable comments

email An optional string containing email address of the physical location’s poc

name An optional name of the physical location

phone An optional string containing the phone number where the the physical location’s poc might be reached

poc The name of a “point of contact” for the physical location

region An optional string naming the region that contains this physical location¹

regionId An integral, unique identifier for the region within which the physical location lies¹

shortName An abbreviation of the name

state An abbreviation of the name of the state or province within which this physical location lies

zip The zip code of the physical location

407: Request Structure

```
PUT /api/2.0/phys_locations/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 268
Content-Type: application/json

{
  "address": "1600 Pennsylvania Avenue NW",
  "city": "Washington",
  "comments": "The White House",
```

(continues on next page)

¹ The only “region” key that actually matters in the request body is regionId; region is not validated and has no effect - particularly not the effect of re-naming the region - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the region. Note that if region is not present in the request body it will be null in the response, but again further requests will show the true region name.

(continued from previous page)

```
"email": "the@white.house",
"name": "CDN_in_a_Box",
"phone": "1-202-456-1414",
"poc": "Donald J. Trump",
"regionId": 2,
"shortName": "ciab",
"state": "DC",
"zip": "20500"
}
```

Response Structure

- address** The physical location's street address
- city** The name of the city in which the physical location lies
- comments** Any and all human-readable comments
- email** The email address of the physical location's poc
- id** An integral, unique identifier for the physical location
- lastUpdated** The date and time at which the physical location was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the physical location
- phone** A phone number where the the physical location's poc might be reached
- poc** The name of a "point of contact" for the physical location
- region** The name of the region within which the physical location lies
- regionId** An integral, unique identifier for the region within which the physical location lies
- shortName** An abbreviation of the name
- state** An abbreviation of the name of the state or province within which this physical location lies
- zip** The zip code of the physical location

408: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→qnMe60qxjSU8H1njlh00HWNr20YnVlOCufqCTdMBcdC1322jk2ICFQsQQ3Xu0OR0WSb7h70HCfXqDC1/
→jA1xjA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 23:39:17 GMT
Content-Length: 385

{ "alerts": [
  {
    "text": "physLocation was updated.",
    "level": "success"
  }
],
"response": {
  "address": "1600 Pennsylvania Avenue NW",
  "city": "Washington",
  "comments": "The White House",
  "email": "the@white.house",
  "id": 2,
  "lastUpdated": "2018-12-05 23:39:17+00",
  "name": "CDN_in_a_Box",
  "phone": "1-202-456-1414",
  "poc": "Donald J. Trump",
  "regionId": 2,
  "region": null,
  "shortName": "ciab",
  "state": "DC",
  "zip": "20500"
}}
```

DELETE

Deletes a *Physical Location*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 188: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Physical Location</i> being deleted

409: Request Example

```
DELETE /api/2.0/phys_locations/3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

410: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: KeW/tEmICwpCGC8F0YMTqHdeR9J6W6Z3w/
→U+HOSbeCGyaEheCIhIsWlngT3dyfH1tiu8UyzaPB6QrJyXdybBkw==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 00:28:48 GMT
Content-Length: 67

{ "alerts": [
  {
    "text": "physLocation was deleted.",
    "level": "success"
  }
]}
```

ping

Checks whether Traffic Ops is online.

GET

Auth. Required No

Response Type undefined

Request Structure

No parameters available.

411: Request Example

```
GET /api/2.0/ping HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

ping Returns an object containing only the "ping" property, which always has the value "pong".

412: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Whole-Content-Sha512: 0HqcLcYHCB4AFYGFzcAsP2h+PCmLYxk/
↪TqMajcy3fWCzY730Tv32k5trUaJLeSBbRx2FUi7z/sTAuzikdg0E4g==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 20:52:01 GMT
Content-Length: 40
Content-Type: application/x-gzip

{
```

(continues on next page)

(continued from previous page)

```
"ping": "pong"
}
```

plugins

See also:

Go Plugins

GET

Retrieves the list of configured enabled Traffic Ops plugins.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

413: Request Example

```
GET /api/2.0/plugins HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

description A short description of the plugin.

name The name of the plugin.

version A (hopefully) semantic version number describing the version of the plugin.

414: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST, GET, OPTIONS, PUT, DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Tue, 11 Dec 2018 20:51:48 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54L
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: n73jg9XR4V5Cwqq56Rf3wuIi99k3mM5u2NAjcZ/
→gQBu8jvAFymDlnZqKeJ+wTll1vjIsHpXCOVXV7+5UGakLgA==
Transfer-Encoding: chunked

{ "response": [
  {
    "name": "helloworld",
    "version": "1.0.0",
    "description": "configuration plugin to run at startup"
  }
]}

```

profileparameter

See also:

profileparameters.

POST

Create one or more *Profile/Parameter* assignments.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

profileId The *ID* of the *Profile* to which the *Parameters* identified within the *parameterIds* array will be assigned

paramIds An array of *Parameter IDs* which shall be assigned to the *Profile* identified by *profileId*

replace An optional boolean (default: false) which, if true, will cause any conflicting *Profile/Parameter* assignments to be overridden.

415: Request Example

```
POST /api/2.0/profileparameter HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 38
Content-Type: application/json

{
  "profileId": 18,
  "paramIds": [2, 3]
}
```

Response Structure

- profileId** The *ID* of the *Profile* to which the *Parameters* identified within the *parameterIds* array are assigned
- paramIds** An array of *Parameter IDs* which have been assigned to the *Profile* identified by *profileId*
- replace** An optional boolean (default: false) which, if true, indicates that any conflicting *Profile/Parameter* assignments have been overridden.

416: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→N2ahnhEnfZ0UqnjylN6Vu3HaOZk340YuiuyiqkhTbk0pENp+kwBPYu4Z/
→sqBAloCfXSQaWlJzaeXw4uOD5heWw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 15:18:23 GMT
Content-Length: 147

{ "alerts": [
  {
    "text": "2 parameters were assigned to the 18 profile",
```

(continues on next page)

(continued from previous page)

```

        "level": "success"
    }
],
"response": {
    "profileId": 18,
    "paramIds": [
        2,
        3
    ],
    "replace": false
}}

```

profileparameters

GET

Retrieves all *Parameter/Profile* assignments.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 189: Request Query Parameters

Name	Re- quired	Description
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Response Structure

lastUpdated The date and time at which this *Profile/Parameter* association was last modified, in *Traffic Ops's Custom Date/Time Format*

parameter The *ID* of a *Parameter* assigned to profile

profile The *Name* of the *Profile* to which the *Parameter* identified by parameter is assigned

417: Response Structure

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳+bnMkRgdx4bJoGGlr3mZl539obj3aQAP8e65FAXgywdRAUfXZCFM6VNDn7wScXBmvF2SFXo9F+MhuSwrtI
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 15:09:13 GMT
Transfer-Encoding: chunked

{ "response": [
  {
    "lastUpdated": "2018-12-05 17:50:49+00",
    "profile": "GLOBAL",
    "parameter": 4
  },
  {
    "lastUpdated": "2018-12-05 17:50:49+00",
    "profile": "GLOBAL",
    "parameter": 5
  }
]}
```

Note: The response example for this endpoint has been truncated to only the first two elements of the resulting array, as the output was hundreds of lines long.

POST

Associate a *Parameter* to a *Profile*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

This endpoint accepts two formats for the request payload:

Single Object Format For assigning a single *Parameter* to a single *Profile*

Array Format For making multiple assignments of *Parameters* to *Profiles* simultaneously

Single Object Format

parameterId The *ID* of a *Parameter* to assign to some *Profile*

profileId The *ID* of the *Profile* to which the *Parameter* identified by parameterId will be assigned

418: Request Example - Single Object Format

```
POST /api/2.0/profileparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 36
Content-Type: application/json

{
  "profileId": 18,
  "parameterId": 1
}
```

Array Format

parameterId The *ID* of a *Parameter* to assign to some *Profile*

profileId The *ID* of the *Profile* to which the *Parameter* identified by parameterId will be assigned

419: Request Example - Array Format

```
POST /api/2.0/profileparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 88
Content-Type: application/json

[
  {
    "profileId": 18,
    "parameterId": 2
  },
  {
    "profileId": 18,
    "parameterId": 3
  }
]
```

Response Structure

lastUpdated The date and time at which the *Profile/Parameter* assignment was last modified, in *Traffic Ops's Custom Date/Time Format*

parameter *Name* of the *Parameter* which is assigned to profile

parameterId The *ID* of the assigned *Parameter*

profile *Name* of the *Profile* to which the *Parameter* is assigned

profileId The *ID* of the *Profile* to which the *Parameter* identified by parameterId is assigned

420: Response Example - Single Object Format

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳eDmIwlzX44fZdxLRPHMNa8aoGAK5fQv9Y70A2eeQHfEkliU4evwcsQ4WeHcH0l3/
    ↳wPTGlpYC0gwLo8LQqpUxWQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 13:50:11 GMT
Content-Length: 166

{ "alerts": [
  {
    "text": "profileParameter was created.",
    "level": "success"
  }
],
"response": {
  "lastUpdated": null,
  "profile": null,
  "profileId": 18,
  "parameter": null,
  "parameterId": 1
}}
```

profileparameters/{{profileID}}/{{parameterID}}

DELETE

Deletes a *Profile/Parameter* association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 190: Request Path Parameters

Name	Description
profileID	The <i>ID</i> of the <i>Profile</i> from which a <i>Parameter</i> shall be removed
parameterID	The <i>ID</i> of the <i>Parameter</i> which shall be removed from the <i>Profile</i> identified by profileID

421: Request Example

```
DELETE /api/2.0/profileparameters/18/129 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

422: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳JQuBqHyT9MnNw09NSIDVQhkRtXdeAJc95W1pF2dwQeoBFmf0Y8knXm3/0/
    ↳rbJDEoUC7DhUQN1aoYIsqqmz4qQQ==
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

Date: Mon, 10 Dec 2018 15:00:15 GMT

Content-Length: 71

```
{ "alerts": [
  {
    "text": "profileParameter was deleted.",
    "level": "success"
  }
]}
```

profiles

GET

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 191: Request Query Parameters

Name	Re- quired	Description
cdn	no	Used to filter <i>Profiles</i> by the integral, unique identifier of the CDN to which they belong
id	no	Filters <i>Profiles</i> by <i>ID</i>
name	no	Filters <i>Profiles</i> by <i>Name</i>
param	no	Used to filter <i>Profiles</i> by the <i>ID</i> of a <i>Parameter</i> associated with them

423: Request Example

```
GET /api/2.0/profiles?name=ATS_EDGE_TIER_CACHE HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cdn** The integral, unique identifier of the *CDN* to which this *Profile* belongs
- cdnName** The name of the *CDN* to which this *Profile* belongs
- description** The *Profile*'s *Description*
- id** The *Profile*'s *ID*
- lastUpdated** The date and time at which this *Profile* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The *Profile*'s *Name*
- routingDisabled** The *Profile*'s *Routing Disabled* setting
- type** The *Profile*'s *Type*

424: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: QEpKM/
    ↳DwHBRvue9K7XKrpwKFKhW6yCMQ2vSQgxE7dWFGJaqC4KOU092bsJU/
    ↳5fjI9qlB+1uMT2kz6mFb1Wzp/w==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 20:40:31 GMT
Content-Length: 220

{ "response": [
  {
    "id": 9,
    "lastUpdated": "2018-12-05 17:51:00+00",
```

(continues on next page)

(continued from previous page)

```

    "name": "ATS_EDGE_TIER_CACHE",
    "description": "Edge Cache - Apache Traffic Server",
    "cdnName": "CDN-in-a-Box",
    "cdn": 2,
    "routingDisabled": false,
    "type": "ATS_PROFILE"
  }
}]

```

POST

Creates a new *Profile*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cdn The integral, unique identifier of the *CDN* to which this *Profile* shall belong

description The *Profile*’s *Description*

name The *Profile*’s *Name*

routingDisabled The *Profile*’s *Routing Disabled* setting

type The *Profile*’s *Type*

425: Request Example

```

POST /api/2.0/profiles HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 125
Content-Type: application/json

{
  "name": "test",
  "description": "A test profile for API examples",
  "cdn": 2,
  "type": "UNK_PROFILE",
  "routingDisabled": true
}

```

Response Structure

- cdn** The integral, unique identifier of the *CDN* to which this *Profile* belongs
- cdnName** The name of the *CDN* to which this *Profile* belongs
- description** The *Profile's Description*
- id** The *Profile's ID*
- lastUpdated** The date and time at which this *Profile* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The *Profile's Name*
- routingDisabled** The *Profile's Routing Disabled* setting
- type** The *Profile's Type*

426: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳UGV3PCnYBY0J3siICR0f9VVRNdUK1+9zsDDP6T9yt6t+AoHckHe6bvz0li9to/
    ↳fGhC2zz5l9Nc1ro4taJUDD8g==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 21:24:49 GMT
Content-Length: 251

{ "alerts": [
  {
    "text": "profile was created.",
    "level": "success"
  }
],
"response": {
  "id": 16,
  "lastUpdated": "2018-12-07 21:24:49+00",
  "name": "test",
  "description": "A test profile for API examples",
  "cdnName": null,
  "cdn": 2,
  "routingDisabled": true,
```

(continues on next page)

(continued from previous page)

```
"type": "UNK_PROFILE"
}}
```

profiles/{{ID}}

PUT

Replaces the specified *Profile* with the one in the request payload

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 192: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> being modified

cdn The integral, unique identifier of the *CDN* to which this *Profile* will belong

description The *Profile*’s new *Description*

name The *Profile*’s new *Name*

routingDisabled The *Profile*’s new *Routing Disabled* setting

type The *Profile*’s new *Type*

Warning: Changing this will likely break something, be **VERY** careful when modifying this value

427: Request Example

```
PUT /api/2.0/profiles/16 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 125
Content-Type: application/json

{
```

(continues on next page)

(continued from previous page)

```
"name": "test",
"description": "A test profile for API examples",
"cdn": 2,
"type": "UNK_PROFILE",
"routingDisabled": true
}
```

Response Structure

- cdn** The integral, unique identifier of the *CDN* to which this *Profile* belongs
- cdnName** The name of the *CDN* to which this *Profile* belongs
- description** The *Profile*'s *Description*
- id** The *Profile*'s *ID*
- lastUpdated** The date and time at which this *Profile* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The *Profile*'s *Name*
- routingDisabled** The *Profile*'s *Routing Disabled* setting
- type** The *Profile*'s *Type*

428: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Pnf+G9G3/
    ↳+edt4b8PVsyGZHsNzaFEgphaGSminjRlRmMpWtuLAA20WZDUo3nX0Q081c2GCuFuEh9uMF2Vjeppg==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 21:45:06 GMT
Content-Length: 251

{ "alerts": [
  {
    "text": "profile was updated.",
    "level": "success"
  }
],
```

(continues on next page)

(continued from previous page)

```
"response": {
  "id": 16,
  "lastUpdated": "2018-12-07 21:45:06+00",
  "name": "test",
  "description": "A test profile for API examples",
  "cdnName": null,
  "cdn": 2,
  "routingDisabled": true,
  "type": "UNK_PROFILE"
}}
```

DELETE

Allows user to delete a *Profile*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 193: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> being deleted

429: Request Example

```
DELETE /api/2.0/profiles/16 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

430: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: HNmJkZaNW9yil08/
→3TnqZ5FllH6Rp+jgp3KI46FZdojLYcu+8jEhDL1lokoirdrHyU4R1c3hjCI0urN7PVvWDA==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 21:55:33 GMT
Content-Length: 62

{ "alerts": [
  {
    "text": "profile was deleted.",
    "level": "success"
  }
]}
```

profiles/{{ID}}/export

GET

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 194: Request Path Parameters

Parameter	Description
id	The <i>ID</i> of the <i>Profile</i> to be exported

431: Request Example

```
GET /api/2.0/profiles/3/export HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- profile** The exported *Profile*
 - cdn** The name of the *CDN* to which this *Profile* belongs
 - description** The *Profile's Description*
 - name** The *Profile's Name*
 - type** The *Profile's Type*
- parameters** An array of *Parameters* in use by this *Profile*
 - config_file** The *Parameter's Config File*
 - name** *Name* of the *Parameter*
 - value** The *Parameter's Value*

432: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Disposition: attachment; filename="GLOBAL.json"
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mzP7DVxFAGhICxqagwDyBDRea7oBZPMAx7NCDeOBVCRqlcCFFe7XL3JP58b80aaVOW/
    ↳2ZGfg/jpYF70cdDfzQA==
X-Server-Name: traffic_ops_golang/
Date: Fri, 13 Sep 2019 20:14:42 GMT
Transfer-Encoding: gzip

{ "profile": {
  "name": "GLOBAL",
  "description": "Global Traffic Ops profile",
  "cdn": "ALL",
  "type": "UNK_PROFILE"
},
  "parameters": [
    {
      "config_file": "global",
      "name": "tm.instance_name",
      "value": "Traffic Ops CDN"
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```

    },
    {
      "config_file": "global",
      "name": "tm.toolname",
      "value": "Traffic Ops"
    }
  ]}

```

profiles/{{ID}}/parameters

GET

Retrieves all *Parameters* assigned to the *Profile*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 195: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> for which <i>Parameters</i> will be listed

433: Request Example

```

GET /api/2.0/parameters/profile/GLOBAL HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...

```

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name* of the *Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

434: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: NudgZXUNyKNpmSFf856KEjyy+Pin/
→bFhG9NoRBDaxYbRKt2T5fF5Ze7sUNZfFI5n/ZZsgbx6Tsgtfd7oM6j+eg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 21:08:56 GMT
Content-Length: 542

{ "response": [
  {
    "configFile": "global",
    "id": 4,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.instance_name",
    "secure": false,
    "value": "Traffic Ops CDN"
  },
  {
    "configFile": "global",
    "id": 5,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.toolname",
    "secure": false,
    "value": "Traffic Ops"
  },
  {
    "configFile": "global",
    "id": 6,
    "lastUpdated": "2018-12-05 17:50:51+00",
    "name": "use_tenancy",
    "secure": false,
    "value": "1"
  },
  {

```

(continues on next page)

(continued from previous page)

```

    "configFile": "regex_revalidate.config",
    "id": 7,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "maxRevalDurationDays",
    "secure": false,
    "value": "90"
  }
}]

```

POST

Associates *Parameters* to a *Profile*. If the *Parameter* does not exist, creates it and associates it to the *Profile*. If the *Parameter* already exists, associates it to the *Profile*. If the *Parameter* is already associated with the *Profile*, keep the association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 196: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> to which <i>Parameters</i> will be assigned

This endpoint accepts two formats for the request payload:

Single Object Format For assigning a single *Parameter* to a single *Profile*

Parameter Array Format For making multiple assignments of *Parameters* to *Profiles* simultaneously

Warning: Most API endpoints dealing with *Parameters* treat *Secure* as a boolean value, whereas this endpoint takes the legacy approach of treating it as an integer. Be careful when passing data back and forth, as boolean values will **not** be accepted by this endpoint!

Single Parameter Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

435: Response Example - Single Parameter Format

```
POST /api/2.0/profiles/18/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 99
Content-Type: application/json

{
  "name": "test",
  "configFile": "quest",
  "value": "A test parameter for API examples",
  "secure": 0
}
```

Parameter Array Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

436: Request Example - Parameter Array Format

```
POST /api/2.0/profiles/18/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 212
Content-Type: application/json

[ {
  "name": "test",
  "configFile": "quest",
```

(continues on next page)

(continued from previous page)

```

    "value": "A test parameter for API examples",
    "secure": 0
  },
  {
    "name": "foo",
    "configFile": "bar",
    "value": "Another test parameter for API examples",
    "secure": 0
  }
]
```

Response Structure

parameters An array of objects representing the *Parameters* which have been assigned

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

profileId The *ID* of the *Profile* to which the *Parameter(s)* have been assigned

profileName *Name* of the *Profile* to which the *Parameter(s)* have been assigned

437: Response Example - Single Parameter Format

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: R2QUyCaNvKvVv/PNVNmEd/ma5h/iP1fMJlqhv+x2jE/
→zNpHJ1KVXt6s3btB8nnHv6IDF/gt5kIzQ0mbW5U8bpg==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 14:45:28 GMT
Content-Length: 253

{ "alerts": [
  {
    "text": "Assign parameters successfully to profile test",
```

(continues on next page)

(continued from previous page)

```

        "level": "success"
    }
],
"response": {
    "parameters": [
        {
            "configFile": "quest",
            "name": "test",
            "secure": 0,
            "value": "A test parameter for API examples",
            "id": 126
        }
    ],
    "profileId": 18,
    "profileName": "test"
}}

```

Note: The format of the request does not affect the format of the response. `parameters` will be an array either way.

profiles/import

POST

Imports a *Profile* that was exported via *profiles/{ID}/export*

Note: On import of the *Profile Parameters* if a *Parameter* already exists with the same *Name*, *Config File* and *Value* it will link that to the *Profile* instead of creating it.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

- profile** The exported *Profile*
 - cdn** The name of the *CDN* to which this *Profile* belongs
 - description** The *Profile's Description*
 - name** The *Profile's Name*
 - type** The *Profile's Type*
- parameters** An array of *Parameters* in use by this *Profile*
 - config_file** The *Parameter's Config File*
 - name** *Name* of the *Parameter*
 - value** The *Parameter's Value*

438: Request Example

```
POST /api/2.0/profiles/import HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Type: application/json

{ "profile": {
  "name": "GLOBAL",
  "description": "Global Traffic Ops profile",
  "cdn": "ALL",
  "type": "UNK_PROFILE"
},
"parameters": [
  {
    "config_file": "global",
    "name": "tm.instance_name",
    "value": "Traffic Ops CDN"
  },
  {
    "config_file": "global",
    "name": "tm.toolname",
    "value": "Traffic Ops"
  }
]
}
```

Response Structure

cdn The name of the *CDN* to which this *Profile* belongs

description The *Profile's Description*

name The *Profile's Name*

type The *Profile's Type*

id The *Profile's ID*

439: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mzP7DVxFAGhICxqagwDyBDRea7oBZPMAx7NCDeOBVCRqlcCFFe7XL3JP58b80aaVOW/
    ↳2ZGfg/jpYF70cdDfzQA==
X-Server-Name: traffic_ops_golang/
Date: Fri, 13 Sep 2019 20:14:42 GMT
Transfer-Encoding: gzip

{ "alerts": [
  {
    "level": "success",
    "text": "Profile imported [ Global ] with 2 new and 0 existing
    ↳parameters"
  }
],
"response": {
  "cdn": "ALL",
  "name": "Global",
  "id": 18,
  "type": "UNK_PROFILE",
  "description": "Global Traffic Ops profile"
}}
```

`profiles/name/{{name}}/copy/{{copy}}`

POST

Copy *Profile* to a new *Profile*. The new *Profile*'s *Name* must not already exist.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 197: Request Path Parameters

Name	Description
name	The <i>Name</i> of the new <i>Profile</i>
copy	The <i>Name</i> of <i>Profile</i> from which the copy will be made

440: Request Example

```
POST /api/2.0/profiles/name/GLOBAL_copy/copy/GLOBAL HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

description The new *Profile*'s *Description*

id The *ID* of the new *Profile*

idCopyFrom The *ID* of the *Profile* from which the copy was made

name The *Name* of the new *Profile*

profileCopyFrom The *Name* of the *Profile* from which the copy was made

441: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Fri, 07 Dec 2018 22:03:54 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:↵
→r6V9viEZui1WCns0AUGEx1MtxjjXiU8SZV0tSQjeq7ZJDL15s8fMmjJdR/
→HRWduHn7Ax6GzYhoKwnIjMyc7ZWg==
Content-Length: 252

{ "alerts": [
  {
    "level": "success",
    "text": "Created new profile [ GLOBAL_copy ] from existing↵
→profile [ GLOBAL ]"
  }
],
"response": {
  "idCopyFrom": 1,
  "name": "GLOBAL_copy",
  "profileCopyFrom": "GLOBAL",
  "id": 17,
  "description": "Global Traffic Ops profile, DO NOT DELETE"
}}
```

`profiles/name/{name}}/parameters`

GET

Retrieves all *Parameters* associated with a given *Profile*

Auth. Required Yes

Roles Required None

Response Type None

Request Structure

Table 198: Request Path Parameters

Name	Description
name	The <i>Name</i> of the <i>Profile</i> for which <i>Parameters</i> will be listed

442: Request Example

```
GET /api/2.0/profiles/name/GLOBAL/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- configFile** The *Parameter's Config File*
- id** The *Parameter's ID*
- lastUpdated** The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** *Name* of the *Parameter*
- profiles** An array of *Profile Names* that use this *Parameter*
- secure** A boolean value that describes whether or not the *Parameter* is *Secure*
- value** The *Parameter's Value*

443: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: NudgZXUNyKNpmSFf856KEjyy+Pin/
→bFhG9NoRBDaxYbRKt2T5fF5Ze7sUNZfFI5n/ZZsgbx6Tsgtfd7oM6j+eg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 21:52:08 GMT
Content-Length: 542
```

(continues on next page)

(continued from previous page)

```
{ "response": [
  {
    "configFile": "global",
    "id": 4,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.instance_name",
    "secure": false,
    "value": "Traffic Ops CDN"
  },
  {
    "configFile": "global",
    "id": 5,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.toolname",
    "secure": false,
    "value": "Traffic Ops"
  },
  {
    "configFile": "global",
    "id": 6,
    "lastUpdated": "2018-12-05 17:50:51+00",
    "name": "use_tenancy",
    "secure": false,
    "value": "1"
  },
  {
    "configFile": "regex_revalidate.config",
    "id": 7,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "maxRevalDurationDays",
    "secure": false,
    "value": "90"
  }
]}
}
```

POST

Associates *Parameters* to a *Profile*. If the *Parameter* does not exist, creates it and associates it to the *Profile*. If the *Parameter* already exists, associates it to the *Profile*. If the *Parameter* is already associated with the *Profile*, keep the association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 199: Request Path Parameters

Name	Description
name	The <i>Name</i> of the <i>Profile</i> to which <i>Parameters</i> will be assigned

This endpoint accepts two formats for the request payload:

Single Parameter Format Specify a single parameter to assign to the specified profile

Parameter Array Format Specify multiple parameters to assign to the specified profile

Warning: Most API endpoints dealing with parameters treat `secure` as a boolean value, whereas this endpoint takes the legacy approach of treating it as an integer. Be careful when passing data back and forth, as boolean values will **not** be accepted by this endpoint!

Single Parameter Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

444: Request Example - Single Parameter Format

```
POST /api/2.0/profiles/name/test/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 99
Content-Type: application/json

{
  "name": "test",
  "configFile": "quest",
  "value": "A test parameter for API examples",
  "secure": 0
}
```

Parameter Array Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

445: Request Example - Parameter Array Format

```
POST /api/2.0/profiles/name/test/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 212
Content-Type: application/json

[{"name": "test",
  "configFile": "quest",
  "value": "A test parameter for API examples",
  "secure": 0},
 {"name": "foo",
  "configFile": "bar",
  "value": "Another test parameter for API examples",
  "secure": 0}]
```

Response Structure

parameters An array of objects representing the *Parameters* which have been assigned

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

profileId The *ID* of the *Profile* to which the *Parameter(s)* have been assigned

profileName *Name* of the *Profile* to which the *Parameter(s)* have been assigned

446: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: HQWq0koYHjvcxheWPrH0b0oZnUC+qLG1L040jtsLLnZYVUIu/
    ↳qgJrzvziPnKq3FEHUWaZrnDCZM/iZD8AXOKBw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 14:20:22 GMT
Content-Length: 357

{ "alerts": [
  {
    "text": "Assign parameters successfully to profile test",
    "level": "success"
  }
],
"response": {
  "parameters": [
    {
      "configFile": "quest",
      "name": "test",
      "secure": 0,
      "value": "A test parameter for API examples",
      "id": 126
    },
    {
      "configFile": "bar",
      "name": "foo",
      "secure": 0,
      "value": "Another test parameter for API examples",
      "id": 129
    }
  ],
  "profileId": 18,
  "profileName": "test"
}}
```

Note: The format of the request does not affect the format of the response. parameters will

be an array either way.

regions

GET

Retrieves information about *Regions*

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 200: Request Query Parameters

Name	Required	Description
division	no	Filter <i>Regions</i> by the integral, unique identifier of the <i>Division</i> which contains them
id	no	Filter <i>Regions</i> by integral, unique identifier
name	no	Filter <i>Regions</i> by name
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

447: Request Example

```
GET /api/2.0/regions?division=1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- divisionName** The name of the division which contains this region
- divisionId** The integral, unique identifier of the division which contains this region
- id** An integral, unique identifier for this region
- lastUpdated** The date and time at which this region was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The region name

448: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳nSYbR+fRXaxhYl7dWgf0Udo2AsiXEnwvED1CPbk7ZNWK03I3TOhtmCQx9ABnJJ6xKYnl6EKMeopVTK0n
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 01:58:38 GMT
Content-Length: 117

{ "response": [
  {
    "divisionName": "Quebec",
    "division": 1,
    "id": 2,
    "lastUpdated": "2018-12-05 17:50:58+00",
    "name": "Montreal"
  }
]}
```

POST

Creates a new region

- Auth. Required** Yes
- Roles Required** “admin” or “operations”
- Response Type** Object

Request Structure

division The integral, unique identifier of the division which shall contain the new region¹

divisionName The name of the division which shall contain the new region¹

name The name of the region

449: Request Example

```
POST /api/2.0/regions HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 65
Content-Type: application/json

{
  "name": "Manchester",
  "division": "4",
  "divisionName": "England"
}
```

Response Structure

divisionName The name of the division which contains this region

divisionId The integral, unique identifier of the division which contains this region

id An integral, unique identifier for this region

lastUpdated The date and time at which this region was last updated, in *Traffic Ops's Custom Date/Time Format*

name The region name

450: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➦Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

¹ The only “division” key that actually matters in the request body is `division`; `divisionName` is not validated and has no effect - particularly not the effect of re-naming the division - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the division. Note that if `divisionName` is not present in the request body it will be `null` in the response, but again further requests will show the true division name (provided it has been assigned to a division).

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→ezxk+iP7o7KE7zpWmGc0j8nz5k+1wAzY0HiNiA2xswTQrt+N+6CgQqUV2r9G1HAsPNr0HF2PhYs/
→Xr7DrYOW0A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 02:14:45 GMT
Content-Length: 178

{ "alerts": [
  {
    "text": "region was created.",
    "level": "success"
  }
],
"response": {
  "divisionName": "England",
  "division": 3,
  "id": 5,
  "lastUpdated": "2018-12-06 02:14:45+00",
  "name": "Manchester"
}}
```

DELETE

Deletes a region. If no query parameter is specified, a 400 Bad Request response is returned.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 201: Request Query Parameters

Name	Required	Description
id	no	Delete <i>Region</i> by integral, unique identifier
name	no	Delete <i>Region</i> by name

451: Request Example

```
DELETE /api/2.0/regions?name=Manchester HTTP/1.1
User-Agent: curl/7.29.0
Host: trafficops.infra.ciab.test
Accept: */*
Cookie: mojolicious=...
```

Response Structure

452: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Fri, 07 Feb 2020 13:56:24
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳yNqXKcoiohEbJrEkH8LD1zifh87dIusuvUqgQnYueyKqCXkfd5bQvQ00hQ2AAdSZa/
    ↳oe2SAqMjojGsUlxHtIQw==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Feb 2020 12:56:24 GMT
Content-Length: 62

{
  "alerts": [
    {
      "text": "region was deleted.",
      "level": "success"
    }
  ]
}
```


regions/{{ID}}

PUT

Updates a *Region*.

Auth. Required Yes

Role(s) Required “admin” or “operator”

Response Type Object

Request Structure

Table 202: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the region to update

division The new integral, unique identifier of the division which shall contain the region¹

divisionName The new name of the division which shall contain the region¹

name The new name of the region

453: Request Example

```
PUT /api/2.0/regions/5 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 60
Content-Type: application/json

{
  "name": "Leeds",
  "division": 3,
  "divisionName": "England"
}
```

¹ The only “division” key that actually matters in the request body is `division`; `divisionName` is not validated and has no effect - particularly not the effect of re-naming the division - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the division. Note that if `divisionName` is not present in the request body it will be `null` in the response, but again further requests will show the true division name (provided it has been assigned to a division).

Response Structure

- divisionName** The name of the division which contains this region
- divisionId** The integral, unique identifier of the division which contains this region
- id** An integral, unique identifier for this region
- lastUpdated** The date and time at which this region was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The region name

454: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳7SVj4q7dtSTNQEJlBApEwlad28WBVFnpdHaatoIpNfeLltfcpcdVTcOKB4JXQv7rlSD2p/
    ↳TxBQC6EXpxwYTnKQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 02:23:40 GMT
Content-Length: 173

{ "alerts": [
  {
    "text": "region was updated.",
    "level": "success"
  }
],
"response": {
  "divisionName": "England",
  "division": 3,
  "id": 5,
  "lastUpdated": "2018-12-06 02:23:40+00",
  "name": "Leeds"
}}
```

roles

GET

Retrieves all user *Roles*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 203: Request Query Parameters

Name	Re- quired	Description
id	no	Return only the <i>Role</i> identified by this integral, unique identifier
name	no	Return only the <i>Role</i> with this name
privLevel	no	Return only those <i>Roles</i> that have this privilege level
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page .

455: Request Example

```
GET /api/2.0/roles?name=admin HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

capabilities An array of the names of the Capabilities given to this *Role*

description A description of the *Role*

id The integral, unique identifier for this *Role*

name The name of the *Role*

privLevel An integer that allows for comparison between *Roles*

456: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→TEDXlQqWMSnJbL10JtFdbw0nqciNpjc4bd6m7iAB8aymakWeF+ghs1k5LayjdzHcjeDE8UNF/
→HXSxOFvoLFEuA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 04 Sep 2019 17:15:36 GMT
Content-Length: 120

{ "response": [
  {
    "id": 4,
    "name": "admin",
    "description": "super-user",
    "privLevel": 30,
    "capabilities": [
      "all-write",
      "all-read"
    ]
  }
]
```

(continues on next page)

(continued from previous page)

```
}
[]}
```

POST

Creates a new *Role*.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

capabilities An optional array of capability names that will be granted to the new *Role*

description A helpful description of the *Role*’s purpose.

name The name of the new *Role*

privLevel The privilege level of the new *Role*¹

457: Request Example

```
POST /api/2.0/roles HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "name": "test",
  "description": "quest",
  "privLevel": 30
}
```

¹ **privLevel** cannot exceed the privilege level of the requesting user. Which, of course, must be the privilege level of “admin”. Basically, this means that there can never exist a *Role* with a higher privilege level than “admin”.

Response Structure

capabilities An array of the names of the Capabilities given to this *Role*

Tip: This can be null *or* empty, depending on whether it was present in the request body, or merely empty. Obviously, it can also be a populated array.

description A description of the *Role*

id The integral, unique identifier for this *Role*

name The name of the *Role*

privLevel An integer that allows for comparison between *Roles*

458: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: gzfc7m/
    ↳in5vVsVP+Y9h6JJfDhgpXKn9VAzoiPENhKbQfP8Q6jug08Rt2AK/
    ↳3Nz1cx5zZ8P9IjVxDdIg7mlC8bw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 04 Sep 2019 17:44:42 GMT
Content-Length: 150

{ "alerts": [{
    "text": "role was created.",
    "level": "success"
}],
  "response": {
    "id": 5,
    "name": "test",
    "description": "quest",
    "privLevel": 30,
    "capabilities": null
  }
}
```

PUT

Replaces an existing *Role* with one provided by the request.

Auth. Required Yes

Roles Required “admin”

Response Type

Request Structure

Table 204: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Role</i> to be replaced

capabilities An optional array of capability names that will be granted to the new *Role*

Warning: When not present, the affected *Role*’s Capabilities will be unchanged - *not* removed, unlike when the array is empty.

description A helpful description of the *Role*’s purpose.

name The new name of the *Role*

privLevel The new privilege level of the new *Role*^{Page 761, 1}

459: Request Example

```
PUT /api/2.0/roles?id=5 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "name": "test",
  "privLevel": 29,
  "description": "quest"
}
```

Response Structure

capabilities An array of the names of the Capabilities given to this *Role*

Tip: This can be null *or* empty, depending on whether it was present in the request body, or merely empty. Obviously, it can also be a populated array.

Warning: If no **capabilities** array was given in the request, this will *always* be null, even if the *Role* has Capabilities that would have gone unchanged.

description A description of the *Role*

id The integral, unique identifier for this *Role*

name The name of the *Role*

privLevel An integer that allows for comparison between *Roles*

460: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mlHQenE1Q3gjrIK21C2hfueQOaTCpdYefboN0A9vYPUIwTiaF5ZaAMPQBdfGyiAhgHRxowITs3bR7s1L+
X-Server-Name: traffic_ops_golang/
Date: Thu, 05 Sep 2019 12:56:46 GMT
Content-Length: 150

{
  "alerts": [
    {
      "text": "role was updated.",
      "level": "success"
    }
  ],
  "response": {
    "id": 5,
    "name": "test",
```

(continues on next page)

(continued from previous page)

```

    "description": "quest",
    "privLevel": 29,
    "capabilities": null
  }
}

```

DELETE

Deletes a *Role*

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 205: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Role</i> to be replaced

461: Request Example

```

DELETE /api/2.0/roles?id=5 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...

```

Response Structure

462: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly

```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: 10jeFZihtbvAus/XyHAW8rhgS9JBD+X/
→ezCp1iExYkEcHxN4gjr1L6x8zDFXORueBSlFldgtbWKT7QsmwCHUWA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 05 Sep 2019 13:02:06 GMT
Content-Length: 59

{ "alerts": [{
  "text": "role was deleted.",
  "level": "success"
}]}
```

server_capabilities

GET

Retrieves *Server Capabilities*.

Auth. Required Yes

Roles Required “read-only”

Response Type Array

Request Structure

Table 206: Request Query Parameters

Name	Required	Description
name	no	Return the <i>Server Capability</i> with this name

463: Request Structure

```
GET /api/2.0/server_capabilities?name=RAM HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

name The name of this *Server Capability*

lastUpdated The date and time at which this *Server Capability* was last updated, in ISO-like format

464: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpGT3YRyKJ/
→p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 21:36:13 GMT
Content-Length: 68

{
  "response": [
    {
      "name": "RAM",
      "lastUpdated": "2019-10-07 20:38:24+00"
    }
  ]
}
```

POST

Create a new *Server Capability*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the *Server Capability*

465: Request Example

```
POST /api/2.0/server_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 15
Content-Type: application/json

{
  "name": "RAM"
}
```

Response Structure

name The name of this *Server Capability*

lastUpdated The date and time at which this *Server Capability* was last updated, in ISO-like format

466: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ysdopC//
→JQI79BRUa61s6M2HzHxYHpo5Rdcuau0oqCYxiV0oUhNZfOVydVkv8zDN2qA374XKnym4kWj3VzQIXg==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:10:00 GMT
Content-Length: 137

{
  "alerts": [
    {
      "text": "server capability was created.",
      "level": "success"
    }
  ],
  "response": {
    "name": "RAM",
    "lastUpdated": "2019-10-07 22:10:00+00"
  }
}
```

DELETE

Deletes a specific *Server Capability*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 207: Request Query Parameters

Name	Required	Description
name	yes	The name of the <i>Server Capability</i> to be deleted

467: Request Example

```
DELETE /api/2.0/server_capabilities?name=RAM HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

468: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 8zCAATbCzcqiqigGVBy7WF1duDuXu1Wg2DBe9yfqTw/
    ↳c+yhE2eUk73hFTA/Oqt0kocaN7+1GkbFdPkQPvbnRaA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 20:44:40 GMT
Content-Length: 72

{
  "alerts": [
    {
      "text": "server capability was deleted.",
      "level": "success"
    }
  ]
}
```

server_server_capabilities

GET

Gets all associations of *Server Capabilities* to *cache servers*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 208: Request Query Parameters

Name	Re- quired	Description
serverId	no	Filter <i>Server Capability</i> associations by the integral, unique identifier of the server to which they are assigned
server- Host- Name	no	Filter <i>Server Capability</i> associations by the host name of the server to which they are assigned
server- Ca- pabil- ity	no	Filter <i>Server Capability</i> associations by <i>Server Capability</i> name
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

469: Request Example

```
GET /api/2.0/server_server_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

serverHostName The server’s host name

serverId The server’s integral, unique identifier

lastUpdated The date and time at which this association between the server and the *Server Capability* was last updated, in *Traffic Ops’s Custom Date/Time Format*

serverCapability The *Server Capability*’s name

470: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
→jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
→DbBwhMAOJoeqDImoDlrLnrVjQG04AooA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 150

{
  "response": [
    {
      "lastUpdated": "2019-10-07 22:05:31+00",
      "serverHostName": "atlanta-org-1",
      "serverId": 260,
      "serverCapability": "ram"
    },
    {
      "lastUpdated": "2019-10-07 22:05:31+00",
      "serverHostName": "atlanta-org-2",
      "serverId": 261,
      "serverCapability": "disk"
    }
  ]
}
```

POST

Associates a *Server Capability* to a server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

serverId The integral, unique identifier of a server to be associated with a *Server Capability*

serverCapability The *Server Capability*'s name to associate

Note: The server referenced must be either an *Edge-tier* or *Mid-tier cache server*.

471: Request Example

```
POST /api/2.0/server_server_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 84
Content-Type: application/json

{
  "serverId": 1,
  "serverCapability": "disk"
}
```

Response Structure

serverId The integral, unique identifier of the newly associated server

lastUpdated The date and time at which this association between the server and the *Server Capability* was last updated, in *Traffic Ops's Custom Date/Time Format*

serverCapability The *Server Capability*'s name

472: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
  ↳Cfh2X9i3G+MQ36eH95gukJqOBObQ==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 157

{
  "alerts": [
    {
      "text": "server server_capability was created.",
      "level": "success"
    }
  ],
  "response": {
    "lastUpdated": "2019-10-07 22:15:11+00",
    "serverId": 1,
    "serverCapability": "disk"
  }
}
```

DELETE

Disassociate a server from a *Server Capability*.

Note: If the serverCapability is a *Server Capability* required by a *Delivery Service* that to which the server is assigned the DELETE will be blocked until either the server is unassigned from the *Delivery Service* or the *Server Capability* is no longer required by the *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 209: Request Query Parameters

Name	Re-quired	Description
serverId	yes	The integral, unique identifier of the server to disassociate
serverCapabil-ity	yes	term: <i>Server Capability</i> name to disassociate from given server

473: Request Example

```
DELETE /api/2.0/server_server_capabilities?serverId=1&
→serverCapability=disk HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

474: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
→jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
→DbBwhMAOJoeqDImoDlrLnrVjQG04AooA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 96

{
  "alerts": [
    {
      "text": "server server_capability was deleted.",
      "level": "success"
    }
  ]
}
```

servercheck

See also:

Check Extensions

GET

Fetches identifying and meta information as well as “check” values regarding all servers that have a *Type* with a name beginning with “EDGE” or “MID” (ostensibly this is equivalent to all *cache servers*).

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

Response Structure

adminState The name of the server’s *Status* - called “adminState” for legacy reasons

cacheGroup The name of the *Cache Group* to which the server belongs

checks An optionally present map of the names of “checks” to their values. Only numeric and boolean checks are represented, and boolean checks are represented as integers with 0 meaning “false” and 1 meaning “true”. Will not appear if the server in question has no valued “checks”.

hostName The (short) hostname of the server

id The server’s integral, unique identifier

profile The name of the *Profile* used by the server

revalPending A boolean that indicates whether or not the server has pending revalidations

type The name of the server’s *Type*

updPending A boolean that indicates whether or not the server has pending updates

475: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Thu, 23 Jan 2020 20:00:19
    ↳GMT; Max-Age=3600; HttpOnly
X-Server-Name: traffic_ops_golang/
Date: Thu, 23 Jan 2020 19:00:19 GMT
Content-Length: 352

{ "response": [
  {
    "adminState": "REPORTED",
    "cacheGroup": "CDN_in_a_Box_Edge",
    "id": 12,
    "hostName": "edge",
    "revalPending": false,
    "profile": "ATS_EDGE_TIER_CACHE",
    "type": "EDGE",
    "updPending": false
  },
  {
    "adminState": "REPORTED",
    "cacheGroup": "CDN_in_a_Box_Mid",
    "id": 11,
    "hostName": "mid",
    "revalPending": false,
    "profile": "ATS_MID_TIER_CACHE",
    "type": "MID",
    "updPending": false
  }
]}

```

POST

Post a server check result to the “serverchecks” table. Updates the resulting value from running a given check extension on a server.

Auth. Required Yes

Roles Required None¹

Response Type Object

Request Structure

The request only requires to have either `host_name` or `id` defined.

host_name The hostname of the server to which this “servercheck” refers.

id The id of the server to which this “servercheck” refers.

servercheck_short_name The short name of the “servercheck”.

value The value of the “servercheck”

¹ No roles are required to use this endpoint, however access is controlled by username. Only the reserved user extension is permitted the use of this endpoint.

476: Request Example

```
POST /api/2.0/servercheck HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 113
Content-Type: application/json

{
  "id": 1,
  "host_name": "edge",
  "servercheck_short_name": "test",
  "value": 1
}
```

Response Structure

477: Response Example

```
{ "alerts": [
  {
    "level": "success",
    "text": "Server Check was successfully updated."
  }
]}
```

servercheck/extensions

See also:

Managing Traffic Ops Extensions

GET

Retrieves the list of Traffic Ops extensions.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 210: Request Query Parameters

Name	Required	Description
id	no	Filter TO Extensions by the integral, unique identifier of an Extension
name	no	Filter TO Extensions by the name of an Extension
script_file	no	Filter TO Extensions by the base filename of the script that runs for the Extension
is-active	no	Boolean used to return either only active (1) or inactive(0) TO Extensions
type	no	Filter TO Extensions by the type of Extension
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

478: Request Example

```
GET /api/2.0/servercheck/extensions HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

additional_config_json A string containing a JSON-encoded object with extra configuration options... inside a JSON object...

description A short description of the extension

Note: This is, unfortunately, `null` for all default extensions

id An integral, unique identifier for this extension definition

info_url A URL where info about this extension may be found

isactive An integer describing the boolean notion of whether or not the extension is active; one of:

0 disabled

1 enabled

name The name of the extension

script_file The base filename of the script that runs for the extension

servercheck_shortcode The name of the column in the table at ‘Monitor’ -> ‘Cache Checks’ in Traffic Portal, where “Check Extension” output is displayed

type The Check *Type* of the extension. This will always be a `CHECK_EXTENSION` type with the naming convention of `CHECK_EXTENSION_*`.

version A (hopefully) semantic version number describing the version of the plugin

479: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST, GET, OPTIONS, PUT, DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Tue, 11 Dec 2018 20:51:48 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: n73jg9XR4V5Cwqq56Rf3wuIi99k3mM5u2NAjcZ/
→gQBu8jvAFymDlnZqKeJ+wTll1vjIsHpXCOVXV7+5UGakLgA==
Transfer-Encoding: chunked

{ "response": [
  {
    "script_file": "ToPingCheck.pl",
    "version": "1.0.0",
    "name": "ILO_PING",
    "description": null,
    "info_url": "-",
    "additional_config_json": "{ check_name: \"ILO\", \"base_url\
→\": \"https://localhost\", \"select\": \"ilo_ip_address\", \"cron\": \
→\"9 * * * *\" }",
    "isactive": 1,
    "type": "CHECK_EXTENSION_BOOL",
    "id": 1,
    "servercheck_short_name": "ILO"
  },
  {
    "script_file": "ToPingCheck.pl",
    "version": "1.0.0",
    "name": "10G_PING",
    "description": null,
    "info_url": "-",
    "additional_config_json": "{ check_name: \"10G\", \"base_url\
→\": \"https://localhost\", \"select\": \"ip_address\", \"cron\": \"18.
→* * * *\" }",
    "isactive": 1,
    "type": "CHECK_EXTENSION_BOOL",
    "id": 2,
    "servercheck_short_name": "10G"
  }
]
```

POST

Creates a new Traffic Ops check extension.

Auth. Required Yes

Roles Required None¹

Response Type undefined

Request Structure

additional_config_json An optional string containing a JSON-encoded object with extra configuration options... inside a JSON object...

description A short description of the extension

info_url A URL where info about this extension may be found

isactive An integer describing the boolean notion of whether or not the extension is active; one of:

0 disabled

1 enabled

name The name of the extension

script_file The base filename of the script that runs for the extension

See also:

Managing Traffic Ops Extensions for details on where the script should be located on the Traffic Ops server

servercheck_shortcode The name of the column in the table at ‘Monitor’ -> ‘Cache Checks’ in Traffic Portal, where “Check Extension” output is displayed

type The *Type* of extension. Must be CHECK_EXTENSION type with the naming convention of CHECK_EXTENSION_*.

version A (hopefully) semantic version number describing the version of the plugin

480: Request Example

```
POST /api/2.0/servercheck/extensions HTTP/1.1
Host: ipcdn-cache-51.cdnlab.comcast.net:6443
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

(continues on next page)

¹ No roles are required to use this endpoint, however access is controlled by username. Only the reserved user extension is permitted the use of this endpoint.

(continued from previous page)

```
Content-Length: 208
Content-Type: application/json

{
  "name": "test",
  "version": "0.0.1-1",
  "info_url": "",
  "script_file": "",
  "isactive": 0,
  "description": "A test extension for API examples",
  "servercheck_short_name": "test",
  "type": "CHECK_EXTENSION_NUM"
}
```

Response Structure

481: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 12 Dec 2018 16:37:44 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 7M67PYnli6WzGQFS3g8Gh1SOyq6VENZMqm/
→kUffOTLLFfuWSEuSLA65R5R+VyJiNjdqOG5Bp78mk+JYcqhtVGw==
Content-Length: 89

{ "supplemental":
  {
    "id": 5
  },
  "alerts": [{
    "level": "success",
    "text": "Check Extension Loaded."
  }]
}
```

`servercheck/extensions/{{ID}}`

DELETE

Deletes a Traffic Ops server check extension definition. This does **not** delete the actual extension file.

Auth. Required Yes

Roles Required None¹

Response Type undefined

Request Structure

Table 211: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the extension definition to be deleted

482: Request Example

```
DELETE /api/2.0/servercheck/extensions/16 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

483: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 12 Dec 2018 16:33:52 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

¹ No roles are required to use this endpoint, however access is controlled by username. Only the reserved user extension is permitted the use of this endpoint.

(continued from previous page)

```
Vary: Accept-Encoding
Whole-Content-Sha512: EB0Nu85azbGzaehDTA0DP3NPqWbByIza1XQhgwtsW2WTXyK/
↳dxQtncp0YiJXy00tH9H+n+6BBfojB0b5h0dFPA==
Content-Length: 60

{ "alerts": [
  {
    "level": "success",
    "text": "Extension deleted."
  }
]}
```

servers

GET

Retrieves properties of all servers across all CDNs.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 212: Request Query Parameters

Name	Re-quired	Description
cacheGroup	no	Return only those servers within the <i>Cache Group</i> that has this <i>ID</i>
dsId	no	Return only those servers assigned to the <i>Delivery Service</i> identified by this integral, unique identifier
host-Name	no	Return only those servers that have this (short) hostname
id	no	Return only the server with this integral, unique identifier
profileId	no	Return only those servers that are using the <i>Profile</i> that has this <i>ID</i>
status	no	Return only those servers with this status - see <i>Health Protocol</i>
type	no	Return only servers of this <i>Type</i>
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

484: Request Example

```
GET /api/2.0/servers?hostName=mid HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

cacheGroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId The integral, unique identifier of the CDN to which the server belongs

cdnName Name of the CDN to which the server belongs

domainName The domain part of the server’s FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be `null`

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service¹

iloIpGateway The IPv4 gateway address of the server's ILO service¹

iloIpNetmask The IPv4 subnet mask of the server's ILO service¹

iloPassword The password of the of the server's ILO service user¹ - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' *Role(s)*

iloUsername The user name for the server's ILO service¹

interfaceMtu The MTU configured on `interfaceName`

interfaceName The name of the primary network interface used by the server

ip6Address The IPv6 address and subnet mask of `interfaceName`

ip6IsService A boolean value which if `true` indicates that the IPv6 address will be used for routing content.

ip6Gateway The IPv6 address of the gateway used by `interfaceName`

ipAddress The IPv4 address of `interfaceName`

ipIsService A boolean value which if `true` indicates that the IPv4 address will be used for routing content.

ipGateway The IPv4 address of the gateway used by `interfaceName`

ipNetmask The IPv4 subnet mask used by `interfaceName`

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server used for 'management'

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for 'management'

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for 'management'

¹ For more information see the [Wikipedia page on Lights-Out management](#).

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status

physLocation The name of the physical location where the server resides

physLocationId An integral, unique identifier for the physical location where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

profileId The *ID* the *Profile* used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack A string indicating “server rack” location

routerHostName The human-readable name of the router responsible for reaching this server

routerPortName The human-readable name of the port used by the router responsible for reaching this server

status The *Status* of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the *Type* of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

485: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳WyapQctUIhjzEALka5QbBiZRZ58Mlc6MJSwjBeGyJS2UzbL3W6lN/
    ↳4kvAZtPrP4qMWQBWz6JjbF7Y5lNRASUmQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 16:13:31 GMT
Content-Length: 939

{ "response": [
  {
    "cachegroup": "CDN_in_a_Box_Mid",
    "cachegroupId": 6,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "domainName": "infra.ciab.test",
    "guid": null,
    "hostName": "mid",
    "httpsPort": 443,
    "id": 10,
    "iloIpAddress": "",
    "iloIpGateway": "",
    "iloIpNetmask": "",
    "iloPassword": "",
    "iloUsername": "",
    "interfaceMtu": 1500,
    "interfaceName": "eth0",
    "ip6Address": "fc01:9400:1000:8::120",
    "ip6Gateway": "fc01:9400:1000:8::1",
    "ipAddress": "172.16.239.120",
    "ipGateway": "172.16.239.1",
    "ipNetmask": "255.255.255.0",
    "lastUpdated": "2018-12-05 18:45:05+00",
    "mgmtIpAddress": "",
    "mgmtIpGateway": "",
    "mgmtIpNetmask": "",
    "offlineReason": "",
    "physLocation": "Apachecon North America 2018",
  }
]

```

(continues on next page)

(continued from previous page)

```

    "physLocationId": 1,
    "profile": "ATS_MID_TIER_CACHE",
    "profileDesc": "Mid Cache - Apache Traffic Server",
    "profileId": 10,
    "rack": "",
    "revalPending": false,
    "routerHostName": "",
    "routerPortName": "",
    "status": "REPORTED",
    "statusId": 3,
    "tcpPort": 80,
    "type": "MID",
    "typeId": 12,
    "updPending": false,
    "xmppId": "mid",
    "xmppPasswd": "",
    "ipIsService": true,
    "ip6IsService": true
  }
}
```

POST

Allows a user to create a new server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cachegroupId An integer that is the *ID of the Cache Group* to which the server shall belong

cdnId The integral, unique identifier of the CDN to which the server shall belong

domainName The domain part of the server’s FQDN

hostName The (short) hostname of the server

httpsPort An optional port number on which the server listens for incoming HTTPS connections/requests

iloIpAddress An optional IPv4 address of the server’s ILO service^{Page 792, 1}

iloIpGateway An optional IPv4 gateway address of the server’s ILO service^{Page 792, 1}

iloIpNetmask An optional IPv4 subnet mask of the server's ILO service^{Page 792, 1}

iloPassword An optional string containing the password of the of the server's ILO service user^{Page 792, 1} - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' *Role(s)*

iloUsername An optional string containing the user name for the server's ILO service^{Page 792, 1}

interfaceMtu The MTU configured on `interfaceName`

Note: In virtually all cases this ought to be 1500. Further note that the only acceptable values are 1500 and 9000.

interfaceName The name of the primary network interface used by the server

ip6Address An optional IPv6 address and subnet mask of `interfaceName`

ip6IsService An optional boolean value which if `true` indicates that the IPv6 address will be used for routing content. Defaults to `true`.

ip6Gateway An optional IPv6 address of the gateway used by `interfaceName`

ipAddress The IPv4 address of `interfaceName`

ipIsService An optional boolean value which if `true` indicates that the IPv4 address will be used for routing content. Defaults to `true`.

ipGateway The IPv4 address of the gateway used by `interfaceName`

ipNetmask The IPv4 subnet mask used by `interfaceName`

mgmtIpAddress An optional IPv4 address of some network interface on the server used for 'management'

mgmtIpGateway An optional IPv4 address of a gateway used by some network interface on the server used for 'management'

mgmtIpNetmask An optional IPv4 subnet mask used by some network interface on the server used for 'management'

physLocationId An integral, unique identifier for the physical location where the server resides

profileId The *ID* the *Profile* that shall be used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack An optional string indicating "server rack" location

routerHostName An optional string containing the human-readable name of the router responsible for reaching this server

routerPortName An optional string containing the human-readable name of the port used by the router responsible for reaching this server

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort An optional port number on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd An optional password used in XMPP communications with the server

486: Request Example

```
POST /api/2.0/servers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 599
Content-Type: application/json

{
  "cachegroupId": 6,
  "cdnId": 2,
  "domainName": "infra.ciab.test",
  "hostName": "test",
  "httpsPort": 443,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "interfaceMtu": 1500,
  "interfaceName": "eth0",
  "ip6Address": "::1",
  "ip6Gateway": "::2",
```

(continues on next page)

(continued from previous page)

```

"ipAddress": "0.0.0.1",
"ipGateway": "0.0.0.2",
"ipNetmask": "255.255.255.0",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocationId": 1,
"profileId": 10,
"routerHostName": "",
"routerPortName": "",
"statusId": 3,
"tcpPort": 80,
"typeId": 12,
"updPending": false,
"ipIsService": true,
"ip6IsService": true
}

```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId The integral, unique identifier of the CDN to which the server belongs

cdnName Name of the CDN to which the server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be null

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service Page 792, 1

iloIpGateway The IPv4 gateway address of the server's ILO service Page 792, 1

- iloIpNetmask** The IPv4 subnet mask of the server's ILO service Page 792, 1
- iloPassword** The password of the of the server's ILO service user Page 792, 1 - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' `ROLE(s) <ROLE>`
- iloUsername** The user name for the server's ILO service Page 792, 1
- interfaceMtu** The MTU configured on `interfaceName`
- interfaceName** The name of the primary network interface used by the server
- ip6Address** The IPv6 address and subnet mask of `interfaceName`
- ip6IsService** A boolean value which if `true` indicates that the IPv6 address will be used for routing content.
- ip6Gateway** The IPv6 address of the gateway used by `interfaceName`
- ipAddress** The IPv4 address of `interfaceName`
- ipIsService** A boolean value which if `true` indicates that the IPv4 address will be used for routing content.
- ipGateway** The IPv4 address of the gateway used by `interfaceName`
- ipNetmask** The IPv4 subnet mask used by `interfaceName`
- lastUpdated** The date and time at which this server description was last modified
- mgmtIpAddress** The IPv4 address of some network interface on the server used for 'management'
- mgmtIpGateway** The IPv4 address of a gateway used by some network interface on the server used for 'management'
- mgmtIpNetmask** The IPv4 subnet mask used by some network interface on the server used for 'management'
- offlineReason** A user-entered reason why the server is in `ADMIN_DOWN` or `OFFLINE` status
- physLocation** The name of the *Physical Location* where the server resides
- physLocationId** An integral, unique identifier for the *Physical Location* where the server resides
- profile** The *Name* of the *Profile* used by this server
- profileDesc** A *Description* of the *Profile* used by this server
- profileId** The *ID* the *Profile* used by this server
- revalPending** A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation
- rack** A string indicating "server rack" location
- routerHostName** The human-readable name of the router responsible for reaching this server

routerPortName The human-readable name of the port used by the router responsible for reaching this server

status The status of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the ‘type’ of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

487: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→mcGmmu5ONDg3jmvIkItcw6jxiT1ecmePYujZfmKiZrn5ThKjsSadeJIynaeOK0XVUjHuYHdt dynSqxr2r
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 17:44:04 GMT
Content-Length: 850

{ "alerts": [
```

(continues on next page)

(continued from previous page)

```
{
  "text": "server was created.",
  "level": "success"
},
],
"response": {
  "cachegroup": null,
  "cachegroupId": 6,
  "cdnId": 2,
  "cdnName": null,
  "domainName": "infra.ciab.test",
  "guid": null,
  "hostName": "test",
  "httpsPort": 443,
  "id": 13,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "interfaceMtu": 1500,
  "interfaceName": "eth0",
  "ip6Address": "::1",
  "ip6Gateway": "::2",
  "ipAddress": "0.0.0.1",
  "ipGateway": "0.0.0.2",
  "ipNetmask": "255.255.255.0",
  "lastUpdated": "2018-12-10 17:44:04+00",
  "mgmtIpAddress": "",
  "mgmtIpGateway": "",
  "mgmtIpNetmask": "",
  "offlineReason": "",
  "physLocation": null,
  "physLocationId": 1,
  "profile": null,
  "profileDesc": null,
  "profileId": 10,
  "rack": null,
  "revalPending": null,
  "routerHostName": "",
  "routerPortName": "",
  "status": null,
  "statusId": 3,
  "tcpPort": 80,
  "type": "",
  "typeId": 12,
```

(continues on next page)

(continued from previous page)

```
"updPending": false,
"xmppId": "test",
"xmppPasswd": null,
"ipIsService": true,
"ip6IsService": true
}}
```

servers/details

Retrieves details of *Servers*.

GET

Auth. Required Yes

Roles Required None

Response Type Array

Note: On top of the response including the response key that is of type array it will also include the keys limit, orderby, and size.

Request Structure

Table 213: Request Query Parameters

Name	Required	Description
host-Name	Required if no physLocationID provided	Return only the servers with this (short) hostname. Capitalization of “hostName” is important.
phys-LocationID	Required if no hostName provided	Return only servers with this integral, unique identifier for the physical location where the server resides. Capitalization of “physLocationID” is important.

488: Request Example

```
GET /api/2.0/servers/details?hostName=edge HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

limit The maximum size of the `response` array, also indicative of the number of results per page using the pagination requested by the query parameters (if any) - this should be the same as the `limit` query parameter (if given)

orderby A string that names the field by which the elements of the `response` array are ordered - should be the same as the `orderby` request query parameter (if given)

response An array of objects, each of which represents the details of a given *Server*.

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cdnName Name of the CDN to which the server belongs

deliveryservices An array of integral, unique identifiers for *Delivery Services* to which this server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be `null`

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service¹

iloIpGateway The IPv4 gateway address of the server's ILO service¹

iloIpNetmask The IPv4 subnet mask of the server's ILO service¹

iloPassword The password of the of the server's ILO service user¹ - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' *Role(s)*

iloUsername The user name for the server's ILO service¹

interfaceMtu The MTU to configured on `interfaceName`

interfaceName The name of the primary network interface used by the server

¹ For more information see the [Wikipedia page on Lights-Out management](#).

ip6Address The IPv6 address and subnet mask of `interfaceName`

ip6Gateway The IPv6 address of the gateway used by `interfaceName`

ipAddress The IPv4 address of `interfaceName`

ipGateway The IPv4 address of the gateway used by `interfaceName`

ipNetmask The IPv4 subnet mask used by `interfaceName`

mgmtIpAddress The IPv4 address of the server's management port

mgmtIpGateway The IPv4 gateway of the server's management port

mgmtIpNetmask The IPv4 subnet mask of the server's management port

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status

physLocation The name of the physical location where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

rack A string indicating "server rack" location

routerHostName The human-readable name of the router responsible for reaching this server

routerPortName The human-readable name of the port used by the router responsible for reaching this server

status The status of the server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with "HTTP port", as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the 'type' of this server

xmppId A system-generated UUID used to generate a server hashId for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

size The page number - if pagination was requested in the query parameters, else 0 to indicate no pagination - of the results represented by the response array. This is named “size” for legacy reasons

489: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 01:27:36
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳HW2F3CEpohNAvNlEDhUfXmtwpEka4dwUWFVUSSjW98aXiv10vI6ysRIcC2P9huabCz5fdHqY3tp0LR4ekv
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 00:27:36 GMT
Content-Length: 493

{
  "limit": 1000,
  "orderby": "hostName",
  "response": [
    {
      "cachegroup": "CDN_in_a_Box_Edge",
      "cdnName": "CDN-in-a-Box",
      "deliveryservices": [
        1
      ],
      "domainName": "infra.ciab.test",
      "guid": null,
      "hardwareInfo": null,
      "hostName": "edge",
      "httpsPort": 443,
      "id": 5,
      "iloIpAddress": "",
      "iloIpGateway": "",
      "iloIpNetmask": "",

```

(continues on next page)

(continued from previous page)

```

        "iloPassword": "",
        "iloUsername": "",
        "interfaceMtu": 1500,
        "interfaceName": "eth0",
        "ip6Address": "fc01:9400:1000:8::3",
        "ip6Gateway": "fc01:9400:1000:8::1",
        "ipAddress": "172.16.239.3",
        "ipGateway": "172.16.239.1",
        "ipNetmask": "255.255.255.0",
        "mgmtIpAddress": "",
        "mgmtIpGateway": "",
        "mgmtIpNetmask": "",
        "offlineReason": "",
        "physLocation": "Apachecon North America 2018",
        "profile": "ATS_EDGE_TIER_CACHE",
        "profileDesc": "Edge Cache - Apache Traffic Server",
        "rack": "",
        "routerHostName": "",
        "routerPortName": "",
        "status": "REPORTED",
        "tcpPort": 80,
        "type": "EDGE",
        "xmppId": "edge",
        "xmppPasswd": ""
    },
    "size": 1
}

```

`servers/{{HostName-Or-ID}}/update`

POST

Queue or dequeue updates and revalidation updates for a specific server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 214: Request Path Parameters

Name	Description
HostName-OR-ID	The hostName or integral, unique identifier of the server on which updates are being queued or dequeued

Table 215: Request Query Parameters

Name	Re-quired	Description
updated	no	The value to set for the queue update flag on this server. May be ‘true’ or ‘false’.
reval_updated	no	The value to set for the queue update flag on this server. May be ‘true’ or ‘false’.

490: Request Example

```
GET /api/2.0/servers/my-edge/update?updated=true&reval_updated=false_
→HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

491: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Mon, 10 Dec 2018 18:20:04 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54_
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 9Mmo9hIFZyF5gAvfdJD//
→VH9eNgiHVLinXt88H0G1JSHhwND8gMxaFyC+f9XZfiNAoGd1MKi1934ZJGmaIR6qQ==
```

(continues on next page)

(continued from previous page)

Content-Length: 49

```
{
  "alerts" :
  [
    {
      "text" : "successfully set server 'my-edge'
→updated=true reval_updated=false",
      "level" : "success"
    }
  ]
}
```

`servers/{hostname}/update_status`

Note: This endpoint only truly has meaning for *cache servers*, though it will return a valid response for any server configured in Traffic Ops.

GET

Retrieves information regarding pending updates and revalidation jobs for a given server

Auth. Required Yes

Roles Required None

Response Type undefined - this endpoint will return a top-level array containing the response, as opposed to within a response object

Request Structure

Table 216: Request Path Parameters

Name	Description
hostname	The (short) hostname of the server being inspected

492: Request Example

```
GET /api/2.0/servers/edge/update_status HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```


Response Structure

Each object in the returned array¹ will contain the following fields:

host_id The integral, unique identifier for the server for which the other fields in this object represent the pending updates and revalidation status

host_name The (short) hostname of the server for which the other fields in this object represent the pending updates and revalidation status

parent_pending A boolean telling whether or not the *parents* of this server have pending updates

parent_reval_pending A boolean telling whether or not the *parents* of this server have pending revalidation jobs

reval_pending true if the server has pending revalidation jobs, false otherwise

status The name of the status of this server

See also:

Health Protocol gives more information on how these statuses are used, and the GET method of the *statuses* endpoint can be used to retrieve information about all server statuses configured in Traffic Ops.

upd_pending true if the server has pending updates, false otherwise

use_reval_pending A boolean which tells *ORT* whether or not this version of Traffic Ops should use pending revalidation jobs

Note: This field was introduced to give *ORT* the ability to work with Traffic Control versions 1.x and 2.x seamlessly - as of Traffic Control v3.0 there is no reason for this field to ever be false.

493: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳R6BjNVrcechGn3eGDqQ1yDiBnEDGQe7QtOMIsRwlpck9SZR8chRQznrkTF3YdROAZ1l8BxR3fXTIvKHIz
    ↳dA==
```

(continues on next page)

¹ Despite that the returned object is an array, exactly one server's information is requested and thus returned. That is to say, the array should always have a length of exactly one.

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 04 Feb 2019 16:24:01 GMT
Content-Length: 174
```

```
[{
  "host_name": "edge",
  "upd_pending": false,
  "reval_pending": false,
  "use_reval_pending": true,
  "host_id": 10,
  "status": "REPORTED",
  "parent_pending": false,
  "parent_reval_pending": false
}]
```

`servers/{{ID}}`

PUT

Allow user to edit a server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 217: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a server

cachegroupId An integer that is the *ID of the Cache Group* to which the server shall belong

cdnId The integral, unique identifier of the CDN to which the server shall belong

domainName The domain part of the server’s FQDN

hostName The (short) hostname of the server

httpsPort An optional port number on which the server listens for incoming HTTPS connections/requests

iloIpAddress An optional IPv4 address of the server’s ILO service¹

¹ For more information see the [Wikipedia page on Lights-Out management](#).

- iloIpGateway** An optional IPv4 gateway address of the server's ILO service¹
- iloIpNetmask** An optional IPv4 subnet mask of the server's ILO service^{Page 810, 1}
- iloPassword** An optional string containing the password of the of the server's ILO service user^{Page 810, 1} - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' `ROLE(s) <ROLE>`
- iloUsername** An optional string containing the user name for the server's ILO service^{Page 810, 1}
- interfaceMtu** The MTU configured on `interfaceName`

Note: In virtually all cases this ought to be 1500. Further note that the only acceptable values are 1500 and 9000.

- interfaceName** The name of the primary network interface used by the server
- ip6Address** An optional IPv6 address and subnet mask of `interfaceName`
- ip6IsService** An optional boolean value which if `true` indicates that the IPv6 address will be used for routing content. Defaults to `true`.
- ip6Gateway** An optional IPv6 address of the gateway used by `interfaceName`
- ipAddress** The IPv4 address of `interfaceName`
- ipIsService** An optional boolean value which if `true` indicates that the IPv4 address will be used for routing content. Defaults to `true`.
- ipGateway** The IPv4 address of the gateway used by `interfaceName`
- ipNetmask** The IPv4 subnet mask used by `interfaceName`
- mgmtIpAddress** An optional IPv4 address of some network interface on the server used for 'management'
- mgmtIpGateway** An optional IPv4 address of a gateway used by some network interface on the server used for 'management'
- mgmtIpNetmask** An optional IPv4 subnet mask used by some network interface on the server used for 'management'
- physLocationId** An integral, unique identifier for the physical location where the server resides
- profileId** The *ID* the *Profile* that shall be used by this server
- revalPending** A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation
- rack** An optional string indicating "server rack" location
- routerHostName** An optional string containing the human-readable name of the router responsible for reaching this server

routerPortName An optional string containing the human-readable name of the port used by the router responsible for reaching this server

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort An optional port number on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd An optional password used in XMPP communications with the server

494: Request Example

```
PUT /api/2.0/servers/13 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 599
Content-Type: application/json

{
  "cachegroupId": 6,
  "cdnId": 2,
  "domainName": "infra.ciab.test",
  "hostName": "quest",
  "httpsPort": 443,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "interfaceMtu": 1500,
```

(continues on next page)

(continued from previous page)

```

"interfaceName": "eth0",
"ip6Address": "::1",
"ip6Gateway": "::2",
"ipAddress": "0.0.0.1",
"ipGateway": "0.0.0.2",
"ipNetmask": "255.255.255.0",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocationId": 1,
"profileId": 10,
"routerHostName": "",
"routerPortName": "",
"statusId": 3,
"tcpPort": 80,
"typeId": 12,
"updPending": true,
"ipIsService": true,
"ip6IsService": true
}

```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId The integral, unique identifier of the CDN to which the server belongs

cdnName Name of the CDN to which the server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be null

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's Integrated Lights-Out (ILO) service Page 810, 1

iloIpGateway The IPv4 gateway address of the server's ILO service Page 810, 1

iloIpNetmask The IPv4 subnet mask of the server's ILO service Page 810, 1

iloPassword The password of the of the server's ILO service user Page 810, 1 - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' role(s)

iloUsername The user name for the server's ILO service Page 810, 1

interfaceMtu The Maximum Transmission Unit (MTU) to configured on `interfaceName`

interfaceName The name of the primary network interface used by the server

ip6Address The IPv6 address and subnet mask of `interfaceName`

ip6IsService A boolean value which if `true` indicates that the IPv6 address will be used for routing content.

ip6Gateway The IPv6 address of the gateway used by `interfaceName`

ipAddress The IPv4 address of `interfaceName`

ipIsService A boolean value which if `true` indicates that the IPv4 address will be used for routing content.

ipGateway The IPv4 address of the gateway used by `interfaceName`

ipNetmask The IPv4 subnet mask used by `interfaceName`

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server used for 'management'

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for 'management'

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for 'management'

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status

physLocation The name of the physical location where the server resides

physLocationId An integral, unique identifier for the physical location where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

profileId The *ID* the *Profile* used by this server

revalPending A boolean value which, if true indicates that this server has pending content invalidation/revalidation

rack A string indicating “server rack” location

routerHostName The human-readable name of the router responsible for reaching this server

routerPortName The human-readable name of the port used by the router responsible for reaching this server

status The status of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the ‘type’ of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if true, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server hashId for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

495: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 9lGAMCCC9I/b0puBSyf3ACffjHeRuXCTuxrA/
→oU78uYzW5FeFTq5PHSSnsnqKG5E0vWg0Rko0CwguGeNc9IT0w== (continues on next page)
```

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 17:58:57 GMT
Content-Length: 848

{ "alerts": [
  {
    "text": "server was updated.",
    "level": "success"
  }
],
"response": {
  "cachegroup": null,
  "cachegroupId": 6,
  "cdnId": 2,
  "cdnName": null,
  "domainName": "infra.ciab.test",
  "guid": null,
  "hostName": "quest",
  "httpsPort": 443,
  "id": 13,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "interfaceMtu": 1500,
  "interfaceName": "eth0",
  "ip6Address": "::1",
  "ip6Gateway": "::2",
  "ipAddress": "0.0.0.1",
  "ipGateway": "0.0.0.2",
  "ipNetmask": "255.255.255.0",
  "lastUpdated": "2018-12-10 17:58:57+00",
  "mgmtIpAddress": "",
  "mgmtIpGateway": "",
  "mgmtIpNetmask": "",
  "offlineReason": "",
  "physLocation": null,
  "physLocationId": 1,
  "profile": null,
  "profileDesc": null,
  "profileId": 10,
  "rack": null,
  "revalPending": null,
  "routerHostName": "",
  "routerPortName": "",
```

(continues on next page)

(continued from previous page)

```
"status": null,
"statusId": 3,
"tcpPort": 80,
"type": "",
"typeId": 12,
"updPending": true,
"xmppId": null,
"xmppPasswd": null,
"ipIsService": true,
"ip6IsService": true
}}
```

DELETE

Allow user to delete server through api.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 218: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a server

496: Request Example

```
DELETE /api/2.0/servers/13 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

497: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: JZdjKJYWN9w9NF6VE/
    ↳rVkgUqecycKB2ABkkI4LNDmgpJLwu53bRHAA+4uWrow0zuba/
    ↳4MSEhHKshutziypSxPg==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 18:23:21 GMT
Content-Length: 61

{ "alerts": [
  {
    "text": "server was deleted.",
    "level": "success"
  }
]}
```

`servers/{ID}/deliveryservices`

GET

Retrieves all *Delivery Services* assigned to a specific server.

Auth. Required Yes

Roles Required None¹

¹ Only the *Delivery Services* visible to the requesting user's *Tenant* will appear, regardless of their *Role* or the

Response Type Array

Request Structure

Table 219: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the server for which assigned <i>Delivery Services</i> shall be listed

Table 220: Request Query Parameters

Name	Re- quired	Description
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

498: Request Example

```
GET /api/2.0/servers/9/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

Delivery Services’ actual ‘server assignment’ status.

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*

geoLimitRedirectUrl A *Geo Limit Redirect URL*

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** The 2nd long description of this *Delivery Service*
- longDesc2** the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using **pattern**.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** The *ID* of the *Profile* with which this *Delivery Service* is associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

signed true if and only if `signingAlgorithm` is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*

rangeSliceBlockSize An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if `rangeRequestHandling` is set to 3.

sslKeyVersion This integer indicates the *SSL Key Version*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service's xml_id*

499: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: CFmtW41aoDezCYxtAXnS54dfFOD6jdxDJ2/
→LMpbBqndy5kac7JQhdFAWF109sl95XVSUV85JHFzXZTw/mJabQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Jun 2019 17:01:30 GMT
Content-Length: 1500

{ "response": [ {
  "active": true,
  "anonymousBlockingEnabled": false,
  "cacheurl": null,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "checkPath": null,
  "displayName": "Demo 1",
```

(continues on next page)

(continued from previous page)

```
"dnsBypassCname": null,
"dnsBypassIp": null,
"dnsBypassIp6": null,
"dnsBypassTtl": null,
"dscp": 0,
"edgeHeaderRewrite": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"ipv6RoutingEnabled": true,
"lastUpdated": "2019-06-10 15:14:29+00",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"longDesc1": null,
"longDesc2": null,
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
```

(continues on next page)

(continued from previous page)

```
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
    "http://video.demo1.mycdn.ciab.test",
    "https://video.demo1.mycdn.ciab.test"
],
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": "root",
"trResponseHeaders": null,
"trRequestHeaders": null,
"consistentHashRegex": null,
"consistentHashQueryParams": [
    "abc",
    "pdq",
    "xxx",
    "zyx"
],
"maxOriginConnections": 0,
"ecsEnabled": false,
"rangeSliceBlockSize": null
}}}
```

POST

Assign an arbitrary number of *Delivery Services* to a single server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 221: Request Path Parameters

Name	Re-quired	Description
ID	Yes	The integral, unique identifier of the server that you want to assign delivery services to.

Table 222: Request Query Parameters

Name	Re-quired	Description
re-place	Yes	Whether the list of <i>Delivery Services</i> you provide should replace the existing list or be merged with the existing list. Must be a 1, or true, or 0, or false.

The request body is an array of IDs of *Delivery Services* that you want to assign to the server. The array can be empty, but it must be provided.

500: Request Example

```
POST /api/2.0/servers/6/deliveryservices?replace=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 3

[
  1
]
```

Response Structure

dsIds An array of integral, unique identifiers for *Delivery Services* which the request added to server. If `:replace:` is `false`, *Delivery Services* that are already assigned will remain, though they are not listed by `:dsIds:`.

replace The `:replace:` value you provided in the body of the request, or `null` if none was provided.

serverId The server's integral, unique identifier

501: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 09:08:32
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳iV+JzAZSsmlxRZsNtIRg3oA9470hAwRMpq5xhcYVi0Y831Trx2YRlsyhYp0PqHg5+QPoXHGF0nx8uso0f
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 08:08:32 GMT
Content-Length: 129

{
  "alerts": [
    {
      "text": "successfully assigned dses to server",
      "level": "success"
    }
  ],
  "response": {
    "serverId": 6,
    "dsIds": [
      1
    ],
    "replace": true
  }
}
```

`servers/{ID}/queue_update`

Caution: In the vast majority of cases, it is advisable that the PUT method of the `servers/{ID}` endpoint be used instead.

POST

Queue or dequeue updates for a specific server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 223: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the server on which updates are being queued or dequeued

action A string describing what action to take regarding server updates; one of:

queue *Queue Updates* for the server, propagating configuration changes to the actual server

dequeue Cancels any pending updates on the server

502: Request Example

```
POST /api/2.0/servers/13/queue_update HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 22
Content-Type: application/json

{
  "action": "dequeue"
}
```

Response Structure

action The action processed, one of:

queue *Queue Updates* was performed on the server, propagating configuration changes to the actual server

dequeue Canceled any pending updates on the server

serverId The integral, unique identifier of the server on which action was taken

503: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Mon, 10 Dec 2018 18:20:04 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 9Mmo9hIFZyF5gAvfdJD//
VH9eNgiHVLinXt88H0GlJSHhwND8gMxaFyC+f9XZfiNAoGd1MKi1934ZJGmaIR6qQ==
Content-Length: 49

{
  "response": {
    "serverId": "13",
    "action": "dequeue"
  }
}
```

servers/{ID}/status

PUT

Updates server status and queues updates on all child caches if server type is EDGE or MID. Also, captures offline reason if status is set to ADMIN_DOWN or OFFLINE and prepends offline reason with the user that initiated the status change.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 224: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the server whose status is being changed

offlineReason A string containing the reason for the status change

status The name or integral, unique identifier of the server’s new status

504: Request Example

```
PUT /api/2.0/servers/13/status HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "status": "ADMIN_DOWN",
  "offlineReason": "Bad drives"
}
```

Response Structure

505: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Mon, 10 Dec 2018 18:08:44 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→LS1jCo5eMVKxmeYDol0I2LgLYazocSggR5hynNoLcPmMov9u2s3ulksPdQtG1N3aS+VM9tdMsCrahFPral
Content-Length: 158

{ "alerts": [
  {
    "level": "success",
    "text": "Updated status [ ADMIN_DOWN ] for quest.infra.ciab.
→test [ admin: Bad drives ] and queued updates on all child caches"
  }
]}
```

snapshot

PUT

Performs a CDN *Snapshot*. Effectively, this propagates the new *configuration* of the CDN to its *operating state*, which replaces the output of the `cdns/{{name}}/snapshot` endpoint with the output of the `cdns/{{name}}/snapshot/new` endpoint. This also changes the output of the `cdns/{{name}}/configs/monitoring` endpoint since that endpoint returns the latest monitoring information from the *operating state*.

Note: Snapshotting the CDN also deletes all HTTPS certificates for every *Delivery Service* which has been deleted since the last *Snapshot*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 225: Request Query Parameters

Name	Description
cdn	The name of the CDN for which a <i>Snapshot</i> shall be taken
cdnID	The id of the CDN for which a <i>Snapshot</i> shall be taken

Note: At least one query parameter must be given.

506: Request Example

```
PUT /api/2.0/snapshot?cdn=CDN-in-a-Box HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

507: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳gmaWI0tKgNFPY00zMrLCGDosBJkPbeIvW4BH9tEh96VjBqyWqzjgPySoMa3ViM1BQXA6VAUOGmc76VyhB
X-Server-Name: traffic_ops_golang/
Date: Wed, 18 Mar 2020 15:51:48 GMT
Content-Length: 47

{
  "response": "SUCCESS"
}
```

staticdnsentries

GET

Retrieve all static DNS entries configured within Traffic Control

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 226: Request Query Parameters

Name	Re- quired	Description
ad- dress	no	Return only static DNS entries that operate on this address/CNAME
cachegroup	no	Return only static DNS entries assigned to the <i>Cache Group</i> that has this <i>Name</i>
cachegroupId	no	Return only static DNS entries assigned to the <i>Cache Group</i> that has this <i>ID</i>
deliv- ery- ser- vice	no	Return only static DNS entries that apply within the domain of the <i>Delivery Service</i> with this <i>xml_id</i>
deliv- ery- servi- ceId	no	Return only static DNS entries that apply within the domain of the <i>Delivery Service</i> identified by this integral, unique identifier
host	no	Return only static DNS entries that resolve this FQDN
id	no	Return only the static DNS entry with this integral, unique identifier
ttl	no	Return only static DNS entries with this TTL
type	no	Return only static DNS entries of this type
typeId	no	Return only static DNS entries of the type identified by this integral, unique identifier
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

508: Request Example

```
GET /api/2.0/staticdnsentries?address=foo.bar HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

address If `typeId` identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which host shall be resolved

cachegroup An optional string containing the *Name of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryservice The name of a *Delivery Service* under the domain of which this static DNS entry shall be active

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If `typeId` identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the Fully Qualified Domain Name (FQDN) which shall resolve to address

id An integral, unique identifier for this static DNS entry

ttd The TTL of this static DNS entry in seconds

type The name of the type of this static DNS entry

typeId The integral, unique identifier of the *Type* of this static DNS entry

509: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Px1zTH3ihg+hfmDADGcap0Juuud39fGsX5Y3CzqaFNmRwFu1ZLMz0sy0EN2pb7vp0tpI6/
    ↳zeIUYAC3dbSbw0mA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:04:33 GMT
Content-Length: 226

{ "response": [
  {
    "address": "foo.bar.",
    "cachegroup": null,
    "cachegroupId": null,
    "deliveryservice": "demo1",
    "deliveryserviceId": 1,
    "host": "test",
    "id": 2,
    "lastUpdated": "2018-12-10 19:59:56+00",
    "ttl": 300,
    "type": "CNAME_RECORD",
    "typeId": 41
  }
]}

```

POST

Creates a new, static DNS entry.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

address If `typeId` identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which `host` shall be resolved

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If `typeId` identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the FQDN which shall resolve to `address`

ttl The TTL of this static DNS entry in seconds

typeId The integral, unique identifier of the *Type* of this static DNS entry

510: Request Example

```
POST /api/2.0/staticdnsentries HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 92
Content-Type: application/json

{
  "address": "test.quest.",
  "deliveryserviceId": 1,
  "host": "test",
  "ttl": 300,
  "typeId": 41
}
```

Response Structure

address If `typeId` identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which `host` shall be resolved

cachegroup An optional string containing the *Name of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryservice The name of a *Delivery Service* under the domain of which this static DNS entry shall be active

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If `typeId` identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the Fully Qualified Domain Name (FQDN) which shall resolve to `address`

id An integral, unique identifier for this static DNS entry

ttl The TTL of this static DNS entry in seconds

type The name of the *Type* of this static DNS entry

typeId The integral, unique identifier of the *Type* of this static DNS entry

511: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 8dcJyjw2NJZx0L90z16P7g/
→7j5A1jlpYiY6Y+rRVQ2wGcwYI3yiGPrz6ur0qKzgqEBBsh8aPF44WTHAR9jUJdg==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 19:54:19 GMT
Content-Length: 282

{ "alerts": [
  {
    "text": "staticDNSEntry was created.",
    "level": "success"
  }
],
"response": {
  "address": "test.quest.",
  "cachegroup": null,
  "cachegroupId": null,
  "deliveryservice": null,
  "deliveryserviceId": 1,
  "host": "test",
  "id": 2,
  "lastUpdated": "2018-12-10 19:54:19+00",
  "ttl": 300,
  "type": "CNAME_RECORD",
  "typeId": 41
}}
```

PUT

Updates a static DNS entry.

Auth. Required Yes

Role(s) Required “admin” or “operator”

Response Type Object

Request Structure

Table 227: Request Query Parameters

Name	Description
id	The integral, unique identifier of the static DNS entry to modify

address If typeId identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which host shall be resolved

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If typeId identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the Fully Qualified Domain Name (FQDN) which shall resolve to address

ttd The TTL of this static DNS entry in seconds

typeId The integral, unique identifier of the *Type* of this static DNS entry

512: Request Example

```
PUT /api/2.0/staticdnsentries?id=2 HTTP/1.1
```

```
Host: trafficops.infra.ciab.test
```

```
User-Agent: curl/7.47.0
```

```
Accept: */*
```

```
Cookie: mojolicious=...
```

```
Content-Length: 89
```

```
Content-Type: application/json
```

```
{
  "address": "foo.bar.",
  "deliveryserviceId": 1,
  "host": "test",
  "ttl": 300,
  "typeId": 41
}
```

Response Structure

address If typeId identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which host shall be resolved

cachegroup An optional string containing the *Name of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryservice The name of a *Delivery Service* under the domain of which this static DNS entry shall be active

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If typeId identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the FQDN which shall resolve to address

id An integral, unique identifier for this static DNS entry

ttl The TTL of this static DNS entry in seconds

type The name of the *Type* of this static DNS entry

typeId The integral, unique identifier of the *Type* of this static DNS entry

513: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳+FaYmpnlIIzVSBq0nosw29NZcV9xFhlVgWuUqXUyiDihVUSzX4jrdAloRDgzDvKsYQB8LSkPdGHwt1zjg
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 19:59:56 GMT
Content-Length: 279

{ "alerts": [
  {
    "text": "staticDNSEntry was updated.",
    "level": "success"
  }
],
"response": {
  "address": "foo.bar.",
  "cachegroup": null,
  "cachegroupId": null,
  "deliveryservice": null,
  "deliveryserviceId": 1,
```

(continues on next page)

(continued from previous page)

```
"host": "test",
"id": 2,
"lastUpdated": "2018-12-10 19:59:56+00",
"ttl": 300,
"type": null,
"typeId": 41
}}
```

DELETE

Delete staticdnsentries.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 228: Request Query Parameters

Name	Description
id	The integral, unique identifier of the static DNS entry to delete

514: Request Example

```
DELETE /api/2.0/staticdnsentries?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

515: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→g6uqHPU44LuTtqU2ahtazrVCpcpNWVc9kWJQ0YRuiVLDnsm39KOB/xt3XM6j0/
→X3WYiIawnNspkxRC85LJHwFA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:05:52 GMT
Content-Length: 69

{ "alerts": [
  {
    "text": "staticDNSEntry was deleted.",
    "level": "success"
  }
]}
```

stats_summary

GET

Either retrieve a list of summary stats or the timestamp of the latest recorded stats summary.

What is returned is driven by the query parameter `lastSummaryDate`.

If the parameter is set it will return an object with the latest timestamp, else an array of summary stats will be returned.

Auth. Required Yes

Roles Required None

Response Type Array or Object

Request Structure

Summary Stats

Table 229: Request Query Parameters

Name	Required	Description
deliveryServiceName	no	Return only summary stats that were reported for <i>Delivery Service</i> with the given display name
cdnName	no	Return only summary stats that were reported for CDN with the given name
statName	no	Return only summary stats that were reported for given stat name
orderBy	no	Choose the ordering of the results - can only be one of deliveryServiceName, statName or cdnName
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

516: Request Example

```
GET /api/2.0/stats_summary HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Last Updated Summary Stat

Table 230: Request Query Parameters

Name	Required	Description
statName	no	Get latest updated date for the given stat
lastSummaryDate	yes	Tells route to get only latest updated timestamp

517: Request Example

```
GET /api/2.0/stats_summary?lastSummaryDate=true HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

Summary Stats

cdnName The CDN name for which the summary stat was taken for

Note: If the `cdn` is equal to `all` it represents `summary_stats` across all delivery services across all CDNs

deliveryServiceName The *Delivery Service* display name for which the summary stat was taken for

Note: If the `deliveryServiceName` is equal to `all` it represents `summary_stats` across all delivery services within the given CDN

statName Stat name summary stat represents

statValue Summary stat value

summaryTime Timestamp of summary, in *Traffic Ops's Custom Date/Time Format*

statDate Date stat was taken, in YYYY-MM-DD format

518: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dHNip9kpTGGs1w39/fWcFehNktgmXZus8XaufnmDpv0PyG/
→3fK/KfoC03Z0j9V74/CCffps7doEygWeL/xRtKA==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:56:59 GMT
Content-Length: 150

{ "response": [
  {
    "cdnName": "CDN-in-a-Box",
    "deliveryServiceName": "all",
    "statName": "daily_maxgbps",
    "statValue": 5,
    "summaryTime": "2019-11-19 00:04:06+00",
    "statDate": "2019-11-19"
  },
  {
    "cdnName": "CDN-in-a-Box",
    "deliveryServiceName": "all",
    "statName": "daily_maxgbps",
    "statValue": 3,
    "summaryTime": "2019-11-18 00:04:06+00",
    "statDate": "2019-11-18"
  },
  {
    "cdnName": "CDN-in-a-Box",
    "deliveryServiceName": "all",
    "statName": "daily_bytesserved",
    "statValue": 1000,
    "summaryTime": "2019-11-19 00:04:06+00",
    "statDate": "2019-11-19"
  }
]}

```

Last Updated Summary Stat

summaryTime Timestamp of the last updated summary, in *Traffic Ops's Custom Date/Time Format*

519: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json

```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dHNip9kpTGGS1w39/fWcFehNktgmXZus8XaufnmDpv0PyG/
→3fK/KfoC03Z0j9V74/CCffps7doEygWeL/xRtKA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:56:59 GMT
Content-Length: 150

{ "response": {
  "summaryTime": "2019-11-19 00:04:06+00"
}}
```

POST

Post a stats summary for a given stat.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

cdnName The CDN name for which the summary stat was taken for

Note: If the `cdn` is equal to `all` it represents `summary_stats` across all delivery services across all CDNs

deliveryServiceName The *Delivery Service* display name for which the summary stat was taken for

Note: If the `deliveryServiceName` is equal to `all` it represents `summary_stats` across all delivery services within the given CDN

statName Stat name summary stat represents

statValue Summary stat value

summaryTime Timestamp of summary, in *Traffic Ops's Custom Date/Time Format*

statDate Date stat was taken, in YYYY-MM-DD format

Note: statName, statValue and summaryTime are required. If cdnName and deliveryServiceName are not given they will default to all.

520: Request Example

```
POST /api/2.0/stats_summary HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 113
Content-Type: application/json

{
  "cdnName": "CDN-in-a-Box",
  "deliveryServiceName": "all",
  "statName": "daily_maxgbps",
  "statValue": 10,
  "summaryTime": "2019-12-05 00:03:57+00",
  "statDate": "2019-12-05"
}
```

Response Structure

521: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳ezxk+iP7o7KE7zpWmGc0j8nz5k+1wAzY0HiNiA2xswTQrt+N+6CgQqUV2r9G1HAsPNr0HF2PhYs/
  ↳Xr7DrY0w0A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 02:14:45 GMT
Content-Length: 97

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

    "text": "Stats Summary was successfully created",
    "level": "success"
  }
}
```

statuses

GET

Retrieves a list of all server *Statuses*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 231: Request Query Parameters

Name	Re-quired	Description
de-scrip-tion	no	Return only <i>Statuses</i> with this <i>exact</i> description
id	no	Return only the <i>Status</i> with this integral, unique identifier
name	no	Return only <i>Statuses</i> with this name
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
off-set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>nth</i> page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

522: Request Example

```

GET /api/2.0/statuses?name=REPORTED HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- description** A short description of the status
- id** The integral, unique identifier of this status
- lastUpdated** The date and time at which this status was last modified, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the status

523: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dHNip9kpTGGS1w39/fWcFehNktgmXZus8XaufnmDpv0PyG/
    ↳3fK/KfoC03Z0j9V74/CCffps7doEygWeL/xRtKA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:56:59 GMT
Content-Length: 150

{ "response": [
  {
    "description": "Server is online and reported in the health
    ↳protocol.",
    "id": 3,
    "lastUpdated": "2018-12-10 19:11:17+00",
    "name": "REPORTED"
  }
]}
```


steering

GET

Gets a list of all *Steering Targets* in the Traffic Ops database.

Auth. Required Yes

Roles Required “Portal”, “Steering”, “Federation”, “operations” or “admin”

Response Type Array

Request Structure

No parameters available.

524: Request Example

```
GET /api/2.0/steering HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

deliveryService A string that is the *xml_id* of the steering *Delivery Service*

clientSteering Whether this is a *client steering* Delivery Service.

targets The delivery services that the :ref:Steering Delivery Service <tr-steering>` targets.

order If this is a *STEERING_ORDER* target, this is the value of the order. Otherwise, 0.

weight If this is a *STEERING_WEIGHT* target, this is the value of the weight. Otherwise, 0.

deliveryService A string that is the *xml_id* of the steering *Delivery Service*

filters Filters of type *STEERING_REGEXP* that exist on either of the targets.

deliveryService A string that is the *xml_id* of the steering *Delivery Service*

pattern A regular expression - the use of this pattern is dependent on the *type* field (backslashes are escaped)

525: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 18:56:57
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳hcJa4xVLDx7bxBmoSjYo5YUwdSBWQr9GqlqRYrc6ZU7LeenjiV3go22YlIHt/
    ↳GtjLcHQjJ5DulKRhdsvFMq7Fng==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 17:56:57 GMT
Content-Length: 167

```

```

{
  "response": [
    {
      "deliveryService": "steering1",
      "clientSteering": true,
      "targets": [
        {
          "order": 0,
          "weight": 1,
          "deliveryService": "demo1"
        },
        {
          "order": 0,
          "weight": 2,
          "deliveryService": "demo2"
        }
      ],
      "filters": [
        {
          "deliveryService": "demo1",
          "pattern": ".*\\.demo1\\.\\.*"
        },
        {
          "deliveryService": "demo2",
          "pattern": ".*\\.demo2*\\.\\.*"
        }
      ]
    }
  ]
}

```

(continues on next page)

(continued from previous page)

```
]
}
```

steering/{ID}/targets

GET

Get all targets for a steering *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 232: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i> for which targets shall be listed

Table 233: Request Query Parameters

Name	Description
target	Return only the target mappings that target the <i>Delivery Service</i> identified by this integral, unique identifier
orderby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

526: Request Structure

```
GET /api/2.0/steering/2/targets?target=1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- deliveryService** A string that is the *xml_id* of the steering *Delivery Service*
- deliveryServiceId** An integral, unique identifier for the steering *Delivery Service*
- target** A string that is the *xml_id* of this target *Delivery Service*
- targetId** An integral, unique identifier for this target *Delivery Service*
- type** The routing type of this target *Delivery Service*
- typeId** An integral, unique identifier for the *routing type* of this target *Delivery Service*
- value** The ‘weight’ attributed to this steering target as an integer

527: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳utlJK4oYS2l6Ff7NzAqRuQeMEtazYn3rM3Nlux2XgTLxvSyslHy0mJrwDExSU05gVMdrgYCLZrZEvPH1E
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 14:09:23 GMT
Content-Length: 130

{ "response": [
  {
    "deliveryService": "test",
    "deliveryServiceId": 2,
    "target": "demo1",
    "targetId": 1,
    "type": "HTTP",
    "typeId": 1,
    "value": 100
  }
]}
```

POST

Create a steering target.

Auth. Required Yes

Roles Required Portal, Steering, Federation, “operations” or “admin”

Response Type Object

Request Structure

Table 234: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i> to which a target shall be added

targetId The integral, unique identifier of a *Delivery Service* which shall be a new steering target for the *Delivery Service* identified by the ID path parameter

typeId The integral, unique identifier of the routing type of the new target *Delivery Service*

value The ‘weight’ which shall be attributed to the new target *Delivery Service*

528: Request Example

```
POST /api/2.0/steering/2/targets HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 43
Content-Type: application/json

{
  "targetId": 1,
  "value": 100,
  "typeId": 1
}
```

Response Structure

- deliveryService** A string that is the *xml_id* of the steering *Delivery Service*
- deliveryServiceId** An integral, unique identifier for the steering *Delivery Service*
- target** A string that is the *xml_id* of this target *Delivery Service*
- targetId** An integral, unique identifier for this target *Delivery Service*
- type** The routing type of this target *Delivery Service*
- typeId** An integral, unique identifier for the *routing type* of this target *Delivery Service*
- value** The ‘weight’ attributed to this steering target as an integer

529: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳+dTvfzrnOhdwaAOMmY28r0+gFV5z+3aABI2FfAMziTYcU+pZrDanrJzMXpKWIL5Q/
  ↳oCUBZpJDRt9hRCFkT4oGYw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 21:22:17 GMT
```

(continues on next page)

(continued from previous page)

Content-Length: 196

```
{ "alerts": [
  {
    "text": "steeringtarget was created.",
    "level": "success"
  }
],
"response": {
  "deliveryService": "test",
  "deliveryServiceId": 2,
  "target": "demo1",
  "targetId": 1,
  "type": "HTTP",
  "typeId": 1,
  "value": 100
}}
```

steering/{ID}/targets/{targetID}

PUT

Updates a steering target.

Auth. Required Yes

Roles Required Portal, Steering, Federation, “operations” or “admin”

Response Type Object

Request Structure

Table 235: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i>
targetID	The integral, unique identifier of a <i>Delivery Service</i> which is a target of the <i>Delivery Service</i> identified by ID

typeId The integral, unique identifier of the *routing type* of the target *Delivery Service*

value The ‘weight’ which shall be attributed to the target *Delivery Service*

530: Request Example

```
PUT /api/2.0/steering/2/targets/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 26
Content-Type: application/json

{
  "value": 1,
  "typeId": 1
}
```

Response Structure

- deliveryService** A string that is the *xml_id* of the steering *Delivery Service*
- deliveryServiceId** An integral, unique identifier for the steering *Delivery Service*
- target** A string that is the *xml_id* of this target *Delivery Service*
- targetId** An integral, unique identifier for this target *Delivery Service*
- type** The routing type of this target *Delivery Service*
- typeId** An integral, unique identifier for the *routing type* of this target *Delivery Service*
- value** The ‘weight’ attributed to this steering target as an integer

531: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→AfXsIRzdtU3HZYkr93qBMVTZRJ5oTF2u5sKYnd+DSqxZ+RQxY6vXtCupnnXCf9dxMt5QXRW1EFOW/
→FBG6lFrTg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 14:34:22 GMT
Content-Length: 194
```

(continues on next page)

(continued from previous page)

```
{ "alerts": [
  {
    "text": "steeringtarget was updated.",
    "level": "success"
  }
],
"response": {
  "deliveryService": "test",
  "deliveryServiceId": 2,
  "target": "demo1",
  "targetId": 1,
  "type": "HTTP",
  "typeId": 1,
  "value": 1
}}
```

DELETE

Removes a specific target mapping from a specific *Delivery Service*

Auth. Required Yes

Roles Required Portal, Steering, Federation, “operations” or “admin”

Response Type undefined

Request Structure

Table 236: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i> - a target of which shall be deleted
targetID	The integral, unique identifier of a <i>Delivery Service</i> which is a target to be removed of the <i>Delivery Service</i> identified by ID

532: Request Example

```
DELETE /api/2.0/steering/2/targets/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

533: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳N6h8Kl7uQveqpTc3fmKXFDY2yYe5smApNcaTow4ab0DHGFdJfqQh89I4nvvaXvmVnhxVAqX3UE/
    ↳6blb08/9Xqg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 14:42:54 GMT
Content-Length: 69

{ "alerts": [
  {
    "text": "steeringtarget was deleted.",
    "level": "success"
  }
]}
```

system/info

GET

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

parameters An object containing information about the Traffic Ops server

Note: These are all the *Parameters* in *The GLOBAL Profile*, so the keys below are merely those present by default required for Traffic Control to operate

default_geo_miss_latitude The default latitude used when geographic lookup of an IP address fails

default_geo_miss_longitude The default longitude used when geographic lookup of an IP address fails

tm.instance_name The name of the Traffic Ops instance; typically used when multiple instances are active

tm.toolname The name of the Traffic Ops tool (usually “Traffic Ops”) - used in several API endpoints and written in comment headers on most Apache Traffic Server (ATS) configuration files generated by Traffic Ops

tm.url The URL for this Traffic Ops instance) - used in several API endpoints and written in comment headers on most Apache Traffic Server (ATS) configuration files generated by Traffic Ops

use_reval_pending A string containing an integer which represents a boolean value (hold your applause); one of:

“0” Do not use pending revalidations - this effectively prohibits the use of “Content Invalidation Jobs”

“1” Use pending revalidations - this effectively enables the use of “Content Invalidation Jobs”

use_tenancy A string containing an integer which represents a boolean value; one of:

“0” Do not use tenancy - this effectively disables all **tenant** endpoints and removes tenancy restrictions on origins and *Delivery Services*

“1” Use tenancy - this effectively enables all **tenant** endpoints and enforces tenancy restrictions on origins and *Delivery Services*

534: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Obx0Xk1jrC1/
→JtrqElUICceyx9iJKJxZydEIHvAU7khTTQwt0QGvS04ELDkdrbu3ctFo3pf3NAMAmm9tAkNokg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 19:06:01 GMT
Content-Length: 285

{ "response": {
  "parameters": {
    "default_geo_miss_latitude": "0",
    "default_geo_miss_longitude": "-1",
    "tm.instance_name": "CDN-In-A-Box",
    "tm.logourl": "/images/tc_logo.png",
    "tm.toolname": "Traffic Ops",
    "tm.url": "https://trafficops.infra.ciab.test:443/",
    "use_reval_pending": "0",
    "use_tenancy": "1"
  }
}}
```

tenants

GET

Get all requested *Tenants*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 237: Request Query Parameters

Name	Description
active	If true, return only active <i>Tenants</i> ; if false return only inactive <i>Tenants</i>
id	Return only <i>Tenants</i> with this integral, unique identifier
name	Return only <i>Tenants</i> with this name
orderBy	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the <i>n</i> th page of results, where “n” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

535: Request Example

```
GET /api/2.0/tenants?name=root HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

active A boolean which indicates whether or not the *Tenant* is active

id The integral, unique identifier of this *Tenant*

name This *Tenant*’s name

parentId The integral, unique identifier of this *Tenant*’s parent

parentName The name of the parent of this *Tenant*

536: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Yzr6TfhxgpZ3pbrrr4TRG4wC3PlnHDDzgs2igtz/
→1ppLSy2MzugqaGW4y5yzwzl5T3+7q6HWej7GQZt1XIVeZQ==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 19:57:58 GMT
Content-Length: 106

{ "response": [
  {
    "id": 1,
    "name": "root",
    "active": true,
    "lastUpdated": "2018-12-10 19:11:17+00",
    "parentId": null
  }
]}
```

POST

Create a new tenant.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

active An optional boolean - default: false - which indicates whether or not the tenant shall be immediately active

name The name of the tenant

parentId The integral, unique identifier of the parent of this tenant

537: Request Example

```
POST /api/2.0/tenants HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 48
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
{
  "active": true,
  "name": "test",
  "parentId": 1
}
```

Response Structure

active A boolean which indicates whether or not the tenant is active

id The integral, unique identifier of this tenant

name This tenant's name

parentId The integral, unique identifier of this tenant's parent

538: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ysdopC//
  ↳JQI79BRUa61s6M2HzHxYHpo5RdcuauOoqCYxiV0oUhNZfOVydVkv8zDN2qA374XKnym4kWj3VzQIXg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 19:37:16 GMT
Content-Length: 162

{ "alerts": [
  {
    "text": "tenant was created.",
    "level": "success"
  }
],
"response": {
  "id": 9,
  "name": "test",
  "active": true,
  "lastUpdated": "2018-12-11 19:37:16+00",
  "parentId": 1
}}
```

`tenants/{{ID}}`

PUT

Updates a specific tenant.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 238: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the tenant being modified

active An optional boolean - default: `false` - which indicates whether or not the tenant shall be immediately active

name The name of the tenant

parentId The integral, unique identifier of the parent of this tenant

539: Request Example

```
PUT /api/2.0/tenants/9 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 59
Content-Type: application/json

{
  "active": true,
  "name": "quest",
  "parentId": 3
}
```

Response Structure

active A boolean which indicates whether or not the tenant is active

id The integral, unique identifier of this tenant

name This tenant's name

parentId The integral, unique identifier of this tenant's parent

540: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 5soYQFrG2x5ZJ1e5UZIOLUv/
  ↳928qyd2Bfgw21Wv85rqjLpyeT3djfRVD1/xpKConulNrZs2czJKrrwZA7X61w==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 20:30:54 GMT
Content-Length: 163

{ "alerts": [
  {
    "text": "tenant was updated.",
    "level": "success"
  }
]}
```

(continues on next page)

(continued from previous page)

```

    }
  ],
  "response": {
    "id": 9,
    "name": "quest",
    "active": true,
    "lastUpdated": "2018-12-11 20:30:54+00",
    "parentId": 3
  }
}
```

DELETE

Deletes a specific tenant.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 239: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the tenant being deleted

541: Request Example

```

DELETE /api/2.0/tenants/9 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

542: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: KU0XIbFoD0Cy06kzH2G159pBqie/
→TEFJgh33mssGNwXJZlRkTLaSTHT8Df4X+pOs7UauZH10akGvaA0UTiN/vg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 20:40:31 GMT
Content-Length: 61

{ "alerts": [
  {
    "text": "tenant was deleted.",
    "level": "success"
  }
]}

```

types

GET

Retrieves all of the *Types* of things configured in Traffic Ops. Yes, that is as specific as a description of a ‘type’ can be.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 240: Request Query Parameters

Name	Re-quired	Description
id	no	Return only the type that is identified by this integral, unique identifier
name	no	Return only types with this name
useInTable	no	Return only types that are used to identify the type of the object stored in the Traffic Ops database table that has this name

543: Request Structure

```
GET /api/2.0/types?name=TC_LOC HTTP/1.1
Host: trafficops.infra.ciab.test

```

(continues on next page)

(continued from previous page)

```
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- description** A short description of this type
- id** An integral, unique identifier for this type
- lastUpdated** The date and time at which this type was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of this type
- useInTable** The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type

544: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
→p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 12 Dec 2018 22:59:22 GMT
Content-Length: 168

{ "response": [
  {
    "id": 48,
    "lastUpdated": "2018-12-12 16:26:41+00",
    "name": "TC_LOC",
    "description": "Location for Traffic Control Component Servers
→",
    "useInTable": "cachegroup"
  }
]}
```

POST

Creates a type

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

description A short description of this type

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type.

Note: The only useInTable value that is allowed to be created dynamically is ‘server’

545: Request Structure

```
POST /api/2.0/type HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 67
Content-Type: application/json

{
  "name": "Example01",
  "description": "Example",
  "useInTable": "server"
}
```

Response Structure

description A short description of this type

id An integral, unique identifier for this type

lastUpdated The date and time at which this type was last updated, in *Traffic Ops’s Custom Date/Time Format*

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type

546: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
→p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 Feb 2020 18:58:41 GMT
Content-Length: 171

{
  "alerts": [
    {
      "text": "type was created.",
      "level": "success"
    }
  ],
  "response": [
    {
      "id": 3004,
      "lastUpdated": "2020-02-26 18:58:41+00",
      "name": "Example01",
      "description": "Example"
      "useInTable": "server"
    }
  ]
}
```

types/{ID}

PUT

Updates a type

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 241: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the type being updated

description A short description of this type

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type.

Note: Only types with useInTable set to ‘server’ are allowed to be updated.

547: Request Structure

```
PUT /api/2.0/type/3004 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 68
Content-Type: application/json

{
  "name": "Example01",
  "description": "Example2",
  "useInTable": "server"
}
```

Response Structure

description A short description of this type

id An integral, unique identifier for this type

lastUpdated The date and time at which this type was last updated, in *Traffic Ops's Custom Date/Time Format*

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type

548: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
    ↳p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 Feb 2020 18:58:41 GMT
Content-Length: 172

{
  "alerts": [
    {
      "text": "type was updated.",
      "level": "success"
    }
  ],
  "response": [
    {
      "id": 3004,
      "lastUpdated": "2020-02-26 18:58:41+00",
      "name": "Example02",
      "description": "Example"
      "useInTable": "server"
    }
  ]
}

```

DELETE

Deletes a type

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 242: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the type being deleted

Note: Only types with useInTable set to “server” are allowed to be deleted.

549: Request Structure

```
DELETE /api/2.0/type/3004 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

550: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
    ↳p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 Feb 2020 18:58:41 GMT
Content-Length: 84

{
  "alerts": [
    {
      "text": "type was deleted.",
      "level": "success"
    }
  ],
}
```

`user/current`

GET

Caution: As a username is needed to log in, any administrator or application must necessarily know the current username at any given time. Thus it's generally better to use the username query parameter of a GET request to `users` instead.

Retrieves the details of the authenticated user.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

addressLine1 The user's address - including street name and number

addressLine2 An additional address field for e.g. apartment number

city The name of the city wherein the user resides

company The name of the company for which the user works

country The name of the country wherein the user resides

email The user's email address

fullName The user's full name, e.g. "John Quincy Adams"

gid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user

id An integral, unique identifier for this user

lastUpdated The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*

newUser A meta field with no apparent purpose that is usually null unless explicitly set during creation or modification of a user via some API endpoint

phoneNumber The user's phone number

postalCode The postal code of the area in which the user resides

publicSshKey The user's public key used for the SSH protocol

registrationSent If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be null

role The integral, unique identifier of the highest-privilege *Role* assigned to this user

rolename The name of the highest-privilege *Role* assigned to this user

stateOrProvince The name of the state or province where this user resides

tenant The name of the *Tenant* to which this user belongs

tenantId The integral, unique identifier of the *Tenant* to which this user belongs

uid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user

username The user's username

551: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳HQwu9FxFyinxSVFK5+wpEhSxU60KbqXuokFbMZ30oerOoM5ZpWpglsHz7mRch8VAw0dzwsJzpPJivj07R
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 15:14:45 GMT
Content-Length: 382

{ "response": {
  "username": "admin",
  "localUser": true,
  "addressLine1": null,
  "addressLine2": null,
  "city": null,
  "company": null,
  "country": null,
  "email": null,
  "fullName": "admin",
  "gid": null,
  "id": 2,
  "newUser": false,
  "phoneNumber": null,
```

(continues on next page)

(continued from previous page)

```

"postalCode": null,
"publicSshKey": null,
"role": 1,
"rolename": "admin",
"stateOrProvince": null,
"tenant": "root",
"tenantId": 1,
"uid": null,
"lastUpdated": "2018-12-12 16:26:32+00"
}}

```

PUT

Warning: Assuming the current user’s integral, unique identifier is known, it’s generally better to use the PUT method of the *users* instead.

Warning: Users that login via LDAP pass-back cannot be modified

Updates the date for the authenticated user.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

user The entire request must be inside a top-level “user” key for legacy reasons

addressLine1 The user’s address - including street name and number

addressLine2 An additional address field for e.g. apartment number

city The name of the city wherein the user resides

company The name of the company for which the user works

confirmLocalPasswd An optional ‘confirm’ field in a new user’s password specification. This has no known effect and in fact *doesn’t even need to match* localPasswd

country The name of the country wherein the user resides

email The user's email address - cannot be an empty string¹. The given email is validated (circuitously) by [GitHub user asaskevich's regular expression](#). Note that it can't actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user's full name, e.g. "John Quincy Adams"

gid A legacy field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - please don't use this

id The user's integral, unique, identifier - this cannot be changed^{Page 810, 1}

localPasswd Optionally, the user's password. This should never be given if it will not be changed. An empty string or null can be used to explicitly specify no change.

phoneNumber The user's phone number

postalCode The user's postal code

publicSshKey The user's public encryption key used for the SSH protocol

role The integral, unique identifier of the highest permission [Role](#) which will be permitted to the user - this cannot be altered from the user's current [Role](#)^{Page 810, 1}

stateOrProvince The state or province in which the user resides

tenantId The integral, unique identifier of the [Tenant](#) to which the new user shall belong^{2Page 810, 1}

uid A legacy field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - please don't use this

username The user's new username^{Page 810, 1}

552: Request Example

```
PUT /api/2.0/user/current HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 465
Content-Type: application/json
```

(continues on next page)

¹ This field cannot be null.

² This endpoint respects tenancy; a user cannot assign itself to a [Tenant](#) that is not the same [Tenant](#) to which it was previously assigned or a descendant thereof.

(continued from previous page)

```
{ "user": {
  "addressLine1": null,
  "addressLine2": null,
  "city": null,
  "company": null,
  "country": null,
  "email": "admin@infra.trafficops.ciab.test",
  "fullName": "admin",
  "gid": null,
  "id": 2,
  "phoneNumber": null,
  "postalCode": null,
  "publicSshKey": null,
  "role": 1,
  "stateOrProvince": null,
  "tenantId": 1,
  "uid": null,
  "username": "admin"
}}
```

Response Structure

addressLine1 The user’s address - including street name and number

addressLine2 An additional address field for e.g. apartment number

city The name of the city wherein the user resides

company The name of the company for which the user works

country The name of the country wherein the user resides

email The user’s email address validated (circuitously) by [GitHub user asaskevich’s regular expression](#) . Note that it can’t actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user’s full name, e.g. “John Quincy Adams”

gid A legacy field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user

id An integral, unique identifier for this user

lastUpdated The date and time at which the user was last modified, in *Traffic Ops’s Custom Date/Time Format*

newUser A meta field with no apparent purpose

phoneNumber The user’s phone number

- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be null
- role** The integral, unique identifier of the highest-privilege *Role* assigned to this user
- rolename** The name of the highest-privilege *Role* assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the *Tenant* to which this user belongs
- tenantId** The integral, unique identifier of the *Tenant* to which this user belongs
- uid** A legacy field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user
- username** The user's username

553: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Date: Thu, 13 Dec 2018 21:05:49 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: sHFqZQ4Cv7IIWaIejoAvM2Fr/HSupcX3D16KU/
    ↳etjw+4jcK9EME3Bq5ohLC+eQ52BDCKW2Ra+AC3TfFtworJww==
Content-Length: 478

{ "alerts": [
  {
    "text": "User profile was successfully updated",
    "level": "success"
  }
],
"response": {
  "addressLine1": null,
  "addressLine2": null,
  "city": null,
```

(continues on next page)

(continued from previous page)

```

"company": null,
"country": null,
"email": "admin@infra.trafficops.ciab.test",
"fullName": null,
"gid": null,
"id": 2,
"lastUpdated": "2019-10-08 20:14:25+00",
"newUser": false,
"phoneNumber": null,
"postalCode": null,
"publicSshKey": null,
"registrationSent": null,
"role": 1,
"roleName": "admin",
"stateOrProvince": null,
"tenant": "root",
"tenantId": 1,
"uid": null,
"username": "admin"
}}
```

user/login

POST

Authentication of a user using username and password. Traffic Ops will send back a session cookie.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

p Password

u Username

554: Request Example

```

POST /api/2.0/user/login HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
```

(continues on next page)

(continued from previous page)

```
Cookie: mojolicious=...
Content-Length: 26
Content-Type: application/json

{
  "u": "admin",
  "p": "twelve"
}
```

Response Structure

555: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Ud06T3tMNctnVusDXzRjVwwYOnD7jmnBzPEB9Pv0t2bHajTv3SKTPiIZjDzvhU6EX4p+JoG4fA5wlhgxp
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 15:21:33 GMT
Content-Length: 65

{ "alerts": [
  {
    "text": "Successfully logged in.",
    "level": "success"
  }
]}
```

user/login/oauth

POST

Authentication of a user by exchanging a code for an encrypted JSON Web Token from an OAuth service. Traffic Ops will POST to the `authCodeTokenUrl` to exchange the code for an encrypted JSON Web Token. It will then decode and validate the token, validate the key set domain, and send back a session cookie.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

authCodeTokenUrl URL for code-to-token conversion

code Code

clientId Client Id

redirectUri Redirect URI

556: Request Example

```
POST /api/2.0/user/login/oauth HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 26
Content-Type: application/json

{
  "authCodeTokenUrl": "https://url-to-convert-code-to-token.example.
  ↪com",
  "code": "AbCd123",
  "clientId": "oauthClientId",
  "redirectUri": "https://traffic-portal.example.com/sso"
}
```

Response Structure

557: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type, ↪
  ↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54 ↪
  ↪GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ↪
  ↪Ud06T3tMNctnVusDXzRjVwwYOnD7jmnBzPEB9PvOt2bHajTv3SKTPiIZiDzyhUGEX4p+lgG4fA5wlhgxp
  (continues on next page)
```

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 15:21:33 GMT
Content-Length: 65

{ "alerts": [
  {
    "text": "Successfully logged in.",
    "level": "success"
  }
]}
```

user/login/token

POST

Authentication of a user using a token. Normally, the token is obtained via a call to either *user/reset_password* or *users/register*.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

t A UUID (Universal Unique Identifier) generated for the user.

Implementation Detail

Though not strictly necessary for authentication provided direct database access, the tokens generated for use with this endpoint are compliant with [RFC 4122](#).

558: Request Example

```
POST /api/2.0/user/login/token HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 44
Content-Type: application/json

{
```

(continues on next page)

(continued from previous page)

```
"t": "18EE200C-FF24-11E8-BF01-870C776752A3"
}
```

Response Structure

559: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: FuS3TkVosxHtpxRGMJ2on+WnFdYTNSPjxz/Gh1iT4UCJ2/
    ↳P0twUbAGQ3tTx9EfGiAzg9CNQiVUFGnYjJZ6NCpg==
X-Server-Name: traffic_ops_golang/
Date: Fri, 20 Sep 2019 15:02:43 GMT
Content-Length: 66

{ "alerts": [
  {
    "text": "Successfully logged in.",
    "level": "success"
  }
]}
```

user/logout

POST

User logout. Invalidates the session cookie of the currently logged-in user.

Auth. Required Yes

Roles Required None

Response Type undefined

Request Structure

No parameters available

Response Structure

560: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 21:25:36 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 6KEdr1ZC512zk0l03KwvQE0L7qrJ/
    ↳+ek6ztymkYy9p8gdPUyYyzGEAJ/Ldb8GY0UBFYmgqeZ3yWHvTcEs0QMiw==
Content-Length: 61

{ "alerts": [
  {
    "level": "success",
    "text": "You are logged out."
  }
]}
```

user/reset_password

POST

Sends an email to reset a user's password.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

email The email address of the user to initiate password reset

561: Request Example

```
POST /api/2.0/user/reset_password HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 35
Content-Type: application/json

{
  "email": "test@example.com"
}
```

Response Structure

562: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 22:11:53 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→lKWwVYbgKklk7bljnQJZwWV5bljIk+GkooD6SAC3CSexVKvfbL9dgL5iBc/
→BNNRk2pIU5I/1GglcdLrXsF1ZA==
Content-Length: 109

{ "alerts": [
  {
    "level": "success",
    "text": "Successfully sent password reset to email
→'test@example.com'"
  }
]
```

(continues on next page)

(continued from previous page)

```
]]}
```

users

GET

Retrieves all requested users.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 243: Request Query Parameters

Name	Re- quired	Description
id	no	Return only the user identified by this integral, unique identifier
tenant	no	Return only users belonging to the <i>Tenant</i> identified by tenant name
role	no	Return only users belonging to the <i>Role</i> identified by role name
username	no	Return only the user with this username
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>n</i> th page of results, where “ <i>n</i> ” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

563: Request Example

```
GET /api/2.0/users?username=admin HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

¹ While no roles are required, this endpoint does respect tenancy. A user will only be able to see, create, delete or modify other users belonging to the same tenant, or its descendants.

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

addressLine1 The user's address - including street name and number

addressLine2 An additional address field for e.g. apartment number

city The name of the city wherein the user resides

company The name of the company for which the user works

country The name of the country wherein the user resides

email The user's email address

fullName The user's full name, e.g. "John Quincy Adams"

gid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`

id An integral, unique identifier for this user

lastUpdated The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*

newUser A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint

phoneNumber The user's phone number

postalCode The postal code of the area in which the user resides

publicSshKey The user's public key used for the SSH protocol

registrationSent If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`

role The integral, unique identifier of the highest-privilege role assigned to this user

rolename The name of the highest-privilege role assigned to this user

stateOrProvince The name of the state or province where this user resides

tenant The name of the tenant to which this user belongs

tenantId The integral, unique identifier of the tenant to which this user belongs

uid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always `null`

username The user's username

564: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳YBJLN8NbOxOvECe1RGtcwCzIPDhyhLpW56nTJHQM5WI2WUDe2mAKREpaEE72nzrfBliq1GABwJlxsxq20dl
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 01:03:53 GMT
Content-Length: 391

{ "response": [
  {
    "username": "admin",
    "registrationSent": null,
    "addressLine1": null,
    "addressLine2": null,
    "city": null,
    "company": null,
    "country": null,
    "email": null,
    "fullName": null,
    "gid": null,
    "id": 2,
    "newUser": false,
    "phoneNumber": null,
    "postalCode": null,
    "publicSshKey": null,
    "role": 1,
    "rolename": "admin",
    "stateOrProvince": null,
    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "lastUpdated": "2018-12-12 16:26:32+00"
  }
]}

```

POST

Creates a new user.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 887, 1}

Response Type Object

Request Structure

addressLine1 An optional field which should contain the user’s address - including street name and number

addressLine2 An optional field which should contain an additional address field for e.g. apartment number

city An optional field which should contain the name of the city wherein the user resides

company An optional field which should contain the name of the company for which the user works

confirmLocalPasswd The ‘confirm’ field in a new user’s password specification - must match `localPasswd`

country An optional field which should contain the name of the country wherein the user resides

email The user’s email address The given email is validated (circuitously) by [GitHub user asaskevich’s regular expression](#) . Note that it can’t actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user’s full name, e.g. “John Quincy Adams”

localPasswd The user’s password

newUser An optional meta field with no apparent purpose - don’t use this

phoneNumber An optional field which should contain the user’s phone number

postalCode An optional field which should contain the user’s postal code

publicSshKey An optional field which should contain the user’s public encryption key used for the SSH protocol

role The number that corresponds to the highest permission role which will be permitted to the user

stateOrProvince An optional field which should contain the name of the state or province in which the user resides

tenantId The integral, unique identifier of the tenant to which the new user shall belong

Note: This field is optional if and only if tenancy is not enabled in Traffic Control

username The new user's username

565: Request Example

```
POST /api/2.0/users HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 304
Content-Type: application/json

{
  "username": "mike",
  "addressLine1": "22 Mike Wazowski You've Got Your Life Back Lane",
  "city": "Monstropolis",
  "company": "Monsters Inc.",
  "email": "mwazowski@minc.biz",
  "fullName": "Mike Wazowski",
  "localPasswd": "BFFsully",
  "confirmLocalPasswd": "BFFsully",
  "newUser": true,
  "role": 1,
  "tenantId": 1
}
```

Response Structure

addressLine1 The user's address - including street name and number

addressLine2 An additional address field for e.g. apartment number

city The name of the city wherein the user resides

company The name of the company for which the user works

country The name of the country wherein the user resides

email The user's email address

fullName The user's full name, e.g. "John Quincy Adams"

gid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always null

id An integral, unique identifier for this user

- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually null unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be null
- role** The integral, unique identifier of the highest-privilege role assigned to this user
- rolename** The name of the highest-privilege role assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the tenant to which this user belongs
- tenantId** The integral, unique identifier of the tenant to which this user belongs
- uid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always null
- username** The user's username

566: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 02:28:27 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳vDqbaMvgeeoIds1czqvIWlyDG8WLnCCJdF14Ub05nsE+oJOakkyeZ8odf4d0Zjtqpk01hoVo14H2tjuWP
Content-Length: 520

{ "alerts": [
  {
    "level": "success",
```

(continues on next page)

(continued from previous page)

```

        "text": "User creation was successful."
    }
],
"response": {
    "registrationSent": null,
    "email": "mwazowski@minc.biz",
    "tenantId": 1,
    "city": "Monstropolis",
    "tenant": "root",
    "id": 8,
    "company": null,
    "rolename": "admin",
    "phoneNumber": null,
    "country": null,
    "fullName": "Mike Wazowski",
    "publicSshKey": null,
    "uid": null,
    "stateOrProvince": null,
    "lastUpdated": null,
    "username": "mike",
    "newUser": false,
    "addressLine2": null,
    "role": 1,
    "addressLine1": "22 Mike Wazowski You've Got Your Life Back Lane",
    "postalCode": null,
    "gid": null
}}

```

users/{{ID}}

GET

Retrieves a specific user.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 244: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the user to be retrieved

567: Request Example

```
GET /api/2.0/users/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege role assigned to this user

rolename The name of the highest-privilege role assigned to this user

stateOrProvince The name of the state or province where this user resides

tenant The name of the tenant to which this user belongs

tenantId The integral, unique identifier of the tenant to which this user belongs

uid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always null

username The user's username

568: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳9vqUmt8fWEuDb+9LQJ4sGbbF4Z0a7uNyBNSWhyzAi3fBUZ5mGhd4Jx5IuSlEqiLZnYeViJJL8mpRortkH
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 17:46:00 GMT
Content-Length: 588

{ "response": [
  {
    "username": "admin",
    "registrationSent": null,
    "addressLine1": "not a real address",
    "addressLine2": "not a real address either",
    "city": "not a real city",
    "company": "not a real company",
    "country": "not a real country",
    "email": "not@real.email",
    "fullName": "Not a real Full Name",
    "gid": null,
    "id": 2,
    "newUser": false,
    "phoneNumber": "not a real phone number",
    "postalCode": "not a real postal code",
    "publicSshKey": "not a real ssh key",
    "role": 1,
    "rolename": "admin",
    "stateOrProvince": "not a real state or province",
```

(continues on next page)

(continued from previous page)

```

    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "lastUpdated": "2018-12-13 17:24:23+00"
  }
}]

```

PUT

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 245: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the user to be modified

addressLine1 An optional field which should contain the user’s address - including street name and number

addressLine2 An optional field which should contain an additional address field for e.g. apartment number

city An optional field which should contain the name of the city wherein the user resides

company An optional field which should contain the name of the company for which the user works

confirmLocalPasswd The ‘confirm’ field in a new user’s password specification - must match `localPasswd`

country An optional field which should contain the name of the country wherein the user resides

email The user’s email address The given email is validated (circuitously) by [GitHub user asaskevich’s regular expression](#) . Note that it can’t actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user’s full name, e.g. “John Quincy Adams”

localPasswd The user’s password

newUser An optional meta field with no apparent purpose - don’t use this

- phoneNumber** An optional field which should contain the user's phone number
- postalCode** An optional field which should contain the user's postal code
- publicSshKey** An optional field which should contain the user's public encryption key used for the SSH protocol
- role** The number that corresponds to the highest permission role which will be permitted to the user
- stateOrProvince** An optional field which should contain the name of the state or province in which the user resides
- tenantId** The integral, unique identifier of the tenant to which the new user shall belong

Note: This field is optional if and only if tenancy is not enabled in Traffic Control

username The new user's username

569: Request Structure

```
PUT /api/2.0/users/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 458
Content-Type: application/json

{
  "addressLine1": "not a real address",
  "addressLine2": "not a real address either",
  "city": "not a real city",
  "company": "not a real company",
  "country": "not a real country",
  "email": "not@real.email",
  "fullName": "Not a real fullName",
  "phoneNumber": "not a real phone number",
  "postalCode": "not a real postal code",
  "publicSshKey": "not a real ssh key",
  "stateOrProvince": "not a real state or province",
  "tenantId": 1,
  "role": 1,
  "username": "admin"
}
```

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege role assigned to this user
- rolename** The name of the highest-privilege role assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the tenant to which this user belongs
- tenantId** The integral, unique identifier of the tenant to which this user belongs
- uid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always `null`
- username** The user's username

570: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 17:24:23 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: QKvGSIwSdreMI/OdgWv9WQfI/
→C1JbXSoQGospTGfCVUJ32XNWMhmREGzWojWsilW8os8b14TGYeyMLUWunf2Ug==
Content-Length: 661

{ "alerts": [
  {
    "level": "success",
    "text": "User update was successful."
  }
],
"response": {
  "registrationSent": null,
  "email": "not@real.email",
  "tenantId": 1,
  "city": "not a real city",
  "tenant": "root",
  "id": 2,
  "company": "not a real company",
  "rolename": "admin",
  "phoneNumber": "not a real phone number",
  "country": "not a real country",
  "fullName": "Not a real Full Name",
  "publicSshKey": "not a real ssh key",
  "uid": null,
  "stateOrProvince": "not a real state or province",
  "lastUpdated": "2018-12-12 16:26:32.821187+00",
  "username": "admin",
  "newUser": false,
  "addressLine2": "not a real address either",
  "role": 1,
  "addressLine1": "not a real address",
  "postalCode": "not a real postal code",
  "gid": null
}}
```

users/register

POST

Register a user and send registration email.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

email Email address of the new user The given email is validated (circuitously) by [GitHub user asaskevich's regular expression](#) . Note that it can't actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

role The integral, unique identifier of the highest permissions *Role* which will be afforded to the new user. It restricts the allowed values to identifiers for *Roles* with at most the same permissions level as the requesting user.

tenantId A field containing the integral, unique identifier of the *Tenant* to which the new user will belong. It restricts the allowed values to identifiers for *Tenants* within the requesting user's *Tenant*'s permissions.

571: Request Example

```
POST /api/2.0/users/register HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 59
Content-Type: application/json

{
  "email": "test@example.com",
  "role": 3,
  "tenantId": 1
}
```

Response Structure

572: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 22:03:22 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→yvf++0qxvu3u0IAYbWLUgJKxZ4T60Mi5H9eGTxrKLxnRsHw0PdDIrThbTnWtATBkak4vU/
→dPHLLXKW85LUTEWg==
Content-Length: 160

{ "alerts": [
  {
    "level": "success",
    "text": "Sent user registration to test@example.com with the
→following permissions [ role: read-only | tenant: root ]"
  }
]}
```

`vault/bucket/{{bucket}}/key/{{key}}/values`

Retrieves the `object` stored under a given `key` from a given `bucket` in *Traffic Vault*.

Deprecated since version ATCv6.

GET

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 246: Request Path Parameters

Name	Description
bucket	The bucket that the key is stored under
key	The key that the object is stored under

573: Request Example

```
GET /api/2.0/vault/bucket/ssl/key/demo1-latest/values HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

The response structure varies according to what is stored. Top-level keys will always be String type, but the values can be any type.

574: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 23:29:27 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: LUq4+MUCgIqxBWqbuA/
Pbsdq5Qfs7vPUcZ0Cu2Fc0UyP0X8xXit3BJrd0LA+dSSJ3tSQ7Qij1+0ahzuouuLT7Q==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 22:29:27 GMT
Transfer-Encoding: chunked

{
  "alerts": [
    {
      "text": "This endpoint is deprecated, and will be removed in the future",
      "level": "warning"
    }
  ],
  "response": {
    "cdn": "CDN-in-a-Box",
    "certificate": {
      "crt": "...",
      "csr": "...",
      "key": "..."
    },
    "deliveryservice": "demo1",
    "hostname": "/*.demo1.mycdn.ciab.test",
    "key": "demo1",
    "version": 1
  }
}
```

vault/ping

GET

Pings Traffic Vault to retrieve status.

Auth. Required Yes

Roles Required “read-only”

Response Type Object

Request Structure

No parameters available.

Response Properties

status The status returned from the ping request to the Traffic Vault server

server The Traffic Vault server that was pinged

575: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 15:37:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳z9P1NkxGebPncUhaChDHtYKYI+XVZfhE6Y84TuwoASZFIMfISELwADLpvpPTN+wnzBfREksLYn+0313Q
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 14:37:55 GMT
Content-Length: 90

{ "response":
  {
    "status": "OK",
    "server": "trafficvault.infra.ciab.test:8087"
  }
}
```


5.1.6 API V3 Routes

API routes available in version 3.

about

GET

Returns info about the Traffic Ops build that is currently running, generated at startup. The output will be the same until the Traffic Ops *version changes*.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

576: Request Example

```
GET /api/3.0/about HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

commitHash The [Git](#) commit hash that Traffic Ops was built at.

commits The number of commits in the branch of the commit that Traffic Ops was built at, including that commit. Calculated by running `git rev-list HEAD | wc -l`.

goVersion The version of [Go](#) that was used to build Traffic Ops.

release The major version of CentOS or Red Hat Enterprise Linux that the build environment was running.

name The human-readable name of the [RPM](#) file.

RPMVersion The entire name of the RPM file, excluding the file extension.

Version The version of ATC that this version of Traffic Control belongs to.

577: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 19:35:28
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳7SVQsddCUVRs+sineziRGR60yMli7XLZbjxyMQgW6E506bh5thM0uttPFT7aJckDcgT45PlhexycwlApO
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 18:35:28 GMT
Content-Length: 145

{
  "commitHash": "1c9a2e9c",
  "commits": "10555",
  "goVersion": "go1.11.13",
  "release": "el7",
  "name": "traffic_ops",
  "RPMVersion": "traffic_ops-4.0.0-10555.1c9a2e9c.el7",
  "Version": "4.0.0"
}

```

acme_accounts

New in version 3.1.

GET

Gets information for all *ACME Account* s.

Auth. Required Yes

Roles Required “admin”

Response Type Array

Request Structure

No parameters available

Response Structure

email The email connected to the *ACME Account*.

privateKey The private key connected to the *ACME Account*.

uri The URI for the *ACME Account*. Differs per provider.

provider The ACME provider.

578: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": [
  {
    "email": "sample@example.com",
    "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----END RSA PRIVATE KEY-----\n",
    "uri": "https://acme.example.com/acct/1",
    "provider": "Lets Encrypt"
  }
]}
```

POST

Creates a new *ACME Account*.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

The request body must be a single *ACME Account* object with the following keys:

email The email connected to the *ACME Account*.

privateKey The private key connected to the *ACME Account*.

uri The URI for the *ACME Account*. Differs per provider.

provider The ACME provider.

579: Request Example

```
POST /api/3.1/acme_accounts HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 181
Content-Type: application/json

{
  "email": "sample@example.com",
  "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----
→END RSA PRIVATE KEY-----\n",
  "uri": "https://acme.example.com/acct/1",
  "provider": "Lets Encrypt"
}
```

Response Structure

- email** The email connected to the *ACME Account*.
- privateKey** The private key connected to the *ACME Account*.
- uri** The URI for the *ACME Account*. Differs per provider.
- provider** The ACME provider.

580: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 10 Dec 2020 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
→Cfh2X9i3G+MQ36eH95gukJqOBOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:18:21 GMT
Content-Length: 253

{ "alerts": [
```

(continues on next page)

(continued from previous page)

```
{
  "text": "Acme account created",
  "level": "success"
},
"response": {
  "email": "sample@example.com",
  "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----
→END RSA PRIVATE KEY-----\n",
  "uri": "https://acme.example.com/acct/1",
  "provider": "Lets Encrypt"
}}
```

PUT

Updates an existing *ACME Account*.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

The request body must be a single *ACME Account* object with the following keys:

email The email connected to the *ACME Account*.

privateKey The private key connected to the *ACME Account*.

uri The URI for the *ACME Account*. Differs per provider.

provider The ACME provider.

581: Request Example

```
PUT /api/3.1/acme_accounts HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 181
Content-Type: application/json

{
  "email": "sample@example.com",
  "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----
→END RSA PRIVATE KEY-----\n",
```

(continues on next page)

(continued from previous page)

```
"uri": "https://acme.example.com/acct/1",
"provider": "Lets Encrypt"
}
```

Response Structure

- email** The email connected to the *ACME Account*.
- privateKey** The private key connected to the *ACME Account*.
- uri** The URI for the *ACME Account*. Differs per provider.
- provider** The ACME provider.

582: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 10 Dec 2020 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
→Cfh2X9i3G+MQ36eH95gukJqOBOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:18:21 GMT
Content-Length: 253

{ "alerts": [
  {
    "text": "Acme account updated",
    "level": "success"
  }
],
"response": {
  "email": "sample@example.com",
  "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----
→END RSA PRIVATE KEY-----\n",
  "uri": "https://acme.example.com/acct/1",
  "provider": "Lets Encrypt"
}}
```

`acme_accounts/{{provider}}/{{email}}`

New in version 3.1.

DELETE

Delete *ACME Account* information.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 247: Request Path Parameters

Name	Description
provider	The ACME provider for the account to be deleted
email	The email used in the <i>ACME Account</i> to be deleted

Response Structure

583: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 10 Dec 2020 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: rGD2sOMHYF0sga1zuTytyLHCUkkc3ZwQRKvZ/
    ↳HuPz0bOP4WztKTOVXB4uhs3iJqBg9zRB2TucMxONHN+3/yShQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 10 Dec 2020 14:24:34 GMT
Content-Length: 60

{"alerts": [
  {
    "text": "Acme account deleted",
    "level": "success"
  }
]}
```

(continues on next page)

(continued from previous page)

```
}
[]}
```

api_capabilities

Deals with the capabilities that may be associated with API endpoints and methods. These capabilities are assigned to *Roles*, of which a user may have one or more. Capabilities support “wildcarding” or “globbing” using asterisks to group multiple routes into a single capability

GET

Get all API-capability mappings.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 248: Request Query Parameters

Name	Required	Type	Description
capability	no	string	Capability name

584: Request Example

```
GET /api/3.0/api_capabilities?capability=types-write HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

capability Capability name

httpMethod An HTTP request method, practically one of:

- GET
- POST
- PUT

- PATCH
- DELETE

httpRoute The request route for which this capability applies - relative to the Traffic Ops server's URL

id An integer which uniquely identifies this capability

lastUpdated The time at which this capability was last updated, in *Traffic Ops's Custom Date/Time Format*

585: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 01 Nov 2018 14:45:24 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: wptErtIop/AfTTQ+1MZdA2YpPXE0uLFfrPQvvaHq0/
→uX5fRruOVYW+7p8JTrtH1xglWN+x6FnjQnSHuWwcpyJg==
Content-Length: 393

{ "response": [
  {
    "httpMethod": "POST",
    "lastUpdated": "2018-11-01 14:10:22.794114+00",
    "httpRoute": "types",
    "id": 261,
    "capability": "types-write"
  },
  {
    "httpMethod": "PUT",
    "lastUpdated": "2018-11-01 14:10:22.795917+00",
    "httpRoute": "types/*",
    "id": 262,
    "capability": "types-write"
  },
  {
    "httpMethod": "DELETE",
    "lastUpdated": "2018-11-01 14:10:22.799748+00",
    "httpRoute": "types/*",
```

(continues on next page)

(continued from previous page)

```

        "id": 263,
        "capability": "types-write"
    }
  ]}

```

asns

See also:

The [Autonomous System Wikipedia page](#) for an explanation of what an ASN actually is.

GET

List all ASNs.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 249: Request Query Parameters

Parameter	Required	Description
cache-group	no	The <i>ID</i> of a <i>Cache Group</i> - only ASNs for this <i>Cache Group</i> will be returned.
id	no	The integral, unique identifier of the desired ASN-to- <i>Cache Group</i> association
order-by	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>n</i> th page of results, where “ <i>n</i> ” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

586: Request Example

```
GET /api/3.0/asns HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cachegroup** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cachegroupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

587: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 22:51:14
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳F2NmDbTpXqrIQDX7IBKH9+1drTL4XedSfJv6klMgLEZwbLCkddIXuSLpmgVCID6kTVqy3fTKjZS3U+HJ
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 21:51:14 GMT
Content-Length: 128

{ "response": [
  {
    "asn": 1,
    "cachegroup": "TRAFFIC_ANALYTICS",
    "cachegroupId": 1,
```

(continues on next page)

(continued from previous page)

```

        "id": 1,
        "lastUpdated": "2019-12-02 21:49:08+00"
    }
}]

```

POST

Creates a new ASN.

Note: There cannot be two different ASN object with the same `asn`. An ASN may only belong to one cachegroup, but a cachegroup can have zero or more ASNs.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

asn The value of the new ASN

cachegroup An optional field which, if present, is a string that specifies the *Name* of a *Cache Group* to which this ASN will be assigned

Note: While this endpoint accepts the `cachegroup` field, sending this in the request payload has no effect except that the response will (erroneously) name the *Cache Group* to which the ASN was assigned. Any subsequent requests will reveal that, in fact, the *Cache Group* is set entirely by the `cachegroupId` field, and so the actual *Name* may differ from what was in the request.

cachegroupId An integer that is the *ID* of a *Cache Group* to which this ASN will be assigned

588: Request Example

```

POST /api/3.0/asns HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 29

```

(continues on next page)

(continued from previous page)

```
{"asn": 1, "cachegroupId": 1}
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cachegroup** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cachegroupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

589: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 22:49:08
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mx8b2GTyojz4QtMxXCmoQyZogCB504vs0yv6WGly4dwM81W3XiejWNuUwchRBYYi8QHaWsmZ3DaiGGfQi
    ↳8Giw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 21:49:08 GMT
Content-Length: 150

{ "alerts": [
  {
    "text": "asn was created.",
    "level": "success"
  }
],
"response": {
  "asn": 1,
  "cachegroup": null,
```

(continues on next page)

(continued from previous page)

```
"cachegroupId": 1,  
"id": 1,  
"lastUpdated": "2019-12-02 21:49:08+00"  
}}
```

PUT

Updates an existing ASN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

asn The value of the new ASN.

cachegroup A string that specifies the *Name* of a *Cache Group* to which this ASN will be assigned. If you do not pass this field, the cachegroup will be null.

cachegroupId The integral, unique identifier of the status of the *Cache Group*.

590: Request Example

```
PUT /api/3.0/asns?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 53

{
  "asn": 1,
  "cachegroup": "TRAFFIC_OPS",
  "cachegroupId": 2
}
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cachegroup** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cachegroupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

591: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 07:21:10
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳MjvwJg6AFbdqGPlAhK+2pfiN+VFjzgeNnhXoMVbh6+fRQYKeej6CCj3x09hw0l4uhp9d9RySrE/
  ↳CQ3+L1b2VGQ==
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

Date: Tue, 25 Feb 2020 06:21:10 GMT

Content-Length: 164

```
{
  "alerts": [
    {
      "text": "asn was updated.",
      "level": "success"
    }
  ],
  "response": {
    "asn": 1,
    "cachegroup": "TRAFFIC_OPS",
    "cachegroupId": 2,
    "id": 1,
    "lastUpdated": "2020-02-25 06:21:10+00"
  }
}
```

DELETE

Deletes an existing ASN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

592: Request Example

```
DELETE /api/3.0/asns?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

593: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 08:27:33
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Woz8NSHIYVpX4V5X4xZWZIX1hvGL2uian7nUhjZ8F23Nb9RWQRMig/cc+1vXEzkT/
    ↳ehKV9t11FKRLX+avSae0g==
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 07:27:33 GMT
Content-Length: 83

{
  "alerts": [
    {
      "text": "asn was deleted.",
      "level": "success"
    }
  ]
}
```

`asns/{{id}}`

See also:

The [Autonomous System Wikipedia](#) page for an explanation of what an ASN actually is.

PUT

Allows user to edit an existing ASN-to-*Cache Group* association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

asn The new ASN which will be associated with the identified *Cache Group* - must not conflict with existing associations

cachegroup An optional field which, if present, is a string that specifies the *Name* of a *Cache Group* to which this ASN will be assigned

Note: While this endpoint accepts the `cachegroup` field, sending this in the request payload has no effect except that the response will (erroneously) name the *Cache Group* to which the ASN was assigned. Any subsequent requests will reveal that, in fact, the *Cache Group* is set entirely by the `cachegroupId` field, and so the actual *Name* may differ from what was in the request.

cachegroupId An integer that is the *ID* of a *Cache Group* to which this ASN will be assigned - must not conflict with existing associations

Table 250: Request Path Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the desired ASN-to- <i>Cache Group</i> as- sociation

594: Request Example

```
PUT /api/3.0/asns/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

(continues on next page)

(continued from previous page)

```
Content-Length: 29
Content-Type: application/x-www-form-urlencoded

{"asn": 2, "cachegroupId": 1}
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cachegroup** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cachegroupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

595: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: /83P4LJVsrQx9BKHfxo5pbhQm1B4o3a9v3PpkspyOJcpNx1S/
→GJhCPpiANBki547sbY+0vTq76IriHZ4GYp8bA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 08 Nov 2018 14:37:39 GMT
Content-Length: 160

{ "alerts": [
  {
    "text": "asn was updated.",
    "level": "success"
  }
],
"response": {
  "asn": 2,
  "cachegroup": null,
```

(continues on next page)

(continued from previous page)

```
"cachegroupId": 1,
"id": 1,
"lastUpdated": "2018-11-08 14:37:39+00"
}}
```

DELETE

Deletes an association between an ASN and a *Cache Group*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 251: Request Path Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the desired ASN-to- <i>Cache Group</i> as- sociation

596: Request Example

```
DELETE /api/3.0/asns/1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

597: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 23:06:24.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→6t3WA+DOcfPJB5UnvDpzEVx5ySfmJgEV9wgk071U5k32L1VXpxcaTdDVLNGgDD19sdNftmYnKXf5jpfWU
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 22:06:24 GMT
Content-Length: 81

{ "alerts": [
  {
    "text": "asn was deleted.",
    "level": "success"
  }
]}
```

cache_stats

Retrieves detailed, aggregated statistics for caches in a specific CDN.

See also:

This gives an aggregate of statistics for *all caches* within a particular CDN and time range. For statistics basic statistics from all caches regardless of CDN and at the current time, use *caches/stats*.

GET

Retrieves statistics about the caches within the CDN

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 252: Request Query Parameters

Name	Required	Description
cdnName	yes	The name of a CDN. Results will represent caches within this CDN
end-Date	yes	The date and time until which statistics shall be aggregated in RFC 3339 format (with or without sub-second precision), the number of nanoseconds since the Unix Epoch, or in the same, proprietary format as the <code>lastUpdated</code> fields prevalent throughout the Traffic Ops API
exclude	no	Either “series” to omit the data series from the result, or “summary” to omit the summary data from the result - directly corresponds to fields in the Response Structure
interval	no	Specifies the interval within which data will be “bucketed”; e.g. when requesting data from 2019-07-25T00:00:00Z to 2019-07-25T23:59:59Z with an interval of “1m”, the resulting data series (assuming it is not excluded) should contain $24 \frac{\text{hours}}{\text{day}} \times 60 \frac{\text{minutes}}{\text{hour}} \times 1 \text{day} \times 1 \frac{\text{minute}}{\text{datapoint}} = 1440$ data points The allowed values for this parameter are valid InfluxQL duration literal strings matching <code>^d+[mhdw]\$</code>
limit	no	A natural number indicating the maximum amount of data points should be returned in the <code>series</code> object
metric-Type	yes	The metric type being reported - one of: ‘connections’, ‘bandwidth’, ‘maxkpbs’
offset	no	A natural number of data points to drop from the beginning of the returned data set
orderby	no	Though one struggles to imagine why, this can be used to specify “time” to sort data points by their “time” (which is the default behavior)
start-Date	yes	The date and time from which statistics shall be aggregated in RFC 3339 format (with or without sub-second precision), the number of nanoseconds since the Unix Epoch, or in the same, proprietary format as the <code>lastUpdated</code> fields prevalent throughout the Traffic Ops API

598: Request Example

```
GET /api/3.0/cache_stats?cdnName=CDN&endDate=2019-10-28T20:49:00Z&
→metricType=bandwidth&startDate=2019-10-28T20:45:00Z HTTP/1.1
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: application/json;timestamp=unix, application/json;
→timestamp=rfc;q=0.9, application/json;q=0.8, */*;q=0.7
Connection: keep-alive
Cookie: mojolicious=...
```

Content Format

It's important to note in *Request Example* the use of a complex “Accept” header. This endpoint accepts two special media types in the “Accept” header that instruct it on how to format the timestamps associated with the returned data. Specifically, Traffic Ops will recognize the special, optional, non-standard parameter of *application/json: timestamp*. The values of this parameter are restricted to one of

- rfc** Returned timestamps will be formatted according to **RFC 3339** (no sub-second precision).
- unix** Returned timestamps will be formatted as the number of nanoseconds since the Unix Epoch (midnight on January 1st 1970 UTC).

Implementation Detail

The endpoint passes back nanoseconds, specifically, because that is the form used both by InfluxDB, which is used to store the data being served, and Go's standard library. Clients may need to convert the value to match their own standard libraries - e.g. the `Date()` class in Javascript expects milliseconds.

The default behavior - when only e.g. *application/json* or **/** is given - is to use **RFC 3339** formatting. It will, however, respect quality parameters. It is suggested that clients request timestamps they can handle specifically, rather than relying on this default behavior, as it is **subject to change** and is in fact **expected to invert in the next major release** as string-based time formats become deprecated.

See also:

For more information on the “Accept” HTTP header, consult [its dedicated page on MDN](#).

Response Structure

series An object containing the actual data series and information necessary for working with it.

columns This is an array of names of the columns of the data contained in the “values” array - should always be `["time", "sum_count"]`

count The number of data points contained in the “values” array

name The name of the data set. Should always match `metric.ds.1min` where `metric` is the requested `metricType`

values The actual array of data points. Each represents a length of time specified by the `interval` query parameter

time The time at which the measurement was taken. This corresponds to the *beginning* of the interval. This time comes in the format of either an [RFC 3339](#)-formatted string, or a number containing the number of nanoseconds since the Unix Epoch depending on the “Accept” header sent by the client, according to the rules outlined in [Content Format](#).

value The value of the requested `metricType` at the time given by `time`. This will always be a floating point number, unless no data is available for the data interval, in which case it will be `null`

summary A summary of the data contained in the “series” object

average The arithmetic mean of the data’s values

count The number of measurements taken within the requested timespan. This is, in general, **not** the same as the `count` field of the `series` object, as it reflects the number of underlying, un-“bucketed” data points, and is therefore dependent on the implementation of Traffic Stats.

fifthPercentile Data points with values less than or equal to this number constitute the “bottom” 5% of the data set

max The maximum value that can be found in the requested data set

min The minimum value that can be found in the requested data set

ninetyEighthPercentile Data points with values greater than or equal to this number constitute the “top” 2% of the data set

ninetyFifthPercentile Data points with values greater than or equal to this number constitute the “top” 5% of the data set

599: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: p4asf1n7fXGtgpW/
    ↳dWgolJWdXjwDcCjyvJOPFqkckbgoXGUHEj5/
    ↳wlz7brlQ48t3ZnOWCq0lbsu2eSiBssBtUQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 28 Oct 2019 20:49:51 GMT

{ "response": {
  "series": {
    "columns": [
      "time",
      "sum_count"
    ],
    "count": 4,
    "name": "bandwidth.cdn.1min",
    "tags": {
      "cdn": "CDN-in-a-Box"
    },
    "values": [
      [
        1572295500000000000,
        null
      ],
      [
        1572295560000000000,
        113.66666666666666
      ],
      [
        1572295620000000000,
        108.83333333333334
      ]
    ]
  }
}
```

(continues on next page)

(continued from previous page)

```

        ],
        [
            15722956800000000000,
            113
        ]
    ],
    },
    "summary": {
        "average": 111.83333333333333,
        "count": 3,
        "fifthPercentile": 0,
        "max": 113.66666666666666,
        "min": 108.83333333333334,
        "ninetyEighthPercentile": 113.66666666666666,
        "ninetyFifthPercentile": 113.66666666666666
    }
}
}

```

cachegroupparameters

Deprecated since version ATCv6.

GET

Extract information about the *Parameters* associated with *Cache Groups*.

Auth. Required Yes

Roles Required None

Response Type Object

Response Structure

Table 253: Request Query Parameters

Name	Re-quired	Description
cacheGroup	no	Show only the <i>Parameters</i> with the <i>Cache Group</i> identified by this integral, unique identifier
parameter	no	Show only the <i>Parameters</i> with the <i>Parameter</i> identified by this integral, unique identifier
orderBy	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>n</i> th page of results, where “n” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

Response Structure

cacheGroupParameters An array of identifying information for the *Parameters* of *Cache Groups*

cacheGroup A string containing the *Name* of the *Cache Group*

last_updated Date and time of last modification in *Traffic Ops’s Custom Date/Time Format*

parameter An integer that is the *Parameter’s ID*

600: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 18:24:12 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
➔GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Vary: Accept-Encoding
Whole-Content-Sha512: PZyh09NeYYy4sXSv+Bfov0v32EuEk/1y7/
↪B+4fyvhbcPxWQ650NXBDpAe8IsmYZQYVRB03xlBtc33bo3Ixunbg==
Content-Length: 124

{ "response": {
  "cachegroupParameters": [
    {
      "parameter": 124,
      "last_updated": "2018-11-14 18:23:40.488853+00",
      "cachegroup": "test"
    }
  ]
}}
```

Deprecated since version ATCv6.

POST

Assign *Parameter*(s) to *Cache Group*(s).

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

This endpoint accepts two formats for the request payload:

Single Object Format For assigning a single *Parameter* to a single *Cache Group*

Array Format For making multiple assignments of *Parameters* to *Cache Groups* simultaneously

Single Object Format

cacheGroupId An integer that is the *ID* of the *Cache Group* to which a *Parameter* is being assigned

parameterId An integer that is the *ID* of the *Parameter* being assigned

601: Request Example

```
POST /api/3.0/cachegrouponparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 39
Content-Type: application/json

{
  "cacheGroupId": 8,
  "parameterId": 124
}
```

Array Format

cacheGroupId An integer that is the *ID* of the *Cache Group* to which a *Parameter* is being assigned

parameterId An integer that is the *ID* of the *Parameter* being assigned

602: Request Example

```
POST /api/3.0/cachegrouponparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 39
Content-Type: application/json

[
  {
    "cacheGroupId": 8,
    "parameterId": 124
  },
  {
    "cacheGroupId": 8,
    "parameterId": 125
  }
]
```

Response Structure

cacheGroupId An integer that is the *ID* of the *Cache Group* to which a *Parameter* has been assigned

parameterId An integer that is the *ID* of the *Parameter* which has been assigned

603: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 15:47:49 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: wCv388wFaSjgFLCnI9dchlcyGxaVr8IhBAG25F+rpI2/
→azCswEYTcVBSlYOg6NxTQRzGkluMvn67jI6rV+vNsQ==
Content-Length: 136

{ "alerts": [
  {
    "level": "success",
    "text": "Cachegroup parameter associations were created."
  }
],
"response": [
  {
    "cacheGroupId": 8,
    "parameterId": 124
  }
]}
```

`cachegroupparameters/{ID}/{parameterID}`

Deprecated since version ATCv6.

DELETE

Dissociate a *Parameter* with a *Cache Group*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 254: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Cache Group</i> which will have the <i>Parameter</i> association deleted
parameterID	The <i>ID</i> of the <i>Parameter</i> which will be removed from a <i>Cache Group</i>

604: Request Example

```
DELETE /api/3.0/cachegroupparameters/8/124 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

605: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 18:26:40 GMT
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→Cuj+ZPAKsDLp4FpbJDCwsWY0yVQAI1Um1CWraeTIQEMlyJSBEm17oKQWDjzTrvqqV8Prhu3gzlcHoVPzE
Content-Length: 84

{ "alerts": [
  {
    "level": "success",
    "text": "cachegroup parameter was deleted."
  }
]}
```

cachegroups

GET

Extract information about *Cache Groups*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 255: Request Query Parameters

Name	Re-quired	Description
id	no	Return the only <i>Cache Group</i> that has this id
name	no	Return only the <i>Cache Group</i> identified by this <i>Name</i>
type	no	Return only <i>Cache Groups</i> that are of the <i>Type</i> identified by this integral, unique identifier
topology	no	Return only <i>Cache Groups</i> that are used in the <i>Topology</i> identified by this unique identifier
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

606: Request Example

```
GET /api/3.0/cachegroups?type=23 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

fallbacks An array of strings that are *Cache Group names* that are registered as *Fallbacks* for this *Cache Group*¹

fallbackToClosest A boolean value that defines the *Fallback to Closest* behavior of this *Cache Group*^{Page 887, 1}

id An integer that is the *ID* of the *Cache Group*

lastUpdated The time and date at which this entry was last updated in *Traffic Ops's Custom Date/Time Format*

¹ Traffic Router will first check for a fallbacks array and, when that is empty/unset/all the *Cache Groups* in it are also unavailable, will subsequently check for fallbackToClosest. If that is true, then it falls back to the geographically closest *Cache Group* capable of serving the same content or, when it is false/no such *Cache Group* exists/said *Cache Group* is also unavailable, will respond to clients with a failure response indicating the problem.

latitude A floating-point *Latitude* for the *Cache Group*

localizationMethods An array of *Localization Methods* as strings

longitude A floating-point *Longitude* for the *Cache Group*

name A string containing the *Name* of the *Cache Group*

parentCachegroupId An integer that is the *ID* of this *Cache Group*'s *Parent* - or null if it doesn't have a *Parent*

parentCachegroupName A string containing the *Name* of this *Cache Group*'s *Parent* - or null if it doesn't have a *Parent*

secondaryParentCachegroupId An integer that is the *ID* of this *Cache Group*'s *Secondary Parent* - or null if it doesn't have a *Secondary Parent*

secondaryParentCachegroupName A string containing the *Name* of this *Cache Group*'s *Secondary Parent Cache Group* - or null if it doesn't have a *Secondary Parent*

shortName A string containing the *Short Name* of the *Cache Group*

typeId An integral, unique identifier for the '*Type*' of the *Cache Group*

typeName A string that names the *Type* of this *Cache Group*

Note: The default value of `fallbackToClosest` is 'true', and if it is 'null' Traffic Control components will still interpret it as 'true'.

607: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳oV6ifEgoFy+v049tVjSsRdWQf4bxjrUvIYfDdgpUtlxiC7gzCv31m5bXQ8EUBW4eg2hfYM+BsGvJpnNDZ
X-Server-Name: traffic_ops_golang/
Date: Wed, 07 Nov 2018 19:46:36 GMT
Content-Length: 379

{ "response": [
  {
    "id": 7,
    "name": "CDN_in_a_Box_Edge",
```

(continues on next page)

(continued from previous page)

```

    "shortName": "ciabEdge",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "parentCachegroupName": "CDN_in_a_Box_Mid",
    "parentCachegroupId": 6,
    "secondaryParentCachegroupName": null,
    "secondaryParentCachegroupId": null,
    "fallbackToClosest": [],
    "localizationMethods": [],
    "typeName": "EDGE_LOC",
    "typeId": 23,
    "lastUpdated": "2018-11-07 14:45:43+00",
    "fallbacks": []
  }
}]

```

POST

Creates a *Cache Group*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

fallbacks An optional field which, when present, should contain an array of strings that are the *Names* of other *Cache Groups* which will be the *Fallbacks*^{Page 887, 1}

fallbackToClosest A boolean that sets the *Fallback to Closest* behavior of the *Cache Group*^{Page 887, 1}

Note: The default value of `fallbackToClosest` is `true`, and if it is `null` Traffic Control components will still interpret it as though it were `true`.

latitude An optional field which, if present, should be a floating-point number that will define the *Latitude* for the *Cache Group*²

localizationMethods Array of *Localization Methods* (as strings)

² While these fields are technically optional, note that if they are not specified many things may break. For this reason, Traffic Portal requires them when creating or editing *Cache Groups*.

Tip: This field has no defined meaning if the *Type* identified by `typeId` is not “EDGE_LOC”.

longitude An optional field which, if present, should be a floating-point number that will define the *Longitude* for the *Cache Group*?

name The *Name* of the *Cache Group*

parentCachegroupId An optional field which, if present, should be an integer that is the *ID* of a *Parent* for this *Cache Group*.

secondaryParentCachegroupId An optional field which, if present, should be an integral, unique identifier for this *Cache Group*’s secondary parent

shortName An abbreviation of the name

typeId An integral, unique identifier for the *Cache Group*’s *Type*

Note: The actual, integral, unique identifiers for these *Types* must first be obtained, generally via *types*.

608: Request Example

```
POST /api/3.0/cachegroups HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 252
Content-Type: application/json

{
  "name": "test",
  "shortName": "test",
  "latitude": 0,
  "longitude": 0,
  "fallbackToClosest": true,
  "localizationMethods": [
    "DEEP_CZ",
    "CZ",
    "GEO"
  ],
  "typeId": 23,
}
```

Response Structure

- fallbacks** An array of strings that are *Cache Group names* that are registered as *Fallbacks* for this *Cache Group*^{Page 887, 1}
- fallbackToClosest** A boolean value that defines the *Fallback to Closest* behavior of this *Cache Group*^{Page 887, 1}
- id** An integer that is the *ID* of the *Cache Group*
- lastUpdated** The time and date at which this entry was last updated in *Traffic Ops's Custom Date/Time Format*
- latitude** A floating-point *Latitude* for the *Cache Group*
- localizationMethods** An array of *Localization Methods* as strings
- longitude** A floating-point *Longitude* for the *Cache Group*
- name** A string containing the *Name* of the *Cache Group*
- parentCachegroupId** An integer that is the *ID* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*
- parentCachegroupName** A string containing the *Name* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*
- secondaryParentCachegroupId** An integer that is the *ID* of this *Cache Group's Secondary Parent* - or null if it doesn't have a *Secondary Parent*
- secondaryParentCachegroupName** A string containing the *Name* of this *Cache Group's Secondary Parent Cache Group* - or null if it doesn't have a *Secondary Parent*
- shortName** A string containing the *Short Name* of the *Cache Group*
- typeId** An integral, unique identifier for the '*Type*' of the *Cache Group*
- typeName** A string that names the *Type* of this *Cache Group*

609: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→YvZlh3rpf13nBq6SbNVhbkt3IvckbB9amqGW2JhLxWK9K3cxjBq5J2sIHBUhrLKUhE9afpxtvaYrLRxjt
→YMQ==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Wed, 07 Nov 2018 22:11:50 GMT
Content-Length: 379

{ "alerts": [
  {
    "text": "cachegroup was created.",
    "level": "success"
  }
],
"response": {
  "id": 8,
  "name": "test",
  "shortName": "test",
  "latitude": 0,
  "longitude": 0,
  "parentCachegroupName": null,
  "parentCachegroupId": null,
  "secondaryParentCachegroupName": null,
  "secondaryParentCachegroupId": null,
  "fallbackToClosest": true,
  "localizationMethods": [
    "DEEP_CZ",
    "CZ",
    "GEO"
  ],
  "typeName": "EDGE_LOC",
  "typeId": 23,
  "lastUpdated": "2019-12-02 22:21:08+00",
  "fallbacks": []
}}
```

`cachegroups/{ID}`

PUT

Update *Cache Group*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 256: Request Path Parameters

Parameter	Description
ID	The <i>ID</i> of a <i>Cache Group</i>

fallbacks An optional field which, when present, should contain an array of strings that are the *Names* of other *Cache Groups* which will be the *Fallbacks*¹

fallbackToClosest A boolean that sets the *Fallback to Closest* behavior of the *Cache Group*^{Page 887, 1}

Note: The default value of `fallbackToClosest` is `true`, and if it is `null` Traffic Control components will still interpret it as though it were `true`.

latitude An optional field which, if present, should be a floating-point number that will define the *Latitude* for the *Cache Group*²

localizationMethods Array of *Localization Methods* (as strings)

Tip: This field has no defined meaning if the *Type* identified by `typeId` is not “EDGE_LOC”.

longitude An optional field which, if present, should be a floating-point number that will define the *Longitude* for the *Cache Group*[?]

name The *Name* of the *Cache Group*

parentCachegroupId An optional field which, if present, should be an integer that is the *ID* of a *Parent* for this *Cache Group*.

secondaryParentCachegroupId An optional field which, if present, should be an integral, unique identifier for this *Cache Group*’s secondary parent

shortName An abbreviation of the name

typeId An integral, unique identifier for the *Cache Group*’s *Type*

Note: The actual, integral, unique identifiers for these *Types* must first be obtained, generally via *types*.

¹ Traffic Router will first check for a `fallbacks` array and, when that is empty/unset/all the *Cache Groups* in it are also unavailable, will subsequently check for `fallbackToClosest`. If that is `true`, then it falls back to the geographically closest *Cache Group* capable of serving the same content or, when it is `false`/no such *Cache Group* exists/said *Cache Group* is also unavailable, will respond to clients with a failure response indicating the problem.

² While these fields are technically optional, note that if they are not specified many things may break. For this reason, Traffic Portal requires them when creating or editing *Cache Groups*.

610: Request Example

```
PUT /api/3.0/cachegroups/8 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 118
Content-Type: application/json

{
  "latitude": 0.0,
  "longitude": 0.0,
  "name": "test",
  "fallbacks": [],
  "fallbackToClosest": true,
  "shortName": "test",
  "typeId": 23,
  "localizationMethods": ["GEO"]
}
```

Response Structure

fallbacks An array of strings that are *Cache Group names* that are registered as *Fallbacks* for this *Cache Group*^{Page 887, 1}

fallbackToClosest A boolean value that defines the *Fallback to Closest* behavior of this *Cache Group*^{Page 887, 1}

id An integer that is the *ID* of the *Cache Group*

lastUpdated The time and date at which this entry was last updated in *Traffic Ops's Custom Date/Time Format*

latitude A floating-point *Latitude* for the *Cache Group*

localizationMethods An array of *Localization Methods* as strings

longitude A floating-point *Longitude* for the *Cache Group*

name A string containing the *Name* of the *Cache Group*

parentCachegroupId An integer that is the *ID* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

parentCachegroupName A string containing the *Name* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

secondaryParentCachegroupId An integer that is the *ID* of this *Cache Group's Secondary Parent* - or null if it doesn't have a *Secondary Parent*

secondaryParentCachegroupName A string containing the *Name* of this *Cache Group's Secondary Parent Cache Group* - or `null` if it doesn't have a *Secondary Parent*

shortName A string containing the *Short Name* of the *Cache Group*

typeId An integral, unique identifier for the '*Type*' of the *Cache Group*

typeName A string that names the *Type* of this *Cache Group*

611: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: t1W65/2kj25QyHt0Ib0xpBaAR2sXu2k0sRZ49WjKZp/
    ↳AK5S1YWhX7VNWCUUGiN1VNM4QRNqODC/7ewhYDFUncA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 19:14:28 GMT
Content-Length: 385

{ "alerts": [
  {
    "text": "cachegroup was updated.",
    "level": "success"
  }
],
"response": {
  "id": 8,
  "name": "test",
  "shortName": "test",
  "latitude": 0,
  "longitude": 0,
  "parentCachegroupName": null,
  "parentCachegroupId": null,
  "secondaryParentCachegroupName": null,
  "secondaryParentCachegroupId": null,
  "fallbacks": [],
  "fallbackToClosest": true,
  "localizationMethods": [
    "GEO"
  ],
  "typeName": "EDGE_LOC",
```

(continues on next page)

(continued from previous page)

```
"typeId": 23,
"lastUpdated": "2018-11-14 19:14:28+00"
}}
```

DELETE

Delete a *Cache Group*. A *Cache Group* which has assigned servers or is the *Parent* of one or more other *Cache Groups* cannot be deleted.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 257: Request Path Parameters

Parameter	Description
ID	The <i>ID</i> of a <i>Cache Group</i> to be deleted

612: Request Example

```
DELETE /api/3.0/cacheGroups/42 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

613: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 5jZBg07h1eNF70J/cmlbi3Hf9KJPx+WLMb1H/pSKF3FWb/
→10GUHIN35ZOB+1N5LZYCkmk3izGbTFkiruG8I41Q==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:31:04 GMT
Content-Length: 57

{ "alerts": [
  {
    "text": "cachegroup was deleted.",
    "level": "success"
  }
]}
```

cachegroups/{{ID}}/deliveryservices

POST

Assigns all of the “assignable” servers within a *Cache Group* to one or more *Delivery Services*.

Note: “Assignable” here means all of the *Cache Group’s servers* that have a *Type* that matches one of the glob patterns `EDGE*` or `ORG*`. If even one server of any *Type* exists within the *Cache Group* that is not assigned to the same CDN as the *Delivery Service* to which an attempt is being made to assign them, the request will fail.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

deliveryServices The integral, unique identifiers of the *Delivery Services* to which the *Cache Group’s servers* are being assigned

614: Request Example

```
POST /api/3.0/cachegroups/8/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 25
Content-Type: application/json

{"deliveryServices": [2]}
```

Response Structure

deliveryServices An array of integral, unique identifiers for *Delivery Services* to which the *Cache Group's servers* have been assigned

id An integer that is the *Cache Group's ID*

serverNames An array of the (short) hostnames of all of the *Cache Group's* “assignable” *Servers*

615: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: j/yH0gvJoaGjiLZU/
→0MA8o5He2004aJ5wh1eF9ex6F6IB01liM9Wk9RkWCw7sdiUHoy13/
→mf7gDntisZwzP7yw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 19:54:17 GMT
Content-Length: 183

{ "alerts": [
  {
    "text": "Delivery services successfully assigned to all the
→servers of cache group 8.",
    "level": "success"
  }
],
"response": {
  "id": 8,
  "serverNames": [
    "foo"
  ],
  "deliveryServices": [
    2
  ]
}}
```

cachegroups/{ID}/parameters

Deprecated since version ATCv6.

GET

Gets all of a *Cache Group's parameters*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 258: Request Query Parameters

Name	Re-quired	Description
pa-ram-e-terId	no	Show only the <i>Parameter</i> with the given <i>ID</i>
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
off-set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>nth</i> page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page .

Table 259: Request Path Parameters

Parameter	Description
ID	The <i>ID</i> of a <i>Cache Group</i>

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name of the Parameter*

secure A boolean value describing whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

616: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 19:56:23 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
↪GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: DfqPtySzVMpnBYqVt/45sSRG/
↪1pRTlQdIcYuQZ0CQt79QSHLzU5e4TbDqht6ntvNP041LimKsj5RzPlPX1n6tg==
Content-Length: 135

{ "response": [
  {
    "lastUpdated": "2018-11-14 18:22:43.754786+00",
    "value": "foobar",
    "secure": false,
    "name": "foo",
    "id": 124,
    "configFile": "bar"
  }
]}
```

cachegroups/{ID}/queue_update

POST

Queue or “dequeue” updates for all of a *Cache Group’s servers*, limited to a specific CDN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 260: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Cache Group</i> for which updates are being <i>Queued</i> /dequeued

action The action to perform; one of “queue” or “dequeue”

cdn The full name of the CDN in need of *Queue Updates*, or a “dequeue” thereof¹

cdnId The integral, unique identifier for the CDN in need of *Queue Updates*, or a “dequeue” thereof^{Page 887, 1}

617: Request Example

```
POST /api/3.0/cachegroups/8/queue_update HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 42
Content-Type: application/json

{"action": "queue", "cdn": "CDN-in-a-Box"}
```

Response Structure

action The action processed, one of “queue” or “dequeue”

cachegroupId An integer that is the *ID* of the *Cache Group* for which *Queue Updates* was performed or cleared

cachegroupName The name of the *Cache Group* for which updates were queued/dequeued

cdn The name of the CDN to which the queue/dequeue operation was restricted

¹ Either ‘cdn’ or ‘cdnID’ *must* be in the request data (but not both).

serverNames An array of the (short) hostnames of the *Cache Group's servers* which are also assigned to the CDN specified in the "cdn" field

618: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→UAcP7LrflU1RnfR4UqbQrJczlk5rkrcL0tTXJTFvIUxxK1Ek1ZkHkE4vewjDaVIhJJ6YQg8jmPGQpr+x1
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:19:46 GMT
Content-Length: 115

{ "response": {
  "cachegroupName": "test",
  "action": "queue",
  "serverNames": [
    "foo"
  ],
  "cdn": "CDN-in-a-Box",
  "cachegroupID": 8
}}
```

caches/stats

An API endpoint that returns cache statistics using the *Traffic Monitor APIs*.

See also:

This gives a set of basic statistics for *all cache servers* at the current time. For statistics from time ranges and/or aggregated over a specific CDN, use *cache_stats*.

GET

Retrieves cache stats from Traffic Monitor. Also includes rows for aggregates.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

Response Structure

cachegroup A string that is the *Name* of the *Cache Group* to which this *cache server* belongs

connections Current number of TCP connections maintained by the *cache server*

healthy true if Traffic Monitor has marked the *cache server* as “healthy”, false otherwise

See also:

Health Protocol

hostname The (short) hostname of the *cache server*

ip The IP address of the *cache server*

kbps The *cache server*’s upload speed (to clients) in Kilobits per second

profile The *Name* of the *Profile* in use by this *cache server*

status The status of the *cache server*

619: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 20:25:01 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
↪GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Vary: Accept-Encoding
Whole-Content-Sha512: DqbLgitanS8q81/
→qKC1i+ImMiEMF+SW4G9rb79FWdeWcgwFjL810t1TRp1nNNfHV+tajgjyK+wMHobqVyaNEfA==
Content-Length: 133

{ "response": [
  {
    "profile": "ALL",
    "connections": 0,
    "ip": null,
    "status": "ALL",
    "healthy": true,
    "kbps": 0,
    "hostname": "ALL",
    "cachegroup": "ALL"
  }
]}
```

capabilities

GET

Get all capabilities.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 261: Request Query Parameters

Name	Re-quired	Description
name	no	Return only the capability that has this name
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

620: Request Example

```
GET /api/3.0/capabilities?name=test HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

name Name of the capability

description Describes the permissions covered by the capability.

lastUpdated Date and time of the last update made to this capability, in *Traffic Ops’s Custom Date/Time Format*

621: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Vary: Accept-Encoding
Transfer-Encoding: chunked
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: c18+GtX2ZI8PoCSwuAzBhl+6w3vDpKQTa/
→cDJC0WHxdpguOL378KBxGWW5PCSyZfJUub7wPyOL5qKMn6NNTufhg==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Aug 2019 17:20:20 GMT
Content-Length: 161

{ "response": [
  {
    "description": "This is only a test. If this were a real_
→capability, it might do something",
    "lastUpdated": "2019-08-15 17:18:03+00",
    "name": "test"
  }
]}
```

cdns

Extract information about all CDNs

GET

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 262: Request Query Parameters

Parameter	Required	Description
domainName	no	Return only the CDN that has this domain name
dnssecEnabled	no	Return only the CDNs that are either dnssec enabled or not
id	no	Return only the CDN that has this id
name	no	Return only the CDN that has this name
orderBy	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

dnssecEnabled true if DNSSEC is enabled on this CDN, otherwise false

domainName Top Level Domain name within which this CDN operates

id The integral, unique identifier for the CDN

lastUpdated Date and time when the CDN was last modified in *Traffic Ops’s Custom Date/Time Format*

name The name of the CDN

622: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→z9P1NkxGebPncUhaChDHtYKYI+XVZfhE6Y84TuwoASZFIMfISELwADLpvpPTN+wwnzBfREksLYn+0313Q
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:46:57 GMT
Content-Length: 237

{ "response": [
  {
    "dnssecEnabled": false,
    "domainName": "-",
    "id": 1,
    "lastUpdated": "2018-11-14 18:21:06+00",
    "name": "ALL"
  },
  {
    "dnssecEnabled": false,
    "domainName": "mycdn.ciab.test",
    "id": 2,
    "lastUpdated": "2018-11-14 18:21:14+00",
    "name": "CDN-in-a-Box"
  }
]}
```

POST

Allows user to create a CDN

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

dnssecEnabled If true, this CDN will use DNSSEC, if false it will not

domainName The top-level domain (TLD) belonging to the new CDN

name Name of the new CDN

623: Request Structure

```
POST /api/3.0/cdns HTTP/1.1
Host: trafficops.infra.ciab.test
```

(continues on next page)

(continued from previous page)

```
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 63
Content-Type: application/json

{"name": "test", "domainName": "quest", "dnssecEnabled": false}
```

Response Structure

dnssecEnabled true if the CDN uses DNSSEC, false otherwise

domainName The top-level domain (TLD) assigned to the newly created CDN

id An integral, unique identifier for the newly created CDN

name The newly created CDN's name

624: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳1rZRl0fQioGRrEb4nCfjGGx7y3Ub2h7BZ4z6NbhcY4acPslKSUNM8QLjWTVwLU4WpkfJNxc0yy8NlKULF
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:49:28 GMT
Content-Length: 174

{ "alerts": [
  {
    "text": "cdn was created.",
    "level": "success"
  }
],
"response": {
  "dnssecEnabled": false,
  "domainName": "quest",
  "id": 3,
  "lastUpdated": "2018-11-14 20:49:28+00",
```

(continues on next page)

(continued from previous page)

```
"name": "test"
}}
```

cdns/capacity

GET

Retrieves the aggregate capacity percentages of all *Cache Groups* for a given CDN.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

availablePercent The percent of available (unused) bandwidth to 64 bits of precision¹

unavailablePercent The percent of unavailable (used) bandwidth to 64 bits of precision¹

utilizedPercent The percent of bandwidth currently in use to 64 bits of precision¹

maintenancePercent The percent of bandwidth being used for administrative or analytical processes internal to the CDN to 64 bits of precision¹

625: Response Example

```
{ "response": {
  "availablePercent": 89.0939840205533,
  "unavailablePercent": 0,
  "utilizedPercent": 10.9060020300395,
  "maintenancePercent": 0.0000139494071146245
}}
```

¹ Following IEEE 754

cdns/dnsseckey/generate

POST

Generates ZSK and KSK keypairs for a CDN and all associated *Delivery Services*.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

effectiveDate An optional string containing the date and time at which the newly-generated ZSK and KSK become effective, in **RFC 3339** format. Defaults to the current time if not specified.

key Name of the CDN

kskExpirationDays Expiration (in days) for the KSKs

ttl Time, in seconds, for which the keypairs shall remain valid

zskExpirationDays Expiration (in days) for the ZSKs

626: Request Example

```
POST /api/3.0/cdns/dnsseckey/generate HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 130

{
  "key": "CDN-in-a-Box",
  "kskExpirationDays": 1095,
  "ttl": 3600,
  "zskExpirationDays": 1095
}
```

Response Structure

627: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 19:42:15
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 09SPWzeMNFgg6I/PPeXittBIhdh3/
  ↳zUKK1NwNlYIM9SszSrK0h/Dfz7tnwgnA7h/s6M4eYBJxykDpCfVC7xpeg==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 18:42:15 GMT
Content-Length: 89

{
  "response": "Successfully created dnssec keys for CDN-in-a-Box"
}
```

cdns/dnsseckey/refresh

GET

Refresh the DNSSEC keys for all CDNs. This call initiates a background process to refresh outdated keys, and immediately returns a response that the process has started.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

No parameters available

Response Structure

628: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 21:37:30 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳Uw1+924m6Ye3NraFP+RBp1dkhcNTTDyXHZbzRaYV95p9tP56Z61gcckeKSr1oQIkNXjXcCsDN5Dmum7Zk1
Content-Length: 69

{
  "response": "Checking DNSSEC keys for refresh in the background"
}
```

cdns/domains

GET

Gets a list of domains and their related Traffic Router *Profiles* for all CDNs.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

Response Structure

domainName The TLD assigned to this CDN

parameterId The *ID* for the *Parameter* that sets this TLD on the Traffic Router

profileDescription A short, human-readable description of the Traffic Router's profile

profileId The *ID* of the *Profile* assigned to the Traffic Router responsible for serving domainName

profileName The *Name* of the *Profile* assigned to the Traffic Router responsible for serving domainName

629: Response Example

```
{ "response": [
  {
    "profileId": 12,
    "parameterId": -1,
    "profileName": "CCR_CIAB",
    "profileDescription": "Traffic Router for CDN-In-A-Box",
    "domainName": "mycdn.ciab.test"
  }
]}
```

cdns/health

Extract health information from all *Cache Groups* across all CDNs

See also:

Health Protocol

GET

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available

Response Structure

cachegroups An array of objects describing the health of each Cache Group

name The name of the Cache Group

offline The number of OFFLINE caches in the Cache Group

online The number of ONLINE caches in the Cache Group

totalOffline Total number of OFFLINE caches across all Cache Groups which are assigned to any CDN

totalOnline Total number of ONLINE caches across all Cache Groups which are assigned to any CDN

630: Response Example

```
{ "response": {
  "totalOffline": 0,
  "totalOnline": 1,
  "cachegroups": [
    {
      "offline": 0,
      "name": "CDN_in_a_Box_Edge",
      "online": 1
    }
  ]
}}
```

`cdns/{ID}`

PUT

Allows a user to edit a specific CDN

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 263: Request Path Parameters

Name	Description
ID	Integral, unique identifier for the CDN to update

dnssecEnabled If `true`, this CDN will use DNSSEC, if `false` it will not

domainName The top-level domain (TLD) belonging to the CDN

name Name of the new CDN

631: Request Example

```
PUT /api/3.0/cdns/3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 63
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
```

```
{"name": "quest", "domainName": "test", "dnssecEnabled": false}
```

Response Structure

dnssecEnabled true if the CDN uses DNSSEC, false otherwise

domainName The top-level domain (TLD) assigned to the newly created CDN

id An integral, unique identifier for the newly created CDN

name The newly created CDN's name

632: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: sI1hzBwG+/
    ↳VAzoFY20kqGFA2RgrU0ThtMeeJqk0ZxH3TRxTWuA8BetACct/
    ↳XICC3n7hPDLlRVpwckEyBdyJkXg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:54:33 GMT
Content-Length: 174

{ "alerts": [
  {
    "text": "cdn was updated.",
    "level": "success"
  }
],
"response": {
  "dnssecEnabled": false,
  "domainName": "test",
  "id": 4,
  "lastUpdated": "2018-11-14 20:54:33+00",
  "name": "quest"
}}
```

DELETE

Allows a user to delete a specific CDN

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 264: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the CDN to delete

Response Structure

633: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Zy4cJN6BEct4ltFLN4e296mM8XnzOs0EQ3/
    ↳jp4TA3L+g8qtkI0WrL+ThcFq4xbJPU+KHVDSi+b0JBav3xsYPqQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:51:23 GMT
Content-Length: 58

{ "alerts": [
  {
    "text": "cdn was deleted.",
    "level": "success"
  }
]}
    
```


cdns/{ID}/queue_update

POST

Queue or “dequeue” updates for all servers assigned to a specific CDN.

- Auth. Required** Yes
- Roles Required** “admin” or “operations”
- Response Type** Object

Request Structure

Table 265: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the CDN on which to (de)queue updates

action One of “queue” or “dequeue” as appropriate

634: Request Example

```
POST /api/3.0/cdns/2/queue_update HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 19
Content-Type: application/json

{"action": "queue"}
```

Response Structure

- action** The action processed, either "queue" or "dequeue"
- cdnId** The integral, unique identifier for the CDN on which *Queue Updates* was performed or cleared

635: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→rBpFfrrP+9IFkwsRloEM+v+I8MuBZDXqFu+WUTGtRGypnAn2gHooPoNQRYVvJGjyIQrLXLvqjEtve+lH2
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:02:07 GMT
Content-Length: 41

{ "response": {
  "action": "queue",
  "cdnId": 2
}}
```

`cdns/{{name}}/configs/monitoring`

See also:

Health Protocol

GET

Retrieves information concerning the monitoring configuration for a specific CDN.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 266: Request Path Parameters

Name	Description
name	The name of the CDN for which monitoring configuration will be fetched

Response Structure

cacheGroups An array of objects representing each of the *Cache Groups* being monitored within this CDN

coordinates An object representing the geographic location of this *Cache Group*

latitude This *Cache Group's latitude* as a floating-point number

longitude This *Cache Group's longitude* as a floating-point number

name A string that is this *Cache Group's name*

config A collection of parameters used to configure the monitoring behaviour of Traffic Monitor

health.polling.interval An interval in milliseconds on which to poll for health statistics

tm.polling.interval The interval at which to poll for configuration updates

deliveryServices An array of objects representing each *Delivery Service* provided by this CDN

status The *Delivery Service's* status

totalKbpsThreshold A threshold rate of data transfer this *Delivery Service* is configured to handle, in Kilobits per second

totalTpsThreshold A threshold amount of transactions per second that this *Delivery Service* is configured to handle

xmlId A string that is the *Delivery Service's XMLID*

profiles An array of the *Profiles* in use by the *cache servers* and *Delivery Services* belonging to this CDN

name A string that is the *Profile's Name*

parameters An array of the *Parameters* in this *Profile* that relate to monitoring configuration. This can be null if the servers using this *Profile* cannot be monitored (e.g. Traffic Routers)

health.connection.timeout A timeout value, in milliseconds, to wait before giving up on a health check request

health.polling.url A URL to request for polling health. Substitutions can be made in a shell-like syntax using

the properties of an object from the "trafficServers" array

health.threshold.availableBandwidthInKbps

The total amount of bandwidth that servers using this profile are allowed - across all network interfaces - in Kilobits per second. This is a string and using comparison operators to specify ranges, e.g. ">10" means "more than 10 kbps"

health.threshold.loadavg The UNIX load-avg at which the server should be marked "unhealthy"

See also:

uptime(1)

health.threshold.queryTime The highest allowed length of time for completing health queries (after connection has been established) in milliseconds

history.count The number of past events to store; once this number is reached, the oldest event will be forgotten before a new one can be added

type A string that names the *Profile's Type*

trafficMonitors An array of objects representing each Traffic Monitor that monitors this CDN (this is used by Traffic Monitor's "peer polling" function)

fqdn An FQDN that resolves to the IPv4 (and/or IPv6) address of the server running this Traffic Monitor instance

hostname The hostname of the server running this Traffic Monitor instance

ip6 The IPv6 address of this Traffic Monitor - when applicable

ip The IPv4 address of this Traffic Monitor

port The port on which this Traffic Monitor listens for incoming connections

profile A string that is the *Name* of the *Profile* assigned to this Traffic Monitor

status The status of the server running this Traffic Monitor instance

trafficServers An array of objects that represent the *cache servers* being monitored within this CDN

- cacheGroup** The *Cache Group* to which this *cache server* belongs
- fqdn** An FQDN that resolves to the *cache server*'s IPv4 (or IPv6) address
- hashId** The (short) hostname for the *cache server* - named "hashId" for legacy reasons
- hostName** The (short) hostname of the *cache server*
- port** The port on which the *cache server* listens for incoming connections
- profile** A string that is the *Name* of the *Profile* assigned to this *cache server*
- status** The status of the *cache server*
- type** A string that names the *Type* of the *cache server* - should (ideally) be either EDGE or MID
- interfaces** A set of the network interfaces in use by the server. In most scenarios, only one will be present, but it is illegal for this set to be an empty collection.
- ipAddresses** A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be present, but it is illegal for this set to be an empty collection.
- address** The actual IP address, including any mask as a CIDR-notation suffix
- gateway** Either the IP address of the network gateway for this address, or null to signify that no such gateway exists
- serviceAddress** A boolean that describes whether or not the server's main service is available at this IP address. When this property is true, the IP address is referred to as a "service address". It is illegal

for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the “service interface” for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning “no limit”. It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface’s device name on the server, e.g. `eth0`.

636: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳uLR+tRoqR8SY038j3DV9wQ+IkJ7Kf+MCoFkcWZtsgbpLJ+0S6f+IiI8laNVeDgrM/
    ↳P23MAQ6BSepm+EJRL1AXQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:09:31 GMT
Transfer-Encoding: chunked

{ "response": {
  "trafficServers": [
    {
      "profile": "ATS_EDGE_TIER_CACHE",
      "status": "REPORTED",
      "port": 80,
      "intefaces": [
        {
          "ipAddresses": [
            {
              "address": "172.16.239.100",
              "gateway": "172.16.239.0/24",
              "serviceAddress": "true"
            },
            {
              "address": "fc01:9400:1000:8::100",
              "gateway": "fc01::",
              "serviceAddress": "true"
            }
          ],
          "name": "eth0",
          "monitor": "true",
          "mtu": 9000,
          "maxBandwidth": 150
        }
      ],
      "cachegroup": "CDN_in_a_Box_Edge",
      "hostname": "edge",
    }
  ]
}

```

(continues on next page)

(continued from previous page)

```

        "fqdn": "edge.infra.ciab.test",
        "type": "EDGE",
        "hashid": "edge"
    },
    {
        "profile": "ATS_MID_TIER_CACHE",
        "status": "REPORTED",
        "port": 80,
        "intefaces": [
            {
                "ipAddresses": [
                    {
                        "address": "172.16.239.120",
                        "gateway": "172.16.239.0/24",
                        "serviceAddress": "true"
                    },
                    {
                        "address": "fc02:9400:1000:8::100",
                        "gateway": "fc02::",
                        "serviceAddress": "true"
                    }
                ],
                "name": "eth0",
                "monitor": "true",
                "mtu": 9000,
                "maxBandwidth": 150
            }
        ],
        "cachegroup": "CDN_in_a_Box_Mid",
        "hostname": "mid",
        "fqdn": "mid.infra.ciab.test",
        "type": "MID",
        "hashid": "mid"
    }
],
"trafficMonitors": [
    {
        "profile": "RASCAL-Traffic_Monitor",
        "status": "ONLINE",
        "ip": "172.16.239.40",
        "ip6": "fc01:9400:1000:8::40",
        "port": 80,
        "cachegroup": "CDN_in_a_Box_Edge",
        "hostname": "trafficmonitor",
        "fqdn": "trafficmonitor.infra.ciab.test"
    }
]

```

(continues on next page)

(continued from previous page)

```

],
"cacheGroups": [
  {
    "name": "CDN_in_a_Box_Mid",
    "coordinates": {
      "latitude": 38.897663,
      "longitude": -77.036574
    }
  },
  {
    "name": "CDN_in_a_Box_Edge",
    "coordinates": {
      "latitude": 38.897663,
      "longitude": -77.036574
    }
  }
],
"profiles": [
  {
    "name": "CCR_CIAB",
    "type": "CCR",
    "parameters": null
  },
  {
    "name": "ATS_EDGE_TIER_CACHE",
    "type": "EDGE",
    "parameters": {
      "health.connection.timeout": 2000,
      "health.polling.url": "http://${hostname}/_astats?
→application=&inf.name=${interface_name}",
      "health.threshold.availableBandwidthInKbps": ">1750000
→",
      "health.threshold.loadavg": "25.0",
      "health.threshold.queryTime": 1000,
      "history.count": 30
    }
  },
  {
    "name": "ATS_MID_TIER_CACHE",
    "type": "MID",
    "parameters": {
      "health.connection.timeout": 2000,
      "health.polling.url": "http://${hostname}/_astats?
→application=&inf.name=${interface_name}",
      "health.threshold.availableBandwidthInKbps": ">1750000
→",

```

(continues on next page)

(continued from previous page)

```

        "health.threshold.loadavg": "25.0",
        "health.threshold.queryTime": 1000,
        "history.count": 30
    }
}
],
"deliveryServices": [],
"config": {
    "health.polling.interval": 6000,
    "heartbeat.polling.interval": 3000,
    "peers.polling.interval": 3000,
    "tm.polling.interval": 2000
}
}
}

```

`cdns/{{name}}/dnsseckey/ksk/generate`

POST

Generates a new KSK for a specific CDN.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

Table 267: Request Path Parameters

Name	Required	Description
name	yes	The name of the CDN for which the KSK will be generated

expirationDays The integral number of days until the newly generated KSK expires

effectiveDate An optional string containing the date and time at which the newly generated KSK becomes effective, in [RFC 3339](#) format. Defaults to the current time if not specified

Response Structure

637: Response Example

```
{ "response": "Successfully generated ksk dnssec keys for my-cdn-name" }
```

`cdns/{name}/federations`

GET

Retrieves a list of federations in use by a specific CDN.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 268: Request Path Parameters

Name	Description
name	The name of the CDN for which federations will be listed

Table 269: Request Query Parameters

Name	Description
id	Return only the federation that has this id
orderby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

638: Request Example

```
GET /api/3.0/cdns/CDN-in-a-Box/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cname** The Canonical Name (CNAME) used by the federation
 - deliveryService** An object with keys that provide identifying information for the *Delivery Service* using this federation
 - id** The integral, unique identifier for the *Delivery Service*
 - xmlId** The *Delivery Service*'s uniquely identifying 'xml_id'
 - description** An optionally-present field containing a description of the field
-
- Note:** This key will only be present if the description was provided when the federation was created. Refer to the POST method of this endpoint to see how federations can be created.
-
- lastUpdated** The date and time at which this federation was last modified, in *Traffic Ops's Custom Date/Time Format*
 - ttl** Time to Live (TTL) for the cname, in hours

639: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
→SJA7G+7G5KcOfCtnE3Dq5DCobWtGRUKSppiDkflZoG5+paq4E1aZGqUb6vGVsd+TpPg75MLlhyqfdfCHnl
→g==
x-server-name: traffic_ops_golang/
content-length: 170
date: Wed, 05 Dec 2018 00:35:40 GMT

{ "response": [
  {
    "id": 1,
    "cname": "test.quest.",
    "ttl": 48,
```

(continues on next page)

(continued from previous page)

```

    "description": "A test federation",
    "lastUpdated": "2018-12-05 00:05:16+00",
    "deliveryService": {
      "id": 1,
      "xmlId": "demo1"
    }
  }
}

```

POST

Creates a new federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 270: Request Path Parameters

Name	Description
name	The name of the CDN for which a new federation will be created

cname The Canonical Name (CNAME) used by the federation

Note: The CNAME must end with a “.”

description An optional description of the federation

ttl Time to Live (TTL) for the name record used for **cname**

640: Request Example

```

POST /api/3.0/cdns/CDN-in-a-Box/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 72
Content-Type: application/json

{

```

(continues on next page)

(continued from previous page)

```

"cname": "test.quest.",
"ttl": 48,
"description": "A test federation"
}

```

Response Structure

cname The Canonical Name (CNAME) used by the federation

description An optionally-present field containing a description of the field

Note: This key will only be present if the description was provided when the federation was created

lastUpdated The date and time at which this federation was last modified, in *Traffic Ops's Custom Date/Time Format*

ttl Time to Live (TTL) for the cname, in hours

641: Response Example

```

HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
→rRsWAIhXzVlj8Hy+8aFjp4Jo1QGTK49m0N1AP5QDyyAZ1TfNIIdgtcgiuehu7FiN1IPWRFiv6D9CygFYKG
x-server-name: traffic_ops_golang/
content-length: 192
date: Wed, 05 Dec 2018 00:05:16 GMT

{ "alerts": [
  {
    "text": "cdnfederation was created.",
    "level": "success"
  }
],
"response": {
  "id": 1,
  "cname": "test.quest.",
  "ttl": 48,

```

(continues on next page)

(continued from previous page)

```
"description": "A test federation",
"lastUpdated": "2018-12-05 00:05:16+00"
}}
```

`cdns/{{name}}/federations/{{ID}}`

PUT

Updates a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 271: Request Path Parameters

Name	Description
name	The name of the CDN for which the federation identified by ID will be inspected
ID	An integral, unique identifier for the federation to be inspected

cname The Canonical Name (CNAME) used by the federation

Note: The CNAME must end with a “.”

description An optional description of the federation

ttl Time to Live (TTL) for the name record used for **cname**

642: Request Example

```
PUT /api/3.0/cdns/CDN-in-a-Box/federations/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 33
Content-Type: application/json

{
  "cname": "foo.bar.",
  "ttl": 48
}
```

Response Structure

cname The Canonical Name (CNAME) used by the federation

description An optionally-present field containing a description of the field

Note: This key will only be present if the description was provided when the federation was created

lastUpdated The date and time at which this federation was last modified, in *Traffic Ops's Custom Date/Time Format*

ttl Time to Live (TTL) for the cname, in hours

643: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
    ↳qcfjQ+gDjNxYQ1aq+dlddgrkFWnkFYxsFF+SHDqqH0uVHBVksmU0aTFgltozek/
    ↳u6wbrGoR1LFf9Fr1C1SbigA==
x-server-name: traffic_ops_golang/
content-length: 174
date: Wed, 05 Dec 2018 01:03:40 GMT

{ "alerts": [
  {
    "text": "cdnfederation was updated.",
    "level": "success"
  }
],
"response": {
  "id": 1,
  "cname": "foo.bar.",
  "ttl": 48,
  "description": null,
  "lastUpdated": "2018-12-05 01:03:40+00"
}}
```


DELETE

Deletes a specific federation.

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 272: Request Path Parameters

Name	Description
name	The name of the CDN for which the federation identified by ID will be inspected
ID	An integral, unique identifier for the federation to be inspected

644: Request Example

```
DELETE /api/3.0/cdns/CDN-in-a-Box/federations/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

645: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512: Cnkfj6dmzTD3if9oiDq33tqf7CnAflKK/
→SPgqJyfu6HUf0jLJ0gKIZvkcs2wWY6EjLVdw5qsatsd4FPoCyjvcw==
x-server-name: traffic_ops_golang/
content-length: 68
date: Wed, 05 Dec 2018 01:17:24 GMT

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

    "text": "cdnfederation was deleted.",
    "level": "success"
  }
}]

```

`cdns/{{name}}/health`

GET

Retrieves the health of all *Cache Groups* for a given CDN.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 273: Request Path Parameters

Name	Description
name	The name of the CDN for which health will be reported

646: Request Example

```

GET /api/3.0/cdns/CDN-in-a-Box/health HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...

```

Response Structure

cachegroups An array of objects describing the health of each *Cache Group*

name A string that is the *Cache Group's Name*

offline The number of OFFLINE *cache servers* in the *Cache Group*

online The number of ONLINE *cache servers* in the *Cache Group*

totalOffline Total number of OFFLINE *cache servers* across all *Cache Groups* which are assigned to the CDN defined by the name request path parameter

totalOnline Total number of ONLINE *cache servers* across all *Cache Groups* which are assigned to the CDN defined by the name request path parameter

647: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Encoding: gzip
Content-Length: 108
Content-Type: application/json
Date: Tue, 03 Dec 2019 21:33:59 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; expires=Wed, 04 Dec 2019 01:33:59 GMT;
    ↳path=/; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳KpXViXeAgch58ueQqdyU8NuINBw1EUedE6Rv2ewcLUajJp6kowdbVynpwW7XiSvAyHdtClIOuT30khImg

{ "response": {
  "totalOffline": 0,
  "totalOnline": 1,
  "cachegroups": [
    {
      "offline": 0,
      "name": "CDN_in_a_Box_Edge",
      "online": 1
    }
  ]
}}
```

`cdns/name/{name}}`

DELETE

Allows a user to delete a CDN by name

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 274: Request Path Parameters

Name	Description
name	The name of the CDN to be deleted

Response Structure

648: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Zy4cJN6BEct4ltFLN4e296mM8XnzOs0EQ3/
→jp4TA3L+g8qtkI0WrL+ThcFq4xbJPU+KHVDSi+b0JBav3xsYPqQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:59:22 GMT
Content-Length: 58

{ "alerts": [
  {
    "text": "cdn was deleted.",
    "level": "success"
  }
]}
```

cdns/name/{name}}/dnsseckey

GET

Gets a list of DNSSEC keys for CDN and all associated *Delivery Services*. Before returning response to user, this will make sure DNSSEC keys for all *Delivery Services* exist and are not expired. If they don't exist or are expired, they will be (re-)generated.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 275: Request Path Parameters

Name	Description
name	The name of the CDN for which keys will be fetched

Response Structure

name The name of the CDN or *Delivery Service* to which the enclosed keys belong

zsk The short-term ZSK

expirationDate A Unix epoch timestamp (in seconds) representing the date and time whereupon the key will expire

inceptionDate A Unix epoch timestamp (in seconds) representing the date and time when the key was created

name The name of the domain for which this key will be used

private Encoded private key

public Encoded public key

ttl The time for which the key should be trusted by the client

ksk The long-term KSK

dsRecord An optionally present object containing information about the algorithm used to generate the key

algorithm The name of the algorithm used to generate the key

digest A hash of the DNSKEY record

digestType The type of hash algorithm used to create the value of digest

expirationDate A Unix epoch timestamp (in seconds) representing the date and time whereupon the key will expire

inceptionDate A Unix epoch timestamp (in seconds) representing the date and time when the key was created

name The name of the domain for which this key will be used

private Encoded private key

public Encoded public key

ttl The time for which the key should be trusted by the client

649: Response Example

```
{ "response": {
  "cdn1": {
    "zsk": {
      "ttl": "60",
      "inceptionDate": "1426196750",
      "private": "zsk private key",
      "public": "zsk public key",
      "expirationDate": "1428788750",
      "name": "foo.kabletown.com."
    },
    "ksk": {
      "name": "foo.kabletown.com.",
      "expirationDate": "1457732750",
      "public": "ksk public key",
      "private": "ksk private key",
      "inceptionDate": "1426196750",
      "ttl": "60",
      "dsRecord": {
        "algorithm": "5",
        "digestType": "2",
        "digest": "abc123def456"
      }
    }
  },
  "ds-01": {
    "zsk": {
      "ttl": "60",
      "inceptionDate": "1426196750",
      "private": "zsk private key",
      "public": "zsk public key",
```

(continues on next page)

(continued from previous page)

```

        "expirationDate": "1428788750",
        "name": "ds-01.foo.kabletown.com."
    },
    "ksk": {
        "name": "ds-01.foo.kabletown.com.",
        "expirationDate": "1457732750",
        "public": "ksk public key",
        "private": "ksk private key",
        "inceptionDate": "1426196750"
    }
}
}}
```

DELETE

Delete DNSSEC keys for a CDN and all associated *Delivery Services*.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

Table 276: Request Path Parameters

Name	Description
name	The name of the CDN for which DNSSEC keys will be deleted

Response Structure

650: Response Example

```
{
  "response": "Successfully deleted dnssec keys for test"
}
```

`cdns/name/{{name}}/sslkeys`

GET

Returns SSL certificates for all *Delivery Services* that are a part of the CDN.

Auth. Required Yes

Roles Required “admin”

Response Type Array

Request Structure

Table 277: Request Path Parameters

Name	Description
name	The name of the CDN for which keys will be fetched

Response Structure

certificate An object representing The SSL keys used for the *Delivery Service* identified by `deliveryservice`

key Base 64-encoded private key for SSL certificate

crt Base 64-encoded SSL certificate

deliveryservice A string that is the *xml_id* of the *Delivery Service* using the SSL key within `certificate`

651: Response Example

```
{ "response": [
  {
    "deliveryservice": "ds1",
    "certificate": {
      "crt": "base64encodedcrt1",
      "key": "base64encodedkey1"
    }
  },
]
```

(continues on next page)

(continued from previous page)

```
{
  "deliveryservice": "ds2",
  "certificate": {
    "crt": "base64encodedcrt2",
    "key": "base64encodedkey2"
  }
}
```

`cdns/{{name}}/snapshot`

Caution: This page is a stub! Much of it may be missing or just downright wrong - it needs a lot of love from people with the domain knowledge required to update it.

GET

Retrieves the *current Snapshot* for a CDN, which represents the current *operating state* of the CDN, **not** the current *configuration* of the CDN. The contents of this *Snapshot* are currently used by Traffic Monitor and Traffic Router.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 278: Request Path Parameters

Name	Description
name	The name of the CDN for which a <i>Snapshot</i> shall be returned

652: Request Example

```
GET /api/3.0/cdns/CDN-in-a-Box/snapshot HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

config An object containing basic configurations on the actual CDN object

api.cache-control.max-age A string containing an integer which specifies the value of `max-age` in the `Cache-Control` header of some HTTP responses, likely the *Traffic Router API* responses

certificates.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for updated SSL certificates

consistent.dns.routing A string containing a boolean which indicates whether DNS routing will use a consistent hashing method or “round-robin”

“false” The “round-robin” method will be used to define DNS routing

“true” A consistent hashing method will be used to define DNS routing

coveragezone.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should check for a new Coverage Zone file

coveragezone.polling.url The URL where a *Coverage Zone File* may be requested by Traffic Routers

dnssec.dynamic.response.expiration A string containing a number and unit suffix that specifies the length of time for which dynamic responses to DNSSEC lookup queries should remain valid

dnssec.dynamic.concurrencylevel An integer that defines the size of the concurrency level (threads) of the Guava cache used by ZoneManager to store zone material

dnssec.dynamic.initialcapacity An integer that defines the initial size of the Guava cache, default is 10000. Too low of a value can lead to expensive resizing

dnssec.init.timeout An integer that defines the number of minutes to allow for zone generation, this bounds the zone priming activity

dnssec.enabled A string that tells whether or not the CDN uses DNSSEC; one of:

“false” DNSSEC is not used within this CDN

“true” DNSSEC is used within this CDN

- domain_name** A string that is the TLD served by the CDN
- federationmapping.polling.interval** A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new federation mappings
- federationmapping.polling.url** The URL where Traffic Control components can request federation mappings
- geolocation.polling.interval** A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new IP-to-geographic-location mapping databases
- geolocation.polling.url** The URL where Traffic Control components can request IP-to-geographic-location mapping database files
- keystore.maintenance.interval** A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should refresh their zone caches
- neustar.polling.interval** A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new “Neustar” databases
- neustar.polling.url** The URL where Traffic Control components can request “Neustar” databases
- soa** An object defining the SOA for the CDN’s TLD (defined in `domain_name`)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which

secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: [RFC 1035](#) dictates that this should always be less than `refresh`.

See also:

[The Wikipedia page on Start of Authority records.](#)

steeringmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Control components should check for new steering mappings

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

zonemanager.cache.maintenance.interval A configuration option for the ZoneManager Java class of Traffic Router

zonemanager.threadpool.scale A configuration option for the ZoneManager Java class of Traffic Router

contentRouters An object containing keys which are the (short) hostnames of the Traffic Routers that serve requests for *Delivery Services* in this CDN

api.port A string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTP

secure.api.port An optionally present string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTPS

fqdn This Traffic Router's FQDN

httpsPort The port number on which this Traffic Router listens for incoming HTTPS requests

ip This Traffic Router's IPv4 address

ip6 This Traffic Router's IPv6 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Router belongs

port The port number on which this Traffic Router listens for incoming HTTP requests

profile The *Name* of the *Profile* used by this Traffic Router

status The health status of this Traffic Router

See also:

Health Protocol

contentServers An object containing keys which are the (short) hostnames of the *Edge-tier cache servers* in the CDN; the values corresponding to those keys are routing information for said servers

cacheGroup A string that is the *Name* of the *Cache Group* to which the server belongs

capabilities An array of this *Cache Server's Server Capabilities*. If the Cache Server has no Server Capabilities, this field is omitted.

deliveryServices An object containing keys which are the names of *Delivery Services* to which this *cache server* is assigned; the values corresponding to those keys are arrays of FQDNs that resolve to this *cache server*

Note: Only *Edge-tier cache servers* can be assigned to a *Delivery Service*, and therefore this field will only be present when **type** is "EDGE".

fqdn The server's FQDN

hashCount The number of servers to be placed into a single "hash ring" in Traffic Router

hashId A unique string to be used as the key for hashing servers - as of version 3.0.0 of Traffic Control, this is always the same as the server's (short) hostname and only still exists for legacy compatibility reasons

httpsPort The port on which the *cache server* listens for incoming HTTPS requests

interfaceName The name of the main network interface device used by this *cache server*

ip6 The server's IPv6 address

ip The server's IPv4 address

locationId This field is exactly the same as **cacheGroup** and only exists for legacy compatibility reasons

port The port on which this *cache server* listens for incoming HTTP requests

profile The *Name* of the *Profile* used by the *cache server*

routingDisabled An integer representing the boolean concept of whether or not Traffic Routers should route client traffic to this *cache server*; one of:

0 Do not route traffic to this server

1 Route traffic to this server normally

status This *cache server*'s status

See also:

Health Protocol

type The *Type* of this *cache server*; which ought to be one of (but in practice need not be in certain special circumstances):

EDGE This is an *Edge-tier cache server*

MID This is a *Mid-tier cache server*

deliveryServices An object containing keys which are the *xml_ids* of all of the *Delivery Services* within the CDN

anonymousBlockingEnabled A string containing a boolean that tells whether or not *Anonymous Blocking* is set on this *Delivery Service*; one of:

“true” Anonymized IP addresses are blocked by this *Delivery Service*

“false” Anonymized IP addresses are not blocked by this *Delivery Service*

See also:

Configure Anonymous Blocking

consistentHashQueryParameters A set of query parameters that Traffic Router should consider when determining a consistent hash for a given client request.

consistentHashRegex An optional regular expression that will ensure clients are consistently routed to a *cache server* based on matches to it.

coverageZoneOnly A string containing a boolean that tells whether or not this *Delivery Service* routes traffic based only on its *Coverage Zone File*

See also:

Geo Limit

deepCachingType A string that defines the *Deep Caching* setting of this *Delivery Service*

dispersion An object describing the “dispersion” - or number of *cache servers* within a single *Cache Group* across which the same content is spread - within the *Delivery Service*

limit The maximum number of *cache servers* in which the response to a single request URL will be stored

Note: If this is greater than the number of *cache servers* in the *Cache Group* chosen to service the request, then content will be spread across all of them. That is, it causes no problems.

shuffled A string containing a boolean that tells whether the *cache servers* chosen for content dispersion are chosen randomly or based on a consistent hash of the request URL; one of:

“false” *cache servers* will be chosen consistently

“true” *cache servers* will be chosen at random

domains An array of domains served by this *Delivery Service*

ecsEnabled A string containing a boolean from *EDNS0 Client Subnet Enabled* that tells whether EDNS0 client subnet is enabled on this *Delivery Service*; one of:

“false” EDNS0 client subnet is not enabled on this *Delivery Service*

“true” EDNS0 client subnet is enabled on this *Delivery Service*

geolocationProvider The name of a provider for IP-to-geographic-location mapping services - currently the only valid value is "maxmindGeolocationService"

ip6RoutingEnabled A string containing a boolean that defines the *IPv6 Routing Enabled* setting for this *Delivery Service*; one of:

“false” IPv6 traffic will not be routed by this *Delivery Service*

“true” IPv6 traffic will be routed by this *Delivery Service*

matchList An array of methods used by Traffic Router to determine whether or not a request can be serviced by this *Delivery Service*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

setNumber An integral, unique identifier for the set of types to which the **type** field belongs

type The name of the *Type* of match performed using **pattern** to determine whether or not to use this *Delivery Service*

HOST_REGEX Use the *Delivery Service* if **pattern** matches the *Host* HTTP header of an HTTP request, or the name requested for resolution in a DNS request

HEADER_REGEX Use the *Delivery Service* if **pattern** matches an HTTP header (both the name and value) in an HTTP request¹

PATH_REGEX Use the *Delivery Service* if **pattern** matches the request path of this *Delivery Service*'s URL Page 960, 1

STEERING_REGEX Use the *Delivery Service* if **pattern** matches the *xml_id* of one of this *Delivery Service*'s “Steering” target *Delivery Services*

missLocation An object representing the default geographic coordinates to use for a client when lookup of their IP has failed in both the *Coverage Zone File* (and/or possibly the *Deep Coverage Zone File*) and the IP-to-geographic-location database

lat Geographic latitude as a floating point number

¹ These only apply to HTTP-routed *Delivery Services*

long Geographic longitude as a floating point number

protocol An object that describes how the *Delivery Service* ought to handle HTTP requests both with and without TLS encryption

acceptHttps A string containing a boolean that tells whether HTTPS requests should be normally serviced by this *Delivery Service*; one of:

“false” Refuse to service HTTPS requests

“true” Service HTTPS requests normally

redirectToHttps A string containing a boolean that tells whether HTTP requests ought to be re-directed to use HTTPS; one of:

“false” Do not redirect unencrypted traffic; service it normally

“true” Respond to HTTP requests with instructions to use HTTPS instead

See also:

Protocol

regionalGeoBlocking A string containing a boolean that defines the *Regional Geoblocking* setting of this *Delivery Service*; one of:

“false” Regional Geographic Blocking is not used by this *Delivery Service*

“true” Regional Geographic Blocking is used by this *Delivery Service*

See also:

Configure Regional Geo-blocking (RGB)

requiredCapabilities An array of this *Delivery Service*’s *required capabilities*. If there are no required capabilities, this field is omitted.

routingName A string that is this *Delivery Service*’s *Routing Name*

soa An object defining the SOA record for the *Delivery Service*'s TLDs (defined in domains)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: **RFC 1035** dictates that this should always be less than **refresh**.

See also:

[The Wikipedia page on Start of Authority records.](#)

sslEnabled A string containing a boolean that tells whether this *Delivery Service* uses SSL; one of:

“false” SSL is not used by this *Delivery Service*

“true” SSL is used by this *Delivery Service*

See also:

[Protocol](#)

topology The name of the *Topology* that this *Delivery Service* is assigned to. If the Delivery Service is not assigned to a

topology, this field is omitted.

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

Note: This overrides `config.ttls`.

edgeLocations An object containing keys which are the names of Edge-Tier *Cache Groups* within the CDN

backupLocations An object that describes this *Cache Group's Fallbacks*

fallbackToClosest A string containing a boolean which defines the *Fallback to Closest* behavior of this *Cache Group*; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

list If this *Cache Group* has any *Fallbacks*, this key will appear and will be an array of those *Cache Groups' Names*

latitude A floating point number that defines this *Cache Group's Latitude*

localizationMethods An array of strings that represents this *Cache Group's Localization Methods*

longitude A floating point number that defines this *Cache Group's Longitude*

monitors An object containing keys which are the (short) hostnames of Traffic Monitors within this CDN

fqdn The FQDN of this Traffic Monitor

httpsPort The port number on which this Traffic Monitor listens for incoming HTTPS requests

ip6 This Traffic Monitor's IPv6 address

ip This Traffic Monitor's IPv4 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Monitor belongs

port The port number on which this Traffic Monitor listens for incoming HTTP requests

profile A string which is the *Name* of the *Profile* used by this Traffic Monitor

Note: For legacy reasons, this must always start with “RASCAL-“.

status The health status of this Traffic Monitor

See also:

Health Protocol

stats An object containing metadata information regarding the CDN

CDN_name The name of this CDN

date The UNIX epoch timestamp date in the Traffic Ops server’s own timezone

tm_host The FQDN of the Traffic Ops server

Deprecated since version ATCv6: This information should never be used; instead all tools and (especially) components **must** use the documented API. This field was removed in APIv4

tm_path A path relative to the root of the Traffic Ops server where a request may be replaced to have this *Snapshot* overwritten by the current *configured state* of the CDN

tm_user The username of the currently logged-in user

tm_version The full version number of the Traffic Ops server, including release number, git commit hash, and supported Enterprise Linux version

topologies An array of *Topologies* where each key is the name of that Topology.

nodes An array of the names of the *Edge-Tier Cache Groups* in this *Topology*. *Mid-Tier* Cache Groups in the topology are not included.

trafficRouterLocations An object containing keys which are the *names of Cache Groups* within the CDN which contain Traffic Routers

backupLocations An object that describes this *Cache Group’s Fallbacks*

fallbackToClosest A string containing a boolean which defines this *Cache Group’s Fallback to Closest* setting; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

latitude A floating point number that defines this *Cache Group’s Latitude*

localizationMethods An array of strings that represents this *Cache Group’s Localization Methods*

longitude A floating point number that defines this *Cache Group’s Longitude*

653: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 27 May 2020 18:33:17
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳B5qdN9URIfu1lgQxPZ8YaaMvy2HMrzsnrpt6vF037yv60QiKCRyrUMX6wYs7QW4YVaeUrvmS2ya512YC0
X-Server-Name: traffic_ops_golang/
Date: Wed, 27 May 2020 17:33:17 GMT
Content-Length: 1360

{
  "response": {
    "config": {
      "api.cache-control.max-age": "10",
      "certificates.polling.interval": "300000",
      "consistent.dns.routing": "true",
      "coveragezone.polling.interval": "3600000",
      "coveragezone.polling.url": "https://trafficops.infra.ciab.
    ↳test:443/coverage-zone.json",
      "dnssec.dynamic.response.expiration": "300s",
      "dnssec.enabled": "false",
      "domain_name": "mycdn.ciab.test",
      "federationmapping.polling.interval": "60000",
      "federationmapping.polling.url": "https://${toHostname}/
    ↳api/2.0/federations/all",
```

(continues on next page)

(continued from previous page)

```

        "geolocation.polling.interval": "86400000",
        "geolocation.polling.url": "https://trafficops.infra.ciab.
→test:443/GeoLite2-City.mmdb.gz",
        "keystore.maintenance.interval": "300",
        "neustar.polling.interval": "86400000",
        "neustar.polling.url": "https://trafficops.infra.ciab.
→test:443/neustar.tar.gz",
        "soa": {
            "admin": "twelve_monkeys",
            "expire": "604800",
            "minimum": "30",
            "refresh": "28800",
            "retry": "7200"
        },
        "steeringmapping.polling.interval": "60000",
        "ttls": {
            "A": "3600",
            "AAAA": "3600",
            "DNSKEY": "30",
            "DS": "30",
            "NS": "3600",
            "SOA": "86400"
        },
        "zonemanager.cache.maintenance.interval": "300",
        "zonemanager.threadpool.scale": "0.50"
    },
    "contentRouters": {
        "trafficrouter": {
            "api.port": "3333",
            "fqdn": "trafficrouter.infra.ciab.test",
            "httpsPort": 443,
            "ip": "172.26.0.15",
            "ip6": "",
            "location": "CDN_in_a_Box_Edge",
            "port": 80,
            "profile": "CCR_CIAB",
            "secure.api.port": "3443",
            "status": "ONLINE"
        }
    },
    "contentServers": {
        "edge": {
            "cacheGroup": "CDN_in_a_Box_Edge",
            "capabilities": [
                "RAM_DISK_STORAGE"
            ],

```

(continues on next page)

(continued from previous page)

```

    "fqdn": "edge.infra.ciab.test",
    "hashCount": 999,
    "hashId": "edge",
    "httpsPort": 443,
    "interfaceName": "eth0",
    "ip": "172.26.0.3",
    "ip6": "",
    "locationId": "CDN_in_a_Box_Edge",
    "port": 80,
    "profile": "ATS_EDGE_TIER_CACHE",
    "routingDisabled": 0,
    "status": "REPORTED",
    "type": "EDGE"
  },
  "mid": {
    "cacheGroup": "CDN_in_a_Box_Mid",
    "capabilities": [
      "RAM_DISK_STORAGE"
    ],
    "fqdn": "mid.infra.ciab.test",
    "hashCount": 999,
    "hashId": "mid",
    "httpsPort": 443,
    "interfaceName": "eth0",
    "ip": "172.26.0.4",
    "ip6": "",
    "locationId": "CDN_in_a_Box_Mid",
    "port": 80,
    "profile": "ATS_MID_TIER_CACHE",
    "routingDisabled": 0,
    "status": "REPORTED",
    "type": "MID"
  }
},
"deliveryServices": {
  "demo1": {
    "anonymousBlockingEnabled": "false",
    "consistentHashQueryParams": [
      "abc",
      "pdq",
      "xxx",
      "zyx"
    ],
    "coverageZoneOnly": "false",
    "deepCachingType": "NEVER",
    "dispersion": {

```

(continues on next page)

(continued from previous page)

```

        "limit": 1,
        "shuffled": "true"
    },
    "domains": [
        "demo1.mycdn.ciab.test"
    ],
    "ecsEnabled": "false",
    "geolocationProvider": "maxmindGeolocationService",
    "ip6RoutingEnabled": "true",
    "matchsets": [
        {
            "matchlist": [
                {
                    "match-type": "HOST",
                    "regex": ".*\\.demo1\\.\\.\\.*"
                }
            ],
            "protocol": "HTTP"
        }
    ],
    "missLocation": {
        "lat": 42,
        "long": -88
    },
    "protocol": {
        "acceptHttps": "true",
        "redirectToHttps": "false"
    },
    "regionalGeoBlocking": "false",
    "requiredCapabilities": [
        "RAM_DISK_STORAGE"
    ],
    "routingName": "video",
    "soa": {
        "admin": "traffic_ops",
        "expire": "604800",
        "minimum": "30",
        "refresh": "28800",
        "retry": "7200"
    },
    "sslEnabled": "true",
    "topology": "my-topology",
    "tls": {
        "A": "",
        "AAAA": "",
        "NS": "3600",

```

(continues on next page)

(continued from previous page)

```

        "SOA": "86400"
      }
    },
    "edgeLocations": {
      "CDN_in_a_Box_Edge": {
        "backupLocations": {
          "fallbackToClosest": "true"
        },
        "latitude": 38.897663,
        "localizationMethods": [
          "GEO",
          "CZ",
          "DEEP_CZ"
        ],
        "longitude": -77.036574
      }
    },
    "monitors": {
      "trafficmonitor": {
        "fqdn": "trafficmonitor.infra.ciab.test",
        "httpsPort": 443,
        "ip": "172.26.0.14",
        "ip6": "",
        "location": "CDN_in_a_Box_Edge",
        "port": 80,
        "profile": "RASCAL-Traffic_Monitor",
        "status": "ONLINE"
      }
    },
    "stats": {
      "CDN_name": "CDN-in-a-Box",
      "date": 1590600715,
      "tm_host": "trafficops.infra.ciab.test:443",
      "tm_path": "/api/3.0/snapshot",
      "tm_user": "admin",
      "tm_version": "development"
    },
    "topologies": {
      "my-topology": {
        "nodes": [
          "CDN_in_a_Box_Edge"
        ]
      }
    },
    "trafficRouterLocations": {

```

(continues on next page)

(continued from previous page)

```

        "CDN_in_a_Box_Edge": {
            "backupLocations": {
                "fallbackToClosest": "false"
            },
            "latitude": 38.897663,
            "localizationMethods": [
                "GEO",
                "CZ",
                "DEEP_CZ"
            ],
            "longitude": -77.036574
        }
    }
}

```

`cdns/{name}/snapshot/new`

GET

Retrieves the *pending Snapshot* for a CDN, which represents the current *configuration* of the CDN, **not** the current *operating state* of the CDN. The contents of this *Snapshot* are currently used by Traffic Monitor and Traffic Router.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 279: Request Path Parameters

Name	Description
name	The name of the CDN for which a <i>Snapshot</i> shall be returned

654: Request Example

```

GET /api/3.0/cdns/CDN-in-a-Box/snapshot/new HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...

```

Response Structure

config An object containing basic configurations on the actual CDN object

api.cache-control.max-age A string containing an integer which specifies the value of `max-age` in the `Cache-Control` header of some HTTP responses, likely the *Traffic Router API* responses

certificates.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for updated SSL certificates

consistent.dns.routing A string containing a boolean which indicates whether DNS routing will use a consistent hashing method or “round-robin”

“false” The “round-robin” method will be used to define DNS routing

“true” A consistent hashing method will be used to define DNS routing

coveragezone.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should check for a new Coverage Zone file

coveragezone.polling.url The URL where a *Coverage Zone File* may be requested by Traffic Routers

dnssec.dynamic.response.expiration A string containing a number and unit suffix that specifies the length of time for which dynamic responses to DNSSEC lookup queries should remain valid

dnssec.dynamic.concurrencylevel An integer that defines the size of the concurrency level (threads) of the Guava cache used by ZoneManager to store zone material

dnssec.dynamic.initialcapacity An integer that defines the initial size of the Guava cache, default is 10000. Too low of a value can lead to expensive resizing

dnssec.init.timeout An integer that defines the number of minutes to allow for zone generation, this bounds the zone priming activity

dnssec.enabled A string that tells whether or not the CDN uses DNSSEC; one of:

“false” DNSSEC is not used within this CDN

“true” DNSSEC is used within this CDN

- domain_name** A string that is the TLD served by the CDN
- federationmapping.polling.interval** A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new federation mappings
- federationmapping.polling.url** The URL where Traffic Control components can request federation mappings
- geolocation.polling.interval** A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new IP-to-geographic-location mapping databases
- geolocation.polling.url** The URL where Traffic Control components can request IP-to-geographic-location mapping database files
- keystore.maintenance.interval** A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should refresh their zone caches
- neustar.polling.interval** A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new “Neustar” databases
- neustar.polling.url** The URL where Traffic Control components can request “Neustar” databases
- soa** An object defining the SOA for the CDN’s TLD (defined in `domain_name`)
- admin** The name of the administrator for this zone - i.e. the RNAME
-
- Note:** This rarely represents a proper email address, unfortunately.
-
- expire** A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond
- minimum** A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching
- refresh** A string containing an integer that sets the number of seconds after which

secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: [RFC 1035](#) dictates that this should always be less than `refresh`.

See also:

[The Wikipedia page on Start of Authority records.](#)

steeringmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Control components should check for new steering mappings

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

zonemanager.cache.maintenance.interval A configuration option for the ZoneManager Java class of Traffic Router

zonemanager.threadpool.scale A configuration option for the ZoneManager Java class of Traffic Router

contentRouters An object containing keys which are the (short) hostnames of the Traffic Routers that serve requests for *Delivery Services* in this CDN

api.port A string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTP

secure.api.port An optionally present string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTPS

fqdn This Traffic Router's FQDN

httpsPort The port number on which this Traffic Router listens for incoming HTTPS requests

ip This Traffic Router's IPv4 address

ip6 This Traffic Router's IPv6 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Router belongs

port The port number on which this Traffic Router listens for incoming HTTP requests

profile The *Name* of the *Profile* used by this Traffic Router

status The health status of this Traffic Router

See also:

Health Protocol

contentServers An object containing keys which are the (short) hostnames of the *Edge-tier cache servers* in the CDN; the values corresponding to those keys are routing information for said servers

cacheGroup A string that is the *Name* of the *Cache Group* to which the server belongs

capabilities An array of this *Cache Server's Server Capabilities*. If the Cache Server has no Server Capabilities, this field is omitted.

deliveryServices An object containing keys which are the names of *Delivery Services* to which this *cache server* is assigned; the values corresponding to those keys are arrays of FQDNs that resolve to this *cache server*

Note: Only *Edge-tier cache servers* can be assigned to a *Delivery Service*, and therefore this field will only be present when **type** is "EDGE".

fqdn The server's FQDN

hashCount The number of servers to be placed into a single "hash ring" in Traffic Router

hashId A unique string to be used as the key for hashing servers - as of version 3.0.0 of Traffic Control, this is always the same as the server's (short) hostname and only still exists for legacy compatibility reasons

httpsPort The port on which the *cache server* listens for incoming HTTPS requests

interfaceName The name of the main network interface device used by this *cache server*

ip6 The server's IPv6 address

ip The server's IPv4 address

locationId This field is exactly the same as **cacheGroup** and only exists for legacy compatibility reasons

port The port on which this *cache server* listens for incoming HTTP requests

profile The *Name* of the *Profile* used by the *cache server*

routingDisabled An integer representing the boolean concept of whether or not Traffic Routers should route client traffic to this *cache server*; one of:

0 Do not route traffic to this server

1 Route traffic to this server normally

status This *cache server*'s status

See also:

Health Protocol

type The *Type* of this *cache server*; which ought to be one of (but in practice need not be in certain special circumstances):

EDGE This is an *Edge-tier cache server*

MID This is a *Mid-tier cache server*

deliveryServices An object containing keys which are the *xml_ids* of all of the *Delivery Services* within the CDN

anonymousBlockingEnabled A string containing a boolean that tells whether or not *Anonymous Blocking* is set on this *Delivery Service*; one of:

“true” Anonymized IP addresses are blocked by this *Delivery Service*

“false” Anonymized IP addresses are not blocked by this *Delivery Service*

See also:

Configure Anonymous Blocking

consistentHashQueryParameters A set of query parameters that Traffic Router should consider when determining a consistent hash for a given client request.

consistentHashRegex An optional regular expression that will ensure clients are consistently routed to a *cache server* based on matches to it.

coverageZoneOnly A string containing a boolean that tells whether or not this *Delivery Service* routes traffic based only on its *Coverage Zone File*

See also:

Geo Limit

deepCachingType A string that defines the *Deep Caching* setting of this *Delivery Service*

dispersion An object describing the “dispersion” - or number of *cache servers* within a single *Cache Group* across which the same content is spread - within the *Delivery Service*

limit The maximum number of *cache servers* in which the response to a single request URL will be stored

Note: If this is greater than the number of *cache servers* in the *Cache Group* chosen to service the request, then content will be spread across all of them. That is, it causes no problems.

shuffled A string containing a boolean that tells whether the *cache servers* chosen for content dispersion are chosen randomly or based on a consistent hash of the request URL; one of:

“false” *cache servers* will be chosen consistently

“true” *cache servers* will be chosen at random

domains An array of domains served by this *Delivery Service*

ecsEnabled A string containing a boolean from *EDNS0 Client Subnet Enabled* that tells whether EDNS0 client subnet is enabled on this *Delivery Service*; one of:

“false” EDNS0 client subnet is not enabled on this *Delivery Service*

“true” EDNS0 client subnet is enabled on this *Delivery Service*

geolocationProvider The name of a provider for IP-to-geographic-location mapping services - currently the only valid value is "maxmindGeolocationService"

ip6RoutingEnabled A string containing a boolean that defines the *IPv6 Routing Enabled* setting for this *Delivery Service*; one of:

“false” IPv6 traffic will not be routed by this *Delivery Service*

“true” IPv6 traffic will be routed by this *Delivery Service*

matchList An array of methods used by Traffic Router to determine whether or not a request can be serviced by this *Delivery Service*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

setNumber An integral, unique identifier for the set of types to which the **type** field belongs

type The name of the *Type* of match performed using **pattern** to determine whether or not to use this *Delivery Service*

HOST_REGEX Use the *Delivery Service* if **pattern** matches the *Host* HTTP header of an HTTP request, or the name requested for resolution in a DNS request

HEADER_REGEX Use the *Delivery Service* if **pattern** matches an HTTP header (both the name and value) in an HTTP request¹

PATH_REGEX Use the *Delivery Service* if **pattern** matches the request path of this *Delivery Service*'s URL Page 960, 1

STEERING_REGEX Use the *Delivery Service* if **pattern** matches the *xml_id* of one of this *Delivery Service*'s “Steering” target *Delivery Services*

missLocation An object representing the default geographic coordinates to use for a client when lookup of their IP has failed in both the *Coverage Zone File* (and/or possibly the *Deep Coverage Zone File*) and the IP-to-geographic-location database

lat Geographic latitude as a floating point number

¹ These only apply to HTTP-routed *Delivery Services*

long Geographic longitude as a floating point number

protocol An object that describes how the *Delivery Service* ought to handle HTTP requests both with and without TLS encryption

acceptHttps A string containing a boolean that tells whether HTTPS requests should be normally serviced by this *Delivery Service*; one of:

“false” Refuse to service HTTPS requests

“true” Service HTTPS requests normally

redirectToHttps A string containing a boolean that tells whether HTTP requests ought to be re-directed to use HTTPS; one of:

“false” Do not redirect unencrypted traffic; service it normally

“true” Respond to HTTP requests with instructions to use HTTPS instead

See also:

Protocol

regionalGeoBlocking A string containing a boolean that defines the *Regional Geoblocking* setting of this *Delivery Service*; one of:

“false” Regional Geographic Blocking is not used by this *Delivery Service*

“true” Regional Geographic Blocking is used by this *Delivery Service*

See also:

Configure Regional Geo-blocking (RGB)

requiredCapabilities An array of this Delivery Service’s *required capabilities*. If there are no required capabilities, this field is omitted.

routingName A string that is this *Delivery Service’s Routing Name*

soa An object defining the SOA record for the *Delivery Service*'s TLDs (defined in domains)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: **RFC 1035** dictates that this should always be less than **refresh**.

See also:

[The Wikipedia page on Start of Authority records.](#)

sslEnabled A string containing a boolean that tells whether this *Delivery Service* uses SSL; one of:

“false” SSL is not used by this *Delivery Service*

“true” SSL is used by this *Delivery Service*

See also:

Protocol

topology The name of the *Topology* that this *Delivery Service* is assigned to. If the Delivery Service is not assigned to a

topology, this field is omitted.

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

Note: This overrides `config.ttls`.

edgeLocations An object containing keys which are the names of Edge-Tier *Cache Groups* within the CDN

backupLocations An object that describes this *Cache Group's Fallbacks*

fallbackToClosest A string containing a boolean which defines the *Fallback to Closest* behavior of this *Cache Group*; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

list If this *Cache Group* has any *Fallbacks*, this key will appear and will be an array of those *Cache Groups' Names*

latitude A floating point number that defines this *Cache Group's Latitude*

localizationMethods An array of strings that represents this *Cache Group's Localization Methods*

longitude A floating point number that defines this *Cache Group's Longitude*

monitors An object containing keys which are the (short) hostnames of Traffic Monitors within this CDN

fqdn The FQDN of this Traffic Monitor

httpsPort The port number on which this Traffic Monitor listens for incoming HTTPS requests

ip6 This Traffic Monitor's IPv6 address

ip This Traffic Monitor's IPv4 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Monitor belongs

port The port number on which this Traffic Monitor listens for incoming HTTP requests

profile A string which is the *Name* of the *Profile* used by this Traffic Monitor

Note: For legacy reasons, this must always start with “RASCAL-“.

status The health status of this Traffic Monitor

See also:

Health Protocol

stats An object containing metadata information regarding the CDN

CDN_name The name of this CDN

date The UNIX epoch timestamp date in the Traffic Ops server’s own timezone

tm_host The FQDN of the Traffic Ops server

tm_path A path relative to the root of the Traffic Ops server where a request may be replaced to have this *Snapshot* overwritten by the current *configured state* of the CDN

Deprecated since version ATCv6: This information should never be used; instead all tools and (especially) components **must** use the documented API. This field was removed in APIv4

tm_user The username of the currently logged-in user

tm_version The full version number of the Traffic Ops server, including release number, git commit hash, and supported Enterprise Linux version

topologies An array of *Topologies* where each key is the name of that Topology.

nodes An array of the names of the *Edge-Tier Cache Groups* in this *Topology*. *Mid-Tier* Cache Groups in the topology are not included.

trafficRouterLocations An object containing keys which are the *names of Cache Groups* within the CDN which contain Traffic Routers

backupLocations An object that describes this *Cache Group’s Fallbacks*

fallbackToClosest A string containing a boolean which defines this *Cache Group’s Fallback to Closest* setting; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

latitude A floating point number that defines this *Cache Group’s Latitude*

localizationMethods An array of strings that represents this *Cache Group’s Localization Methods*

longitude A floating point number that defines this *Cache Group’s Longitude*

655: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 27 May 2020 20:31:13.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→M6uhE2oPpjpTUR7gALsP0nM2CepD+VCAjp4dj5Xnppo0G5zL31PQgiteD23q67r7/bq/
→JJpMvIvdaENVYFtrqQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 27 May 2020 19:31:13 GMT
Content-Length: 1374

{
  "response": {
    "config": {
      "api.cache-control.max-age": "10",
      "certificates.polling.interval": "300000",
      "consistent.dns.routing": "true",
      "coveragezone.polling.interval": "3600000",
      "coveragezone.polling.url": "https://trafficops.infra.ciab.
→test:443/coverage-zone.json",
      "dnssec.dynamic.response.expiration": "300s",
      "dnssec.enabled": "false",
      "domain_name": "mycdn.ciab.test",
      "federationmapping.polling.interval": "60000",
      "federationmapping.polling.url": "https://${toHostname}/
→api/2.0/federations/all",
```

(continues on next page)

(continued from previous page)

```

    "geolocation.polling.interval": "86400000",
    "geolocation.polling.url": "https://trafficops.infra.ciab.
→test:443/GeoLite2-City.mmdb.gz",
    "keystore.maintenance.interval": "300",
    "neustar.polling.interval": "86400000",
    "neustar.polling.url": "https://trafficops.infra.ciab.
→test:443/neustar.tar.gz",
    "soa": {
        "admin": "twelve_monkeys",
        "expire": "604800",
        "minimum": "30",
        "refresh": "28800",
        "retry": "7200"
    },
    "steeringmapping.polling.interval": "60000",
    "ttls": {
        "A": "3600",
        "AAAA": "3600",
        "DNSKEY": "30",
        "DS": "30",
        "NS": "3600",
        "SOA": "86400"
    },
    "zonemanager.cache.maintenance.interval": "300",
    "zonemanager.threadpool.scale": "0.50"
},
"contentServers": {
    "edge": {
        "cacheGroup": "CDN_in_a_Box_Edge",
        "capabilities": [
            "RAM_DISK_STORAGE"
        ],
        "fqdn": "edge.infra.ciab.test",
        "hashCount": 999,
        "hashId": "edge",
        "httpsPort": 443,
        "interfaceName": "eth0",
        "ip": "172.26.0.3",
        "ip6": "",
        "locationId": "CDN_in_a_Box_Edge",
        "port": 80,
        "profile": "ATS_EDGE_TIER_CACHE",
        "status": "REPORTED",
        "type": "EDGE",
        "routingDisabled": 0
    },

```

(continues on next page)

(continued from previous page)

```

    "mid": {
      "cacheGroup": "CDN_in_a_Box_Mid",
      "capabilities": [
        "RAM_DISK_STORAGE"
      ],
      "fqdn": "mid.infra.ciab.test",
      "hashCount": 999,
      "hashId": "mid",
      "httpsPort": 443,
      "interfaceName": "eth0",
      "ip": "172.26.0.4",
      "ip6": "",
      "locationId": "CDN_in_a_Box_Mid",
      "port": 80,
      "profile": "ATS_MID_TIER_CACHE",
      "status": "REPORTED",
      "type": "MID",
      "routingDisabled": 0
    }
  },
  "contentRouters": {
    "trafficrouter": {
      "api.port": "3333",
      "fqdn": "trafficrouter.infra.ciab.test",
      "httpsPort": 443,
      "ip": "172.26.0.15",
      "ip6": "",
      "location": "CDN_in_a_Box_Edge",
      "port": 80,
      "profile": "CCR_CIAB",
      "secure.api.port": "3443",
      "status": "ONLINE"
    }
  },
  "deliveryServices": {
    "demo1": {
      "anonymousBlockingEnabled": "false",
      "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
      ],
      "coverageZoneOnly": "false",
      "deepCachingType": "NEVER",
      "dispersion": {

```

(continues on next page)

(continued from previous page)

```

        "limit": 1,
        "shuffled": "true"
    },
    "domains": [
        "demo1.mycdn.ciab.test"
    ],
    "ecsEnabled": "false",
    "geolocationProvider": "maxmindGeolocationService",
    "ip6RoutingEnabled": "true",
    "matchsets": [
        {
            "protocol": "HTTP",
            "matchlist": [
                {
                    "regex": ".*\\.demo1\\.\\.\\.*",
                    "match-type": "HOST"
                }
            ]
        }
    ],
    "missLocation": {
        "lat": 42,
        "long": -88
    },
    "protocol": {
        "acceptHttps": "true",
        "redirectToHttps": "false"
    },
    "regionalGeoBlocking": "false",
    "requiredCapabilities": [
        "RAM_DISK_STORAGE"
    ],
    "routingName": "video",
    "soa": {
        "admin": "traffic_ops",
        "expire": "604800",
        "minimum": "30",
        "refresh": "28800",
        "retry": "7200"
    },
    "sslEnabled": "true",
    "topology": "my-topology",
    "ttls": {
        "A": "",
        "AAAA": "",
        "NS": "3600",

```

(continues on next page)

(continued from previous page)

```

        "SOA": "86400"
    }
}
},
"edgeLocations": {
    "CDN_in_a_Box_Edge": {
        "latitude": 38.897663,
        "longitude": -77.036574,
        "backupLocations": {
            "fallbackToClosest": "true"
        },
        "localizationMethods": [
            "GEO",
            "CZ",
            "DEEP_CZ"
        ]
    }
},
"trafficRouterLocations": {
    "CDN_in_a_Box_Edge": {
        "latitude": 38.897663,
        "longitude": -77.036574,
        "backupLocations": {
            "fallbackToClosest": "false"
        },
        "localizationMethods": [
            "GEO",
            "CZ",
            "DEEP_CZ"
        ]
    }
},
"monitors": {
    "trafficmonitor": {
        "fqdn": "trafficmonitor.infra.ciab.test",
        "httpsPort": 443,
        "ip": "172.26.0.14",
        "ip6": "",
        "location": "CDN_in_a_Box_Edge",
        "port": 80,
        "profile": "RASCAL-Traffic_Monitor",
        "status": "ONLINE"
    }
},
"stats": {
    "CDN_name": "CDN-in-a-Box",

```

(continues on next page)

(continued from previous page)

```

        "date": 1590607873,
        "tm_host": "trafficops.infra.ciab.test:443",
        "tm_path": "/api/3.0/cdns/CDN-in-a-Box/snapshot/new",
        "tm_user": "admin",
        "tm_version": "development"
    },
    "topologies": {
        "my-topology": {
            "nodes": [
                "CDN_in_a_Box_Edge"
            ]
        }
    }
}

```

cdns/routing

GET

Retrieves the aggregated routing percentages across all CDNs. This is accomplished by polling stats from all online Traffic Routers via the `/crs/stats` route.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available

Response Structure

cz The percent of requests to online Traffic Routers that were satisfied by a *Coverage Zone File*

deepCz The percent of requests to online Traffic Routers that were satisfied by a *Deep Coverage Zone File*

dssr The percent of requests to online Traffic Routers that were satisfied by sending the client to an overflow *Delivery Service*

err The percent of requests to online Traffic Routers that resulted in an error

- fed** The percent of requests to online Traffic Routers that were satisfied by sending the client to a federated CDN
- geo** The percent of requests to online Traffic Routers that were satisfied using 3rd party geographic IP mapping
- miss** The percent of requests to online Traffic Routers that could not be satisfied
- regionalAlternate** The percent of requests to online Traffic Routers that were satisfied by sending the client to the alternate, Regional Geo-blocking URL
- regionalDenied** The percent of requests to online Traffic Routers that were denied due to geographic location policy
- staticRoute** The percent of requests to online Traffic Routers that were satisfied with *Static DNS Entries*

656: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 21:29:32 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→7LjytwKyRzSKM4cRIol40MIJxApFpTWJaSK73rbtUIQdASZjI64XxLVzZP00GRU7XeJ22YKUyQ30qbKHD
Content-Length: 130

{ "response": {
  "cz": 79,
  "deepCz": 0.50,
  "dsr": 0,
  "err": 0,
  "fed": 0.25,
  "geo": 20,
  "miss": 0.25,
  "regionalAlternate": 0,
  "regionalDenied": 0,
  "staticRoute": 0
}}
```

consistenthash

Test Pattern-Based Consistent Hashing for a *Delivery Service* using a regular expression and a request path

POST

Queries database for an active Traffic Router on a given CDN and sends GET request to get the resulting path to consistent hash with a given regex and request path.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

regex The regular expression to apply to the request path to get a resulting path that will be used for consistent hashing

requestPath The request path to use to test the regular expression against

cdnId The unique identifier of a CDN that will be used to query for an active Traffic Router

657: Request Example

```
POST /api/3.0/consistenthash HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.54.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 80
Content-Type: application/x-www-form-urlencoded

{"regex":"/.*?(/.*?/).*(m3u8)","requestPath":"/test/path/asset.m3u8",
  ↪ "cdnId":2}
```

Response Structure

resultingPathToConsistentHash The resulting path that Traffic Router will use for consistent hashing

consistentHashRegex The regex used by Traffic Router derived from POST 'regex' parameter

requestPath The request path used by Traffic Router to test regex against

658: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳QMDFOOnUfqH4TcZ4YnUQyqnXDier0YiUMIfwBGDcT7ySjw9uASBGsLQW35lpnKFi4as0vYlHuSSGpe4hHG
X-Server-Name: traffic_ops_golang/
Date: Tue, 12 Feb 2019 21:32:05 GMT
Content-Length: 142

{ "response": {
  "resultingPathToConsistentHash":"/path/m3u8",
  "consistentHashRegex":"/.*?(/.*?/).*(m3u8)",
  "requestPath":"/test/path/asset.m3u8"
}}
```

coordinates

GET

Gets a list of all coordinates in the Traffic Ops database

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 280: Request Query Parameters

Name	Re-quired	Description
id	no	Return only coordinates that have this integral, unique identifier
name	no	Return only coordinates with this name
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

id Integral, unique, identifier for this coordinate pair

lastUpdated The time and date at which this entry was last updated, in a ctime-like format

latitude Latitude of the coordinate

longitude Longitude of the coordinate

name The name of the coordinate - typically this just reflects the name of the Cache Group for which the coordinate was created

659: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Y2vxC3hpxIg6aRNBBT7i2hbAViIJp+dJoqHIzu3acFM+vGay/
    ↳I5E+eZYOC9RY8hcJPrKNXysZOD8DOb9KsFgaw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:32:28 GMT
    
```

(continues on next page)

(continued from previous page)

Content-Length: 942

```
{ "response": [  
  {  
    "id": 1,  
    "name": "from_cachegroup_TRAFFIC_ANALYTICS",  
    "latitude": 38.897663,  
    "longitude": -77.036574,  
    "lastUpdated": "2018-10-24 16:07:04+00"  
  },  
  {  
    "id": 2,  
    "name": "from_cachegroup_TRAFFIC_OPS",  
    "latitude": 38.897663,  
    "longitude": -77.036574,  
    "lastUpdated": "2018-10-24 16:07:04+00"  
  },  
  {  
    "id": 3,  
    "name": "from_cachegroup_TRAFFIC_OPS_DB",  
    "latitude": 38.897663,  
    "longitude": -77.036574,  
    "lastUpdated": "2018-10-24 16:07:04+00"  
  },  
  {  
    "id": 4,  
    "name": "from_cachegroup_TRAFFIC_PORTAL",  
    "latitude": 38.897663,  
    "longitude": -77.036574,  
    "lastUpdated": "2018-10-24 16:07:04+00"  
  },  
  {  
    "id": 5,  
    "name": "from_cachegroup_TRAFFIC_STATS",  
    "latitude": 38.897663,  
    "longitude": -77.036574,  
    "lastUpdated": "2018-10-24 16:07:04+00"  
  },  
  {  
    "id": 6,  
    "name": "from_cachegroup_CDN_in_a_Box_Mid",  
    "latitude": 38.897663,  
    "longitude": -77.036574,  
    "lastUpdated": "2018-10-24 16:07:04+00"  
  },  
]
```

(continues on next page)

(continued from previous page)

```

    "id": 7,
    "name": "from_cachegroup_CDN_in_a_Box_Edge",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:05+00"
  }
}]

```

POST

Creates a new coordinate pair

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the new coordinate

latitude The desired latitude of the new coordinate (must be on the interval [-180, 180])

longitude The desired longitude of the new coordinate (must be on the interval [-90, 90])

660: Request Example

```
POST /api/3.0/coordinates HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 47
Content-Type: application/json

{"name": "test", "latitude": 0, "longitude": 0}
```

Response Structure

- id** Integral, unique, identifier for the newly created coordinate pair
- lastUpdated** The time and date at which this entry was last updated, in a ctime-like format
- latitude** Latitude of the newly created coordinate
- longitude** Longitude of the newly created coordinate
- name** The name of the coordinate

661: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 7pWdeZyIIXE1P7o/
→JVon+5eSCbDw+FGamAzdXzWHXJ8IhF+Vh+/
→tWfCkzHYw3rP2kBVwZu+gqLffjQpBCMjt7A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 17:48:55 GMT
Content-Length: 165

{ "alerts": [
  {
    "text": "coordinate was created.",
    "level": "success"
  }
]}
```

(continues on next page)

(continued from previous page)

```
],
"response": {
  "id": 9,
  "name": "test",
  "latitude": 0,
  "longitude": 0,
  "lastUpdated": "2018-11-15 17:48:55+00"
}}
```

PUT

Updates a coordinate

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 281: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the coordinate to edit

name The name of the new coordinate

latitude The desired new latitude of the coordinate (must be on the interval [-180, 180])

longitude The desired new longitude of the coordinate (must be on the interval [-90, 90])

662: Request Example

```
PUT /api/3.0/coordinates?id=9 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 48
Content-Type: application/json

{"name": "quest", "latitude": 0, "longitude": 0}
```

Response Structure

- id** Integral, unique, identifier for the coordinate pair
- lastUpdated** The time and date at which this entry was last updated, in a ctime-like format
- latitude** Latitude of the coordinate
- longitude** Longitude of the coordinate
- name** The name of the coordinate

663: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳zd03Uvbnv8EbSZZ75Xp5tnnYStZsZTdyPxXnoqK4QZ5WhELLPL8iHlRf0aiLTbrUWUeJ8ue2HRz6aBS/
    ↳iXCCGA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 17:54:30 GMT
Content-Length: 166

{ "alerts": [
  {
    "text": "coordinate was updated.",
    "level": "success"
  }
],
"response": {
  "id": 9,
  "name": "quest",
  "latitude": 0,
  "longitude": 0,
  "lastUpdated": "2018-11-15 17:54:30+00"
}}
```

DELETE

Deletes a coordinate

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 282: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the coordinate to delete

Response Structure

664: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 82x/Wdckqgk4LN5LilZfBJ26xkDrUVUGDjs5QFa/
    ↳Lzap7dU30Zkjbv8XW41xeFYj8PDmxHIpb7hiV0bvLaxnEDA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 17:57:42 GMT
Content-Length: 65

{ "alerts": [
  {
    "text": "coordinate was deleted.",
    "level": "success"
  }
]}

```

current_stats

An API endpoint that returns current statistics for each CDN and an aggregate across them all.

GET

Retrieves current stats for each CDN. Also includes aggregate stats across them.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

665: Request Example

```
GET /api/3.0/current_stats HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

cdn The name of the CDN

connections Current number of TCP connections maintained

capacity 85 percent capacity of the CDN in Gps

bandwidth The total amount of bandwidth in Gbs

Note: If **cdn** name is total and capacity is omitted it represents the aggregate stats across CDNs

666: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=; Path=/; HttpOnly
Whole-Content-Sha512: ↵
  ↵Rs3wgd7v5dP0b0Qs4I3J1q6mnWIMSM2AKSAWirK1kymvDY0oFISArF7Kkypgy10I34yn7FtFdMh6U7ABa
X-Server-Name: traffic_ops_golang/
Date: Thu, 14 Nov 2019 15:35:31 GMT
Content-Length: 138

{"response": {
  "currentStats": [
    {
      "bandwidth": null,
      "capacity": null,
      "cdn": "ALL",
      "connections": null
    },
    {
      "bandwidth": 0.000104,
      "capacity": 17,
      "cdn": "CDN-in-a-Box",
      "connections": 4
    },
    {
      "bandwidth": 0.000104,
      "cdn": "total",
      "connections": 4
    }
  ]
}}
```

dbdump

Caution: This is an extremely dangerous thing to do, as it exposes the entirety of the database, including possibly sensitive information. Administrators and systems engineers are advised to instead use database-specific tools to make server transitions more securely.

Dumps the Traffic Ops database as an SQL script that should recreate its schema and contents exactly.

Implementation Detail

The script is output using the *pg_dump(1)* utility, and is thus compatible for use with the

`pg_restore(1)` utility.

GET

Fetches the database dump.

Auth. Required Yes

Roles Required “admin”

Response Type undefined - outputs an SQL script, not JSON

Request Structure

No parameters available

667: Request Example

```
GET /api/3.0/dbdump HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

668: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/sql
Content-Disposition: attachment
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→YwvPB0ZToyzT8ilBnDlWWdwV+E3f2Xgus10KrkNaipQqgrw5zGwq0rC1U9TZ8Zl6kAGcRZgCYnr1EWfHX
X-Server-Name: traffic_ops_golang/
Date: Mon, 09 Sep 2019 21:08:28 GMT
Transfer-Encoding: chunked

-- Actual text omitted - it's huge
```


deliveryservice_request_comments

GET

Gets delivery service request comments.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 283: Request Query Parameters

Name	Re-quired	Description
author	no	Filter for <i>Delivery Service Request</i> comments submitted by the user identified by this username
authorId	no	Filter for <i>Delivery Service Request</i> comments submitted by the user identified by this integral, unique identifier
deliveryServiceRequestId	no	Filter for <i>Delivery Service Request</i> comments submitted for the delivery service identified by this integral, unique identifier
id	no	Filter for the <i>Delivery Service Request</i> comment identified by this integral, unique identifier

669: Request Example

```
GET /api/3.0/deliveryservice_request_comments HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

author The username of the user who created the comment.

authorId The integral, unique identifier of the user who created the comment.

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

id The integral, unique identifier of the *DSR* comment.

lastUpdated The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*

value The text of the comment that was posted.

xmlId This is the xmlId value that you provided in the request.

670: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:00:26
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳RaJZS1XFJ4oIxVKyyDjTuoQY7gPOmm5EuIL4AgHpyQpuaaNviw0XhGC4V/AKf/
    ↳Ws6zXLgIUc40yvMsTxnrilww==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:00:26 GMT
Content-Length: 207

{
  "response": [
    {
      "authorId": 2,
      "author": "admin",
      "deliveryServiceRequestId": 2,
      "id": 3,
      "lastUpdated": "2020-02-24 19:59:46+00",
      "value": "Changing to a different origin for now.",
      "xmlId": "demo1"
    },
    {
      "authorId": 2,
      "author": "admin",
      "deliveryServiceRequestId": 2,
      "id": 4,
      "lastUpdated": "2020-02-24 19:59:55+00",
      "value": "Using HTTPS.",
      "xmlId": "demo1"
    }
  ]
}
```

POST

Allows user to create a *Delivery Service Request* comment.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

deliveryServiceRequestId The integral, unique identifier of the delivery service that you are commenting on.

value The comment text itself.

xmlId This can be any string. It is not validated or used, though it is returned in the response.

671: Request Example

```
POST /api/3.0/deliveryservice_request_comments HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 111

{
  "deliveryServiceRequestId": 2,
  "value": "Does anyone have time to review my delivery service_
→request?"
}
```

Response Structure

author The username of the user who created the comment.

authorId The integral, unique identifier of the user who created the comment.

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

id The integral, unique identifier of the *DSR* comment.

lastUpdated The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*

value The text of the comment that was posted.

xmlId This is the xmlId value that you provided in the request.

672: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:02:20
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳LiakFP6L7PrnF05kLXftx7WQoKn3bGpIJT5N15PvNG2sHridRMV3k23eRJM66ET0LcRfM0rQgRiydE+Xg
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:02:20 GMT
Content-Length: 223

{
  "alerts": [
    {
      "text": "deliveryservice_request_comment was created.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": 2,
    "author": null,
    "deliveryServiceRequestId": 2,
    "id": 6,
    "lastUpdated": "2020-02-24 20:02:20+00",
    "value": "Does anyone have time to review my delivery service
    ↳request?",
    "xmlId": null
  }
}
```

PUT

Updates a delivery service request comment.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

value The comment text itself.

xmlId This can be any string. It is not validated or used, though it is returned in the response.

Table 284: Request Query Parameters

Parameter	Required	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> comment that you wish to update.

673: Request Example

```
PUT /api/3.0/deliveryservice_request_comments?id=6 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 166

{
  "deliveryServiceRequestId": 2,
  "value": "Update: We no longer need this, feel free to reject.\n\
  ↪nDoes anyone have time to review my delivery service request?"
}
```

Response Structure

- author** The username of the user who created the comment.
- authorId** The integral, unique identifier of the user who created the comment.
- deliveryServiceRequestId** The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.
- id** The integral, unique identifier of the *DSR* comment.
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- value** The text of the comment that was posted.
- xmlId** This is the `xmlId` value that you provided in the request.

674: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type, ↪
  ↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:05:46 ↪
  ↪GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ↪
  ↪RalS34imPw7c42nlnu5eTuv6FSxuGcAvxEdeIyNma1zpE3ZojAMFbhj8qi1s+h0VDYybfFPzMz82c+xc1
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

Date: Mon, 24 Feb 2020 20:05:46 GMT

Content-Length: 255

```
{
  "alerts": [
    {
      "text": "deliveryservice_request_comment was updated.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": null,
    "author": null,
    "deliveryServiceRequestId": 2,
    "id": 6,
    "lastUpdated": "2020-02-24 20:05:46+00",
    "value": "Update: We no longer need this, feel free to reject.\n\nDoes anyone have time to review my delivery service request?",
    "xmlId": null
  }
}
```

DELETE

Deletes a delivery service request comment.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type undefined

Request Structure

Table 285: Request Query Parameters

Parameter	Required	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> comment that you wish to delete.

675: Request Example

DELETE /api/3.0/deliveryservice_request_comments?id=6 HTTP/1.1

User-Agent: python-requests/2.22.0

(continues on next page)

(continued from previous page)

```
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

676: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:07:40
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 10pGzqeIh/1JAx85mz3MI/
→5A1i1g5beTSLtfvgcfQmCjNKQvOMs/4TLviuVzOCRrEIPmNcjy35tmvfxwlv7RMQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:07:40 GMT
Content-Length: 101

{
  "alerts": [
    {
      "text": "deliveryservice_request_comment was deleted.",
      "level": "success"
    }
  ]
}
```

deliveryservice_requests

GET

Retrieves *Delivery Service Requests*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 286: Request Query Parameters

Name	Re-quired	Description
as-signee	no	Filter for <i>Delivery Service Requests</i> that are assigned to the user identified by this username.
as-signeeId	no	Filter for <i>Delivery Service Requests</i> that are assigned to the user identified by this integral, unique identifier
author	no	Filter for <i>Delivery Service Requests</i> submitted by the user identified by this username
authorId	no	Filter for <i>Delivery Service Requests</i> submitted by the user identified by this integral, unique identifier
changeType	no	Filter for <i>Delivery Service Requests</i> of the change type specified. Can be create , update , or delete .
createdAt	no	Filter for <i>Delivery Service Requests</i> created on a certain date/time. Value must be RFC 3339 compliant. Eg. 2019-09-19T19:35:38.828535Z
id	no	Filter for the <i>Delivery Service Request</i> identified by this integral, unique identifier.
status	no	Filter for <i>Delivery Service Requests</i> whose status is the status specified. The status can be draft , submitted , pending , rejected , or complete .
xmlId	no	Filter for <i>Delivery Service Requests</i> that have the given <i>xml_id</i> .
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

New in version ATCv6: The `createdAt` query parameter was added to this in endpoint across all API versions in ATC version 6.0.0.

677: Request Example

```
GET /api/3.0/deliveryservice_requests?status=draft HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

- author** The username of the user who created the Delivery Service Request.
- authorId** The integral, unique identifier assigned to the author
- changeType** The change type of the *DSR*. It can be create, update, or delete....
- createdAt** The date and time at which the *DSR* was created, in *Traffic Ops's Custom Date/Time Format*.
- deliveryService** The delivery service that the *DSR* is requesting to update.
 - active** A boolean that defines *Active*.
 - anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
 - cacheurl** A *Cache URL Expression*
 - Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
 - ccrDnsTtl** The *DNS TTL* - named "ccrDnsTtl" for legacy reasons
 - cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
 - cdnName** Name of the *CDN* to which the *Delivery Service* belongs
 - checkPath** A *Check Path*
 - consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
 - consistentHashRegex** A *Consistent Hashing Regular Expression*
 - deepCachingType** The *Deep Caching* setting for this *Delivery Service*
 - displayName** The *Display Name*
 - dnsBypassCname** A *DNS Bypass CNAME*
 - dnsBypassIp** A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*¹

geoLimitRedirectUrl A *Geo Limit Redirect URL* Page 960, 1

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

longDesc2 An optional field containing the 3rd long description of this *Delivery Service*

¹ These fields must be defined if and only if `geoLimit` is non-zero

matchList The *Delivery Service's Match List*

pattern A regular expression - the use of this pattern is dependent on the `type` field (backslashes are escaped)

setNumber An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

type The type of match performed using pattern.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- lastEditedBy** The username of user who last edited this *DSR*
- lastEditedById** The integral, unique identifier assigned to the user who last edited this *DSR*
- lastUpdated** The date and time at which the *DSR* was last updated, in *Traffic Ops's Custom Date/Time Format*.
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

678: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:14:07 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UBp3nklJr2x2cAW/
TKbhXMVJH6+OduxUaEBGbX4P7IahDk3VkaTd9LsQj01zgFEnZLwHrikpwFfNlU032RAZOA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:14:07 GMT
Content-Length: 872
```

```
{
  "response": [
    {
      "authorId": 2,
      "author": "admin",
      "changeType": "update",
      "createdAt": "2020-02-24 19:11:12+00",
      "id": 1,
      "lastEditedBy": "admin",
      "lastEditedById": 2,
      "lastUpdated": "2020-02-24 19:11:12+00",
      "deliveryService": {
        "active": false,
        "anonymousBlockingEnabled": false,
        "cacheurl": null,
        "ccrDnsTtl": null,
        "cdnId": 2,
        "cdnName": "CDN-in-a-Box",
        "checkPath": null,
        "displayName": "Demo 1",
        "dnsBypassCname": null,
        "dnsBypassIp": null,
        "dnsBypassIp6": null,
        "dnsBypassTtl": null,
        "dscp": 0,
        "edgeHeaderRewrite": null,
        "firstHeaderRewrite": null,
        "geoLimit": 0,
        "geoLimitCountries": null,
        "geoLimitRedirectURL": null,
        "geoProvider": 0,
        "globalMaxMbps": null,
        "globalMaxTps": null,
        "httpBypassFqdn": null,
```

(continues on next page)

(continued from previous page)

```

    "id": 1,
    "infoUrl": null,
    "initialDispersion": 1,
    "innerHeaderRewrite": null,
    "ipv6RoutingEnabled": true,
    "lastHeaderRewrite": null,
    "lastUpdated": "0001-01-01 00:00:00+00",
    "logsEnabled": true,
    "longDesc": "Apachecon North America 2018",
    "longDesc1": null,
    "longDesc2": null,
    "matchList": [
        {
            "type": "HOST_REGEX",
            "setNumber": 0,
            "pattern": ".*\\.demo1\\.\\.\\.*"
        }
    ],
    "maxDnsAnswers": null,
    "midHeaderRewrite": null,
    "missLat": 42,
    "missLong": -88,
    "multiSiteOrigin": false,
    "originShield": null,
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": 2,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": 1,
    "tenantId": 1,
    "topology": null,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],

```

(continues on next page)

(continued from previous page)

```

        "deepCachingType": "NEVER",
        "fqPacingRate": null,
        "signingAlgorithm": null,
        "tenant": "root",
        "trResponseHeaders": null,
        "trRequestHeaders": null,
        "consistentHashRegex": null,
        "consistentHashQueryParams": [
            "abc",
            "pdq",
            "xxx",
            "zyx"
        ],
        "maxOriginConnections": 0,
        "ecsEnabled": false
    },
    "status": "draft"
}
]
}

```

POST

Note: This route does NOT do the same thing as *POST deliveryservices/request*.

Creates a new *Delivery Service Request*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

changeType The action that you want to perform on the delivery service. It can be “create”, “update”, or “delete”.

status The status of your request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

deliveryService The *Delivery Service* that you have submitted for review as part of this request.

active A boolean that defines *Active*.

- anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
- cacheurl** A *Cache URL Expression*
- Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
- ccrDnsTtl** The *DNS TTL* - named “ccrDnsTtl” for legacy reasons
- cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
- cdnName** Name of the *CDN* to which the *Delivery Service* belongs
- checkPath** A *Check Path*
- consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
- consistentHashRegex** A *Consistent Hashing Regular Expression*
- deepCachingType** The *Deep Caching* setting for this *Delivery Service*
- displayName** The *Display Name*
- dnsBypassCname** A *DNS Bypass CNAME*
- dnsBypassIp** A *DNS Bypass IP*
- dnsBypassIp6** A *DNS Bypass IPv6*
- dnsBypassTtl** The *DNS Bypass TTL*
- dscp** A *DSCP* to be used within the *Delivery Service*
- ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*
- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*
- firstHeaderRewrite** A set of *First Header Rewrite Rules*
- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*
- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*^{Page 960, 1}
- geoLimitRedirectUrl** A *Geo Limit Redirect URL*^{Page 960, 1}
- geoProvider** The *Geolocation Provider*

- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*
- httpBypassFqdn** A *HTTP Bypass FQDN*
- id** An integral, unique identifier for this *Delivery Service*
- infoUrl** An *Info URL*
- initialDispersion** The *Initial Dispersion*
- innerHeaderRewrite** A set of *Inner Header Rewrite Rules*
- ipv6RoutingEnabled** A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*
- lastHeaderRewrite** A set of *Last Header Rewrite Rules*
- lastUpdated** The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** An optional field containing the 2nd long description of this *Delivery Service*
- longDesc2** An optional field containing the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using pattern.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*

- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

679: Request Example

```
POST /api/3.0/deliveryservice_requests HTTP/1.1
```

```
User-Agent: python-requests/2.22.0
```

```
Accept-Encoding: gzip, deflate
```

```
Accept: */*
```

```
Connection: keep-alive
```

```
Cookie: mojolicious=...
```

```
Content-Length: 1979
```

```
{
  "changeType": "update",
  "status": "draft",
  "deliveryService": {
    "active": false,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "Demo 1",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "firstHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
```

(continues on next page)

(continued from previous page)

```
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "2020-02-13 16:43:54+00",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"longDesc1": null,
"longDesc2": null,
"matchList": [
    {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
    "http://video.demo1.mycdn.ciab.test",
    "https://video.demo1.mycdn.ciab.test"
],
```

(continues on next page)

(continued from previous page)

```

    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "topology": null,
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false
}

```

Response Structure

- author** The username of the user who created the Delivery Service Request.
- authorId** The integral, unique identifier assigned to the author
- changeType** The change type of the *DSR*. It can be create, update, or delete....
- createdAt** The date and time at which the *DSR* was created, in *Traffic Ops's Custom Date/Time Format*.
- deliveryService** The delivery service that the *DSR* is requesting to update.
 - active** A boolean that defines *Active*.
 - anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
 - cacheurl** A *Cache URL Expression*
 - Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
 - ccrDnsTtl** The *DNS TTL* - named "ccrDnsTtl" for legacy reasons
 - cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

consistentHashRegex A *Consistent Hashing Regular Expression*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*^{Page 960, 1}

geoLimitRedirectUrl A *Geo Limit Redirect URL*^{Page 960, 1}

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

- ipv6RoutingEnabled** A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*
- lastHeaderRewrite** A set of *Last Header Rewrite Rules*
- lastUpdated** The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** An optional field containing the 2nd long description of this *Delivery Service*
- longDesc2** An optional field containing the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using **pattern**.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string

- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*

- xmlId** This *Delivery Service*'s *xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- lastEditedBy** The username of user who last edited this *DSR*
- lastEditedById** The integral, unique identifier assigned to the user who last edited this *DSR*
- lastUpdated** The date and time at which the *DSR* was last updated, in *Traffic Ops's Custom Date/Time Format*.
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

680: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:11:12.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: aWlrFTwUGnLq56WNZPL/FgOi/
→NwAVUtOy4iqjFPwx4gj7RMZ6+nd++bQKIiasBl8ytAY0WmFvNnmm30Fq9mLpA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:11:12 GMT
Content-Length: 901

{
  "alerts": [
    {
      "text": "deliveryservice_request was created.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": 2,
    "author": null,
    "changeType": "update",
    "createdAt": null,
    "id": 1,
    "lastEditedBy": null,
    "lastEditedById": 2,
    "lastUpdated": "2020-02-24 19:11:12+00",
    "deliveryService": {
```

(continues on next page)

(continued from previous page)

```

"active": false,
"anonymousBlockingEnabled": false,
"cacheurl": null,
"ccrDnsTtl": null,
"cdnId": 2,
"cdnName": "CDN-in-a-Box",
"checkPath": null,
"displayName": "Demo 1",
"dnsBypassCname": null,
"dnsBypassIp": null,
"dnsBypassIp6": null,
"dnsBypassTtl": null,
"dscp": 0,
"edgeHeaderRewrite": null,
"firstHeaderRewrite": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "0001-01-01 00:00:00+00",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"longDesc1": null,
"longDesc2": null,
"matchList": [
    {
        "type": "HOST_REGEXP",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,

```

(continues on next page)

(continued from previous page)

```
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": 2,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": 1,
    "tenantId": 1,
    "topology": null,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false
},
"status": "draft"
}
```

PUT

Updates an existing *Delivery Service Request*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

changeType The change type of the *DSR*. It can be create, update, or delete....

deliveryService The delivery service that the *DSR* is requesting to update.

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

consistentHashRegex A *Consistent Hashing Regular Expression*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*^{Page 960, 1}

geoLimitRedirectUrl A *Geo Limit Redirect URL*^{Page 960, 1}

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

longDesc2 An optional field containing the 3rd long description of this *Delivery Service*

matchList The *Delivery Service's Match List*

pattern A regular expression - the use of this pattern is dependent on the `type` field (backslashes are escaped)

setNumber An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

type The type of match performed using pattern.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

routingName The *Routing Name* of this *Delivery Service*

signed true if and only if **signingAlgorithm** is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*

sslKeyVersion This integer indicates the *SSL Key Version*

tenant The name of the *Tenant* who owns this *Origin*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

topology The unique name of the *Topology* that this *Delivery Service* is assigned to

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

id The integral, unique identifier assigned to the *DSR*

status The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

Table 287: Request Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> that you want to update.

681: Request Example

```
PUT /api/3.0/deliveryservice_requests?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
```

(continues on next page)

(continued from previous page)

Cookie: mojolicious=...

Content-Length: 2256

```
{
  "authorId": 2,
  "author": "admin",
  "changeType": "update",
  "createdAt": "2020-02-24 19:11:12+00",
  "id": 1,
  "lastEditedBy": "admin",
  "lastEditedById": 2,
  "lastUpdated": "2020-02-24 19:33:26+00",
  "deliveryService": {
    "active": false,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "Demo 1",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "firstHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 1,
    "infoUrl": null,
    "initialDispersion": 1,
    "innerHeaderRewrite": null,
    "ipv6RoutingEnabled": true,
    "lastHeaderRewrite": null,
    "lastUpdated": "0001-01-01 00:00:00+00",
    "logsEnabled": true,
    "longDesc": "Apachecon North America 2018",
    "longDesc1": null,
    "longDesc2": null,
  }
}
```

(continues on next page)

(continued from previous page)

```
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"topology": null,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
  "http://video.demo1.mycdn.ciab.test",
  "https://video.demo1.mycdn.ciab.test"
],
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": "root",
"trResponseHeaders": "",
"trRequestHeaders": null,
"consistentHashRegex": null,
"consistentHashQueryParams": [
  "abc",
  "pdq",
  "xxx",
```

(continues on next page)

(continued from previous page)

```

        "zyx"
      ],
      "maxOriginConnections": 0,
      "ecsEnabled": false
    },
    "status": "submitted"
  }

```

Response Structure

changeType The change type of the *DSR*. It can be create, update, or delete....

deliveryService The delivery service that the *DSR* is requesting to update.

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

consistentHashRegex A *Consistent Hashing Regular Expression*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*^{Page 960, 1}

geoLimitRedirectUrl A *Geo Limit Redirect URL*^{Page 960, 1}

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

longDesc2 An optional field containing the 3rd long description of this *Delivery Service*

matchList The *Delivery Service's Match List*

pattern A regular expression - the use of this pattern is dependent on the `type` field (backslashes are escaped)

setNumber An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

type The type of match performed using pattern.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- lastEditedBy** The username of user who last edited this *DSR*
- lastEditedById** The integral, unique identifier assigned to the user who last edited this *DSR*
- lastUpdated** The date and time at which the *DSR* was last updated, in *Traffic Ops's Custom Date/Time Format*.
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

682: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:36:16.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +W0vFm96yFkZUJqa0GAX7uzIpRKh/
→ohyBm0uH3egpiERTcxy50fVVtoP3h8Ee2teLu8KFooDYXJ6rpQg6UhbNQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:36:16 GMT
Content-Length: 913
```

```
{
  "alerts": [
    {
      "text": "deliveryservice_request was updated.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": 0,
    "author": "admin",
    "changeType": "update",
    "createdAt": "0001-01-01 00:00:00+00",
    "id": 1,
    "lastEditedBy": "admin",
    "lastEditedById": 2,
    "lastUpdated": "2020-02-24 19:36:16+00",
    "deliveryService": {
      "active": false,
      "anonymousBlockingEnabled": false,
      "cacheurl": null,
      "ccrDnsTtl": null,
      "cdnId": 2,
      "cdnName": "CDN-in-a-Box",
      "checkPath": null,
      "displayName": "Demo 1",
      "dnsBypassCname": null,
      "dnsBypassIp": null,
      "dnsBypassIp6": null,
      "dnsBypassTtl": null,
      "dscp": 0,
      "edgeHeaderRewrite": null,
      "firstHeaderRewrite": null,
      "geoLimit": 0,
      "geoLimitCountries": null,
      "geoLimitRedirectURL": null,
```

(continues on next page)

(continued from previous page)

```
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "0001-01-01 00:00:00+00",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"longDesc1": null,
"longDesc2": null,
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"topology": null,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
```

(continues on next page)

(continued from previous page)

```

    "exampleURLs": [
      "http://video.demo1.mycdn.ciab.test",
      "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": "",
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
      "abc",
      "pdq",
      "xxx",
      "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false
  },
  "status": "submitted"
}

```

DELETE

Deletes a *Delivery Service Request*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type undefined

Request Structure

Table 288: Request Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> that you want to delete.

683: Request Example

```
DELETE /api/3.0/deliveryservice_requests?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

684: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:48:55
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳jNCbNo8Tw+JMMaWpAYQgntSXPq2Xuj+n2zSEVRaDQFWMV1SYbT9djes6SPdwiBoKq6W0lNE04h0E92jBV
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:48:55 GMT
Content-Length: 96

{
  "alerts": [
    {
      "text": "deliveryservice_request was deleted.",
      "level": "success"
    }
  ]
}
```

deliveryservice_requests/{{ID}}/assign

Assign a *Delivery Service Request* to a user.

PUT

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

id The integral, unique identifier assigned to the *DSR*

assignee The username of the user to whom the *Delivery Service Request* is assigned.

685: Request Example

```
PUT /api/3.0/deliveryservice_requests/1/assign HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 28

{
  "id": 1,
  "assigneeId": 2
}
```

Response Structure

assignee The username of the user to whom the *Delivery Service Request* is assigned.

author The author of the *Delivery Service Request*

authorId The integral, unique identifier assigned to the author

changeType The change type of the *DSR*. It can be create, update, or delete....

createdAt The date and time at which the *DSR* was created, in *Traffic Ops’s Custom Date/Time Format*.

- deliveryService** The delivery service that the *DSR* is requesting to update.
- active** A boolean that defines *Active*.
- anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
- cacheurl** A *Cache URL Expression*
- Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
- ccrDnsTtl** The *DNS TTL* - named “ccrDnsTtl” for legacy reasons
- cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
- cdnName** Name of the *CDN* to which the *Delivery Service* belongs
- checkPath** A *Check Path*
- consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
- consistentHashRegex** A *Consistent Hashing Regular Expression*
- deepCachingType** The *Deep Caching* setting for this *Delivery Service*
- displayName** The *Display Name*
- dnsBypassCname** A *DNS Bypass CNAME*
- dnsBypassIp** A *DNS Bypass IP*
- dnsBypassIp6** A *DNS Bypass IPv6*
- dnsBypassTtl** The *DNS Bypass TTL*
- dscp** A *DSCP* to be used within the *Delivery Service*
- ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*
- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*
- firstHeaderRewrite** A set of *First Header Rewrite Rules*
- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*

- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*¹
- geoLimitRedirectUrl** A *Geo Limit Redirect URL*^{Page 960, 1}
- geoProvider** The *Geolocation Provider*
- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*
- httpBypassFqdn** A *HTTP Bypass FQDN*
- id** An integral, unique identifier for this *Delivery Service*
- infoUrl** An *Info URL*
- initialDispersion** The *Initial Dispersion*
- innerHeaderRewrite** A set of *Inner Header Rewrite Rules*
- ipv6RoutingEnabled** A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*
- lastHeaderRewrite** A set of *Last Header Rewrite Rules*
- lastUpdated** The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** An optional field containing the 2nd long description of this *Delivery Service*
- longDesc2** An optional field containing the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using pattern.

¹ These fields must be defined if and only if `geoLimit` is non-zero

- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*

- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- lastEditedBy** The username of user who last edited this *DSR*
- lastEditedById** The integral, unique identifier assigned to the user who last edited this *DSR*
- lastUpdated** The date and time at which the *DSR* was last updated, in *Traffic Ops*'s *Custom Date/Time Format*.
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

686: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 14:45:51
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳h7uBZHLQtRYbOSOR5AtQQRZ4uMeEWivWNT74fCf6WtLbAMwGpRrMjNmBYKduv48DEnRqG6WVM/
    ↳4nBu3AkCUqPw==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 13:45:51 GMT
Content-Length: 931
```

(continues on next page)

(continued from previous page)

```
{
  "alerts": [
    {
      "text": "deliveryservice_request was updated.",
      "level": "success"
    }
  ],
  "response": {
    "assigneeId": 2,
    "assignee": "admin",
    "authorId": 2,
    "author": "admin",
    "changeType": "update",
    "createdAt": "2020-02-23 11:06:00+00",
    "id": 1,
    "lastEditedBy": "admin",
    "lastEditedById": 2,
    "lastUpdated": "2020-02-23 13:45:51+00",
    "deliveryService": {
      "active": true,
      "anonymousBlockingEnabled": false,
      "cacheurl": null,
      "ccrDnsTtl": null,
      "cdnId": 2,
      "cdnName": "CDN-in-a-Box",
      "checkPath": null,
      "displayName": "Demo 2",
      "dnsBypassCname": null,
      "dnsBypassIp": null,
      "dnsBypassIp6": null,
      "dnsBypassTtl": null,
      "dscp": 0,
      "edgeHeaderRewrite": null,
      "firstHeaderRewrite": null,
      "geoLimit": 0,
      "geoLimitCountries": null,
      "geoLimitRedirectURL": null,
      "geoProvider": 0,
      "globalMaxMbps": null,
      "globalMaxTps": null,
      "httpBypassFqdn": null,
      "id": 1,
      "infoUrl": null,
      "initialDispersion": 1,
      "innerHeaderRewrite": null,
      "ipv6RoutingEnabled": true,
```

(continues on next page)

(continued from previous page)

```

"lastHeaderRewrite": null,
"lastUpdated": "0001-01-01 00:00:00+00",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"longDesc1": null,
"longDesc2": null,
"matchList": [
    {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": null,
"tenantId": 1,
"topology": null,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
    "http://video.demo1.mycdn.ciab.test",
    "https://video.demo1.mycdn.ciab.test"
],
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": "root",
"trResponseHeaders": null,

```

(continues on next page)

(continued from previous page)

```

        "trRequestHeaders": null,
        "consistentHashRegex": null,
        "consistentHashQueryParams": [
            "abc",
            "pdq",
            "xxx",
            "zyx"
        ],
        "maxOriginConnections": 0,
        "ecsEnabled": false
    },
    "status": "submitted"
}

```

deliveryservice_requests/{{ID}}/status

Sets the status of a *Delivery Service Request*.

PUT

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

id The integral, unique identifier assigned to the *DSR*

status The status of the *DSR* <*Delivery Service Request*>. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

687: Request Example

```

PUT /api/3.0/deliveryservice_requests/1/status HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 28

{

```

(continues on next page)

(continued from previous page)

```
"id": 1,
"status": "rejected"
}
```

Response Structure

assignee The username of the user to whom the *Delivery Service Request* is assigned.

assigneeId The integral, unique identifier of the user to whom the *Delivery Service Request* is assigned.

author The author of the *Delivery Service Request*

authorId The integral, unique identifier assigned to the author

changeType The change type of the *DSR*. It can be create, update, or delete....

createdAt The date and time at which the *DSR* was created, in *Traffic Ops's Custom Date/Time Format*.

deliveryService The delivery service that the *DSR* is requesting to update.

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named "ccrDnsTtl" for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

consistentHashRegex A *Consistent Hashing Regular Expression*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*¹

geoLimitRedirectUrl A *Geo Limit Redirect URL* Page 960, 1

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

¹ These fields must be defined if and only if `geoLimit` is non-zero

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

longDesc2 An optional field containing the 3rd long description of this *Delivery Service*

matchList The *Delivery Service*'s *Match List*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

setNumber An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

type The type of match performed using pattern.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- routingName** The *Routing Name* of this *Delivery Service*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenant** The name of the *Tenant* who owns this *Origin*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*
- id** The integral, unique identifier assigned to the *DSR*
- lastEditedBy** The username of user who last edited this *DSR*
- lastEditedById** The integral, unique identifier assigned to the user who last edited this *DSR*
- lastUpdated** The date and time at which the *DSR* was last updated, in *Traffic Ops's Custom Date/Time Format*.
- status** The status of the request. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

688: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 15:54:53
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳C8Nhciy1jv5X7CGgHwAnLp1qmLizHq+4dv1AApb3cFSz5V2dABl7+N1Z4ndzB7GertB7rNLP31pVcat8v
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 14:54:53 GMT
Content-Length: 930

{
  "alerts": [
    {
      "text": "deliveryservice_request was updated.",
      "level": "success"
    }
  ],
  "response": {
    "assigneeId": 2,
    "assignee": "admin",
    "authorId": 2,
    "author": "admin",
    "changeType": "update",
    "createdAt": "2020-02-23 11:06:00+00",
    "id": 1,
    "lastEditedBy": "admin",
    "lastEditedById": 2,
    "lastUpdated": "2020-02-23 14:54:53+00",
    "deliveryService": {
      "active": true,
      "anonymousBlockingEnabled": false,
      "cacheurl": null,
      "ccrDnsTtl": null,
      "cdnId": 2,
      "cdnName": "CDN-in-a-Box",
      "checkPath": null,
      "displayName": "Demo 2",
      "dnsBypassCname": null,
      "dnsBypassIp": null,
    }
  }
}

```

(continues on next page)

(continued from previous page)

```

"dnsBypassIp6": null,
"dnsBypassTtl": null,
"dscp": 0,
"edgeHeaderRewrite": null,
"firstHeaderRewrite": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "0001-01-01 00:00:00+00",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"longDesc1": null,
"longDesc2": null,
"matchList": [
    {
        "type": "HOST_REGEXP",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,

```

(continues on next page)

(continued from previous page)

```

        "routingName": "video",
        "signed": false,
        "sslKeyVersion": null,
        "tenantId": 1,
        "topology": null,
        "type": "HTTP",
        "typeId": 1,
        "xmlId": "demo1",
        "exampleURLs": [
            "http://video.demo1.mycdn.ciab.test",
            "https://video.demo1.mycdn.ciab.test"
        ],
        "deepCachingType": "NEVER",
        "fqPacingRate": null,
        "signingAlgorithm": null,
        "tenant": "root",
        "trResponseHeaders": null,
        "trRequestHeaders": null,
        "consistentHashRegex": null,
        "consistentHashQueryParams": [
            "abc",
            "pdq",
            "xxx",
            "zyx"
        ],
        "maxOriginConnections": 0,
        "ecsEnabled": false
    },
    "status": "rejected"
}

```

deliveryservice_stats

GET

Retrieves time-aggregated statistics on a specific *Delivery Service*.

Auth. Required Yes

Roles Required None¹

Response Type Object

¹ This endpoint respects *Tenancy*, and users whose *Tenant* does not have access to a *Delivery Service* will be unable to view the statistics of said *Delivery Service*.

Request Structure

Table 289: Request Query Parameters

Name	Required	Description
deliveryService	yes ²	Either the <i>xml_id</i> of a <i>Delivery Service</i> for which statistics will be aggregated or the integral, unique identifier of said <i>Delivery Service</i>
deliveryServiceName	yes [?]	The <i>xml_id</i> of the <i>Delivery Service</i> for which statistics will be aggregated
endDate	yes	The date and time until which statistics shall be aggregated in RFC 3339 format (with or without sub-second precision), the number of nanoseconds since the Unix Epoch, or in the same, proprietary format as the <i>lastUpdated</i> fields prevalent throughout the Traffic Ops API
exclude	no	Either “series” to omit the data series from the result, or “summary” to omit the summary data from the result - directly corresponds to fields in the <i>Response Structure</i>
interval	no	Specifies the interval within which data will be “bucketed”; e.g. when requesting data from 2019-07-25T00:00:00Z to 2019-07-25T23:59:59Z with an interval of “1m”, the resulting data series (assuming it is not excluded) should contain $24 \frac{\text{hours}}{\text{day}} \times 60 \frac{\text{minutes}}{\text{hour}} \times 1 \text{day} \times 1 \frac{\text{minute}}{\text{datapoint}} = 1440 \text{data points}$ The allowed values for this parameter are valid InfluxQL duration literal strings matching <code>^d+[mhdw]\$</code>
limit	no	A natural number indicating the maximum amount of data points should be returned in the series object
5.1. Traffic Ops API		1099
metricType	yes	The metric type being reported - one of: kbps The total traffic rate

689: Request Example

```
GET /api/3.0/deliveryservice_stats?deliveryServiceName=demo1&
→startDate=2019-07-22T17:55:00Z&endDate=2019-07-22T17:56:00.000Z&
→metricType=tps_total HTTP/1.1
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: application/json;timestamp=unix, application/json;
→timestamp=rfc;q=0.9, application/json;q=0.8, */*;q=0.7
Connection: keep-alive
Cookie: mojolicious=...
```

Content Format

It's important to note in *Request Example* the use of a complex “Accept” header. This endpoint accepts two special media types in the “Accept” header that instruct it on how to format the timestamps associated with the returned data. Specifically, Traffic Ops will recognize the special, optional, non-standard parameter of *application/json: timestamp*. The values of this parameter are restricted to one of

rfc Returned timestamps will be formatted according to **RFC 3339** (no sub-second precision).

unix Returned timestamps will be formatted as the number of nanoseconds since the Unix Epoch (midnight on January 1st 1970 UTC).

Implementation Detail

The endpoint passes back nanoseconds, specifically, because that is the form used both by InfluxDB, which is used to store the data being served, and Go's standard library. Clients may need to convert the value to match their own standard libraries - e.g. the `Date()` class in Javascript expects milliseconds.

The default behavior - when only e.g. *application/json* or **/** is given - is to use **RFC 3339** formatting. It will, however, respect quality parameters. It is suggested that clients request timestamps they can handle specifically, rather than relying on this default behavior, as it **is subject to change** and is in fact **expected to invert in the next major release** as string-based time formats become deprecated.

See also:

For more information on the “Accept” HTTP header, consult [its dedicated page on MDN](#).

² Either `deliveryServiceName` or `deliveryService` *must* be present, but if both are `deliveryServiceName` will be used and `deliveryService` will be ignored.

Response Structure

series An object containing the actual data series and information necessary for working with it.

columns This is an array of names of the columns of the data contained in the “values” array - should always be `["time", "sum_count"]`

count The number of data points contained in the “values” array

name The name of the data set. Should always match `metric.ds.1min` where `metric` is the requested `metricType`

values The actual array of data points. Each represents a length of time specified by the `interval` query parameter

time The time at which the measurement was taken. This corresponds to the *beginning* of the interval. This time comes in the format of either an [RFC 3339](#)-formatted string, or a number containing the number of nanoseconds since the Unix Epoch depending on the “Accept” header sent by the client, according to the rules outlined in [Content Format](#).

value The value of the requested `metricType` at the time given by `time`. This will always be a floating point number, unless no data is available for the data interval, in which case it will be `null`

source A legacy field meant only for plugins that override this endpoint to name themselves. Should always be “TrafficStats”.

Deprecated since version 1.4: As this has no known purpose, developers are advised it will be removed in the future.

summary An object containing summary statistics describing the data series

average The arithmetic mean of the data’s values

count The number of measurements taken within the requested timespan. This is, in general, **not** the same as the `count` field of the `series` object, as it reflects the number of underlying, un-“bucketed” data points, and is therefore dependent on the implementation of Traffic Stats.

fifthPercentile Data points with values less than or equal to this number constitute the “bottom” 5% of the data set

max The maximum value that can be found in the requested data set

min The minimum value that can be found in the requested data set

ninetyEighthPercentile Data points with values greater than or equal to this number constitute the “top” 2% of the data set

ninetyFifthPercentile Data points with values greater than or equal to this number constitute the “top” 5% of the data set

totalBytes When the `metricType` requested is `kbps`, this will contain the total number of bytes transferred by the *Delivery Service* within the requested time window. Note that fractional amounts are possible, as the data transfer rate will almost certainly not be cleanly divided by the requested time range.

totalTransactions When the `metricType` requested is `not kbps`, this will contain the total number of transactions completed by the *Delivery Service* within the requested time window. Note that fractional amounts are possible, as the transaction rate will almost certainly not be cleanly divided by the requested time range.

version A legacy field that seems to have been meant to indicate the API version used. Will always be “1.2”

Deprecated since version 1.4: As this has no known purpose, developers are advised it will be removed in the future.

690: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: zXJGjcYuu6HxWINVp8HA1gL31J3ukry5wCsTDNxtP/
    ↳waC6rSD8h10KJ9jEAtrZJ9owOSVPvKaA/2bRu/QeuCpQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 22 Jul 2019 17:57:14 GMT
Transfer-Encoding: chunked
```

(continues on next page)

(continued from previous page)

```
{ "response": {
  "series": {
    "columns": [
      "time",
      "sum_count"
    ],
    "count": 2,
    "name": "tps_total.ds.1min",
    "tags": {
      "cachegroup": "total"
    },
    "values": [
      [
        15638181000000000000,
        0
      ],
      [
        15638181600000000000,
        0
      ]
    ]
  },
  "source": "TrafficStats",
  "summary": {
    "average": 0,
    "count": 2,
    "fifthPercentile": 0,
    "max": 0,
    "min": 0,
    "ninetyEighthPercentile": 0,
    "ninetyFifthPercentile": 0,
    "totalBytes": null,
    "totalTransactions": 0
  },
  "version": "1.2"
}}
```

deliveryservices

GET

Retrieves *Delivery Services*

Auth. Required Yes

Roles Required None¹

Response Type Array

¹ Only those *Delivery Services* assigned to *Tenants* that are the requesting user's *Tenant* or children thereof will appear in the output of a GET request, and the same constraints are placed on the allowed values of the `tenantId` field of a POST request to create a new *Delivery Service*

Request Structure

Table 290: Request Query Parameters

Name	Re- quired	Description
cdn	no	Show only the <i>Delivery Services</i> belonging to the <i>CDN</i> identified by this integral, unique identifier
id	no	Show only the <i>Delivery Service</i> that has this integral, unique identifier
logsEnabled	no	Show only the <i>Delivery Services</i> that have <i>Logs Enabled</i> set or not based on this boolean
profile	no	Return only <i>Delivery Services</i> using the <i>Profile</i> that has this <i>ID</i>
tenant	no	Show only the <i>Delivery Services</i> belonging to the <i>Tenant</i> identified by this integral, unique identifier
topology	no	Show only the <i>Delivery Services</i> assigned to the <i>Topology</i> identified by this unique name
type	no	Return only <i>Delivery Services</i> of the <i>Delivery Service Type</i> identified by this integral, unique identifier
accessibleTo	no	Return the <i>Delivery Services</i> accessible from a <i>Tenant</i> or it's children identified by this integral, unique identifier
service-Category	no	Show only the <i>Delivery Services</i> belonging to the <i>Service Category</i> that has this name
xmlId	no	Show only the <i>Delivery Service</i> that has this text-based, unique identifier
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.
active	no	Show only the <i>Delivery Services</i> that have <i>Active</i> set or not based on this boolean (whether or not they are active)

Response Structure

- active** A boolean that defines *Active*.
- anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
- cacheurl** A *Cache URL Expression*
 Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
- ccrDnsTtl** The *DNS TTL* - named “ccrDnsTtl” for legacy reasons
- cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
- cdnName** Name of the *CDN* to which the *Delivery Service* belongs
- checkPath** A *Check Path*
- consistentHashRegex** A *Consistent Hashing Regular Expression*
- consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
- deepCachingType** The *Deep Caching* setting for this *Delivery Service*
- displayName** The *Display Name*
- dnsBypassCname** A *DNS Bypass CNAME*
- dnsBypassIp** A *DNS Bypass IP*
- dnsBypassIp6** A *DNS Bypass IPv6*
- dnsBypassTtl** The *DNS Bypass TTL*
- dscp** A *DSCP* to be used within the *Delivery Service*
- ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*
- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*
- firstHeaderRewrite** A set of *First Header Rewrite Rules*
- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*
- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*
- geoLimitRedirectUrl** A *Geo Limit Redirect URL*
- geoProvider** The *Geolocation Provider*
- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 The 2nd long description of this *Delivery Service*

longDesc2 the 3rd long description of this *Delivery Service*

matchList The *Delivery Service's Match List*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

setNumber An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

type The type of match performed using **pattern**.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

maxRequestHeaderBytes The *Max Request Header Bytes*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

- profileId** The *ID* of the *Profile* with which this *Delivery Service* is associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- serviceCategory** The name of the *Service Category* with which the *Delivery Service* is associated
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if *rangeRequestHandling* is set to 3.
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service's xml_id*

691: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: mCLMjvACRKHNGP/
→OSx4javkOtxxzyiDdQzsV78IamUhVmvKyKaCeOKRmpsG69w+nhh30kPZ6e9MMeJpcJSKcA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 19:04:29 GMT
Transfer-Encoding: chunked

{ "response": [{
  "active": true,
  "anonymousBlockingEnabled": false,
  "cacheurl": null,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "checkPath": null,
  "displayName": "Demo 1",
  "dnsBypassCname": null,
  "dnsBypassIp": null,
  "dnsBypassIp6": null,
  "dnsBypassTtl": null,
  "dscp": 0,
  "edgeHeaderRewrite": null,
  "firstHeaderRewrite": null,
  "geoLimit": 0,
  "geoLimitCountries": null,
  "geoLimitRedirectURL": null,
  "geoProvider": 0,
  "globalMaxMbps": null,
  "globalMaxTps": null,
  "httpBypassFqdn": null,
  "id": 1,
  "infoUrl": null,
  "initialDispersion": 1,
  "innerHeaderRewrite": null,
  "ipv6RoutingEnabled": true,
  "lastHeaderRewrite": null,
  "lastUpdated": "2019-05-15 14:32:05+00",
  "logsEnabled": true,
  "longDesc": "Apachecon North America 2018",
  "longDesc1": null,
  "longDesc2": null,
  "matchList": [
```

(continues on next page)

(continued from previous page)

```

    {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": null,
"tenantId": 1,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
    "http://video.demo1.mycdn.ciab.test",
    "https://video.demo1.mycdn.ciab.test"
],
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": "root",
"trResponseHeaders": null,
"trRequestHeaders": null,
"consistentHashRegex": null,
"consistentHashQueryParams": [
    "abc",
    "pdq",
    "xxx",
    "zyx"
],

```

(continues on next page)

(continued from previous page)

```
"maxOriginConnections": 0,
"maxRequestHeaderBytes": 131072,
"ecsEnabled": false,
"rangeSliceBlockSize": null,
"topology": null
"serviceCategory": null
}}}
```

POST

Allows users to create *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 960, 1}

Response Type Array

Request Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*²

geoLimitRedirectUrl A *Geo Limit Redirect URL*[?]

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

longDesc2 An optional field containing the 3rd long description of this *Delivery Service*

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

maxRequestHeaderBytes The *Max Request Header Bytes*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

² These fields must be defined if and only if `geoLimit` is non-zero

- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileId** An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- serviceCategory** The name of the *Service Category* with which the *Delivery Service* is associated - or null if there is to be no such category
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if *rangeRequestHandling* is set to 3. It can only be between (inclusive) 262144 (256KB) - 33554432 (32MB).
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*

692: Request Example

```
POST /api/3.0/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 761
Content-Type: application/json

{
  "active": false,
  "anonymousBlockingEnabled": false,
  "cdnId": 2,
  "deepCachingType": "NEVER",
  "displayName": "test",
  "dscp": 0,
  "ecsEnabled": true,
  "geoLimit": 0,
  "geoProvider": 0,
  "initialDispersion": 1,
  "ipv6RoutingEnabled": false,
  "logsEnabled": true,
  "longDesc": "A Delivery Service created expressly for API_
↪documentation examples",
  "missLat": 0,
  "missLong": 0,
  "maxOriginConnections": 0,
  "maxRequestHeaderBytes": 131072,
  "multiSiteOrigin": false,
  "orgServerFqdn": "http://origin.infra.ciab.test",
  "protocol": 0,
  "qstringIgnore": 0,
  "rangeRequestHandling": 0,
  "regionalGeoBlocking": false,
  "routingName": "test",
  "serviceCategory": null,
  "signed": false,
  "tenant": "root",
  "tenantId": 1,
  "typeId": 1,
  "xmlId": "test"
}
```

Response Structure

- active** A boolean that defines *Active*.
- anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
- cacheurl** A *Cache URL Expression*
 Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
- ccrDnsTtl** The *DNS TTL* - named “ccrDnsTtl” for legacy reasons
- cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
- cdnName** Name of the *CDN* to which the *Delivery Service* belongs
- checkPath** A *Check Path*
- consistentHashRegex** A *Consistent Hashing Regular Expression*
- consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
- deepCachingType** The *Deep Caching* setting for this *Delivery Service*
- displayName** The *Display Name*
- dnsBypassCname** A *DNS Bypass CNAME*
- dnsBypassIp** A *DNS Bypass IP*
- dnsBypassIp6** A *DNS Bypass IPv6*
- dnsBypassTtl** The *DNS Bypass TTL*
- dscp** A *DSCP* to be used within the *Delivery Service*
- ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*
- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*
- firstHeaderRewrite** A set of *First Header Rewrite Rules*
- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*
- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*
- geoLimitRedirectUrl** A *Geo Limit Redirect URL*
- geoProvider** The *Geolocation Provider*
- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 The 2nd long description of this *Delivery Service*

longDesc2 the 3rd long description of this *Delivery Service*

matchList The *Delivery Service's Match List*

- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
- setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
- type** The type of match performed using **pattern**.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

maxRequestHeaderBytes The *Max Request Header Bytes*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

- profileId** The *ID* of the *Profile* with which this *Delivery Service* is associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- serviceCategory** The name of the *Service Category* with which the *Delivery Service* is associated
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if *rangeRequestHandling* is set to 3.
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*

693: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: SVveQ5hGwfPv8N5APUskwLOzwrTUVA+z8wuFLsSLCr1/
→vVnFJJ0VQOGMUctg1NbqhAuQ795MJmuuAaAwR8dSOQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 19 Nov 2018 19:45:49 GMT
Content-Length: 1404
```

```
{ "alerts": [
  {
    "text": "Deliveryservice creation was successful.",
    "level": "success"
  }
],
"response": [
  {
    "active": false,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "test",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "firstHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 2,
    "infoUrl": null,
    "initialDispersion": 1,
    "innerHeaderRewrite": null,
    "ipv6RoutingEnabled": false,
```

(continues on next page)

(continued from previous page)

```

    "lastHeaderRewrite": null,
    "lastUpdated": "2018-11-19 19:45:49+00",
    "logsEnabled": true,
    "longDesc": "A Delivery Service created expressly for API_
→documentation examples",
    "longDesc1": null,
    "longDesc2": null,
    "matchList": [
        {
            "type": "HOST_REGEX",
            "setNumber": 0,
            "pattern": ".*\\.test\\.\\.*"
        }
    ],
    "maxDnsAnswers": null,
    "maxOriginConnections": 0,
    "maxRequestHeaderBytes": 131072,
    "midHeaderRewrite": null,
    "missLat": -1,
    "missLong": -1,
    "multiSiteOrigin": false,
    "originShield": null,
    "orgServerFqdn": "http://origin.infra.ciab.test",
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": 0,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "test",
    "serviceCategory": null,
    "signed": false,
    "sslKeyVersion": null,
    "tenantId": 1,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "test",
    "exampleURLs": [
        "http://test.test.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "signingAlgorithm": null,
    "tenant": "root",

```

(continues on next page)

(continued from previous page)

```

    "ecsEnabled": true,
    "rangeSliceBlockSize": null,
    "topology": null
  }
}]}
```

deliveryservices/dnsseckey/generate

POST

Generates ZSK and KSK keypairs for a CDN and all associated *Delivery Services*.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

effectiveDate UNIX epoch start date for the signing keys

key Name of the CDN

kskExpirationDays Expiration (in days) for the KSKs

name Domain name used by the CDN

ttl Time for which the keypairs shall remain valid

zskExpirationDays Expiration (in days) for the ZSKs

Response Structure

694: Response Example

```
{
  "response": "Successfully created dnssec keys for cdn1"
}
```

deliveryservices/{ID}

PUT

Allows users to edit an existing *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type **NOT PRESENT** - Despite returning a 200 OK response (rather than e.g. a 204 NO CONTENT response), this endpoint does **not** return a representation of the modified resource in its payload, and instead returns nothing - not even a success message.

Request Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

Note: If the Delivery Service has SSL Keys, then cdnId is not allowed to change as that would invalidate the SSL Key

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

¹ Only those *Delivery Services* assigned to *Tenants* that are the requesting user’s *Tenant* or children thereof will appear in the output of a GET request, and the same constraints are placed on the allowed values of the tenantId field of a PUT request to update a new *Delivery Service*. Furthermore, the only *Delivery Services* a user may delete are those assigned to a *Tenant* that is either the same *Tenant* as the user’s *Tenant*, or a descendant thereof.

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*²

geoLimitRedirectUrl A *Geo Limit Redirect URL*[?]

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 An optional field containing the 2nd long description of this *Delivery Service*

longDesc2 An optional field containing the 3rd long description of this *Delivery Service*

² These fields must be defined if and only if `geoLimit` is non-zero

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileId An optional *ID* of the *Profile* with which this *Delivery Service* will be associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

routingName The *Routing Name* of this *Delivery Service*

Note: If the Delivery Service has SSL Keys, then routingName is not allowed to change as that would invalidate the SSL Key

signed true if and only if signingAlgorithm is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*

rangeSliceBlockSize An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if rangeRequestHandling is set to 3. It can only be between (inclusive) 262144 (256KB) - 33554432 (32MB).

sslKeyVersion This integer indicates the *SSL Key Version*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

topology The unique name of the *Topology* that this *Delivery Service* is assigned to

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

Note: While this field **must** be present, it is **not** allowed to change; this must be the same as the `xml_id` the *Delivery Service* already has. This should almost never be different from the *Delivery Service*'s `displayName`.

695: Request Example

```
PUT /api/3.0/deliveryservices/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 761
Content-Type: application/json

{
  "active": true,
  "anonymousBlockingEnabled": false,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "deepCachingType": "NEVER",
  "displayName": "demo",
  "dscp": 0,
  "ecsEnabled": true,
  "geoLimit": 0,
  "geoProvider": 0,
  "initialDispersion": 1,
  "ipv6RoutingEnabled": false,
  "lastUpdated": "2018-11-14 18:21:17+00",
  "logsEnabled": true,
  "longDesc": "A Delivery Service created expressly for API_
↪documentation examples",
  "missLat": -1,
  "missLong": -1,
  "multiSiteOrigin": false,
  "orgServerFqdn": "http://origin.infra.ciab.test",
  "protocol": 0,
  "qstringIgnore": 0,
  "rangeRequestHandling": 0,
```

(continues on next page)

(continued from previous page)

```

    "regionalGeoBlocking": false,
    "routingName": "video",
    "signed": false,
    "tenant": "root",
    "tenantId": 1,
    "typeId": 1,
    "xmlId": "demo1"
  }

```

Response Structure

696: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: z4PhNX7vuL3xVChQ1m2AB9Yg5AULVxXcg/
    ↳SpIdNs6c5H0NE8XYXysP+DGNKHfuwvY7kxvUdBeoGlODJ6+SfaPg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 20 Nov 2018 14:12:25 GMT
Content-Length: 0
Content-Type: text/plain; charset=utf-8

```

DELETE

Deletes the target *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 960, 1}

Response Type undefined

Request Structure

Table 291: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> to be deleted

697: Request Example

```
DELETE /api/3.0/deliveryservices/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

698: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: w9NlQpJJEl56r6iYq/
    ↳fk8o5WfAXeUS5XR9yDHvKUgPO8lYEo8YyftaSF0MPFseeOk60dk6kQo+MLYTDIAhhRxw==
X-Server-Name: traffic_ops_golang/
Date: Tue, 20 Nov 2018 14:56:37 GMT
Content-Length: 57

{ "alerts": [
  {
    "text": "ds was deleted.",
    "level": "success"
  }
]}
```

`deliveryservices/{{ID}}/capacity`

See also:

Health Protocol

GET

Retrieves the usage percentages of a servers associated with a *Delivery Service*

Auth. Required Yes

Roles Required None¹

Response Type Object

Request Structure

Table 292: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the <i>Delivery Service</i> of interest

Response Structure

availablePercent The percent of servers assigned to this *Delivery Service* that is available - the allowed traffic level in terms of data per time period for all *cache servers* that remains unused

unavailablePercent The percent of servers assigned to this *Delivery Service* that is unavailable - the allowed traffic level in terms of data per time period for all *cache servers* that can't be used because the servers are deemed unhealthy

utilizedPercent The percent of servers assigned to this *Delivery Service* that is currently in use - the allowed traffic level in terms of data per time period that is currently devoted to servicing requests

maintenancePercent The percent of servers assigned to this *Delivery Service* that is unavailable due to server maintenance - the allowed traffic level in terms of data per time period that is unavailable because servers have intentionally been marked offline by administrators

699: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
```

(continues on next page)

¹ Users will only be able to see capacity details for the *Delivery Services* their *Tenant* is allowed to see.

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 14:41:27 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→++dFR9V1c60CHGNwMjX6JSFEjHreXcL4QnhT03hiv04ByY379aLpL40rOzX2bPgJgpR94+f6jZ0+iDIyT
Content-Length: 134

{ "response": {
  "availablePercent": 99.9993696969697,
  "unavailablePercent": 0,
  "utilizedPercent": 0.00063030303030303,
  "maintenancePercent": 0
}}
```

deliveryservices/{{ID}}/health

See also:

Health Protocol

GET

Retrieves the health of all *Cache Groups* assigned to a particular *Delivery Service*

Auth. Required Yes

Roles Required None¹

Response Type Object

¹ Users will only be able to see *Cache Group* health details for the *Delivery Services* their *Tenant* is allowed to see.

Request Structure

Table 293: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the Delivery service for which <i>Cache Groups</i> will be displayed

Response Structure

cachegroups An array of objects that represent the health of each *Cache Group* assigned to this *Delivery Service*

name A string that is the *name of the Cache Group* represented by this object

offline The number of OFFLINE *cache servers* within this *Cache Group*

online The number of ONLINE *cache servers* within this *Cache Group*

totalOffline Total number of OFFLINE *cache servers* assigned to this *Delivery Service*

totalOnline Total number of ONLINE *cache servers* assigned to this *Delivery Service*

700: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 14:43:43 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→KpXViXeAgch58ueQqdyU8NuINBw1EUedE6Rv2ewcLUajJp6kowdbVynpwW7XiSvAyHdtClIOuT30khIm
Content-Length: 115

{ "response": {
  "totalOffline": 0,
```

(continues on next page)

(continued from previous page)

```

    "totalOnline": 1,
    "cachegroups": [
      {
        "offline": 0,
        "name": "CDN_in_a_Box_Edge",
        "online": 1
      }
    ]
  }
}
```

deliveryservices/{{ID}}/regexes

GET

Retrieves routing regular expressions for a specific *Delivery Service*.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 294: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected

Table 295: Request Query Parameters

Name	Re- quired	Description
id	no	Show only the <i>Delivery Service</i> regular expression that has this integral, unique identifier
limit	no	Choose the maximum number of results to return
off- set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>n</i> th page of results, where “ <i>n</i> ” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

¹ Users will only be able to view and create regular expressions for the *Delivery Services* their *Tenant* is allowed to see.

701: Request Example

```
GET /api/3.0/deliveryservices/1/regexes HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

id The integral, unique identifier of this regular expression

pattern The actual regular expression - \s are escaped

setNumber The order in which the regular expression is evaluated against requests

type The integral, unique identifier of the *Type* of this regular expression

typeName The *Type* of regular expression - determines that against which it will be evaluated

702: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: fw9Fde4WRpp2ShRAC41P9s/PhU71LI/
↳SEzHgYjGqfzhk45wq0kpaWy76JvPfLpowY8eDTp8Y8TL5rNGEc+bM+A==
X-Server-Name: traffic_ops_golang/
Date: Tue, 27 Nov 2018 20:56:43 GMT
Content-Length: 100

{ "response": [
  {
    "id": 1,
    "type": 31,
    "typeName": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
]
}]
```

POST

Creates a routing regular expression for a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 960, 1}

Response Type Object

Request Structure

Table 296: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected

pattern The actual regular expression

Warning: Be sure that \s are escaped, or the expression may not work as intended!

setNumber The order in which this regular expression should be checked

type The integral, unique identifier of a routing regular expression type

703: Request Example

```
POST /api/3.0/deliveryservices/1/regexes HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 55
Content-Type: application/json

{
  "pattern": ".*\\.foo-bar\\.\\.\\.\"",
  "type": 31,
  "setNumber": 1
}
```

Response Structure

- id** The integral, unique identifier of this regular expression
- pattern** The actual regular expression - \s are escaped
- setNumber** The order in which the regular expression is evaluated against requests
- type** The integral, unique identifier of the type of this regular expression
- typeName** The type of regular expression - determines that against which it will be evaluated

704: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: kS5dRzAhFKE7vfzHK7XVIwpMOjztksk9MU+qtj5YU/
  ↳1oxVHmqNbJ12Fe00IJsZJCXbYlnBS04sCI95Sz5wed1Q==
X-Server-Name: traffic_ops_golang/
Date: Wed, 28 Nov 2018 17:00:42 GMT
Content-Length: 188

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

        "text": "Delivery service regex creation was successful.",
        "level": "success"
    }
],
"response": {
    "id": 2,
    "type": 31,
    "typeName": "HOST_REGEX",
    "setNumber": 1,
    "pattern": ".*\\.foo-bar\\.\\.\\.*"
}}

```

deliveryservices/{{ID}}/regexes/{{rID}}

PUT

Updates a routing regular expression.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type Object

Request Structure

Table 297: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected
rID	The integral, unique identifier of the routing regular expression being inspected

pattern The actual regular expression

Warning: Be sure that \s are escaped, or the expression may not work as intended!

setNumber The order in which this regular expression should be checked

type The integral, unique identifier of a routing regular expression type

¹ Users will only be able to view, delete and update regular expressions for the *Delivery Services* their *Tenant* is allowed to see.

705: Request Example

```
PUT /api/3.0/deliveryservices/1/regexes/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 55
Content-Type: application/json

{
  "pattern": ".*\\.foo-bar\\.\\.\\.\"",
  "type": 33,
  "setNumber": 1
}
```

Response Structure

- id** The integral, unique identifier of this regular expression
- pattern** The actual regular expression - \s are escaped
- setNumber** The order in which the regular expression is evaluated against requests
- type** The integral, unique identifier of the type of this regular expression
- typeName** The type of regular expression - determines that against which it will be evaluated

706: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: kS5dRzAhFKE7vfzHK7XVIwpMOjztksk9MU+qtj5YU/
  ↳1oxVHmqNbJ12Fe00IJsZJCXbYlnBS04sCI95Sz5wed1Q==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 17:54:58 GMT
Content-Length: 188

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

        "text": "Delivery service regex creation was successful.",
        "level": "success"
    }
],
"response": {
    "id": 2,
    "type": 33,
    "typeName": "PATH_REGEX",
    "setNumber": 1,
    "pattern": ".*\\.foo-bar\\.\\.*"
}}

```

DELETE

Deletes a routing regular expression.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 960, 1}

Response Type undefined

Request Structure

Table 298: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected
rID	The integral, unique identifier of the routing regular expression being inspected

707: Request Example

```
DELETE /api/3.0/deliveryservices/1/regexes/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

708: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 8oEa78x7f/o39LIS98W6G+UqE6cX/
    ↳Iw4v3mMHvbAsliWHALuDYZRz3V0tA6jzfGQKpB040m8qaVG+zWRrBVoCmQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 18:44:00 GMT
Content-Length: 76

{ "alerts": [
  {
    "text": "deliveryservice_regex was deleted.",
    "level": "success"
  }
]}
```

deliveryservices/{{ID}}/routing

GET

Retrieves the aggregated routing percentages for a given *Delivery Service*. This is accomplished by polling stats from all online Traffic Routers via the */crs/stats* route.

Auth. Required Yes

Roles Required None¹

¹ Users will only be able to view routing details for the *Delivery Services* their *Tenant* is allowed to see.

Response Type Object

Note: Only HTTP or DNS *Delivery Services* can be requested.

Request Structure

Table 299: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the <i>Delivery Service</i> of interest

709: Request Example

```
GET /api/3.0/deliveryservices/1/routing HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cz** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by a *Coverage Zone File*
- deepCz** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by a *Deep Coverage Zone File*
- dsr** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by sending the client to an overflow *Delivery Service*
- err** The percent of requests to online Traffic Routers for this *Delivery Service* that resulted in an error
- fed** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by sending the client to a federated CDN
- geo** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied using 3rd party geographic IP mapping
- miss** The percent of requests to online Traffic Routers for this *Delivery Service* that could not be satisfied
- regionalAlternate** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by sending the client to the alternate, Regional Geo-blocking URL
- regionalDenied** The percent of requests to online Traffic Routers for this *Delivery Service* that were denied due to geographic location policy

staticRoute The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied with *Static DNS Entries*

710: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Fri, 30 Nov 2018 15:08:07 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: UgPziRC/5u4+CfkZ9xm0EkEzjjJVu6cwBrFd/n3xH/
→ZmlkaXkQaa1y4+B7DyE46vxFLYE0OD0cQchyn7JkoQOg==
Content-Length: 132

{ "response": {
  "cz": 79,
  "deepCz": 0.50,
  "dsr": 0,
  "err": 0,
  "fed": 0.25,
  "geo": 20,
  "miss": 0.25,
  "regionalAlternate": 0,
  "regionalDenied": 0,
  "staticRoute": 0
}}
```

deliveryservices/{{ID}}/safe

PUT

Allows a user to edit metadata fields of a *Delivery Service*.

Auth. Required Yes

Roles Required None¹

Response Type Array

¹ Only those *Delivery Services* assigned to *Tenants* that are the requesting user's *Tenant* or children thereof may be modified with this endpoint.

Request Structure

Table 300: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being modified

displayName A string that is the *Display Name*

infoUrl An optional² string containing the *Info URL*

longDesc An optional² string containing the *Long Description* of this *Delivery Service*

longDesc1 An optional² string containing the 2nd long description of this *Delivery Service*

711: Request Example

```
PUT /api/3.0/deliveryservices/1/safe HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 132

{
  "displayName": "test",
  "infoUrl": "this is not even a real URL",
  "longDesc": "longDesc1 is implicitly set to null in this example"
}
```

Response Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

cacheurl A *Cache URL Expression*

Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

² If these fields are not present in the request body they are *implicitly set to null*.

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*

geoLimitRedirectUrl A *Geo Limit Redirect URL*

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- longDesc1** The 2nd long description of this *Delivery Service*
- longDesc2** the 3rd long description of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using **pattern**.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** The *ID* of the *Profile* with which this *Delivery Service* is associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

signed true if and only if `signingAlgorithm` is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*

rangeSliceBlockSize An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if `rangeRequestHandling` is set to 3.

sslKeyVersion This integer indicates the *SSL Key Version*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

topology The unique name of the *Topology* that this *Delivery Service* is assigned to

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

712: Response Example

```
HTTP/1.1 200 OK
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 10 Feb 2020 16:33:03.
→GMT; Max-Age=3600; HttpOnly
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Feb 2020 15:33:03 GMT
Content-Length: 853

{ "alerts": [
  {
    "text": "Delivery Service safe update successful.",
    "level": "success"
  }
],
"response": [
  {
    "active": true,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
```

(continues on next page)

(continued from previous page)

```

"cdnId": 2,
"cdnName": "CDN-in-a-Box",
"checkPath": null,
"displayName": "test",
"dnsBypassCname": null,
"dnsBypassIp": null,
"dnsBypassIp6": null,
"dnsBypassTtl": null,
"dscp": 0,
"edgeHeaderRewrite": null,
"firstHeaderRewrite": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": "this is not even a real URL",
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "2020-02-10 15:33:03+00",
"logsEnabled": true,
"longDesc": "longDesc1 is implicitly set to null in this_
→example",
"longDesc1": null,
"longDesc2": null,
"matchList": [
    {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,

```

(continues on next page)

(continued from previous page)

```

    "profileName": null,
    "protocol": 2,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": 1,
    "tenantId": 1,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false,
    "rangeSliceBlockSize": null,
    "topology": null
}
}]

```

`deliveryservices/{{id}}/server_types/{{type}}/metric_types/start_date/{{start}}/end_date/{{end}}`

Danger: This endpoint doesn't appear to work, and so its use is strongly discouraged! The below documentation cannot be verified, therefore it may be inaccurate and/or incomplete!

GET

Retrieves detailed and summary metrics for Mid-tier and Edge-tier caches assigned to a *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 301: Request Path Parameters

Name	Re-quired	Description
id	yes	The delivery service id.
server_types	yes	EDGE or MID.
metric_types	yes	One of the following: “kbps”, “tps”, “tps_2xx”, “tps_3xx”, “tps_4xx”, “tps_5xx”.
start_date	yes	UNIX time
end_date	yes	UNIX time

Table 302: Request Query Parameters

Name	Required	Description
stats	no	Flag used to return only summary metrics

Response Structure

Parameter	Type	Description
stats	hash	
>>count	int	
>>98thPercentile	number	
>>min	number	
>>max	number	
>>5thPercentile	number	
>>95thPercentile	number	
>>median	number	
>>mean	number	
>>stddev	number	
>>sum	number	
data	array	
>>item	array	
>>time	number	
>>value	number	
label	string	

713: Response Example

```
{ "response": [
  {
    "stats": {
      "count": 988,
      "98thPercentile": 16589105.55958,
      "min": 3185442.975,
      "max": 17124754.257,
      "5thPercentile": 3901253.95445,
      "95thPercentile": 16013210.034,
      "median": 8816895.576,
      "mean": 8995846.31741194,
      "stddev": 3941169.83683573,
      "sum": 333296106.060112
    },
    "data": [
      [
        1414303200000,
        12923518.466
      ],
      [
        1414303500000,
        12625139.65
      ]
    ]
  }
],
```

(continues on next page)

(continued from previous page)

```

    "label": "MID Kbps"
  }
}]}
```

deliveryservices/{{ID}}/servers

Caution: It's often much easier to use *deliveryservices/{{xml_id}}/servers* instead

GET

Retrieves properties of Edge-Tier servers assigned to a *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 303: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the Delivery service for which servers will be displayed

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId An integral, unique identifier the CDN to which the server belongs

cdnName The name of the CDN to which the server belongs

domainName The domain name part of the FQDN of the server

guid Optionally represents an identifier used to uniquely identify the server

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS requests - 443 in most cases

id An integral, unique identifier for the server

iloIpAddress The IPv4 address of the lights-out-management port¹

iloIpGateway The IPv4 gateway address of the lights-out-management port^{Page 960, 1}

iloIpNetmask The IPv4 subnet mask of the lights-out-management port^{Page 960, 1}

iloPassword The password of the of the lights-out-management user - displays as ***** unless the requesting user has the ‘admin’ role)^{Page 960, 1}

iloUsername The user name for lights-out-management^{Page 960, 1}

interfaces An array of interface and IP address information

max_bandwidth The maximum allowed bandwidth for this interface to be considered “healthy” by Traffic Monitor. This has no effect if *monitor* is not true. Values are in kb/s. The value *null* means “no limit”.

monitor A boolean indicating if Traffic Monitor should monitor this interface

mtu The MTU to configure for *interfaceName*

See also:

[The Wikipedia article on Maximum Transmission Unit](#)

name The network interface name used by the server.

ipAddresses An array of the IP address information for the interface

address The IPv4 or IPv6 address and subnet mask of the server - applicable for the interface name

gateway The IPv4 or IPv6 gateway address of the server - applicable for the interface name

service_address A boolean determining if content will be routed to the IP address

lastUpdated The time and date at which this server was last updated, in *Traffic Ops’s Custom Date/Time Format*

mgmtIpAddress The IPv4 address of the server’s management port

mgmtIpGateway The IPv4 gateway of the server’s management port

mgmtIpNetmask The IPv4 subnet mask of the server’s management port

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status (will be empty if not offline)

¹ See [the Wikipedia article on Out-of-Band Management](#) for more information.

physLocation The name of the *Physical Location* at which the server resides

physLocationId An integral, unique identifier for the *Physical Location* at which the server resides

profile The *Name* of the *Profile* assigned to this server

profileDesc A *Description* of the *Profile* assigned to this server

profileId The *ID* of the *Profile* assigned to this server

rack A string indicating “rack” location

routerHostName The human-readable name of the router

routerPortName The human-readable name of the router port

status The Status of the server

See also:

Health Protocol

statusId An integral, unique identifier for the status of the server

See also:

Health Protocol

tcpPort The default port on which the main application listens for incoming TCP connections - 80 in most cases

type The name of the type of this server

typeId An integral, unique identifier for the type of this server

updPending true if the server has updates pending, false otherwise

714: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: MaIva080Sjysr4bCkuXFEMf3o6mOqga1aM4IHN/
    ↳tcP2aa1iXEmA5IrHB7DaqNX/2vGHLXvN+01FEAR/lRNqr1w==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:28:23 GMT
Content-Length: 891

{ "response": [
```

(continues on next page)

(continued from previous page)

```
{
  "cachegroup": "CDN_in_a_Box_Edge",
  "cachegroupId": 7,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "domainName": "infra.ciab.test",
  "guid": null,
  "hostName": "edge",
  "httpsPort": 443,
  "id": 10,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "lastUpdated": "2018-11-14 21:08:44+00",
  "mgmtIpAddress": "",
  "mgmtIpGateway": "",
  "mgmtIpNetmask": "",
  "offlineReason": "",
  "physLocation": "Apachecon North America 2018",
  "physLocationId": 1,
  "profile": "ATS_EDGE_TIER_CACHE",
  "profileDesc": "Edge Cache - Apache Traffic Server",
  "profileId": 9,
  "rack": "",
  "routerHostName": "",
  "routerPortName": "",
  "status": "REPORTED",
  "statusId": 3,
  "tcpPort": 80,
  "type": "EDGE",
  "typeId": 11,
  "updPending": false,
  "interfaces": [{
    "ipAddresses": [
      {
        "address": "172.16.239.100",
        "gateway": "172.16.239.1",
        "service_address": true
      },
      {
        "address": "fc01:9400:1000:8::100",
        "gateway": "fc01:9400:1000:8::1",
        "service_address": true
      }
    ]
  }]
}
```

(continues on next page)

(continued from previous page)

```

    ],
    "max_bandwidth": 0,
    "monitor": true,
    "mtu": 1500,
    "name": "eth0"
  }]
}
[]}

```

deliveryservices/{{ID}}/servers/eligible

Caution: This endpoint may not work as advertised, and its use is therefore discouraged!

GET

Retrieves properties of *Edge-tier cache servers* eligible for assignment to a particular *Delivery Service*. Eligibility is determined based on the following properties:

- The name of the server's *Type* must match one of the glob patterns `EDGE*`, `ORG*`
- The server and *Delivery Service* must belong to the same CDN
- If the *Delivery Service* has *Required Capabilities*, an *Edge-tier cache server* must have all of those defined capabilities

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 304: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the Delivery service for which servers will be displayed

Response Structure

cachegroup A string which is the *Name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId An integral, unique identifier the CDN to which the server belongs

cdnName The name of the CDN to which the server belongs

domainName The domain name part of the FQDN of the server

guid Optionally represents an identifier used to uniquely identify the server

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS requests - 443 in most cases

id An integral, unique identifier for the server

iloIpAddress The IPv4 address of the lights-out-management port¹

iloIpGateway The IPv4 gateway address of the lights-out-management port^{Page 960, 1}

iloIpNetmask The IPv4 subnet mask of the lights-out-management port^{Page 960, 1}

iloPassword The password of the of the lights-out-management user - displays as ***** unless the requesting user has the ‘admin’ role)^{Page 960, 1}

iloUsername The user name for lights-out-management^{Page 960, 1}

interfaces An array of interface and IP address information

max_bandwidth The maximum allowed bandwidth for this interface to be considered “healthy” by Traffic Monitor. This has no effect if *monitor* is not true. Values are in kb/s. The value *null* means “no limit”.

monitor A boolean indicating if Traffic Monitor should monitor this interface

mtu The MTU to configure for *interfaceName*

See also:

[The Wikipedia article on Maximum Transmission Unit](#)

name The network interface name used by the server.

ipAddresses An array of the IP address information for the interface

¹ See [the Wikipedia article on Out-of-Band Management](#) for more information.

- address** The IPv4 or IPv6 address and subnet mask of the server - applicable for the interface name
- gateway** The IPv4 or IPv6 gateway address of the server - applicable for the interface name
- service_address** A boolean determining if content will be routed to the IP address
- lastUpdated** The time and date at which this server was last updated, in *Traffic Ops's Custom Date/Time Format*
- mgmtIpAddress** The IPv4 address of the server's management port
- mgmtIpGateway** The IPv4 gateway of the server's management port
- mgmtIpNetmask** The IPv4 subnet mask of the server's management port
- offlineReason** A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status (will be empty if not offline)
- physLocation** The name of the *Physical Location* at which the server resides
- physLocationId** An integral, unique identifier for the *Physical Location* at which the server resides
- profile** The *Name* of the *Profile* assigned to this server
- profileDesc** A *Description* of the *Profile* assigned to this server
- profileId** The *ID* of the *Profile* assigned to this server
- rack** A string indicating "rack" location
- routerHostName** The human-readable name of the router
- routerPortName** The human-readable name of the router port
- status** The Status of the server
- See also:
Health Protocol
- statusId** An integral, unique identifier for the status of the server
- See also:
Health Protocol
- tcpPort** The default port on which the main application listens for incoming TCP connections - 80 in most cases
- type** The name of the *Type* of this server
- typeId** An integral, unique identifier for the *Type* of this server
- updPending** true if the server has updates pending, false otherwise

715: Response Example

```
{ "response": [
  {
    "cachegroup": "CDN_in_a_Box_Edge",
    "cachegroupId": 7,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "domainName": "infra.ciab.test",
    "guid": null,
    "hostName": "edge",
    "httpsPort": 443,
    "id": 10,
    "iloIpAddress": "",
    "iloIpGateway": "",
    "iloIpNetmask": "",
    "iloPassword": "",
    "iloUsername": "",
    "lastUpdated": "2018-10-30 16:01:12+00",
    "mgmtIpAddress": "",
    "mgmtIpGateway": "",
    "mgmtIpNetmask": "",
    "offlineReason": "",
    "physLocation": "Apachecon North America 2018",
    "physLocationId": 1,
    "profile": "ATS_EDGE_TIER_CACHE",
    "profileDesc": "Edge Cache - Apache Traffic Server",
    "profileId": 9,
    "rack": "",
    "routerHostName": "",
    "routerPortName": "",
    "status": "REPORTED",
    "statusId": 3,
    "tcpPort": 80,
    "type": "EDGE",
    "typeId": 11,
    "updPending": false,
    "interfaces": [{
      "ipAddresses": [
        {
          "address": "172.16.239.100",
          "gateway": "172.16.239.1",
          "service_address": true
        }
      ],
      {
        "address": "fc01:9400:1000:8::100",
        "gateway": "fc01:9400:1000:8::1",

```

(continues on next page)

(continued from previous page)

```

        "service_address": true
    }
],
"max_bandwidth": 0,
"monitor": true,
"mtu": 1500,
"name": "eth0"
}]
}
}]

```

`deliveryservices/{{ID}}/urlkeys`

GET

See also:

`deliveryservices/xmlId/{{xmlid}}/urlkeys`

Retrieves URL signing keys for a *Delivery Service*.

Caution: This method will return the *Delivery Service*'s **PRIVATE** URL signing keys! Be wary of using this endpoint and **NEVER** share the output with anyone who would be unable to see it on their own.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 305: Request Path Parameters

Name	Description
id	Filter for the <i>Delivery Service</i> identified by this integral, unique identifier

716: Request Example

```

GET /api/3.0/deliveryservices/1/urlkeys HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*

```

(continues on next page)

(continued from previous page)

```
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

key<N> The private URL signing key for this *Delivery Service* as a base-64-encoded string, where <N> is the “generation” of the key e.g. the first key will always be named "key0". Up to 16 concurrent generations are retained at any time (<N> is always on the interval [0,15])

717: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 16:34:56
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: cTc50PE3hM+CiyQPCy36zD2tsQcfkvIqQ7/
    ↳D82WGMWHm+ACW3YbcKhgPnSQU6+Tuj4jya52Kx9+nw5+OonFvPQ==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 15:34:56 GMT
Content-Length: 533

{
  "response": {
    "key0": "...",
    "key1": "...",
    "key2": "...",
    "key3": "...",
    "key4": "...",
    "key5": "...",
    "key6": "...",
    "key7": "...",
    "key8": "...",
    "key9": "...",
    "key10": "...",
    "key11": "...",
    "key12": "...",
    "key13": "...",
    "key14": "...",
```

(continues on next page)

(continued from previous page)

```

    "key15": "...",
  }
}
```

deliveryservices_regexes

GET

Retrieves routing regular expressions for all *Delivery Services*.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

No parameters available

Response Structure

dsName The name of the *Delivery Service* represented by this object

regexes An array of objects that represent various routing regular expressions used by dsName

pattern The actual regular expression - \s are escaped

setNumber The order in which the regular expression is evaluated against requests

type The type of regular expression - determines that against which it will be evaluated

718: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

¹ If tenancy is used, then users (regardless of role) will only be able to see the routing regular expressions used by *Delivery Services* their tenant has permissions to see.

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +2MI+Q/NJqTizlMR/MhPAL+yu6/z/
Yqvo5fD08F593RM0mK6dX/A14wARbEG+HQaJNgSCRPSiLVATusrmnnCMA==
X-Server-Name: traffic_ops_golang/
Date: Tue, 27 Nov 2018 19:22:59 GMT
Content-Length: 110

{ "response": [
  {
    "regexes": [
      {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
      }
    ],
    "dsName": "demo1"
  }
]}
```

deliveryservices/request

Note: This route does NOT do the same thing as *POST deliveryservice_requests*.

Deprecated since version ATCv6: This endpoint does not appear in Traffic Ops API version 4.0 - released with Apache Traffic Control version 6.0 - or later.

POST

Submits an emailed requesting that a *Delivery Service* be created.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type undefined

Request Structure

details An object describing the actual parameters for the Delivery Service request

customer Name of the customer associated with the *Delivery Service* - must only contain alphanumeric characters and the characters @, !, #, \$, %, ^, &, *, (,), [,], ., :kbd:`, and :kbd:-`

Changed in version ATCv6: Prior to ATC version 6, this field had no restrictions.

deepCachingType An optional string describing when to do Deep Caching for this *Delivery Service* - one of:

NEVER Never use deep caching (default)

ALWAYS Always use deep caching

deliveryProtocol The protocol used to retrieve content from the CDN - one of:

- http
- https
- http/https

hasNegativeCachingCustomization true if any customization is required for negative caching, false otherwise

hasOriginACLWhitelist true if access to the origin is restricted using an Access Control List (ACL or “whitelist”) of IP addresses

hasOriginDynamicRemap If true, this *Delivery Service* can dynamically map to multiple origin URLs

hasSignedURLs If true, this *Delivery Service*’s URLs are signed

headerRewriteEdge An optional string containing a header rewrite rule to be used at the Edge tier

headerRewriteMid An optional string containing a header rewrite rule to be used at the Mid tier

headerRewriteRedirectRouter An optional string containing a header re-write rule to be used by the Traffic Router

maxLibrarySizeEstimate A special string that describes the estimated size of the sum total of content available through this *Delivery Service*

negativeCachingCustomizationNote A note remarking on the use, customization, or complications associated with negative caching for this *Delivery Service*

- notes** An optional string containing additional instructions or notes regarding the Request
- originHeaders** An optional, comma-separated string of header values that must be passed to requests to the *Delivery Service*'s origin
- originTestFile** A URL path to a test file available on the *Delivery Service*'s origin server
- originURL** The URL of the *Delivery Service*'s origin server
- otherOriginSecurity** An optional string describing any and all other origin security measures that need to be considered for access to the *Delivery Service*'s origin
- overflowService** An optional string containing the IP address or URL of an overflow point (used if rate limits are met or exceeded)
- peakBPSEstimate** A special string describing the estimated peak data transfer rate of the *Delivery Service* in Bytes Per Second (BPS)
- peakTPSEstimate** A special string describing the estimated peak transaction rate of the *Delivery Service* in Transactions Per Second (TPS)
- queryStringHandling** A special string describing how the *Delivery Service* should treat URLs containing query parameters
- rangeRequestHandling** A special string describing how the *Delivery Service* should handle range requests
- rateLimitingGBPS** An optional field which, if defined, should contain the maximum allowed data transfer rate for the *Delivery Service* in GigaBytes Per Second (GBPS)
- rateLimitingTPS** An optional field which, if defined, should contain the maximum allowed transaction rate for the *Delivery Service* in Transactions Per Second (TPS)
- routingName** An optional field which, if defined, should contain the routing name for the *Delivery Service*, e.g. `SomeRoutingName.DeliveryService_xml_id.CDNName.com`
- routingType** The *Delivery Service*'s routing type, should be one of:
- HTTP** The Traffic Router re-directs clients to *cache servers* using the HTTP 302 REDIRECT response code

DNS The Traffic Router responds to requests for name resolution of the *Delivery Service*'s routing name with IP addresses of *cache servers*

STEERING This *Delivery Service* routes clients to other *Delivery Services* - which will in turn (generally) route them to clients

ANY_MAP Some kind of undocumented black magic is used to get clients to... content, probably?

serviceAliases An optional array of aliases for this *Delivery Service*

serviceDesc A description of the *Delivery Service*

emailTo The email to which the Delivery Service request will be sent

719: Request Example

```
{ "emailTo": "foo@bar.com",
  "details": {
    "customer": "XYZ Corporation",
    "contentType": "static",
    "deepCachingType": "NEVER",
    "deliveryProtocol": "http",
    "routingType": "http",
    "routingName": "demo1",
    "serviceDesc": "service description goes here",
    "peakBPSEstimate": "less-than-5-Gbps",
    "peakTPSEstimate": "less-than-1000-TPS",
    "maxLibrarySizeEstimate": "less-than-200-GB",
    "originURL": "http://myorigin.com",
    "hasOriginDynamicRemap": false,
    "originTestFile": "http://origin.infra.ciab.test",
    "hasOriginACLWhitelist": false,
    "originHeaders": "",
    "otherOriginSecurity": "",
    "queryStringHandling": "ignore-in-cache-key-and-pass-up",
    "rangeRequestHandling": "range-requests-not-used",
    "hasSignedURLs": false,
    "hasNegativeCachingCustomization": false,
    "negativeCachingCustomizationNote": "",
    "serviceAliases": [],
    "rateLimitingGBPS": 50,
    "rateLimitingTPS": 5000,
    "overflowService": null,
    "headerRewriteEdge": "",
    "headerRewriteMid": "",
    "headerRewriteRedirectRouter": "",
```

(continues on next page)

(continued from previous page)

```
"notes": ""
}}
```

Response Structure

720: Response Example

```
{ "alerts": [{
  "level": "success",
  "text": "Delivery Service request sent to foo@bar.com."
}]}
```

deliveryservices_required_capabilities

GET

Gets all associations of *Server Capability* to *Delivery Services*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 306: Request Query Parameters

Name	Re-quired	Description
deliv-ery-Servi-ceID	no	Filter <i>Server Capability</i> associations by <i>Delivery Service</i> integral, unique identifier
xm-IID	no	Filter <i>Server Capability</i> associations by <i>Delivery Service xml_id</i>
re-quired-Capa-bility	no	Filter <i>Server Capability</i> associations by <i>Server Capability</i> name
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sor-tOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

721: Request Example

```
GET /api/3.0/deliveryservices_required_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

deliveryServiceID The associated *Delivery Service*’s integral, unique identifier

xmlID The associated *Delivery Service*’s *xml_id*

lastUpdated The date and time at which this association between the *Delivery Service* and the *Server Capability* was last updated, in *Traffic Ops’s Custom Date/Time Format*

requiredCapability The *Server Capability*’s name

722: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
    ↳jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
    ↳DbBwhMAOJoeqDIImoDlrLnrVjQG04AooA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 396

{
  "response": [
    {
      "deliveryServiceID": 1,
      "lastUpdated": "2019-10-07 22:05:31+00",
      "requiredCapability": "ram",
      "xmlId": "example_ds-1"
    },
    {
      "deliveryServiceID": 2,
      "lastUpdated": "2019-10-07 22:05:31+00",
      "requiredCapability": "disk",
      "xmlId": "example_ds-2"
    }
  ]
}

```

POST

Associates a *Server Capability* with a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Note: A *Server Capability* can only be made required on a *Delivery Service* if its associated

Servers already have that *Server Capability* assigned.

Request Structure

deliveryServiceID The integral, unique identifier of the *Delivery Service* to be associated

requiredCapability The name of the *Server Capability* to be associated

723: Request Example

```
POST /api/3.0/deliveryservices_required_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "deliveryServiceID": 1,
  "requiredCapability": "disk"
}
```

Response Structure

deliveryServiceID The newly associated *Delivery Service*'s integral, unique identifier

lastUpdated The date and time at which this association between the *Delivery Service* and the *Server Capability* was last updated, in *Traffic Ops's Custom Date/Time Format*

requiredCapability The newly associated *Server Capability*'s name

724: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512:↵
↵eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
↵Cfh2X9i3G+MQ36eH95gukJq0BOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 287

{
  "alerts": [
    {
      "level": "success",
      "text": "deliveryservice.RequiredCapability was created."
    }
  ],
  "response": {
    "deliveryServiceID": 1,
    "lastUpdated": "2019-10-07 22:15:11+00",
    "requiredCapability": "disk"
  }
}
```

DELETE

Dissociate a *Server Capability* from a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

deliveryServiceID The integral, unique identifier of the *Delivery Service* from which a *Server Capability* will be dissociated

requiredCapability The name of the *Server Capability* to dissociate

725: Request Example

```
POST /api/3.0/deliveryservices_required_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json

{
  "deliveryServiceID": 1,
  "requiredCapability": "disk"
}
```

Response Structure

726: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
→Cfh2X9i3G+MQ36eH95gukJqOBOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 127

{
  "alerts": [
    {
      "level": "success",
      "text": "deliveryservice.RequiredCapability was deleted."
    }
  ]
}
```


deliveryservices/sslkeys/add

See also:

In most cases it is preferable to allow Traffic Ops to generate the keys via *deliveryservices/sslkeys/generate*, rather than uploading them manually using this endpoint.

POST

Allows user to upload an SSL certificate, csr, and private key for a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

cdn The name of the CDN to which the *Delivery Service* belongs

certificate An object that contains the actual components of the SSL key

crt The certificate for the *Delivery Service* identified by key

csr The csr file for the *Delivery Service* identified by key

key The private key for the *Delivery Service* identified by key

key The *xml_id* of the *Delivery Service* to which these keys will be assigned

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

727: Request Example

```
POST /api/3.0/deliveryservices/sslkeys/add HTTP/1.1
Host: trafficops.infra.ciab.test
Content-Type: application/json

{
  "key": "ds-01",
  "version": "1",
  "certificate": {
    "key": "some_key",
    "csr": "some_csr",
    "crt": "some_crt"
  }
}
```

Response Structure

728: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "response": "Successfully added ssl keys for ds-01"
}
```

deliveryservices/sslkeys/generate

POST

Generates an SSL certificate, csr, and private key for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

city An optional field which, if present, will represent the resident city of the generated SSL certificate

country An optional field which, if present, will represent the resident country of the generated SSL certificate

hostname The desired hostname of the *Delivery Service*

Note: In most cases, this must be the same as the *Delivery Service* URL’

key The *xml_id* of the *Delivery Service* for which keys will be generated

organization An optional field which, if present, will represent the organization for which the SSL certificate was generated

state An optional field which, if present, will represent the resident state or province of the generated SSL certificate

businessUnit An optional field which, if present, will represent the business unit for which the SSL certificate was generated

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

729: Request Example

```
POST /api/3.0/deliveryservices/sslkeys/generate HTTP/1.1
Content-Type: application/json

{
  "key": "ds-01",
  "businessUnit": "CDN Engineering",
  "version": "3",
  "hostname": "tr.ds-01.ott.kabletown.com",
  "country": "US",
  "organization": "Kabletown",
  "city": "Denver",
  "state": "Colorado"
}
```

Response Structure

730: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": "Successfully created ssl keys for ds-01" }
```

deliveryservices/sslkeys/generate/letsencrypt

POST

Generates an SSL certificate and private key using Let's Encrypt for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

key The *xml_id* of the *Delivery Service* for which keys will be generated¹

deliveryservice The *xml_id* of the *Delivery Service* for which keys will be generated^{Page 1158, 1}

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

hostname The desired hostname of the *Delivery Service*

Note: In most cases, this must be the same as the *Example URLs*.

cdn The name of the CDN of the *Delivery Service* for which the certs will be generated

731: Request Example

```
POST /api/3.0/deliveryservices/sslkeys/generate/letsencrypt HTTP/1.1
Content-Type: application/json

{
  "key": "ds-01",
  "deliveryservice": "ds-01",
  "version": "3",
  "hostname": "tr.ds-01.ott.kabletown.com",
  "cdn": "test-cdn"
}
```

Response Structure

¹ Either the key or the deliveryservice field must be provided. If both are provided, then they must match.

732: Response Example

```
{ "alerts": [{
  "level": "success",
  "text": "Beginning async ACME call for demo1 using Lets Encrypt.
→ This may take a few minutes. Status updates can be found here: /api/
→ 4.0/async_status/1"
}]}
```

`deliveryservices/{xml_id}/servers`

POST

Assigns *cache servers* to a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type Object

Request Structure

Table 307: Request Path Parameters

Name	Description
xml_id	The ‘xml_id’ of the <i>Delivery Service</i> whose server assignments are being edited

serverNames An array of hostname of *cache servers* to assign to this *Delivery Service*

733: Request Example

```
POST /api/3.0/deliveryservices/test/servers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 24
Content-Type: application/json

{ "serverNames": [ "edge" ] }
```

¹ Users can only assign servers to *Delivery Services* that are visible to their *Tenant*.

Response Structure

xml_id The *xml_id* of the *Delivery Service* to which the servers in **serverNames** have been assigned

serverNames An array of hostnames of *cache servers* assigned to *Delivery Service* identified by **xml_id**

734: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳zTpLrWiLM4xRsm8mlBQFB5KzT478AjloSyXHgtyWhebCv1YIwWltnmkjr0HFgc3GMGZODt+fyzk0Yy5Zl/
    ↳yBtJw==
X-Server-Name: traffic_ops_golang/
Date: Tue, 20 Nov 2018 15:21:50 GMT
Content-Length: 52

{ "response": {
  "serverNames": [
    "edge"
  ],
  "xmlId": "test"
}}
```

deliveryservices/{xml_id}/urisignkeys

DELETE

Deletes URISigning objects for a *Delivery Service*.

Auth. Required Yes

Roles Required admin¹

Response Type undefined

¹ URI Signing Keys can only be created, viewed, deleted, or modified on *Delivery Services* that either match the requesting user's *Tenant* or are descendants thereof.

Request Structure

Table 308: Request Path Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Response Structure

TBD

GET

Retrieves one or more URISigning objects for a delivery service.

Auth. Required Yes

Roles Required admin Page 1158, 1

Response Type undefined

Request Structure

Table 309: Request Route Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Response Structure

Issuer a string describing the issuer of the URI signing object. Multiple URISigning objects may be returned in a response, see example

renewal_kid a string naming the jwt key used for renewals

keys json array of jwt symmetric keys

alg this parameter repeats for each jwt key in the array and specifies the jwa encryption algorithm to use with this key, **RFC 7518**

kid this parameter repeats for each jwt key in the array and specifies the unique id for the key as defined in **RFC 7516**

key this parameter repeats for each jwt key in the array and specifies the key type as defined in **RFC 7516**

k this parameter repeats for each jwt key in the array and specifies the base64 encoded symmetric key see **RFC 7516**

735: Response Example

```
{ "Kabletown URI Authority": {
  "renewal_kid": "Second Key",
  "keys": [
    {
      "alg": "HS256",
      "kid": "First Key",
      "kty": "oct",
      "k": "Kh_RkUMj-fzbD37qBnDf_3e_RvQ3RP9PaSmVEpE24AM"
    },
    {
      "alg": "HS256",
      "kid": "Second Key",
      "kty": "oct",
      "k": "fZBpDBNbk2GqhwoB_DGBAsBxqQZVix04rIoLJ7p_RlE"
    }
  ]
}}
```

POST

Assigns URISigning objects to a delivery service.

Auth. Required Yes

Roles Required admin Page 1158, 1

Response Type undefined

Request Structure

Table 310: Request Path Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Request Structure

Issuer a string describing the issuer of the URI signing object. Multiple URISigning objects may be returned in a response, see example

renewal_kid a string naming the jwt key used for renewals

keys json array of jwt symmetric keys

- alg** this parameter repeats for each jwt key in the array and specifies the jwa encryption algorithm to use with this key, [RFC 7518](#)
- kid** this parameter repeats for each jwt key in the array and specifies the unique id for the key as defined in [RFC 7516](#)
- kt** this parameter repeats for each jwt key in the array and specifies the key type as defined in [RFC 7516](#)
- k** this parameter repeats for each jwt key in the array and specifies the base64 encoded symmetric key see [RFC 7516](#)

736: Request Example

```
{ "Kabletown URI Authority": {
  "renewal_kid": "Second Key",
  "keys": [
    {
      "alg": "HS256",
      "kid": "First Key",
      "kty": "oct",
      "k": "Kh_RkUMj-fzbD37qBnDf_3e_RvQ3RP9PaSmVEpE24AM"
    },
    {
      "alg": "HS256",
      "kid": "Second Key",
      "kty": "oct",
      "k": "fZBpDBNbk2GqhwoB_DGBAsBxqQZVix04rIoLJ7p_RlE"
    }
  ]
}}
```

PUT

updates URISigning objects on a delivery service.

Auth. Required Yes

Roles Required admin Page 1158, 1

Response Type undefined

Request Structure

Table 311: Request Path Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Request Structure

Issuer a string describing the issuer of the URI signing object. Multiple URISigning objects may be returned in a response, see example

renewal_kid a string naming the jwt key used for renewals

keys json array of jwt symmetric keys

alg this parameter repeats for each jwt key in the array and specifies the jwa encryption algorithm to use with this key, [RFC 7518](#)

kid this parameter repeats for each jwt key in the array and specifies the unique id for the key as defined in [RFC 7516](#)

kty this parameter repeats for each jwt key in the array and specifies the key type as defined in [RFC 7516](#)

k this parameter repeats for each jwt key in the array and specifies the base64 encoded symmetric key see [RFC 7516](#)

737: Request Example

```
{ "Kabletown URI Authority": {
  "renewal_kid": "Second Key",
  "keys": [
    {
      "alg": "HS256",
      "kid": "First Key",
      "kty": "oct",
      "k": "Kh_RkUMj-fzbD37qBnDf_3e_RvQ3RP9PaSmVEpE24AM"
    },
    {
      "alg": "HS256",
      "kid": "Second Key",
      "kty": "oct",
      "k": "fZBpDBNbk2GqhwoB_DGBAsBxqQZVix04rIoLJ7p_RlE"
    }
  ]
}}
```

deliveryservices/xmlId/{{XMLID}}/sslkeys

GET

Retrieves SSL keys for a *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 312: Request Path Parameters

Name	Description
XMLID	The ‘xml_id’ of the desired <i>Delivery Service</i>

Table 313: Request Query Parameters

Name	Re-quired	Description
ver-sion	no	The version number of the SSL keys to retrieve
de-code	no	If <code>true</code> , the returned keys will be decoded - if <code>false</code> , they will not be decoded

Caution: There’s almost certainly no good reason to request the private key! Even when “base 64-encoded” do not let **ANYONE** see this who would be unable to request it themselves!

Response Structure

businessUnit An optional field which, if present, contains the business unit entered by the user when generating the SSL certificate¹

certificate An object containing the actual generated key, certificate, and signature of the SSL keys

crt Base 64-encoded (or not if the decode query parameter was given and `true`) certificate for the *Delivery Service* identified by `deliveryservice`

¹ These optional fields will be present in the response if and only if they were specified during key generation; they are optional during key generation and thus cannot be guaranteed to exist or not exist.

csr Base 64-encoded (or not if the decode query parameter was given and true) csr file for the *Delivery Service* identified by deliveryservice

key Base 64-encoded (or not if the decode query parameter was given and true) private key for the *Delivery Service* identified by deliveryservice

Caution: There's almost certainly no good reason to request the private key! Even when "base 64-encoded" do not let **ANYONE** see this who would be unable to request it themselves!

cdn The CDN of the *Delivery Service* for which the certs were generated

city An optional field which, if present, contains the city entered by the user when generating the SSL certificate^{Page 1179, 1}

country An optional field which, if present, contains the country entered by the user when generating the SSL certificate^{Page 1179, 1}

deliveryservice The 'xml_id' of the *Delivery Service* for which the certificate was generated

hostname The hostname generated by Traffic Ops that is used as the common name when generating the certificate - this will be a FQDN for DNS *Delivery Services* and a wildcard URL for HTTP *Delivery Services*

organization An optional field which, if present, contains the organization entered by the user when generating certificate^{Page 1179, 1}

state An optional field which, if present, contains the state entered by the user when generating certificate^{Page 1179, 1}

version An integer that defines the "version" of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

expiration The expiration date of the certificate for the *Delivery Service* in **RFC 3339** format

738: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": {
  "certificate": {
    "crt": "crt",
    "key": "key",
    "csr": "csr"
  },

```

(continues on next page)

(continued from previous page)

```
"deliveryservice": "my-ds",
"cdn": "qa",
"businessUnit": "CDN_Eng",
"city": "Denver",
"organization": "KableTown",
"hostname": "foober.com",
"country": "US",
"state": "Colorado",
"version": "1",
"expiration": "2020-08-18T13:53:06Z"
}}
```

DELETE

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 314: Request Path Parameters

Name	Required	Description
xmlId	yes	The <i>xml_id</i> of the desired <i>Delivery Service</i>

Table 315: Request Query Parameters

Name	Required	Description
version	no	The version number of the SSL keys that shall be retrieved

Response Structure

739: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 18 Mar 2020 17:36:10 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Pj+zCo0Xg19nGNxcSkjib2iDjG062Y3RcEEV+0YnwbGIsLcpa0BKZleY/qJOKT5DkSoX2qQkckUxUqdDxjVorQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 18 Mar 2020 16:36:10 GMT
Content-Length: 79

{
  "response": "Successfully deleted ssl keys for demo1"
}
```

`deliveryservices/xmlId/{XMLID}/sslkeys/renew`

POST

Uses ACME protocol to renew SSL keys for a *Delivery Service*.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 316: Request Path Parameters

Name	Description
XMLID	The ‘xml_id’ of the desired <i>Delivery Service</i>

Request Structure

No parameters available

Response Structure

740: Response Example

```
{ "alerts": [{
  "level": "success",
  "text": "Certificate for test-xml-id successfully renewed."
}]}
```

`deliveryservices/xmlId/{xmlid}/urlkeys`

GET

See also:

deliveryservices/{ID}/urlkeys

Retrieves URL signing keys for a *Delivery Service*.

Caution: This method will return the *Delivery Service*'s **PRIVATE** URL signing keys! Be wary of using this endpoint and **NEVER** share the output with anyone who would be unable to see it on their own.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 317: Request Path Parameters

Name	Description
xmlid	The 'xml_id' of the desired <i>Delivery Service</i>

Response Structure

key<N> The private URL signing key for this *Delivery Service* as a base-64-encoded string, where <N> is the “generation” of the key e.g. the first key will always be named "key0". Up to 16 concurrent generations are retained at any time (<N> is always on the interval [0,15])

741: Response Example

```
{ "response": {
  "key9": "ZvVQNYpPVQWQV8tjQnUl6osm4y7xK4zD",
  "key6": "JhGdpw5X9o8TqHfgezCm0bqb9SQPASWL",
  "key8": "ySXdp1T8IeDEE10CMftzZb9EIw_20wwq",
  "key0": "D4AYzJ1AE2nYisA9MxMtY03TPDCHji9C",
  "key3": "W90YHlGc_kYlYw5_I0LrkpV9J0zSIneI",
  "key12": "ZbtMb3mrKqfS8hnx9_xWBIP_OPWlUpzc",
  "key2": "0qgEoD07sUsugIQemZbwmMt0tNCwB1sf",
  "key4": "aFJ2Gb7atmxVB8uv7T9S60aDml3ycpGf",
  "key1": "wnWNR1mCz104C7EFPtcqHd0xUMQyNFhA",
  "key11": "k6HMzlBH1x6htKkypRFfWQhAndQqe50e",
  "key10": "zYONfdD7fGYKj4kLvIj4U0918csuZ00d",
  "key15": "3360cGaIip_layZMc_0hI2teJbazxTQh",
  "key5": "SIwv3G0hWN7EE9wSwPFj18qE4M07sFxN",
  "key13": "SqQKBR6LqEOzp8AewZUCVtBcW_8YFc1g",
  "key14": "DtXsu8nsw04YhT0kNoKBhu2G3P9WRpQJ",
  "key7": "cmKoIIxXGAxUMdCsWvnGLoIMGmNiuT5I"
}}
```

deliveryservices/xmlId/{xml_id}/urlkeys/copyFromXmlId/
{{copyFrom_xml_id}}

POST

Allows a user to copy URL signing keys from a specified *Delivery Service* to another *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 318: Request Path Parameters

Name	Description
xml_id	The <i>xml_id</i> of the <i>Delivery Service</i> to which keys will be copied
copyFrom_xml_id	The <i>xml_id</i> of the <i>Delivery Service</i> from which keys will be copied

Response Structure

742: Response Example

```
{
  "response": "Successfully copied and stored keys"
}
```

`deliveryservices/xmlId/{xml_id}/urlkeys/generate`

POST

Generates URL signing keys for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 319: Request Path Parameters

Name	Description
xml_id	The <i>xml_id</i> of the desired <i>Delivery Service</i>

Response Structure

743: Response Example

```
{
  "response": "Successfully generated and stored keys"
}
```

`deliveryservicesserver`

GET

Retrieve information about the assignment of servers to *Delivery Services*

Auth. Required Yes

Roles Required None¹

¹ While no roles are required, this endpoint *does* respect tenancy permissions (pending [GitHub Issue #2978](#)).

Response Type Array

Request Structure

Table 320: Request Query Parameters

Name	Required	Default	Description
page	no	0	The page number for use in pagination - 0 means “no pagination”
limit	no	20	Limits the results to a maximum of this number - if pagination is used, this defines the number of results per page
orderby	no	“deliveryservice”	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array

744: Request Example

```
GET /api/3.0/deliveryserviceserver?page=1&limit=2&orderby=lastUpdated_
→HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

Unlike most API endpoints, this will return a JSON response body containing both a “response” object as well as other, top-level fields (besides the optional “alerts” field). For this reason, this section contains a “response” key, which normally is implicit.

See also:

Response Structure

limit The maximum size of the response array, also indicative of the number of results per page using the pagination requested by the query parameters (if any) - this should be the same as the `limit` query parameter (if given)

orderby A string that names the field by which the elements of the response array are ordered - should be the same as the `orderby` request query parameter (if given)

response An array of objects, each of which represents a server’s *Delivery Service* assignment

deliveryService The integral, unique identifier of the *Delivery Service* to which the server identified by `server` is assigned

lastUpdated The date and time at which the server's assignment to a *Delivery Service* was last updated

server The integral, unique identifier of a server which is assigned to the *Delivery Service* identified by `deliveryService`

size The page number - if pagination was requested in the query parameters, else 0 to indicate no pagination - of the results represented by the response array. This is named "size" for legacy reasons

745: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: J7sK8PohQWyTpTrMjJrWdlJwPj+Zyep/
    ↳xutM25uVosL6cHgi30nXa6VMYOC5Y3vd9r5KLES8rTgR+qUQcZcJ/A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 01 Nov 2018 14:27:45 GMT
Content-Length: 129

{ "orderBy": "lastUpdated",
  "response": [
    {
      "server": 8,
      "deliveryService": 1,
      "lastUpdated": "2018-11-01 14:10:38+00"
    }
  ],
  "size": 1,
  "limit": 2
}
```

POST

Assign a set of one or more servers to a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”²

Response Type Object

Request Structure

dsId The integral, unique identifier of the *Delivery Service* to which the servers identified in the `servers` array will be assigned

replace If `true`, any existing assignments for a server identified in the `servers` array will be overwritten by this request

servers An array of integral, unique identifiers for servers which are to be assigned to the *Delivery Service* identified by `deliveryService`

746: Request Example

```
POST /api/3.0/deliveryserviceserver HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 46
Content-Type: application/x-www-form-urlencoded

dsId=1&replace=true&servers=12
```

Response Structure

dsId The integral, unique identifier of the *Delivery Service* to which the servers identified by the elements of the `servers` array have been assigned

replace If `true`, any existing assignments for a server identified in the `servers` array have been overwritten by this request

servers An array of integral, unique identifiers for servers which have been assigned to the *Delivery Service* identified by `deliveryService`

² Users with the “admin” or “operations” roles will be able to modify ALL server-to-Delivery-Service assignments, whereas all other users can only assign servers to the *Delivery Services* their Tenant has permissions to edit.

747: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳D+HhGhoxzaxvka9vZIStoa0ZUpX23nz7zZnMbpFHNRO3MawyEaSb3GVUHQyCv6sDgwhpZZjRggDmctGCw
X-Server-Name: traffic_ops_golang/
Date: Thu, 01 Nov 2018 14:12:49 GMT
Content-Length: 123

{ "alerts": [
  {
    "text": "server assignments complete",
    "level": "success"
  }
],
"response": {
  "dsId": 1,
  "replace": false,
  "servers": [ 12 ]
}}
```

`deliveryserviceserver/{{DSID}}/{{serverID}}`

DELETE

Removes a *cache server* from a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type undefined

¹ Users with the “admin” or “operations” roles will be able to delete *any Delivery Service*, whereas other users will only be able to delete *Delivery Services* that their tenant has permissions to delete.

Request Structure

Table 321: Request Path Parameters

Name	Required	Description
dsId	yes	An integral, unique identifier for a <i>Delivery Service</i>
serverID	yes	An integral, unique identifier for a server

Note: The server identified by serverID must be a *cache server*, or the assignment will fail.

Response Structure

748: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: rGD2sOMHYF0sga1zuTytyLHCUkkc3ZwQRKvZ/
    ↳HuPzObOP4WztKTOVXB4uhs3iJqBg9zRB2TucMxONHN+3/yShQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 01 Nov 2018 14:24:34 GMT
Content-Length: 80

{ "alerts": [
  {
    "text": "Server unlinked from delivery service.",
    "level": "success"
  }
]}
```

divisions

GET

Returns a JSON representation of all configured *Divisions*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 322: Request Query Parameters

Name	Description
id	Filter for <i>Divisions</i> having this integral, unique identifier
name	Filter for <i>Divisions</i> with this name
orderby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

id An integral, unique identifier for this Division

lastUpdated The date and time at which this Division was last modified, in *Traffic Ops’s Custom Date/Time Format*

name The Division name

749: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→SLKi9RHa67sGoSz62IDcQsk7KZjTXKfonqMoCUFPXGcNUdhBssvUjc1G7KkWK8X1Ny16geMx2BN8Hm/
→3dQ75GA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 19:44:03 GMT
Content-Length: 139

{ "response": [
  {
    "id": 1,
    "lastUpdated": "2018-11-29 18:38:28+00",
    "name": "Quebec"
  },
  {
    "id": 2,
    "lastUpdated": "2018-11-29 18:38:28+00",
    "name": "USA"
  }
]}

```

POST

Creates a new Division.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the new Division

750: Request Example

```
POST /api/3.0/divisions HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 16
Content-Type: application/json

```

(continues on next page)

(continued from previous page)

```
{"name": "test"}
```

Response Structure

id An integral, unique identifier for this Division

lastUpdated The date and time at which this Division was last modified, in *Traffic Ops's Custom Date/Time Format*

name The Division name

751: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +pJm4c30+JTaSXNt+LP+u240Ba/
    ↳SsvSSDOQ4rDc6hcyZ0FIL+iY/WWrMHhpLulRGKGY88bM4YPCMaxGn3FZ9yQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 19:52:06 GMT
Content-Length: 136

{ "alerts": [
  {
    "text": "division was created.",
    "level": "success"
  }
],
"response": {
  "id": 3,
  "lastUpdated": "2018-11-29 19:52:06+00",
  "name": "test"
}}
```

`divisions/{ID}`

PUT

Updates a specific Division

Auth. Required Yes

Roles Required “admin” or “operations”

Request Structure

Table 323: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the requested Division

name The new name of the Division

752: Request Example

```
PUT /api/3.0/divisions/3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 17
Content-Type: application/json

{"name": "quest"}
```

Response Structure

id An integral, unique identifier for this Division

lastUpdated The date and time at which this Division was last modified, in *Traffic Ops’s Custom Date/Time Format*

name The Division name

753: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: yBd8MzBR/Qbc/
→xTs44WEIFRTrqeMKZwUe2ufpm6JH6frh1UjFmYRs3/
→B7E5FTruFWRTuvEIlx5EpDmp3f9LjzA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 20:10:36 GMT
Content-Length: 137

{ "alerts": [
  {
    "text": "division was updated.",
    "level": "success"
  }
],
"response": {
  "id": 3,
  "lastUpdated": "2018-11-29 20:10:36+00",
  "name": "quest"
}}
```

federation_resolvers

GET

Retrieves *Federation* Resolvers.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 324: Request Query Parameters

Name	Re-quired	Description
id	no	Return only the Federation Resolver identified by this integral, unique identifier
ipAddress	no	Return only the Federation Resolver(s) that has/have this IP Address
type	no	Return only the Federation Resolvers of this <i>Type</i>
orderBy	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

754: Request Example

```
GET /api/3.0/federation_resolvers?type=RESOLVE6 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.63.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

id The integral, unique identifier of the resolver

ipAddress The IP address or CIDR-notation subnet of the resolver - may be IPv4 or IPv6

lastUpdated The date and time at which this resolver was last updated, in *Traffic Ops’s Custom Date/Time Format*

type The *Type* of the resolver

755: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→4TLkULAOAuap47H+hpwyf2lHjDbHbSNQHLmj7BCTHtps2CQxCuq7mwctbwqmPdmAjLOUXAIRsHmvSuAp4
X-Server-Name: traffic_ops_golang/
Date: Wed, 06 Nov 2019 00:03:56 GMT
Content-Length: 101

{ "response": [
  {
    "id": 1,
    "ipAddress": "::1/1",
    "lastUpdated": "2019-11-06 00:00:40+00",
    "type": "RESOLVE6"
  }
]}
```

POST

Creates a new federation resolver.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

ipAddress The IP address of the resolver - may be IPv4 or IPv6

typeId The integral, unique identifier of the *Type* of resolver being created

Caution: This field should only ever be an identifier for one of the *Types* “RESOLVE4” or “RESOLVE6”, but there is **no protection for this built into Traffic Ops** and therefore **any valid *Type* identifier will be silently accepted by Traffic Ops** and so care should be taken to ensure that these *Types* are properly identified. If any *Type* besides “RESOLVE4” or “RESOLVE6” is identified, the resulting resolver *will not work*.

See also:

types is the endpoint that can be used to determine the identifier for various

Types

756: Request Example

```
POST /api/3.0/federation_resolvers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.63.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 36
Content-Type: application/json

{
  "ipAddress": "::1/1",
  "typeId": 37
}
```

Response Structure

id The integral, unique identifier of the resolver

ipAddress The IP address or CIDR-notation subnet of the resolver - may be IPv4 or IPv6

type The *Type* of the resolver

typeId The integral, unique identifier of the *Type* of the resolver

757: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳e9D8JNrQb64xpuDwoBwbISSWUkDGCL2l37NuDXsXsPYof2EqmeHondD8NzxDSwWNJ8d9B9DXpZDbRUtgd
X-Server-Name: traffic_ops_golang/
Date: Wed, 06 Nov 2019 00:00:40 GMT
Content-Length: 153

{ "alerts": [
  {
    "text": "Federation Resolver created [ IP = ::1/1 ] with id: 1
  },
```

(continues on next page)

(continued from previous page)

```
        "level": "success"
      }
    ],
    "response": {
      "id": 1,
      "ipAddress": "::1/1",
      "type": "RESOLVE6",
      "typeId": 37
    }
  }
}
```

DELETE

Deletes a federation resolver.

- Auth. Required Yes
- Roles Required “admin”
- Response Type Object

Request Structure

Table 325: Request Query Parameters

Name	Required	Description
id	yes	Integral, unique identifier for the federation resolver to be deleted

758: Request Example

```
DELETE /api/3.0/federation_resolvers?id=4 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

id The integral, unique identifier of the resolver

ipAddress The IP address or CIDR-notation subnet of the resolver - may be IPv4 or IPv6

type The *Type* of the resolver

759: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; HttpOnly
Whole-Content-Sha512:
  ↳2v4LYQdRVhaFJVd86Iv1BWVYzNPSlzpQ222bUB7Zz+Ss8A48FNyHZjPlq5a+a4g9KAQCTUIytWnIQk+L1
X-Server-Name: traffic_ops_golang/
Date: Fri, 08 Nov 2019 23:19:01 GMT
Content-Length: 161

{ "alerts": [
  {
    "text": "Federation resolver deleted [ IP = 1.2.6.4/22 ] with
    ↳id: 4",
    "level": "success"
  }
],
"response": {
  "id": 4,
  "ipAddress": "1.2.6.4/22",
```

(continues on next page)

(continued from previous page)

```
"type": "RESOLVE6"
}}
```

federations

GET

Retrieves a list of *Federation* mappings (i.e. *Federation* Resolvers) for the current user.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Array

Request Structure

No parameters available.

Response Structure

deliveryService The `xml_id` that uniquely identifies the *Delivery Service* that uses the federation mappings in mappings

mappings An array of objects that represent the mapping of a *Federation*’s CNAME to one or more Resolvers

cname The actual CNAME used by the *Federation*

resolve4 An array of IPv4 addresses (or subnets in CIDR notation) capable of resolving the *Federation*’s CNAME

resolve6 An array of IPv6 addresses (or subnets in CIDR notation) capable of resolving the *Federation*’s CNAME

ttl The TTL of the CNAME in hours

760: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512:↵
↵d6Llm5qNc2sfgVH9IimW7hA4wvtBUq6EzUmpJf805kB0k6v2WysNgFEWK4hBXNdAYkr8hYuKPrwDy3tCx
X-Server-Name: traffic_ops_golang/
Date: Mon, 03 Dec 2018 17:19:13 GMT
Content-Length: 136

{ "response": [
  {
    "mappings": [
      {
        "ttl": 300,
        "cname": "blah.blah.",
        "resolve4": [
          "0.0.0.0/32"
        ],
        "resolve6": [
          "::/128"
        ]
      }
    ],
    "deliveryService": "demo1"
  }
]}
```

POST

Allows a user to create *Federation* Resolvers for *Delivery Services*, providing the *Delivery Service* is within a CDN that has some associated *Federation*.

Warning: Confusingly, this method of this endpoint does **not** create a new *Federation*; to do that, the *cdns/{{name}}/federations* endpoint must be used. Furthermore, the *Federation* must properly be assigned to a *Delivery Service* using the *federations/{{ID}}/deliveryservices* and assigned to the user creating Resolvers using *federations/{{ID}}/users*.

See also:

The *federations/{{ID}}/federation_resolvers* endpoint duplicates this functionality.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

The request payload is an array of objects that describe Delivery Service *Federation* Resolver mappings. Each object in the array must be in the following format.

deliveryService The *xml_id* of the *Delivery Service* which will use the *Federation* Resolvers specified in mappings

mappings An object containing two arrays of IP addresses (or subnets in CIDR notation) to use as *Federation* Resolvers

resolve4 An array of IPv4 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service's Federation*

resolve6 An array of IPv6 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service's Federation*

761: Request Example

```
POST /api/3.0/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 118
Content-Type: application/json

[{"deliveryService": "demo1",
  "mappings": {
    "resolve4": ["127.0.0.1", "0.0.0.0/32"],
    "resolve6": ["::1", "5efa::ff00/128"]
  }
}]
```

Response Structure

762: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: B7TSUOYZPRPyi3mVy+CuxiXR5k/
→d0s07w4i6kYzpWS+YL79juEfkusqfedayG/kMA809XbjkWRjcBAdxOVrdTQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 23 Oct 2019 22:28:02 GMT
Content-Length: 152

{ "alerts": [
  {
    "text": "admin successfully created federation resolvers.",
    "level": "success"
  }
],
"response": "admin successfully created federation resolvers."
}
```

DELETE

Deletes **all** *Federation* Resolvers associated with the logged-in user's *Federations*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

No parameters available

763: Request Example

```
DELETE /api/3.0/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

764: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳fd7P45mIiHuYqZZW6+8K+YjY1Pe504Aaw4J4Zp9AhrqLX72ERytTqWtAp1msutzNSRUdUSC72+odNPtpv
X-Server-Name: traffic_ops_golang/
Date: Wed, 23 Oct 2019 23:34:53 GMT
Content-Length: 184

{ "alerts": [
  {
    "text": "admin successfully deleted all federation resolvers:
    ↳[ 8.8.8.8 ]",
    "level": "success"
  }
],
"response": "admin successfully deleted all federation resolvers: [ 8.
    ↳8.8.8 ]"
}
```

PUT

Replaces **all** *Federations* associated with a user's *Delivery Service*(s) with those defined inside the request payload.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

The request payload is an array of objects that describe Delivery Service *Federation* Resolver mappings. Each object in the array must be in the following format.

deliveryService The *xml_id* of the *Delivery Service* which will use the *Federation* Resolvers specified in **mappings**

mappings An object containing two arrays of IP addresses (or subnets in CIDR notation) to use as *Federation* Resolvers

resolve4 An array of IPv4 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service*'s *Federation*

resolve6 An array of IPv6 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service*'s *Federation*

765: Request Example

```
PUT /api/3.0/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 95
Content-Type: application/json

[{"mappings": {
  "resolve4": ["8.8.8.8"],
  "resolve6": []
},
"deliveryService": "demo1"
}]
```

Response Structure

766: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dQ5AvQULhc254zQwgUpBl1/CHbLr/
→clKtkbs0Ju9f1BM4xIfbb03puFNN9zaEaZ1iz0lBvHFp/PgfUqisD3QHA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 23 Oct 2019 23:22:03 GMT
Content-Length: 258
Content-Type: application/json

{ "alerts": [
  {
    "text": "admin successfully deleted all federation resolvers:
→[ 8.8.8.8 ]",
    "level": "success"
  },
  {
    "text": "admin successfully created federation resolvers.",
    "level": "success"
  }
]
```

(continues on next page)

(continued from previous page)

```
}
],
"response": "admin successfully created federation resolvers."
}
```

federations/all

GET

Retrieves a list of *Federation* mappings (also called *Federation* Resolvers) for the current user.

Auth. Required Yes

Roles Required “admin”

Response Type Array

Request Structure

No parameters available.

767: Request Example

```
GET /api/3.0/federations/all HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

deliveryService The *xml_id* of the delivery service.

mappings An array of objects that represent the mapping of a *Federation*’s CNAME to one or more Resolvers

cname The actual CNAME used by the *Federation*

ttl The TTL of the CNAME in hours

768: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 21:38:06.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→UQBlGVPJytYMkv0V42EAIoJUnXjBTCXnOGp0berxte6TtnX63LTAKFfD2LejBVYXkKtnCdkBbs+SzhA0H.
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 20:38:06 GMT
Content-Length: 138

{
  "response": [
    {
      "mappings": [
        {
          "ttl": 60,
          "cname": "img1.mcdn.ciab.test."
        },
        {
          "ttl": 60,
          "cname": "img2.mycdn.ciab.test."
        }
      ],
      "deliveryService": "demo1"
    },
    {
      "mappings": [
        {
          "ttl": 60,
          "cname": "static.mycdn.ciab.test."
        }
      ],
      "deliveryService": "demo2"
    }
  ]
}
```

`federations/{{ID}}/deliveryservices`

GET

Retrieves *Delivery Services* assigned to a *Federation*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 326: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation to be inspected

Table 327: Request Query Parameters

Name	Re-quired	Description
dsID	no	Show only the <i>Delivery Service</i> identified by this integral, unique identifier
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

769: Request Example

```
GET /api/3.0/federations/1/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cdn** The CDN to which this *Delivery Service* Belongs
- id** The integral, unique identifier for the *Delivery Service*
- type** The routing type used by this *Delivery Service*
- xmlId** The 'xml_id' which uniquely identifies this *Delivery Service*

770: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:44:13 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:44:13 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: 7Y9Q/
→qHeXfbjJduvucRCR85wf4VRfyYhlK59sNRkzIJuwnsMhFcEfYfNqrvELwfexOum/
→VEX2f/1oa+I/edGfw==
content-length: 74

{ "response": [
  {
    "xmlId": "demo1",
    "cdn": "CDN-in-a-Box",
    "type": "HTTP",
    "id": 1
  }
]}
```

POST

Assigns one or more *Delivery Services* to a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 328: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation to be inspected

dsIds An array of integral, unique identifiers for *Delivery Services* which will be assigned to this federation

replace An optional boolean (default: `false`) which, if `true`, will cause any conflicting assignments already in place to be overridden by this request

Note: If `replace` is not given (and/or not `true`), then any conflicts with existing assignments will cause the entire operation to fail.

771: Request Example

```
POST /api/3.0/federations/1/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 32
Content-Type: application/json

{
  "dsIds": [1],
  "replace": true
}
```

Response Structure

dsIds An array of integral, unique identifiers for *Delivery Services* which are now assigned to this federation

replace An optional boolean (default: false) which, if true, means any conflicting assignments already in place were overridden by this request

772: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
→rVd0nx8G3bRI8ub1zw6FTdmwQ7jer4zoqzOZf5tC1ckrR0HEIOH1Azdcmvv0FVE5I0omcHVnrYbzab7tU
x-server-name: traffic_ops_golang/
content-length: 137
date: Wed, 05 Dec 2018 00:34:06 GMT

{ "alerts": [
  {
    "text": "1 delivery service(s) were assigned to the federation",
    →1",
    "level": "success"
  }
],
```

(continues on next page)

(continued from previous page)

```
"response": {
  "dsIds": [
    1
  ],
  "replace": true
}}
```

`federations/{{ID}}/deliveryservices/{{dsID}}`

DELETE

Removes a *Delivery Service* from a federation. A *Delivery Service* cannot be removed from a federation if it is the only *Delivery Service* assigned to said federation

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 329: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the federation from which the <i>Delivery Service</i> identified by dsID will be removed
dsID	The integral, unique identifier of the <i>Delivery Service</i> which will be removed from the federation identified by ID

773: Request Example

```
DELETE /api/3.0/federations/1/deliveryservices/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

774: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 01:06:51 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 05:06:51 GMT;
    ↳path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: NqAZuZYlF1UW0aazbj/
    ↳j4gWX7ye0kGGakRRFEkK6ShxqXvCxEOdCTyu75qiLPN2wSgr3FGQnp2Sq345sE7In9g==
content-length: 98

{ "alerts": [
  {
    "level": "success",
    "text": "federation deliveryservice was deleted."
  }
]}
```

federations/{ID}/federation_resolvers

GET

Retrieves federation resolvers assigned to a federation.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 330: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation for which resolvers will be retrieved

775: Request Example

```
GET /api/3.0/federations/1/federation_resolvers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

id The integral, unique identifier of this federation resolver

ipAddress The IP address of the federation resolver - may be IPv4 or IPv6

type The type of resolver - one of:

RESOLVE4 This resolver is for IPv4 addresses (and **ipAddress** is IPv4)

RESOLVE6 This resolver is for IPv6 addresses (and **ipAddress** is IPv6)

776: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:49:50 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:49:50 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: csC18kE3YjiILHP1wmJg7V4h/
→XWY8HUMKyPuZWnde2g7HJ4gTY51HfjCSqhyKvIJQ8Rl7uEqshF3Ey6xIMOX4A==
content-length: 63
```

(continues on next page)

(continued from previous page)

```
{ "response": [
  {
    "ipAddress": "0.0.0.0",
    "type": "RESOLVE4",
    "id": 1
  }
]}
```

POST

Assigns one or more resolvers to a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 331: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation for which resolvers will be retrieved

fedResolverIds An array of integral, unique identifiers for federation resolvers

replace An optional boolean (default: `false`) which, if `true`, will cause any conflicting assignments already in place to be overridden by this request

Note: If `replace` is not given (and/or not `true`), then any conflicts with existing assignments will cause the entire operation to fail.

777: Request Example

```
POST /api/3.0/federations/1/federation_resolvers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 41
Content-Type: application/json

{
```

(continues on next page)

(continued from previous page)

```
"fedResolverIds": [1],
"replace": true
}
```

Response Structure

fedResolverIds An array of integral, unique identifiers for federation resolvers

replace An optionally-present boolean (default: `false`) which, if `true`, any conflicting assignments already in place were overridden by this request

778: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:47:47 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:47:47 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: +JDcRByS3H06pMg3Gzkvn0w7/
→v5oRu19e+RxyFIOKJKNH0kZILyQBS+PJpxDeCgwI19+0poW5dyHPPR9SwbNCA==
content-length: 148

{ "alerts": [
  {
    "level": "success",
    "text": "1 resolver(s) were assigned to the test.request.
→federation"
  }
],
"response": {
  "replace": true,
  "fedResolverIds": [
    1
  ]
}}
```

`federations/{{ID}}/users`

GET

Retrieves users assigned to a federation.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 332: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the federation for which users will be retrieved

Table 333: Request Query Parameters

Name	Re-quired	Description
userId	no	Show only the user that has this integral, unique identifier
role	no	Show only the users that have this role
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Response Structure

company The company to which the user belongs

email The user’s email address

fullName The user’s full name

id An integral, unique identifier for the user

role The user’s highest role

username The user’s short “username”

779: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:31:34 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:31:34 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: eQQoF2xlbK2I2oTja7zrt/
→FlkLzCgwpU2zb2+rmIjHbHJ3MnmsSczSamIAAyTzs5gDaqcuUX1G35ZB8d7Bj82g==
content-length: 101

{ "response": [
  {
    "fullName": null,
    "email": null,
    "id": 2,
    "role": "admin",
    "company": null,
    "username": "admin"
  }
]}
```

POST

Assigns one or more users to a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

userIds An array of integral, unique identifiers for users which will be assigned to this federation

replace An optional boolean (default: `false`) which, if `true`, will cause any conflicting assignments already in place to be overridden by this request

Note: If `replace` is not given (and/or not `true`), then any conflicts with existing assignments will cause the entire operation to fail.

780: Request Example

```
POST /api/3.0/federations/1/users HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 34
Content-Type: application/json

{
  "userIds": [2],
  "replace": true
}
```

Response Structure

userIds An array of integral, unique identifiers for users which have been assigned to this federation

replace An optional boolean (default: `false`) which, if `true`, caused any conflicting assignments already in place to be overridden by this request

781: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
➔Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:29:19 GMT
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

```
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:29:19 GMT;␣
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512:␣
→MvPmgOAs58aSOgVh+iEilflgOexbaexg+qE2IPrQZX0H4iSX4JvEys9adbGE9a9yaLj9uUMxg77N6ZyDhV
content-length: 137

{ "alerts": [
  {
    "level": "success",
    "text": "1 user(s) were assigned to the test.quest. federation"
  }
],
"response": {
  "userIds": [
    2
  ],
  "replace": true
}}
```

`federations/{{ID}}/users/{{userID}}`

DELETE

Removes a user from a federation.

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 334: Request Path Parameters

Name	Description
ID	An integral, unique identifier for the federation from which the user identified by userID will be removed
userID	An integral, unique identifier for the user who will be removed from the federation identified by ID

782: Request Structure

```
DELETE /api/3.0/federations/1/users/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

783: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 01:14:04 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 05:14:04 GMT;
    ↳path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512:
    ↳xdF6l7jdd2t8au6lh4pFtDqYxTfehake2aDBuytL7I74hK9KCT7ssLuYbfvD8ejdqqF3+jjBiFk7neQ8c
content-length: 93

{ "alerts": [
  {
    "level": "success",
    "text": "Removed user [ admin ] from federation [ foo.bar. ]"
  }
]}
```

isos

POST

Generates an ISO from the requested ISO source.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined - ISO image as a streaming download

Request Structure

dhcp A string that specifies whether the generated system image will use DHCP IP address leasing; one of:

yes DHCP will be used, and other network configuration keys need not be present in the request (and are ignored if they are)

no DHCP will not be used, and the desired network configuration **must** be specified manually in the request body

disk An optional string that names the block device (under /dev/) used for the boot media, e.g. “sda”

domainName The domain part of the system image’s Fully Qualified Domain Name (FQDN)

hostName The host name part of the system image’s FQDN

interfaceMtu A number that specifies the Maximum Transmission Unit (MTU) for the system image’s network interface card - the only valid values of which I’m aware are 1500 or 9000, and this should almost always just be 1500

interfaceName An optional string naming the network interface to be used by the generated system image e.g. “bond0”, “eth0”, etc. If the special name “bond0” is used, an LACP binding configuration will be created and included in the system image

See also:

[The Link Aggregation Wikipedia page.](#)

ip6Address An optional string containing the IPv6 address of the generated system image

ip6Gateway An optional string specifying the IPv6 address of the generated system image’s network gateway - this will be ignored if **ipGateway** is specified

ipAddress An optional¹ string containing the IP address of the generated system image

ipGateway An optional¹ string specifying the IP address of the generated system image’s network gateway

ipNetmask An optional¹ string specifying the subnet mask of the generated system image

osversionDir The name of the directory containing the ISO source

See also:

[osversions](#)

¹ This optional key is required if and only if **dhcp** is “no”.

rootPass The password used by the generated system image's root user

784: Request Example

```
POST /api/3.0/isos HTTP/1.1
Host: some.trafficops.host
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 334
Content-Type: application/json

{
  "osversionDir": "centos72",
  "hostName": "test",
  "domainName": "quest",
  "rootPass": "twelve",
  "dhcp": "no",
  "interfaceMtu": 1500,
  "ipAddress": "1.3.3.7",
  "ipNetmask": "255.255.255.255",
  "ipGateway": "8.0.0.8",
  "ip6Address": "1::3:3:7",
  "ip6Gateway": "8::8",
  "interfaceName": "eth0",
  "disk": "hda"
}
```

Response Structure

ISO image as a streaming download.

785: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Connection: keep-alive
Content-Disposition: attachment; filename="test-centos72_centos72-
↳netinstall.iso"
Content-Encoding: gzip
Content-Type: application/download
Date: Wed, 05 Feb 2020 21:59:15 GMT
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 05 Feb 2020 22:59:11
↳GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Transfer-Encoding: chunked
Whole-Content-sha512: sLSVQGrLCQ4hGQhv2reragQHWNi2aKMcz2c/
↪HMAH45tLcZ1LenPy0zWRcRfHUNbV4PEEK0oiTfwE2H1A+WtRIQ==
X-Server-Name: traffic_ops_golang/
```

jobs

GET

Retrieve content invalidation jobs.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 335: Request Query Parameters

Name	Re- quired	Description
assetUrl	no	Return only invalidation jobs that operate on URLs by matching this regular expression
createdBy	no	Return only invalidation jobs that were created by the user with this username
delivery-Service	no	Return only invalidation jobs that operate on the <i>Delivery Service</i> with this <i>xml_id</i>
dsId	no	Return only invalidation jobs pending on the <i>Delivery Service</i> identified by this integral, unique identifier
id	no	Return only the single invalidation job identified by this integral, unique identifier
keyword	no	Return only invalidation jobs that have this “keyword” - only “PURGE” should exist
userId	no	Return only invalidation jobs created by the user identified by this integral, unique identifier

¹ When viewing content invalidation jobs, only those jobs that operate on a *Delivery Service* visible to the requesting user’s *Tenant* will be returned. Likewise, creating a new content invalidation job requires that the target *Delivery Service* is modifiable by the requesting user’s *Tenant*. However, when modifying or deleting an existing content invalidation job, the operation can be completed if and only if the requesting user’s *Tenant* is the same as the job’s *Delivery Service*’s *Tenant* or a descendant thereof, **and** if the requesting user’s *Tenant* is the same as the *Tenant* of the user who initially created the job or a descendant thereof.

786: Request Example

```
GET /api/3.0/jobs?id=3&dsId=1&userId=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the *assetUrl* until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

787: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: gH41oEi2zrd3y8yo+wfohn4/
→oHU098RpyPnqBzU7H1LUDkMOPKjAZnamcYqfdy7yDCFDUcgqkvbFAvnljxyb8w==
X-Server-Name: traffic_ops_golang/
Date: Tue, 18 Jun 2019 19:47:30 GMT
Content-Length: 186
```

(continues on next page)

(continued from previous page)

```
{ "response": [{
  "assetUrl": "http://origin.infra.ciab.test/.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
  "parameters": "TTL:2h",
  "startTime": "2019-06-18 21:28:31+00"
}]}
```

POST

Creates a new content invalidation job.

Caution: Creating a content invalidation job immediately triggers a CDN-wide revalidation update. In the case that the global *Parameter* `use_reval_pending` has a value of exactly `"0"`, this will instead trigger a CDN-wide “Queue Updates”. This means that content invalidation jobs become active **immediately** at their `startTime` - unlike most other configuration changes they do not wait for a *Snapshot* or a “Queue Updates”. Furthermore, if the global *Parameter* `use_reval_pending` is `"0"`, this will cause all pending configuration changes to propagate to all *cache servers* in the CDN. Take care when using this endpoint.

Auth. Required Yes

Roles Required “operations” or “admin”^{Page 1224, 1}

Response Type Object

Request Structure

deliveryService This should either be the integral, unique identifier of a *Delivery Service*, or a string containing an *xml_id*

startTime This can be a string in the legacy YYYY-MM-DD HH:MM:SS format, or a string in **RFC 3339** format, or a string representing a date in the same non-standard format as the `last_updated` fields common in other API responses, or finally it can be a number indicating the number of milliseconds since the Unix Epoch (January 1, 1970 UTC). This date must be in the future.

regex A regular expression that will be used to match the path part of URIs for content stored on *cache servers* that service traffic for the *Delivery Service* identified by `deliveryService`.

ttl Either the number of hours for which the content invalidation job should remain active, or a “duration” string, which is a sequence of numbers followed by units. The accepted units are:

- **h** gives a duration in hours
- **m** gives a duration in minutes
- **s** gives a duration in seconds
- **ms** gives a duration in milliseconds
- **us** (or **µs**) gives a duration in microseconds
- **ns** gives a duration in nanoseconds

These durations can be combined e.g. **2h45m** specifies a TTL of two hours and forty-five minutes - however note that durations are always rounded up to the nearest hour so that e.g. **121m** becomes three hours. TTLs cannot ever be negative, obviously.

788: Request Example

```
POST /api/3.0/jobs HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 80
Content-Type: application/json

{
  "deliveryService": "demo1",
  "startTime": 1560893311219,
  "regex": "/.*",
  "ttl": "121m"
}
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the **assetUrl** until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

789: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Location: https://trafficops.infra.ciab.test/api/3.0/jobs?id=3
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳nB2xg2IqO56rLT8dI4+KZgxOsTe5ShctG1U8epRsY9NyyMIpx8TZYt5MrO2QikuYh+NnyoR6V0VICCnGCI
X-Server-Name: traffic_ops_golang/
Date: Tue, 18 Jun 2019 19:37:06 GMT
Content-Length: 238

{
  "alerts": [
    {
      "text": "Invalidation Job creation was successful",
      "level": "success"
    }
  ],
  "response": {
    "assetUrl": "http://origin.infra.ciab.test/.*",
    "createdBy": "admin",
    "deliveryService": "demo1",
    "id": 3,
    "keyword": "PURGE",
    "parameters": "TTL:2h",
    "startTime": "2019-06-18 21:28:31+00"
  }
}
```

PUT

Replaces an existing content invalidation job with a new one provided in the request. This method of editing a content invalidation job does not prevent the requesting user from changing fields that normally only have one value. Use with care.

Caution: Modifying a content invalidation job immediately triggers a CDN-wide revalidation update. In the case that the global *Parameter* `use_reval_pending` has a value of exactly "0", this will instead trigger a CDN-wide "Queue Updates". This means that content invalidation jobs become active **immediately** at their `startTime` - unlike most other configuration changes they do not wait for a *Snapshot* or a "Queue Updates". Furthermore, if the global *Parameter* `use_reval_pending` is "0", this will cause all pending configuration changes to propagate to all *cache servers* in the CDN. Take care when using this endpoint.

Auth. Required Yes

Roles Required "operations" or "admin"^{Page 1224, 1}

Response Type Object

Request Structure

Table 336: Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the content invalidation job being modified

assetUrl A regular expression - matching URLs will be operated upon according to keyword

Note: Unlike in the payloads of *POST* requests to this endpoint, this must be a **full** URL regular expression, as it is **not** combined with the *Origin Server Base URL* of the *Delivery Service* identified by `deliveryService`.

createdBy The username of the user who initiated the job²

deliveryService The *xml_id* of the *Delivery Service* on which this job operates[?] - unlike *POST* request payloads, this cannot be an integral, unique identifier

id An integral, unique identifier for this job[?]

keyword A keyword that represents the operation being performed by the job. It can have any (string) value, but the only value with any meaning to Traffic

² This field must exist, but it must *not* be different than the same field of the existing job (i.e. as seen in a *GET* response)

Control is:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing space-separated key/value pairs - delimited by colons (`:`s) representing parameters associated with the job. In practice, any string can be passed as a job's `parameters`, but the only value with meaning is a single key/value pair indicated a TTL in hours in the format `TTL:hoursh`, and any other type of value may cause components of Traffic Control to work improperly or not at all.

startTime This can be a string in the legacy `YYYY-MM-DD HH:MM:SS` format, or a string in [RFC 3339](#) format, or a string representing a date in the same non-standard format as the `last_updated` fields common in other API responses, or finally it can be a number indicating the number of milliseconds since the Unix Epoch (January 1, 1970 UTC). This **must** be in the future, but only by no more than two days.

790: Request Example

```
PUT /api/3.0/jobs?id=3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 188
Content-Type: application/json

{
  "assetUrl": "http://origin.infra.ciab.test/*.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
  "parameters": "TTL:360h",
  "startTime": "2019-06-20 18:33:40+00"
}
```


Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

791: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳+P1PTav4ZBoiQcCqQnUqf+J0dCfQgVj8mzzKtUCA69mWYulya9Bjf6BUd8Aro2apmpgPBkCEA5sITJV1t
X-Server-Name: traffic_ops_golang/
Date: Wed, 19 Jun 2019 13:38:59 GMT
Content-Length: 234

{ "alerts": [{
  "text": "Content invalidation job updated",
  "level": "success"
}],
  "response": {
    "assetUrl": "http://origin.infra.ciab.test/.*",
    "createdBy": "admin",
    "deliveryService": "demo1",
    "id": 3,
    "keyword": "PURGE",
    "parameters": "TTL:360h",
    "startTime": "2019-06-20 18:33:40+00"
```

(continues on next page)

(continued from previous page)

```
}}
```

DELETE

Deletes a content invalidation job.

Tip: Content invalidation jobs that have passed their TTL are not automatically deleted - for record-keeping purposes - so use this to clean up old jobs that are no longer useful.

Caution: Deleting a content invalidation job immediately triggers a CDN-wide revalidation update. In the case that the global *Parameter* `use_reval_pending` has a value of exactly "0", this will instead trigger a CDN-wide "Queue Updates". This means that content invalidation jobs become active **immediately** at their `startTime` - unlike most other configuration changes they do not wait for a *Snapshot* or a "Queue Updates". Furthermore, if the global *Parameter* `use_reval_pending` is "0", this will cause all pending configuration changes to propagate to all *cache servers* in the CDN. Take care when using this endpoint.

Auth. Required Yes

Roles Required "operations" or "admin"^{Page 1224, 1}

Response Type Object

Request Structure

Table 337: Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the content invalidation job being modified

792: Request Example

```
DELETE /api/3.0/jobs?id=3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

793: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: FqfziXJYYwHb84Fac9+p4NEY3EsklYxe94wg/
→V0mlXk4R6l4SaPSh015CChPt/yT72MsWSETnIuRD9KtoK4I+w==
X-Server-Name: traffic_ops_golang/
Date: Tue, 18 Jun 2019 22:55:15 GMT
Content-Length: 234

{ "alerts": [
  {
    "text": "Content invalidation job was deleted",
    "level": "success"
  }
],
"response": {
  "assetUrl": "http://origin.infra.ciab.test/.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
```

(continues on next page)

(continued from previous page)

```
"parameters": "TTL:36h",
"startTime": "2019-06-20 18:33:40+00"
}}
```

letsencrypt/autorenew

POST

Generates an SSL certificate and private key using Let's Encrypt for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

No parameters available

Response Structure

794: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "alerts": [
  {
    "text": "This endpoint is deprecated, please use letsencrypt/
    ↪autorenew instead",
    "level": "warning"
  },
  {
    "text": "Beginning async call to renew certificates. This may
    ↪take a few minutes.",
    "level": "success"
  }
]}
```

letsencrypt/dnsrecords

GET

Gets DNS challenge records for Let's Encrypt DNS challenge for a specified FQDN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

Table 338: Request Query Parameters

Name	Required	Description
fqdn	no	Return only DNS challenge records for the specified FQDN

795: Request Example

```
GET /api/3.0/letsencrypt/dnsrecord?fqdn=_acme-challenge.demo1.example.
→com. HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

fqdn The FQDN for the TXT record location to complete the DNS challenge

record The record provided by Let's Encrypt to complete the DNS challenge

796: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": [
  {
    "fqdn": "_acme-challenge.demo1.example.com.",
    "record": "testRecord"
  }
]}
```

logs

Note: This endpoint's responses will contain a cookie (`last_seen_log`) that is used by `logs/newcount` to determine the time of last access. Be sure your client uses cookies properly if you intend to use `logs/newcount` in concert with this endpoint!

GET

Fetches a list of changes that have been made to the Traffic Control system

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 339: Request Query Parameters

Name	Re- quired	Description
days	no	An integer number of days of change logs to return, by default there is no limit applied
limit	no	The number of records to which to limit the response, if there is no limit query params, it limits to 1000
off- set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.
user- name	no	A name to which to limit the response too

New in version ATCv6: The username, page, offset query parameters were added to this in endpoint across across all API versions in ATC version 6.0.0.

797: Request Example

```
GET /api/3.0/logs?days=1&limit=2&username=admin HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- id** Integral, unique identifier for the Log entry
- lastUpdated** Date and time at which the change was made, in *Traffic Ops's Custom Date/Time Format*
- level** Log categories for each entry, e.g. 'UICHANGE', 'OPER', 'APICHANGE'
- message** Log detail about what occurred
- ticketNum** Optional field to cross reference with any bug tracking systems
- user** Name of the user who made the change

798: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 15:11:38 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: last_seen_log="2018-11-15% 15:11:38"; path=/; Max-
→Age=604800
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→40dV+azaZ3b6F30y6YHVbV3H2a3ekZrdoxICupwaxQnj62pwYfb7YCM7Qhe30AItmB77Tbg9INy27ymaz
Content-Length: 357

{ "response": [
  {
    "ticketNum": null,
    "level": "APICHANGE",
    "lastUpdated": "2018-11-14 21:40:06.493975+00",
    "user": "admin",
    "id": 444,
    "message": "User [ test ] unlinked from deliveryservice [ 1 |
→demo1 ]."
  },
  {
    "ticketNum": null,
    "level": "APICHANGE",
    "lastUpdated": "2018-11-14 21:37:30.707571+00",
```

(continues on next page)

(continued from previous page)

```
    "user": "admin",
    "id": 443,
    "message": "1 delivery services were assigned to test"
  }
},
"summary": {
  "count": 2
}
}
```

Summary Fields

The summary object returned by this method of this endpoint uses only the count *standard property*.

logs/newcount

GET

Gets the number of new changes made to the Traffic Control system - “new” being defined as the last time the client requested either *logs*

Note: This endpoint’s functionality is implemented by the *logs* endpoint’s response setting cookies for the client to use when requesting `_this_` endpoint. Take care that your client respects cookies!

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available

Response Structure

newLogcount The integer number of new changes

799: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 15:17:35 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: Ugdqe8GXKSOExphwbDX/
    ↳Gli+2vBpubttbpfYMBJaCP7adox3MzmVRi2RxTDL5kwPewrcL1C088zGITskh0sc9g==
Content-Length: 30

{ "response": {
  "newLogcount": 4
}}
```

origins

GET

Gets all requested *Origins*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 340: Request Query Parameters

Name	Re- quired	Description
cacheGroup	no	Return only <i>Origins</i> within the <i>Cache Group</i> that has this <i>ID</i>
co- ordi- nate	no	Return only <i>Origins</i> located at the geographic coordinates identified by this integral, unique identifier
de- liv- ery- ser- vice	no	Return only <i>Origins</i> that belong to the <i>Delivery Service</i> identified by this integral, unique identifier
id	no	Return only the <i>Origin</i> that has this integral, unique identifier
name	no	Return only <i>Origins</i> by this name
profileId	no	Return only <i>Origins</i> which use the <i>Profile</i> that has this <i>ID</i>
pri- mary	no	If <code>true</code> , return only <i>Origins</i> which are the the primary <i>Origin</i> of the <i>Delivery Service</i> to which they belong - if <code>false</code> return only <i>Origins</i> which are <i>not</i> the primary <i>Origin</i> of the <i>Delivery Service</i> to which they belong
tenant	no	Return only <i>Origins</i> belonging to the tenant identified by this integral, unique identifier
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “ n ” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Note: Several fields of origin definitions which are filterable by Query Parameters are allowed to be `null`. `null` values in these fields will be filtered *out* appropriately by such Query Parameters, but do note that `null` is not a valid value accepted by any of these Query Parameters, and attempting to pass it will result in an error.

800: Request Example

```
GET /api/3.0/origins?name=demo1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cachegroup** A string that is the *name of the Cache Group* to which the *Origin* belongs
- cachegroupId** An integer that is the *ID of the Cache Group* to which the *Origin* belongs
- coordinate** The name of a coordinate pair that defines the origin's geographic location
- coordinateId** An integral, unique identifier for the coordinate pair that defines the *Origin's* geographic location
- deliveryService** A string that is the *xml_id* of the *Delivery Service* to which the *Origin* belongs
- deliveryServiceId** An integral, unique identifier for the *Delivery Service* to which the *Origin* belongs
- fqdn** The FQDN of the *Origin*
- id** An integral, unique identifier for this *Origin*
- ip6Address** The IPv6 address of the *Origin*
- ipAddress** The IPv4 address of the *Origin*
- isPrimary** A boolean value which, when `true` specifies this *Origin* as the 'primary' *Origin* served by `deliveryService`
- lastUpdated** The date and time at which this *Origin* was last modified
- name** The name of the *Origin*
- port** The TCP port on which the *Origin* listens
- profile** The *Name* of the *Profile* used by this *Origin*
- profileId** The *ID* of the *Profile* used by this *Origin*
- protocol** The protocol used by this origin - will be one of 'http' or 'https'
- tenant** The name of the *Tenant* that owns this *Origin*
- tenantId** An integral, unique identifier for the *Tenant* that owns this *Origin*

801: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→sm8DpvdvrfdSVLtmXTdfjsZbTlbc+pI40Gy0aj00XIURTPfFXuv/
→4LgHb6A3r92iybRHvFrH6qdB2g97U2sBg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 15:43:41 GMT
Content-Length: 376
```

```
{ "response": [
  {
    "cachegroup": null,
    "cachegroupId": null,
    "coordinate": null,
    "coordinateId": null,
    "deliveryService": "demo1",
    "deliveryServiceId": 1,
    "fqdn": "origin.infra.ciab.test",
    "id": 1,
    "ip6Address": null,
    "ipAddress": null,
    "isPrimary": true,
    "lastUpdated": "2018-12-10 19:11:32+00",
    "name": "demo1",
    "port": null,
    "profile": null,
    "profileId": null,
    "protocol": "http",
    "tenant": "root",
    "tenantId": 1
  }
]}
```

POST

Creates a new origin definition.

Warning: At the time of this writing it is possible to create and/or modify origin definitions assigned to STEERING and CLIENT_STEERING *Delivery Services* - despite that an origin has no meaning in those contexts. In these cases, the API responses may give incorrect output - see [GitHub Issue #3107](#) for details and updates.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cachegroupId An optional, integer which, if present, should be the *Cache Group ID* that identifies a *Cache Group* to which the new *Origin* shall belong

coordinateId An optional, integral, unique identifier of a coordinate pair that shall define the *Origin*’s geographic location

deliveryServiceId The integral, unique identifier of the *Delivery Service* to which the new *Origin* shall belong

fqdn The FQDN of the *Origin*

ip6Address An optional string containing the IPv6 address of the *Origin*

ipAddress An optional string containing the IPv4 address of the *Origin*

isPrimary An optional boolean which, if `true` will set this *Origin* as the ‘primary’ *Origin* served by the *Delivery Service* identified by `deliveryServiceID`

Note: Though not specifying this field in this request will leave it as `null` in the output, Traffic Ops will silently coerce that to its default value: `false`.

name A human-friendly name of the *Origin*

port An optional port number on which the *Origin* listens for incoming TCP connections

profileId An optional *ID* of a *Profile* that shall be used by this *Origin*

protocol The protocol used by the origin - must be one of ‘http’ or ‘https’

tenantId An optional¹, integral, unique identifier for the *Tenant* which shall own the new *Origin*

¹ The `tenantId` field is required if and only if tenancy is enabled within Traffic Ops.

802: Request Example

```
POST /api/3.0/origins HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 114
Content-Type: application/json

{
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "name": "example",
  "port": 80,
  "protocol": "http",
  "tenantId": 1
}
```

Response Structure

- cachegroup** A string that is the *name of the Cache Group* to which the *Origin* belongs
- cachegroupId** An integer that is the *ID of the Cache Group* to which the *Origin* belongs
- coordinate** The name of a coordinate pair that defines the origin's geographic location
- coordinateId** An integral, unique identifier for the coordinate pair that defines the *Origin's* geographic location
- deliveryService** The 'xml_id' of the *Delivery Service* to which the *Origin* belongs
- deliveryServiceId** An integral, unique identifier for the *Delivery Service* to which the *Origin* belongs
- fqdn** The FQDN of the *Origin*
- id** An integral, unique identifier for this *Origin*
- ip6Address** The IPv6 address of the *Origin*
- ipAddress** The IPv4 address of the *Origin*
- isPrimary** A boolean value which, when `true` specifies this *Origin* as the 'primary' *Origin* served by *deliveryService*
- lastUpdated** The date and time at which this *Origin* was last modified
- name** The name of the *Origin*

- port** The TCP port on which the *Origin* listens
- profile** The *Name* of the *Profile* used by this *Origin*
- profileId** The *ID* the *Profile* used by this *Origin*
- protocol** The protocol used by this origin - will be one of 'http' or 'https'
- tenant** The name of the *Tenant* that owns this *Origin*
- tenantId** An integral, unique identifier for the *Tenant* that owns this *Origin*

803: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→z4gp0MaqYu+gSRORhKT2e0bVBuVDVx1rdteRaN5kRL9uJ3hNzUCi4dSKIt0rgNgOEDt6x/
→iTYrmVhr/TSHYtmA==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 15:14:27 GMT
Content-Length: 418

{ "alerts": [
  {
    "text": "origin was created.",
    "level": "success"
  }
],
"response": {
  "cachegroup": null,
  "cachegroupId": null,
  "coordinate": null,
  "coordinateId": null,
  "deliveryService": null,
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "id": 2,
  "ip6Address": null,
  "ipAddress": null,
  "isPrimary": null,
  "lastUpdated": "2018-12-11 15:14:27+00",
  "name": "example",
```

(continues on next page)

(continued from previous page)

```
"port": 80,
"profile": null,
"profileId": null,
"protocol": "http",
"tenant": null,
"tenantId": 1
}}
```

PUT

Updates an *Origin* definition.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 341: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Origin</i> definition being edited

cachegroupId An optional, integer which, if present, should be the *Cache Group ID* that identifies a *Cache Group* to which the new *Origin* shall belong

coordinateId An optional, integral, unique identifier of a coordinate pair that shall define the *Origin*’s geographic location

deliveryServiceId The integral, unique identifier of the *Delivery Service* to which the *Origin* shall belong

fqdn The FQDN of the *Origin*

ip6Address An optional string containing the IPv6 address of the *Origin*

ipAddress An optional string containing the IPv4 address of the *Origin*

isPrimary An optional boolean which, if `true` will set this *Origin* as the ‘primary’ origin served by the *Delivery Service* identified by `deliveryServiceID`

name A human-friendly name of the *Origin*

port An optional port number on which the *Origin* listens for incoming TCP connections

profileId An optional *ID* of the *Profile* that shall be used by this *Origin*

protocol The protocol used by the *Origin* - must be one of ‘http’ or ‘https’

tenantId An optional^{Page 1245, 1}, integral, unique identifier for the *Tenant* which shall own the new *Origin*

804: Request Example

```
PUT /api/3.0/origins?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 135
Content-Type: application/json

{
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "isprimary": true,
  "name": "example",
  "port": 443,
  "protocol": "https",
  "tenantId": 1
}
```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the *Origin* belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the *Origin* belongs

coordinate The name of a coordinate pair that defines the origin's geographic location

coordinateId An integral, unique identifier for the coordinate pair that defines the *Origin's* geographic location

deliveryService The 'xml_id' of the *Delivery Service* to which the *Origin* belongs

deliveryServiceId An integral, unique identifier for the *Delivery Service* to which the *Origin* belongs

fqdn The FQDN of the *Origin*

id An integral, unique identifier for this *Origin*

ip6Address The IPv6 address of the *Origin*

ipAddress The IPv4 address of the *Origin*

isPrimary A boolean value which, when true specifies this *Origin* as the 'primary' *Origin* served by deliveryService

lastUpdated The date and time at which this *Origin* was last modified

name The name of the *Origin*

port The TCP port on which the *Origin* listens

profile The *Name* of the *Profile* used by this *Origin*

profileId The *ID* the *Profile* used by this *Origin*

protocol The protocol used by this origin - will be one of 'http' or 'https'

tenant The name of the *Tenant* that owns this *Origin*

tenantId An integral, unique identifier for the *Tenant* that owns this *Origin*

805: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Zx7j0a7UAQxRtDenYodvGQSoooPj4m0yY0AIEUpbdelmYMiNdPYtW82BCmMesFXkmP74nV4HbTUyDHVMu.
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 15:40:53 GMT
Content-Length: 420

{ "alerts": [
  {
    "text": "origin was updated.",
    "level": "success"
  }
],
"response": {
  "cachegroup": null,
  "cachegroupId": null,
  "coordinate": null,
  "coordinateId": null,
  "deliveryService": null,
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "id": 2,
  "ip6Address": null,
  "ipAddress": null,
  "isPrimary": true,
```

(continues on next page)

(continued from previous page)

```
"lastUpdated": "2018-12-11 15:40:53+00",
"name": "example",
"port": 443,
"profile": null,
"profileId": null,
"protocol": "https",
"tenant": null,
"tenantId": 1
}}
```

DELETE

Deletes an *Origin* definition.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 342: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Origin</i> definition being deleted

806: Request Example

```
DELETE /api/3.0/origins?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

807: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: fLaY4/
→nh0yR38xq5weBKYg02+aQV6Z1Zro0q9UqUCHLMMrH1NMyhOHx+EphPq7JxkjmGY04WCt6VvDyjGWcgfQ==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 17:04:14 GMT
Content-Length: 61

{ "alerts": [
  {
    "text": "origin was deleted.",
    "level": "success"
  }
]}

```

osversions

See also:

Generate ISO

GET

Gets all available OS versions for ISO generation, as well as the name of the directory where the “kickstarter” files are found.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

This endpoint has no constant keys in its response. Instead, each key in the response object is the name of an OS, and the value is a string that names the directory where the ISO source can be found. These directories sit under `/var/www/files/` on the Traffic Ops host machine by default, or at the location defined by the `kickstart.files.location` *Parameter* of the Traffic Ops server's *Profile*, if it is defined.

808: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳RxbRY2DZ+1Y0dTzzUETEZ3wtLBiD2BwXMVuaZjhe4a4cwgcZKRBWxZ6Qy5YYujFe1+UBiTG4sML/
    ↳Amn27F4AVg==
X-Server-Name: traffic_ops_golang/
Date: Fri, 30 Nov 2018 19:14:36 GMT
Content-Length: 38

{ "response": {
  "CentOS 7.2": "centos72"
}}
```

Configuration File

The data returned from the endpoint comes directly from a configuration file. By default, the file is located at `/var/www/files/osversions.json`. The **directory** of the file can be changed by creating a specific *Parameter* named `kickstart.files.location` in configuration file `mkisofs`.

The format of the file is a JSON object as described in *Response Structure*.

809: Example osversions.json file

```
{
  "CentOS 7.2": "centos72"
}
```

The legacy Perl Traffic Ops used a Perl configuration file located by default at `/var/www/files/osversions.cfg`. A Perl script is provided to convert the legacy configuration file to the new JSON format. The script is located within the Traffic Control repository at

traffic_ops/app/bin/osversions-convert.pl.

810: Example usage of conversion script

```
./osversions-convert.pl < /var/www/files/osversions.cfg > /var/www/  
→files/osversions.json
```

parameterprofile

POST

Create one or more *Parameter/Profile* assignments.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

paramId The *ID* of the *Parameter* to be assigned to the *Profiles* identified within the profileIds array

profileIds An array of *Profile IDs* to which the *Parameter* identified by paramId shall be assigned

replace An optional boolean (default: false) which, if true, will cause any conflicting *Profile/Parameter* assignments to be overridden.

811: Request Example

```
POST /api/3.0/parameterprofile HTTP/1.1  
Host: trafficops.infra.ciab.test  
User-Agent: curl/7.47.0  
Accept: */*  
Cookie: mojolicious=...  
Content-Length: 38  
Content-Type: application/json  
  
{  
  "paramId": 4,  
  "profileIds": [18]  
}
```

Response Structure

paramId The *ID* of the *Parameter* which has been assigned to the *Profiles* identified within the `profileIds` array

profileIds An array of *Profile IDs* to which the *Parameter* identified by `paramId` has been assigned

replace An optional boolean (default: false) which, if true, caused any conflicting *Profile/Parameter* assignments to be overridden.

812: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳N2ahnhEnfZ0UqnjylN6Vu3HaOZk340YuiuyiqkhTbk0pENp+kwBPYu4Z/
    ↳sqBAloCfXSQaWlJzaeXw4uOD5heWw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 15:18:23 GMT
Content-Length: 147

{ "alerts": [
  {
    "text": "2 parameters were assigned to the 18 profile",
    "level": "success"
  }
],
"response": {
  "profileId": 18,
  "paramIds": [
    2,
    3
  ],
  "replace": false
}}
```

parameters

GET

Gets all *Parameters* configured in Traffic Ops

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 343: Request Query Parameters

Name	Re- quired	Description
con- fig- File	no	Filter <i>Parameters</i> by <i>Config File</i>
id	no	Filters <i>Parameters</i> by <i>ID</i>
name	no	Filter <i>Parameters</i> by <i>Name</i>
value	no	Filter <i>Parameters</i> by <i>Value</i>
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

New in version ATCv6: The value query parameter was added to all API versions in ATC version 6.0.

813: Request Example

```
GET /api/3.0/parameters?configFile=records.config&name=location HTTP/1.
↪1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```


Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name of the Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

814: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
→jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
→DbBwhMAOJoeqDImoDlrLnrvjQGO4AooA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 18:23:39 GMT
Content-Length: 212

{ "response": [
  {
    "configFile": "records.config",
    "id": 29,
    "lastUpdated": "2018-12-05 17:51:02+00",
    "name": "location",
    "profiles": [
      "ATS_EDGE_TIER_CACHE",
      "ATS_MID_TIER_CACHE"
    ],
    "secure": false,
    "value": "/etc/trafficserver/"
  }
]}
```

POST

Creates one or more new *Parameters*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

The request body may be in one of two formats, a single *Parameter* object or an array of *Parameter* objects. Each *Parameter* object shall have the following keys:

configFile The *Parameter*’s *Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*’s *Value*

815: Request Example - Single Object Format

```
POST /api/3.0/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 84
Content-Type: application/json

{
  "name": "test",
  "value": "quest",
  "configFile": "records.config",
  "secure": false
}
```

816: Request Example - Array Format

```
POST /api/3.0/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 180
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
[{
  "name": "test",
  "value": "quest",
  "configFile": "records.config",
  "secure": false
},
{
  "name": "foo",
  "value": "bar",
  "configFile": "records.config",
  "secure": false
}]
```

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name of the Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

817: Response Example - Single Object Format

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→eQrl48zWids0kDpfCYmntYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
→Cfh2X9i3G+MQ36eH95gukJqOBOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:18:21 GMT
Content-Length: 212
```

(continues on next page)

(continued from previous page)

```
{ "alerts": [
  {
    "text": "param was created.",
    "level": "success"
  }
],
"response": {
  "configFile": "records.config",
  "id": 124,
  "lastUpdated": "2018-12-05 19:18:21+00",
  "name": "test",
  "profiles": null,
  "secure": false,
  "value": "quest"
}}
```

parameters/{{ID}}

PUT

Replaces a *Parameter*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 344: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Parameter</i> which will be deleted

configFile The *Parameter*’s *Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*’s *Value*

818: Request Example

```
PUT /api/3.0/parameters/124 HTTP/1.1
Host: trafficops.infra.ciab.test
```

(continues on next page)

(continued from previous page)

```
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 81
Content-Type: application/json

{
  "name": "foo",
  "value": "bar",
  "configFile": "records.config",
  "secure": false
}
```

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name of the Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

819: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: DMxS2gKceFVKRtezON/
→vsnrC+zI8onASSHaGv5i3wwvUvyt9KEe72gxQd6ZgVcSq3K8ZpkH6g3UI/WtEfdp5vA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 20:21:07 GMT
Content-Length: 209

{ "alerts": [
```

(continues on next page)

(continued from previous page)

```
{
  "text": "param was updated.",
  "level": "success"
},
"response": {
  "configFile": "records.config",
  "id": 125,
  "lastUpdated": "2018-12-05 20:21:07+00",
  "name": "foo",
  "profiles": null,
  "secure": false,
  "value": "bar"
}}
```

DELETE

Deletes the specified *Parameter*. If, however, the *Parameter* is associated with one or more *Profiles*, deletion will fail.

Auth. Required Yes

Roles Required “admin” or “operations”

Response TYPe undefined

Request Structure

Table 345: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Parameter</i> which will be deleted

820: Request Example

```
DELETE /api/3.0/parameters/124 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

821: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: hJjQq2Seg7sqWt+jKgp6gwRxUtoVU34PFoc9wEaweXdaIBTn/
    ↳BscoUuyw2/n+V8GZPqpeQcihZE50/0oQhdtHw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:20:30 GMT
Content-Length: 60

{ "alerts": [
  {
    "text": "param was deleted.",
    "level": "success"
  }
]}
```

phys_locations

GET

Retrieves *Physical Locations*

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 346: Request Query Parameters

Name	Description
id	Filter by integral, unique identifier
re-gion	Filter by integral, unique identifier of containing <i>Region</i>
name	Filter by name
or-derby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

822: Request Example

```
GET /api/3.0/phys_locations?name=CDN_in_a_Box HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- address** The physical location’s street address
- city** The name of the city in which the physical location lies
- comments** Any and all human-readable comments
- email** The email address of the physical location’s poc
- id** An integral, unique identifier for the physical location
- lastUpdated** The date and time at which the physical location was last updated, in *Traffic Ops’s Custom Date/Time Format*
- name** The name of the physical location
- phone** A phone number where the the physical location’s poc might be reached
- poc** The name of a “point of contact” for the physical location
- region** The name of the region within which the physical location lies

regionId An integral, unique identifier for the region within which the physical location lies

shortName An abbreviation of the name

state An abbreviation of the name of the state or province within which this physical location lies

zip The zip code of the physical location

823: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳0g4b3W1AwXytCnBo8TReQQij2v9oHA17MG9KuwMig5V4sFcMM5qP8dgPsFTunFr00DPI20c7BpUbZsvJts
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 22:19:52 GMT
Content-Length: 275

{ "response": [
  {
    "address": "1600 Pennsylvania Avenue NW",
    "city": "Washington",
    "comments": "",
    "email": "",
    "id": 2,
    "lastUpdated": "2018-12-05 17:50:58+00",
    "name": "CDN_in_a_Box",
    "phone": "",
    "poc": "",
    "regionId": 1,
    "region": "Washington, D.C",
    "shortName": "ciab",
    "state": "DC",
    "zip": "20500"
  }
]}
```

POST

Creates a new physical location

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

address The physical location’s street address

city The name of the city in which the physical location lies

comments An optional string for containing any and all human-readable comments

email An optional string containing email address of the physical location’s poc

name An optional name of the physical location

phone An optional string containing the phone number where the the physical location’s poc might be reached

poc The name of a “point of contact” for the physical location

region An optional string naming the region that contains this physical location¹

regionId An integral, unique identifier for the region within which the physical location lies¹

shortName An abbreviation of the name

state An abbreviation of the name of the state or province within which this physical location lies

zip The zip code of the physical location

824: Request Example

```
POST /api/3.0/phys_locations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 326
Content-Type: application/json
```

(continues on next page)

¹ The only “region” key that actually matters in the request body is **regionId**; **region** is not validated and has no effect - particularly not the effect of re-naming the region - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the region. Note that if **region** is not present in the request body it will be **null** in the response, but again further requests will show the true region name.

(continued from previous page)

```
{
  "address": "Buckingham Palace",
  "city": "London",
  "comments": "Buckingham Palace",
  "email": "steve.kingstone@royal.gsx.gov.uk",
  "name": "Great_Britain",
  "phone": "0-843-816-6276",
  "poc": "Her Majesty The Queen Elizabeth Alexandra Mary Windsor II",
  "regionId": 3,
  "shortName": "uk",
  "state": "Westminster",
  "zip": "SW1A 1AA"
}
```

Response Structure

- address** The physical location's street address
- city** The name of the city in which the physical location lies
- comments** Any and all human-readable comments
- email** The email address of the physical location's poc
- id** An integral, unique identifier for the physical location
- lastUpdated** The date and time at which the physical location was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the physical location
- phone** A phone number where the the physical location's poc might be reached
- poc** The name of a "point of contact" for the physical location
- region** The name of the region within which the physical location lies
- regionId** An integral, unique identifier for the region within which the physical location lies
- shortName** An abbreviation of the name
- state** An abbreviation of the name of the state or province within which this physical location lies
- zip** The zip code of the physical location

825: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: GZ/
    ↳BC+AgGpOQNfd9oiZy19jtsD8MP0deyi7PVdz+9YSiLYP44gmn5K+Xi1yS0l59yjHf70+C1loVQPSlIeP9
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 00:14:47 GMT
Content-Length: 443

{ "alerts": [
  {
    "text": "physLocation was created.",
    "level": "success"
  }
],
"response": {
  "address": "Buckingham Palace",
  "city": "London",
  "comments": "Buckingham Palace",
  "email": "steve.kingstone@royal.gsx.gov.uk",
  "id": 3,
  "lastUpdated": "2018-12-06 00:14:47+00",
  "name": "Great_Britain",
  "phone": "0-843-816-6276",
  "poc": "Her Majesty The Queen Elizabeth Alexandra Mary Windsor II",
  "regionId": 3,
  "region": null,
  "shortName": "uk",
  "state": "Westminster",
  "zip": "SW1A 1AA"
}}
```

`phys_locations/{ID}`

PUT

Updates a *Physical Location*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

Table 347: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Physical Location</i> being modified

address The physical location’s street address

city The name of the city in which the physical location lies

comments An optional string for containing any and all human-readable comments

email An optional string containing email address of the physical location’s poc

name An optional name of the physical location

phone An optional string containing the phone number where the the physical location’s poc might be reached

poc The name of a “point of contact” for the physical location

region An optional string naming the region that contains this physical location¹

regionId An integral, unique identifier for the region within which the physical location lies¹

shortName An abbreviation of the name

state An abbreviation of the name of the state or province within which this physical location lies

zip The zip code of the physical location

826: Request Structure

```
PUT /api/3.0/phys_locations/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 268
Content-Type: application/json

{
  "address": "1600 Pennsylvania Avenue NW",
  "city": "Washington",
  "comments": "The White House",
```

(continues on next page)

¹ The only “region” key that actually matters in the request body is regionId; region is not validated and has no effect - particularly not the effect of re-naming the region - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the region. Note that if region is not present in the request body it will be null in the response, but again further requests will show the true region name.

(continued from previous page)

```
"email": "the@white.house",
"name": "CDN_in_a_Box",
"phone": "1-202-456-1414",
"poc": "Donald J. Trump",
"regionId": 2,
"shortName": "ciab",
"state": "DC",
"zip": "20500"
}
```

Response Structure

- address** The physical location's street address
- city** The name of the city in which the physical location lies
- comments** Any and all human-readable comments
- email** The email address of the physical location's poc
- id** An integral, unique identifier for the physical location
- lastUpdated** The date and time at which the physical location was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the physical location
- phone** A phone number where the the physical location's poc might be reached
- poc** The name of a "point of contact" for the physical location
- region** The name of the region within which the physical location lies
- regionId** An integral, unique identifier for the region within which the physical location lies
- shortName** An abbreviation of the name
- state** An abbreviation of the name of the state or province within which this physical location lies
- zip** The zip code of the physical location

827: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→qnMe60qxjSU8H1njlh00HWNr20YnVlOCufqCTdMBcdC1322jk2ICFQsQQ3Xu0OR0WSb7h70HCfXqDC1/
→jA1xjA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 23:39:17 GMT
Content-Length: 385

{ "alerts": [
  {
    "text": "physLocation was updated.",
    "level": "success"
  }
],
"response": {
  "address": "1600 Pennsylvania Avenue NW",
  "city": "Washington",
  "comments": "The White House",
  "email": "the@white.house",
  "id": 2,
  "lastUpdated": "2018-12-05 23:39:17+00",
  "name": "CDN_in_a_Box",
  "phone": "1-202-456-1414",
  "poc": "Donald J. Trump",
  "regionId": 2,
  "region": null,
  "shortName": "ciab",
  "state": "DC",
  "zip": "20500"
}}
```

DELETE

Deletes a *Physical Location*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 348: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Physical Location</i> being deleted

828: Request Example

```
DELETE /api/3.0/phys_locations/3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

829: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: KeW/tEmICwpCGC8F0YMTqHdeR9J6W6Z3w/
    ↳U+H0SbeCGyaEheCIhIsWlngT3dyfH1tiu8UyzaPB6QrJyXdybBkw==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 00:28:48 GMT
Content-Length: 67

{ "alerts": [
  {
    "text": "physLocation was deleted.",
    "level": "success"
  }
]}
```


ping

Checks whether Traffic Ops is online.

GET

Auth. Required No

Response Type undefined

Request Structure

No parameters available.

830: Request Example

```
GET /api/3.0/ping HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

ping Returns an object containing only the "ping" property, which always has the value "pong".

831: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Whole-Content-Sha512: 0HqcLcYHCB4AFYGFzcAsP2h+PCmLYxk/
↳TqMajcy3fWCzY730Tv32k5trUaJLeSBbRx2FUi7z/sTAuzikdg0E4g==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 20:52:01 GMT
Content-Length: 40
Content-Type: application/x-gzip

{
```

(continues on next page)

(continued from previous page)

```
"ping": "pong"
}
```

plugins

See also:

Go Plugins

GET

Retrieves the list of configured enabled Traffic Ops plugins.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

832: Request Example

```
GET /api/3.0/plugins HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

description A short description of the plugin.

name The name of the plugin.

version A (hopefully) semantic version number describing the version of the plugin.

833: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
Access-Control-Allow-Methods: POST, GET, OPTIONS, PUT, DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Tue, 11 Dec 2018 20:51:48 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↪GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: n73jg9XR4V5Cwqq56Rf3wuIi99k3mM5u2NAjcZ/
    ↪gQBu8jvAFymDlnZqKeJ+wTll1vjIsHpXC0VXV7+5UGakLgA==
Transfer-Encoding: chunked

{ "response": [
  {
    "name": "helloworld",
    "version": "1.0.0",
    "description": "configuration plugin to run at startup"
  }
]
}
```

profileparameter

See also:

profileparameters.

POST

Create one or more *Profile/Parameter* assignments.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

profileId The *ID* of the *Profile* to which the *Parameters* identified within the *parameterIds* array will be assigned

paramIds An array of *Parameter IDs* which shall be assigned to the *Profile* identified by *profileId*

replace An optional boolean (default: false) which, if true, will cause any conflicting *Profile/Parameter* assignments to be overridden.

834: Request Example

```
POST /api/3.0/profileparameter HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 38
Content-Type: application/json

{
  "profileId": 18,
  "paramIds": [2, 3]
}
```

Response Structure

- profileId** The *ID* of the *Profile* to which the *Parameters* identified within the *parameterIds* array are assigned
- paramIds** An array of *Parameter IDs* which have been assigned to the *Profile* identified by *profileId*
- replace** An optional boolean (default: false) which, if true, indicates that any conflicting *Profile/Parameter* assignments have been overridden.

835: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→N2ahnhEnfZ0UqnjylN6Vu3HaOZk340YuiuyiqkhTbk0pENp+kwBPYu4Z/
→sqBAloCfXSQaWlJzaeXw4uOD5heWw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 15:18:23 GMT
Content-Length: 147

{ "alerts": [
  {
    "text": "2 parameters were assigned to the 18 profile",
```

(continues on next page)

(continued from previous page)

```

        "level": "success"
    }
],
"response": {
    "profileId": 18,
    "paramIds": [
        2,
        3
    ],
    "replace": false
}}

```

profileparameters

GET

Retrieves all *Parameter/Profile* assignments.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 349: Request Query Parameters

Name	Re- quired	Description
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Response Structure

lastUpdated The date and time at which this *Profile/Parameter* association was last modified, in *Traffic Ops's Custom Date/Time Format*

parameter The *ID* of a *Parameter* assigned to profile

profile The *Name* of the *Profile* to which the *Parameter* identified by parameter is assigned

836: Response Structure

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳+bnMkRgdx4bJoGGlr3mZl539obj3aQAP8e65FAXgywdRAUfXZCFM6VNDn7wScXBmvF2SFXo9F+MhuSwrtI
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 15:09:13 GMT
Transfer-Encoding: chunked

{ "response": [
  {
    "lastUpdated": "2018-12-05 17:50:49+00",
    "profile": "GLOBAL",
    "parameter": 4
  },
  {
    "lastUpdated": "2018-12-05 17:50:49+00",
    "profile": "GLOBAL",
    "parameter": 5
  }
]}
```

Note: The response example for this endpoint has been truncated to only the first two elements of the resulting array, as the output was hundreds of lines long.

POST

Associate a *Parameter* to a *Profile*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

This endpoint accepts two formats for the request payload:

Single Object Format For assigning a single *Parameter* to a single *Profile*

Array Format For making multiple assignments of *Parameters* to *Profiles* simultaneously

Single Object Format

parameterId The *ID* of a *Parameter* to assign to some *Profile*

profileId The *ID* of the *Profile* to which the *Parameter* identified by parameterId will be assigned

837: Request Example - Single Object Format

```
POST /api/3.0/profileparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 36
Content-Type: application/json

{
  "profileId": 18,
  "parameterId": 1
}
```

Array Format

parameterId The *ID* of a *Parameter* to assign to some *Profile*

profileId The *ID* of the *Profile* to which the *Parameter* identified by parameterId will be assigned

838: Request Example - Array Format

```
POST /api/3.0/profileparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 88
Content-Type: application/json

[
  {
    "profileId": 18,
    "parameterId": 2
  },
  {
    "profileId": 18,
    "parameterId": 3
  }
]
```


Response Structure

lastUpdated The date and time at which the *Profile/Parameter* assignment was last modified, in *Traffic Ops's Custom Date/Time Format*

parameter *Name* of the *Parameter* which is assigned to profile

parameterId The *ID* of the assigned *Parameter*

profile *Name* of the *Profile* to which the *Parameter* is assigned

profileId The *ID* of the *Profile* to which the *Parameter* identified by parameterId is assigned

839: Response Example - Single Object Format

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳eDmIwlzX44fZdxLRPHMNa8aoGAK5fQv9Y70A2eeQHfEkliU4evwcsQ4WeHcH0l3/
    ↳wPTGlpYC0gwLo8LQqpUxWQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 13:50:11 GMT
Content-Length: 166

{ "alerts": [
  {
    "text": "profileParameter was created.",
    "level": "success"
  }
],
"response": {
  "lastUpdated": null,
  "profile": null,
  "profileId": 18,
  "parameter": null,
  "parameterId": 1
}}
```

profileparameters/{profileID}/{parameterID}

DELETE

Deletes a *Profile/Parameter* association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 350: Request Path Parameters

Name	Description
profileID	The <i>ID</i> of the <i>Profile</i> from which a <i>Parameter</i> shall be removed
parameterID	The <i>ID</i> of the <i>Parameter</i> which shall be removed from the <i>Profile</i> identified by profileID

840: Request Example

```
DELETE /api/3.0/profileparameters/18/129 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

841: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳JQuBqHyT9MnNw09NSIDVQhkRtXdeAJc95W1pF2dwQeoBFmf0Y8knXm3/0/
    ↳rbJDEoUC7DhUQN1aoYIsqqmz4qQQ==
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

Date: Mon, 10 Dec 2018 15:00:15 GMT

Content-Length: 71

```
{ "alerts": [
  {
    "text": "profileParameter was deleted.",
    "level": "success"
  }
]}
```

profiles

GET

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 351: Request Query Parameters

Name	Re- quired	Description
cdn	no	Used to filter <i>Profiles</i> by the integral, unique identifier of the CDN to which they belong
id	no	Filters <i>Profiles</i> by <i>ID</i>
name	no	Filters <i>Profiles</i> by <i>Name</i>
param	no	Used to filter <i>Profiles</i> by the <i>ID</i> of a <i>Parameter</i> associated with them

842: Request Example

```
GET /api/3.0/profiles?name=ATS_EDGE_TIER_CACHE HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cdn** The integral, unique identifier of the *CDN* to which this *Profile* belongs
- cdnName** The name of the *CDN* to which this *Profile* belongs
- description** The *Profile*'s *Description*
- id** The *Profile*'s *ID*
- lastUpdated** The date and time at which this *Profile* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The *Profile*'s *Name*
- routingDisabled** The *Profile*'s *Routing Disabled* setting
- type** The *Profile*'s *Type*

843: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: QEpKM/
    ↳DwHBRvue9K7XKrpwKFKhW6yCMQ2vSQgxE7dWFGJaqC4KOU092bsJU/
    ↳5fjI9qlB+1uMT2kz6mFb1Wzp/w==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 20:40:31 GMT
Content-Length: 220

{ "response": [
  {
    "id": 9,
    "lastUpdated": "2018-12-05 17:51:00+00",
```

(continues on next page)

(continued from previous page)

```

    "name": "ATS_EDGE_TIER_CACHE",
    "description": "Edge Cache - Apache Traffic Server",
    "cdnName": "CDN-in-a-Box",
    "cdn": 2,
    "routingDisabled": false,
    "type": "ATS_PROFILE"
  }
}]

```

POST

Creates a new *Profile*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cdn The integral, unique identifier of the *CDN* to which this *Profile* shall belong

description The *Profile*’s *Description*

name The *Profile*’s *Name*

routingDisabled The *Profile*’s *Routing Disabled* setting

type The *Profile*’s *Type*

844: Request Example

```

POST /api/3.0/profiles HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 125
Content-Type: application/json

{
  "name": "test",
  "description": "A test profile for API examples",
  "cdn": 2,
  "type": "UNK_PROFILE",
  "routingDisabled": true
}

```

Response Structure

- cdn** The integral, unique identifier of the *CDN* to which this *Profile* belongs
- cdnName** The name of the *CDN* to which this *Profile* belongs
- description** The *Profile's Description*
- id** The *Profile's ID*
- lastUpdated** The date and time at which this *Profile* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The *Profile's Name*
- routingDisabled** The *Profile's Routing Disabled* setting
- type** The *Profile's Type*

845: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→UGV3PCnYBY0J3siICR0f9VVRNdUK1+9zsDDP6T9yt6t+AoHckHe6bvz0li9to/
→fGhC2zz5l9Nc1ro4taJUDD8g==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 21:24:49 GMT
Content-Length: 251

{ "alerts": [
  {
    "text": "profile was created.",
    "level": "success"
  }
],
"response": {
  "id": 16,
  "lastUpdated": "2018-12-07 21:24:49+00",
  "name": "test",
  "description": "A test profile for API examples",
  "cdnName": null,
  "cdn": 2,
  "routingDisabled": true,
```

(continues on next page)

(continued from previous page)

```
"type": "UNK_PROFILE"
}}
```

`profiles/{{ID}}`

PUT

Replaces the specified *Profile* with the one in the request payload

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 352: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> being modified

cdn The integral, unique identifier of the *CDN* to which this *Profile* will belong

description The *Profile*’s new *Description*

name The *Profile*’s new *Name*

routingDisabled The *Profile*’s new *Routing Disabled* setting

type The *Profile*’s new *Type*

Warning: Changing this will likely break something, be **VERY** careful when modifying this value

846: Request Example

```
PUT /api/3.0/profiles/16 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 125
Content-Type: application/json

{
```

(continues on next page)

(continued from previous page)

```
"name": "test",
"description": "A test profile for API examples",
"cdn": 2,
"type": "UNK_PROFILE",
"routingDisabled": true
}
```

Response Structure

- cdn** The integral, unique identifier of the *CDN* to which this *Profile* belongs
- cdnName** The name of the *CDN* to which this *Profile* belongs
- description** The *Profile*'s *Description*
- id** The *Profile*'s *ID*
- lastUpdated** The date and time at which this *Profile* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The *Profile*'s *Name*
- routingDisabled** The *Profile*'s *Routing Disabled* setting
- type** The *Profile*'s *Type*

847: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Pnf+G9G3/
→+edt4b8PVsyGZHsNzaFEgphaGSminjRlRmMpWtuLAA20WZDUo3nX0Q081c2GCuFuEh9uMF2Vjeppg==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 21:45:06 GMT
Content-Length: 251

{ "alerts": [
  {
    "text": "profile was updated.",
    "level": "success"
  }
],
```

(continues on next page)

(continued from previous page)

```
"response": {
  "id": 16,
  "lastUpdated": "2018-12-07 21:45:06+00",
  "name": "test",
  "description": "A test profile for API examples",
  "cdnName": null,
  "cdn": 2,
  "routingDisabled": true,
  "type": "UNK_PROFILE"
}}
```

DELETE

Allows user to delete a *Profile*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 353: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> being deleted

848: Request Example

```
DELETE /api/3.0/profiles/16 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

849: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: HNmJkZaNW9yil08/
→3TnqZ5FllH6Rp+jgp3KI46FZdojLYcu+8jEhDL1lokoirdrHyU4R1c3hjCI0urN7PVvWDA==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 21:55:33 GMT
Content-Length: 62

{ "alerts": [
  {
    "text": "profile was deleted.",
    "level": "success"
  }
]}
```

`profiles/{{ID}}/export`

GET

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 354: Request Path Parameters

Parameter	Description
id	The <i>ID</i> of the <i>Profile</i> to be exported

850: Request Example

```
GET /api/3.0/profiles/3/export HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- profile** The exported *Profile*
 - cdn** The name of the *CDN* to which this *Profile* belongs
 - description** The *Profile's Description*
 - name** The *Profile's Name*
 - type** The *Profile's Type*
- parameters** An array of *Parameters* in use by this *Profile*
 - config_file** The *Parameter's Config File*
 - name** *Name* of the *Parameter*
 - value** The *Parameter's Value*

851: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Disposition: attachment; filename="GLOBAL.json"
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mzP7DVxFAGhICxqagwDyBDRea7oBZPMAx7NCDeOBVCRqlcCFFe7XL3JP58b80aaVOW/
    ↳2ZGfg/jpYF70cdDfzQA==
X-Server-Name: traffic_ops_golang/
Date: Fri, 13 Sep 2019 20:14:42 GMT
Transfer-Encoding: gzip

{ "profile": {
  "name": "GLOBAL",
  "description": "Global Traffic Ops profile",
  "cdn": "ALL",
  "type": "UNK_PROFILE"
},
  "parameters": [
    {
      "config_file": "global",
      "name": "tm.instance_name",
      "value": "Traffic Ops CDN"
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```

    },
    {
      "config_file": "global",
      "name": "tm.toolname",
      "value": "Traffic Ops"
    }
  ]
}
```

profiles/{{ID}}/parameters

GET

Retrieves all *Parameters* assigned to the *Profile*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 355: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> for which <i>Parameters</i> will be listed

852: Request Example

```

GET /api/3.0/parameters/profile/GLOBAL HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name* of the *Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

853: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: NudgZXUNyKNpmSFf856KEjyy+Pin/
    ↳bFhG9NoRBDaxYbRKt2T5fF5Ze7sUNZfFI5n/ZZsgbx6Tsgtfd7oM6j+eg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 21:08:56 GMT
Content-Length: 542
```

```
{ "response": [
  {
    "configFile": "global",
    "id": 4,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.instance_name",
    "secure": false,
    "value": "Traffic Ops CDN"
  },
  {
    "configFile": "global",
    "id": 5,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.toolname",
    "secure": false,
    "value": "Traffic Ops"
  },
  {
    "configFile": "global",
    "id": 6,
    "lastUpdated": "2018-12-05 17:50:51+00",
    "name": "use_tenancy",
    "secure": false,
    "value": "1"
  },
  {
```

(continues on next page)

(continued from previous page)

```

    "configFile": "regex_revalidate.config",
    "id": 7,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "maxRevalDurationDays",
    "secure": false,
    "value": "90"
  }
}]

```

POST

Associates *Parameters* to a *Profile*. If the *Parameter* does not exist, creates it and associates it to the *Profile*. If the *Parameter* already exists, associates it to the *Profile*. If the *Parameter* is already associated with the *Profile*, keep the association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 356: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> to which <i>Parameters</i> will be assigned

This endpoint accepts two formats for the request payload:

Single Object Format For assigning a single *Parameter* to a single *Profile*

Parameter Array Format For making multiple assignments of *Parameters* to *Profiles* simultaneously

Warning: Most API endpoints dealing with *Parameters* treat *Secure* as a boolean value, whereas this endpoint takes the legacy approach of treating it as an integer. Be careful when passing data back and forth, as boolean values will **not** be accepted by this endpoint!

Single Parameter Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

854: Response Example - Single Parameter Format

```
POST /api/3.0/profiles/18/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 99
Content-Type: application/json

{
  "name": "test",
  "configFile": "quest",
  "value": "A test parameter for API examples",
  "secure": 0
}
```

Parameter Array Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

855: Request Example - Parameter Array Format

```
POST /api/3.0/profiles/18/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 212
Content-Type: application/json

[ {
  "name": "test",
  "configFile": "quest",
```

(continues on next page)

(continued from previous page)

```

    "value": "A test parameter for API examples",
    "secure": 0
  },
  {
    "name": "foo",
    "configFile": "bar",
    "value": "Another test parameter for API examples",
    "secure": 0
  }
]
```

Response Structure

parameters An array of objects representing the *Parameters* which have been assigned

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

profileId The *ID* of the *Profile* to which the *Parameter(s)* have been assigned

profileName *Name* of the *Profile* to which the *Parameter(s)* have been assigned

856: Response Example - Single Parameter Format

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: R2QUyCaNvKvVv/PNVNmEd/ma5h/iP1fMJlqhv+x2jE/
→zNpHJ1KVXt6s3btB8nnHv6IDF/gt5kIzQ0mbW5U8bpg==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 14:45:28 GMT
Content-Length: 253

{ "alerts": [
  {
    "text": "Assign parameters successfully to profile test",
```

(continues on next page)

(continued from previous page)

```

        "level": "success"
      }
    ],
    "response": {
      "parameters": [
        {
          "configFile": "quest",
          "name": "test",
          "secure": 0,
          "value": "A test parameter for API examples",
          "id": 126
        }
      ],
      "profileId": 18,
      "profileName": "test"
    }
  }
}
```

Note: The format of the request does not affect the format of the response. `parameters` will be an array either way.

profiles/import

POST

Imports a *Profile* that was exported via *profiles/{ID}/export*

Note: On import of the *Profile Parameters* if a *Parameter* already exists with the same *Name*, *Config File* and *Value* it will link that to the *Profile* instead of creating it.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

- profile** The exported *Profile*
 - cdn** The name of the *CDN* to which this *Profile* belongs
 - description** The *Profile's Description*
 - name** The *Profile's Name*
 - type** The *Profile's Type*
- parameters** An array of *Parameters* in use by this *Profile*
 - config_file** The *Parameter's Config File*
 - name** *Name* of the *Parameter*
 - value** The *Parameter's Value*

857: Request Example

```
POST /api/3.0/profiles/import HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Type: application/json

{ "profile": {
  "name": "GLOBAL",
  "description": "Global Traffic Ops profile",
  "cdn": "ALL",
  "type": "UNK_PROFILE"
},
"parameters": [
  {
    "config_file": "global",
    "name": "tm.instance_name",
    "value": "Traffic Ops CDN"
  },
  {
    "config_file": "global",
    "name": "tm.toolname",
    "value": "Traffic Ops"
  }
]
}
```

Response Structure

cdn The name of the *CDN* to which this *Profile* belongs

description The *Profile's Description*

name The *Profile's Name*

type The *Profile's Type*

id The *Profile's ID*

858: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mzP7DVxFAGhICxqagwDyBDRea7oBZPMAx7NCDeOBVCRqlcCFFe7XL3JP58b80aaVOW/
    ↳2ZGfg/jpYF70cdDfzQA==
X-Server-Name: traffic_ops_golang/
Date: Fri, 13 Sep 2019 20:14:42 GMT
Transfer-Encoding: gzip

{ "alerts": [
  {
    "level": "success",
    "text": "Profile imported [ Global ] with 2 new and 0 existing
    ↳parameters"
  }
],
"response": {
  "cdn": "ALL",
  "name": "Global",
  "id": 18,
  "type": "UNK_PROFILE",
  "description": "Global Traffic Ops profile"
}}
```

`profiles/name/{{name}}/copy/{{copy}}`

POST

Copy *Profile* to a new *Profile*. The new *Profile*'s *Name* must not already exist.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 357: Request Path Parameters

Name	Description
name	The <i>Name</i> of the new <i>Profile</i>
copy	The <i>Name</i> of <i>Profile</i> from which the copy will be made

859: Request Example

```
POST /api/3.0/profiles/name/GLOBAL_copy/copy/GLOBAL HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

description The new *Profile*'s *Description*

id The *ID* of the new *Profile*

idCopyFrom The *ID* of the *Profile* from which the copy was made

name The *Name* of the new *Profile*

profileCopyFrom The *Name* of the *Profile* from which the copy was made

860: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Fri, 07 Dec 2018 22:03:54 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→r6V9viEZui1WCns0AUGEx1MtxjjXiU8SZV0tSQjeq7ZJDL15s8fMmjJdR/
→HRWduHn7Ax6GzYhoKwnIjMyc7ZWg==
Content-Length: 252

{ "alerts": [
  {
    "level": "success",
    "text": "Created new profile [ GLOBAL_copy ] from existing.
→profile [ GLOBAL ]"
  }
],
"response": {
  "idCopyFrom": 1,
  "name": "GLOBAL_copy",
  "profileCopyFrom": "GLOBAL",
  "id": 17,
  "description": "Global Traffic Ops profile, DO NOT DELETE"
}}
```

`profiles/name/{name}/parameters`

GET

Retrieves all *Parameters* associated with a given *Profile*

Auth. Required Yes

Roles Required None

Response Type None

Request Structure

Table 358: Request Path Parameters

Name	Description
name	The <i>Name</i> of the <i>Profile</i> for which <i>Parameters</i> will be listed

861: Request Example

```
GET /api/3.0/profiles/name/GLOBAL/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name* of the *Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

862: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: NudgZXUNyKNpmSFf856KEjyy+Pin/
→bFhG9NoRBDaxYbRKt2T5fF5Ze7sUNZfFI5n/ZZsgbx6Tsgtfd7oM6j+eg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 21:52:08 GMT
Content-Length: 542
```

(continues on next page)

(continued from previous page)

```
{ "response": [
  {
    "configFile": "global",
    "id": 4,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.instance_name",
    "secure": false,
    "value": "Traffic Ops CDN"
  },
  {
    "configFile": "global",
    "id": 5,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.toolname",
    "secure": false,
    "value": "Traffic Ops"
  },
  {
    "configFile": "global",
    "id": 6,
    "lastUpdated": "2018-12-05 17:50:51+00",
    "name": "use_tenancy",
    "secure": false,
    "value": "1"
  },
  {
    "configFile": "regex_revalidate.config",
    "id": 7,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "maxRevalDurationDays",
    "secure": false,
    "value": "90"
  }
]}
}
```

POST

Associates *Parameters* to a *Profile*. If the *Parameter* does not exist, creates it and associates it to the *Profile*. If the *Parameter* already exists, associates it to the *Profile*. If the *Parameter* is already associated with the *Profile*, keep the association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 359: Request Path Parameters

Name	Description
name	The <i>Name</i> of the <i>Profile</i> to which <i>Parameters</i> will be assigned

This endpoint accepts two formats for the request payload:

Single Parameter Format Specify a single parameter to assign to the specified profile

Parameter Array Format Specify multiple parameters to assign to the specified profile

Warning: Most API endpoints dealing with parameters treat `secure` as a boolean value, whereas this endpoint takes the legacy approach of treating it as an integer. Be careful when passing data back and forth, as boolean values will **not** be accepted by this endpoint!

Single Parameter Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

863: Request Example - Single Parameter Format

```
POST /api/3.0/profiles/name/test/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 99
Content-Type: application/json

{
  "name": "test",
  "configFile": "quest",
  "value": "A test parameter for API examples",
  "secure": 0
}
```


Parameter Array Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

864: Request Example - Parameter Array Format

```
POST /api/3.0/profiles/name/test/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 212
Content-Type: application/json

[{"name": "test",
  "configFile": "quest",
  "value": "A test parameter for API examples",
  "secure": 0},
 {"name": "foo",
  "configFile": "bar",
  "value": "Another test parameter for API examples",
  "secure": 0}]
```

Response Structure

parameters An array of objects representing the *Parameters* which have been assigned

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

profileId The *ID* of the *Profile* to which the *Parameter(s)* have been assigned

profileName *Name* of the *Profile* to which the *Parameter(s)* have been assigned

865: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: HQWq0koYHjvcxheWPrH0b0oZnUC+qLG1L040jtsLLnZYVUIu/
    ↳qgJrzvziPnKq3FEHUWaZrnDCZM/iZD8AXOKBw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 14:20:22 GMT
Content-Length: 357

{ "alerts": [
  {
    "text": "Assign parameters successfully to profile test",
    "level": "success"
  }
],
"response": {
  "parameters": [
    {
      "configFile": "quest",
      "name": "test",
      "secure": 0,
      "value": "A test parameter for API examples",
      "id": 126
    },
    {
      "configFile": "bar",
      "name": "foo",
      "secure": 0,
      "value": "Another test parameter for API examples",
      "id": 129
    }
  ],
  "profileId": 18,
  "profileName": "test"
}}
```

Note: The format of the request does not affect the format of the response. parameters will

be an array either way.

regions

GET

Retrieves information about *Regions*

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 360: Request Query Parameters

Name	Required	Description
division	no	Filter <i>Regions</i> by the integral, unique identifier of the <i>Division</i> which contains them
id	no	Filter <i>Regions</i> by integral, unique identifier
name	no	Filter <i>Regions</i> by name
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

866: Request Example

```
GET /api/3.0/regions?division=1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- divisionName** The name of the division which contains this region
- divisionId** The integral, unique identifier of the division which contains this region
- id** An integral, unique identifier for this region
- lastUpdated** The date and time at which this region was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The region name

867: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳nSYbR+fRXaxhYl7dWgf0Udo2AsiXEnwvED1CPbk7ZNWK03I3TOhtmCQx9ABnJJ6xKYnl6EKMeopVTK0n
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 01:58:38 GMT
Content-Length: 117

{ "response": [
  {
    "divisionName": "Quebec",
    "division": 1,
    "id": 2,
    "lastUpdated": "2018-12-05 17:50:58+00",
    "name": "Montreal"
  }
]}
```

POST

Creates a new region

- Auth. Required** Yes
- Roles Required** “admin” or “operations”
- Response Type** Object

Request Structure

division The integral, unique identifier of the division which shall contain the new region¹

divisionName The name of the division which shall contain the new region¹

name The name of the region

868: Request Example

```
POST /api/3.0/regions HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 65
Content-Type: application/json

{
  "name": "Manchester",
  "division": "4",
  "divisionName": "England"
}
```

Response Structure

divisionName The name of the division which contains this region

divisionId The integral, unique identifier of the division which contains this region

id An integral, unique identifier for this region

lastUpdated The date and time at which this region was last updated, in *Traffic Ops's Custom Date/Time Format*

name The region name

869: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST, GET, OPTIONS, PUT, DELETE
```

(continues on next page)

¹ The only “division” key that actually matters in the request body is `division`; `divisionName` is not validated and has no effect - particularly not the effect of re-naming the division - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the division. Note that if `divisionName` is not present in the request body it will be `null` in the response, but again further requests will show the true division name (provided it has been assigned to a division).

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→ezxk+iP7o7KE7zpWmGc0j8nz5k+1wAzY0HiNiA2xswTQrt+N+6CgQqUV2r9G1HAsPNr0HF2PhYs/
→Xr7DrYOW0A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 02:14:45 GMT
Content-Length: 178

{ "alerts": [
  {
    "text": "region was created.",
    "level": "success"
  }
],
"response": {
  "divisionName": "England",
  "division": 3,
  "id": 5,
  "lastUpdated": "2018-12-06 02:14:45+00",
  "name": "Manchester"
}}
```

DELETE

Deletes a region. If no query parameter is specified, a 400 Bad Request response is returned.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 361: Request Query Parameters

Name	Required	Description
id	no	Delete <i>Region</i> by integral, unique identifier
name	no	Delete <i>Region</i> by name

870: Request Example

```
DELETE /api/3.0/regions?name=Manchester HTTP/1.1
User-Agent: curl/7.29.0
Host: trafficops.infra.ciab.test
Accept: */*
Cookie: mojolicious=...
```

Response Structure

871: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Fri, 07 Feb 2020 13:56:24
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳yNqXKcoiohEbJrEkH8LD1zifh87dIusuvUqgQnYueyKqCXkfd5bQvQ00hQ2AAdSZa/
    ↳oe2SAqMjojGsUlxHtIQw==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Feb 2020 12:56:24 GMT
Content-Length: 62

{
  "alerts": [
    {
      "text": "region was deleted.",
      "level": "success"
    }
  ]
}
```

regions/{{ID}}

PUT

Updates a *Region*.

Auth. Required Yes

Role(s) Required “admin” or “operator”

Response Type Object

Request Structure

Table 362: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the region to update

division The new integral, unique identifier of the division which shall contain the region¹

divisionName The new name of the division which shall contain the region¹

name The new name of the region

872: Request Example

```
PUT /api/3.0/regions/5 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 60
Content-Type: application/json

{
  "name": "Leeds",
  "division": 3,
  "divisionName": "England"
}
```

¹ The only “division” key that actually matters in the request body is `division`; `divisionName` is not validated and has no effect - particularly not the effect of re-naming the division - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the division. Note that if `divisionName` is not present in the request body it will be `null` in the response, but again further requests will show the true division name (provided it has been assigned to a division).

Response Structure

- divisionName** The name of the division which contains this region
- divisionId** The integral, unique identifier of the division which contains this region
- id** An integral, unique identifier for this region
- lastUpdated** The date and time at which this region was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The region name

873: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳7SVj4q7dtSTNQEJlBApEwlad28WBVFnpdHaatoIpNfeLltfcpcdVTcOKB4JXQv7rlSD2p/
    ↳TxBQC6EXpxwYTnKQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 02:23:40 GMT
Content-Length: 173

{ "alerts": [
  {
    "text": "region was updated.",
    "level": "success"
  }
],
"response": {
  "divisionName": "England",
  "division": 3,
  "id": 5,
  "lastUpdated": "2018-12-06 02:23:40+00",
  "name": "Leeds"
}}
```

roles

GET

Retrieves all user *Roles*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 363: Request Query Parameters

Name	Re-quired	Description
id	no	Return only the <i>Role</i> identified by this integral, unique identifier
name	no	Return only the <i>Role</i> with this name
privLevel	no	Return only those <i>Roles</i> that have this privilege level
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page .

874: Request Example

```
GET /api/3.0/roles?name=admin HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

capabilities An array of the names of the Capabilities given to this *Role*

description A description of the *Role*

id The integral, unique identifier for this *Role*

name The name of the *Role*

privLevel An integer that allows for comparison between *Roles*

875: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳TEDXlQqWMSnJbL10JtFdbw0nqciNpjc4bd6m7iAB8aymakWeF+ghs1k5LayjdzHcjeDE8UNF/
    ↳HXSxOFvoLFEuA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 04 Sep 2019 17:15:36 GMT
Content-Length: 120

{ "response": [
  {
    "id": 4,
    "name": "admin",
    "description": "super-user",
    "privLevel": 30,
    "capabilities": [
      "all-write",
      "all-read"
    ]
  }
]
```

(continues on next page)

(continued from previous page)

```
}
[]}
```

POST

Creates a new *Role*.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

capabilities An optional array of capability names that will be granted to the new *Role*

description A helpful description of the *Role*’s purpose.

name The name of the new *Role*

privLevel The privilege level of the new *Role*¹

876: Request Example

```
POST /api/3.0/roles HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "name": "test",
  "description": "quest",
  "privLevel": 30
}
```

¹ **privLevel** cannot exceed the privilege level of the requesting user. Which, of course, must be the privilege level of “admin”. Basically, this means that there can never exist a *Role* with a higher privilege level than “admin”.

Response Structure

capabilities An array of the names of the Capabilities given to this *Role*

Tip: This can be null *or* empty, depending on whether it was present in the request body, or merely empty. Obviously, it can also be a populated array.

description A description of the *Role*

id The integral, unique identifier for this *Role*

name The name of the *Role*

privLevel An integer that allows for comparison between *Roles*

877: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: gzfc7m/
    ↳in5vVsVP+Y9h6JJfDhgpXKn9VAzoiPENhKbQfP8Q6jug08Rt2AK/
    ↳3Nz1cx5zZ8P9IjVxDdIg7mlC8bw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 04 Sep 2019 17:44:42 GMT
Content-Length: 150

{ "alerts": [{
    "text": "role was created.",
    "level": "success"
}],
  "response": {
    "id": 5,
    "name": "test",
    "description": "quest",
    "privLevel": 30,
    "capabilities": null
  }
}
```

PUT

Replaces an existing *Role* with one provided by the request.

Auth. Required Yes

Roles Required “admin”

Response Type

Request Structure

Table 364: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Role</i> to be replaced

capabilities An optional array of capability names that will be granted to the new *Role*

Warning: When not present, the affected *Role*’s Capabilities will be unchanged - *not* removed, unlike when the array is empty.

description A helpful description of the *Role*’s purpose.

name The new name of the *Role*

privLevel The new privilege level of the new *Role*^{Page 1312, 1}

878: Request Example

```
PUT /api/3.0/roles?id=5 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "name": "test",
  "privLevel": 29,
  "description": "quest"
}
```

Response Structure

capabilities An array of the names of the Capabilities given to this *Role*

Tip: This can be null *or* empty, depending on whether it was present in the request body, or merely empty. Obviously, it can also be a populated array.

Warning: If no **capabilities** array was given in the request, this will *always* be null, even if the *Role* has Capabilities that would have gone unchanged.

description A description of the *Role*

id The integral, unique identifier for this *Role*

name The name of the *Role*

privLevel An integer that allows for comparison between *Roles*

879: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mlHQenE1Q3gjrIK21C2hfueQOaTCpdYefboN0A9vYPUIwTiaF5ZaAMPQBdfGyiAhgHRxowITs3bR7s1L+
X-Server-Name: traffic_ops_golang/
Date: Thu, 05 Sep 2019 12:56:46 GMT
Content-Length: 150

{
  "alerts": [
    {
      "text": "role was updated.",
      "level": "success"
    }
  ],
  "response": {
    "id": 5,
    "name": "test",
```

(continues on next page)

(continued from previous page)

```

    "description": "quest",
    "privLevel": 29,
    "capabilities": null
  }
}

```

DELETE

Deletes a *Role*

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 365: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Role</i> to be replaced

880: Request Example

```

DELETE /api/3.0/roles?id=5 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...

```

Response Structure

881: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly

```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: 10jeFZihtbvAus/XyHAW8rhgS9JBD+X/
→ezCp1iExYkEcHxN4gjr1L6x8zDFXORueBSlFldgtbWKT7QsmwCHUWA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 05 Sep 2019 13:02:06 GMT
Content-Length: 59

{ "alerts": [{
  "text": "role was deleted.",
  "level": "success"
}]}
```

server_capabilities

GET

Retrieves *Server Capabilities*.

Auth. Required Yes

Roles Required “read-only”

Response Type Array

Request Structure

Table 366: Request Query Parameters

Name	Required	Description
name	no	Return the <i>Server Capability</i> with this name

882: Request Structure

```
GET /api/3.0/server_capabilities?name=RAM HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

name The name of this *Server Capability*

lastUpdated The date and time at which this *Server Capability* was last updated, in ISO-like format

883: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpGT3YRyKJ/
    ↳p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 21:36:13 GMT
Content-Length: 68

{
  "response": [
    {
      "name": "RAM",
      "lastUpdated": "2019-10-07 20:38:24+00"
    }
  ]
}
```

POST

Create a new *Server Capability*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the *Server Capability*

884: Request Example

```
POST /api/3.0/server_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 15
Content-Type: application/json

{
  "name": "RAM"
}
```

Response Structure

name The name of this *Server Capability*

lastUpdated The date and time at which this *Server Capability* was last updated, in ISO-like format

885: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ysdopC//
→JQI79BRUa61s6M2HzHxYHpo5Rdcuau0oqCYxiV0oUhNZfOVydVkv8zDN2qA374XKnym4kWj3VzQIXg==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:10:00 GMT
Content-Length: 137

{
  "alerts": [
    {
      "text": "server capability was created.",
      "level": "success"
    }
  ],
  "response": {
    "name": "RAM",
    "lastUpdated": "2019-10-07 22:10:00+00"
  }
}
```

DELETE

Deletes a specific *Server Capability*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 367: Request Query Parameters

Name	Required	Description
name	yes	The name of the <i>Server Capability</i> to be deleted

886: Request Example

```
DELETE /api/3.0/server_capabilities?name=RAM HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

887: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 8zCAATbCzcqiqigGVBy7WF1duDuXu1Wg2DBe9yfqTw/
    ↳c+yhE2eUk73hFTA/Oqt0kocaN7+1GkbFdPkQPvbnRaA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 20:44:40 GMT
Content-Length: 72

{
  "alerts": [
    {
      "text": "server capability was deleted.",
      "level": "success"
    }
  ]
}
```

server_server_capabilities

GET

Gets all associations of *Server Capabilities* to *cache servers*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 368: Request Query Parameters

Name	Re- quired	Description
serverId	no	Filter <i>Server Capability</i> associations by the integral, unique identifier of the server to which they are assigned
server-Host-Name	no	Filter <i>Server Capability</i> associations by the host name of the server to which they are assigned
server-Ca-pabil-ity	no	Filter <i>Server Capability</i> associations by <i>Server Capability</i> name
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

888: Request Example

```
GET /api/3.0/server_server_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

serverHostName The server’s host name

serverId The server’s integral, unique identifier

lastUpdated The date and time at which this association between the server and the *Server Capability* was last updated, in *Traffic Ops’s Custom Date/Time Format*

serverCapability The *Server Capability*’s name

889: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
    ↳jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
    ↳DbBwhMAOJoeqDIImoDlrLnrVjQG04AooA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 150

{
  "response": [
    {
      "lastUpdated": "2019-10-07 22:05:31+00",
      "serverHostName": "atlanta-org-1",
      "serverId": 260,
      "serverCapability": "ram"
    },
    {
      "lastUpdated": "2019-10-07 22:05:31+00",
      "serverHostName": "atlanta-org-2",
      "serverId": 261,
      "serverCapability": "disk"
    }
  ]
}

```

POST

Associates a *Server Capability* to a server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

serverId The integral, unique identifier of a server to be associated with a *Server Capability*

serverCapability The *Server Capability*'s name to associate

Note: The server referenced must be either an *Edge-tier* or *Mid-tier cache server*.

890: Request Example

```
POST /api/3.0/server_server_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 84
Content-Type: application/json

{
  "serverId": 1,
  "serverCapability": "disk"
}
```

Response Structure

serverId The integral, unique identifier of the newly associated server

lastUpdated The date and time at which this association between the server and the *Server Capability* was last updated, in *Traffic Ops's Custom Date/Time Format*

serverCapability The *Server Capability*'s name

891: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
  ↳Cfh2X9i3G+MQ36eH95gukJqOBObQ==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 157

{
  "alerts": [
    {
      "text": "server server_capability was created.",
      "level": "success"
    }
  ],
  "response": {
    "lastUpdated": "2019-10-07 22:15:11+00",
    "serverId": 1,
    "serverCapability": "disk"
  }
}
```

DELETE

Disassociate a server from a *Server Capability*.

Note: If the serverCapability is a *Server Capability* required by a *Delivery Service* that to which the server is assigned the DELETE will be blocked until either the server is unassigned from the *Delivery Service* or the *Server Capability* is no longer required by the *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 369: Request Query Parameters

Name	Re-quired	Description
serverId	yes	The integral, unique identifier of the server to disassociate
serverCapabil-ity	yes	term: <i>Server Capability</i> name to disassociate from given server

892: Request Example

```
DELETE /api/3.0/server_server_capabilities?serverId=1&
→serverCapability=disk HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

893: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
→jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
→DbBwhMAOJoeqDImoDlrLnrVjQG04AooA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 96

{
  "alerts": [
    {
      "text": "server server_capability was deleted.",
      "level": "success"
    }
  ]
}
```

servercheck

See also:

Check Extensions

GET

Fetches identifying and meta information as well as “check” values regarding all servers that have a *Type* with a name beginning with “EDGE” or “MID” (ostensibly this is equivalent to all *cache servers*).

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 370: Request Query Parameters

Name	Required	Description
id	no	Return only <i>cache servers</i> with this integral, unique identifier (id)
hostName	no	Return only <i>cache servers</i> with this host_name

894: Request Example with hostName query param

```
GET /api/4.0/servercheck?hostName=edge HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

895: Request Example with id query param

```
GET /api/4.0/servercheck?id=12 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

adminState The name of the server’s *Status* - called “adminState” for legacy reasons

cacheGroup The name of the *Cache Group* to which the server belongs

checks An optionally present map of the names of “checks” to their values. Only numeric and boolean checks are represented, and boolean checks are represented as integers with 0 meaning “false” and 1 meaning “true”. Will not appear if the server in question has no valued “checks”.

hostName The (short) hostname of the server

id The server’s integral, unique identifier

profile The name of the *Profile* used by the server

revalPending A boolean that indicates whether or not the server has pending revalidations

type The name of the server’s *Type*

updPending A boolean that indicates whether or not the server has pending updates

896: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Thu, 18 Feb 2021 20:00:19
    ↳GMT; Max-Age=3600; HttpOnly
X-Server-Name: traffic_ops_golang/
Date: Thu, 18 Feb 2021 19:00:19 GMT
Content-Length: 352
```

(continues on next page)

(continued from previous page)

```
{ "response": [
  {
    "adminState": "REPORTED",
    "cacheGroup": "CDN_in_a_Box_Edge",
    "id": 12,
    "hostName": "edge",
    "revalPending": false,
    "profile": "ATS_EDGE_TIER_CACHE",
    "type": "EDGE",
    "updPending": false
  }
]}
```

POST

Post a server check result to the “serverchecks” table. Updates the resulting value from running a given check extension on a server.

Auth. Required Yes

Roles Required None¹

Response Type Object

Request Structure

The request only requires to have either `host_name` or `id` defined.

host_name The hostname of the server to which this “servercheck” refers.

id The id of the server to which this “servercheck” refers.

servercheck_short_name The short name of the “servercheck”.

value The value of the “servercheck”

897: Request Example

```
POST /api/3.0/servercheck HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 113
Content-Type: application/json
```

(continues on next page)

¹ No roles are required to use this endpoint, however access is controlled by username. Only the reserved user extension is permitted the use of this endpoint.

(continued from previous page)

```
{
  "id": 1,
  "host_name": "edge",
  "servercheck_short_name": "test",
  "value": 1
}
```

Response Structure

898: Response Example

```
{ "alerts": [
  {
    "level": "success",
    "text": "Server Check was successfully updated."
  }
]}
```

servercheck/extensions

See also:

Managing Traffic Ops Extensions

GET

Retrieves the list of Traffic Ops extensions.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 371: Request Query Parameters

Name	Re-quired	Description
id	no	Filter TO Extensions by the integral, unique identifier of an Extension
name	no	Filter TO Extensions by the name of an Extension
script_file	no	Filter TO Extensions by the base filename of the script that runs for the Extension
is-active	no	Boolean used to return either only active (1) or inactive(0) TO Extensions
type	no	Filter TO Extensions by the type of Extension
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

899: Request Example

```
GET /api/3.0/servercheck/extensions HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

additional_config_json A string containing a JSON-encoded object with extra configuration options... inside a JSON object...

description A short description of the extension

Note: This is, unfortunately, null for all default extensions

id An integral, unique identifier for this extension definition

info_url A URL where info about this extension may be found

isactive An integer describing the boolean notion of whether or not the extension is active; one of:

0 disabled

1 enabled

name The name of the extension

script_file The base filename of the script that runs for the extension

servercheck_shortname The name of the column in the table at ‘Monitor’ -> ‘Cache Checks’ in Traffic Portal, where “Check Extension” output is displayed

type The Check *Type* of the extension. This will always be a CHECK_EXTENSION type with the naming convention of CHECK_EXTENSION_*.

version A (hopefully) semantic version number describing the version of the plugin

900: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Tue, 11 Dec 2018 20:51:48 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: n73jg9XR4V5Cwqq56Rf3wuIi99k3mM5u2NAjcZ/
→gQB8jvAFymDlnZqKeJ+wTll1vjIsHpXCOVXV7+5UGakLgA==
Transfer-Encoding: chunked

{ "response": [
  {
    "script_file": "ToPingCheck.pl",
    "version": "1.0.0",
    "name": "ILO_PING",
    "description": null,
    "info_url": "-",
    "additional_config_json": "{ check_name: \"ILO\", \"base_url\
→\": \"https://localhost\", \"select\": \"ilo_ip_address\", \"cron\": \
→\"9 * * * *\" }",
    "isactive": 1,
    "type": "CHECK_EXTENSION_BOOL",
    "id": 1,
    "servercheck_short_name": "ILO"
```

(continues on next page)

(continued from previous page)

```

    },
    {
      "script_file": "ToPingCheck.pl",
      "version": "1.0.0",
      "name": "10G_PING",
      "description": null,
      "info_url": "-",
      "additional_config_json": "{ check_name: \"10G\", \"base_url\"
→: \"https://localhost\", \"select\": \"ip_address\", \"cron\": \"18_
→* * * *\" }",
      "isactive": 1,
      "type": "CHECK_EXTENSION_BOOL",
      "id": 2,
      "servercheck_short_name": "10G"
    }
  ]}

```

POST

Creates a new Traffic Ops check extension.

Auth. Required Yes

Roles Required None¹

Response Type undefined

Request Structure

additional_config_json An optional string containing a JSON-encoded object with extra configuration options... inside a JSON object...

description A short description of the extension

info_url A URL where info about this extension may be found

isactive An integer describing the boolean notion of whether or not the extension is active; one of:

0 disabled

1 enabled

name The name of the extension

script_file The base filename of the script that runs for the extension

¹ No roles are required to use this endpoint, however access is controlled by username. Only the reserved user extension is permitted the use of this endpoint.

See also:

Managing Traffic Ops Extensions for details on where the script should be located on the Traffic Ops server

servercheck_shortcode The name of the column in the table at ‘Monitor’ -> ‘Cache Checks’ in Traffic Portal, where “Check Extension” output is displayed

type The *Type* of extension. Must be CHECK_EXTENSION type with the naming convention of CHECK_EXTENSION_*.

version A (hopefully) semantic version number describing the version of the plugin

901: Request Example

```
POST /api/3.0/servercheck/extensions HTTP/1.1
Host: ipcdn-cache-51.cdnlab.comcast.net:6443
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 208
Content-Type: application/json

{
  "name": "test",
  "version": "0.0.1-1",
  "info_url": "",
  "script_file": "",
  "isactive": 0,
  "description": "A test extension for API examples",
  "servercheck_shortcode": "test",
  "type": "CHECK_EXTENSION_NUM"
}
```

Response Structure

902: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Date: Wed, 12 Dec 2018 16:37:44 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↪GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 7M67PYnli6WzGQFS3g8Gh1SOyq6VENZMqm/
    ↪kUffOTLLFfuWSEuSLA65R5R+VyJiNjdqOG5Bp78mk+JYcqhtVGw==
Content-Length: 89

{ "supplemental":
  {
    "id": 5
  },
  "alerts": [{
    "level": "success",
    "text": "Check Extension Loaded."
  }]
}
```

`servercheck/extensions/{ID}`

DELETE

Deletes a Traffic Ops server check extension definition. This does **not** delete the actual extension file.

Auth. Required Yes

Roles Required None¹

Response Type undefined

Request Structure

Table 372: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the extension definition to be deleted

903: Request Example

```
DELETE /api/3.0/servercheck/extensions/16 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

¹ No roles are required to use this endpoint, however access is controlled by username. Only the reserved user extension is permitted the use of this endpoint.

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

904: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 12 Dec 2018 16:33:52 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: EB0Nu85azbGzaehDTAODP3NPqWbByIza1XQhgwtS2WTXyK/
    ↳dxQtncp0YiJXy00tH9H+n+6BBfojB0b5h0dFPA==
Content-Length: 60

{ "alerts": [
  {
    "level": "success",
    "text": "Extension deleted."
  }
]}
```

servers

GET

Retrieves properties of all servers across all CDNs.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 373: Request Query Parameters

Name	Re- quired	Description
cache-group	no	Return only those servers within the <i>Cache Group</i> that has this <i>ID</i>
cache-group-Name	no	Return only those servers within the <i>Cache Group</i> that has this <i>Name</i>
dsId	no	Return only those servers assigned to the <i>Delivery Service</i> identified by this integral, unique identifier. If the Delivery Service has a <i>Topology</i> assigned to it, the <i>servers</i> endpoint will return each server whose <i>Cache Group</i> is associated with a <i>Topology Node</i> of that Topology and has the <i>Server Capabilities</i> that are <i>required by the Delivery Service</i> but excluding <i>Origin Servers</i> that are not assigned to the Delivery Service. For more information, see <i>Configure Multi-Site Origin</i> .
host-Name	no	Return only those servers that have this (short) hostname
id	no	Return only the server with this integral, unique identifier
profileId	no	Return only those servers that are using the <i>Profile</i> that has this <i>ID</i>
status	no	Return only those servers with this status - see <i>Health Protocol</i>
type	no	Return only servers of this <i>Type</i>
topology	no	Return only servers who belong to cachegroups assigned to the <i>Topology</i> identified by this name
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

905: Request Example

```
GET /api/3.0/servers?hostName=mid HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId The integral, unique identifier of the CDN to which the server belongs

cdnName Name of the CDN to which the server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be `null`

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service¹

iloIpGateway The IPv4 gateway address of the server's ILO service^{Page 1339, 1}

iloIpNetmask The IPv4 subnet mask of the server's ILO service^{Page 1339, 1}

iloPassword The password of the of the server's ILO service user^{Page 1339, 1} - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' *Role(s)*

iloUsername The user name for the server's ILO service^{Page 1339, 1}

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be present, but it is illegal for this set to be an empty collection.

¹ For more information see the [Wikipedia page on Lights-Out management](#).

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be present, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the "service interface" for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning "no limit". It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface's device name on the server, e.g. `eth0`.

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status

physLocation The name of the physical location where the server resides

physLocationId An integral, unique identifier for the physical location where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

profileId The *ID* the *Profile* used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack A string indicating “server rack” location

routerHostName The human-readable name of the router responsible for reaching this server

routerPortName The human-readable name of the port used by the router responsible for reaching this server

status The *Status* of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the *Type* of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

906: Response Example

```
HTTP/1.1 200 OK
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 19 May 2020 17:06:25 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 19 May 2020 16:06:25 GMT
Content-Length: 538

{ "response": [{
  "cachegroup": "CDN_in_a_Box_Mid",
  "cachegroupId": 6,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "domainName": "infra.ciab.test",
  "guid": null,
  "hostName": "mid",
  "httpsPort": 443,
  "id": 12,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "lastUpdated": "2020-05-19 14:49:39+00",
  "mgmtIpAddress": "",
  "mgmtIpGateway": "",
```

(continues on next page)

(continued from previous page)

```
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_MID_TIER_CACHE",
"profileDesc": "Mid Cache - Apache Traffic Server",
"profileId": 10,
"rack": "",
"revalPending": false,
"routerHostName": "",
"routerPortName": "",
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "MID",
"typeId": 12,
"updPending": false,
"xmppId": "",
"xmppPasswd": "",
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "172.26.0.4/16",
        "gateway": "172.26.0.1",
        "serviceAddress": true
      }
    ],
    "maxBandwidth": null,
    "monitor": false,
    "mtu": 1500,
    "name": "eth0"
  }
]
}],
"summary": {
  "count": 13
}}
```

Summary Fields

The summary object returned by this method of this endpoint uses only the count *standard property*.

POST

Allows a user to create a new server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cachegroupId An integer that is the *ID of the Cache Group* to which the server shall belong

cdnId The integral, unique identifier of the CDN to which the server shall belong

domainName The domain part of the server’s FQDN

hostName The (short) hostname of the server

httpsPort An optional port number on which the server listens for incoming HTTPS connections/requests

iloIpAddress An optional IPv4 address of the server’s ILO service^{Page 1339, 1}

iloIpGateway An optional IPv4 gateway address of the server’s ILO service^{Page 1339, 1}

iloIpNetmask An optional IPv4 subnet mask of the server’s ILO service^{Page 1339, 1}

iloPassword An optional string containing the password of the of the server’s ILO service user^{Page 1339, 1} - displays as simply ***** if the currently logged-in user does not have the ‘admin’ or ‘operations’ *Role(s)*

iloUsername An optional string containing the user name for the server’s ILO service^{Page 1339, 1}

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be necessary, but it is illegal for this set to be an empty collection.

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be necessary, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the "service interface" for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning "no limit". It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface. This unsigned integer may not be less than 1280.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface's device name on the server, e.g. `eth0`.

mgmtIpAddress The IPv4 address of some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

physLocationId An integral, unique identifier for the physical location where the server resides

profileId The *ID* the *Profile* that shall be used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack An optional string indicating “server rack” location

routerHostName An optional string containing the human-readable name of the router responsible for reaching this server

routerPortName An optional string containing the human-readable name of the port used by the router responsible for reaching this server

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort An optional port number on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd An optional password used in XMPP communications with the server

907: Request Example

```
POST /api/3.0/servers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 599
Content-Type: application/json

{
  "cachegroupId": 6,
  "cdnId": 2,
  "domainName": "infra.ciab.test",
  "hostName": "test",
  "httpsPort": 443,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "interfaces": [
    {
      "ipAddresses": [
        {
          "address": "::1",
          "gateway": "::2",
          "serviceAddress": true
        },
        {
          "address": "0.0.0.1/24",
          "gateway": "0.0.0.2",
          "serviceAddress": true
        }
      ],
      "maxBandwidth": null,
      "monitor": true,
      "mtu": 1500,
      "name": "eth0"
    }
  ],
  "interfaceMtu": 1500,
  "interfaceName": "eth0",
  "ip6Address": "::1",
  "ip6Gateway": "::2",
  "ipAddress": "0.0.0.1",

```

(continues on next page)

(continued from previous page)

```

"ipGateway": "0.0.0.2",
"ipNetmask": "255.255.255.0",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocationId": 1,
"profileId": 10,
"routerHostName": "",
"routerPortName": "",
"statusId": 3,
"tcpPort": 80,
"typeId": 12,
"updPending": false
}

```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId The integral, unique identifier of the CDN to which the server belongs

cdnName Name of the CDN to which the server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be null

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service [Page 1339, 1](#)

iloIpGateway The IPv4 gateway address of the server's ILO service [Page 1339, 1](#)

iloIpNetmask The IPv4 subnet mask of the server's ILO service [Page 1339, 1](#)

iloPassword The password of the of the server's ILO service user^{Page 1339, 1} - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' `ROLE(s) <ROLE>`

iloUsername The user name for the server's ILO service^{Page 1339, 1}

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be present, but it is illegal for this set to be an empty collection.

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be present, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the "service interface" for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning "no limit". It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface's device name on the server, e.g. `eth0`.

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

offlineReason A user-entered reason why the server is in `ADMIN_DOWN` or `OFFLINE` status

physLocation The name of the *Physical Location* where the server resides

physLocationId An integral, unique identifier for the *Physical Location* where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

profileId The *ID* the *Profile* used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack A string indicating "server rack" location

routerHostName The human-readable name of the router responsible for reaching this server

routerPortName The human-readable name of the port used by the router responsible for reaching this server

status The status of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the ‘type’ of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

908: Response Example

```
HTTP/1.1 201 Created
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 19 May 2020 17:34:40 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 19 May 2020 16:34:40 GMT
Content-Length: 562

{ "alerts": [
  {
    "text": "Server created",
    "level": "success"
  }
],
"response": {
  "cachegroup": "CDN_in_a_Box_Mid",
  "cachegroupId": 6,
  "cdnId": 2,
```

(continues on next page)

(continued from previous page)

```
"cdnName": "CDN-in-a-Box",
"domainName": "infra.ciab.test",
"guid": null,
"hostName": "test",
"httpsPort": 443,
"id": 14,
"iloIpAddress": "",
"iloIpGateway": "",
"iloIpNetmask": "",
"iloPassword": "",
"iloUsername": "",
"lastUpdated": "2020-05-19 16:34:40+00",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_MID_TIER_CACHE",
"profileDesc": "Mid Cache - Apache Traffic Server",
"profileId": 10,
"rack": null,
"revalPending": false,
"routerHostName": "",
"routerPortName": "",
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "MID",
"typeId": 12,
"updPending": false,
"xmppId": null,
"xmppPasswd": null,
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "::1",
        "gateway": "::2",
        "serviceAddress": true
      },
      {
        "address": "0.0.0.1/24",
        "gateway": "0.0.0.2",
        "serviceAddress": true
      }
    ]
  }
]
```

(continues on next page)

(continued from previous page)

```

    ],
    "maxBandwidth": null,
    "monitor": true,
    "mtu": 1500,
    "name": "eth0"
  }
]
}}
```

servers/details

Retrieves details of *Servers*.

GET

Auth. Required Yes

Roles Required None

Response Type Array

Note: On top of the response including the response key that is of type array it will also include the keys `limit`, `orderby`, and `size`.

Request Structure

Table 374: Request Query Parameters

Name	Required	Description
host-Name	Required if no physLocationID provided	Return only the servers with this (short) hostname. Capitalization of “hostName” is important.
phys-LocationID	Required if no hostName provided	Return only servers with this integral, unique identifier for the physical location where the server resides. Capitalization of “physLocationID” is important.

909: Request Example

```

GET /api/3.0/servers/details?hostName=edge HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
```

(continues on next page)

(continued from previous page)

Connection: keep-alive
Cookie: mojolicious=...

Response Structure

limit The maximum size of the `response` array, also indicative of the number of results per page using the pagination requested by the query parameters (if any) - this should be the same as the `limit` query parameter (if given)

orderby A string that names the field by which the elements of the `response` array are ordered - should be the same as the `orderby` request query parameter (if given)

response An array of objects, each of which represents the details of a given *Server*.

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cdnName Name of the CDN to which the server belongs

deliveryservices An array of integral, unique identifiers for *Delivery Services* to which this server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be `null`

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service¹

iloIpGateway The IPv4 gateway address of the server's ILO service¹

iloIpNetmask The IPv4 subnet mask of the server's ILO service¹

iloPassword The password of the of the server's ILO service user¹ - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' *Role(s)*

¹ For more information see the [Wikipedia page on Lights-Out management](#).

iloUsername The user name for the server's ILO service¹

interfaces An array of interface and IP address information

max_bandwidth The maximum allowed bandwidth for this interface to be considered “healthy” by Traffic Monitor. This has no effect if *monitor* is not true. Values are in kb/s. The value 0 means “no limit”.

monitor A boolean indicating if Traffic Monitor should monitor this interface

mtu The MTU to configure for *interfaceName*

See also:

[The Wikipedia article on Maximum Transmission Unit](#)

name The network interface name used by the server.

ipAddresses An array of the IP address information for the interface

address The IPv4 or IPv6 address and subnet mask of the server - applicable for the interface name

gateway The IPv4 or IPv6 gateway address of the server - applicable for the interface name

service_address A boolean determining if content will be routed to the IP address

mgmtIpAddress The IPv4 address of the server's management port

mgmtIpGateway The IPv4 gateway of the server's management port

mgmtIpNetmask The IPv4 subnet mask of the server's management port

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status

physLocation The name of the physical location where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

rack A string indicating “server rack” location

routerHostName The human-readable name of the router responsible for reaching this server

routerPortName The human-readable name of the port used by the router responsible for reaching this server

status The status of the server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the ‘type’ of this server

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

size The page number - if pagination was requested in the query parameters, else 0 to indicate no pagination - of the results represented by the response array. This is named “size” for legacy reasons

910: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 01:27:36.
→GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512:↵
↵HW2F3CEpohNAvNlEDhUfXmtwpEka4dwUWFVUSSjW98aXiv10vI6ysRIcC2P9huabCz5fdHqY3tp0LR4ekv
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 00:27:36 GMT
Content-Length: 493

{
  "limit": 1000,
  "orderby": "hostName",
  "response": [
    {
      "cachegroup": "CDN_in_a_Box_Edge",
      "cdnName": "CDN-in-a-Box",
      "deliveryservices": [
        1
      ],
      "domainName": "infra.ciab.test",
      "guid": null,
      "hardwareInfo": null,
      "hostName": "edge",
      "httpsPort": 443,
      "id": 5,
      "iloIpAddress": "",
      "iloIpGateway": "",
      "iloIpNetmask": "",
      "iloPassword": "",
      "iloUsername": "",
      "mgmtIpAddress": "",
      "mgmtIpGateway": "",
      "mgmtIpNetmask": "",
      "offlineReason": "",
      "physLocation": "Apachecon North America 2018",
      "profile": "ATS_EDGE_TIER_CACHE",
      "profileDesc": "Edge Cache - Apache Traffic Server",
      "rack": "",
      "routerHostName": "",
      "routerPortName": "",
      "status": "REPORTED",
      "tcpPort": 80,
      "type": "EDGE",
      "xmppId": "edge",
      "xmppPasswd": "",
      "interfaces": [
        { "ipAddresses": [
          {
            "address": "172.16.239.100",
```

(continues on next page)

(continued from previous page)

```

        "gateway": "172.16.239.1",
        "service_address": true
    },
    {
        "address": "fc01:9400:1000:8::100",
        "gateway": "fc01:9400:1000:8::1",
        "service_address": true
    }
],
"max_bandwidth": 0,
"monitor": true,
"mtu": 1500,
"name": "eth0"
}
]
"size": 1
}

```

servers/{HostName-Or-ID}/update

POST

Queue or dequeue updates and revalidation updates for a specific server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 375: Request Path Parameters

Name	Description
HostName-OR-ID	The hostName or integral, unique identifier of the server on which updates are being queued or dequeued

Table 376: Request Query Parameters

Name	Re-quired	Description
updated	no	The value to set for the queue update flag on this server. May be 'true' or 'false'.
reval_updated	no	The value to set for the queue update flag on this server. May be 'true' or 'false'.

911: Request Example

```
GET /api/3.0/servers/my-edge/update?updated=true&reval_updated=false_
→HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

912: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Mon, 10 Dec 2018 18:20:04 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54_
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 9Mmo9hIFZyF5gAvfdJD//
→VH9eNgiHVLinXt88H0GlJSHhwND8gMxaFyC+f9XZfiNAoGd1MKi1934ZJGmaIR6qQ==
Content-Length: 49

{
  "alerts" :
  [
    {
      "text" : "successfully set server 'my-edge'_
→updated=true reval_updated=false",
      "level" : "success"
```

(continues on next page)

(continued from previous page)

```

    }
  ]
}
```

servers/{hostname}/update_status

Note: This endpoint only truly has meaning for *cache servers*, though it will return a valid response for any server configured in Traffic Ops.

GET

Retrieves information regarding pending updates and revalidation jobs for a given server

Auth. Required Yes

Roles Required None

Response Type undefined - this endpoint will return a top-level array containing the response, as opposed to within a `response` object

Request Structure

Table 377: Request Path Parameters

Name	Description
hostname	The (short) hostname of the server being inspected

913: Request Example

```
GET /api/3.0/servers/edge/update_status HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

Each object in the returned array¹ will contain the following fields:

- host_id** The integral, unique identifier for the server for which the other fields in this object represent the pending updates and revalidation status
- host_name** The (short) hostname of the server for which the other fields in this object represent the pending updates and revalidation status
- parent_pending** A boolean telling whether or not any *Topology* ancestor or *parent* of this server has pending updates
- parent_reval_pending** A boolean telling whether or not any *Topology* ancestor or *parent* of this server has pending revalidation jobs
- reval_pending** true if the server has pending revalidation jobs, false otherwise
- status** The name of the status of this server

See also:

Health Protocol gives more information on how these statuses are used, and the GET method of the *statuses* endpoint can be used to retrieve information about all server statuses configured in Traffic Ops.

- upd_pending** true if the server has pending updates, false otherwise
- use_reval_pending** A boolean which tells *ORT* whether or not this version of Traffic Ops should use pending revalidation jobs

Note: This field was introduced to give *ORT* the ability to work with Traffic Control versions 1.x and 2.x seamlessly - as of Traffic Control v3.0 there is no reason for this field to ever be false.

914: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

¹ The returned object is an array, and there is no guarantee that one server exists for a given hostname. However, for each server in the array, that server's update status will be accurate for the server with that particular server ID.

(continued from previous page)

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳R6BjNVrceCHGn3eGDqQ1yDiBnEDGQe7QtOMIsRwlpck9SZR8chRQznrkTF3YdROAZ1l8BxR3fXTIvKHIz
    ↳dA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 04 Feb 2019 16:24:01 GMT
Content-Length: 174

[{"
  "host_name": "edge",
  "upd_pending": false,
  "reval_pending": false,
  "use_reval_pending": true,
  "host_id": 10,
  "status": "REPORTED",
  "parent_pending": false,
  "parent_reval_pending": false
}]
```

`servers/{ID}`

PUT

Allow user to edit a server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 378: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a server

cachegroupId An integer that is the *ID of the Cache Group* to which the server shall belong

cdnId The integral, unique identifier of the CDN to which the server shall belong

domainName The domain part of the server's FQDN

hostName The (short) hostname of the server

httpsPort An optional port number on which the server listens for incoming HTTPS connections/requests

iloIpAddress An optional IPv4 address of the server's ILO service¹

iloIpGateway An optional IPv4 gateway address of the server's ILO service^{Page 1364, 1}

iloIpNetmask An optional IPv4 subnet mask of the server's ILO service^{Page 1364, 1}

iloPassword An optional string containing the password of the of the server's ILO service user^{Page 1364, 1} - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' `ROLE(s) <ROLE>`

iloUsername An optional string containing the user name for the server's ILO service^{Page 1364, 1}

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be necessary, but it is illegal for this set to be an empty collection.

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be necessary, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface -

¹ For more information see the [Wikipedia page on Lights-Out management](#).

which is therefore sometimes referred to as the “service interface” for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning “no limit”. It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface. This unsigned integer must not be less than 1280.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface’s device name on the server, e.g. `eth0`.

mgmtIpAddress The IPv4 address of some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

physLocationId An integral, unique identifier for the physical location where the server resides

profileId The *ID* the *Profile* that shall be used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack An optional string indicating “server rack” location

routerHostName An optional string containing the human-readable name of the router responsible for reaching this server

routerPortName An optional string containing the human-readable name of the port used by the router responsible for reaching this server

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort An optional port number on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by **httpsPort** may also be used for incoming TCP connections.

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if **true**, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server hashId for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd An optional password used in XMPP communications with the server

915: Request Example

```
PUT /api/3.0/servers/14 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 599
Content-Type: application/json

{
  "cachegroupId": 6,
  "cdnId": 2,
  "domainName": "infra.ciab.test",
  "hostName": "quest",
  "httpsPort": 443,
  "iloIpAddress": "",
  "iloIpGateway": "",
```

(continues on next page)

(continued from previous page)

```

"iloIpNetmask": "",
"iloPassword": "",
"iloUsername": "",
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "::1",
        "gateway": "::2",
        "serviceAddress": true
      },
      {
        "address": "0.0.0.1/24",
        "gateway": "0.0.0.2",
        "serviceAddress": false
      }
    ],
    "maxBandwidth": null,
    "monitor": true,
    "mtu": 1500,
    "name": "bond0"
  }
],
"interfaceMtu": 1500,
"interfaceName": "eth0",
"ip6Address": "::1",
"ip6Gateway": "::2",
"ipAddress": "0.0.0.1",
"ipGateway": "0.0.0.2",
"ipNetmask": "255.255.255.0",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocationId": 1,
"profileId": 10,
"routerHostName": "",
"routerPortName": "",
"statusId": 3,
"tcpPort": 80,
"typeId": 12,
"updPending": false
}

```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId The integral, unique identifier of the CDN to which the server belongs

cdnName Name of the CDN to which the server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be `null`

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service Page 1364, 1

iloIpGateway The IPv4 gateway address of the server's ILO service Page 1364, 1

iloIpNetmask The IPv4 subnet mask of the server's ILO service Page 1364, 1

iloPassword The password of the of the server's ILO service user Page 1364, 1 - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' `ROLE(s) <ROLE>`

iloUsername The user name for the server's ILO service Page 1364, 1

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be present, but it is illegal for this set to be an empty collection.

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be present, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a “service address”. It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the “service interface” for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning “no limit”. It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface's device name on the server, e.g. `eth0`.

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces`

property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status

physLocation The name of the *Physical Location* where the server resides

physLocationId An integral, unique identifier for the *Physical Location* where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

profileId The *ID* the *Profile* used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack A string indicating “server rack” location

routerHostName The human-readable name of the router responsible for reaching this server

routerPortName The human-readable name of the port used by the router responsible for reaching this server

status The status of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the ‘type’ of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server hashId for use in Traffic Router's consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

916: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 19 May 2020 17:46:33.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 19 May 2020 16:46:33 GMT
Content-Length: 566

{ "alerts": [
  {
    "text": "Server updated",
    "level": "success"
  }
],
"response": {
  "cachegroup": "CDN_in_a_Box_Mid",
  "cachegroupId": 6,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "domainName": "infra.ciab.test",
  "guid": null,
  "hostName": "quest",
  "httpsPort": 443,
  "id": 14,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "lastUpdated": "2020-05-19 16:46:33+00",
  "mgmtIpAddress": "",
```

(continues on next page)

(continued from previous page)

```

"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_MID_TIER_CACHE",
"profileDesc": "Mid Cache - Apache Traffic Server",
"profileId": 10,
"rack": null,
"revalPending": false,
"routerHostName": "",
"routerPortName": "",
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "MID",
"typeId": 12,
"updPending": false,
"xmppId": null,
"xmppPasswd": null,
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "::1",
        "gateway": "::2",
        "serviceAddress": true
      },
      {
        "address": "0.0.0.1/24",
        "gateway": "0.0.0.2",
        "serviceAddress": false
      }
    ],
    "maxBandwidth": null,
    "monitor": true,
    "mtu": 1500,
    "name": "bond0"
  }
]
}}
```

DELETE

Allow user to delete server through api.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Changed in version 3.0: In older versions of the API, this endpoint did not return a response object. It now returns a representation of the deleted server.

Request Structure

Table 379: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a server

917: Request Example

```
DELETE /api/3.0/servers/14 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belonged

cachegroupId An integer that is the *ID of the Cache Group* to which the server belonged

cdnId The integral, unique identifier of the CDN to which the server belonged

cdnName Name of the CDN to which the server belonged

domainName The domain part of the server’s FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be null

hostName The (short) hostname of the server

httpsPort The port on which the server listened for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service [Page 1364, 1](#)

iloIpGateway The IPv4 gateway address of the server's ILO service [Page 1364, 1](#)

iloIpNetmask The IPv4 subnet mask of the server's ILO service [Page 1364, 1](#)

iloPassword The password of the of the server's ILO service user [Page 1364, 1](#) - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' *Role(s)*

iloUsername The user name for the server's ILO service [Page 1364, 1](#)

interfaces A set of the network interfaces that were in use by the server

ipAddresses A set of objects representing IP Addresses that were assigned to this network interface

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address".

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors would have considered the entire server unhealthy - which includes *all* configured network interfaces. If this was `null`, it has the meaning "no limit". It had no effect if `monitor` was not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should have been monitored by Traffic Monitor for statistics and health consideration

mtu The MTU of this interface. If it is `null`, it may be assumed that the information was either not available or not applicable for this interface.

name The name of the interface. It is the same as the network interface's device name on the server, e.g. `eth0`.

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server that was used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server that was used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server that was used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

offlineReason A user-entered reason why the server was in ADMIN_DOWN or OFFLINE status

physLocation The name of the physical location where the server resided

physLocationId An integral, unique identifier for the physical location where the server resided

profile The *Name* of the *Profile* which was used by this server

profileDesc A *Description* of the *Profile* which was used by this server

profileId The *ID* the *Profile* which was used by this server

revalPending A boolean value which, if `true` indicates that this server had pending content invalidation/revalidation

rack A string indicating “server rack” location

routerHostName The human-readable name of the router responsible for reaching this server

routerPortName The human-readable name of the port used by the router responsible for reaching this server

status The *Status* of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listened for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the *Type* of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server had updates of some kind pending, typically to be acted upon by Traffic Ops *ORT*

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

918: Response Example

```
HTTP/1.1 200 OK
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 19 May 2020 17:50:13 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 19 May 2020 16:50:13 GMT
Content-Length: 568

{ "alerts": [
  {
    "text": "Server deleted",
    "level": "success"
  }
],
"response": {
  "cachegroup": "CDN_in_a_Box_Mid",
  "cachegroupId": 6,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "domainName": "infra.ciab.test",
  "guid": null,
  "hostName": "quest",
  "httpsPort": 443,
  "id": 14,
  "iloIpAddress": "",
  "iloIpGateway": "",
```

(continues on next page)

(continued from previous page)

```

"iloIpNetmask": "",
"iloPassword": "",
"iloUsername": "",
"lastUpdated": "2020-05-19 16:46:33+00",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_MID_TIER_CACHE",
"profileDesc": "Mid Cache - Apache Traffic Server",
"profileId": 10,
"rack": null,
"revalPending": false,
"routerHostName": "",
"routerPortName": "",
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "MID",
"typeId": 12,
"updPending": false,
"xmppId": null,
"xmppPasswd": null,
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "0.0.0.1/24",
        "gateway": "0.0.0.2",
        "serviceAddress": false
      },
      {
        "address": "::1",
        "gateway": "::2",
        "serviceAddress": true
      }
    ],
    "maxBandwidth": null,
    "monitor": true,
    "mtu": 1500,
    "name": "bond0"
  }
]
}
}

```

`servers/{{ID}}/deliveryservices`

GET

Retrieves all *Delivery Services* assigned to a specific server.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 380: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the server for which assigned <i>Delivery Services</i> shall be listed

Table 381: Request Query Parameters

Name	Re- quired	Description
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the ⁿ th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

919: Request Example

```
GET /api/3.0/servers/9/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

¹ Only the *Delivery Services* visible to the requesting user’s *Tenant* will appear, regardless of their *Role* or the *Delivery Services*’ actual ‘server assignment’ status.

Response Structure

- active** A boolean that defines *Active*.
- anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
- cacheurl** A *Cache URL Expression*
 Deprecated since version ATCv3.0: This field has been deprecated in Traffic Control 3.x and is subject to removal in Traffic Control 4.x or later
- ccrDnsTtl** The *DNS TTL* - named “ccrDnsTtl” for legacy reasons
- cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
- cdnName** Name of the *CDN* to which the *Delivery Service* belongs
- checkPath** A *Check Path*
- consistentHashRegex** A *Consistent Hashing Regular Expression*
- consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
- deepCachingType** The *Deep Caching* setting for this *Delivery Service*
- displayName** The *Display Name*
- dnsBypassCname** A *DNS Bypass CNAME*
- dnsBypassIp** A *DNS Bypass IP*
- dnsBypassIp6** A *DNS Bypass IPv6*
- dnsBypassTtl** The *DNS Bypass TTL*
- dscp** A *DSCP* to be used within the *Delivery Service*
- ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*
- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*
- firstHeaderRewrite** A set of *First Header Rewrite Rules*
- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*
- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*
- geoLimitRedirectUrl** A *Geo Limit Redirect URL*
- geoProvider** The *Geolocation Provider*
- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in *Traffic Ops's Custom Date/Time Format*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

longDesc1 The 2nd long description of this *Delivery Service*

longDesc2 the 3rd long description of this *Delivery Service*

matchList The *Delivery Service's Match List*

- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
- setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
- type** The type of match performed using pattern.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId The *ID* of the *Profile* with which this *Delivery Service* is associated

- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if *rangeRequestHandling* is set to 3.
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*

920: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: CFmtW41aoDezCYxtAXnS54dffOD6jdxDJ2/
→LMpbBqnn5kac7JQhdFAWF109s195XVSUV85JHFzXZTw/mJabQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Jun 2019 17:01:30 GMT
Content-Length: 1500
```

```
{ "response": [ {
  "active": true,
  "anonymousBlockingEnabled": false,
  "cacheurl": null,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "checkPath": null,
  "displayName": "Demo 1",
  "dnsBypassCname": null,
  "dnsBypassIp": null,
  "dnsBypassIp6": null,
  "dnsBypassTtl": null,
  "dscp": 0,
  "edgeHeaderRewrite": null,
  "firstHeaderRewrite": null,
  "geoLimit": 0,
  "geoLimitCountries": null,
  "geoLimitRedirectURL": null,
  "geoProvider": 0,
  "globalMaxMbps": null,
  "globalMaxTps": null,
  "httpBypassFqdn": null,
  "id": 1,
  "infoUrl": null,
  "initialDispersion": 1,
  "innerHeaderRewrite": null,
  "ipv6RoutingEnabled": true,
  "lastHeaderRewrite": null,
  "lastUpdated": "2019-06-10 15:14:29+00",
  "logsEnabled": true,
  "longDesc": "Apachecon North America 2018",
  "longDesc1": null,
  "longDesc2": null,
  "matchList": [
    {
      "type": "HOST_REGEX",
      "setNumber": 0,
```

(continues on next page)

(continued from previous page)

```

        "pattern": ".*\\.demo1\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
    "http://video.demo1.mycdn.ciab.test",
    "https://video.demo1.mycdn.ciab.test"
],
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": "root",
"trResponseHeaders": null,
"trRequestHeaders": null,
"consistentHashRegex": null,
"consistentHashQueryParams": [
    "abc",
    "pdq",
    "xxx",
    "zyx"
],
"maxOriginConnections": 0,
"ecsEnabled": false,
"rangeSliceBlockSize": null,

```

(continues on next page)

(continued from previous page)

```
"topology": null
}}}
```

POST

Assign an arbitrary number of *Delivery Services* to a single server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 382: Request Path Parameters

Name	Re- quired	Description
ID	Yes	The integral, unique identifier of the server that you want to assign delivery services to.

Table 383: Request Query Parameters

Name	Re- quired	Description
re- place	Yes	Whether the list of <i>Delivery Services</i> you provide should replace the existing list or be merged with the existing list. Must be a 1, or true, or 0, or false.

The request body is an array of IDs of *Delivery Services* that you want to assign to the server. The array can be empty, but it must be provided.

921: Request Example

```
POST /api/3.0/servers/6/deliveryservices?replace=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 3

[
  1
]
```

Response Structure

dsIds An array of integral, unique identifiers for *Delivery Services* which the request added to server. If `:replace:` is false, *Delivery Services* that are already assigned will remain, though they are not listed by `:dsIds:`.

replace The `:replace:` value you provided in the body of the request, or null if none was provided.

serverId The server's integral, unique identifier

922: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 09:08:32
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳iV+JzAZSsmlxRZsNtIRg3oA9470hAwRMpq5xhcYVi0Y831Trx2YRlsyhYp0PqHg5+QPoXHGF0nx8uso0f
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 08:08:32 GMT
Content-Length: 129

{
  "alerts": [
    {
      "text": "successfully assigned dses to server",
      "level": "success"
    }
  ],
  "response": {
    "serverId": 6,
    "dsIds": [
      1
    ],
    "replace": true
  }
}
```

servers/{{ID}}/queue_update

Caution: In the vast majority of cases, it is advisable that the PUT method of the *servers/{{ID}}* endpoint be used instead.

POST

Queue or dequeue updates for a specific server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 384: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the server on which updates are being queued or dequeued

action A string describing what action to take regarding server updates; one of:

queue *Queue Updates* for the server, propagating configuration changes to the actual server

dequeue Cancels any pending updates on the server

923: Request Example

```
POST /api/3.0/servers/13/queue_update HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 22
Content-Type: application/json

{
  "action": "dequeue"
}
```

Response Structure

action The action processed, one of:

queue *Queue Updates* was performed on the server, propagating configuration changes to the actual server

dequeue Canceled any pending updates on the server

serverId The integral, unique identifier of the server on which action was taken

924: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Mon, 10 Dec 2018 18:20:04 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 9Mmo9hIFZyF5gAvfdJD//
→VH9eNgiHVLinXt88H0GlJSHhwND8gMxaFyC+f9XZfiNAoGd1MKi1934ZJGmaIR6qQ==
Content-Length: 49

{
  "response": {
    "serverId": "13",
    "action": "dequeue"
  }
}
```

servers/{{ID}}/status

PUT

Updates server status and queues updates on all descendant *Topology* nodes or child caches if server type is EDGE or MID. Also, captures offline reason if status is set to ADMIN_DOWN or OFFLINE and prepends offline reason with the user that initiated the status change.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 385: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the server whose status is being changed

offlineReason A string containing the reason for the status change

status The name or integral, unique identifier of the server's new status

925: Request Example

```
PUT /api/3.0/servers/13/status HTTP/1.1
```

```
Host: trafficops.infra.ciab.test
```

```
User-Agent: curl/7.47.0
```

```
Accept: */*
```

```
Cookie: mojolicious=...
```

```
Content-Length: 56
```

```
Content-Type: application/json
```

```
{
  "status": "ADMIN_DOWN",
  "offlineReason": "Bad drives"
}
```

Response Structure

926: Response Example

```
HTTP/1.1 200 OK
```

```
Access-Control-Allow-Credentials: true
```

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
```

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

```
Access-Control-Allow-Origin: *
```

```
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
```

```
Content-Type: application/json
```

```
Date: Mon, 10 Dec 2018 18:08:44 GMT
```

```
X-Server-Name: traffic_ops_golang/
```

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
```

```
Vary: Accept-Encoding
```

```
Whole-Content-Sha512:
→LS1jCo5eMVKxmeYDol0I2LgLYazocSggR5hynNoLcPmMov9u2s3ulksPdQtG1N3aS+VM9tdMsCrahFPra
```

```
Content-Length: 158
```

(continues on next page)

(continued from previous page)

```
{ "alerts": [
  {
    "level": "success",
    "text": "Updated status [ ADMIN_DOWN ] for quest.infra.ciab.
→test [ admin: Bad drives ] and queued updates on all child caches"
  }
]}
```

service_categories

GET

Get all requested *Service Categories*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 386: Request Query Parameters

Name	Description
name	Filter for <i>Service Categories</i> with this name
or-derby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the <i>n</i> th page of results, where “ <i>n</i> ” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

927: Request Example

```
GET /api/3.0/service_categories?name=SERVICE_CATEGORY_NAME HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

name This *Service Category*’s name

lastUpdated The date and time at which this *Service Category* was last modified, in *Traffic Ops*’s *Custom Date/Time Format*

928: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Yzr6TfhxgpZ3pbrrr4TRG4wC3PlnHDDzgs2igtz/
→1ppLSy2MzugqaGW4y5yzwzl5T3+7q6HWej7GQZt1XIVeZQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 11 Mar 2020 20:02:47 GMT
Content-Length: 102

{
  "response": [
    {
      "lastUpdated": "2020-03-04 15:46:20-07",
      "name": "SERVICE_CATEGORY_NAME"
    }
  ]
}
```

POST

Create a new service category.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name This *Service Category*'s name

929: Request Example

```
POST /api/3.0/service_categories HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 48
Content-Type: application/json

{
  "name": "SERVICE_CATEGORY_NAME",
}
```

Response Structure

name This *Service Category*'s name

lastUpdated The date and time at which this *Service Category* was last modified,
in *Traffic Ops's Custom Date/Time Format*

930: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +pJm4c30+JTaSXNt+LP+u240Ba/
→SsvSSDOQ4rDc6hcyZ0FIL+iY/WWrMHhpLulRGKGY88bM4YPCMaxGn3FZ9yQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 11 Mar 2020 20:12:20 GMT
Content-Length: 154

{
  "alerts": [
    {
      "text": "serviceCategory was created.",
      "level": "success"
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```

    }
  ],
  "response": {
    "lastUpdated": "2020-03-11 14:12:20-06",
    "name": "SERVICE_CATEGORY_NAME"
  }
}

```

DELETE

Deletes a specific *Service Category*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

931: Request Example

```

DELETE /api/3.0/service_categories/my-service-category HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0

```

Response Structure

932: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 17 Aug 2020 16:13:31
→GMT; Max-Age=3600; HttpOnly

```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: yErJobzG9IA0khvqZQK+Yi7X4pFVvOqxn6PjrdzN5DnKVm/
↪K8Kka3REul1XmKJnMXVRY8RayoEVDm16mBFfe4Q==
X-Server-Name: traffic_ops_golang/
Date: Mon, 17 Aug 2020 15:13:31 GMT
Content-Length: 93

{
  "alerts": [
    {
      "text": "serviceCategory was deleted.",
      "level": "success"
    }
  ]
}
```

snapshot

PUT

Performs a CDN *Snapshot*. Effectively, this propagates the new *configuration* of the CDN to its *operating state*, which replaces the output of the `cdns/{name}/snapshot` endpoint with the output of the `cdns/{name}/snapshot/new` endpoint. This also changes the output of the `cdns/{name}/configs/monitoring` endpoint since that endpoint returns the latest monitoring information from the *operating state*.

Note: Snapshotting the CDN also deletes all HTTPS certificates for every *Delivery Service* which has been deleted since the last *Snapshot*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 387: Request Query Parameters

Name	Description
cdn	The name of the CDN for which a <i>Snapshot</i> shall be taken
cdnID	The id of the CDN for which a <i>Snapshot</i> shall be taken

Note: At least one query parameter must be given.

933: Request Example

```
PUT /api/3.0/snapshot?cdn=CDN-in-a-Box HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

934: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳gmaWI0tKgNFPY00zMrLCGDosBJkPbeIvW4BH9tEh96VjBqyWqzjgPySoMa3ViM1BQXA6VAUOGmc76VyhB
X-Server-Name: traffic_ops_golang/
Date: Wed, 18 Mar 2020 15:51:48 GMT
Content-Length: 47

{
  "response": "SUCCESS"
}
```

staticdnsentries

GET

Retrieve all static DNS entries configured within Traffic Control

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 388: Request Query Parameters

Name	Re- quired	Description
ad- dress	no	Return only static DNS entries that operate on this address/CNAME
cachegroup	no	Return only static DNS entries assigned to the <i>Cache Group</i> that has this <i>Name</i>
cachegroupId	no	Return only static DNS entries assigned to the <i>Cache Group</i> that has this <i>ID</i>
deliv- ery- ser- vice	no	Return only static DNS entries that apply within the domain of the <i>Delivery Service</i> with this <i>xml_id</i>
deliv- ery- servi- ceId	no	Return only static DNS entries that apply within the domain of the <i>Delivery Service</i> identified by this integral, unique identifier
host	no	Return only static DNS entries that resolve this FQDN
id	no	Return only the static DNS entry with this integral, unique identifier
ttl	no	Return only static DNS entries with this TTL
type	no	Return only static DNS entries of this type
typeId	no	Return only static DNS entries of the type identified by this integral, unique identifier
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

935: Request Example

```
GET /api/3.0/staticdnsentries?address=foo.bar HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

address If `typeId` identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which `host` shall be resolved

cachegroup An optional string containing the *Name of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryservice The name of a *Delivery Service* under the domain of which this static DNS entry shall be active

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If `typeId` identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the Fully Qualified Domain Name (FQDN) which shall resolve to `address`

id An integral, unique identifier for this static DNS entry

ttl The TTL of this static DNS entry in seconds

type The name of the type of this static DNS entry

typeId The integral, unique identifier of the *Type* of this static DNS entry

936: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Px1zTH3ihg+hfmDADGcap0Juuud39fGsX5Y3CzqaFNmRwFu1ZLMz0sy0EN2pb7vp0tpI6/
    ↳zeIUYAC3dbSbw0mA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:04:33 GMT
Content-Length: 226

{ "response": [
  {
    "address": "foo.bar.",
    "cachegroup": null,
    "cachegroupId": null,
    "deliveryservice": "demo1",
    "deliveryserviceId": 1,
    "host": "test",
    "id": 2,
    "lastUpdated": "2018-12-10 19:59:56+00",
    "ttl": 300,
    "type": "CNAME_RECORD",
    "typeId": 41
  }
]}

```

POST

Creates a new, static DNS entry.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

address If `typeId` identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which `host` shall be resolved

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If `typeId` identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the FQDN which shall resolve to `address`

ttl The TTL of this static DNS entry in seconds

typeId The integral, unique identifier of the *Type* of this static DNS entry

937: Request Example

```
POST /api/3.0/staticdnsentries HTTP/1.1
```

```
Host: trafficops.infra.ciab.test
```

```
User-Agent: curl/7.47.0
```

```
Accept: */*
```

```
Cookie: mojolicious=...
```

```
Content-Length: 92
```

```
Content-Type: application/json
```

```
{
  "address": "test.quest.",
  "deliveryserviceId": 1,
  "host": "test",
  "ttl": 300,
  "typeId": 41
}
```


Response Structure

address If `typeId` identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which `host` shall be resolved

cachegroup An optional string containing the *Name of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryservice The name of a *Delivery Service* under the domain of which this static DNS entry shall be active

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If `typeId` identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the Fully Qualified Domain Name (FQDN) which shall resolve to `address`

id An integral, unique identifier for this static DNS entry

ttl The TTL of this static DNS entry in seconds

type The name of the *Type* of this static DNS entry

typeId The integral, unique identifier of the *Type* of this static DNS entry

938: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 8dcJyjw2NJZx0L90z16P7g/
→7j5A1jlpYiY6Y+rRVQ2wGcwYI3yiGPrz6ur0qKzggqEBBsh8aPF44WTHAR9jUJdg==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 19:54:19 GMT
Content-Length: 282

{ "alerts": [
  {
    "text": "staticDNSEntry was created.",
    "level": "success"
  }
],
"response": {
  "address": "test.quest.",
  "cachegroup": null,
  "cachegroupId": null,
  "deliveryservice": null,
  "deliveryserviceId": 1,
  "host": "test",
  "id": 2,
  "lastUpdated": "2018-12-10 19:54:19+00",
  "ttl": 300,
  "type": "CNAME_RECORD",
  "typeId": 41
}}
```

PUT

Updates a static DNS entry.

Auth. Required Yes

Role(s) Required “admin” or “operator”

Response Type Object

Request Structure

Table 389: Request Query Parameters

Name	Description
id	The integral, unique identifier of the static DNS entry to modify

address If typeId identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which host shall be resolved

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If typeId identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the Fully Qualified Domain Name (FQDN) which shall resolve to address

ttl The TTL of this static DNS entry in seconds

typeId The integral, unique identifier of the *Type* of this static DNS entry

939: Request Example

```
PUT /api/3.0/staticdnsentries?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 89
Content-Type: application/json

{
  "address": "foo.bar.",
  "deliveryserviceId": 1,
  "host": "test",
  "ttl": 300,
  "typeId": 41
}
```

Response Structure

address If typeId identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which host shall be resolved

cachegroup An optional string containing the *Name of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

- deliveryservice** The name of a *Delivery Service* under the domain of which this static DNS entry shall be active
- deliveryserviceId** The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active
- host** If typeId identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the FQDN which shall resolve to address
- id** An integral, unique identifier for this static DNS entry
- ttl** The TTL of this static DNS entry in seconds
- type** The name of the *Type* of this static DNS entry
- typeId** The integral, unique identifier of the *Type* of this static DNS entry

940: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳+FaYmpnlIIzVSBq0nosw29NZcV9xFhlVgWuUqXUyiDihVUSzX4jrdAlORDgzDvKsYQB8LSkPdGHwt1zjg
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 19:59:56 GMT
Content-Length: 279

{ "alerts": [
  {
    "text": "staticDNSEntry was updated.",
    "level": "success"
  }
],
"response": {
  "address": "foo.bar.",
  "cachegroup": null,
  "cachegroupId": null,
  "deliveryservice": null,
  "deliveryserviceId": 1,
```

(continues on next page)

(continued from previous page)

```
"host": "test",
"id": 2,
"lastUpdated": "2018-12-10 19:59:56+00",
"ttl": 300,
"type": "CNAME_RECORD",
"typeId": 41
}}
```

DELETE

Delete staticdnsentries.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 390: Request Query Parameters

Name	Description
id	The integral, unique identifier of the static DNS entry to delete

941: Request Example

```
DELETE /api/3.0/staticdnsentries?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

942: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→g6uqHPU44LuTtqU2ahtazrVCpcpNWVc9kWJQ0YRuiVLDnsm39KOB/xt3XM6j0/
→X3WYiIawnNspkxRC85LJHwFA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:05:52 GMT
Content-Length: 69

{ "alerts": [
  {
    "text": "staticDNSEntry was deleted.",
    "level": "success"
  }
]}

```

stats_summary

GET

Either retrieve a list of summary stats or the timestamp of the latest recorded stats summary.

What is returned is driven by the query parameter `lastSummaryDate`.

If the parameter is set it will return an object with the latest timestamp, else an array of summary stats will be returned.

Auth. Required Yes

Roles Required None

Response Type Array or Object

Request Structure

Summary Stats

Table 391: Request Query Parameters

Name	Required	Description
deliveryServiceName	no	Return only summary stats that were reported for <i>Delivery Service</i> with the given display name
cdnName	no	Return only summary stats that were reported for CDN with the given name
statName	no	Return only summary stats that were reported for given stat name
orderBy	no	Choose the ordering of the results - can only be one of deliveryServiceName, statName or cdnName
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

943: Request Example

```
GET /api/3.0/stats_summary HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Last Updated Summary Stat

Table 392: Request Query Parameters

Name	Required	Description
statName	no	Get latest updated date for the given stat
lastSummaryDate	yes	Tells route to get only latest updated timestamp

944: Request Example

```
GET /api/3.0/stats_summary?lastSummaryDate=true HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

Summary Stats

cdnName The CDN name for which the summary stat was taken for

Note: If the `cdn` is equal to `all` it represents `summary_stats` across all delivery services across all CDNs

deliveryServiceName The *Delivery Service* display name for which the summary stat was taken for

Note: If the `deliveryServiceName` is equal to `all` it represents `summary_stats` across all delivery services within the given CDN

statName Stat name summary stat represents

statValue Summary stat value

summaryTime Timestamp of summary, in *Traffic Ops's Custom Date/Time Format*

statDate Date stat was taken, in YYYY-MM-DD format

945: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dHNip9kpTGGs1w39/fWcFehNktgmXZus8XaufnmDpv0PyG/
→3fK/KfoC03Z0j9V74/CCffps7doEygWeL/xRtKA==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:56:59 GMT
Content-Length: 150

{ "response": [
  {
    "cdnName": "CDN-in-a-Box",
    "deliveryServiceName": "all",
    "statName": "daily_maxgbps",
    "statValue": 5,
    "summaryTime": "2019-11-19 00:04:06+00",
    "statDate": "2019-11-19"
  },
  {
    "cdnName": "CDN-in-a-Box",
    "deliveryServiceName": "all",
    "statName": "daily_maxgbps",
    "statValue": 3,
    "summaryTime": "2019-11-18 00:04:06+00",
    "statDate": "2019-11-18"
  },
  {
    "cdnName": "CDN-in-a-Box",
    "deliveryServiceName": "all",
    "statName": "daily_bytesserved",
    "statValue": 1000,
    "summaryTime": "2019-11-19 00:04:06+00",
    "statDate": "2019-11-19"
  }
]}

```

Last Updated Summary Stat

summaryTime Timestamp of the last updated summary, in *Traffic Ops's Custom Date/Time Format*

946: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json

```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dHNip9kpTGGS1w39/fWcFehNktgmXZus8XaufnmDpv0PyG/
→3fK/KfoC03Z0j9V74/CCffps7doEygWeL/xRtKA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:56:59 GMT
Content-Length: 150

{ "response": {
  "summaryTime": "2019-11-19 00:04:06+00"
}}
```

POST

Post a stats summary for a given stat.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

cdnName The CDN name for which the summary stat was taken for

Note: If the `cdn` is equal to `all` it represents `summary_stats` across all delivery services across all CDNs

deliveryServiceName The *Delivery Service* display name for which the summary stat was taken for

Note: If the `deliveryServiceName` is equal to `all` it represents `summary_stats` across all delivery services within the given CDN

statName Stat name summary stat represents

statValue Summary stat value

summaryTime Timestamp of summary, in *Traffic Ops's Custom Date/Time Format*

statDate Date stat was taken, in YYYY-MM-DD format

Note: statName, statValue and summaryTime are required. If cdnName and deliveryServiceName are not given they will default to all.

947: Request Example

```
POST /api/3.0/stats_summary HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 113
Content-Type: application/json

{
  "cdnName": "CDN-in-a-Box",
  "deliveryServiceName": "all",
  "statName": "daily_maxgbps",
  "statValue": 10,
  "summaryTime": "2019-12-05 00:03:57+00",
  "statDate": "2019-12-05"
}
```

Response Structure

948: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳ezxk+iP7o7KE7zpWmGc0j8nz5k+1wAzY0HiNiA2xswTQrt+N+6CgQqUV2r9G1HAsPNr0HF2PhYs/
  ↳Xr7DrY0w0A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 02:14:45 GMT
Content-Length: 97

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

    "text": "Stats Summary was successfully created",
    "level": "success"
  }
}
```

statuses

GET

Retrieves a list of all server *Statuses*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 393: Request Query Parameters

Name	Re- quired	Description
de- scrip- tion	no	Return only <i>Statuses</i> with this <i>exact</i> description
id	no	Return only the <i>Status</i> with this integral, unique identifier
name	no	Return only <i>Statuses</i> with this name
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
off- set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>n</i> th page of results, where “ <i>n</i> ” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

949: Request Example

```

GET /api/3.0/statuses?name=REPORTED HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- description** A short description of the status
- id** The integral, unique identifier of this status
- lastUpdated** The date and time at which this status was last modified, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the status

950: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dHNip9kpTGGS1w39/fWcFehNktgmXZus8XaufnmDpv0PyG/
    ↳3fK/KfoC03Z0j9V74/CCffps7doEygWeL/xRtKA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:56:59 GMT
Content-Length: 150

{ "response": [
  {
    "description": "Server is online and reported in the health
    ↳protocol.",
    "id": 3,
    "lastUpdated": "2018-12-10 19:11:17+00",
    "name": "REPORTED"
  }
]}
```

steering

GET

Gets a list of all *Steering Targets* in the Traffic Ops database.

Auth. Required Yes

Roles Required “Portal”, “Steering”, “Federation”, “operations” or “admin”

Response Type Array

Request Structure

No parameters available.

951: Request Example

```
GET /api/3.0/steering HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

deliveryService A string that is the *xml_id* of the steering *Delivery Service*

clientSteering Whether this is a *client steering* Delivery Service.

targets The delivery services that the :ref:Steering Delivery Service <tr-steering>` targets.

order If this is a *STEERING_ORDER* target, this is the value of the order. Otherwise, 0.

weight If this is a *STEERING_WEIGHT* target, this is the value of the weight. Otherwise, 0.

deliveryService A string that is the *xml_id* of the steering *Delivery Service*

filters Filters of type *STEERING_REGEXP* that exist on either of the targets.

deliveryService A string that is the *xml_id* of the steering *Delivery Service*

pattern A regular expression - the use of this pattern is dependent on the *type* field (backslashes are escaped)

952: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 18:56:57
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳hcJa4xVLDx7bxBmoSjYo5YUwdSBWQr9GqlqRYrc6ZU7LeenjiV3go22YlIHt/
    ↳GtjLcHQjJ5DulKRhdsvFMq7Fng==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 17:56:57 GMT
Content-Length: 167
```

```
{
  "response": [
    {
      "deliveryService": "steering1",
      "clientSteering": true,
      "targets": [
        {
          "order": 0,
          "weight": 1,
          "deliveryService": "demo1"
        },
        {
          "order": 0,
          "weight": 2,
          "deliveryService": "demo2"
        }
      ],
      "filters": [
        {
          "deliveryService": "demo1",
          "pattern": ".*\\.demo1\\.\\.*"
        },
        {
          "deliveryService": "demo2",
          "pattern": ".*\\.demo2*\\.\\.*"
        }
      ]
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```
]
}
```

steering/{ID}/targets

GET

Get all targets for a steering *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 394: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i> for which targets shall be listed

Table 395: Request Query Parameters

Name	Description
target	Return only the target mappings that target the <i>Delivery Service</i> identified by this integral, unique identifier
orderBy	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

953: Request Structure

```
GET /api/3.0/steering/2/targets?target=1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- deliveryService** A string that is the *xml_id* of the steering *Delivery Service*
- deliveryServiceId** An integral, unique identifier for the steering *Delivery Service*
- target** A string that is the *xml_id* of this target *Delivery Service*
- targetId** An integral, unique identifier for this target *Delivery Service*
- type** The steering type of this target *Delivery Service*. This should be one of STEERING_WEIGHT, STEERING_ORDER, STEERING_GEO_ORDER or STEERING_GEO_WEIGHT
- typeId** An integral, unique identifier for the *steering type* of this target *Delivery Service*
- value** The 'weight', 'order', 'geo_order' or 'geo_weight' attributed to this steering target as an integer

954: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳utlJK4oYS2l6Ff7NzAqRuQeMEtaZyn3rM3Nlux2XgTLxvSyslHy0mJrwDExSU05gVMdrgYCLZrZEvPHlEL
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 14:09:23 GMT
Content-Length: 130

{ "response": [
  {
    "deliveryService": "test",
    "deliveryServiceId": 2,
    "target": "demo1",
    "targetId": 1,
    "type": "STEERING_ORDER",
    "typeId": 44,
```

(continues on next page)

(continued from previous page)

```

    "value": 100
  }
}]

```

POST

Create a steering target.

Auth. Required Yes

Roles Required Portal, Steering, Federation, “operations” or “admin”

Response Type Object

Request Structure

Table 396: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i> to which a target shall be added

targetId The integral, unique identifier of a *Delivery Service* which shall be a new steering target for the *Delivery Service* identified by the ID path parameter

typeId The integral, unique identifier of the steering type of the new target *Delivery Service*. This should be corresponding to one of STEERING_WEIGHT, STEERING_ORDER, STEERING_GEO_ORDER or STEERING_GEO_WEIGHT

value The ‘weight’, ‘order’, ‘geo_order’ or ‘geo_weight’ which shall be attributed to the new target *Delivery Service*

955: Request Example

```

POST /api/3.0/steering/2/targets HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 43
Content-Type: application/json

{
  "targetId": 1,
  "value": 100,
  "typeId": 43
}

```

Response Structure

- deliveryService** A string that is the *xml_id* of the steering *Delivery Service*
- deliveryServiceId** An integral, unique identifier for the steering *Delivery Service*
- target** A string that is the *xml_id* of this target *Delivery Service*
- targetId** An integral, unique identifier for this target *Delivery Service*
- type** The steering type of this target *Delivery Service*. This should be one of STEERING_WEIGHT, STEERING_ORDER, STEERING_GEO_ORDER or STEERING_GEO_WEIGHT
- typeId** An integral, unique identifier for the *steering type* of this target *Delivery Service*
- value** The ‘weight’, ‘order’, ‘geo_order’ or ‘geo_weight’ attributed to this steering target as an integer

956: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳+dTvfzrnOhdWAOMmY28r0+gFV5z+3aABI2FfAMziTYcU+pZrDanrJzMXpKWIL5Q/
    ↳oCUBZpJDRt9hRCFkT4oGYw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 21:22:17 GMT
Content-Length: 196

{ "alerts": [
  {
    "text": "steeringtarget was created.",
    "level": "success"
  }
],
"response": {
  "deliveryService": "test",
  "deliveryServiceId": 2,
  "target": "demo1",
  "targetId": 1,
  "type": "HTTP",
```

(continues on next page)

(continued from previous page)

```
"typeId": 1,
"value": 100
}}
```

steering/{ID}/targets/{targetID}

PUT

Updates a steering target.

Auth. Required Yes

Roles Required Portal, Steering, Federation, “operations” or “admin”

Response Type Object

Request Structure

Table 397: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i>
targetID	The integral, unique identifier of a <i>Delivery Service</i> which is a target of the <i>Delivery Service</i> identified by ID

typeId The integral, unique identifier of the *steering type* of the target *Delivery Service*. This should be corresponding to one of STEERING_WEIGHT, STEERING_ORDER, STEERING_GEO_ORDER or STEERING_GEO_WEIGHT

value The ‘weight’, ‘order’, ‘geo_order’ or ‘geo_weight’ which shall be attributed to the target *Delivery Service*

957: Request Example

```
PUT /api/3.0/steering/2/targets/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 26
Content-Type: application/json

{
  "value": 1,
  "typeId": 43
}
```

Response Structure

- deliveryService** A string that is the *xml_id* of the steering *Delivery Service*
- deliveryServiceId** An integral, unique identifier for the steering *Delivery Service*
- target** A string that is the *xml_id* of this target *Delivery Service*
- targetId** An integral, unique identifier for this target *Delivery Service*
- type** The steering type of this target *Delivery Service*
- typeId** An integral, unique identifier for the *steering type* of this target *Delivery Service*
- value** The ‘weight’ attributed to this steering target as an integer

958: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→AfXsIRzdtU3HZYkr93qBMVTZRJ5oTF2u5sKYnd+DSqxZ+RQxY6vXtCupnnXCf9dxMt5QXRW1EFOW/
→FBG6lFrTg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 14:34:22 GMT
Content-Length: 194

{ "alerts": [
  {
    "text": "steeringtarget was updated.",
    "level": "success"
  }
],
"response": {
  "deliveryService": "test",
  "deliveryServiceId": 2,
  "target": "demo1",
  "targetId": 1,
  "type": "HTTP",
  "typeId": 1,
  "value": 1
}}
```

DELETE

Removes a specific target mapping from a specific *Delivery Service*

Auth. Required Yes

Roles Required Portal, Steering, Federation, “operations” or “admin”

Response Type undefined

Request Structure

Table 398: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i> - a target of which shall be deleted
targetID	The integral, unique identifier of a <i>Delivery Service</i> which is a target to be removed of the <i>Delivery Service</i> identified by ID

959: Request Example

```
DELETE /api/3.0/steering/2/targets/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

960: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳N6h8Kl7uQveqpTc3fmKXFDY2yYe5smApNcaTow4ab0DHGFdJfqQh89I4nvvaXvmVNhxVAqX3UE/
    ↳6blb08/9Xqg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 14:42:54 GMT
```

(continues on next page)

(continued from previous page)

Content-Length: 69

```
{ "alerts": [
  {
    "text": "steeringtarget was deleted.",
    "level": "success"
  }
]}
```

system/info

GET

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

parameters An object containing information about the Traffic Ops server

Note: These are all the *Parameters* in *The GLOBAL Profile*, so the keys below are merely those present by default required for Traffic Control to operate

default_geo_miss_latitude The default latitude used when geographic lookup of an IP address fails

default_geo_miss_longitude The default longitude used when geographic lookup of an IP address fails

tm.instance_name The name of the Traffic Ops instance; typically used when multiple instances are active

tm.toolname The name of the Traffic Ops tool (usually “Traffic Ops”) - used in several API endpoints and written in comment headers on most Apache Traffic Server (ATS) configuration files generated by Traffic Ops

tm.url The URL for this Traffic Ops instance) - used in several API endpoints and written in comment headers on most Apache Traffic Server (ATS) configuration files generated by Traffic Ops

use_reval_pending A string containing an integer which represents a boolean value (hold your applause); one of:

“0” Do not use pending revalidations - this effectively prohibits the use of “Content Invalidation Jobs”

“1” Use pending revalidations - this effectively enables the use of “Content Invalidation Jobs”

use_tenancy A string containing an integer which represents a boolean value; one of:

“0” Do not use tenancy - this effectively disables all **tenant** endpoints and removes tenancy restrictions on origins and *Delivery Services*

“1” Use tenancy - this effectively enables all **tenant** endpoints and enforces tenancy restrictions on origins and *Delivery Services*

961: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ObxOXk1jrC1/
→JtrqElUICceyx9iJKJxZydEIHvAU7khTTQwt0QGvS04ELdkdrbu3ctFo3pf3NAMAmm9tAkNokg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 19:06:01 GMT
Content-Length: 285

{ "response": {
  "parameters": {
    "default_geo_miss_latitude": "0",
    "default_geo_miss_longitude": "-1",
    "tm.instance_name": "CDN-In-A-Box",
    "tm.logourl": "/images/tc_logo.png",
    "tm.toolname": "Traffic Ops",
    "tm.url": "https://trafficops.infra.ciab.test:443/",
    "use_reval_pending": "0",
```

(continues on next page)

(continued from previous page)

```

    "use_tenancy": "1"
  }
}
```

tenants

GET

Get all requested *Tenants*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 399: Request Query Parameters

Name	Description
ac- tive	If true, return only active <i>Tenants</i> ; if false return only inactive <i>Tenants</i>
id	Return only <i>Tenants</i> with this integral, unique identifier
name	Return only <i>Tenants</i> with this name
or- derby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

962: Request Example

```

GET /api/3.0/tenants?name=root HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

active A boolean which indicates whether or not the *Tenant* is active

id The integral, unique identifier of this *Tenant*

name This *Tenant*'s name

parentId The integral, unique identifier of this *Tenant*'s parent

parentName The name of the parent of this *Tenant*

963: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Yzr6TfhxgpZ3pbrrr4TRG4wC3PlnHDDzgs2igtz/
    ↳1ppLSy2MzugqaGW4y5yzwzl5T3+7q6HWej7GQZt1XIVeZQ==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 19:57:58 GMT
Content-Length: 106

{ "response": [
  {
    "id": 1,
    "name": "root",
    "active": true,
    "lastUpdated": "2018-12-10 19:11:17+00",
    "parentId": null
  }
]}
```

POST

Create a new tenant.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

active An optional boolean - default: false - which indicates whether or not the tenant shall be immediately active

name The name of the tenant

parentId The integral, unique identifier of the parent of this tenant

964: Request Example

```
POST /api/3.0/tenants HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 48
Content-Type: application/json

{
  "active": true,
  "name": "test",
  "parentId": 1
}
```

Response Structure

active A boolean which indicates whether or not the tenant is active

id The integral, unique identifier of this tenant

name This tenant's name

parentId The integral, unique identifier of this tenant's parent

965: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
↪GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ysdopC//
↪JQI79BRUa61s6M2HzHxYHpo5Rdcuau0oqCYxiV0oUhNZfOVydVkv8zDN2qA374XKnym4kWj3VzQIXg==
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

```
Date: Tue, 11 Dec 2018 19:37:16 GMT
Content-Length: 162

{ "alerts": [
  {
    "text": "tenant was created.",
    "level": "success"
  }
],
"response": {
  "id": 9,
  "name": "test",
  "active": true,
  "lastUpdated": "2018-12-11 19:37:16+00",
  "parentId": 1
}}
```

`tenants/{ID}`

PUT

Updates a specific tenant.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 400: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the tenant being modified

active An optional boolean - default: `false` - which indicates whether or not the tenant shall be immediately active

name The name of the tenant

parentId The integral, unique identifier of the parent of this tenant

966: Request Example

```
PUT /api/3.0/tenants/9 HTTP/1.1
Host: trafficops.infra.ciab.test
```

(continues on next page)

(continued from previous page)

```
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 59
Content-Type: application/json

{
  "active": true,
  "name": "quest",
  "parentId": 3
}
```

Response Structure

active A boolean which indicates whether or not the tenant is active

id The integral, unique identifier of this tenant

name This tenant's name

parentId The integral, unique identifier of this tenant's parent

967: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 5soYQFrG2x5ZJ1e5UZIOLUv/
→928qyd2Bfgw21Wv85rqjLpyeT3djkrVD1/xpKConulNrZs2czJKrrwZA7X6lw==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 20:30:54 GMT
Content-Length: 163

{ "alerts": [
  {
    "text": "tenant was updated.",
    "level": "success"
  }
],
"response": {
  "id": 9,
```

(continues on next page)

(continued from previous page)

```
"name": "quest",
"active": true,
"lastUpdated": "2018-12-11 20:30:54+00",
"parentId": 3
}}
```

DELETE

Deletes a specific tenant.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 401: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the tenant being deleted

968: Request Example

```
DELETE /api/3.0/tenants/9 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

969: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: KU0XIbFoD0Cy06kzH2G159pBqie/
→TEFJgh33mssGNwXJZlRkTLaSTHT8Df4X+pOs7UauZH10akGvaA0UTiN/vg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 20:40:31 GMT
Content-Length: 61

{ "alerts": [
  {
    "text": "tenant was deleted.",
    "level": "success"
  }
]}
```

topologies

GET

Retrieves *Topologies*.

Auth. Required Yes

Roles Required “read-only”

Response Type Array

Request Structure

Table 402: Request Query Parameters

Name	Required	Description
name	no	Return the <i>Topology</i> with this name

970: Request Example

```
GET /api/3.0/topologies HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

- description** A short sentence that describes the *Topology*.
- lastUpdated** The date and time at which this *Topology* was last updated, in ISO-like format
- name** The name of the *Topology*. This can only be letters, numbers, and dashes.
- nodes** An array of nodes in the *Topology*
 - cachegroup** The name of a *Cache Group*
 - parents** The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

971: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 13 Apr 2020 18:22:32
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳1F4MCJCinuQWz0f1LAAZBrzbuPVsHrNn2BtTozRZojEjGpm76IsXBQK5Q0wSwBoHac+D0C1Z3p7M8kdjc
X-Server-Name: traffic_ops_golang/
Date: Mon, 13 Apr 2020 17:22:32 GMT
Content-Length: 205

{
  "response": [
    {
      "description": "This is my topology",
      "name": "my-topology",
```

(continues on next page)

(continued from previous page)

```

"nodes": [
  {
    "cachegroup": "edge1",
    "parents": [
      7
    ]
  },
  {
    "cachegroup": "edge2",
    "parents": [
      7,
      8
    ]
  },
  {
    "cachegroup": "edge3",
    "parents": [
      8,
      9
    ]
  },
  {
    "cachegroup": "edge4",
    "parents": [
      9
    ]
  },
  {
    "cachegroup": "mid1",
    "parents": []
  },
  {
    "cachegroup": "mid2",
    "parents": [
      4
    ]
  },
  {
    "cachegroup": "mid3",
    "parents": [
      4
    ]
  },
  {
    "cachegroup": "mid4",
    "parents": [

```

(continues on next page)

(continued from previous page)

```

        5
      ]
    },
    {
      "cachegroup": "mid5",
      "parents": [
        5,
        6
      ]
    },
    {
      "cachegroup": "mid6",
      "parents": [
        6
      ]
    }
  ],
  "lastUpdated": "2020-04-13 17:12:34+00"
}
]
}

```

POST

Create a new *Topology*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

description A short sentence that describes the topology.

name The name of the topology. This can only be letters, numbers, and dashes.

nodes An array of nodes in the *Topology*

cachegroup The name of a *Cache Group* with at least 1 server in it

parents The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

972: Request Example

```
POST /api/3.0/topologies HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 924
Content-Type: application/json

{
  "name": "my-topology",
  "description": "This is my topology",
  "nodes": [
    {
      "cachegroup": "edge1",
      "parents": [
        7
      ]
    },
    {
      "cachegroup": "edge2",
      "parents": [
        7,
        8
      ]
    },
    {
      "cachegroup": "edge3",
      "parents": [
        8,
        9
      ]
    },
    {
      "cachegroup": "edge4",
      "parents": [
        9
      ]
    },
    {
      "cachegroup": "mid1",
      "parents": []
    },
    {
      "cachegroup": "mid2",
```

(continues on next page)

(continued from previous page)

```

        "parents": [
            4
        ]
    },
    {
        "cachegroup": "mid3",
        "parents": [
            4
        ]
    },
    {
        "cachegroup": "mid4",
        "parents": [
            5
        ]
    },
    {
        "cachegroup": "mid5",
        "parents": [
            5,
            6
        ]
    },
    {
        "cachegroup": "mid6",
        "parents": [
            6
        ]
    }
]
}

```

Response Structure

description A short sentence that describes the topology.

lastUpdated The date and time at which this *Topology* was last updated, in ISO-like format

name The name of the topology. This can only be letters, numbers, and dashes.

nodes An array of nodes in the *Topology*

cachegroup The name of a *Cache Group*

parents The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

973: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 13 Apr 2020 18:12:34
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ftNcDRjYCDMkQM+o/
    ↳szayKZriQZHGpcT0vNY0HpKgy88i0pXeEEeLGbUPh6LXtK7TvL76EgGECTzvCkcm+2LVA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 13 Apr 2020 17:12:34 GMT
Content-Length: 239

{
  "alerts": [
    {
      "text": "topology was created.",
      "level": "success"
    }
  ],
  "response": {
    "description": "This is my topology",
    "name": "my-topology",
    "nodes": [
      {
        "cachegroup": "edge1",
        "parents": [
          7
        ]
      },
      {
        "cachegroup": "edge2",
        "parents": [
          7,
          8
        ]
      },
      {
        "cachegroup": "edge3",
        "parents": [
          8,
          9
        ]
      }
    ]
  }
}

```

(continues on next page)

(continued from previous page)

```

    ]
  },
  {
    "cachegroup": "edge4",
    "parents": [
      9
    ]
  },
  {
    "cachegroup": "mid1",
    "parents": []
  },
  {
    "cachegroup": "mid2",
    "parents": [
      4
    ]
  },
  {
    "cachegroup": "mid3",
    "parents": [
      4
    ]
  },
  {
    "cachegroup": "mid4",
    "parents": [
      5
    ]
  },
  {
    "cachegroup": "mid5",
    "parents": [
      5,
      6
    ]
  },
  {
    "cachegroup": "mid6",
    "parents": [
      6
    ]
  }
],
"lastUpdated": "2020-04-13 17:12:34+00"
}

```

(continues on next page)

(continued from previous page)

```
}
```

PUT

Updates a specific *Topology*

Request Structure

Table 403: Request Query Parameters

Name	Required	Description
name	yes	The name of the <i>Topology</i> to be updated

description A short sentence that describes the *Topology*.

name The name of the *Topology*. This can only be letters, numbers, and dashes.

nodes An array of nodes in the *Topology*

cachegroup The name of a *Cache Group* with at least 1 server in it

parents The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

974: Request Example

```
PUT /api/3.0/topologies?name=my-topology HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 853
Content-Type: application/json

{
  "name": "my-topology",
  "description": "The description is updated, too",
  "nodes": [
    {
      "cachegroup": "edge1",
      "parents": [
        6
      ]
    },
  ],
}
```

(continues on next page)

(continued from previous page)

```
{
  "cachegroup": "edge2",
  "parents": [
    6,
    7
  ]
},
{
  "cachegroup": "edge3",
  "parents": [
    7,
    8
  ]
},
{
  "cachegroup": "edge4",
  "parents": [
    8
  ]
},
{
  "cachegroup": "mid2",
  "parents": []
},
{
  "cachegroup": "mid3",
  "parents": []
},
{
  "cachegroup": "mid4",
  "parents": [
    4
  ]
},
{
  "cachegroup": "mid5",
  "parents": [
    4,
    5
  ]
},
{
  "cachegroup": "mid6",
  "parents": [
    5
  ]
}
```

(continues on next page)

(continued from previous page)

```

    }
  ]
}
```

Response Structure

description A short sentence that describes the *Topology*.

lastUpdated The date and time at which this *Topology* was last updated, in ISO-like format

name The name of the *Topology*. This can only be letters, numbers, and dashes.

nodes An array of nodes in the *Topology*

cachegroup The name of a *Cache Group*

parents The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

975: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 13 Apr 2020 18:33:13.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: WV0tsoOVrEWcVjWM2TmT5DXy/
→a5Q0ygTZEQRhbKHHUmz9dgVLK1F5Joc9jtKA8gZu8/eM5+Tqqguh3mzrhAy/Q==
X-Server-Name: traffic_ops_golang/
Date: Mon, 13 Apr 2020 17:33:13 GMT
Content-Length: 237

{
  "alerts": [
    {
      "text": "topology was updated.",
      "level": "success"
    }
  ],
  "response": {
    "description": "The description is updated, too",
    "name": "my-topology",
```

(continues on next page)

(continued from previous page)

```

"nodes": [
  {
    "cachegroup": "edge1",
    "parents": [
      6
    ]
  },
  {
    "cachegroup": "edge2",
    "parents": [
      6,
      7
    ]
  },
  {
    "cachegroup": "edge3",
    "parents": [
      7,
      8
    ]
  },
  {
    "cachegroup": "edge4",
    "parents": [
      8
    ]
  },
  {
    "cachegroup": "mid2",
    "parents": []
  },
  {
    "cachegroup": "mid3",
    "parents": []
  },
  {
    "cachegroup": "mid4",
    "parents": [
      4
    ]
  },
  {
    "cachegroup": "mid5",
    "parents": [
      4,
      5
    ]
  }
]

```

(continues on next page)

(continued from previous page)

```

        ]
      },
      {
        "cachegroup": "mid6",
        "parents": [
          5
        ]
      }
    ],
    "lastUpdated": "2020-04-13 17:33:13+00"
  }
}

```

DELETE

Deletes a specific *Topology*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 404: Request Query Parameters

Name	Required	Description
name	yes	The name of the <i>Topology</i> to be deleted

976: Request Example

```
DELETE /api/3.0/topologies?name=my-topology HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

977: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 13 Apr 2020 18:35:32
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: yErJobzG9IA0khvqZQK+Yi7X4pFVvOqxn6PjrdzN5DnKVm/
    ↳K8Kka3REul1XmKJnMXVRY8RayoEVDm16mBFfe4Q==
X-Server-Name: traffic_ops_golang/
Date: Mon, 13 Apr 2020 17:35:32 GMT
Content-Length: 87

{
  "alerts": [
    {
      "text": "topology was deleted.",
      "level": "success"
    }
  ]
}
```

`topologies/{{name}}/queue_update`

POST

Queue or “dequeue” updates for all servers assigned to the *Cache Groups* in a specific *Topology*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 405: Request Path Parameters

Name	Description
name	The name of the <i>Topology</i> on which to queue or dequeue updates.

action One of “queue” or “dequeue” as appropriate

cdnId The integral, unique identifier for the CDN on which to (de)queue updates

978: Request Example

```
POST /api/3.0/topologies/demo1-top/queue_update HTTP/1.1
User-Agent: python-requests/2.24.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 28

{
  "action": "queue",
  "cdnId": 1
}
```

Response Structure

action The action processed, either “queue” or “dequeue”

cdnId The CDN ID on which *Queue Updates* was performed or cleared

topology The name of the *Topology* on which *Queue Updates* was performed or cleared

979: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 08 Sep 2020 17:35:42
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳nmu3TMVmlcHeEstLuiqPsEypNV2jcs5PyrqsqJKkexxb8N7qk84AWzTJWUpsfdVWrj/
    ↳JzRiCPGJS4hw0phQ==
X-Server-Name: traffic_ops_golang/
Date: Tue, 08 Sep 2020 16:35:42 GMT
Content-Length: 79

{
  "response": {
    "action": "queue",
    "cdnId": 1,
    "topology": "demo1-top"
  }
}

```

types

GET

Retrieves all of the *Types* of things configured in Traffic Ops. Yes, that is as specific as a description of a ‘type’ can be.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 406: Request Query Parameters

Name	Re-quired	Description
id	no	Return only the type that is identified by this integral, unique identifier
name	no	Return only types with this name
useInTable	no	Return only types that are used to identify the type of the object stored in the Traffic Ops database table that has this name

980: Request Structure

```
GET /api/3.0/types?name=TC_LOC HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- description** A short description of this type
- id** An integral, unique identifier for this type
- lastUpdated** The date and time at which this type was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of this type
- useInTable** The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type

981: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
    ↳p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 12 Dec 2018 22:59:22 GMT
```

(continues on next page)

(continued from previous page)

Content-Length: 168

```
{ "response": [
  {
    "id": 48,
    "lastUpdated": "2018-12-12 16:26:41+00",
    "name": "TC_LOC",
    "description": "Location for Traffic Control Component Servers",
    "useInTable": "cachegroup"
  }
]}
```

POST

Creates a type

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

description A short description of this type

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type.

Note: The only useInTable value that is allowed to be created dynamically is ‘server’

982: Request Structure

```
POST /api/3.0/type HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 67
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
{
  "name": "Example01",
  "description": "Example",
  "useInTable": "server"
}
```

Response Structure

description A short description of this type

id An integral, unique identifier for this type

lastUpdated The date and time at which this type was last updated, in *Traffic Ops's Custom Date/Time Format*

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type

983: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
  ↳p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 Feb 2020 18:58:41 GMT
Content-Length: 171

{
  "alerts": [
    {
      "text": "type was created.",
      "level": "success"
    }
  ],
  "response": [
    {
      "id": 3004,
      "lastUpdated": "2020-02-26 18:58:41+00",
```

(continues on next page)

(continued from previous page)

```

    "name": "Example01",
    "description": "Example"
    "useInTable": "server"
  }]
}
```

types/{ID}

PUT

Updates a type

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 407: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the type being updated

description A short description of this type

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type.

Note: Only types with useInTable set to ‘server’ are allowed to be updated.

984: Request Structure

```

PUT /api/3.0/type/3004 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 68
Content-Type: application/json

{
```

(continues on next page)

(continued from previous page)

```
"name": "Example01",
"description": "Example2",
"useInTable": "server"
}
```

Response Structure

description A short description of this type

id An integral, unique identifier for this type

lastUpdated The date and time at which this type was last updated, in *Traffic Ops's Custom Date/Time Format*

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type

985: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
→p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 Feb 2020 18:58:41 GMT
Content-Length: 172

{
  "alerts": [
    {
      "text": "type was updated.",
      "level": "success"
    }
  ],
  "response": [
    {
      "id": 3004,
      "lastUpdated": "2020-02-26 18:58:41+00",
      "name": "Example02",
```

(continues on next page)

(continued from previous page)

```
    "description": "Example"
    "useInTable": "server"
  }
}
```

DELETE

Deletes a type

- Auth. Required** Yes
- Roles Required** “admin” or “operations”
- Response Type** Object

Request Structure

Table 408: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the type being deleted

Note: Only types with useInTable set to “server” are allowed to be deleted.

986: Request Structure

```
DELETE /api/3.0/type/3004 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

987: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
→p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 Feb 2020 18:58:41 GMT
Content-Length: 84
```

```
{
  "alerts": [
    {
      "text": "type was deleted.",
      "level": "success"
    }
  ],
}
```

user/current

GET

Caution: As a username is needed to log in, any administrator or application must necessarily know the current username at any given time. Thus it's generally better to use the username query parameter of a GET request to *users* instead.

Retrieves the details of the authenticated user.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege *Role* assigned to this user
- rolename** The name of the highest-privilege *Role* assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the *Tenant* to which this user belongs
- tenantId** The integral, unique identifier of the *Tenant* to which this user belongs
- uid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user
- username** The user's username

988: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→HQwu9FxFyinXSVFK5+wpEhSxU60KbqXuokFbMZ30oerOoM5ZpWpglsHz7mRch8VAw0dzwsJzpPJivj07R:
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 15:14:45 GMT
Content-Length: 382

{ "response": {
    "username": "admin",
    "localUser": true,
    "addressLine1": null,
    "addressLine2": null,
    "city": null,
    "company": null,
    "country": null,
    "email": null,
    "fullName": "admin",
    "gid": null,
    "id": 2,
    "newUser": false,
    "phoneNumber": null,
    "postalCode": null,
    "publicSshKey": null,
    "role": 1,
    "rolename": "admin",
    "stateOrProvince": null,
    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "lastUpdated": "2018-12-12 16:26:32+00"
}}
```

PUT

Warning: Assuming the current user's integral, unique identifier is known, it's generally better to use the PUT method of the [users](#) instead.

Warning: Users that login via LDAP pass-back cannot be modified

Updates the date for the authenticated user.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

user The entire request must be inside a top-level “user” key for legacy reasons

addressLine1 The user's address - including street name and number

addressLine2 An additional address field for e.g. apartment number

city The name of the city wherein the user resides

company The name of the company for which the user works

confirmLocalPasswd An optional ‘confirm’ field in a new user's password specification. This has no known effect and in fact *doesn't even need to match localPasswd*

country The name of the country wherein the user resides

email The user's email address - cannot be an empty string¹. The given email is validated (circuitously) by [GitHub user asaskevich's regular expression](#). Note that it can't actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user's full name, e.g. “John Quincy Adams”

gid A legacy field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - please don't use this

¹ This field cannot be null.

id The user's integral, unique, identifier - this cannot be changed^{Page 1364, 1}

localPasswd Optionally, the user's password. This should never be given if it will not be changed. An empty string or null can be used to explicitly specify no change.

phoneNumber The user's phone number

postalCode The user's postal code

publicSshKey The user's public encryption key used for the SSH protocol

role The integral, unique identifier of the highest permission *Role* which will be permitted to the user - this cannot be altered from the user's current *Role*^{Page 1364, 1}

stateOrProvince The state or province in which the user resides

tenantId The integral, unique identifier of the *Tenant* to which the new user shall belong^{2Page 1364, 1}

uid A legacy field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - please don't use this

username The user's new username^{Page 1364, 1}

989: Request Example

```
PUT /api/3.0/user/current HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 465
Content-Type: application/json

{ "user": {
  "addressLine1": null,
  "addressLine2": null,
  "city": null,
  "company": null,
  "country": null,
  "email": "admin@infra.trafficops.ciab.test",
  "fullName": "admin",
  "gid": null,
  "id": 2,
  "phoneNumber": null,
```

(continues on next page)

² This endpoint respects tenancy; a user cannot assign itself to a *Tenant* that is not the same *Tenant* to which it was previously assigned or a descendant thereof.

(continued from previous page)

```

"postalCode": null,
"publicSshKey": null,
"role": 1,
"stateOrProvince": null,
"tenantId": 1,
"uid": null,
"username": "admin"
}}
```

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address validated (circuitously) by [GitHub user asaskevich's regular expression](#) . Note that it can't actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A legacy field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the [users/register](#) endpoint, this will be the date and time at which the registration email was sent - otherwise it will be null
- role** The integral, unique identifier of the highest-privilege *Role* assigned to this user
- rolename** The name of the highest-privilege *Role* assigned to this user
- stateOrProvince** The name of the state or province where this user resides

- tenant** The name of the *Tenant* to which this user belongs
- tenantId** The integral, unique identifier of the *Tenant* to which this user belongs
- uid** A legacy field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user
- username** The user's username

990: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Date: Thu, 13 Dec 2018 21:05:49 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: sHFqZQ4Cv7IIWaIejoAvM2Fr/HSupcX3D16KU/
    ↳etjw+4jcK9EME3Bq5ohLC+eQ52BDCKW2Ra+AC3TfFtworJww==
Content-Length: 478

{ "alerts": [
  {
    "text": "User profile was successfully updated",
    "level": "success"
  }
],
"response": {
  "addressLine1": null,
  "addressLine2": null,
  "city": null,
  "company": null,
  "country": null,
  "email": "admin@infra.trafficops.ciab.test",
  "fullName": null,
  "gid": null,
  "id": 2,
  "lastUpdated": "2019-10-08 20:14:25+00",
  "newUser": false,
  "phoneNumber": null,
  "postalCode": null,
  "publicSshKey": null,
  "registrationSent": null,

```

(continues on next page)

(continued from previous page)

```

    "role": 1,
    "roleName": "admin",
    "stateOrProvince": null,
    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "username": "admin"
  }}

```

user/login

POST

Authentication of a user using username and password. Traffic Ops will send back a session cookie.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

p Password

u Username

991: Request Example

```

POST /api/3.0/user/login HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 26
Content-Type: application/json

{
  "u": "admin",
  "p": "twelve"
}

```

Response Structure

992: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳UdO6T3tMNctnVusDXzRjVwwYOnD7jmnBzPEB9PvOt2bHajTv3SKTPiIZjDzvhU6EX4p+JoG4fA5wlhgxp
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 15:21:33 GMT
Content-Length: 65

{ "alerts": [
  {
    "text": "Successfully logged in.",
    "level": "success"
  }
]}
```

user/login/oauth

POST

Authentication of a user by exchanging a code for an encrypted JSON Web Token from an OAuth service. Traffic Ops will POST to the `authCodeTokenUrl` to exchange the code for an encrypted JSON Web Token. It will then decode and validate the token, validate the key set domain, and send back a session cookie.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

authCodeTokenUrl URL for code-to-token conversion

code Code

clientId Client Id

redirectUri Redirect URI

993: Request Example

```
POST /api/3.0/user/login/oauth HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 26
Content-Type: application/json

{
  "authCodeTokenUrl": "https://url-to-convert-code-to-token.example.
  ↪com",
  "code": "AbCd123",
  "clientId": "oauthClientId",
  "redirectUri": "https://traffic-portal.example.com/sso"
}
```

Response Structure

994: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type, ↪
  ↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54. ↪
  ↪GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ↪
  ↪Ud06T3tMNctnVusDXzRjVwwYOnD7jmnBzPEB9PvOt2bHajTv3SKTPiIZjDzvhU6EX4p+JoG4fA5wlhgxp
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 15:21:33 GMT
Content-Length: 65

{ "alerts": [
```

(continues on next page)

(continued from previous page)

```
{
  "text": "Successfully logged in.",
  "level": "success"
}
]}
```

user/login/token

POST

Authentication of a user using a token. Normally, the token is obtained via a call to either *user/reset_password* or *users/register*.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

t A UUID generated for the user.

Implementation Detail

Though not strictly necessary for authentication provided direct database access, the tokens generated for use with this endpoint are compliant with [RFC 4122](#).

995: Request Example

```
POST /api/3.0/user/login/token HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 44
Content-Type: application/json

{
  "t": "18EE200C-FF24-11E8-BF01-870C776752A3"
}
```

Response Structure

996: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: FuS3TkVosxHtpxRGMJ2on+WnFdYTNSPjxz/Gh1iT4UCJ2/
    ↳P0twUbAGQ3tTx9EfGiAzg9CNQiVUFGnYjJZ6NCpg==
X-Server-Name: traffic_ops_golang/
Date: Fri, 20 Sep 2019 15:02:43 GMT
Content-Length: 66

{ "alerts": [
  {
    "text": "Successfully logged in.",
    "level": "success"
  }
]}
```

user/logout

POST

User logout. Invalidates the session cookie of the currently logged-in user.

Auth. Required Yes

Roles Required None

Response Type undefined

Request Structure

No parameters available

Response Structure

997: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 21:25:36 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 6KEdr1ZC512zk0l03KwvQE0L7qrJ/
    ↳+ek6ztymkYy9p8gdPUyYyzGEAJ/Ldb8GY0UBFYmgqeZ3yWHvTcEsOQMiw==
Content-Length: 61

{ "alerts": [
  {
    "level": "success",
    "text": "You are logged out."
  }
]}
```

user/reset_password

POST

Sends an email to reset a user's password.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

email The email address of the user to initiate password reset

998: Request Example

```
POST /api/3.0/user/reset_password HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 35
Content-Type: application/json

{
  "email": "test@example.com"
}
```

Response Structure

999: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 22:11:53 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→lKWwVYbgKklk7bljnQJZwWV5bljIk+GkooD6SAC3CSexVKvfbL9dgL5iBc/
→BNNRk2pIU5I/1GglcdLrXsF1ZA==
Content-Length: 109

{ "alerts": [
  {
    "level": "success",
    "text": "Successfully sent password reset to email
→'test@example.com'"
  }
]}
```

(continues on next page)

(continued from previous page)

```
  ]}
```

users

GET

Retrieves all requested users.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 409: Request Query Parameters

Name	Re-quired	Description
id	no	Return only the user identified by this integral, unique identifier
tenant	no	Return only users belonging to the <i>Tenant</i> identified by tenant name
role	no	Return only users belonging to the <i>Role</i> identified by role name
username	no	Return only the user with this username
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the ⁿ th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1000: Request Example

```
GET /api/3.0/users?username=admin HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

¹ While no roles are required, this endpoint does respect tenancy. A user will only be able to see, create, delete or modify other users belonging to the same tenant, or its descendants.

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege role assigned to this user
- rolename** The name of the highest-privilege role assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the tenant to which this user belongs
- tenantId** The integral, unique identifier of the tenant to which this user belongs
- uid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always `null`
- username** The user's username

1001: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳YBJLN8NbOxOvECe1RGtcwCzIPDhyhLpW56nTJHQM5WI2WUDe2mAKREpaEE72nzrfBliq1GABwJlxsxq20dl
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 01:03:53 GMT
Content-Length: 391

{ "response": [
  {
    "username": "admin",
    "registrationSent": null,
    "addressLine1": null,
    "addressLine2": null,
    "city": null,
    "company": null,
    "country": null,
    "email": null,
    "fullName": null,
    "gid": null,
    "id": 2,
    "newUser": false,
    "phoneNumber": null,
    "postalCode": null,
    "publicSshKey": null,
    "role": 1,
    "rolename": "admin",
    "stateOrProvince": null,
    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "lastUpdated": "2018-12-12 16:26:32+00"
  }
]}

```

POST

Creates a new user.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 1467, 1}

Response Type Object

Request Structure

addressLine1 An optional field which should contain the user’s address - including street name and number

addressLine2 An optional field which should contain an additional address field for e.g. apartment number

city An optional field which should contain the name of the city wherein the user resides

company An optional field which should contain the name of the company for which the user works

confirmLocalPasswd The ‘confirm’ field in a new user’s password specification - must match `localPasswd`

country An optional field which should contain the name of the country wherein the user resides

email The user’s email address The given email is validated (circuitously) by [GitHub user asaskevich’s regular expression](#) . Note that it can’t actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user’s full name, e.g. “John Quincy Adams”

localPasswd The user’s password

newUser An optional meta field with no apparent purpose - don’t use this

phoneNumber An optional field which should contain the user’s phone number

postalCode An optional field which should contain the user’s postal code

publicSshKey An optional field which should contain the user’s public encryption key used for the SSH protocol

role The number that corresponds to the highest permission role which will be permitted to the user

stateOrProvince An optional field which should contain the name of the state or province in which the user resides

tenantId The integral, unique identifier of the tenant to which the new user shall belong

Note: This field is optional if and only if tenancy is not enabled in Traffic Control

username The new user's username

1002: Request Example

```
POST /api/3.0/users HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 304
Content-Type: application/json

{
  "username": "mike",
  "addressLine1": "22 Mike Wazowski You've Got Your Life Back Lane",
  "city": "Monstropolis",
  "company": "Monsters Inc.",
  "email": "mwazowski@minc.biz",
  "fullName": "Mike Wazowski",
  "localPasswd": "BFFsully",
  "confirmLocalPasswd": "BFFsully",
  "newUser": true,
  "role": 1,
  "tenantId": 1
}
```

Response Structure

addressLine1 The user's address - including street name and number

addressLine2 An additional address field for e.g. apartment number

city The name of the city wherein the user resides

company The name of the company for which the user works

country The name of the country wherein the user resides

email The user's email address

fullName The user's full name, e.g. "John Quincy Adams"

gid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always null

id An integral, unique identifier for this user

- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually null unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be null
- role** The integral, unique identifier of the highest-privilege role assigned to this user
- rolename** The name of the highest-privilege role assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the tenant to which this user belongs
- tenantId** The integral, unique identifier of the tenant to which this user belongs
- uid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always null
- username** The user's username

1003: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 02:28:27 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→vDqbaMvgeeoIds1czqvIWlyDG8WLnCCJdF14Ub05nsE+oJOakkyeZ8odf4d0Zjtqpk01hoVo14H2tjuWP
Content-Length: 520

{ "alerts": [
  {
    "level": "success",
```

(continues on next page)

(continued from previous page)

```

        "text": "User creation was successful."
    }
],
"response": {
    "registrationSent": null,
    "email": "mwazowski@minc.biz",
    "tenantId": 1,
    "city": "Monstropolis",
    "tenant": "root",
    "id": 8,
    "company": null,
    "rolename": "admin",
    "phoneNumber": null,
    "country": null,
    "fullName": "Mike Wazowski",
    "publicSshKey": null,
    "uid": null,
    "stateOrProvince": null,
    "lastUpdated": null,
    "username": "mike",
    "newUser": false,
    "addressLine2": null,
    "role": 1,
    "addressLine1": "22 Mike Wazowski You've Got Your Life Back Lane",
    "postalCode": null,
    "gid": null
}}

```

users/{{ID}}

GET

Retrieves a specific user.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 410: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the user to be retrieved

1004: Request Example

```
GET /api/3.0/users/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege role assigned to this user

rolename The name of the highest-privilege role assigned to this user

stateOrProvince The name of the state or province where this user resides

tenant The name of the tenant to which this user belongs

tenantId The integral, unique identifier of the tenant to which this user belongs

uid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always null

username The user's username

1005: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳9vqUmt8fWEuDb+9LQJ4sGbbF4Z0a7uNyBNSWhyzAi3fBUZ5mGhd4Jx5IuSlEqiLZnYeViJJL8mpRortkH
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 17:46:00 GMT
Content-Length: 588

{ "response": [
  {
    "username": "admin",
    "registrationSent": null,
    "addressLine1": "not a real address",
    "addressLine2": "not a real address either",
    "city": "not a real city",
    "company": "not a real company",
    "country": "not a real country",
    "email": "not@real.email",
    "fullName": "Not a real Full Name",
    "gid": null,
    "id": 2,
    "newUser": false,
    "phoneNumber": "not a real phone number",
    "postalCode": "not a real postal code",
    "publicSshKey": "not a real ssh key",
    "role": 1,
    "rolename": "admin",
    "stateOrProvince": "not a real state or province",
```

(continues on next page)

(continued from previous page)

```

    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "lastUpdated": "2018-12-13 17:24:23+00"
  }
}]

```

PUT

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 411: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the user to be modified

addressLine1 An optional field which should contain the user’s address - including street name and number

addressLine2 An optional field which should contain an additional address field for e.g. apartment number

city An optional field which should contain the name of the city wherein the user resides

company An optional field which should contain the name of the company for which the user works

confirmLocalPasswd The ‘confirm’ field in a new user’s password specification - must match `localPasswd`

country An optional field which should contain the name of the country wherein the user resides

email The user’s email address The given email is validated (circuitously) by [GitHub user asaskevich’s regular expression](#) . Note that it can’t actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user’s full name, e.g. “John Quincy Adams”

localPasswd The user’s password

newUser An optional meta field with no apparent purpose - don’t use this

- phoneNumber** An optional field which should contain the user's phone number
- postalCode** An optional field which should contain the user's postal code
- publicSshKey** An optional field which should contain the user's public encryption key used for the SSH protocol
- role** The number that corresponds to the highest permission role which will be permitted to the user
- stateOrProvince** An optional field which should contain the name of the state or province in which the user resides
- tenantId** The integral, unique identifier of the tenant to which the new user shall belong

Note: This field is optional if and only if tenancy is not enabled in Traffic Control

username The new user's username

1006: Request Structure

```
PUT /api/3.0/users/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 458
Content-Type: application/json

{
  "addressLine1": "not a real address",
  "addressLine2": "not a real address either",
  "city": "not a real city",
  "company": "not a real company",
  "country": "not a real country",
  "email": "not@real.email",
  "fullName": "Not a real fullName",
  "phoneNumber": "not a real phone number",
  "postalCode": "not a real postal code",
  "publicSshKey": "not a real ssh key",
  "stateOrProvince": "not a real state or province",
  "tenantId": 1,
  "role": 1,
  "username": "admin"
}
```

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege role assigned to this user
- rolename** The name of the highest-privilege role assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the tenant to which this user belongs
- tenantId** The integral, unique identifier of the tenant to which this user belongs
- uid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always `null`
- username** The user's username

1007: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 17:24:23 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: QKvGSIwSdreMI/OdgWv9WQfI/
→C1JbXSoQGospTGfCVUJ32XNWMhmREGzWojWsilW8os8b14TGYeyMLUWunf2Ug==
Content-Length: 661

{ "alerts": [
  {
    "level": "success",
    "text": "User update was successful."
  }
],
"response": {
  "registrationSent": null,
  "email": "not@real.email",
  "tenantId": 1,
  "city": "not a real city",
  "tenant": "root",
  "id": 2,
  "company": "not a real company",
  "rolename": "admin",
  "phoneNumber": "not a real phone number",
  "country": "not a real country",
  "fullName": "Not a real Full Name",
  "publicSshKey": "not a real ssh key",
  "uid": null,
  "stateOrProvince": "not a real state or province",
  "lastUpdated": "2018-12-12 16:26:32.821187+00",
  "username": "admin",
  "newUser": false,
  "addressLine2": "not a real address either",
  "role": 1,
  "addressLine1": "not a real address",
  "postalCode": "not a real postal code",
  "gid": null
}}
```

users/register

POST

Register a user and send registration email.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

email Email address of the new user The given email is validated (circuitously) by [GitHub user asaskevich's regular expression](#) . Note that it can't actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

role The integral, unique identifier of the highest permissions *Role* which will be afforded to the new user. It restricts the allowed values to identifiers for *Roles* with at most the same permissions level as the requesting user.

tenantId A field containing the integral, unique identifier of the *Tenant* to which the new user will belong. It restricts the allowed values to identifiers for *Tenants* within the requesting user's *Tenant*'s permissions.

1008: Request Example

```
POST /api/3.0/users/register HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 59
Content-Type: application/json

{
  "email": "test@example.com",
  "role": 3,
  "tenantId": 1
}
```

Response Structure

1009: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 22:03:22 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→yvf++0qxvu3u0IAYbWLUgJKxZ4T60Mi5H9eGTxrKLxnRsHw0PdDIrThbTnWtATBkak4vU/
→dPHLLXKW85LUTEWg==
Content-Length: 160

{ "alerts": [
  {
    "level": "success",
    "text": "Sent user registration to test@example.com with the
→following permissions [ role: read-only | tenant: root ]"
  }
]}
```

`vault/bucket/{{bucket}}/key/{{key}}/values`

Retrieves the `object` stored under a given `key` from a given `bucket` in *Traffic Vault*.

Deprecated since version ATCv6.

GET

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 412: Request Path Parameters

Name	Description
bucket	The bucket that the key is stored under
key	The key that the object is stored under

1010: Request Example

```
GET /api/3.0/vault/bucket/ssl/key/demo1-latest/values HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

The response structure varies according to what is stored. Top-level keys will always be String type, but the values can be any type.

1011: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 23:29:27 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: LUq4+MUCgIqxBWqbuA/
Pbsdq5Qfs7vPUcZ0Cu2Fc0UyP0X8xXit3BJrd0LA+dSSJ3tSQ7Qij1+0ahzuouuLT7Q==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 22:29:27 GMT
Transfer-Encoding: chunked

{
  "alerts": [
    {
      "text": "This endpoint is deprecated, and will be removed in the future",
      "level": "warning"
    }
  ],
  "response": {
    "cdn": "CDN-in-a-Box",
    "certificate": {
      "crt": "...",
      "csr": "...",
      "key": "..."
    },
    "deliveryservice": "demo1",
    "hostname": "/*.demo1.mycdn.ciab.test",
    "key": "demo1",
    "version": 1
  }
}
```

vault/ping

GET

Pings Traffic Vault to retrieve status.

Auth. Required Yes

Roles Required “read-only”

Response Type Object

Request Structure

No parameters available.

Response Properties

status The status returned from the ping request to the Traffic Vault server

server The Traffic Vault server that was pinged

1012: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 15:37:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳z9P1NkxGebPncUhaChDHtYKYI+XVZfhE6Y84TuwoASZFIMfISELwADLpvpPTN+wnnzBfREksLYn+0313Q
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 14:37:55 GMT
Content-Length: 90

{ "response":
  {
    "status": "OK",
    "server": "trafficvault.infra.ciab.test:8087"
  }
}
```

5.1.7 API V4 Routes

API routes available in version 4.

Danger: API version 4 is *unstable*, meaning that breaking changes can occur at any time. Use at your own peril!

about

GET

Returns info about the Traffic Ops build that is currently running, generated at startup. The output will be the same until the Traffic Ops *version changes*.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

1013: Request Example

```
GET /api/4.0/about HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

commitHash The [Git](#) commit hash that Traffic Ops was built at.

commits The number of commits in the branch of the commit that Traffic Ops was built at, including that commit. Calculated by running `git rev-list HEAD | wc -l`.

goVersion The version of [Go](#) that was used to build Traffic Ops.

release The major version of CentOS or Red Hat Enterprise Linux that the build environment was running.

name The human-readable name of the [RPM](#) file.

RPMVersion The entire name of the RPM file, excluding the file extension.

Version The version of ATC that this version of Traffic Control belongs to.

1014: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 19:35:28.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→7SVQsddCUVRs+sineziRGR60yMli7XLZbjxyMQgW6E506bh5thM0uttPFT7aJckDcgT45PlhexycwlApO
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 18:35:28 GMT
Content-Length: 145
```

```
{
  "commitHash": "1c9a2e9c",
  "commits": "10555",
  "goVersion": "go1.11.13",
  "release": "el7",
  "name": "traffic_ops",
  "RPMVersion": "traffic_ops-4.0.0-10555.1c9a2e9c.el7",
  "Version": "4.0.0"
}
```

acme_accounts

New in version 3.1.

GET

Gets information for all *ACME Account* s.

Auth. Required Yes

Roles Required “admin”

Response Type Array

Request Structure

No parameters available

Response Structure

- email** The email connected to the *ACME Account*.
- privateKey** The private key connected to the *ACME Account*.
- uri** The URI for the *ACME Account*. Differs per provider.
- provider** The ACME provider.

1015: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": [
  {
    "email": "sample@example.com",
    "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----END RSA PRIVATE KEY-----\n",
    "uri": "https://acme.example.com/acct/1",
    "provider": "Lets Encrypt"
  }
]}
```

POST

Creates a new *ACME Account*.

- Auth. Required** Yes
- Roles Required** “admin”
- Response Type** Object

Request Structure

The request body must be a single *ACME Account* object with the following keys:

- email** The email connected to the *ACME Account*.
- privateKey** The private key connected to the *ACME Account*.
- uri** The URI for the *ACME Account*. Differs per provider.
- provider** The ACME provider.

1016: Request Example

```
POST /api/4.0/acme_accounts HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 181
Content-Type: application/json

{
  "email": "sample@example.com",
  "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----
→END RSA PRIVATE KEY-----\n",
  "uri": "https://acme.example.com/acct/1",
  "provider": "Lets Encrypt"
}
```

Response Structure

- email** The email connected to the *ACME Account*.
- privateKey** The private key connected to the *ACME Account*.
- uri** The URI for the *ACME Account*. Differs per provider.
- provider** The ACME provider.

1017: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 10 Dec 2020 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→eQrl48zWids0kDpfCYmntYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
→Cfh2X9i3G+MQ36eH95gukJq0BOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:18:21 GMT
Content-Length: 253

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

        "text": "Acme account created",
        "level": "success"
    }
],
"response": {
    "email": "sample@example.com",
    "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----
→END RSA PRIVATE KEY-----\n",
    "uri": "https://acme.example.com/acct/1",
    "provider": "Lets Encrypt"
}}

```

PUT

Updates an existing *ACME Account*.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

The request body must be a single *ACME Account* object with the following keys:

email The email connected to the *ACME Account*.

privateKey The private key connected to the *ACME Account*.

uri The URI for the *ACME Account*. Differs per provider.

provider The ACME provider.

1018: Request Example

```

PUT /api/4.0/acme_accounts HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 181
Content-Type: application/json

{
    "email": "sample@example.com",
    "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----
→END RSA PRIVATE KEY-----\n",

```

(continues on next page)

(continued from previous page)

```
"uri": "https://acme.example.com/acct/1",
"provider": "Lets Encrypt"
}
```

Response Structure

- email** The email connected to the *ACME Account*.
- privateKey** The private key connected to the *ACME Account*.
- uri** The URI for the *ACME Account*. Differs per provider.
- provider** The ACME provider.

1019: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 10 Dec 2020 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
    ↳Cfh2X9i3G+MQ36eH95gukJqOBOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:18:21 GMT
Content-Length: 253

{ "alerts": [
  {
    "text": "Acme account updated",
    "level": "success"
  }
],
"response": {
  "email": "sample@example.com",
  "privateKey": "-----BEGIN RSA PRIVATE KEY-----\nSampleKey\n-----
    ↳END RSA PRIVATE KEY-----\n",
  "uri": "https://acme.example.com/acct/1",
  "provider": "Lets Encrypt"
}}
```

`acme_accounts/{{provider}}/{{email}}`

New in version 3.1.

DELETE

Delete *ACME Account* information.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 413: Request Path Parameters

Name	Description
provider	The ACME provider for the account to be deleted
email	The email used in the <i>ACME Account</i> to be deleted

Response Structure

1020: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 10 Dec 2020 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: rGD2sOMHYF0sga1zuTytyLHCUkkc3ZwQRKvZ/
    ↳HuPz0bOP4WztKTOVXB4uhs3iJqBg9zRB2TucMxONHN+3/yShQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 10 Dec 2020 14:24:34 GMT
Content-Length: 60

{"alerts": [
  {
    "text": "Acme account deleted",
    "level": "success"
  }
]}
```

(continues on next page)

(continued from previous page)

```
}
[]}
```

acme_accounts/providers

New in version 4.0.

GET

Gets a list of all ACME providers set up in *cdn.conf* and Let's Encrypt.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

No parameters available

Response Structure

1021: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": [
    "CertAuth1",
    "CertAuth2",
    "CertAuth3"
]}
```

acme_autorenew

POST

Generates SSL certificates and private keys for all *Delivery Services* that have certificates expiring within the configured time. This uses:abbr:ACME (*Automatic Certificate Management Environment*) or Let's Encrypt depending on the certificate.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

No parameters available

Response Structure

1022: Response Example

```
HTTP/1.1 202 Accepted
Content-Type: application/json

{ "alerts": [
  {
    "text": "Beginning async call to renew certificates. This may
    ↳take a few minutes. Status updates can be found here: /api/4.0/async_
    ↳status/1",
    "level": "success"
  }
]}
```

api_capabilities

Deals with the capabilities that may be associated with API endpoints and methods. These capabilities are assigned to *Roles*, of which a user may have one or more. Capabilities support “wildcarding” or “globbing” using asterisks to group multiple routes into a single capability

GET

Get all API-capability mappings.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 414: Request Query Parameters

Name	Required	Type	Description
capability	no	string	Capability name

1023: Request Example

```
GET /api/4.0/api_capabilities?capability=types-write HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

capability Capability name

httpMethod An HTTP request method, practically one of:

- GET
- POST
- PUT
- PATCH
- DELETE

httpRoute The request route for which this capability applies - relative to the Traffic Ops server's URL

id An integer which uniquely identifies this capability

lastUpdated The time at which this capability was last updated, in *Traffic Ops's Custom Date/Time Format*

1024: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 01 Nov 2018 14:45:24 GMT
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: wptErtIop/AfTTQ+1MZdA2YpPXE0uLFfrPQvvaHq0/
→uX5fRruOVYW+7p8JTTrtH1xg1WN+x6FnjQnSHuWwcpyJg==
Content-Length: 393

{ "response": [
  {
    "httpMethod": "POST",
    "lastUpdated": "2018-11-01 14:10:22.794114+00",
    "httpRoute": "types",
    "id": 261,
    "capability": "types-write"
  },
  {
    "httpMethod": "PUT",
    "lastUpdated": "2018-11-01 14:10:22.795917+00",
    "httpRoute": "types/*",
    "id": 262,
    "capability": "types-write"
  },
  {
    "httpMethod": "DELETE",
    "lastUpdated": "2018-11-01 14:10:22.799748+00",
    "httpRoute": "types/*",
    "id": 263,
    "capability": "types-write"
  }
]}

```

asns

See also:

[The Autonomous System Wikipedia page](#) for an explanation of what an ASN actually is.

GET

List all ASNs.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 415: Request Query Parameters

Parameter	Required	Description
cacheGroup	no	The <i>ID</i> of a <i>Cache Group</i> - only ASNs for this <i>Cache Group</i> will be returned.
id	no	The integral, unique identifier of the desired ASN-to- <i>Cache Group</i> association
orderBy	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

1025: Request Example

```
GET /api/4.0/asns HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cachegroup** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cachegroupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

1026: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 22:51:14
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳F2NmDbTpXqrIQDX7IBKH9+1drTL4XedSfJv6klMgLEZwbLCkddIXuSLpmgVCID6kTVqy3fTKjZS3U+HJ
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 21:51:14 GMT
Content-Length: 128

{ "response": [
  {
    "asn": 1,
    "cachegroup": "TRAFFIC_ANALYTICS",
    "cachegroupId": 1,
```

(continues on next page)

(continued from previous page)

```

        "id": 1,
        "lastUpdated": "2019-12-02 21:49:08+00"
    }
}]

```

POST

Creates a new ASN.

Note: There cannot be two different ASN object with the same `asn`. An ASN may only belong to one cachegroup, but a cachegroup can have zero or more ASNs.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

asn The value of the new ASN

cachegroup An optional field which, if present, is a string that specifies the *Name* of a *Cache Group* to which this ASN will be assigned

Note: While this endpoint accepts the `cachegroup` field, sending this in the request payload has no effect except that the response will (erroneously) name the *Cache Group* to which the ASN was assigned. Any subsequent requests will reveal that, in fact, the *Cache Group* is set entirely by the `cachegroupId` field, and so the actual *Name* may differ from what was in the request.

cachegroupId An integer that is the *ID* of a *Cache Group* to which this ASN will be assigned

1027: Request Example

```

POST /api/4.0/asns HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 29

```

(continues on next page)

(continued from previous page)

```
{"asn": 1, "cachegroupId": 1}
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cachegroup** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cachegroupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

1028: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 22:49:08
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mx8b2GTyojz4QtMxXCmoQyZogCB504vs0yv6WGly4dwM81W3XiejWNuUwchRBYyi8QHawsMZ3DaiGGfQi
    ↳8Giw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 21:49:08 GMT
Content-Length: 150

{ "alerts": [
  {
    "text": "asn was created.",
    "level": "success"
  }
],
"response": {
  "asn": 1,
  "cachegroup": null,
```

(continues on next page)

(continued from previous page)

```
"cachegroupId": 1,  
"id": 1,  
"lastUpdated": "2019-12-02 21:49:08+00"  
}}
```

PUT

Updates an existing ASN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

asn The value of the new ASN.

cachegroup A string that specifies the *Name* of a *Cache Group* to which this ASN will be assigned. If you do not pass this field, the cachegroup will be null.

cachegroupId The integral, unique identifier of the status of the *Cache Group*.

1029: Request Example

```
PUT /api/4.0/asns?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 53

{
  "asn": 1,
  "cachegroup": "TRAFFIC_OPS",
  "cachegroupId": 2
}
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cachegroup** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cachegroupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

1030: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 07:21:10
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳MjvwJg6AFbdqGPlAhK+2pfiN+VFjzgeNnhXoMVbh6+fRQYKeej6CCj3x09hw0l4uhp9d9RySrE/
  ↳CQ3+L1b2VGQ==
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

Date: Tue, 25 Feb 2020 06:21:10 GMT

Content-Length: 164

```
{
  "alerts": [
    {
      "text": "asn was updated.",
      "level": "success"
    }
  ],
  "response": {
    "asn": 1,
    "cachegroup": "TRAFFIC_OPS",
    "cachegroupId": 2,
    "id": 1,
    "lastUpdated": "2020-02-25 06:21:10+00"
  }
}
```

DELETE

Deletes an existing ASN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

1031: Request Example

```
DELETE /api/4.0/asns?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

1032: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 08:27:33
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Woz8NSHIYVpX4V5X4xZWZIX1hvGL2uian7nUhjZ8F23Nb9RWQRMig/cc+1vXEzkT/
    ↳ehKV9t11FKRLX+avSae0g==
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 07:27:33 GMT
Content-Length: 83

{
  "alerts": [
    {
      "text": "asn was deleted.",
      "level": "success"
    }
  ]
}
```

`asns/{{id}}`

See also:

The [Autonomous System Wikipedia page](#) for an explanation of what an ASN actually is.

PUT

Allows user to edit an existing ASN-to-*Cache Group* association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

asn The new ASN which will be associated with the identified *Cache Group* - must not conflict with existing associations

cachegroup An optional field which, if present, is a string that specifies the *Name* of a *Cache Group* to which this ASN will be assigned

Note: While this endpoint accepts the `cachegroup` field, sending this in the request payload has no effect except that the response will (erroneously) name the *Cache Group* to which the ASN was assigned. Any subsequent requests will reveal that, in fact, the *Cache Group* is set entirely by the `cachegroupId` field, and so the actual *Name* may differ from what was in the request.

cachegroupId An integer that is the *ID* of a *Cache Group* to which this ASN will be assigned - must not conflict with existing associations

Table 416: Request Path Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the desired ASN-to- <i>Cache Group</i> association

1033: Request Example

```
PUT /api/4.0/asns/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

(continues on next page)

(continued from previous page)

```
Content-Length: 29
Content-Type: application/x-www-form-urlencoded

{"asn": 2, "cachegroupId": 1}
```

Response Structure

- asn** An ASN as specified by IANA for identifying a service provider
- cachegroup** A string that is the *Name* of the *Cache Group* that is associated with this ASN
- cachegroupId** An integer that is the *ID* of the *Cache Group* that is associated with this ASN
- id** An integral, unique identifier for this association between an ASN and a *Cache Group*
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*

1034: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: /83P4LJVsrQx9BKHfxo5pbhQm1B4o3a9v3PpkspyOJcpNx1S/
→GJhCPpiANBki547sbY+0vTq76IriHZ4GYp8bA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 08 Nov 2018 14:37:39 GMT
Content-Length: 160

{ "alerts": [
  {
    "text": "asn was updated.",
    "level": "success"
  }
],
"response": {
  "asn": 2,
  "cachegroup": null,
```

(continues on next page)

(continued from previous page)

```
"cachegroupId": 1,
"id": 1,
"lastUpdated": "2018-11-08 14:37:39+00"
}}
```

DELETE

Deletes an association between an ASN and a *Cache Group*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 417: Request Path Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the desired ASN-to- <i>Cache Group</i> as- sociation

1035: Request Example

```
DELETE /api/4.0/asns/1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

1036: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 23:06:24.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→6t3WA+DOcfPJB5UnvDpzEVx5ySfmJgEV9wgk071U5k32L1VXpxcaTdDVLNGgDD19sdNftmYnKXf5jpfWU
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 22:06:24 GMT
Content-Length: 81

{ "alerts": [
  {
    "text": "asn was deleted.",
    "level": "success"
  }
]}
```

`async_status/{id}`

GET

Returns a status update for an asynchronous task.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 418: Request Path Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier for the desired asynchronous job status. This will be provided when the asynchronous job is started.

Response Structure

- id** The integral, unique identifier for the asynchronous job status.
- status** The status of the asynchronous job. This will be *PENDING*, *SUCCEEDED*, or *FAILED*.
- start_time** The time the asynchronous job was started.
- end_time** The time the asynchronous job completed. This will be *null* if it has not completed yet.
- message** A message about the job status.

1037: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response":
  {
    "id":1,
    "status":"PENDING",
    "start_time":"2021-02-18T17:13:56.352261Z",
    "end_time":null,
    "message":"Async job has started."
  }
}
```

cache_stats

Retrieves detailed, aggregated statistics for caches in a specific CDN.

See also:

This gives an aggregate of statistics for *all caches* within a particular CDN and time range. For statistics basic statistics from all caches regardless of CDN and at the current time, use [caches/stats](#).

GET

Retrieves statistics about the caches within the CDN

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 419: Request Query Parameters

Name	Required	Description
cdnName	yes	The name of a CDN. Results will represent caches within this CDN
end-Date	yes	The date and time until which statistics shall be aggregated in RFC 3339 format (with or without sub-second precision), the number of nanoseconds since the Unix Epoch, or in the same, proprietary format as the <code>lastUpdated</code> fields prevalent throughout the Traffic Ops API
exclude	no	Either “series” to omit the data series from the result, or “summary” to omit the summary data from the result - directly corresponds to fields in the Response Structure
interval	no	Specifies the interval within which data will be “bucketed”; e.g. when requesting data from 2019-07-25T00:00:00Z to 2019-07-25T23:59:59Z with an interval of “1m”, the resulting data series (assuming it is not excluded) should contain $24 \frac{\text{hours}}{\text{day}} \times 60 \frac{\text{minutes}}{\text{hour}} \times 1 \text{day} \times 1 \frac{\text{minute}}{\text{datapoint}} = 1440$ data points The allowed values for this parameter are valid InfluxQL duration literal strings matching <code>^d+[mhdw]\$</code>
limit	no	A natural number indicating the maximum amount of data points should be returned in the <code>series</code> object
metric-Type	yes	The metric type being reported - one of: ‘connections’, ‘bandwidth’, ‘maxkbits’
offset	no	A natural number of data points to drop from the beginning of the returned data set
orderby	no	Though one struggles to imagine why, this can be used to specify “time” to sort data points by their “time” (which is the default behavior)
start-Date	yes	The date and time from which statistics shall be aggregated in RFC 3339 format (with or without sub-second precision), the number of nanoseconds since the Unix Epoch, or in the same, proprietary format as the <code>lastUpdated</code> fields prevalent throughout the Traffic Ops API

1038: Request Example

```
GET /api/4.0/cache_stats?cdnName=CDN&endDate=2019-10-28T20:49:00Z&
→metricType=bandwidth&startDate=2019-10-28T20:45:00Z HTTP/1.1
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: application/json;timestamp=unix, application/json;
→timestamp=rfc;q=0.9, application/json;q=0.8, */*;q=0.7
Connection: keep-alive
Cookie: mojolicious=...
```

Content Format

It's important to note in *Request Example* the use of a complex “Accept” header. This endpoint accepts two special media types in the “Accept” header that instruct it on how to format the timestamps associated with the returned data. Specifically, Traffic Ops will recognize the special, optional, non-standard parameter of *application/json: timestamp*. The values of this parameter are restricted to one of

rfc Returned timestamps will be formatted according to **RFC 3339** (no sub-second precision).

unix Returned timestamps will be formatted as the number of nanoseconds since the Unix Epoch (midnight on January 1st 1970 UTC).

Implementation Detail

The endpoint passes back nanoseconds, specifically, because that is the form used both by InfluxDB, which is used to store the data being served, and Go's standard library. Clients may need to convert the value to match their own standard libraries - e.g. the `Date()` class in Javascript expects milliseconds.

The default behavior - when only e.g. *application/json* or **/** is given - is to use **RFC 3339** formatting. It will, however, respect quality parameters. It is suggested that clients request timestamps they can handle specifically, rather than relying on this default behavior, as it is **subject to change** and is in fact **expected to invert in the next major release** as string-based time formats become deprecated.

See also:

For more information on the “Accept” HTTP header, consult [its dedicated page on MDN](#).

Response Structure

series An object containing the actual data series and information necessary for working with it.

columns This is an array of names of the columns of the data contained in the “values” array - should always be `["time", "sum_count"]`

count The number of data points contained in the “values” array

name The name of the data set. Should always match `metric.ds.1min` where `metric` is the requested `metricType`

values The actual array of data points. Each represents a length of time specified by the `interval` query parameter

time The time at which the measurement was taken. This corresponds to the *beginning* of the interval. This time comes in the format of either an [RFC 3339](#)-formatted string, or a number containing the number of nanoseconds since the Unix Epoch depending on the “Accept” header sent by the client, according to the rules outlined in [Content Format](#).

value The value of the requested `metricType` at the time given by `time`. This will always be a floating point number, unless no data is available for the data interval, in which case it will be `null`

summary A summary of the data contained in the “series” object

average The arithmetic mean of the data’s values

count The number of measurements taken within the requested timespan. This is, in general, **not** the same as the `count` field of the `series` object, as it reflects the number of underlying, un-“bucketed” data points, and is therefore dependent on the implementation of Traffic Stats.

fifthPercentile Data points with values less than or equal to this number constitute the “bottom” 5% of the data set

max The maximum value that can be found in the requested data set

min The minimum value that can be found in the requested data set

ninetyEighthPercentile Data points with values greater than or equal to this number constitute the “top” 2% of the data set

ninetyFifthPercentile Data points with values greater than or equal to this number constitute the “top” 5% of the data set

1039: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: p4asf1n7fXGtgpW/
    ↳dWgolJWdXjwDcCjyvJOPFqkckbgoXGUHEj5/
    ↳wlz7brlQ48t3ZnOWCq0lbsu2eSiBssBtUQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 28 Oct 2019 20:49:51 GMT

{ "response": {
  "series": {
    "columns": [
      "time",
      "sum_count"
    ],
    "count": 4,
    "name": "bandwidth.cdn.1min",
    "tags": {
      "cdn": "CDN-in-a-Box"
    },
    "values": [
      [
        1572295500000000000,
        null
      ],
      [
        1572295560000000000,
        113.66666666666666
      ],
      [
        1572295620000000000,
        108.83333333333334
      ]
    ]
  }
}
```

(continues on next page)

(continued from previous page)

```

        ],
        [
            15722956800000000000,
            113
        ]
    ],
    },
    "summary": {
        "average": 111.83333333333333,
        "count": 3,
        "fifthPercentile": 0,
        "max": 113.66666666666666,
        "min": 108.83333333333334,
        "ninetyEighthPercentile": 113.66666666666666,
        "ninetyFifthPercentile": 113.66666666666666
    }
}
}

```

cachegroups

GET

Extract information about *Cache Groups*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 420: Request Query Parameters

Name	Re-quired	Description
id	no	Return the only <i>Cache Group</i> that has this id
name	no	Return only the <i>Cache Group</i> identified by this <i>Name</i>
type	no	Return only <i>Cache Groups</i> that are of the <i>Type</i> identified by this integral, unique identifier
topology	no	Return only <i>Cache Groups</i> that are used in the <i>Topology</i> identified by this unique identifier
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1040: Request Example

```
GET /api/4.0/cachegroups?type=23 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

fallbacks An array of strings that are *Cache Group names* that are registered as *Fallbacks* for this *Cache Group*¹

fallbackToClosest A boolean value that defines the *Fallback to Closest* behavior of this *Cache Group*^{Page 1467, 1}

id An integer that is the *ID* of the *Cache Group*

lastUpdated The time and date at which this entry was last updated in *Traffic Ops's Custom Date/Time Format*

¹ Traffic Router will first check for a fallbacks array and, when that is empty/unset/all the *Cache Groups* in it are also unavailable, will subsequently check for fallbackToClosest. If that is true, then it falls back to the geographically closest *Cache Group* capable of serving the same content or, when it is false/no such *Cache Group* exists/said *Cache Group* is also unavailable, will respond to clients with a failure response indicating the problem.

latitude A floating-point *Latitude* for the *Cache Group*

localizationMethods An array of *Localization Methods* as strings

longitude A floating-point *Longitude* for the *Cache Group*

name A string containing the *Name* of the *Cache Group*

parentCachegroupId An integer that is the *ID* of this *Cache Group*'s *Parent* - or null if it doesn't have a *Parent*

parentCachegroupName A string containing the *Name* of this *Cache Group*'s *Parent* - or null if it doesn't have a *Parent*

secondaryParentCachegroupId An integer that is the *ID* of this *Cache Group*'s *Secondary Parent* - or null if it doesn't have a *Secondary Parent*

secondaryParentCachegroupName A string containing the *Name* of this *Cache Group*'s *Secondary Parent Cache Group* - or null if it doesn't have a *Secondary Parent*

shortName A string containing the *Short Name* of the *Cache Group*

typeId An integral, unique identifier for the '*Type*' of the *Cache Group*

typeName A string that names the *Type* of this *Cache Group*

Note: The default value of `fallbackToClosest` is 'true', and if it is 'null' Traffic Control components will still interpret it as 'true'.

1041: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳oV6ifEgoFy+v049tVjSsRdWQf4bxjrUvIYfDdgpUtlxiC7gzCv31m5bXQ8EUBW4eg2hfYM+BsGvJpnNDZ
X-Server-Name: traffic_ops_golang/
Date: Wed, 07 Nov 2018 19:46:36 GMT
Content-Length: 379

{ "response": [
  {
    "id": 7,
    "name": "CDN_in_a_Box_Edge",
```

(continues on next page)

(continued from previous page)

```

    "shortName": "ciabEdge",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "parentCachegroupName": "CDN_in_a_Box_Mid",
    "parentCachegroupId": 6,
    "secondaryParentCachegroupName": null,
    "secondaryParentCachegroupId": null,
    "fallbackToClosest": [],
    "localizationMethods": [],
    "typeName": "EDGE_LOC",
    "typeId": 23,
    "lastUpdated": "2018-11-07 14:45:43+00",
    "fallbacks": []
  }
}]

```

POST

Creates a *Cache Group*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

fallbacks An optional field which, when present, should contain an array of strings that are the *Names* of other *Cache Groups* which will be the *Fallbacks*^{Page 1467, 1}

fallbackToClosest A boolean that sets the *Fallback to Closest* behavior of the *Cache Group*^{Page 1467, 1}

Note: The default value of `fallbackToClosest` is `true`, and if it is `null` Traffic Control components will still interpret it as though it were `true`.

latitude An optional field which, if present, should be a floating-point number that will define the *Latitude* for the *Cache Group*²

localizationMethods Array of *Localization Methods* (as strings)

² While these fields are technically optional, note that if they are not specified many things may break. For this reason, Traffic Portal requires them when creating or editing *Cache Groups*.

Tip: This field has no defined meaning if the *Type* identified by `typeId` is not “EDGE_LOC”.

longitude An optional field which, if present, should be a floating-point number that will define the *Longitude* for the *Cache Group*?

name The *Name* of the *Cache Group*

parentCachegroupId An optional field which, if present, should be an integer that is the *ID* of a *Parent* for this *Cache Group*.

secondaryParentCachegroupId An optional field which, if present, should be an integral, unique identifier for this *Cache Group*’s secondary parent

shortName An abbreviation of the name

typeId An integral, unique identifier for the *Cache Group*’s *Type*

Note: The actual, integral, unique identifiers for these *Types* must first be obtained, generally via *types*.

1042: Request Example

```
POST /api/4.0/cachegroups HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 252
Content-Type: application/json

{
  "name": "test",
  "shortName": "test",
  "latitude": 0,
  "longitude": 0,
  "fallbackToClosest": true,
  "localizationMethods": [
    "DEEP_CZ",
    "CZ",
    "GEO"
  ],
  "typeId": 23,
}
```

Response Structure

- fallbacks** An array of strings that are *Cache Group names* that are registered as *Fallbacks* for this *Cache Group*^{Page 1467, 1}
- fallbackToClosest** A boolean value that defines the *Fallback to Closest* behavior of this *Cache Group*^{Page 1467, 1}
- id** An integer that is the *ID* of the *Cache Group*
- lastUpdated** The time and date at which this entry was last updated in *Traffic Ops's Custom Date/Time Format*
- latitude** A floating-point *Latitude* for the *Cache Group*
- localizationMethods** An array of *Localization Methods* as strings
- longitude** A floating-point *Longitude* for the *Cache Group*
- name** A string containing the *Name* of the *Cache Group*
- parentCachegroupId** An integer that is the *ID* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*
- parentCachegroupName** A string containing the *Name* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*
- secondaryParentCachegroupId** An integer that is the *ID* of this *Cache Group's Secondary Parent* - or null if it doesn't have a *Secondary Parent*
- secondaryParentCachegroupName** A string containing the *Name* of this *Cache Group's Secondary Parent Cache Group* - or null if it doesn't have a *Secondary Parent*
- shortName** A string containing the *Short Name* of the *Cache Group*
- typeId** An integral, unique identifier for the '*Type*' of the *Cache Group*
- typeName** A string that names the *Type* of this *Cache Group*

1043: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→YvZlh3rpf13nBq6SbNVhbkt3IvckbB9amqGW2JhLxWK9K3cxjBq5J2sIHB UhrLKU hE9afpxtvaYrLRxjt
→YMQ==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Wed, 07 Nov 2018 22:11:50 GMT
Content-Length: 379

{ "alerts": [
  {
    "text": "cachegroup was created.",
    "level": "success"
  }
],
"response": {
  "id": 8,
  "name": "test",
  "shortName": "test",
  "latitude": 0,
  "longitude": 0,
  "parentCachegroupName": null,
  "parentCachegroupId": null,
  "secondaryParentCachegroupName": null,
  "secondaryParentCachegroupId": null,
  "fallbackToClosest": true,
  "localizationMethods": [
    "DEEP_CZ",
    "CZ",
    "GEO"
  ],
  "typeName": "EDGE_LOC",
  "typeId": 23,
  "lastUpdated": "2019-12-02 22:21:08+00",
  "fallbacks": []
}}
```

`cachegroups/{ID}`

PUT

Update *Cache Group*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 421: Request Path Parameters

Parameter	Description
ID	The <i>ID</i> of a <i>Cache Group</i>

fallbacks An optional field which, when present, should contain an array of strings that are the *Names* of other *Cache Groups* which will be the *Fallbacks*¹

fallbackToClosest A boolean that sets the *Fallback to Closest* behavior of the *Cache Group*^{Page 1467, 1}

Note: The default value of `fallbackToClosest` is `true`, and if it is `null` Traffic Control components will still interpret it as though it were `true`.

latitude An optional field which, if present, should be a floating-point number that will define the *Latitude* for the *Cache Group*²

localizationMethods Array of *Localization Methods* (as strings)

Tip: This field has no defined meaning if the *Type* identified by `typeId` is not “EDGE_LOC”.

longitude An optional field which, if present, should be a floating-point number that will define the *Longitude* for the *Cache Group*[?]

name The *Name* of the *Cache Group*

parentCachegroupId An optional field which, if present, should be an integer that is the *ID* of a *Parent* for this *Cache Group*.

secondaryParentCachegroupId An optional field which, if present, should be an integral, unique identifier for this *Cache Group*’s secondary parent

shortName An abbreviation of the name

typeId An integral, unique identifier for the *Cache Group*’s *Type*

Note: The actual, integral, unique identifiers for these *Types* must first be obtained, generally via *types*.

¹ Traffic Router will first check for a `fallbacks` array and, when that is empty/unset/all the *Cache Groups* in it are also unavailable, will subsequently check for `fallbackToClosest`. If that is `true`, then it falls back to the geographically closest *Cache Group* capable of serving the same content or, when it is `false`/no such *Cache Group* exists/said *Cache Group* is also unavailable, will respond to clients with a failure response indicating the problem.

² While these fields are technically optional, note that if they are not specified many things may break. For this reason, Traffic Portal requires them when creating or editing *Cache Groups*.

1044: Request Example

```
PUT /api/4.0/cachegroups/8 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 118
Content-Type: application/json

{
  "latitude": 0.0,
  "longitude": 0.0,
  "name": "test",
  "fallbacks": [],
  "fallbackToClosest": true,
  "shortName": "test",
  "typeId": 23,
  "localizationMethods": ["GEO"]
}
```

Response Structure

fallbacks An array of strings that are *Cache Group names* that are registered as *Fallbacks* for this *Cache Group*^{Page 1467, 1}

fallbackToClosest A boolean value that defines the *Fallback to Closest* behavior of this *Cache Group*^{Page 1467, 1}

id An integer that is the *ID* of the *Cache Group*

lastUpdated The time and date at which this entry was last updated in *Traffic Ops's Custom Date/Time Format*

latitude A floating-point *Latitude* for the *Cache Group*

localizationMethods An array of *Localization Methods* as strings

longitude A floating-point *Longitude* for the *Cache Group*

name A string containing the *Name* of the *Cache Group*

parentCachegroupId An integer that is the *ID* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

parentCachegroupName A string containing the *Name* of this *Cache Group's Parent* - or null if it doesn't have a *Parent*

secondaryParentCachegroupId An integer that is the *ID* of this *Cache Group's Secondary Parent* - or null if it doesn't have a *Secondary Parent*

secondaryParentCachegroupName A string containing the *Name* of this *Cache Group's Secondary Parent Cache Group* - or `null` if it doesn't have a *Secondary Parent*

shortName A string containing the *Short Name* of the *Cache Group*

typeId An integral, unique identifier for the '*Type*' of the *Cache Group*

typeName A string that names the *Type* of this *Cache Group*

1045: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: t1W65/2kj25QyHt0Ib0xpBaAR2sXu2k0sRZ49WjKZp/
    ↳AK5S1YWhX7VNWCUUGiN1VNM4QRNqODC/7ewhYDFUncA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 19:14:28 GMT
Content-Length: 385

{ "alerts": [
  {
    "text": "cachegroup was updated.",
    "level": "success"
  }
],
"response": {
  "id": 8,
  "name": "test",
  "shortName": "test",
  "latitude": 0,
  "longitude": 0,
  "parentCachegroupName": null,
  "parentCachegroupId": null,
  "secondaryParentCachegroupName": null,
  "secondaryParentCachegroupId": null,
  "fallbacks": [],
  "fallbackToClosest": true,
  "localizationMethods": [
    "GEO"
  ],
  "typeName": "EDGE_LOC",
```

(continues on next page)

(continued from previous page)

```
"typeId": 23,
"lastUpdated": "2018-11-14 19:14:28+00"
}}
```

DELETE

Delete a *Cache Group*. A *Cache Group* which has assigned servers or is the *Parent* of one or more other *Cache Groups* cannot be deleted.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 422: Request Path Parameters

Parameter	Description
ID	The <i>ID</i> of a <i>Cache Group</i> to be deleted

1046: Request Example

```
DELETE /api/4.0/cacheGroups/42 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1047: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 5jZBg07h1eNF70J/cmlbi3Hf9KJPx+WLMb1H/pSKF3FWb/
→10GUHIN35ZOB+1N5LZYCkmk3izGbTFk1ruG8I41Q==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:31:04 GMT
Content-Length: 57

{ "alerts": [
  {
    "text": "cachegroup was deleted.",
    "level": "success"
  }
]}
```

cachegroups/{{ID}}/deliveryservices

POST

Assigns all of the “assignable” servers within a *Cache Group* to one or more *Delivery Services*.

Note: “Assignable” here means all of the *Cache Group’s servers* that have a *Type* that matches one of the glob patterns `EDGE*` or `ORG*`. If even one server of any *Type* exists within the *Cache Group* that is not assigned to the same CDN as the *Delivery Service* to which an attempt is being made to assign them, the request will fail.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

deliveryServices The integral, unique identifiers of the *Delivery Services* to which the *Cache Group’s servers* are being assigned

1048: Request Example

```
POST /api/4.0/cachegroups/8/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 25
Content-Type: application/json

{"deliveryServices": [2]}
```

Response Structure

deliveryServices An array of integral, unique identifiers for *Delivery Services* to which the *Cache Group's servers* have been assigned

id An integer that is the *Cache Group's ID*

serverNames An array of the (short) hostnames of all of the *Cache Group's* “assignable” *Servers*

1049: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: j/yH0gvJoaGjiLZU/
→0MA8o5He2004aJ5wh1eF9ex6F6IB01liM9Wk9RkWCw7sdiUHoy13/
→mf7gDntisZwzP7yw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 19:54:17 GMT
Content-Length: 183

{ "alerts": [
  {
    "text": "Delivery services successfully assigned to all the
→servers of cache group 8.",
    "level": "success"
  }
],
"response": {
  "id": 8,
  "serverNames": [
    "foo"
  ],
  "deliveryServices": [
    2
  ]
}}
```

cachegroups/{ID}/queue_update

POST

Queue or “dequeue” updates for all of a *Cache Group’s servers*, limited to a specific CDN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 423: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Cache Group</i> for which updates are being <i>Queued</i> /dequeued

action The action to perform; one of “queue” or “dequeue”

cdn The full name of the CDN in need of *Queue Updates*, or a “dequeue” thereof¹

cdnId The integral, unique identifier for the CDN in need of *Queue Updates*, or a “dequeue” thereof^{Page 1467, 1}

1050: Request Example

```
POST /api/4.0/cachegroups/8/queue_update HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 42
Content-Type: application/json

{"action": "queue", "cdn": "CDN-in-a-Box"}
```

Response Structure

action The action processed, one of “queue” or “dequeue”

cachegroupId An integer that is the *ID* of the *Cache Group* for which *Queue Updates* was performed or cleared

cachegroupName The name of the *Cache Group* for which updates were queued/dequeued

cdn The name of the CDN to which the queue/dequeue operation was restricted

¹ Either ‘cdn’ or ‘cdnID’ *must* be in the request data (but not both).

serverNames An array of the (short) hostnames of the *Cache Group's servers* which are also assigned to the CDN specified in the "cdn" field

1051: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→UAcP7LrflU1RnfR4UqbQrJczlk5rkrcLOtTXJTFvIUxxK1Ek1ZkHkE4vewjDaVIhJJ6YQg8jmPGQpr+x1
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:19:46 GMT
Content-Length: 115

{ "response": {
  "cachegroupName": "test",
  "action": "queue",
  "serverNames": [
    "foo"
  ],
  "cdn": "CDN-in-a-Box",
  "cachegroupID": 8
}}
```

caches/stats

An API endpoint that returns cache statistics using the *Traffic Monitor APIs*.

See also:

This gives a set of basic statistics for *all cache servers* at the current time. For statistics from time ranges and/or aggregated over a specific CDN, use *cache_stats*.

GET

Retrieves cache stats from Traffic Monitor. Also includes rows for aggregates.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

Response Structure

cachegroup A string that is the *Name* of the *Cache Group* to which this *cache server* belongs

connections Current number of TCP connections maintained by the *cache server*

healthy true if Traffic Monitor has marked the *cache server* as “healthy”, false otherwise

See also:

Health Protocol

hostname The (short) hostname of the *cache server*

ip The IP address of the *cache server*

kbps The *cache server*’s upload speed (to clients) in Kilobits per second

profile The *Name* of the *Profile* in use by this *cache server*

status The status of the *cache server*

1052: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 20:25:01 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
↪GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Vary: Accept-Encoding
Whole-Content-Sha512: DqbLgitanS8q81/
→qKC1i+ImMiEMF+SW4G9rb79FWdeWcgwFjL810tlTRp1nNNfHV+tajgjyK+wMHobqVyaNEfA==
Content-Length: 133

{ "response": [
  {
    "profile": "ALL",
    "connections": 0,
    "ip": null,
    "status": "ALL",
    "healthy": true,
    "kbps": 0,
    "hostname": "ALL",
    "cachegroup": "ALL"
  }
]}
```

capabilities

GET

Get all capabilities.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 424: Request Query Parameters

Name	Re-quired	Description
name	no	Return only the capability that has this name
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1053: Request Example

```
GET /api/4.0/capabilities?name=test HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

name Name of the capability

description Describes the permissions covered by the capability.

lastUpdated Date and time of the last update made to this capability, in *Traffic Ops’s Custom Date/Time Format*

1054: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Vary: Accept-Encoding
Transfer-Encoding: chunked
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: c18+GtX2ZI8PoCSwuAzBhl+6w3vDpKQTa/
→cDJC0WHxdpguOL378KBxGWW5PCSyZfJUub7wPyOL5qKMn6NNTufhg==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Aug 2019 17:20:20 GMT
Content-Length: 161

{ "response": [
  {
    "description": "This is only a test. If this were a real_
→capability, it might do something",
    "lastUpdated": "2019-08-15 17:18:03+00",
    "name": "test"
  }
]}
```

cdn_locks

New in version 4.0.

GET

Gets information for all CDN locks.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 425: Request Query Parameters

Parameter	Required	Description
username	no	Return only the CDN lock that the user with <code>username</code> possesses
cdn	no	Return only the CDN lock for the CDN that has the name <code>cdn</code>

Response Structure

userName The username for which the lock exists.

cdn The name of the CDN for which the lock exists.

message The message or reason that the user specified while acquiring the lock.

soft Whether or not this is a soft(shared) lock.

lastUpdated Time that this lock was last updated(created).

1055: Response Example

```
HTTP/2 200
Content-Type: application/json

{ "response": [
  {
    "userName": "foo",
    "cdn": "bar",
    "message": "acquiring lock to snap CDN",
    "soft": true,
    "lastUpdated": "2021-05-26T09:31:57-06"
  }
]}
```

POST

Allows user to acquire a lock on a CDN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

The request body must be a single CDN Lock object with the following keys: :cdn: The name of the CDN for which the user wants to acquire a lock. :message: The message or reason for the user to acquire the lock. This is an optional field. :soft: Whether or not this is a soft(shared) lock. This is an optional field; soft will be set to true by default.

1056: Request Example

```
POST /api/4.0/cdn_locks HTTP/2
Host: localhost:8443
User-Agent: curl/7.64.2
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
Content-Type: application/json
Content-Length: 81

{
  "cdn": "bar",
  "message": "acquiring lock to snap CDN",
  "soft": true
}
```

Response Structure

userName The username for which the lock was created.

cdn The name of the CDN for which the lock was created.

message The message or reason that the user specified while acquiring the lock.

soft Whether or not this is a soft(shared) lock.

lastUpdated Time that this lock was last updated(created).

1057: Response Example

```
HTTP/2 201
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 26 May 2021 17:59:10
↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
↳IWjt4zhg40lPDTf0ebjMTS1uHsZ8LycEaHgSS3KHnmc6Vvmw5/
↳S6q70CCnbAePV2x1bxKkVEiftIxfft8vq3sg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 May 2021 16:59:10 GMT
Content-Length: 204

{ "alerts": [
  {
    "text": "soft CDN lock acquired!",
    "level": "success"
  }
],
```

(continues on next page)

(continued from previous page)

```
"response": {
  "userName": "foo",
  "cdn": "bar",
  "message": "acquiring lock to snap CDN",
  "soft": true,
  "lastUpdated": "2021-05-26T10:59:10-06"
}}
```

DELETE

Deletes an existing CDN Lock.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 426: Request Query Parameters

Parameter	Required	Description
cdn	yes	Delete the CDN lock for the CDN that has the name <code>cdn</code>

1058: Request Example

```
DELETE /api/4.0/cdn_locks?cdn=bar HTTP/2
Host: localhost:8443
User-Agent: curl/7.64.1
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
Content-Type: application/json
```

Response Structure

1059: Response Example

```
HTTP/2 200
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 26 May 2021 22:20:10GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: p/M20Emhaws6QLhzzoSBvpC5UnIM+/
84RI1wO42PYXiyUKWnxoQQEtm4lkN+K5NOKIH+OkyUli2ovQZP6lG0cg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 May 2021 21:20:10 GMT
Content-Length: 202

{ "alerts": [
  {
    "text": "cdn lock deleted",
    "level": "success"
  }
],
"response": {
  "userName": "foo",
  "cdn": "bar",
  "message": "acquiring lock to snap CDN",
  "soft": true,
  "lastUpdated": "2021-05-26T10:59:10-06"
}}
```

cdn_notifications

GET

List CDN notifications.

Auth. Required Yes

Roles Required Read-Only

Response Type Array

Request Structure

Table 427: Request Query Parameters

Parameter	Required	Description
cdn	no	The CDN name of the notifications you wish to retrieve.
id	no	The integral, unique identifier of the notification you wish to retrieve.
user	no	The username of the user responsible for creating the CDN notifications.

1060: Request Example

```
GET /api/4.0/cdn_notifications HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

- id** The integral, unique identifier of the notification
- cdn** The name of the CDN to which the notification belongs to
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*
- notification** The content of the notification
- user** The user responsible for creating the notification

1061: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 22:51:14
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳F2NmDbTpXqrIQDX7IBKH9+1drTL4XedSfJv6klMgLEZwbLCkddIXuSLpmgVCID6kTVqy3fTKjZS3U+HJ...
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 21:51:14 GMT
Content-Length: 128

{ "response": [
  {
    "id": 42,
    "cdn": "cdn1",
    "lastUpdated": "2019-12-02 21:49:08+00",
    "notification": "the content of the notification",
    "user": "username123",
  }
]}
```

POST

Creates a notification for a specific CDN.

Note: Currently only one notification per CDN is supported.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cdn The name of the CDN to which the notification shall belong

notification The content of the notification

1062: Request Example

```
POST /api/4.0/cdn_notifications HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 29

{"cdn": "cdn1", "notification": "the content of the notification"}
```

Response Structure

- id** The integral, unique identifier of the notification
- cdn** The name of the CDN to which the notification belongs to
- lastUpdated** The time and date this server entry was last updated in *Traffic Ops's Custom Date/Time Format*
- notification** The content of the notification
- user** The user responsible for creating the notification

1063: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 02 Dec 2019 22:49:08
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mx8b2GTyOjz4QtMxXCmoQyZogCB504vs0yv6WGly4dwM81W3XiejWNuUwchRBYyi8QHaWsmZ3DaiGGfQi,
    ↳8Giw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 02 Dec 2019 21:49:08 GMT
Content-Length: 150

{
  "alerts":
    [
      {
        "text": "notification was created.",
        "level": "success"
      }
    ],
  "response":
    {
      "id": 42,
      "cdn": "cdn1",
      "lastUpdated": "2019-12-02 21:49:08+00",
      "notification": "the content of the notification",
      "user": "username123",
    }
}
```

DELETE

Deletes an existing CDN notification.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 428: Request Query Parameters

Parameter	Required	Description
id	yes	The integral, unique identifier of the notification you wish to delete.

1064: Request Example

```
DELETE /api/4.0/cdn_notifications?id=42 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

1065: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 08:27:33.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→Woz8NSHIYVpX4V5X4xZWZIX1hvGL2uian7nUhjZ8F23Nb9RWQRMIg/cc+1vXEzkT/
→ehKV9t11FKRLX+avSae0g==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/  
Date: Tue, 25 Feb 2020 07:27:33 GMT  
Content-Length: 83  
  
{  
  "alerts": [  
    {  
      "text": "notification was deleted.",  
      "level": "success"  
    }  
  ]  
}
```

cdns

Extract information about all CDNs

GET

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 429: Request Query Parameters

Parameter	Required	Description
domainName	no	Return only the CDN that has this domain name
dnssecEnabled	no	Return only the CDNs that are either dnssec enabled or not
id	no	Return only the CDN that has this id
name	no	Return only the CDN that has this name
orderBy	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

dnssecEnabled true if DNSSEC is enabled on this CDN, otherwise false

domainName Top Level Domain name within which this CDN operates

id The integral, unique identifier for the CDN

lastUpdated Date and time when the CDN was last modified in *Traffic Ops’s Custom Date/Time Format*

name The name of the CDN

1066: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→z9P1NkxGebPncUhaChDHtYKYI+XVZfhE6Y84TuwoASZFIMfISELwADLpvpPTN+wwnzBfREksLYn+0313Q
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:46:57 GMT
Content-Length: 237

{ "response": [
  {
    "dnssecEnabled": false,
    "domainName": "-",
    "id": 1,
    "lastUpdated": "2018-11-14 18:21:06+00",
    "name": "ALL"
  },
  {
    "dnssecEnabled": false,
    "domainName": "mycdn.ciab.test",
    "id": 2,
    "lastUpdated": "2018-11-14 18:21:14+00",
    "name": "CDN-in-a-Box"
  }
]}

```

POST

Allows user to create a CDN

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

dnssecEnabled If true, this CDN will use DNSSEC, if false it will not

domainName The top-level domain (TLD) belonging to the new CDN

name Name of the new CDN

1067: Request Structure

```
POST /api/4.0/cdns HTTP/1.1
Host: trafficops.infra.ciab.test

```

(continues on next page)

(continued from previous page)

```
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 63
Content-Type: application/json

{"name": "test", "domainName": "quest", "dnssecEnabled": false}
```

Response Structure

dnssecEnabled true if the CDN uses DNSSEC, false otherwise

domainName The top-level domain (TLD) assigned to the newly created CDN

id An integral, unique identifier for the newly created CDN

name The newly created CDN's name

1068: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳1rZRl0fQioGRrEb4nCfjGGx7y3Ub2h7BZ4z6NbhcY4acPslKSUNM8QLjWTVwLU4WpkfJNxc0yy8NlKULF
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:49:28 GMT
Content-Length: 174

{ "alerts": [
  {
    "text": "cdn was created.",
    "level": "success"
  }
],
"response": {
  "dnssecEnabled": false,
  "domainName": "quest",
  "id": 3,
  "lastUpdated": "2018-11-14 20:49:28+00",
```

(continues on next page)

(continued from previous page)

```
"name": "test"
}}
```

cdns/capacity

GET

Retrieves the aggregate capacity percentages of all *Cache Groups* for a given CDN.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

availablePercent The percent of available (unused) bandwidth to 64 bits of precision¹

unavailablePercent The percent of unavailable (used) bandwidth to 64 bits of precision¹

utilizedPercent The percent of bandwidth currently in use to 64 bits of precision¹

maintenancePercent The percent of bandwidth being used for administrative or analytical processes internal to the CDN to 64 bits of precision¹

1069: Response Example

```
{ "response": {
  "availablePercent": 89.0939840205533,
  "unavailablePercent": 0,
  "utilizedPercent": 10.9060020300395,
  "maintenancePercent": 0.0000139494071146245
}}
```

¹ Following IEEE 754

cdns/dnsseckey/generate

POST

Generates ZSK and KSK keypairs for a CDN and all associated *Delivery Services*.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

effectiveDate An optional string containing the date and time at which the newly-generated ZSK and KSK become effective, in **RFC 3339** format. Defaults to the current time if not specified.

key Name of the CDN

kskExpirationDays Expiration (in days) for the KSKs

ttl Time, in seconds, for which the keypairs shall remain valid

zskExpirationDays Expiration (in days) for the ZSKs

1070: Request Example

```
POST /api/4.0/cdns/dnsseckey/generate HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 130

{
  "key": "CDN-in-a-Box",
  "kskExpirationDays": 1095,
  "ttl": 3600,
  "zskExpirationDays": 1095
}
```

Response Structure

1071: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 19:42:15
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 09SPWzeMNFgg6I/PPeXittBIhdh3/
  ↳zUKK1NwNlYIM9SszSrK0h/Dfz7tnwgnA7h/s6M4eYBJxykDpCfVC7xpeg==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 18:42:15 GMT
Content-Length: 89

{
  "response": "Successfully created dnssec keys for CDN-in-a-Box"
}
```

cdns/dnsseckey/refresh

GET

Refresh the DNSSEC keys for all CDNs. This call initiates a background process to refresh outdated keys, and immediately returns a response that the process has started.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

No parameters available

Response Structure

1072: Response Example

```
HTTP/1.1 202 Accepted
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Location: /api/4.0/async_status/3
Permissions-Policy: interest-cohort=()
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 20 Jul 2021 23:55:11.
↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: yJUGNCYygBYvHft4z0nxJ0/
↳p230s3PdPT5Tld+8hIWfxmpmKDciY4D7+1Bf8S69ckmZR/yxY95kIZEbg9/jFgw==
X-Server-Name: traffic_ops_golang/
Date: Tue, 20 Jul 2021 22:55:11 GMT
Content-Length: 176

{
  "alerts": [
    {
      "text": "Starting DNSSEC key refresh in the background.
↳This may take a few minutes. Status updates can be found here: /api/
↳4.0/async_status/3",
      "level": "success"
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```

    }
  ]
}
```

cdns/domains

GET

Gets a list of domains and their related Traffic Router *Profiles* for all CDNs.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

Response Structure

domainName The TLD assigned to this CDN

parameterId The *ID* for the *Parameter* that sets this TLD on the Traffic Router

profileDescription A short, human-readable description of the Traffic Router's profile

profileId The *ID* of the *Profile* assigned to the Traffic Router responsible for serving domainName

profileName The *Name* of the *Profile* assigned to the Traffic Router responsible for serving domainName

1073: Response Example

```

{ "response": [
  {
    "profileId": 12,
    "parameterId": -1,
    "profileName": "CCR_CIAB",
    "profileDescription": "Traffic Router for CDN-In-A-Box",
    "domainName": "mycdn.ciab.test"
  }
]}
```

cdns/health

Extract health information from all *Cache Groups* across all CDNs

See also:

Health Protocol

GET

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available

Response Structure

cachegroups An array of objects describing the health of each Cache Group

name The name of the Cache Group

offline The number of OFFLINE caches in the Cache Group

online The number of ONLINE caches in the Cache Group

totalOffline Total number of OFFLINE caches across all Cache Groups which are assigned to any CDN

totalOnline Total number of ONLINE caches across all Cache Groups which are assigned to any CDN

1074: Response Example

```
{ "response": {
  "totalOffline": 0,
  "totalOnline": 1,
  "cachegroups": [
    {
      "offline": 0,
      "name": "CDN_in_a_Box_Edge",
      "online": 1
    }
  ]
}}
```

`cdns/{{ID}}`

PUT

Allows a user to edit a specific CDN

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 430: Request Path Parameters

Name	Description
ID	Integral, unique identifier for the CDN to update

dnssecEnabled If true, this CDN will use DNSSEC, if false it will not

domainName The top-level domain (TLD) belonging to the CDN

name Name of the new CDN

1075: Request Example

```
PUT /api/4.0/cdns/3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 63
Content-Type: application/json

{"name": "quest", "domainName": "test", "dnssecEnabled": false}
```

Response Structure

dnssecEnabled true if the CDN uses DNSSEC, false otherwise

domainName The top-level domain (TLD) assigned to the newly created CDN

id An integral, unique identifier for the newly created CDN

name The newly created CDN’s name

1076: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: sI1hzBwG+/
    ↳VAzoFY20kqGFA2RgrU0ThtMeeJqk0ZxH3TRxTWuA8BetACct/
    ↳XICC3n7hPDLlRVpwckEyBdyJkXg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:54:33 GMT
Content-Length: 174

{ "alerts": [
  {
    "text": "cdn was updated.",
    "level": "success"
  }
],
"response": {
  "dnssecEnabled": false,
  "domainName": "test",
  "id": 4,
  "lastUpdated": "2018-11-14 20:54:33+00",
  "name": "quest"
}}
```

DELETE

Allows a user to delete a specific CDN

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 431: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the CDN to delete

Response Structure

1077: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Zy4cJN6BEct4ltFLN4e296mM8XnzOs0EQ3/
    ↳jp4TA3L+g8qtkI0WrL+ThcFq4xbJPU+KHVDSi+b0JBav3xsYPqQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:51:23 GMT
Content-Length: 58

{ "alerts": [
  {
    "text": "cdn was deleted.",
    "level": "success"
  }
]}

```

cdns/{{ID}}/queue_update

POST

Queue or “dequeue” updates for all servers assigned to a specific CDN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 432: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the CDN on which to (de)queue updates

Table 433: Request Query Parameters

Name	Re-quired	Description
type	no	The name of the type of servers, for which the updates need to be queued or dequeued.
pro-file	no	The name of the profile of servers, for which the updates need to be queued or dequeued.

action One of “queue” or “dequeue” as appropriate

1078: Request Example

```
POST /api/4.0/cdns/2/queue_update?type=EDGE HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 19
Content-Type: application/json

{"action": "queue"}
```

Response Structure

action The action processed, either "queue" or "dequeue"

cdnId The integral, unique identifier for the CDN on which *Queue Updates* was performed or cleared

1079: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512:↵
↵rBpFfrrP+9IFkwsRloEM+v+I8MuBZDXqFu+WUTGtRGypnAn2gHooPoNQRYVvJGjyIQRXLXlvqjEtve+lH2
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:02:07 GMT
Content-Length: 41

{ "response": {
  "action": "queue",
  "cdnId": 2
}}
```

`cdns/{{name}}/configs/monitoring`

See also:

Health Protocol

GET

Retrieves information concerning the monitoring configuration for a specific CDN.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 434: Request Path Parameters

Name	Description
name	The name of the CDN for which monitoring configuration will be fetched

Response Structure

cacheGroups An array of objects representing each of the *Cache Groups* being monitored within this CDN

coordinates An object representing the geographic location of this *Cache Group*

latitude This *Cache Group's latitude* as a floating-point number

- longitude** This *Cache Group's longitude* as a floating-point number
- name** A string that is this *Cache Group's name*
- config** A collection of parameters used to configure the monitoring behaviour of Traffic Monitor
 - health.polling.interval** An interval in milliseconds on which to poll for health statistics
 - tm.polling.interval** The interval at which to poll for configuration updates
- deliveryServices** An array of objects representing each *Delivery Service* provided by this CDN
 - status** The *Delivery Service's* status
 - totalKbpsThreshold** A threshold rate of data transfer this *Delivery Service* is configured to handle, in Kilobits per second
 - totalTpsThreshold** A threshold amount of transactions per second that this *Delivery Service* is configured to handle
 - xmlId** A string that is the *Delivery Service's XMLID*
- profiles** An array of the *Profiles* in use by the *cache servers* and *Delivery Services* belonging to this CDN
 - name** A string that is the *Profile's Name*
 - parameters** An array of the *Parameters* in this *Profile* that relate to monitoring configuration. This can be null if the servers using this *Profile* cannot be monitored (e.g. Traffic Routers)
 - health.connection.timeout** A timeout value, in milliseconds, to wait before giving up on a health check request
 - health.polling.url** A URL to request for polling health. Substitutions can be made in a shell-like syntax using the properties of an object from the "trafficServers" array
 - health.threshold.availableBandwidthInKbps** The total amount of bandwidth that servers using this profile are allowed - across all network interfaces - in Kilobits per second. This is a string and using comparison operators to specify

ranges, e.g. “>10” means “more than 10 kbps”

health.threshold.loadavg The UNIX load-avg at which the server should be marked “unhealthy”

See also:

uptime(1)

health.threshold.queryTime The highest allowed length of time for completing health queries (after connection has been established) in milliseconds

history.count The number of past events to store; once this number is reached, the oldest event will be forgotten before a new one can be added

type A string that names the *Profile's Type*

trafficMonitors An array of objects representing each Traffic Monitor that monitors this CDN (this is used by Traffic Monitor's “peer polling” function)

fqdn An FQDN that resolves to the IPv4 (and/or IPv6) address of the server running this Traffic Monitor instance

hostname The hostname of the server running this Traffic Monitor instance

ip6 The IPv6 address of this Traffic Monitor - when applicable

ip The IPv4 address of this Traffic Monitor

port The port on which this Traffic Monitor listens for incoming connections

profile A string that is the *Name* of the *Profile* assigned to this Traffic Monitor

status The status of the server running this Traffic Monitor instance

trafficServers An array of objects that represent the *cache servers* being monitored within this CDN

cacheGroup The *Cache Group* to which this *cache server* belongs

fqdn An FQDN that resolves to the *cache server's* IPv4 (or IPv6) address

hashId The (short) hostname for the *cache server* - named “hashId” for legacy reasons

- hostName** The (short) hostname of the *cache server*
- port** The port on which the *cache server* listens for incoming connections
- profile** A string that is the *Name* of the *Profile* assigned to this *cache server*
- status** The status of the *cache server*
- type** A string that names the *Type* of the *cache server* - should (ideally) be either EDGE or MID
- interfaces** A set of the network interfaces in use by the server. In most scenarios, only one will be present, but it is illegal for this set to be an empty collection.
- ipAddresses** A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be present, but it is illegal for this set to be an empty collection.
- address** The actual IP address, including any mask as a CIDR-notation suffix
- gateway** Either the IP address of the network gateway for this address, or null to signify that no such gateway exists
- serviceAddress** A boolean that describes whether or not the server's main service is available at this IP address. When this property is true, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family

(i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the “service interface” for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning “no limit”. It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface’s device name on the server, e.g. `eth0`.

1080: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→uLR+tRoqR8SY038j3DV9wQ+IkJ7Kf+MCoFkcWZtsgbpLJ+0S6f+IiI8laNVeDgrM/
→P23MAQ6BSepm+EJRl1AXQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:09:31 GMT
Transfer-Encoding: chunked
```

```
{ "response": {
  "trafficServers": [
    {
      "profile": "ATS_EDGE_TIER_CACHE",
      "status": "REPORTED",
      "port": 80,
      "interfaces": [
        {
          "ipAddresses": [
            {
              "address": "172.16.239.100",
              "gateway": "172.16.239.0/24",
              "serviceAddress": "true"
            },
            {
              "address": "fc01:9400:1000:8::100",
              "gateway": "fc01::",
              "serviceAddress": "true"
            }
          ],
          "name": "eth0",
          "monitor": "true",
          "mtu": 9000,
          "maxBandwidth": 150
        }
      ],
      "cachegroup": "CDN_in_a_Box_Edge",
      "hostname": "edge",
      "fqdn": "edge.infra.ciab.test",
      "type": "EDGE",
      "hashid": "edge"
    },
    {
      "profile": "ATS_MID_TIER_CACHE",
      "status": "REPORTED",
      "port": 80,
      "interfaces": [
```

(continues on next page)

(continued from previous page)

```

        {
            "ipAddresses": [
                {
                    "address": "172.16.239.120",
                    "gateway": "172.16.239.0/24",
                    "serviceAddress": "true"
                },
                {
                    "address": "fc02:9400:1000:8::100",
                    "gateway": "fc02::",
                    "serviceAddress": "true"
                }
            ],
            "name": "eth0",
            "monitor": "true",
            "mtu": 9000,
            "maxBandwidth": 150
        }
    ],
    "cachegroup": "CDN_in_a_Box_Mid",
    "hostname": "mid",
    "fqdn": "mid.infra.ciab.test",
    "type": "MID",
    "hashid": "mid"
}
],
"trafficMonitors": [
    {
        "profile": "RASCAL-Traffic_Monitor",
        "status": "ONLINE",
        "ip": "172.16.239.40",
        "ip6": "fc01:9400:1000:8::40",
        "port": 80,
        "cachegroup": "CDN_in_a_Box_Edge",
        "hostname": "trafficmonitor",
        "fqdn": "trafficmonitor.infra.ciab.test"
    }
],
"cacheGroups": [
    {
        "name": "CDN_in_a_Box_Mid",
        "coordinates": {
            "latitude": 38.897663,
            "longitude": -77.036574
        }
    }
],

```

(continues on next page)

(continued from previous page)

```
{
  "name": "CDN_in_a_Box_Edge",
  "coordinates": {
    "latitude": 38.897663,
    "longitude": -77.036574
  }
},
],
"profiles": [
  {
    "name": "CCR_CIAB",
    "type": "CCR",
    "parameters": null
  },
  {
    "name": "ATS_EDGE_TIER_CACHE",
    "type": "EDGE",
    "parameters": {
      "health.connection.timeout": 2000,
      "health.polling.url": "http://${hostname}/_astats?
→application=&inf.name=${interface_name}",
      "health.threshold.availableBandwidthInKbps": ">1750000
→",
      "health.threshold.loadavg": "25.0",
      "health.threshold.queryTime": 1000,
      "history.count": 30
    }
  },
  {
    "name": "ATS_MID_TIER_CACHE",
    "type": "MID",
    "parameters": {
      "health.connection.timeout": 2000,
      "health.polling.url": "http://${hostname}/_astats?
→application=&inf.name=${interface_name}",
      "health.threshold.availableBandwidthInKbps": ">1750000
→",
      "health.threshold.loadavg": "25.0",
      "health.threshold.queryTime": 1000,
      "history.count": 30
    }
  }
],
"deliveryServices": [],
"config": {
  "health.polling.interval": 6000,
```

(continues on next page)

(continued from previous page)

```

    "heartbeat.polling.interval": 3000,
    "peers.polling.interval": 3000,
    "tm.polling.interval": 2000
  }
}
```

`cdns/{name}/dnsseckey/ksk/generate`

POST

Generates a new KSK for a specific CDN.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

Table 435: Request Path Parameters

Name	Required	Description
name	yes	The name of the CDN for which the KSK will be generated

expirationDays The integral number of days until the newly generated KSK expires

effectiveDate An optional string containing the date and time at which the newly generated KSK becomes effective, in **RFC 3339** format. Defaults to the current time if not specified

Response Structure

1081: Response Example

```
{ "response": "Successfully generated ksk dnssec keys for my-cdn-name" }
```

`cdns/{{name}}/federations`

GET

Retrieves a list of federations in use by a specific CDN.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 436: Request Path Parameters

Name	Description
name	The name of the CDN for which federations will be listed

Table 437: Request Query Parameters

Name	Description
id	Return only the federation that has this id
orderby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

1082: Request Example

```
GET /api/4.0/cdns/CDN-in-a-Box/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

cname The Canonical Name (CNAME) used by the federation

deliveryService An object with keys that provide identifying information for the *Delivery Service* using this federation

id The integral, unique identifier for the *Delivery Service*

xmlId The *Delivery Service*'s uniquely identifying 'xml_id'

description An optionally-present field containing a description of the field

Note: This key will only be present if the description was provided when the federation was created. Refer to the POST method of this endpoint to see how federations can be created.

lastUpdated The date and time at which this federation was last modified, in *Traffic Ops's Custom Date/Time Format*

ttl Time to Live (TTL) for the cname, in hours

1083: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
→SJA7G+7G5KcOfCtnE3Dq5DCobWtGRUKSppiDkflZoG5+paq4E1aZGqUb6vGVsd+TpPg75ML1hyqfdfCHnl
→g==
x-server-name: traffic_ops_golang/
content-length: 170
date: Wed, 05 Dec 2018 00:35:40 GMT

{ "response": [
  {
    "id": 1,
    "cname": "test.quest.",
    "ttl": 48,
    "description": "A test federation",
    "lastUpdated": "2018-12-05 00:05:16+00",
    "deliveryService": {
      "id": 1,
      "xmlId": "demo1"
```

(continues on next page)

(continued from previous page)

```
    }  
  }  
}]}
```

POST

Creates a new federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 438: Request Path Parameters

Name	Description
name	The name of the CDN for which a new federation will be created

cname The Canonical Name (CNAME) used by the federation

Note: The CNAME must end with a “.”

description An optional description of the federation

ttl Time to Live (TTL) for the name record used for **cname**

1084: Request Example

```
POST /api/4.0/cdns/CDN-in-a-Box/federations HTTP/1.1  
Host: trafficops.infra.ciab.test  
User-Agent: curl/7.62.0  
Accept: */*  
Cookie: mojolicious=...  
Content-Length: 72  
Content-Type: application/json  
  
{  
  "cname": "test.quest.",  
  "ttl": 48,  
  "description": "A test federation"  
}
```

Response Structure

cname The Canonical Name (CNAME) used by the federation

description An optionally-present field containing a description of the field

Note: This key will only be present if the description was provided when the federation was created

lastUpdated The date and time at which this federation was last modified, in *Traffic Ops's Custom Date/Time Format*

ttl Time to Live (TTL) for the cname, in hours

1085: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
    ↳rRsWAIhXzVlj8Hy+8aFjp4JJo1QGTK49m0N1AP5QDyyAZ1TfNIIdgtcgiuehu7FiN1IPWRFiv6D9CygFYKG
x-server-name: traffic_ops_golang/
content-length: 192
date: Wed, 05 Dec 2018 00:05:16 GMT

{ "alerts": [
  {
    "text": "cdnfederation was created.",
    "level": "success"
  }
],
"response": {
  "id": 1,
  "cname": "test.quest.",
  "ttl": 48,
  "description": "A test federation",
  "lastUpdated": "2018-12-05 00:05:16+00"
}}
```

`cdns/{{name}}/federations/{{ID}}`

PUT

Updates a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 439: Request Path Parameters

Name	Description
name	The name of the CDN for which the federation identified by ID will be inspected
ID	An integral, unique identifier for the federation to be inspected

cname The Canonical Name (CNAME) used by the federation

Note: The CNAME must end with a “.”

description An optional description of the federation

ttd Time to Live (TTL) for the name record used for **cname**

1086: Request Example

```
PUT /api/4.0/cdns/CDN-in-a-Box/federations/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 33
Content-Type: application/json

{
  "cname": "foo.bar.",
  "ttl": 48
}
```

Response Structure

cname The Canonical Name (CNAME) used by the federation

description An optionally-present field containing a description of the field

Note: This key will only be present if the description was provided when the federation was created

lastUpdated The date and time at which this federation was last modified, in *Traffic Ops's Custom Date/Time Format*

ttl Time to Live (TTL) for the cname, in hours

1087: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
  ↳qcjfq+gDjNxYQ1aq+dlddgrkFWnkFYxsFF+SHDqqH0uVHBVksmU0aTFgltozek/
  ↳u6wbrGoR1LFf9Fr1C1SbigA==
x-server-name: traffic_ops_golang/
content-length: 174
date: Wed, 05 Dec 2018 01:03:40 GMT
```

(continues on next page)

(continued from previous page)

```
{ "alerts": [
  {
    "text": "cdnfederation was updated.",
    "level": "success"
  }
],
"response": {
  "id": 1,
  "cname": "foo.bar.",
  "ttl": 48,
  "description": null,
  "lastUpdated": "2018-12-05 01:03:40+00"
}}
```

DELETE

Deletes a specific federation.

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 440: Request Path Parameters

Name	Description
name	The name of the CDN for which the federation identified by ID will be inspected
ID	An integral, unique identifier for the federation to be inspected

1088: Request Example

```
DELETE /api/4.0/cdns/CDN-in-a-Box/federations/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1089: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512: Cnkfj6dmzTD3if9oiDq33tqf7CnAflKK/
    ↳SPgqJyfu6HUf0jLJOgKIZvkcs2wWY6EjLVdw5qsatsd4FPoCyjvcw==
x-server-name: traffic_ops_golang/
content-length: 68
date: Wed, 05 Dec 2018 01:17:24 GMT

{ "alerts": [
  {
    "text": "cdnfederation was deleted.",
    "level": "success"
  }
]}
```

`cdns/{{name}}/health`

GET

Retrieves the health of all *Cache Groups* for a given CDN.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 441: Request Path Parameters

Name	Description
name	The name of the CDN for which health will be reported

1090: Request Example

```
GET /api/4.0/cdns/CDN-in-a-Box/health HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

cachegroups An array of objects describing the health of each *Cache Group*

name A string that is the *Cache Group's Name*

offline The number of OFFLINE *cache servers* in the *Cache Group*

online The number of ONLINE *cache servers* in the *Cache Group*

totalOffline Total number of OFFLINE *cache servers* across all *Cache Groups* which are assigned to the CDN defined by the **name** request path parameter

totalOnline Total number of ONLINE *cache servers* across all *Cache Groups* which are assigned to the CDN defined by the **name** request path parameter

1091: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Encoding: gzip
Content-Length: 108
Content-Type: application/json
Date: Tue, 03 Dec 2019 21:33:59 GMT
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; expires=Wed, 04 Dec 2019 01:33:59 GMT;␣
→path=/; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:␣
→KpXViXeAgch58ueQqdyU8NuINBw1EUedE6Rv2ewcLUajJp6kowdbVynpwW7XiSvAyHdtClIOuT30khImq

{ "response": {
  "totalOffline": 0,
  "totalOnline": 1,
  "cachegroups": [
    {
      "offline": 0,
      "name": "CDN_in_a_Box_Edge",
      "online": 1
    }
  ]
}}
```

`cdns/name/{name}}`

DELETE

Allows a user to delete a CDN by name

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 442: Request Path Parameters

Name	Description
name	The name of the CDN to be deleted

Response Structure

1092: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Zy4cJN6BEct4ltFLN4e296mM8XnzOs0EQ3/
    ↳jp4TA3L+g8qtkI0WrL+ThcFq4xbJPU+KHVDSi+b0JBav3xsYPqQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 20:59:22 GMT
Content-Length: 58

{ "alerts": [
  {
    "text": "cdn was deleted.",
    "level": "success"
  }
]}
```

cdns/name/{{name}}/dnsseckey

GET

Gets a list of DNSSEC keys for CDN and all associated *Delivery Services*. Before returning response to user, this will make sure DNSSEC keys for all *Delivery Services* exist and are not expired. If they don't exist or are expired, they will be (re-)generated.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 443: Request Path Parameters

Name	Description
name	The name of the CDN for which keys will be fetched

Response Structure

name The name of the CDN or *Delivery Service* to which the enclosed keys belong

zsk The short-term ZSK

expirationDate A Unix epoch timestamp (in seconds) representing the date and time whereupon the key will expire

inceptionDate A Unix epoch timestamp (in seconds) representing the date and time when the key was created

name The name of the domain for which this key will be used

private Encoded private key

public Encoded public key

ttd The time for which the key should be trusted by the client

ksk The long-term KSK

dsRecord An optionally present object containing information about the algorithm used to generate the key

algorithm The name of the algorithm used to generate the key

digest A hash of the DNSKEY record

digestType The type of hash algorithm used to create the value of digest

expirationDate A Unix epoch timestamp (in seconds) representing the date and time whereupon the key will expire

inceptionDate A Unix epoch timestamp (in seconds) representing the date and time when the key was created

name The name of the domain for which this key will be used

private Encoded private key

public Encoded public key

ttl The time for which the key should be trusted by the client

1093: Response Example

```
{ "response": {
  "cdn1": {
    "zsk": {
      "ttl": "60",
      "inceptionDate": "1426196750",
      "private": "zsk private key",
      "public": "zsk public key",
      "expirationDate": "1428788750",
      "name": "foo.kabletown.com."
    },
    "ksk": {
      "name": "foo.kabletown.com.",
      "expirationDate": "1457732750",
      "public": "ksk public key",
      "private": "ksk private key",
      "inceptionDate": "1426196750",
      "ttl": "60",
      "dsRecord": {
        "algorithm": "5",
        "digestType": "2",
        "digest": "abc123def456"
      }
    }
  },
  "ds-01": {
    "zsk": {
      "ttl": "60",
      "inceptionDate": "1426196750",
      "private": "zsk private key",
      "public": "zsk public key",
      "expirationDate": "1428788750",
      "name": "ds-01.foo.kabletown.com."
    },
    "ksk": {
```

(continues on next page)

(continued from previous page)

```

        "name": "ds-01.foo.kabletown.com.",
        "expirationDate": "1457732750",
        "public": "ksk public key",
        "private": "ksk private key",
        "inceptionDate": "1426196750"
    }
}
}}
```

DELETE

Delete DNSSEC keys for a CDN and all associated *Delivery Services*.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

Table 444: Request Path Parameters

Name	Description
name	The name of the CDN for which DNSSEC keys will be deleted

Response Structure

1094: Response Example

```

{
    "response": "Successfully deleted dnssec keys for test"
}
```

cdns/name/{name}}/sslkeys

GET

Returns SSL certificates for all *Delivery Services* that are a part of the CDN.

Auth. Required Yes

Roles Required “admin”

Response Type Array

Request Structure

Table 445: Request Path Parameters

Name	Description
name	The name of the CDN for which keys will be fetched

Response Structure

certificate An object representing The SSL keys used for the *Delivery Service* identified by `deliveryservice`

key Base 64-encoded private key for SSL certificate

crt Base 64-encoded SSL certificate

deliveryservice A string that is the *xml_id* of the *Delivery Service* using the SSL key within `certificate`

1095: Response Example

```
{ "response": [
  {
    "deliveryservice": "ds1",
    "certificate": {
      "crt": "base64encodedcrt1",
      "key": "base64encodedkey1"
    }
  },
  {
    "deliveryservice": "ds2",
    "certificate": {
      "crt": "base64encodedcrt2",
      "key": "base64encodedkey2"
    }
  }
]}
```

`cdns/{{name}}/snapshot`

Caution: This page is a stub! Much of it may be missing or just downright wrong - it needs a lot of love from people with the domain knowledge required to update it.

GET

Retrieves the *current Snapshot* for a CDN, which represents the current *operating state* of the CDN, **not** the current *configuration* of the CDN. The contents of this *Snapshot* are currently used by Traffic Monitor and Traffic Router.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 446: Request Path Parameters

Name	Description
name	The name of the CDN for which a <i>Snapshot</i> shall be returned

1096: Request Example

```
GET /api/4.0/cdns/CDN-in-a-Box/snapshot HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

config An object containing basic configurations on the actual CDN object

api.cache-control.max-age A string containing an integer which specifies the value of `max-age` in the `Cache-Control` header of some HTTP responses, likely the *Traffic Router API* responses

certificates.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for updated SSL certificates

consistent.dns.routing A string containing a boolean which indicates whether DNS routing will use a consistent hashing method or “round-robin”

“false” The “round-robin” method will be used to define DNS routing

“true” A consistent hashing method will be used to define DNS routing

coveragezone.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should check for a new Coverage Zone file

coveragezone.polling.url The URL where a *Coverage Zone File* may be requested by Traffic Routers

dnssec.dynamic.response.expiration A string containing a number and unit suffix that specifies the length of time for which dynamic responses to DNSSEC lookup queries should remain valid

dnssec.dynamic.concurrencylevel An integer that defines the size of the concurrency level (threads) of the Guava cache used by ZoneManager to store zone material

dnssec.dynamic.initialcapacity An integer that defines the initial size of the Guava cache, default is 10000. Too low of a value can lead to expensive resizing

dnssec.init.timeout An integer that defines the number of minutes to allow for zone generation, this bounds the zone priming activity

dnssec.enabled A string that tells whether or not the CDN uses DNSSEC; one of:

“false” DNSSEC is not used within this CDN

“true” DNSSEC is used within this CDN

domain_name A string that is the TLD served by the CDN

federationmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new federation mappings

federationmapping.polling.url The URL where Traffic Control components can request federation mappings

geolocation.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new IP-to-geographic-location mapping databases

geolocation.polling.url The URL where Traffic Control components can request IP-to-geographic-location mapping database files

keystore.maintenance.interval A string containing an integer which specifies the interval, in seconds, on which Traffic

Routers should refresh their zone caches

neustar.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new “Neustar” databases

neustar.polling.url The URL where Traffic Control components can request “Neustar” databases

soa An object defining the SOA for the CDN’s TLD (defined in `domain_name`)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: **RFC 1035** dictates that this should always be less than `refresh`.

See also:

[The Wikipedia page on Start of Authority records.](#)

steeringmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which

Traffic Control components should check for new steering mappings

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

zonemanager.cache.maintenance.interval A configuration option for the ZoneManager Java class of Traffic Router

zonemanager.threadpool.scale A configuration option for the ZoneManager Java class of Traffic Router

contentRouters An object containing keys which are the (short) hostnames of the Traffic Routers that serve requests for *Delivery Services* in this CDN

api.port A string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTP

secure.api.port An optionally present string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTPS

fqdn This Traffic Router's FQDN

httpsPort The port number on which this Traffic Router listens for incoming HTTPS requests

ip This Traffic Router's IPv4 address

ip6 This Traffic Router's IPv6 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Router belongs

port The port number on which this Traffic Router listens for incoming HTTP requests

profile The *Name* of the *Profile* used by this Traffic Router

status The health status of this Traffic Router

See also:

Health Protocol

contentServers An object containing keys which are the (short) hostnames of the *Edge-tier cache servers* in the CDN; the values corresponding to those keys are routing information for said servers

cacheGroup A string that is the *Name* of the *Cache Group* to which the server belongs

capabilities An array of this *Cache Server's Server Capabilities*. If the Cache Server has no Server Capabilities, this field is omitted.

deliveryServices An object containing keys which are the names of *Delivery Services* to which this *cache server* is assigned; the values corresponding to those keys are arrays of FQDNs that resolve to this *cache server*

Note: Only *Edge-tier cache servers* can be assigned to a *Delivery Service*, and therefore this field will only be present when `type` is "EDGE".

fqdn The server's FQDN

hashCount The number of servers to be placed into a single "hash ring" in Traffic Router

hashId A unique string to be used as the key for hashing servers - as of version 3.0.0 of Traffic Control, this is always the same as the server's (short) hostname and only still exists for legacy compatibility reasons

httpsPort The port on which the *cache server* listens for incoming HTTPS requests

interfaceName The name of the main network interface device used by this *cache server*

ip6 The server's IPv6 address

ip The server's IPv4 address

locationId This field is exactly the same as `cacheGroup` and only exists for legacy compatibility reasons

port The port on which this *cache server* listens for incoming HTTP requests

profile The *Name* of the *Profile* used by the *cache server*

routingDisabled An integer representing the boolean concept of whether or not Traffic Routers should route client traffic to this *cache server*; one of:

0 Do not route traffic to this server

1 Route traffic to this server normally

status This *cache server*'s status

See also:

Health Protocol

type The *Type* of this *cache server*; which ought to be one of (but in practice need not be in certain special circumstances):

EDGE This is an *Edge-tier cache server*

MID This is a *Mid-tier cache server*

deliveryServices An object containing keys which are the *xml_ids* of all of the *Delivery Services* within the CDN

anonymousBlockingEnabled A string containing a boolean that tells whether or not *Anonymous Blocking* is set on this *Delivery Service*; one of:

“true” Anonymized IP addresses are blocked by this *Delivery Service*

“false” Anonymized IP addresses are not blocked by this *Delivery Service*

See also:

Configure Anonymous Blocking

consistentHashQueryParameters A set of query parameters that Traffic Router should consider when determining a consistent hash for a given client request.

consistentHashRegex An optional regular expression that will ensure clients are consistently routed to a *cache server* based on matches to it.

coverageZoneOnly A string containing a boolean that tells whether or not this *Delivery Service* routes traffic based only on its *Coverage Zone File*

See also:

Geo Limit

deepCachingType A string that defines the *Deep Caching* setting of this *Delivery Service*

dispersion An object describing the “dispersion” - or number of *cache servers* within a single *Cache Group* across which the same content is spread - within the *Delivery Service*

limit The maximum number of *cache servers* in which the response to a single request URL will be stored

Note: If this is greater than the number of *cache servers* in the *Cache Group* chosen to service the request, then content will be spread across all of them. That is, it causes no problems.

shuffled A string containing a boolean that tells whether the *cache servers* chosen for content dispersion are chosen randomly or based on a consistent hash of the request URL; one of:

“false” *cache servers* will be chosen consistently

“true” *cache servers* will be chosen at random

domains An array of domains served by this *Delivery Service*

ecsEnabled A string containing a boolean from *EDNS0 Client Subnet Enabled* that tells whether EDNS0 client subnet is enabled on this *Delivery Service*; one of:

“false” EDNS0 client subnet is not enabled on this *Delivery Service*

“true” EDNS0 client subnet is enabled on this *Delivery Service*

geolocationProvider The name of a provider for IP-to-geographic-location mapping services - currently the only valid value is "maxmindGeolocationService"

ip6RoutingEnabled A string containing a boolean that defines the *IPv6 Routing Enabled* setting for this *Delivery Service*; one of:

“false” IPv6 traffic will not be routed by this *Delivery Service*

“true” IPv6 traffic will be routed by this *Delivery Service*

matchList An array of methods used by Traffic Router to determine whether or not a request can be serviced by this *Delivery Service*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

setNumber An integral, unique identifier for the set of types to which the **type** field belongs

type The name of the *Type* of match performed using **pattern** to determine whether or not to use this *Delivery Service*

HOST_REGEX Use the *Delivery Service* if `pattern` matches the *Host* HTTP header of an HTTP request, or the name requested for resolution in a DNS request

HEADER_REGEX Use the *Delivery Service* if `pattern` matches an HTTP header (both the name and value) in an HTTP request¹

PATH_REGEX Use the *Delivery Service* if `pattern` matches the request path of this *Delivery Service*'s URL Page 1544, 1

STEERING_REGEX Use the *Delivery Service* if `pattern` matches the *xml_id* of one of this *Delivery Service*'s “Steering” target *Delivery Services*

missLocation An object representing the default geographic coordinates to use for a client when lookup of their IP has failed in both the *Coverage Zone File* (and/or possibly the *Deep Coverage Zone File*) and the IP-to-geographic-location database

lat Geographic latitude as a floating point number

long Geographic longitude as a floating point number

protocol An object that describes how the *Delivery Service* ought to handle HTTP requests both with and without TLS encryption

acceptHttps A string containing a boolean that tells whether HTTPS requests should be normally serviced by this *Delivery Service*; one of:

“false” Refuse to service HTTPS requests

“true” Service HTTPS requests normally

redirectToHttps A string containing a boolean that tells whether HTTP re-

¹ These only apply to HTTP-routed *Delivery Services*

quests ought to be re-directed to use HTTPS; one of:

“false” Do not redirect unencrypted traffic; service it normally

“true” Respond to HTTP requests with instructions to use HTTPS instead

See also:

Protocol

regionalGeoBlocking A string containing a boolean that defines the *Regional Geoblocking* setting of this *Delivery Service*; one of:

“false” Regional Geographic Blocking is not used by this *Delivery Service*

“true” Regional Geographic Blocking is used by this *Delivery Service*

See also:

Configure Regional Geo-blocking (RGB)

requiredCapabilities An array of this Delivery Service’s *required capabilities*. If there are no required capabilities, this field is omitted.

routingName A string that is this *Delivery Service’s Routing Name*

soa An object defining the SOA record for the *Delivery Service’s* TLDs (defined in domains)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: [RFC 1035](#) dictates that this should always be less than `refresh`.

See also:

The Wikipedia page on [Start of Authority records](#).

sslEnabled A string containing a boolean that tells whether this *Delivery Service* uses SSL; one of:

“false” SSL is not used by this *Delivery Service*

“true” SSL is used by this *Delivery Service*

See also:

Protocol

topology The name of the *Topology* that this *Delivery Service* is assigned to. If the *Delivery Service* is not assigned to a topology, this field is omitted.

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

Note: This overrides `config.ttls`.

edgeLocations An object containing keys which are the names of Edge-Tier *Cache Groups* within the CDN

backupLocations An object that describes this *Cache Group's* *Fallbacks*

fallbackToClosest A string containing a boolean which defines the *Fallback to Closest* behavior of this *Cache Group*; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

list If this *Cache Group* has any *Fallbacks*, this key will appear and will be an array of those *Cache Groups’ Names*

latitude A floating point number that defines this *Cache Group’s Latitude*

localizationMethods An array of strings that represents this *Cache Group’s Localization Methods*

longitude A floating point number that defines this *Cache Group’s Longitude*

monitors An object containing keys which are the (short) hostnames of Traffic Monitors within this CDN

fqdn The FQDN of this Traffic Monitor

httpsPort The port number on which this Traffic Monitor listens for incoming HTTPS requests

ip6 This Traffic Monitor’s IPv6 address

ip This Traffic Monitor’s IPv4 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Monitor belongs

port The port number on which this Traffic Monitor listens for incoming HTTP requests

profile A string which is the *Name* of the *Profile* used by this Traffic Monitor

Note: For legacy reasons, this must always start with “RASCAL-“.

status The health status of this Traffic Monitor

See also:

Health Protocol

stats An object containing metadata information regarding the CDN

CDN_name The name of this CDN

date The UNIX epoch timestamp date in the Traffic Ops server’s own timezone

- tm_host** The FQDN of the Traffic Ops server
- tm_user** The username of the currently logged-in user
- tm_version** The full version number of the Traffic Ops server, including release number, git commit hash, and supported Enterprise Linux version
- topologies** An array of *Topologies* where each key is the name of that Topology.
- nodes** An array of the names of the *Edge-Tier Cache Groups* in this *Topology*. *Mid-Tier* Cache Groups in the topology are not included.
- trafficRouterLocations** An object containing keys which are the *names of Cache Groups* within the CDN which contain Traffic Routers
- backupLocations** An object that describes this *Cache Group's Fallbacks*
- fallbackToClosest** A string containing a boolean which defines this *Cache Group's Fallback to Closest* setting; one of:
- “false”** Do not fall back on the closest available *Cache Group*
 - “true”** Fall back on the closest available *Cache Group*
- latitude** A floating point number that defines this *Cache Group's Latitude*
- localizationMethods** An array of strings that represents this *Cache Group's Localization Methods*
- longitude** A floating point number that defines this *Cache Group's Longitude*

1097: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 27 May 2020 18:33:17
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→B5qdN9URIfu1lgQxPZ8YaaMvy2HMrzsnrpt6vF037yv60QiKCRyrUMX6wYsu7QW4YVa0gvmS2ya512YC0L
```

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Wed, 27 May 2020 17:33:17 GMT
Content-Length: 1360

{
  "response": {
    "config": {
      "api.cache-control.max-age": "10",
      "certificates.polling.interval": "300000",
      "consistent.dns.routing": "true",
      "coveragezone.polling.interval": "3600000",
      "coveragezone.polling.url": "https://static.infra.ciab.
→test:443/coverage-zone.json",
      "dnssec.dynamic.response.expiration": "300s",
      "dnssec.enabled": "false",
      "domain_name": "mycdn.ciab.test",
      "federationmapping.polling.interval": "60000",
      "federationmapping.polling.url": "https://${toHostname}/
→api/2.0/federations/all",
      "geolocation.polling.interval": "86400000",
      "geolocation.polling.url": "https://static.infra.ciab.
→test:443/GeoLite2-City.mmdb.gz",
      "keystore.maintenance.interval": "300",
      "neustar.polling.interval": "86400000",
      "neustar.polling.url": "https://static.infra.ciab.test:443/
→neustar.tar.gz",
      "soa": {
        "admin": "twelve_monkeys",
        "expire": "604800",
        "minimum": "30",
        "refresh": "28800",
        "retry": "7200"
      },
      "steeringmapping.polling.interval": "60000",
      "ttls": {
        "A": "3600",
        "AAAA": "3600",
        "DNSKEY": "30",
        "DS": "30",
        "NS": "3600",
        "SOA": "86400"
      },
      "zonemanager.cache.maintenance.interval": "300",
      "zonemanager.threadpool.scale": "0.50"
    },
  },
}
```

(continues on next page)

(continued from previous page)

```
"contentRouters": {
  "trafficrouter": {
    "api.port": "3333",
    "fqdn": "trafficrouter.infra.ciab.test",
    "httpsPort": 443,
    "ip": "172.26.0.15",
    "ip6": "",
    "location": "CDN_in_a_Box_Edge",
    "port": 80,
    "profile": "CCR_CIAB",
    "secure.api.port": "3443",
    "status": "ONLINE"
  }
},
"contentServers": {
  "edge": {
    "cacheGroup": "CDN_in_a_Box_Edge",
    "capabilities": [
      "RAM_DISK_STORAGE"
    ],
    "fqdn": "edge.infra.ciab.test",
    "hashCount": 999,
    "hashId": "edge",
    "httpsPort": 443,
    "interfaceName": "eth0",
    "ip": "172.26.0.3",
    "ip6": "",
    "locationId": "CDN_in_a_Box_Edge",
    "port": 80,
    "profile": "ATS_EDGE_TIER_CACHE",
    "routingDisabled": 0,
    "status": "REPORTED",
    "type": "EDGE"
  },
  "mid": {
    "cacheGroup": "CDN_in_a_Box_Mid",
    "capabilities": [
      "RAM_DISK_STORAGE"
    ],
    "fqdn": "mid.infra.ciab.test",
    "hashCount": 999,
    "hashId": "mid",
    "httpsPort": 443,
    "interfaceName": "eth0",
    "ip": "172.26.0.4",
    "ip6": "",
```

(continues on next page)

(continued from previous page)

```

        "locationId": "CDN_in_a_Box_Mid",
        "port": 80,
        "profile": "ATS_MID_TIER_CACHE",
        "routingDisabled": 0,
        "status": "REPORTED",
        "type": "MID"
    },
    },
    "deliveryServices": {
        "demo1": {
            "anonymousBlockingEnabled": "false",
            "consistentHashQueryParams": [
                "abc",
                "pdq",
                "xxx",
                "zyx"
            ],
            "coverageZoneOnly": "false",
            "deepCachingType": "NEVER",
            "dispersion": {
                "limit": 1,
                "shuffled": "true"
            },
            "domains": [
                "demo1.mycdn.ciab.test"
            ],
            "ecsEnabled": "false",
            "geolocationProvider": "maxmindGeolocationService",
            "ip6RoutingEnabled": "true",
            "matchsets": [
                {
                    "matchlist": [
                        {
                            "match-type": "HOST",
                            "regex": ".*\\.demo1\\.\\.\\.*"
                        }
                    ],
                    "protocol": "HTTP"
                }
            ],
            "missLocation": {
                "lat": 42,
                "long": -88
            },
            "protocol": {
                "acceptHttps": "true",

```

(continues on next page)

(continued from previous page)

```

        "redirectToHttps": "false"
    },
    "regionalGeoBlocking": "false",
    "requiredCapabilities": [
        "RAM_DISK_STORAGE"
    ],
    "routingName": "video",
    "soa": {
        "admin": "traffic_ops",
        "expire": "604800",
        "minimum": "30",
        "refresh": "28800",
        "retry": "7200"
    },
    "sslEnabled": "true",
    "topology": "my-topology",
    "ttls": {
        "A": "",
        "AAAA": "",
        "NS": "3600",
        "SOA": "86400"
    }
},
"edgeLocations": {
    "CDN_in_a_Box_Edge": {
        "backupLocations": {
            "fallbackToClosest": "true"
        },
        "latitude": 38.897663,
        "localizationMethods": [
            "GEO",
            "CZ",
            "DEEP_CZ"
        ],
        "longitude": -77.036574
    }
},
"monitors": {
    "trafficmonitor": {
        "fqdn": "trafficmonitor.infra.ciab.test",
        "httpsPort": 443,
        "ip": "172.26.0.14",
        "ip6": "",
        "location": "CDN_in_a_Box_Edge",
        "port": 80,
    }
}

```

(continues on next page)

(continued from previous page)

```

        "profile": "RASCAL-Traffic_Monitor",
        "status": "ONLINE"
    },
    "stats": {
        "CDN_name": "CDN-in-a-Box",
        "date": 1590600715,
        "tm_host": "trafficops.infra.ciab.test:443",
        "tm_user": "admin",
        "tm_version": "development"
    },
    "topologies": {
        "my-topology": {
            "nodes": [
                "CDN_in_a_Box_Edge"
            ]
        }
    },
    "trafficRouterLocations": {
        "CDN_in_a_Box_Edge": {
            "backupLocations": {
                "fallbackToClosest": "false"
            },
            "latitude": 38.897663,
            "localizationMethods": [
                "GEO",
                "CZ",
                "DEEP_CZ"
            ],
            "longitude": -77.036574
        }
    }
}

```

`cdns/{{name}}/snapshot/new`

GET

Retrieves the *pending Snapshot* for a CDN, which represents the current *configuration* of the CDN, **not** the current *operating state* of the CDN. The contents of this *Snapshot* are currently used by Traffic Monitor and Traffic Router.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 447: Request Path Parameters

Name	Description
name	The name of the CDN for which a <i>Snapshot</i> shall be returned

1098: Request Example

```
GET /api/4.0/cdns/CDN-in-a-Box/snapshot/new HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

config An object containing basic configurations on the actual CDN object

api.cache-control.max-age A string containing an integer which specifies the value of `max-age` in the *Cache-Control* header of some HTTP responses, likely the *Traffic Router API* responses

certificates.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for updated SSL certificates

consistent.dns.routing A string containing a boolean which indicates whether DNS routing will use a consistent hashing method or “round-robin”

“false” The “round-robin” method will be used to define DNS routing

“true” A consistent hashing method will be used to define DNS routing

coveragezone.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should check for a new Coverage Zone file

coveragezone.polling.url The URL where a *Coverage Zone File* may be requested by Traffic Routers

dnssec.dynamic.response.expiration A string containing a number and unit suffix that specifies the length of time for which dynamic responses to DNSSEC lookup queries should remain valid

dnssec.dynamic.concurrencylevel An integer that defines the size of the concurrency level (threads) of the Guava cache used by ZoneManager to store zone material

dnssec.dynamic.initialcapacity An integer that defines the initial size of the Guava cache, default is 10000. Too low of a value can lead to expensive resizing

dnssec.init.timeout An integer that defines the number of minutes to allow for zone generation, this bounds the zone priming activity

dnssec.enabled A string that tells whether or not the CDN uses DNSSEC; one of:

“false” DNSSEC is not used within this CDN

“true” DNSSEC is used within this CDN

domain_name A string that is the TLD served by the CDN

federationmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new federation mappings

federationmapping.polling.url The URL where Traffic Control components can request federation mappings

geolocation.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new IP-to-geographic-location mapping databases

geolocation.polling.url The URL where Traffic Control components can request IP-to-geographic-location mapping database files

keystore.maintenance.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Routers should refresh their zone caches

neustar.polling.interval A string containing an integer which specifies the interval, in seconds, on which other Traffic Control components should check for new “Neustar” databases

neustar.polling.url The URL where Traffic Control components can request “Neustar” databases

soa An object defining the SOA for the CDN's TLD (defined in `domain_name`)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to request the serial number from the master if the master does not respond

Note: **RFC 1035** dictates that this should always be less than `refresh`.

See also:

[The Wikipedia page on Start of Authority records.](#)

steeringmapping.polling.interval A string containing an integer which specifies the interval, in seconds, on which Traffic Control components should check for new steering mappings

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

zonemanager.cache.maintenance.interval A configuration option for the ZoneManager Java class of Traffic Router

zonemanager.threadpool.scale A configuration option for the ZoneManager Java class of Traffic Router

contentRouters An object containing keys which are the (short) hostnames of the Traffic Routers that serve requests for *Delivery Services* in this CDN

api.port A string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTP

secure.api.port An optionally present string containing the port number on which the *Traffic Router API* is served by this Traffic Router via HTTPS

fqdn This Traffic Router's FQDN

httpsPort The port number on which this Traffic Router listens for incoming HTTPS requests

ip This Traffic Router's IPv4 address

ip6 This Traffic Router's IPv6 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Router belongs

port The port number on which this Traffic Router listens for incoming HTTP requests

profile The *Name* of the *Profile* used by this Traffic Router

status The health status of this Traffic Router

See also:

Health Protocol

contentServers An object containing keys which are the (short) hostnames of the *Edge-tier cache servers* in the CDN; the values corresponding to those keys are routing information for said servers

cacheGroup A string that is the *Name* of the *Cache Group* to which the server belongs

capabilities An array of this *Cache Server's Server Capabilities*. If the Cache Server has no Server Capabilities, this field is omitted.

deliveryServices An object containing keys which are the names of *Delivery Services* to which this *cache server* is assigned; the values corresponding to those keys are arrays of FQDNs that resolve to this *cache server*

Note: Only *Edge-tier cache servers* can be assigned to a *Delivery Service*, and therefore this field will only be present when **type** is "EDGE".

fqdn The server's FQDN

hashCount The number of servers to be placed into a single “hash ring” in Traffic Router

hashId A unique string to be used as the key for hashing servers - as of version 3.0.0 of Traffic Control, this is always the same as the server's (short) hostname and only still exists for legacy compatibility reasons

httpsPort The port on which the *cache server* listens for incoming HTTPS requests

interfaceName The name of the main network interface device used by this *cache server*

ip6 The server's IPv6 address

ip The server's IPv4 address

locationId This field is exactly the same as `cacheGroup` and only exists for legacy compatibility reasons

port The port on which this *cache server* listens for incoming HTTP requests

profile The *Name* of the *Profile* used by the *cache server*

routingDisabled An integer representing the boolean concept of whether or not Traffic Routers should route client traffic to this *cache server*; one of:

0 Do not route traffic to this server

1 Route traffic to this server normally

status This *cache server*'s status

See also:

Health Protocol

type The *Type* of this *cache server*; which ought to be one of (but in practice need not be in certain special circumstances):

EDGE This is an *Edge-tier cache server*

MID This is a *Mid-tier cache server*

deliveryServices An object containing keys which are the *xml_ids* of all of the *Delivery Services* within the CDN

anonymousBlockingEnabled A string containing a boolean that tells whether or not *Anonymous Blocking* is set on this *Delivery Service*; one of:

“true” Anonymized IP addresses are blocked by this *Delivery Service*

“false” Anonymized IP addresses are not blocked by this *Delivery Service*

See also:

Configure Anonymous Blocking

consistentHashQueryParameters A set of query parameters that Traffic Router should consider when determining a consistent hash for a given client request.

consistentHashRegex An optional regular expression that will ensure clients are consistently routed to a *cache server* based on matches to it.

coverageZoneOnly A string containing a boolean that tells whether or not this *Delivery Service* routes traffic based only on its *Coverage Zone File*

See also:

Geo Limit

deepCachingType A string that defines the *Deep Caching* setting of this *Delivery Service*

dispersion An object describing the “dispersion” - or number of *cache servers* within a single *Cache Group* across which the same content is spread - within the *Delivery Service*

limit The maximum number of *cache servers* in which the response to a single request URL will be stored

Note: If this is greater than the number of *cache servers* in the *Cache Group* chosen to service the request, then content will be spread across all of them. That is, it causes no problems.

shuffled A string containing a boolean that tells whether the *cache servers* chosen for content dispersion are chosen randomly or based on a consistent hash of the request URL; one of:

“false” *cache servers* will be chosen consistently

“true” *cache servers* will be chosen at random

domains An array of domains served by this *Delivery Service*

ecsEnabled A string containing a boolean from *EDNS0 Client Subnet Enabled* that tells whether EDNS0 client subnet is enabled on this *Delivery Service*; one of:

“false” EDNS0 client subnet is not enabled on this *Delivery Service*

“true” EDNS0 client subnet is enabled on this *Delivery Service*

geolocationProvider The name of a provider for IP-to-geographic-location mapping services - currently the only valid value is "maxmindGeolocationService"

ip6RoutingEnabled A string containing a boolean that defines the *IPv6 Routing Enabled* setting for this *Delivery Service*; one of:

“false” IPv6 traffic will not be routed by this *Delivery Service*

“true” IPv6 traffic will be routed by this *Delivery Service*

matchList An array of methods used by Traffic Router to determine whether or not a request can be serviced by this *Delivery Service*

pattern A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)

setNumber An integral, unique identifier for the set of types to which the **type** field belongs

type The name of the *Type* of match performed using **pattern** to determine whether or not to use this *Delivery Service*

HOST_REGEX Use the *Delivery Service* if **pattern** matches the *Host* HTTP header of an HTTP request, or the name requested for resolution in a DNS request

HEADER_REGEX Use the *Delivery Service* if **pattern** matches an HTTP header (both the name

and value) in an HTTP request¹

PATH_REGEX Use the *Delivery Service* if pattern matches the request path of this *Delivery Service*'s URL Page 1544, 1

STEERING_REGEX Use the *Delivery Service* if pattern matches the *xml_id* of one of this *Delivery Service*'s “Steering” target *Delivery Services*

missLocation An object representing the default geographic coordinates to use for a client when lookup of their IP has failed in both the *Coverage Zone File* (and/or possibly the *Deep Coverage Zone File*) and the IP-to-geographic-location database

lat Geographic latitude as a floating point number

long Geographic longitude as a floating point number

protocol An object that describes how the *Delivery Service* ought to handle HTTP requests both with and without TLS encryption

acceptHttps A string containing a boolean that tells whether HTTPS requests should be normally serviced by this *Delivery Service*; one of:

“false” Refuse to service HTTPS requests

“true” Service HTTPS requests normally

redirectToHttps A string containing a boolean that tells whether HTTP requests ought to be re-directed to use HTTPS; one of:

“false” Do not redirect unencrypted traffic; service it normally

“true” Respond to HTTP requests with instructions to use HTTPS instead

¹ These only apply to HTTP-routed *Delivery Services*

See also:

Protocol

regionalGeoBlocking A string containing a boolean that defines the *Regional Geoblocking* setting of this *Delivery Service*; one of:

“false” Regional Geographic Blocking is not used by this *Delivery Service*

“true” Regional Geographic Blocking is used by this *Delivery Service*

See also:

Configure Regional Geo-blocking (RGB)

requiredCapabilities An array of this Delivery Service’s *required capabilities*. If there are no required capabilities, this field is omitted.

routingName A string that is this *Delivery Service’s Routing Name*

soa An object defining the SOA record for the *Delivery Service’s* TLDs (defined in domains)

admin The name of the administrator for this zone - i.e. the RNAME

Note: This rarely represents a proper email address, unfortunately.

expire A string containing an integer that sets the number of seconds after which secondary name servers should stop answering requests for this zone if the master does not respond

minimum A string containing an integer that sets the TTL - in seconds - of the record for the purpose of negative caching

refresh A string containing an integer that sets the number of seconds after which secondary name servers should query the master for the SOA record, to detect zone changes

retry A string containing an integer that sets the number of seconds after which secondary name servers should retry to re-

quest the serial number from the master
if the master does not respond

Note: [RFC 1035](#) dictates that this should always be less than `refresh`.

See also:

The [Wikipedia page on Start of Authority records](#).

sslEnabled A string containing a boolean that tells whether this *Delivery Service* uses SSL; one of:

“false” SSL is not used by this *Delivery Service*

“true” SSL is used by this *Delivery Service*

See also:

Protocol

topology The name of the *Topology* that this *Delivery Service* is assigned to. If the *Delivery Service* is not assigned to a topology, this field is omitted.

ttls An object that contains keys which are types of DNS records that have values which are strings containing integers that specify the time for which a response to the specific type of record request should remain valid

Note: This overrides `config.ttls`.

edgeLocations An object containing keys which are the names of Edge-Tier *Cache Groups* within the CDN

backupLocations An object that describes this *Cache Group's* *Fallbacks*

fallbackToClosest A string containing a boolean which defines the *Fallback to Closest* behavior of this *Cache Group*; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

list If this *Cache Group* has any *Fallbacks*, this key will appear and will be an array of those *Cache Groups' Names*

latitude A floating point number that defines this *Cache Group's Latitude*

localizationMethods An array of strings that represents this *Cache Group's Localization Methods*

longitude A floating point number that defines this *Cache Group's Longitude*

monitors An object containing keys which are the (short) hostnames of Traffic Monitors within this CDN

fqdn The FQDN of this Traffic Monitor

httpsPort The port number on which this Traffic Monitor listens for incoming HTTPS requests

ip6 This Traffic Monitor's IPv6 address

ip This Traffic Monitor's IPv4 address

location A string which is the *Name* of the *Cache Group* to which this Traffic Monitor belongs

port The port number on which this Traffic Monitor listens for incoming HTTP requests

profile A string which is the *Name* of the *Profile* used by this Traffic Monitor

Note: For legacy reasons, this must always start with "RASCAL-".

status The health status of this Traffic Monitor

See also:

Health Protocol

stats An object containing metadata information regarding the CDN

CDN_name The name of this CDN

date The UNIX epoch timestamp date in the Traffic Ops server's own timezone

tm_host The FQDN of the Traffic Ops server

tm_user The username of the currently logged-in user

tm_version The full version number of the Traffic Ops server, including release number, git commit hash, and supported Enterprise Linux version

topologies An array of *Topologies* where each key is the name of that Topology.

nodes An array of the names of the *Edge-Tier Cache Groups* in this *Topology*. *Mid-Tier* Cache Groups in the topology are not included.

trafficRouterLocations An object containing keys which are the *names of Cache Groups* within the CDN which contain Traffic Routers

backupLocations An object that describes this *Cache Group's Fallbacks*

fallbackToClosest A string containing a boolean which defines this *Cache Group's Fallback to Closest* setting; one of:

“false” Do not fall back on the closest available *Cache Group*

“true” Fall back on the closest available *Cache Group*

latitude A floating point number that defines this *Cache Group's Latitude*

localizationMethods An array of strings that represents this *Cache Group's Localization Methods*

longitude A floating point number that defines this *Cache Group's Longitude*

1099: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 27 May 2020 20:31:13.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→M6uhE2oPpjpTUR7gALsP0nM2CepD+VCAj4dj5Xnppo0G5zL31PQgiteD23q67r7/bq/
→JJpMvIvdaENVYFtrqQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 27 May 2020 19:31:13 GMT
Content-Length: 1374

{
  "response": {
```

(continues on next page)

(continued from previous page)

```

"config": {
  "api.cache-control.max-age": "10",
  "certificates.polling.interval": "300000",
  "consistent.dns.routing": "true",
  "coveragezone.polling.interval": "3600000",
  "coveragezone.polling.url": "https://static.infra.ciab.
→test:443/coverage-zone.json",
  "dnssec.dynamic.response.expiration": "300s",
  "dnssec.enabled": "false",
  "domain_name": "mycdn.ciab.test",
  "federationmapping.polling.interval": "60000",
  "federationmapping.polling.url": "https://${toHostname}/
→api/2.0/federations/all",
  "geolocation.polling.interval": "86400000",
  "geolocation.polling.url": "https://static.infra.ciab.
→test:443/GeoLite2-City.mmdb.gz",
  "keystore.maintenance.interval": "300",
  "neustar.polling.interval": "86400000",
  "neustar.polling.url": "https://static.infra.ciab.test:443/
→neustar.tar.gz",
  "soa": {
    "admin": "twelve_monkeys",
    "expire": "604800",
    "minimum": "30",
    "refresh": "28800",
    "retry": "7200"
  },
  "steeringmapping.polling.interval": "60000",
  "ttls": {
    "A": "3600",
    "AAAA": "3600",
    "DNSKEY": "30",
    "DS": "30",
    "NS": "3600",
    "SOA": "86400"
  },
  "zonemanager.cache.maintenance.interval": "300",
  "zonemanager.threadpool.scale": "0.50"
},
"contentServers": {
  "edge": {
    "cacheGroup": "CDN_in_a_Box_Edge",
    "capabilities": [
      "RAM_DISK_STORAGE"
    ],
    "fqdn": "edge.infra.ciab.test",

```

(continues on next page)

(continued from previous page)

```

        "hashCount": 999,
        "hashId": "edge",
        "httpsPort": 443,
        "interfaceName": "eth0",
        "ip": "172.26.0.3",
        "ip6": "",
        "locationId": "CDN_in_a_Box_Edge",
        "port": 80,
        "profile": "ATS_EDGE_TIER_CACHE",
        "status": "REPORTED",
        "type": "EDGE",
        "routingDisabled": 0
    },
    "mid": {
        "cacheGroup": "CDN_in_a_Box_Mid",
        "capabilities": [
            "RAM_DISK_STORAGE"
        ],
        "fqdn": "mid.infra.ciab.test",
        "hashCount": 999,
        "hashId": "mid",
        "httpsPort": 443,
        "interfaceName": "eth0",
        "ip": "172.26.0.4",
        "ip6": "",
        "locationId": "CDN_in_a_Box_Mid",
        "port": 80,
        "profile": "ATS_MID_TIER_CACHE",
        "status": "REPORTED",
        "type": "MID",
        "routingDisabled": 0
    }
},
"contentRouters": {
    "trafficrouter": {
        "api.port": "3333",
        "fqdn": "trafficrouter.infra.ciab.test",
        "httpsPort": 443,
        "ip": "172.26.0.15",
        "ip6": "",
        "location": "CDN_in_a_Box_Edge",
        "port": 80,
        "profile": "CCR_CIAB",
        "secure.api.port": "3443",
        "status": "ONLINE"
    }
}

```

(continues on next page)

(continued from previous page)

```

},
"deliveryServices": {
  "demo1": {
    "anonymousBlockingEnabled": "false",
    "consistentHashQueryParams": [
      "abc",
      "pdq",
      "xxx",
      "zyx"
    ],
    "coverageZoneOnly": "false",
    "deepCachingType": "NEVER",
    "dispersion": {
      "limit": 1,
      "shuffled": "true"
    },
    "domains": [
      "demo1.mycdn.ciab.test"
    ],
    "ecsEnabled": "false",
    "geolocationProvider": "maxmindGeolocationService",
    "ip6RoutingEnabled": "true",
    "matchsets": [
      {
        "protocol": "HTTP",
        "matchlist": [
          {
            "regex": ".*\\.demo1\\.\\.\\.*",
            "match-type": "HOST"
          }
        ]
      }
    ],
    "missLocation": {
      "lat": 42,
      "long": -88
    },
    "protocol": {
      "acceptHttps": "true",
      "redirectToHttps": "false"
    },
    "regionalGeoBlocking": "false",
    "requiredCapabilities": [
      "RAM_DISK_STORAGE"
    ],
    "routingName": "video",

```

(continues on next page)

(continued from previous page)

```

    "soa": {
      "admin": "traffic_ops",
      "expire": "604800",
      "minimum": "30",
      "refresh": "28800",
      "retry": "7200"
    },
    "sslEnabled": "true",
    "topology": "my-topology",
    "ttls": {
      "A": "",
      "AAAA": "",
      "NS": "3600",
      "SOA": "86400"
    }
  },
  "edgeLocations": {
    "CDN_in_a_Box_Edge": {
      "latitude": 38.897663,
      "longitude": -77.036574,
      "backupLocations": {
        "fallbackToClosest": "true"
      },
      "localizationMethods": [
        "GEO",
        "CZ",
        "DEEP_CZ"
      ]
    }
  },
  "trafficRouterLocations": {
    "CDN_in_a_Box_Edge": {
      "latitude": 38.897663,
      "longitude": -77.036574,
      "backupLocations": {
        "fallbackToClosest": "false"
      },
      "localizationMethods": [
        "GEO",
        "CZ",
        "DEEP_CZ"
      ]
    }
  },
  "monitors": {

```

(continues on next page)

(continued from previous page)

```

        "trafficmonitor": {
            "fqdn": "trafficmonitor.infra.ciab.test",
            "httpsPort": 443,
            "ip": "172.26.0.14",
            "ip6": "",
            "location": "CDN_in_a_Box_Edge",
            "port": 80,
            "profile": "RASCAL-Traffic_Monitor",
            "status": "ONLINE"
        },
    },
    "stats": {
        "CDN_name": "CDN-in-a-Box",
        "date": 1590607873,
        "tm_host": "trafficops.infra.ciab.test:443",
        "tm_user": "admin",
        "tm_version": "development"
    },
    "topologies": {
        "my-topology": {
            "nodes": [
                "CDN_in_a_Box_Edge"
            ]
        }
    }
}

```

cdns/routing

GET

Retrieves the aggregated routing percentages across all CDNs. This is accomplished by polling stats from all online Traffic Routers via the `/crs/stats` route.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available

Response Structure

- cz** The percent of requests to online Traffic Routers that were satisfied by a *Coverage Zone File*
- deepCz** The percent of requests to online Traffic Routers that were satisfied by a *Deep Coverage Zone File*
- dsr** The percent of requests to online Traffic Routers that were satisfied by sending the client to an overflow *Delivery Service*
- err** The percent of requests to online Traffic Routers that resulted in an error
- fed** The percent of requests to online Traffic Routers that were satisfied by sending the client to a federated CDN
- geo** The percent of requests to online Traffic Routers that were satisfied using 3rd party geographic IP mapping
- miss** The percent of requests to online Traffic Routers that could not be satisfied
- regionalAlternate** The percent of requests to online Traffic Routers that were satisfied by sending the client to the alternate, Regional Geo-blocking URL
- regionalDenied** The percent of requests to online Traffic Routers that were denied due to geographic location policy
- staticRoute** The percent of requests to online Traffic Routers that were satisfied with *Static DNS Entries*

1100: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 14 Nov 2018 21:29:32 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
↪GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
↪7LjytwKyRzSKM4cRIol40MIJxApFpTWJaSK73rbtUIQdASZjI64XxLVzZP00GRU7XeJ22YKUyQ30qbKHD
```

(continues on next page)

(continued from previous page)

Content-Length: 130

```
{ "response": {
  "cz": 79,
  "deepCz": 0.50,
  "dsr": 0,
  "err": 0,
  "fed": 0.25,
  "geo": 20,
  "miss": 0.25,
  "regionalAlternate": 0,
  "regionalDenied": 0,
  "staticRoute": 0
}}
```

consistenthash

Test Pattern-Based Consistent Hashing for a *Delivery Service* using a regular expression and a request path

POST

Queries database for an active Traffic Router on a given CDN and sends GET request to get the resulting path to consistent hash with a given regex and request path.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

regex The regular expression to apply to the request path to get a resulting path that will be used for consistent hashing

requestPath The request path to use to test the regular expression against

cdnId The unique identifier of a CDN that will be used to query for an active Traffic Router

1101: Request Example

```
POST /api/4.0/consistenthash HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.54.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
Content-Length: 80
Content-Type: application/x-www-form-urlencoded

{"regex":"/.*?(/.*?/).*(m3u8)","requestPath":"/test/path/asset.m3u8",
  ↪ "cdnId":2}
```

Response Structure

resultingPathToConsistentHash The resulting path that Traffic Router will use for consistent hashing

consistentHashRegex The regex used by Traffic Router derived from POST ‘regex’ parameter

requestPath The request path used by Traffic Router to test regex against

1102: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type, ↵
  ↪ Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54. ↵
  ↪ GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ↵
  ↪ QMDFOnUfqH4TcZ4YnUQyqnXDier0YiUMIfwBGDcT7ySjw9uASBGsLQW35lpnKFi4as0vYlHuSSGpe4hHG
X-Server-Name: traffic_ops_golang/
Date: Tue, 12 Feb 2019 21:32:05 GMT
Content-Length: 142

{ "response": {
  "resultingPathToConsistentHash":"/path/m3u8",
  "consistentHashRegex":"/.*?(/.*?/).*(m3u8)",
  "requestPath":"/test/path/asset.m3u8"
}}
```

coordinates

GET

Gets a list of all coordinates in the Traffic Ops database

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 448: Request Query Parameters

Name	Re- quired	Description
id	no	Return only coordinates that have this integral, unique identifier
name	no	Return only coordinates with this name
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

id Integral, unique, identifier for this coordinate pair

lastUpdated The time and date at which this entry was last updated, in a ctime-like format

latitude Latitude of the coordinate

longitude Longitude of the coordinate

name The name of the coordinate - typically this just reflects the name of the Cache Group for which the coordinate was created

1103: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

(continued from previous page)

```

Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Y2vxC3hpxIg6aRNBBT7i2hbAViIJp+dJoqHIzu3acFM+vGay/
    ↳I5E+eZYOC9RY8hcJPrKNXysZOD8DOb9KsFgaw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:32:28 GMT
Content-Length: 942

```

```

{ "response": [
  {
    "id": 1,
    "name": "from_cachegroup_TRAFFIC_ANALYTICS",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 2,
    "name": "from_cachegroup_TRAFFIC_OPS",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 3,
    "name": "from_cachegroup_TRAFFIC_OPS_DB",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 4,
    "name": "from_cachegroup_TRAFFIC_PORTAL",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 5,
    "name": "from_cachegroup_TRAFFIC_STATS",
    "latitude": 38.897663,

```

(continues on next page)

(continued from previous page)

```

    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 6,
    "name": "from_cachegroup_CDN_in_a_Box_Mid",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:04+00"
  },
  {
    "id": 7,
    "name": "from_cachegroup_CDN_in_a_Box_Edge",
    "latitude": 38.897663,
    "longitude": -77.036574,
    "lastUpdated": "2018-10-24 16:07:05+00"
  }
]

```

POST

Creates a new coordinate pair

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the new coordinate

latitude The desired latitude of the new coordinate (must be on the interval [-180, 180])

longitude The desired longitude of the new coordinate (must be on the interval [-90, 90])

1104: Request Example

```

POST /api/4.0/coordinates HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 47

```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
```

```
{"name": "test", "latitude": 0, "longitude": 0}
```

Response Structure

id Integral, unique, identifier for the newly created coordinate pair

lastUpdated The time and date at which this entry was last updated, in a ctime-like format

latitude Latitude of the newly created coordinate

longitude Longitude of the newly created coordinate

name The name of the coordinate

1105: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 7pWdeZyIIXE1P7o/
→JVon+5eSCbDw+FGamAzdXzWHXJ8IhF+Vh+/
→tWfCkzHYw3rP2kBVwZu+gqLffjQpBCMjt7A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 17:48:55 GMT
Content-Length: 165

{ "alerts": [
  {
    "text": "coordinate was created.",
    "level": "success"
  }
],
"response": {
  "id": 9,
  "name": "test",
  "latitude": 0,
  "longitude": 0,
  "lastUpdated": "2018-11-15 17:48:55+00"
```

(continues on next page)

(continued from previous page)

```
}}
```

PUT

Updates a coordinate

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 449: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the coordinate to edit

name The name of the new coordinate

latitude The desired new latitude of the coordinate (must be on the interval [-180, 180])

longitude The desired new longitude of the coordinate (must be on the interval [-90, 90])

1106: Request Example

```
PUT /api/4.0/coordinates?id=9 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 48
Content-Type: application/json

{"name": "quest", "latitude": 0, "longitude": 0}
```

Response Structure

- id** Integral, unique, identifier for the coordinate pair
- lastUpdated** The time and date at which this entry was last updated, in a ctime-like format
- latitude** Latitude of the coordinate
- longitude** Longitude of the coordinate
- name** The name of the coordinate

1107: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳zd03Uvbnv8EbSZZ75Xp5tnnYStZsZTdyPxXnoqK4QZ5WhELLPL8iHlRf0aiLTbrUWUeJ8ue2HRz6aBS/
    ↳iXCCGA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 17:54:30 GMT
Content-Length: 166

{ "alerts": [
  {
    "text": "coordinate was updated.",
    "level": "success"
  }
]}
```

(continues on next page)

(continued from previous page)

```
] ,
"response": {
  "id": 9,
  "name": "quest",
  "latitude": 0,
  "longitude": 0,
  "lastUpdated": "2018-11-15 17:54:30+00"
}}
```

DELETE

Deletes a coordinate

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 450: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the coordinate to delete

Response Structure

1108: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 82x/Wdckqgk4LN5LI1ZfBJ26xkDrUVUGDjs5QFa/
  ↳Lzap7dU30Zkjv8XW41xeFYj8PDmxHIpb7hiV0bvLaxnEDA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 15 Nov 2018 17:57:42 GMT
Content-Length: 65
```

(continues on next page)

(continued from previous page)

```
{ "alerts": [  
  {  
    "text": "coordinate was deleted.",  
    "level": "success"  
  }  
]}
```

current_stats

An API endpoint that returns current statistics for each CDN and an aggregate across them all.

GET

Retrieves current stats for each CDN. Also includes aggregate stats across them.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

No parameters available.

1109: Request Example

```
GET /api/4.0/current_stats HTTP/1.1  
Host: trafficops.infra.ciab.test  
User-Agent: curl/7.47.0  
Accept: */*  
Cookie: mojolicious=...
```

Response Structure

cdn The name of the CDN

connections Current number of TCP connections maintained

capacity 85 percent capacity of the CDN in Gps

bandwidth The total amount of bandwidth in Gbs

Note: If `cdn` name is total and capacity is omitted it represents the aggregate stats across CDNs

1110: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=; Path=/; HttpOnly
Whole-Content-Sha512:
    ↳Rs3wgd7v5dP0b0Qs4I3J1q6mnWIMSM2AKSAWirK1kymvDYOoFISArF7Kkypgy10I34yn7FtFdMh6U7ABa
X-Server-Name: traffic_ops_golang/
Date: Thu, 14 Nov 2019 15:35:31 GMT
Content-Length: 138

{"response": {
  "currentStats": [
    {
      "bandwidth": null,
      "capacity": null,
      "cdn": "ALL",
      "connections": null
    },
    {
      "bandwidth": 0.000104,
      "capacity": 17,
      "cdn": "CDN-in-a-Box",
      "connections": 4
    },
    {
      "bandwidth": 0.000104,
      "cdn": "total",
      "connections": 4
    }
  ]
}}
```

dbdump

Caution: This is an extremely dangerous thing to do, as it exposes the entirety of the database, including possibly sensitive information. Administrators and systems engineers are advised to instead use database-specific tools to make server transitions more securely.

Dumps the Traffic Ops database as an SQL script that should recreate its schema and contents exactly.

Implementation Detail

The script is output using the *pg_dump(1)* utility, and is thus compatible for use with the *pg_restore(1)* utility.

GET

Fetches the database dump.

Auth. Required Yes

Roles Required “admin”

Response Type undefined - outputs an SQL script, not JSON

Request Structure

No parameters available

1111: Request Example

```
GET /api/4.0/dbdump HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1112: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/sql
Content-Disposition: attachment
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳YwvPB0ZToyzT8ilBnDlWWdwV+E3f2Xgus10KrkNaipQqgrw5zGwq0rC1U9TZ8Zl6kAGcRZgCYnr1EWfHX
X-Server-Name: traffic_ops_golang/
Date: Mon, 09 Sep 2019 21:08:28 GMT
Transfer-Encoding: chunked

-- Actual text omitted - it's huge
```

deliveryservice_request_comments

GET

Gets delivery service request comments.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 451: Request Query Parameters

Name	Re-quired	Description
author	no	Filter for <i>Delivery Service Request</i> comments submitted by the user identified by this username
authorId	no	Filter for <i>Delivery Service Request</i> comments submitted by the user identified by this integral, unique identifier
deliveryServiceRequestId	no	Filter for <i>Delivery Service Request</i> comments submitted for the delivery service identified by this integral, unique identifier
id	no	Filter for the <i>Delivery Service Request</i> comment identified by this integral, unique identifier

1113: Request Example

```
GET /api/4.0/deliveryservice_request_comments HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

- author** The username of the user who created the comment.
- authorId** The integral, unique identifier of the user who created the comment.
- deliveryServiceRequestId** The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.
- id** The integral, unique identifier of the *DSR* comment.
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- value** The text of the comment that was posted.
- xmlId** This is the xmlId value that you provided in the request.

1114: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:00:26.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→RaJZS1XFJ4oIxVKyyDjTuoQY7gPOmm5EuIL4AgHpyQpuaaNviw0XhGC4V/AKf/
→Ws6zXLgIUc40yvMsTxnriIww==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:00:26 GMT
Content-Length: 207

{
  "response": [
    {
      "authorId": 2,
      "author": "admin",
      "deliveryServiceRequestId": 2,
      "id": 3,
      "lastUpdated": "2020-02-24 19:59:46+00",
      "value": "Changing to a different origin for now.",
      "xmlId": "demo1"
    },
    {
      "authorId": 2,
      "author": "admin",
      "deliveryServiceRequestId": 2,
      "id": 4,
      "lastUpdated": "2020-02-24 19:59:55+00",
      "value": "Using HTTPS.",
      "xmlId": "demo1"
    }
  ]
}
```

POST

Allows user to create a *Delivery Service Request* comment.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

deliveryServiceRequestId The integral, unique identifier of the delivery service that you are commenting on.

value The comment text itself.

xmlId This can be any string. It is not validated or used, though it is returned in the response.

1115: Request Example

```
POST /api/4.0/deliveryservice_request_comments HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 111

{
  "deliveryServiceRequestId": 2,
  "value": "Does anyone have time to review my delivery service_
↪request?"
}
```

Response Structure

author The username of the user who created the comment.

authorId The integral, unique identifier of the user who created the comment.

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

id The integral, unique identifier of the *DSR* comment.

lastUpdated The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*

value The text of the comment that was posted.

xmlId This is the xmlId value that you provided in the request.

1116: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:02:20 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: LiakFP6L7PrnF05kLXftx7WQoKn3bGpIJT5N15PvNG2sHridRMV3k23eRJM66ET0LcRfMOrQgRiydE+Xg
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:02:20 GMT
Content-Length: 223

{
  "alerts": [
    {
      "text": "deliveryservice_request_comment was created.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": 2,
    "author": null,
    "deliveryServiceRequestId": 2,
    "id": 6,
    "lastUpdated": "2020-02-24 20:02:20+00",
    "value": "Does anyone have time to review my delivery service request?",
    "xmlId": null
  }
}
```

PUT

Updates a delivery service request comment.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

value The comment text itself.

xmlId This can be any string. It is not validated or used, though it is returned in the response.

Table 452: Request Query Parameters

Parameter	Required	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> comment that you wish to update.

1117: Request Example

```
PUT /api/4.0/deliveryservice_request_comments?id=6 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 166

{
  "deliveryServiceRequestId": 2,
  "value": "Update: We no longer need this, feel free to reject.\n\
→nDoes anyone have time to review my delivery service request?"
}
```

Response Structure

author The username of the user who created the comment.

authorId The integral, unique identifier of the user who created the comment.

deliveryServiceRequestId The integral, unique identifier of the *Delivery Service Request* that the comment was posted on.

id The integral, unique identifier of the *DSR* comment.

lastUpdated The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*

value The text of the comment that was posted.

xmlId This is the xmlId value that you provided in the request.

1118: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:05:46
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳RalS34imPw7c42nlnu5eTuv6FSxuGcAvxEdeIyNma1zpE3ZojAMFbhj8qi1s+hOVDYybfFPzMz82c+xc1
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:05:46 GMT
Content-Length: 255

{
  "alerts": [
    {
      "text": "deliveryservice_request_comment was updated.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": null,
    "author": null,
    "deliveryServiceRequestId": 2,
    "id": 6,
    "lastUpdated": "2020-02-24 20:05:46+00",
    "value": "Update: We no longer need this, feel free to reject.\n
    ↳\nDoes anyone have time to review my delivery service request?",
    "xmlId": null
  }
}

```

DELETE

Deletes a delivery service request comment.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type undefined

Request Structure

Table 453: Request Query Parameters

Parameter	Required	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> comment that you wish to delete.

1119: Request Example

```
DELETE /api/4.0/deliveryservice_request_comments?id=6 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

1120: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 21:07:40
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 10pGzqeIh/1jAx85mz3MI/
→5A1i1g5beTSLtfvgcfQmCjNKQvOMs/4TLviuVzOCRRrEIPmNcjy35tmvfxwlv7RMQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 20:07:40 GMT
Content-Length: 101

{
  "alerts": [
    {
      "text": "deliveryservice_request_comment was deleted.",
      "level": "success"
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```
    ]  
  }
```

deliveryservice_requests

GET

Retrieves *Delivery Service Requests*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 454: Request Query Parameters

Name	Re-quired	Description
as-signee	no	Filter for <i>Delivery Service Requests</i> that are assigned to the user identified by this username.
as-signeeId	no	Filter for <i>Delivery Service Requests</i> that are assigned to the user identified by this integral, unique identifier
author	no	Filter for <i>Delivery Service Requests</i> submitted by the user identified by this username
authorId	no	Filter for <i>Delivery Service Requests</i> submitted by the user identified by this integral, unique identifier
changeType	no	Filter for <i>Delivery Service Requests</i> of the change type specified. Can be create, update, or delete.
createdAt	no	Filter for <i>Delivery Service Requests</i> created on a certain date/time. Value must be RFC 3339 compliant. Eg. 2019-09-19T19:35:38.828535Z
id	no	Filter for the <i>Delivery Service Requests</i> identified by this integral, unique identifier.
status	no	Filter for <i>Delivery Service Requests</i> whose status is the status specified. The status can be draft, submitted, pending, rejected, or complete.
xmlId	no	Filter for <i>Delivery Service Requests</i> that have the given <i>xml_id</i> .
orderBy	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>n</i> th page of results, where “ <i>n</i> ” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

New in version ATCv6: The *createdAt* query parameter was added to this in endpoint across all API versions in ATC version 6.0.0.

1121: Request Example

```
GET /api/4.0/deliveryservice_requests?status=draft HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

The response is an array of representations of *Delivery Service Requests*.

1122: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:14:07
    ↳GMT; Max-Age=3600; HttpOnly
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:14:07 GMT
Content-Length: 872

{ "response": [{
  "authorId": 2,
  "author": "admin",
  "changeType": "update",
  "createdAt": "2020-02-24 19:11:12+00",
  "id": 1,
  "lastEditedBy": "admin",
  "lastEditedById": 2,
  "lastUpdated": "2020-02-24 19:11:12+00",
  "requested": {
    "active": false,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "Demo 1",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "firstHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
```

(continues on next page)

(continued from previous page)

```

"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "0001-01-01T00:00:00Z",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"matchList": [
    {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"topology": null,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [

```

(continues on next page)

(continued from previous page)

```

        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false,
    "tlsVersions": null
},
"status": "draft"
}]}
```

POST

Creates a new *Delivery Service Request*. “Closed” *Delivery Service Requests* cannot be created, an existing *Delivery Service Request* must be placed into a closed *Status*. A *Delivery Service Request* to create, modify or delete a *Delivery Service* cannot be created if an open *Delivery Service Request* exists for a *Delivery Service* with the same *xml_id*. Because of this, *Delivery Service Requests* cannot be used to change a *Delivery Service*’s *xml_id*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

The request must be a well-formed representation of a *Delivery Service Request*, without any response-only fields, of course.

1123: Request Example

```

POST /api/4.0/deliveryservice_requests HTTP/1.1
User-Agent: python-requests/2.22.0
```

(continues on next page)

(continued from previous page)

```

Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 1979

{
  "changeType": "update",
  "status": "draft",
  "requested": {
    "active": false,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "Demo 1",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "firstHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 1,
    "infoUrl": null,
    "initialDispersion": 1,
    "innerHeaderRewrite": null,
    "ipv6RoutingEnabled": true,
    "lastHeaderRewrite": null,
    "lastUpdated": "2020-02-13T16:43:54Z",
    "logsEnabled": true,
    "longDesc": "Apachecon North America 2018",
    "matchList": [
      {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
      }
    ]
  }
}

```

(continues on next page)

(continued from previous page)

```

    }
  ],
  "maxDnsAnswers": null,
  "midHeaderRewrite": null,
  "missLat": 42,
  "missLong": -88,
  "multiSiteOrigin": false,
  "originShield": null,
  "orgServerFqdn": "http://origin.infra.ciab.test",
  "profileDescription": null,
  "profileId": null,
  "profileName": null,
  "protocol": 2,
  "qstringIgnore": 0,
  "rangeRequestHandling": 0,
  "regexRemap": null,
  "regionalGeoBlocking": false,
  "remapText": null,
  "routingName": "video",
  "signed": false,
  "sslKeyVersion": 1,
  "tenantId": 1,
  "type": "HTTP",
  "typeId": 1,
  "xmlId": "demo1",
  "exampleURLs": [
    "http://video.demo1.mycdn.ciab.test",
    "https://video.demo1.mycdn.ciab.test"
  ],
  "deepCachingType": "NEVER",
  "fqPacingRate": null,
  "signingAlgorithm": null,
  "tenant": "root",
  "topology": null,
  "trResponseHeaders": null,
  "trRequestHeaders": null,
  "consistentHashRegex": null,
  "consistentHashQueryParams": [
    "abc",
    "pdq",
    "xxx",
    "zyx"
  ],
  ],
  "maxOriginConnections": 0,
  "ecsEnabled": false,
  "serviceCategory": null,

```

(continues on next page)

(continued from previous page)

```

    "tlsVersions": null
  }
}

```

Response Structure

The response will be a representation of the created *Delivery Service Request*.

1124: Response Example

```

HTTP/1.1 201 CREATED
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:11:12
    ↳GMT; Max-Age=3600; HttpOnly
Location: /api/4.0/deliveryservice_requests/2
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:11:12 GMT
Content-Length: 901

{
  "alerts": [
    {
      "text": "deliveryservice_request was created.",
      "level": "success"
    }
  ],
  "response": {
    "authorId": 2,
    "author": null,
    "changeType": "update",
    "createdAt": null,
    "id": 2,
    "lastEditedBy": null,
    "lastEditedById": 2,
    "lastUpdated": "2020-02-24 19:11:12+00",
    "requested": {
      "active": false,
      "anonymousBlockingEnabled": false,
      "cacheurl": null,

```

(continues on next page)

(continued from previous page)

```

"ccrDnsTtl": null,
"cdnId": 2,
"cdnName": "CDN-in-a-Box",
"checkPath": null,
"displayName": "Demo 1",
"dnsBypassCname": null,
"dnsBypassIp": null,
"dnsBypassIp6": null,
"dnsBypassTtl": null,
"dscp": 0,
"edgeHeaderRewrite": null,
"firstHeaderRewrite": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "0001-01-01T00:00:00Z",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"matchList": [
    {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,

```

(continues on next page)

(continued from previous page)

```

    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": 1,
    "tenantId": 1,
    "topology": null,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false,
    "tlsVersions": null
},
"original": {
    "active": true,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "Demo 1",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,

```

(continues on next page)

(continued from previous page)

```

"dnstBypassTtl": null,
"dscp": 0,
"edgeHeaderRewrite": null,
"firstHeaderRewrite": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "2020-02-13T16:43:54Z",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"matchList": [
    {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,

```

(continues on next page)

(continued from previous page)

```

        "tenantId": 1,
        "type": "HTTP",
        "typeId": 1,
        "xmlId": "demo1",
        "exampleURLs": [
            "http://video.demo1.mycdn.ciab.test",
            "https://video.demo1.mycdn.ciab.test"
        ],
        "deepCachingType": "NEVER",
        "fqPacingRate": null,
        "signingAlgorithm": null,
        "tenant": "root",
        "topology": null,
        "trResponseHeaders": null,
        "trRequestHeaders": null,
        "consistentHashRegex": null,
        "consistentHashQueryParams": [
            "abc",
            "pdq",
            "xxx",
            "zyx"
        ],
        "maxOriginConnections": 0,
        "ecsEnabled": false,
        "serviceCategory": null,
        "tlsVersions": null
    },
    "status": "draft"
}

```

PUT

Updates an existing *Delivery Service Request*. Note that “closed” *Delivery Service Requests* are uneditable.

See also:

The proper way to change a *Delivery Service Request*’s *Status* is by using the *deliveryservice_requests/{ID}/status* endpoint’s PUT handler.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

Table 455: Request Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> that you want to update.

The request body must be a representation of a *Delivery Service Request* without any response-only fields.

1125: Request Example

```
PUT /api/4.0/deliveryservice_requests?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 2256
```

```
{
  "changeType": "update",
  "requested": {
    "active": true,
    "cdnId": 2,
    "ccrDnsTtl": 30,
    "deepCachingType": "NEVER",
    "displayName": "Demo 1 but I modified the DSR",
    "dscp": 0,
    "geoLimit": 0,
    "geoProvider": 0,
    "initialDispersion": 3,
    "logsEnabled": false,
    "longDesc": "long desc",
    "regionalGeoBlocking": false,
    "tenantId": 1,
    "typeId": 8,
    "xmlId": "demo1",
    "id": 1
  },
  "status": "draft"
}
```

Response Structure

The response is a full representation of the edited *Delivery Service Request*.

1126: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:36:16
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +W0vFm96yFkZUJqa0GAX7uzIpRKh/
    ↳ohyBm0uH3egpiERTcxy50fVVtoP3h8Ee2teLu8KFooDYXJ6rpQg6UhbNQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:36:16 GMT
Content-Length: 913

{ "alerts": [{
    "text": "Delivery Service Request #2 updated",
    "level": "success"
}],
  "response": {
    "assignee": null,
    "author": "",
    "changeType": "update",
    "createdAt": "2020-09-25T06:23:30.683058Z",
    "id": null,
    "lastEditedBy": "admin",
    "lastUpdated": "2020-09-25T02:38:04.180237Z",
    "original": {
      "active": true,
      "anonymousBlockingEnabled": false,
      "cacheurl": null,
      "ccrDnsTtl": null,
      "cdnId": 2,
      "cdnName": "CDN-in-a-Box",
      "checkPath": null,
      "displayName": "Demo 1",
      "dnsBypassCname": null,
      "dnsBypassIp": null,
      "dnsBypassIp6": null,
      "dnsBypassTtl": null,
```

(continues on next page)

(continued from previous page)

```
"dscp": 0,
"edgeHeaderRewrite": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"ipv6RoutingEnabled": true,
"lastUpdated": "2020-09-25T02:09:54Z",
"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
```

(continues on next page)

(continued from previous page)

```

    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false,
    "rangeSliceBlockSize": null,
    "topology": "demo1-top",
    "firstHeaderRewrite": null,
    "innerHeaderRewrite": null,
    "lastHeaderRewrite": null,
    "serviceCategory": null,
    "tlsVersions": null
},
"requested": {
    "active": true,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": 30,
    "cdnId": 2,
    "cdnName": null,
    "checkPath": null,
    "displayName": "Demo 1 but I modified the DSR",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,

```

(continues on next page)

(continued from previous page)

```
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 3,
"ipv6RoutingEnabled": null,
"lastUpdated": null,
"logsEnabled": false,
"longDesc": "long desc",
"matchList": null,
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": null,
"missLong": null,
"multiSiteOrigin": null,
"originShield": null,
"orgServerFqdn": null,
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": null,
"qstringIgnore": null,
"rangeRequestHandling": null,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "cdn",
"signed": false,
"sslKeyVersion": null,
"tenantId": 1,
"type": null,
"typeId": 8,
"xmlId": "demo1",
"exampleURLs": null,
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": null,
"trResponseHeaders": null,
"trRequestHeaders": null,
"consistentHashRegex": null,
"consistentHashQueryParams": null,
"maxOriginConnections": 0,
"ecsEnabled": false,
"rangeSliceBlockSize": null,
```

(continues on next page)

(continued from previous page)

```

    "topology": null,
    "firstHeaderRewrite": null,
    "innerHeaderRewrite": null,
    "lastHeaderRewrite": null,
    "serviceCategory": null,
    "tlsVersions": null
  },
  "status": "draft"
}}
```

DELETE

Deletes a *Delivery Service Request*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

Table 456: Request Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the <i>Delivery Service Request</i> that you want to delete.

1127: Request Example

```
DELETE /api/4.0/deliveryservice_requests?id=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

The response is a full representation of the deleted *Delivery Service Request*.

1128: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 20:48:55
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳jNCbNo8Tw+JMMaWpAYQgntSXPq2Xuj+n2zSEVRaDQFWMV1SYbT9djes6SPdwiBoKq6W0lNE04h0E92jBV
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 19:48:55 GMT
Content-Length: 96

{
  "alerts": [
    {
      "text": "deliveryservice_request was deleted.",
      "level": "success"
    }
  ]
}
```

deliveryservice_requests/{{ID}}/assign

Assign a *Delivery Service Request* to a user.

GET

New in version 4.0.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 457: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service Request</i> for which assignment is being retrieved

1129: Request Example

```
GET /api/4.0/deliveryservice_requests/1/assign HTTP/1.1
User-Agent: python-requests/2.24.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

The response is the username of the user to whom the *Delivery Service Request* is assigned - or null if it is unassigned.

1130: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 02 Feb 2021 22:48:48 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 02 Feb 2021 21:48:48 GMT
Content-Length: 45

{ "response": "admin" }
```

PUT

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 458: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service Request</i> being assigned

assignee The username of the user to whom the *Delivery Service Request* is assigned

New in version 4.0.

assigneeId The integral, unique identifier of the user to whom the *Delivery Service Request* is assigned

Changed in version 4.0: Prior to APIv4.0, this was the only property that could be used to change a *Delivery Service Request*’s Assignee - and thus was a required field.

It is not required to send both of these; either property is sufficient to determine an *Assignee*. In most cases, it’s easier to use just *assignee*. If both are given, then *assigneeId* will take precedence in the event that the two properties do not refer to the same user. Sending a request that sets the assignee to `null` un-assigns the *DSR* from any assignees it previously had¹.

¹ Because of how the Traffic Ops API parses requests, there is no distinction between `null` and `undefined`/missing properties. This means that sending the request payload `{}` in this case will result in the *DSR* being unassigned.

1131: Request Example

```
PUT /api/4.0/deliveryservice_requests/1/assign HTTP/1.1
User-Agent: python-requests/2.24.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 20

{"assignee": "admin"}
```

Response Structure

The response contains a full representation of the newly assigned *Delivery Service Request*.

1132: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 14:45:51
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→h7uBZHLQtRYbOSOR5AtQQRZ4uMeEWivWNT74fCf6WtLbAMwGpRrMjNmBYKduv48DnRqG6WVM/
→4nBu3AkCUqPw==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 13:45:51 GMT
Content-Length: 931

{ "alerts": [{
    "text": "Changed assignee of 'demo1' Delivery Service Request to
→'admin'",
    "level": "success"
}],
"response": {
    "assignee": "admin",
    "author": "admin",
    "changeType": "update",
    "createdAt": "2020-09-25T06:52:23.758877Z",
    "id": 6,
```

(continues on next page)

(continued from previous page)

```

"lastEditedBy": "admin",
"lastUpdated": "2020-09-25T07:01:24.600029Z",
"original": {
  "active": true,
  "anonymousBlockingEnabled": false,
  "cacheurl": null,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "checkPath": null,
  "displayName": "Demo 1",
  "dnsBypassCname": null,
  "dnsBypassIp": null,
  "dnsBypassIp6": null,
  "dnsBypassTtl": null,
  "dscp": 0,
  "edgeHeaderRewrite": null,
  "geoLimit": 0,
  "geoLimitCountries": null,
  "geoLimitRedirectURL": null,
  "geoProvider": 0,
  "globalMaxMbps": null,
  "globalMaxTps": null,
  "httpBypassFqdn": null,
  "id": 1,
  "infoUrl": null,
  "initialDispersion": 1,
  "ipv6RoutingEnabled": true,
  "lastUpdated": "2020-09-25T02:09:54Z",
  "logsEnabled": true,
  "longDesc": "Apachecon North America 2018",
  "matchList": [
    {
      "type": "HOST_REGEX",
      "setNumber": 0,
      "pattern": ".*\\.demo1\\.\\.\\.*"
    }
  ],
  "maxDnsAnswers": null,
  "midHeaderRewrite": null,
  "missLat": 42,
  "missLong": -88,
  "multiSiteOrigin": false,
  "originShield": null,
  "orgServerFqdn": "http://origin.infra.ciab.test",
  "profileDescription": null,

```

(continues on next page)

(continued from previous page)

```

    "profileId": null,
    "profileName": null,
    "protocol": 2,
    "qstringIgnore": 0,
    "rangeRequestHandling": 0,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "video",
    "signed": false,
    "sslKeyVersion": 1,
    "tenantId": 1,
    "type": "HTTP",
    "typeId": 1,
    "xmlId": "demo1",
    "exampleURLs": [
        "http://video.demo1.mycdn.ciab.test",
        "https://video.demo1.mycdn.ciab.test"
    ],
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": "root",
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": [
        "abc",
        "pdq",
        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false,
    "rangeSliceBlockSize": null,
    "topology": "demo1-top",
    "firstHeaderRewrite": null,
    "innerHeaderRewrite": null,
    "lastHeaderRewrite": null,
    "serviceCategory": null,
    "tlsVersions": null
},
"requested": {
    "active": true,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,

```

(continues on next page)

(continued from previous page)

```
"ccrDnsTtl": 30,
"cdnId": 2,
"cdnName": null,
"checkPath": null,
"displayname": "Demo 1 but modified by a DSR",
"dnsBypassCname": null,
"dnsBypassIp": null,
"dnsBypassIp6": null,
"dnsBypassTtl": null,
"dscp": 0,
"edgeHeaderRewrite": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 3,
"ipv6RoutingEnabled": null,
"lastUpdated": null,
"logsEnabled": false,
"longDesc": "long desc",
"matchList": null,
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": null,
"missLong": null,
"multiSiteOrigin": null,
"originShield": null,
"orgServerFqdn": null,
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": null,
"qstringIgnore": null,
"rangeRequestHandling": null,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "cdn",
"signed": false,
"sslKeyVersion": null,
"tenantId": 1,
```

(continues on next page)

(continued from previous page)

```

    "type": null,
    "typeId": 8,
    "xmlId": "demo1",
    "exampleURLs": null,
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": null,
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": null,
    "maxOriginConnections": 0,
    "ecsEnabled": false,
    "rangeSliceBlockSize": null,
    "topology": null,
    "firstHeaderRewrite": null,
    "innerHeaderRewrite": null,
    "lastHeaderRewrite": null,
    "serviceCategory": null,
    "tlsVersions": null
  },
  "status": "draft"
}}
```

deliveryservice_requests/{{ID}}/status

Get or set the status of a *Delivery Service Request*.

GET

Gets the status of a *DSR*.

New in version 4.0.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

Table 459: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service Request</i> being inspected

1133: Request Example

```
GET /api/4.0/deliveryservice_requests/1/status HTTP/1.1
User-Agent: python-requests/2.24.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

The response is the status of the requested *DSR*.

1134: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 02 Feb 2021 22:56:47
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 02 Feb 2021 21:56:47 GMT
Content-Length: 45

{ "response": "draft" }
```

PUT

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object

Request Structure

Table 460: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service Request</i> being modified

status The status of the *DSR*. Can be “draft”, “submitted”, “rejected”, “pending”, or “complete”.

1135: Request Example

```
PUT /api/4.0/deliveryservice_requests/1/status HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 28

{
  "status": "rejected"
}
```

Response Structure

The response is a full representation of the modified *DSR*.

1136: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 15:54:53.
→GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512:↵
↵C8Nhciy1jv5X7CGgHwAnLp1qmLizHq+4dv1AApb3cFSz5V2dABl7+N1Z4ndzB7GertB7rNLp31pVcat8v
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 14:54:53 GMT
Content-Length: 930

{ "alerts": [{
  "text": "Changed status of 'demo1' Delivery Service Request from
↵'draft' to 'submitted'",
  "level": "success"
}],
"response": {
  "assignee": "admin",
  "author": "admin",
  "changeType": "update",
  "createdAt": "2020-09-25T06:52:23.758877Z",
  "id": 6,
  "lastEditedBy": "admin",
  "lastUpdated": "2020-09-25T07:13:28.753352Z",
  "original": {
    "active": true,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "displayName": "Demo 1",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 1,
    "infoUrl": null,
    "initialDispersion": 1,
    "ipv6RoutingEnabled": true,
    "lastUpdated": "2020-09-25T02:09:54Z",
```

(continues on next page)

(continued from previous page)

```

"logsEnabled": true,
"longDesc": "Apachecon North America 2018",
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"signed": false,
"sslKeyVersion": 1,
"tenantId": 1,
"type": "HTTP",
"typeId": 1,
"xmlId": "demo1",
"exampleURLs": [
  "http://video.demo1.mycdn.ciab.test",
  "https://video.demo1.mycdn.ciab.test"
],
"deepCachingType": "NEVER",
"fqPacingRate": null,
"signingAlgorithm": null,
"tenant": "root",
"trResponseHeaders": null,
"trRequestHeaders": null,
"consistentHashRegex": null,
"consistentHashQueryParams": [
  "abc",
  "pdq",

```

(continues on next page)

(continued from previous page)

```

        "xxx",
        "zyx"
    ],
    "maxOriginConnections": 0,
    "ecsEnabled": false,
    "rangeSliceBlockSize": null,
    "topology": "demo1-top",
    "firstHeaderRewrite": null,
    "innerHeaderRewrite": null,
    "lastHeaderRewrite": null,
    "serviceCategory": null,
    "tlsVersions": null
},
"requested": {
    "active": true,
    "anonymousBlockingEnabled": false,
    "cacheurl": null,
    "ccrDnsTtl": 30,
    "cdnId": 2,
    "cdnName": null,
    "checkPath": null,
    "displayName": "Demo 1 but modified by a DSR",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "edgeHeaderRewrite": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 1,
    "infoUrl": null,
    "initialDispersion": 3,
    "ipv6RoutingEnabled": null,
    "lastUpdated": null,
    "logsEnabled": false,
    "longDesc": "long desc",
    "matchList": null,
    "maxDnsAnswers": null,
    "midHeaderRewrite": null,
    "missLat": null,

```

(continues on next page)

(continued from previous page)

```
    "missLong": null,
    "multiSiteOrigin": null,
    "originShield": null,
    "orgServerFqdn": null,
    "profileDescription": null,
    "profileId": null,
    "profileName": null,
    "protocol": null,
    "qstringIgnore": null,
    "rangeRequestHandling": null,
    "regexRemap": null,
    "regionalGeoBlocking": false,
    "remapText": null,
    "routingName": "cdn",
    "signed": false,
    "sslKeyVersion": null,
    "tenantId": 1,
    "type": null,
    "typeId": 8,
    "xmlId": "demo1",
    "exampleURLs": null,
    "deepCachingType": "NEVER",
    "fqPacingRate": null,
    "signingAlgorithm": null,
    "tenant": null,
    "trResponseHeaders": null,
    "trRequestHeaders": null,
    "consistentHashRegex": null,
    "consistentHashQueryParams": null,
    "maxOriginConnections": 0,
    "ecsEnabled": false,
    "rangeSliceBlockSize": null,
    "topology": null,
    "firstHeaderRewrite": null,
    "innerHeaderRewrite": null,
    "lastHeaderRewrite": null,
    "serviceCategory": null,
    "tlsVersions": null
  },
  "status": "submitted"
}
```


deliveryservice_stats

GET

Retrieves time-aggregated statistics on a specific *Delivery Service*.

Auth. Required Yes

Roles Required None¹

Response Type Object

¹ This endpoint respects *Tenancy*, and users whose *Tenant* does not have access to a *Delivery Service* will be unable to view the statistics of said *Delivery Service*.

Request Structure

Table 461: Request Query Parameters

Name	Required	Description
deliveryService	yes ²	Either the <i>xml_id</i> of a <i>Delivery Service</i> for which statistics will be aggregated or the integral, unique identifier of said <i>Delivery Service</i>
deliveryServiceName	yes [?]	The <i>xml_id</i> of the <i>Delivery Service</i> for which statistics will be aggregated
endDate	yes	The date and time until which statistics shall be aggregated in RFC 3339 format (with or without sub-second precision), the number of nanoseconds since the Unix Epoch, or in the same, proprietary format as the <code>lastUpdated</code> fields prevalent throughout the Traffic Ops API
exclude	no	Either “series” to omit the data series from the result, or “summary” to omit the summary data from the result - directly corresponds to fields in the <i>Response Structure</i>
interval	no	Specifies the interval within which data will be “bucketed”; e.g. when requesting data from 2019-07-25T00:00:00Z to 2019-07-25T23:59:59Z with an interval of “1m”, the resulting data series (assuming it is not excluded) should contain $24 \frac{\text{hours}}{\text{day}} \times 60 \frac{\text{minutes}}{\text{hour}} \times 1 \text{day} \times 1 \frac{\text{minute}}{\text{datapoint}} = 1440 \text{data points}$ The allowed values for this parameter are valid InfluxQL duration literal strings matching <code>^d+[mhdw]\$</code>
limit	no	A natural number indicating the maximum amount of data points should be returned in the series
metricType	yes	The metric type being reported - one of: Chapter 5. APIs 1666 kbps The total traffic rate

1137: Request Example

```
GET /api/4.0/deliveryservice_stats?deliveryServiceName=demo1&
→startDate=2019-07-22T17:55:00Z&endDate=2019-07-22T17:56:00.000Z&
→metricType=tps_total HTTP/1.1
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: application/json;timestamp=unix, application/json;
→timestamp=rfc;q=0.9, application/json;q=0.8, */*;q=0.7
Connection: keep-alive
Cookie: mojolicious=...
```

Content Format

It's important to note in *Request Example* the use of a complex “Accept” header. This endpoint accepts two special media types in the “Accept” header that instruct it on how to format the timestamps associated with the returned data. Specifically, Traffic Ops will recognize the special, optional, non-standard parameter of *application/json: timestamp*. The values of this parameter are restricted to one of

rfc Returned timestamps will be formatted according to **RFC 3339** (no sub-second precision).

unix Returned timestamps will be formatted as the number of nanoseconds since the Unix Epoch (midnight on January 1st 1970 UTC).

Implementation Detail

The endpoint passes back nanoseconds, specifically, because that is the form used both by InfluxDB, which is used to store the data being served, and Go's standard library. Clients may need to convert the value to match their own standard libraries - e.g. the `Date()` class in Javascript expects milliseconds.

The default behavior - when only e.g. *application/json* or **/** is given - is to use **RFC 3339** formatting. It will, however, respect quality parameters. It is suggested that clients request timestamps they can handle specifically, rather than relying on this default behavior, as it **is subject to change** and is in fact **expected to invert in the next major release** as string-based time formats become deprecated.

See also:

For more information on the “Accept” HTTP header, consult [its dedicated page on MDN](#).

² Either `deliveryServiceName` or `deliveryService` *must* be present, but if both are `deliveryServiceName` will be used and `deliveryService` will be ignored.

Response Structure

series An object containing the actual data series and information necessary for working with it.

columns This is an array of names of the columns of the data contained in the “values” array - should always be `["time", "sum_count"]`

count The number of data points contained in the “values” array

name The name of the data set. Should always match `metric.ds.1min` where `metric` is the requested `metricType`

values The actual array of data points. Each represents a length of time specified by the `interval` query parameter

time The time at which the measurement was taken. This corresponds to the *beginning* of the interval. This time comes in the format of either an [RFC 3339](#)-formatted string, or a number containing the number of nanoseconds since the Unix Epoch depending on the “Accept” header sent by the client, according to the rules outlined in [Content Format](#).

value The value of the requested `metricType` at the time given by `time`. This will always be a floating point number, unless no data is available for the data interval, in which case it will be `null`

source A legacy field meant only for plugins that override this endpoint to name themselves. Should always be “TrafficStats”.

Deprecated since version 1.4: As this has no known purpose, developers are advised it will be removed in the future.

summary An object containing summary statistics describing the data series

average The arithmetic mean of the data’s values

count The number of measurements taken within the requested timespan. This is, in general, **not** the same as the `count` field of the `series` object, as it reflects the number of underlying, un-“bucketed” data points, and is therefore dependent on the implementation of Traffic Stats.

fifthPercentile Data points with values less than or equal to this number constitute the “bottom” 5% of the data set

max The maximum value that can be found in the requested data set

min The minimum value that can be found in the requested data set

ninetyEighthPercentile Data points with values greater than or equal to this number constitute the “top” 2% of the data set

ninetyFifthPercentile Data points with values greater than or equal to this number constitute the “top” 5% of the data set

totalBytes When the `metricType` requested is `kbps`, this will contain the total number of bytes transferred by the *Delivery Service* within the requested time window. Note that fractional amounts are possible, as the data transfer rate will almost certainly not be cleanly divided by the requested time range.

totalTransactions When the `metricType` requested is `not kbps`, this will contain the total number of transactions completed by the *Delivery Service* within the requested time window. Note that fractional amounts are possible, as the transaction rate will almost certainly not be cleanly divided by the requested time range.

version A legacy field that seems to have been meant to indicate the API version used. Will always be “1.2”

Deprecated since version 1.4: As this has no known purpose, developers are advised it will be removed in the future.

1138: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: zXJGjcYuu6HxWINVp8HA1gL31J3ukry5wCsTDNxtP/
    ↳waC6rSD8h10KJ9jEAtrZJ9owOSVPvKaA/2bRu/QeuCpQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 22 Jul 2019 17:57:14 GMT
Transfer-Encoding: chunked
```

(continues on next page)

(continued from previous page)

```
{ "response": {
  "series": {
    "columns": [
      "time",
      "sum_count"
    ],
    "count": 2,
    "name": "tps_total.ds.1min",
    "tags": {
      "cachegroup": "total"
    },
    "values": [
      [
        15638181000000000000,
        0
      ],
      [
        15638181600000000000,
        0
      ]
    ]
  },
  "source": "TrafficStats",
  "summary": {
    "average": 0,
    "count": 2,
    "fifthPercentile": 0,
    "max": 0,
    "min": 0,
    "ninetyEighthPercentile": 0,
    "ninetyFifthPercentile": 0,
    "totalBytes": null,
    "totalTransactions": 0
  },
  "version": "1.2"
}}
```

deliveryservices

GET

Retrieves *Delivery Services*

Auth. Required Yes

Roles Required None¹

Response Type Array

¹ Only those *Delivery Services* assigned to *Tenants* that are the requesting user's *Tenant* or children thereof will appear in the output of a GET request, and the same constraints are placed on the allowed values of the `tenantId` field of a POST request to create a new *Delivery Service*

Request Structure

Table 462: Request Query Parameters

Name	Re-quired	Description
cdn	no	Show only the <i>Delivery Services</i> belonging to the <i>CDN</i> identified by this integral, unique identifier
id	no	Show only the <i>Delivery Service</i> that has this integral, unique identifier
logsEnabled	no	Show only the <i>Delivery Services</i> that have <i>Logs Enabled</i> set or not based on this boolean
profile	no	Return only <i>Delivery Services</i> using the <i>Profile</i> that has this <i>ID</i>
tenant	no	Show only the <i>Delivery Services</i> belonging to the <i>Tenant</i> identified by this integral, unique identifier
topology	no	Show only the <i>Delivery Services</i> assigned to the <i>Topology</i> identified by this unique name
type	no	Return only <i>Delivery Services</i> of the <i>Delivery Service Type</i> identified by this integral, unique identifier
accessibleTo	no	Return the <i>Delivery Services</i> accessible from a <i>Tenant</i> or it's children identified by this integral, unique identifier
service-Category	no	Show only the <i>Delivery Services</i> belonging to the <i>Service Category</i> that has this name
xmlId	no	Show only the <i>Delivery Service</i> that has this text-based, unique identifier
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.
active	no	Show only the <i>Delivery Services</i> that have <i>Active</i> set or not based on this boolean (whether or not they are active)

1139: Request Example

```
GET /api/4.0/deliveryservices?xmlId=demo2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.24.0
```

(continues on next page)

(continued from previous page)

```
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

- active** A boolean that defines *Active*.
- anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
- ccrDnsTtl** The *DNS TTL* - named “ccrDnsTtl” for legacy reasons
- cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
- cdnName** Name of the *CDN* to which the *Delivery Service* belongs
- checkPath** A *Check Path*
- consistentHashRegex** A *Consistent Hashing Regular Expression*
- consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
- deepCachingType** The *Deep Caching* setting for this *Delivery Service*
- displayName** The *Display Name*
- dnsBypassCname** A *DNS Bypass CNAME*
- dnsBypassIp** A *DNS Bypass IP*
- dnsBypassIp6** A *DNS Bypass IPv6*
- dnsBypassTtl** The *DNS Bypass TTL*
- dscp** A *DSCP* to be used within the *Delivery Service*
- ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*
- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*
- firstHeaderRewrite** A set of *First Header Rewrite Rules*
- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*
- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*
- geoLimitRedirectUrl** A *Geo Limit Redirect URL*
- geoProvider** The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in :rfc:3339 format

Changed in version 4.0: Prior to API version 4.0, this property used *Traffic Ops's Custom Date/Time Format*.

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

matchList The *Delivery Service's Match List*

- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
- setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
- type** The type of match performed using pattern.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

maxRequestHeaderBytes The *Max Request Header Bytes*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** The *ID* of the *Profile* with which this *Delivery Service* is associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- serviceCategory** The name of the *Service Category* with which the *Delivery Service* is associated
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if *rangeRequestHandling* is set to 3.
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- tlsVersions** A list of explicitly supported *TLS Versions*
New in version 4.0.
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*

1140: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Permissions-Policy: interest-cohort=()
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 07 Jun 2021 22:52:20
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Jun 2021 21:52:20 GMT
Content-Length: 847

{ "response": [
  {
    "active": true,
    "anonymousBlockingEnabled": false,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "checkPath": null,
    "consistentHashQueryParams": [],
    "consistentHashRegex": null,
    "deepCachingType": "NEVER",
    "displayName": "Demo 2",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "ecsEnabled": false,
    "edgeHeaderRewrite": null,
    "exampleURLs": [
      "http://video.demo2.mycdn.ciab.test",
      "https://video.demo2.mycdn.ciab.test"
    ],
    "firstHeaderRewrite": null,
    "fqPacingRate": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
  }
]

```

(continues on next page)

(continued from previous page)

```

"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "2021-06-07T21:50:03.009954Z",
"logsEnabled": true,
"longDesc": "DNS Delivery Service for use with a Federation",
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo2\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"maxOriginConnections": 0,
"maxRequestHeaderBytes": 0,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,
"multiSiteOrigin": true,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"rangeSliceBlockSize": null,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"serviceCategory": null,
"signed": false,
"signingAlgorithm": null,
"sslKeyVersion": null,
"tenant": "root",
"tenantId": 1,
"tlsVersions": null,

```

(continues on next page)

(continued from previous page)

```

        "topology": "demo1-top",
        "trResponseHeaders": null,
        "trRequestHeaders": null,
        "type": "DNS",
        "typeId": 5,
        "xmlId": "demo2"
    }
}]

```

POST

Allows users to create *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 1544, 1}

Response Type Array

Request Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*²

geoLimitRedirectUrl A *Geo Limit Redirect URL*[?]

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

maxRequestHeaderBytes The *Max Request Header Bytes*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileId An optional *ID* of a *Profile* with which this *Delivery Service* shall be associated

² These fields must be defined if and only if `geoLimit` is non-zero

- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- serviceCategory** The name of the *Service Category* with which the *Delivery Service* is associated - or null if there is to be no such category
- signed** true if and only if **signingAlgorithm** is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if **rangeRequestHandling** is set to 3. It can only be between (inclusive) 262144 (256KB) - 33554432 (32MB).
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- tlsVersions** An array of explicitly supported *TLS Versions*
New in version 4.0.
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*

1141: Request Example

```
POST /api/4.0/deliveryservices HTTP/1.1
User-Agent: python-requests/2.24.0
Accept-Encoding: gzip, deflate
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 1602
Content-Type: application/json
Host: trafficops.infra.ciab.test

{
  "active": false,
  "anonymousBlockingEnabled": false,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "checkPath": null,
  "consistentHashRegex": null,
  "consistentHashQueryParams": [],
  "deepCachingType": "NEVER",
  "displayName": "test",
  "dnsBypassCname": null,
  "dnsBypassIp": null,
  "dnsBypassIp6": null,
  "dnsBypassTtl": null,
  "dscp": 0,
  "ecsEnabled": true,
  "edgeHeaderRewrite": null,
  "firstHeaderRewrite": null,
  "fqPacingRate": null,
  "geoLimit": 0,
  "geoLimitCountries": null,
  "geoLimitRedirectUrl": null,
  "geoProvider": 0,
  "globalMaxMbps": null,
  "globalMaxTps": null,
  "httpBypassFqdn": null,
  "infoUrl": null,
  "initialDispersion": 1,
  "innerHeaderRewrite": null,
  "ipv6RoutingEnabled": false,
  "lastHeaderRewrite": null,
  "logsEnabled": true,
  "longDesc": "A Delivery Service created expressly for API_
↪documentation examples",
  "maxDnsAnswers": null,
  "missLat": 0,
  "missLong": 0,
  "maxOriginConnections": 0,
  "maxRequestHeaderBytes": 131072,
```

(continues on next page)

(continued from previous page)

```

"midHeaderRewrite": null,
"multiSiteOrigin": false,
"orgServerFqdn": "http://origin.infra.ciab.test",
"originShield": null,
"profileId": null,
"protocol": 0,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"routingName": "test",
"serviceCategory": null,
"signed": false,
"signingAlgorithm": null,
"rangeSliceBlockSize": null,
"sslKeyVersion": null,
"tenant": "root",
"tenantId": 1,
"tlsVersions": [
    "1.2",
    "1.3"
],
"topology": null,
"trRequestHeaders": null,
"trResponseHeaders": null,
"type": "HTTP",
"typeId": 1,
"xmlId": "test"
}

```

Response Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*

geoLimitRedirectUrl A *Geo Limit Redirect URL*

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in :rfc:3339 format

Changed in version 4.0: Prior to API version 4.0, this property used *Traffic Ops's Custom Date/Time Format*.

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

matchList The *Delivery Service's Match List*

- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
- setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
- type** The type of match performed using **pattern**.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

maxRequestHeaderBytes The *Max Request Header Bytes*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId The *ID* of the *Profile* with which this *Delivery Service* is associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

serviceCategory The name of the *Service Category* with which the *Delivery Service* is associated

- signed** true if and only if `signingAlgorithm` is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if `rangeRequestHandling` is set to 3.
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- tlsVersions** An array of explicitly supported *TLS Versions*
- New in version 4.0.
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*

1142: Response Example

```

HTTP/1.1 201 Created
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Location: /api/4.0/deliveryservices?id=6
Permissions-Policy: interest-cohort=()
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 07 Jun 2021 23:37:37
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Jun 2021 22:37:37 GMT
Content-Length: 903

{ "alerts": [
  {
    "text": "tlsVersions has no effect on 'HTTP' Delivery Services
    ↳",
  
```

(continues on next page)

(continued from previous page)

```

        "level": "warning"
    },
    {
        "text": "Delivery Service creation was successful",
        "level": "success"
    }
],
"response": [{
    "active": false,
    "anonymousBlockingEnabled": false,
    "ccrDnsTtl": null,
    "cdnId": 2,
    "cdnName": null,
    "checkPath": null,
    "consistentHashQueryParams": [],
    "consistentHashRegex": null,
    "deepCachingType": "NEVER",
    "displayName": "test",
    "dnsBypassCname": null,
    "dnsBypassIp": null,
    "dnsBypassIp6": null,
    "dnsBypassTtl": null,
    "dscp": 0,
    "ecsEnabled": true,
    "edgeHeaderRewrite": null,
    "exampleURLs": [
        "http://test.test.mycdn.ciab.test"
    ],
    "firstHeaderRewrite": null,
    "fqPacingRate": null,
    "geoLimit": 0,
    "geoLimitCountries": null,
    "geoLimitRedirectURL": null,
    "geoProvider": 0,
    "globalMaxMbps": null,
    "globalMaxTps": null,
    "httpBypassFqdn": null,
    "id": 6,
    "infoUrl": null,
    "initialDispersion": 1,
    "innerHeaderRewrite": null,
    "ipv6RoutingEnabled": false,
    "lastHeaderRewrite": null,
    "lastUpdated": "2021-06-07T22:37:37.187822Z",
    "logsEnabled": true,
    "longDesc": "A Delivery Service created expressly for API_
→documentation examples",

```

(continues on next page)

(continued from previous page)

```

"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.test\\.\\.*"
  }
],
"maxDnsAnswers": null,
"maxOriginConnections": 0,
"maxRequestHeaderBytes": 131072,
"midHeaderRewrite": null,
"missLat": 0,
"missLong": 0,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 0,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"rangeSliceBlockSize": null,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "test",
"serviceCategory": null,
"signed": false,
"signingAlgorithm": null,
"sslKeyVersion": null,
"tenant": "root",
"tenantId": 1,
"tlsVersions": [
  "1.2",
  "1.3"
],
"topology": null,
"trResponseHeaders": null,
"trRequestHeaders": null,
"type": "HTTP",
"typeId": 1,
"xmlId": "test"
}]

```

deliveryservices/dnsseckey/generate

POST

Generates ZSK and KSK keypairs for a CDN and all associated *Delivery Services*.

Auth. Required Yes

Roles Required “admin”

Response Type Object (string)

Request Structure

effectiveDate UNIX epoch start date for the signing keys

key Name of the CDN

skExpirationDays Expiration (in days) for the KSKs

name Domain name used by the CDN

ttl Time for which the keypairs shall remain valid

zskExpirationDays Expiration (in days) for the ZSKs

Response Structure

1143: Response Example

```
{
  "response": "Successfully created dnssec keys for cdn1"
}
```

deliveryservices/{{ID}}

PUT

Allows users to edit an existing *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type Array (should always have a length of exactly one on success)

¹ Only those *Delivery Services* assigned to *Tenants* that are the requesting user’s *Tenant* or children thereof will appear in the output of a GET request, and the same constraints are placed on the allowed values of the `tenantId` field of a PUT request to update a new *Delivery Service*. Furthermore, the only *Delivery Services* a user may delete are those assigned to a *Tenant* that is either the same *Tenant* as the user’s *Tenant*, or a descendant thereof.

Request Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

Note: If the Delivery Service has SSL Keys, then cdnId is not allowed to change as that would invalidate the SSL Key

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*²

geoLimitRedirectUrl A *Geo Limit Redirect URL*[?]

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

² These fields must be defined if and only if geoLimit is non-zero

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileId An optional *ID* of the *Profile* with which this *Delivery Service* will be associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

routingName The *Routing Name* of this *Delivery Service*

Note: If the Delivery Service has SSL Keys, then `routingName` is not allowed to change as that would invalidate the SSL Key

signed true if and only if `signingAlgorithm` is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or `null` to indicate URL/URI signing is not implemented on this *Delivery Service*

rangeSliceBlockSize An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if `rangeRequestHandling` is set to 3. It can only be between (inclusive) 262144 (256KB) - 33554432 (32MB).

sslKeyVersion This integer indicates the *SSL Key Version*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

tlsVersions An array of explicitly supported *TLS Versions*

New in version 4.0.

topology The unique name of the *Topology* that this *Delivery Service* is assigned to

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

Note: While this field **must** be present, it is **not** allowed to change; this must be the same as the `xml_id` the *Delivery Service* already has. This should almost never be different from the *Delivery Service*'s `displayName`.

1144: Request Example

```
PUT /api/4.0/deliveryservices/6 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.24.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 1585
Content-Type: application/json

{
  "active": false,
  "anonymousBlockingEnabled": false,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "checkPath": null,
```

(continues on next page)

(continued from previous page)

```

"consistentHashRegex": null,
"consistentHashQueryParams": [],
"deepCachingType": "NEVER",
"displayName": "test",
"dnsBypassCname": null,
"dnsBypassIp": null,
"dnsBypassIp6": null,
"dnsBypassTtl": null,
"dscp": 0,
"ecsEnabled": true,
"edgeHeaderRewrite": null,
"firstHeaderRewrite": null,
"fqPacingRate": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectUrl": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": false,
"lastHeaderRewrite": null,
"logsEnabled": true,
"longDesc": "A Delivery Service created expressly for API_
→documentation examples",
"maxDnsAnswers": null,
"missLat": 0,
"missLong": 0,
"maxOriginConnections": 0,
"maxRequestHeaderBytes": 131072,
"midHeaderRewrite": null,
"multiSiteOrigin": false,
"orgServerFqdn": "http://origin.infra.ciab.test",
"originShield": null,
"profileId": null,
"protocol": 0,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"regexRemap": null,
"regionalGeoBlocking": false,
"routingName": "test",
"serviceCategory": null,
"signed": false,

```

(continues on next page)

(continued from previous page)

```

"signingAlgorithm": null,
"rangeSliceBlockSize": null,
"sslKeyVersion": null,
"tenant": "root",
"tenantId": 1,
"tlsVersions": null,
"topology": null,
"trRequestHeaders": null,
"trResponseHeaders": null,
"type": "HTTP",
"typeId": 1,
"xmlId": "test"
}

```

Response Structure

- active** A boolean that defines *Active*.
- anonymousBlockingEnabled** A boolean that defines *Anonymous Blocking*
- ccrDnsTtl** The *DNS TTL* - named “ccrDnsTtl” for legacy reasons
- cdnId** The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs
- cdnName** Name of the *CDN* to which the *Delivery Service* belongs
- checkPath** A *Check Path*
- consistentHashRegex** A *Consistent Hashing Regular Expression*
- consistentHashQueryParams** An array of *Consistent Hashing Query Parameters*
- deepCachingType** The *Deep Caching* setting for this *Delivery Service*
- displayName** The *Display Name*
- dnsBypassCname** A *DNS Bypass CNAME*
- dnsBypassIp** A *DNS Bypass IP*
- dnsBypassIp6** A *DNS Bypass IPv6*
- dnsBypassTtl** The *DNS Bypass TTL*
- dscp** A *DSCP* to be used within the *Delivery Service*
- ecsEnabled** A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*
- edgeHeaderRewrite** A set of *Edge Header Rewrite Rules*
- exampleURLs** An array of *Example URLs*

- firstHeaderRewrite** A set of *First Header Rewrite Rules*
- fqPacingRate** The *Fair-Queuing Pacing Rate Bps*
- geoLimit** An integer that defines the *Geo Limit*
- geoLimitCountries** A string containing a comma-separated list defining the *Geo Limit Countries*
- geoLimitRedirectUrl** A *Geo Limit Redirect URL*
- geoProvider** The *Geolocation Provider*
- globalMaxMbps** The *Global Max Mbps*
- globalMaxTps** The *Global Max TPS*
- httpBypassFqdn** A *HTTP Bypass FQDN*
- id** An integral, unique identifier for this *Delivery Service*
- infoUrl** An *Info URL*
- initialDispersion** The *Initial Dispersion*
- innerHeaderRewrite** A set of *Inner Header Rewrite Rules*
- ipv6RoutingEnabled** A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*
- lastHeaderRewrite** A set of *Last Header Rewrite Rules*
- lastUpdated** The date and time at which this *Delivery Service* was last updated, in :rfc:3339 format
- Changed in version 4.0: Prior to API version 4.0, this property used *Traffic Ops's Custom Date/Time Format*.
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using pattern.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- maxRequestHeaderBytes** The *Max Request Header Bytes*

- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** The *ID* of the *Profile* with which this *Delivery Service* is associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*
- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- serviceCategory** The name of the *Service Category* with which the *Delivery Service* is associated
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if *rangeRequestHandling* is set to 3.
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- tlsVersions** An array of explicitly supported *TLS Versions*
New in version 4.0.
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

1145: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Permissions-Policy: interest-cohort=()
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 08 Jun 2021 00:34:04
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳tTncbRoJR+pyykVbEc6nWyoFnhlJzsbge9hVZfw+WK28rzSGECZ/
    ↳Q4zXTQtFjHWY5G+0Rk4w9GKrSFK3k+u5Ng==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Jun 2021 23:34:04 GMT
Content-Length: 840

{ "alerts": [
  {
    "text": "Delivery Service update was successful",
    "level": "success"
  }
],
"response": [{
  "active": false,
  "anonymousBlockingEnabled": false,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "cdnName": null,
  "checkPath": null,
  "consistentHashQueryParams": [],
  "consistentHashRegex": null,
  "deepCachingType": "NEVER",
  "displayName": "test",
```

(continues on next page)

(continued from previous page)

```

"dnkBypassCname": null,
"dnkBypassIp": null,
"dnkBypassIp6": null,
"dnkBypassTtl": null,
"dscp": 0,
"ecsEnabled": true,
"edgeHeaderRewrite": null,
"exampleURLs": null,
"firstHeaderRewrite": null,
"fqPacingRate": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 6,
"infoUrl": null,
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": false,
"lastHeaderRewrite": null,
"lastUpdated": "2021-06-07T23:34:04.831215Z",
"logsEnabled": true,
"longDesc": "A Delivery Service created expressly for API_
↪documentation examples",
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.test\\..*"
  }
],
"maxDnsAnswers": null,
"maxOriginConnections": 0,
"maxRequestHeaderBytes": 131072,
"midHeaderRewrite": null,
"missLat": 0,
"missLong": 0,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,

```

(continues on next page)

(continued from previous page)

```
"protocol": 0,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"rangeSliceBlockSize": null,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "test",
"serviceCategory": null,
"signed": false,
"signingAlgorithm": null,
"sslKeyVersion": null,
"tenant": "root",
"tenantId": 1,
"tlsVersions": null,
"topology": null,
"trResponseHeaders": null,
"trRequestHeaders": null,
"type": "HTTP",
"typeId": 1,
"xmlId": "test"
}}}
```

DELETE

Deletes the target *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 1544, 1}

Response Type undefined

Request Structure

Table 463: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> to be deleted

1146: Request Example

```
DELETE /api/4.0/deliveryservices/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1147: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: w9NlQpJJEl56r6iYq/
    ↳fk8o5WfAXeUS5XR9yDHvKUgPO8lYEo8YyftaSF0MPFseeOk60dk6kQo+MLYTDIAhhRxw==
X-Server-Name: traffic_ops_golang/
Date: Tue, 20 Nov 2018 14:56:37 GMT
Content-Length: 57

{ "alerts": [
  {
    "text": "ds was deleted.",
    "level": "success"
  }
]}
```

deliveryservices/{{ID}}/capacity

See also:

Health Protocol

GET

Retrieves the usage percentages of a servers associated with a *Delivery Service*

Auth. Required Yes

Roles Required None¹

Response Type Object

¹ Users will only be able to see capacity details for the *Delivery Services* their *Tenant* is allowed to see.

Request Structure

Table 464: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the <i>Delivery Service</i> of interest

Response Structure

availablePercent The percent of servers assigned to this *Delivery Service* that is available - the allowed traffic level in terms of data per time period for all *cache servers* that remains unused

unavailablePercent The percent of servers assigned to this *Delivery Service* that is unavailable - the allowed traffic level in terms of data per time period for all *cache servers* that can't be used because the servers are deemed unhealthy

utilizedPercent The percent of servers assigned to this *Delivery Service* that is currently in use - the allowed traffic level in terms of data per time period that is currently devoted to servicing requests

maintenancePercent The percent of servers assigned to this *Delivery Service* that is unavailable due to server maintenance - the allowed traffic level in terms of data per time period that is unavailable because servers have intentionally been marked offline by administrators

1148: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 14:41:27 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→+++dFR9V1c60CHGNwMjX6JSFEjHreXcL4QnhT03hiv04ByY379aLpL40r0zX2bPgJgpR94+f6jZ0+iDIyT
Content-Length: 134

{ "response": {
  "availablePercent": 99.9993696969697,
  "unavailablePercent": 0,
```

(continues on next page)

(continued from previous page)

```
"utilizedPercent": 0.0006303030303030303,
"maintenancePercent": 0
}}
```

deliveryservices/{{ID}}/health

See also:

Health Protocol

GET

Retrieves the health of all *Cache Groups* assigned to a particular *Delivery Service*

Auth. Required Yes

Roles Required None¹

Response Type Object

Request Structure

Table 465: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the Delivery service for which <i>Cache Groups</i> will be displayed

Response Structure

cachegroups An array of objects that represent the health of each *Cache Group* assigned to this *Delivery Service*

name A string that is the *name of the Cache Group* represented by this object

offline The number of OFFLINE *cache servers* within this *Cache Group*

online The number of ONLINE *cache servers* within this *Cache Group*

totalOffline Total number of OFFLINE *cache servers* assigned to this *Delivery Service*

¹ Users will only be able to see *Cache Group* health details for the *Delivery Services* their *Tenant* is allowed to see.

totalOnline Total number of ONLINE *cache servers* assigned to this *Delivery Service*

1149: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 14:43:43 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳KpXViXeAgch58ueQqdyU8NuINBw1EUedE6Rv2ewcLUajJp6kowdbVynpwW7XiSvAyHdtClIOuT30khIm
Content-Length: 115

{ "response": {
  "totalOffline": 0,
  "totalOnline": 1,
  "cachegroups": [
    {
      "offline": 0,
      "name": "CDN_in_a_Box_Edge",
      "online": 1
    }
  ]
}}
```

deliveryservices/{{ID}}/regexes

GET

Retrieves routing regular expressions for a specific *Delivery Service*.

Auth. Required Yes

Roles Required None¹

Response Type Array

¹ Users will only be able to view and create regular expressions for the *Delivery Services* their *Tenant* is allowed to see.

Request Structure

Table 466: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected

Table 467: Request Query Parameters

Name	Required	Description
id	no	Show only the <i>Delivery Service</i> regular expression that has this integral, unique identifier
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1150: Request Example

```
GET /api/4.0/deliveryservices/1/regexes HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- id** The integral, unique identifier of this regular expression
- pattern** The actual regular expression - \s are escaped
- setNumber** The order in which the regular expression is evaluated against requests
- type** The integral, unique identifier of the *Type* of this regular expression
- typeName** The *Type* of regular expression - determines that against which it will be evaluated

1151: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: fW9Fde4WRpp2ShRAC41P9s/PhU71LI/
→SEzHgYjGqfzhk45wq0kpaWy76JvPflpowY8eDTp8Y8TL5rNGEc+bM+A==
X-Server-Name: traffic_ops_golang/
Date: Tue, 27 Nov 2018 20:56:43 GMT
Content-Length: 100

{ "response": [
  {
    "id": 1,
    "type": 31,
    "typeName": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.demo1\\.\\.\\.*"
  }
]}
```

POST

Creates a routing regular expression for a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”[Page 1544, 1](#)

Response Type Object

Request Structure

Table 468: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected

pattern The actual regular expression

Warning: Be sure that \s are escaped, or the expression may not work as intended!

setNumber The order in which this regular expression should be checked

type The integral, unique identifier of a routing regular expression type

1152: Request Example

```
POST /api/4.0/deliveryservices/1/regexes HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 55
Content-Type: application/json

{
  "pattern": ".*\\.foo-bar\\.\\.\\.\"",
  "type": 31,
  "setNumber": 1
}
```

Response Structure

- id** The integral, unique identifier of this regular expression
- pattern** The actual regular expression - \s are escaped
- setNumber** The order in which the regular expression is evaluated against requests
- type** The integral, unique identifier of the type of this regular expression
- typeName** The type of regular expression - determines that against which it will be evaluated

1153: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: kS5dRzAhFKE7vfzHK7XVIwpMOjztk9MU+qtj5YU/
  ↳1oxVHmqNbJ12Fe00IJsZJCXbYlnBS04sCI95Sz5wed1Q==
X-Server-Name: traffic_ops_golang/
Date: Wed, 28 Nov 2018 17:00:42 GMT
Content-Length: 188

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

        "text": "Delivery service regex creation was successful.",
        "level": "success"
    }
],
"response": {
    "id": 2,
    "type": 31,
    "typeName": "HOST_REGEX",
    "setNumber": 1,
    "pattern": ".*\\.foo-bar\\.\\.\\.*"
}}

```

deliveryservices/{{ID}}/regexes/{{rID}}

PUT

Updates a routing regular expression.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type Object

Request Structure

Table 469: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected
rID	The integral, unique identifier of the routing regular expression being inspected

pattern The actual regular expression

Warning: Be sure that \s are escaped, or the expression may not work as intended!

setNumber The order in which this regular expression should be checked

type The integral, unique identifier of a routing regular expression type

¹ Users will only be able to view, delete and update regular expressions for the *Delivery Services* their *Tenant* is allowed to see.

1154: Request Example

```
PUT /api/4.0/deliveryservices/1/regexes/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 55
Content-Type: application/json

{
  "pattern": ".*\\.foo-bar\\.\\.\\.\"",
  "type": 33,
  "setNumber": 1
}
```

Response Structure

- id** The integral, unique identifier of this regular expression
- pattern** The actual regular expression - \s are escaped
- setNumber** The order in which the regular expression is evaluated against requests
- type** The integral, unique identifier of the type of this regular expression
- typeName** The type of regular expression - determines that against which it will be evaluated

1155: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: kS5dRzAhFKE7vfzHK7XVIwpMOjztksk9MU+qtj5YU/
  ↳1oxVHmqNbJ12Fe00IJsZJCXbYlnBS04sCI95Sz5wed1Q==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 17:54:58 GMT
Content-Length: 188

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

        "text": "Delivery service regex creation was successful.",
        "level": "success"
    }
],
"response": {
    "id": 2,
    "type": 33,
    "typeName": "PATH_REGEX",
    "setNumber": 1,
    "pattern": ".*\\.foo-bar\\.\\.*"
}}

```

DELETE

Deletes a routing regular expression.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 1544, 1}

Response Type undefined

Request Structure

Table 470: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being inspected
rID	The integral, unique identifier of the routing regular expression being inspected

1156: Request Example

```
DELETE /api/4.0/deliveryservices/1/regexes/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1157: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 8oEa78x7f/o39LIS98W6G+UqE6cX/
    ↳Iw4v3mMHvbAsliWHALuDYZRz3V0tA6jzfGQKpB040m8qaVG+zWRrBVoCmQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 18:44:00 GMT
Content-Length: 76

{ "alerts": [
  {
    "text": "deliveryservice_regex was deleted.",
    "level": "success"
  }
]}
```

deliveryservices/{{ID}}/routing

GET

Retrieves the aggregated routing percentages for a given *Delivery Service*. This is accomplished by polling stats from all online Traffic Routers via the */crs/stats* route.

Auth. Required Yes

Roles Required None¹

¹ Users will only be able to view routing details for the *Delivery Services* their *Tenant* is allowed to see.

Response Type Object

Note: Only HTTP or DNS *Delivery Services* can be requested.

Request Structure

Table 471: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the <i>Delivery Service</i> of interest

1158: Request Example

```
GET /api/4.0/deliveryservices/1/routing HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cz** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by a *Coverage Zone File*
- deepCz** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by a *Deep Coverage Zone File*
- dsr** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by sending the client to an overflow *Delivery Service*
- err** The percent of requests to online Traffic Routers for this *Delivery Service* that resulted in an error
- fed** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by sending the client to a federated CDN
- geo** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied using 3rd party geographic IP mapping
- miss** The percent of requests to online Traffic Routers for this *Delivery Service* that could not be satisfied
- regionalAlternate** The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied by sending the client to the alternate, Regional Geo-blocking URL
- regionalDenied** The percent of requests to online Traffic Routers for this *Delivery Service* that were denied due to geographic location policy

staticRoute The percent of requests to online Traffic Routers for this *Delivery Service* that were satisfied with *Static DNS Entries*

1159: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Fri, 30 Nov 2018 15:08:07 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: UgPziRC/5u4+CfkZ9xm0EkEzjjJVu6cwBrFd/n3xH/
→ZmlkaXkQaa1y4+B7DyE46vxFLYE00D0cQchyn7JkoQOg==
Content-Length: 132

{ "response": {
  "cz": 79,
  "deepCz": 0.50,
  "dsr": 0,
  "err": 0,
  "fed": 0.25,
  "geo": 20,
  "miss": 0.25,
  "regionalAlternate": 0,
  "regionalDenied": 0,
  "staticRoute": 0
}}
```

deliveryservices/{{ID}}/safe

PUT

Allows a user to edit metadata fields of a *Delivery Service*.

Auth. Required Yes

Roles Required None¹

Response Type Array

¹ Only those *Delivery Services* assigned to *Tenants* that are the requesting user's *Tenant* or children thereof may be modified with this endpoint.

Request Structure

Table 472: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Delivery Service</i> being modified

displayName A string that is the *Display Name*

infoUrl An optional² string containing the *Info URL*

longDesc An optional² string containing the *Long Description* of this *Delivery Service*

1160: Request Example

```
PUT /api/4.0/deliveryservices/1/safe HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 132
Content-Type: application/json

{
  "displayName": "test",
  "infoUrl": "this is not even a real URL",
  "longDesc": "this is a description of the delivery service"
}
```

Response Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

² If these fields are not present in the request body they are *implicitly set to null*.

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*

geoLimitRedirectUrl A *Geo Limit Redirect URL*

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

initialDispersion The *Initial Dispersion*

innerHeaderRewrite A set of *Inner Header Rewrite Rules*

ipv6RoutingEnabled A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*

lastHeaderRewrite A set of *Last Header Rewrite Rules*

lastUpdated The date and time at which this *Delivery Service* was last updated, in :rfc:3339 format

Changed in version 4.0: Prior to API version 4.0, this property used *Traffic Ops's Custom Date/Time Format*.

logsEnabled A boolean that defines the *Logs Enabled* setting on this *Delivery Service*

longDesc The *Long Description* of this *Delivery Service*

matchList The *Delivery Service's Match List*

pattern A regular expression - the use of this pattern is dependent on the *type* field (backslashes are escaped)

setNumber An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.

type The type of match performed using *pattern*.

maxDnsAnswers The *Max DNS Answers* allowed for this *Delivery Service*

maxOriginConnections The *Max Origin Connections*

midHeaderRewrite A set of *Mid Header Rewrite Rules*

missLat The *Geo Miss Default Latitude* used by this *Delivery Service*

missLong The *Geo Miss Default Longitude* used by this *Delivery Service*

multiSiteOrigin A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*

orgServerFqdn The *Origin Server Base URL*

originShield A *Origin Shield* string

profileDescription The *Description* of the *Profile* with which this *Delivery Service* is associated

profileId The *ID* of the *Profile* with which this *Delivery Service* is associated

profileName The *Name* of the *Profile* with which this *Delivery Service* is associated

protocol An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

qstringIgnore An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*

rangeRequestHandling An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*

regexRemap A *Regex Remap Expression*

regionalGeoBlocking A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*

remapText *Raw Remap Text*

signed true if and only if *signingAlgorithm* is not null, false otherwise

signingAlgorithm Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*

rangeSliceBlockSize An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if `rangeRequestHandling` is set to 3.

sslKeyVersion This integer indicates the *SSL Key Version*

tenantId The integral, unique identifier of the *Tenant* who owns this *Delivery Service*

tlsVersions A list of explicitly supported *TLS Versions*
New in version 4.0.

topology The unique name of the *Topology* that this *Delivery Service* is assigned to

trRequestHeaders If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*

trResponseHeaders If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*

type The *Type* of this *Delivery Service*

typeId The integral, unique identifier of the *Type* of this *Delivery Service*

xmlId This *Delivery Service*'s *xml_id*

1161: Response Example

```
HTTP/1.1 200 OK
Content-Encoding: gzip
Content-Type: application/json
Permissions-Policy: interest-cohort=()
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 08 Jun 2021 00:53:26 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: Ys/SfWWijsXCNXEqZ84oldfyXTgMe8UE/
wWb53VU390H7kW0XF1BH5Hg7Y40nCgXoWEqcaBq5+WCZg0bYuJdAA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Jun 2021 23:53:26 GMT
Content-Length: 903

{ "alerts": [{
  "text": "Delivery Service safe update successful.",
  "level": "success"
}],
"response": [{
  "active": true,
  "anonymousBlockingEnabled": false,
  "ccrDnsTtl": null,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "checkPath": null,
```

(continues on next page)

(continued from previous page)

```

"consistentHashQueryParams": [],
"consistentHashRegex": null,
"deepCachingType": "NEVER",
"displayName": "test",
"dnsBypassCname": null,
"dnsBypassIp": null,
"dnsBypassIp6": null,
"dnsBypassTtl": null,
"dscp": 0,
"ecsEnabled": false,
"edgeHeaderRewrite": null,
"exampleURLs": [
    "http://video.demo2.mycdn.ciab.test",
    "https://video.demo2.mycdn.ciab.test"
],
"firstHeaderRewrite": null,
"fqPacingRate": null,
"geoLimit": 0,
"geoLimitCountries": null,
"geoLimitRedirectURL": null,
"geoProvider": 0,
"globalMaxMbps": null,
"globalMaxTps": null,
"httpBypassFqdn": null,
"id": 1,
"infoUrl": "this is not even a real URL",
"initialDispersion": 1,
"innerHeaderRewrite": null,
"ipv6RoutingEnabled": true,
"lastHeaderRewrite": null,
"lastUpdated": "2021-06-07T23:53:26.139899Z",
"logsEnabled": true,
"longDesc": "this is a description of the delivery service",
"matchList": [
    {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo2\\.\\.\\.*"
    }
],
"maxDnsAnswers": null,
"maxOriginConnections": 0,
"maxRequestHeaderBytes": 0,
"midHeaderRewrite": null,
"missLat": 42,
"missLong": -88,

```

(continues on next page)

(continued from previous page)

```

"multiSiteOrigin": true,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 2,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"rangeSliceBlockSize": null,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "video",
"serviceCategory": null,
"signed": false,
"signingAlgorithm": null,
"sslKeyVersion": null,
"tenant": "root",
"tenantId": 1,
"tlsVersions": null,
"topology": "demo1-top",
"trResponseHeaders": null,
"trRequestHeaders": null,
"type": "DNS",
"typeId": 5,
"xmlId": "demo2"
  ]}

```

`deliveryservices/{{id}}/server_types/{{type}}/metric_types/start_date/{{start}}/end_date/{{end}}`

Danger: This endpoint doesn't appear to work, and so its use is strongly discouraged! The below documentation cannot be verified, therefore it may be inaccurate and/or incomplete!

GET

Retrieves detailed and summary metrics for Mid-tier and Edge-tier caches assigned to a *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 473: Request Path Parameters

Name	Re-quired	Description
id	yes	The delivery service id.
server_type	yes	EDGE or MID.
metric_type	yes	One of the following: “kpbs”, “tps”, “tps_2xx”, “tps_3xx”, “tps_4xx”, “tps_5xx”.
start_date	yes	UNIX time
end_date	yes	UNIX time

Table 474: Request Query Parameters

Name	Required	Description
stats	no	Flag used to return only summary metrics

Response Structure

Parameter	Type	Description
stats	hash	
>>count	int	
>>98thPercentile	number	
>>min	number	
>>max	number	
>>5thPercentile	number	
>>95thPercentile	number	
>>median	number	
>>mean	number	
>>stddev	number	
>>sum	number	
data	array	
>>item	array	
>>time	number	
>>value	number	
label	string	

1162: Response Example

```
{ "response": [
  {
    "stats": {
      "count": 988,
```

(continues on next page)

(continued from previous page)

```

        "98thPercentile": 16589105.55958,
        "min": 3185442.975,
        "max": 17124754.257,
        "5thPercentile": 3901253.95445,
        "95thPercentile": 16013210.034,
        "median": 8816895.576,
        "mean": 8995846.31741194,
        "stddev": 3941169.83683573,
        "sum": 333296106.060112
    },
    "data": [
        [
            1414303200000,
            12923518.466
        ],
        [
            1414303500000,
            12625139.65
        ]
    ],
    "label": "MID Kbps"
}
]]}

```

`deliveryservices/{{ID}}/servers`

Caution: It's often much easier to use `deliveryservices/{{xml_id}}/servers` instead

GET

Retrieves properties of Edge-Tier servers assigned to a *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 475: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the Delivery service for which servers will be displayed

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId An integral, unique identifier the CDN to which the server belongs

cdnName The name of the CDN to which the server belongs

domainName The domain name part of the FQDN of the server

guid Optionally represents an identifier used to uniquely identify the server

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS requests - 443 in most cases

id An integral, unique identifier for the server

iloIpAddress The IPv4 address of the lights-out-management port¹

iloIpGateway The IPv4 gateway address of the lights-out-management port^{Page 1544, 1}

iloIpNetmask The IPv4 subnet mask of the lights-out-management port^{Page 1544, 1}

iloPassword The password of the of the lights-out-management user - displays as ***** unless the requesting user has the ‘admin’ role)^{Page 1544, 1}

iloUsername The user name for lights-out-management^{Page 1544, 1}

interfaces An array of interface and IP address information

max_bandwidth The maximum allowed bandwidth for this interface to be considered “healthy” by Traffic Monitor. This has no effect if *monitor* is not true. Values are in kb/s. The value *null* means “no limit”.

monitor A boolean indicating if Traffic Monitor should monitor this interface

¹ See [the Wikipedia article on Out-of-Band Management](#) for more information.

mtu The MTU to configure for `interfaceName`

See also:

[The Wikipedia article on Maximum Transmission Unit](#)

name The network interface name used by the server.

ipAddresses An array of the IP address information for the interface

address The IPv4 or IPv6 address and subnet mask of the server - applicable for the interface name

gateway The IPv4 or IPv6 gateway address of the server - applicable for the interface name

service_address A boolean determining if content will be routed to the IP address

lastUpdated The time and date at which this server was last updated, in *Traffic Ops's Custom Date/Time Format*

mgmtIpAddress The IPv4 address of the server's management port

mgmtIpGateway The IPv4 gateway of the server's management port

mgmtIpNetmask The IPv4 subnet mask of the server's management port

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status (will be empty if not offline)

physLocation The name of the *Physical Location* at which the server resides

physLocationId An integral, unique identifier for the *Physical Location* at which the server resides

profile The *Name* of the *Profile* assigned to this server

profileDesc A *Description* of the *Profile* assigned to this server

profileId The *ID* of the *Profile* assigned to this server

rack A string indicating "rack" location

routerHostName The human-readable name of the router

routerPortName The human-readable name of the router port

status The Status of the server

See also:

[Health Protocol](#)

statusId An integral, unique identifier for the status of the server

See also:

Health Protocol

tcpPort The default port on which the main application listens for incoming TCP connections - 80 in most cases

type The name of the type of this server

typeId An integral, unique identifier for the type of this server

updPending true if the server has updates pending, false otherwise

1163: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: MaIva080Sjysr4bCkuXFEMf3o6mOqga1aM4IHN/
→tcP2aa1iXEmA5IrHB7DaqNX/2vGHLXvN+01FEAR/lRNqr1w==
X-Server-Name: traffic_ops_golang/
Date: Wed, 14 Nov 2018 21:28:23 GMT
Content-Length: 891

{ "response": [
  {
    "cachegroup": "CDN_in_a_Box_Edge",
    "cachegroupId": 7,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "domainName": "infra.ciab.test",
    "guid": null,
    "hostName": "edge",
    "httpsPort": 443,
    "id": 10,
    "iloIpAddress": "",
    "iloIpGateway": "",
    "iloIpNetmask": "",
    "iloPassword": "",
    "iloUsername": "",
    "lastUpdated": "2018-11-14 21:08:44+00",
    "mgmtIpAddress": "",
    "mgmtIpGateway": "",
    "mgmtIpNetmask": "",
```

(continues on next page)

(continued from previous page)

```

"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_EDGE_TIER_CACHE",
"profileDesc": "Edge Cache - Apache Traffic Server",
"profileId": 9,
"rack": "",
"routerHostName": "",
"routerPortName": "",
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "EDGE",
"typeId": 11,
"updPending": false,
"interfaces": [{
  "ipAddresses": [
    {
      "address": "172.16.239.100",
      "gateway": "172.16.239.1",
      "service_address": true
    },
    {
      "address": "fc01:9400:1000:8::100",
      "gateway": "fc01:9400:1000:8::1",
      "service_address": true
    }
  ],
  "max_bandwidth": 0,
  "monitor": true,
  "mtu": 1500,
  "name": "eth0"
}]
}
}]

```

deliveryservices/{{ID}}/servers/eligible

Caution: This endpoint may not work as advertised, and its use is therefore discouraged!

GET

Retrieves properties of *Edge-tier cache servers* eligible for assignment to a particular *Delivery Service*. Eligibility is determined based on the following properties:

- The name of the server's *Type* must match one of the glob patterns `EDGE*`, `ORG*`
- The server and *Delivery Service* must belong to the same CDN
- If the *Delivery Service* has *Required Capabilities*, an *Edge-tier cache server* must have all of those defined capabilities

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 476: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the Delivery service for which servers will be displayed

Response Structure

cachegroup A string which is the *Name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId An integral, unique identifier the CDN to which the server belongs

cdnName The name of the CDN to which the server belongs

domainName The domain name part of the FQDN of the server

guid Optionally represents an identifier used to uniquely identify the server

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS requests - 443 in most cases

id An integral, unique identifier for the server

iloIpAddress The IPv4 address of the lights-out-management port¹

iloIpGateway The IPv4 gateway address of the lights-out-management port^{Page 1544, 1}

iloIpNetmask The IPv4 subnet mask of the lights-out-management port^{Page 1544, 1}

iloPassword The password of the of the lights-out-management user - displays as ***** unless the requesting user has the ‘admin’ role)^{Page 1544, 1}

iloUsername The user name for lights-out-management^{Page 1544, 1}

interfaces An array of interface and IP address information

max_bandwidth The maximum allowed bandwidth for this interface to be considered “healthy” by Traffic Monitor. This has no effect if *monitor* is not true. Values are in kb/s. The value *null* means “no limit”.

monitor A boolean indicating if Traffic Monitor should monitor this interface

mtu The MTU to configure for *interfaceName*

See also:

[The Wikipedia article on Maximum Transmission Unit](#)

name The network interface name used by the server.

ipAddresses An array of the IP address information for the interface

address The IPv4 or IPv6 address and subnet mask of the server - applicable for the interface name

gateway The IPv4 or IPv6 gateway address of the server - applicable for the interface name

service_address A boolean determining if content will be routed to the IP address

lastUpdated The time and date at which this server was last updated, in *Traffic Ops’s Custom Date/Time Format*

mgmtIpAddress The IPv4 address of the server’s management port

mgmtIpGateway The IPv4 gateway of the server’s management port

mgmtIpNetmask The IPv4 subnet mask of the server’s management port

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status (will be empty if not offline)

¹ See [the Wikipedia article on Out-of-Band Management](#) for more information.

- physLocation** The name of the *Physical Location* at which the server resides
- physLocationId** An integral, unique identifier for the *Physical Location* at which the server resides
- profile** The *Name* of the *Profile* assigned to this server
- profileDesc** A *Description* of the *Profile* assigned to this server
- profileId** The *ID* of the *Profile* assigned to this server
- rack** A string indicating “rack” location
- routerHostName** The human-readable name of the router
- routerPortName** The human-readable name of the router port
- status** The Status of the server
- See also:**
- Health Protocol*
- statusId** An integral, unique identifier for the status of the server
- See also:**
- Health Protocol*
- tcpPort** The default port on which the main application listens for incoming TCP connections - 80 in most cases
- type** The name of the *Type* of this server
- typeId** An integral, unique identifier for the *Type* of this server
- updPending** true if the server has updates pending, false otherwise

1164: Response Example

```
{ "response": [
  {
    "cachegroup": "CDN_in_a_Box_Edge",
    "cachegroupId": 7,
    "cdnId": 2,
    "cdnName": "CDN-in-a-Box",
    "domainName": "infra.ciab.test",
    "guid": null,
    "hostName": "edge",
    "httpsPort": 443,
    "id": 10,
    "iloIpAddress": "",
    "iloIpGateway": "",
    "iloIpNetmask": "",
    "iloPassword": "",
    "iloUsername": "",
```

(continues on next page)

(continued from previous page)

```

    "lastUpdated": "2018-10-30 16:01:12+00",
    "mgmtIpAddress": "",
    "mgmtIpGateway": "",
    "mgmtIpNetmask": "",
    "offlineReason": "",
    "physLocation": "Apachecon North America 2018",
    "physLocationId": 1,
    "profile": "ATS_EDGE_TIER_CACHE",
    "profileDesc": "Edge Cache - Apache Traffic Server",
    "profileId": 9,
    "rack": "",
    "routerHostName": "",
    "routerPortName": "",
    "status": "REPORTED",
    "statusId": 3,
    "tcpPort": 80,
    "type": "EDGE",
    "typeId": 11,
    "updPending": false,
    "interfaces": [{
        "ipAddresses": [
            {
                "address": "172.16.239.100",
                "gateway": "172.16.239.1",
                "service_address": true
            },
            {
                "address": "fc01:9400:1000:8::100",
                "gateway": "fc01:9400:1000:8::1",
                "service_address": true
            }
        ],
        "max_bandwidth": 0,
        "monitor": true,
        "mtu": 1500,
        "name": "eth0"
    }]
}
]]

```

`deliveryservices/{{ID}}/urlkeys`

GET

See also:

`deliveryservices/xmlId/{{xmlid}}/urlkeys`

Retrieves URL signing keys for a *Delivery Service*.

Caution: This method will return the *Delivery Service*'s **PRIVATE** URL signing keys! Be wary of using this endpoint and **NEVER** share the output with anyone who would be unable to see it on their own.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 477: Request Path Parameters

Name	Description
id	Filter for the <i>Delivery Service</i> identified by this integral, unique identifier

1165: Request Example

```
GET /api/4.0/deliveryservices/1/urlkeys HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

key<N> The private URL signing key for this *Delivery Service* as a base-64-encoded string, where <N> is the “generation” of the key e.g. the first key will always be named "key0". Up to 16 concurrent generations are retained at any time (<N> is always on the interval [0,15])

1166: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 16:34:56
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: cTc5OPE3hM+CiyQPCy36zD2tsQcfkvIqQ7/
    ↳D82WGMWHm+ACW3YbcKhgPnSQU6+Tuj4jya52Kx9+nw5+OonFvPQ==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 15:34:56 GMT
Content-Length: 533

{
  "response": {
    "key0": "...",
    "key1": "...",
    "key2": "...",
    "key3": "...",
    "key4": "...",
    "key5": "...",
    "key6": "...",
    "key7": "...",
    "key8": "...",
    "key9": "...",
    "key10": "...",
    "key11": "...",
    "key12": "...",
    "key13": "...",
    "key14": "...",
    "key15": "...",
  }
}

```

DELETE

See also:

deliveryservices/xmlId/{xmlid}/urlkeys

Deletes URL signing keys for a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 478: Request Path Parameters

Name	Description
id	Filter for the <i>Delivery Service</i> identified by this integral, unique identifier

Response Structure

1167: Response Example

```
{
  "alerts": [{
    "level": "success",
    "text": "Successfully deleted URL Sig keys from Traffic Vault"
  }]
}
```

deliveryservices_regexes

GET

Retrieves routing regular expressions for all *Delivery Services*.

Auth. Required Yes

Roles Required None¹

Response Type Array

¹ If tenancy is used, then users (regardless of role) will only be able to see the routing regular expressions used by *Delivery Services* their tenant has permissions to see.

Request Structure

No parameters available

Response Structure

dsName The name of the *Delivery Service* represented by this object

regexes An array of objects that represent various routing regular expressions used by dsName

pattern The actual regular expression - \s are escaped

setNumber The order in which the regular expression is evaluated against requests

type The type of regular expression - determines that against which it will be evaluated

1168: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +2MI+Q/NJqTizlMR/MhPAL+yu6/z/
→Yqvo5fD08F593RM0mK6dX/Al4wARbEG+HQaJNgSCRPSiLVATusrmnnCMA==
X-Server-Name: traffic_ops_golang/
Date: Tue, 27 Nov 2018 19:22:59 GMT
Content-Length: 110

{ "response": [
  {
    "regexes": [
      {
        "type": "HOST_REGEX",
        "setNumber": 0,
        "pattern": ".*\\.demo1\\.\\.*"
      }
    ],
    "dsName": "demo1"
  }
]
}
```

deliveryservices_required_capabilities

GET

Gets all associations of *Server Capability* to *Delivery Services*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 479: Request Query Parameters

Name	Re- quired	Description
deliv- ery- Servi- ceID	no	Filter <i>Server Capability</i> associations by <i>Delivery Service</i> integral, unique identifier
xml- IID	no	Filter <i>Server Capability</i> associations by <i>Delivery Service xml_id</i>
re- quired- Capa- bility	no	Filter <i>Server Capability</i> associations by <i>Server Capability</i> name
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1169: Request Example

```
GET /api/4.0/deliveryservices_required_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

deliveryServiceID The associated *Delivery Service*'s integral, unique identifier

xmlID The associated *Delivery Service*'s *xml_id*

lastUpdated The date and time at which this association between the *Delivery Service* and the *Server Capability* was last updated, in *Traffic Ops's Custom Date/Time Format*

requiredCapability The *Server Capability*'s name

1170: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
    ↳jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
    ↳DbBwhMAOJoeqDImoDlrLnrVjQG04AooA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 396

{
  "response": [
    {
      "deliveryServiceID": 1,
      "lastUpdated": "2019-10-07 22:05:31+00",
      "requiredCapability": "ram",
      "xmlId": "example_ds-1"
    },
    {
      "deliveryServiceID": 2,
      "lastUpdated": "2019-10-07 22:05:31+00",
      "requiredCapability": "disk",
      "xmlId": "example_ds-2"
    }
  ]
}
```

POST

Associates a *Server Capability* with a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Note: A *Server Capability* can only be made required on a *Delivery Service* if its associated Servers already have that *Server Capability* assigned.

Request Structure

deliveryServiceID The integral, unique identifier of the *Delivery Service* to be associated

requiredCapability The name of the *Server Capability* to be associated

1171: Request Example

```
POST /api/4.0/deliveryservices_required_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "deliveryServiceID": 1,
  "requiredCapability": "disk"
}
```

Response Structure

deliveryServiceID The newly associated *Delivery Service*’s integral, unique identifier

lastUpdated The date and time at which this association between the *Delivery Service* and the *Server Capability* was last updated, in *Traffic Ops’s Custom Date/Time Format*

requiredCapability The newly associated *Server Capability*’s name

1172: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳eQrl48zWids0kDpfCYmntYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
    ↳Cfh2X9i3G+MQ36eH95gukJq0BOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 287

{
  "alerts": [
    {
      "level": "success",
      "text": "deliveryservice.RequiredCapability was created."
    }
  ],
  "response": {
    "deliveryServiceID": 1,
    "lastUpdated": "2019-10-07 22:15:11+00",
    "requiredCapability": "disk"
  }
}
```

DELETE

Dissociate a *Server Capability* from a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

deliveryServiceID The integral, unique identifier of the *Delivery Service* from which a *Server Capability* will be dissociated

requiredCapability The name of the *Server Capability* to dissociate

1173: Request Example

```
POST /api/4.0/deliveryservices_required_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "deliveryServiceID": 1,
  "requiredCapability": "disk"
}
```

Response Structure

1174: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
  ↳Cfh2X9i3G+MQ36eH95gukJqOBOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 127

{
  "alerts": [
    {
      "level": "success",
      "text": "deliveryservice.RequiredCapability was deleted."
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```

    }
  ]
}
```

deliveryservices/sslkeys/add

See also:

In most cases it is preferable to allow Traffic Ops to generate the keys via [deliveryservices/sslkeys/generate](#), rather than uploading them manually using this endpoint.

POST

Allows user to upload an SSL certificate, csr, and private key for a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

cdn The name of the CDN to which the *Delivery Service* belongs

certificate An object that contains the actual components of the SSL key

crt The certificate for the *Delivery Service* identified by key

csr The csr file for the *Delivery Service* identified by key

key The private key for the *Delivery Service* identified by key

key The *xml_id* of the *Delivery Service* to which these keys will be assigned

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

1175: Request Example

```

POST /api/4.0/deliveryservices/sslkeys/add HTTP/1.1
Host: trafficops.infra.ciab.test
Content-Type: application/json

{
  "key": "ds-01",
  "version": "1",
```

(continues on next page)

(continued from previous page)

```
"certificate": {
  "key": "some_key",
  "csr": "some_csr",
  "crt": "some_crt"
}
```

Response Structure

1176: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "response": "Successfully added ssl keys for ds-01"
}
```

deliveryservices/sslkeys/generate

POST

Generates an SSL certificate, csr, and private key for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

city An optional field which, if present, will represent the resident city of the generated SSL certificate

country An optional field which, if present, will represent the resident country of the generated SSL certificate

hostname The desired hostname of the *Delivery Service*

Note: In most cases, this must be the same as the *Delivery Service* URL’

key The *xml_id* of the *Delivery Service* for which keys will be generated

organization An optional field which, if present, will represent the organization for which the SSL certificate was generated

state An optional field which, if present, will represent the resident state or province of the generated SSL certificate

businessUnit An optional field which, if present, will represent the business unit for which the SSL certificate was generated

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

1177: Request Example

```
POST /api/4.0/deliveryservices/sslkeys/generate HTTP/1.1
Content-Type: application/json
```

```
{
  "key": "ds-01",
  "businessUnit": "CDN Engineering",
  "version": "3",
  "hostname": "tr.ds-01.ott.kabletown.com",
  "country": "US",
  "organization": "Kabletown",
  "city": "Denver",
  "state": "Colorado"
}
```

Response Structure

1178: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": "Successfully created ssl keys for ds-01" }
```

deliveryservices/sslkeys/generate/acme

New in version 4.0.

POST

Generates an SSL certificate and private key using ACME protocol for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

authType The certificate provider correlating to an ACME account in *cdn.conf* or Let’s Encrypt.

key The *xml_id* of the *Delivery Service* for which keys will be generated¹

deliveryservice The *xml_id* of the *Delivery Service* for which keys will be generated^{Page 1730, 1}

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

hostname The desired hostname of the *Delivery Service*

Note: In most cases, this must be the same as the *Example URLs*.

cdn The name of the CDN of the *Delivery Service* for which the certs will be generated

¹ Either the key or the deliveryservice field must be provided. If both are provided, then they must match.

1179: Request Example

```
POST /api/4.0/deliveryservices/sslkeys/generate/acme HTTP/1.1
Content-Type: application/json

{
  "authType": "Lets Encrypt",
  "key": "ds-01",
  "deliveryservice": "ds-01",
  "version": "3",
  "hostname": "tr.ds-01.ott.kabletown.com",
  "cdn": "test-cdn"
}
```

Response Structure

1180: Response Example

```
{ "alerts": [{
  "level": "success",
  "text": "Beginning async ACME call for demo1 using Lets Encrypt.
→ This may take a few minutes. Status updates can be found here: /api/
→ 4.0/async_status/1"
}]}
```

deliveryservices/sslkeys/generate/letsencrypt

Deprecated since version ATCv6.

POST

Generates an SSL certificate and private key using Let's Encrypt for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

key The *xml_id* of the *Delivery Service* for which keys will be generated¹

deliveryservice The *xml_id* of the *Delivery Service* for which keys will be generated^{Page 1730, 1}

version An integer that defines the “version” of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

hostname The desired hostname of the *Delivery Service*

Note: In most cases, this must be the same as the *Example URLs*.

cdn The name of the CDN of the *Delivery Service* for which the certs will be generated

1181: Request Example

```
POST /api/4.0/deliveryservices/sslkeys/generate/letsencrypt HTTP/1.1
Content-Type: application/json

{
  "key": "ds-01",
  "deliveryservice": "ds-01",
  "version": "3",
  "hostname": "tr.ds-01.ott.kabletown.com",
  "cdn": "test-cdn"
}
```

Response Structure

1182: Response Example

```
{ "alerts": [{
  "level": "warning",
  "text": "This endpoint is deprecated, please use /deliveryservices/
→sslkeys/generate/acme instead."
},{
  "level": "success",
  "text": "Beginning async ACME call for demo1 using Lets Encrypt.
→This may take a few minutes. Status updates can be found here: /api/
→4.0/async_status/1"
}]}
```

¹ Either the key or the deliveryservice field must be provided. If both are provided, then they must match.

`deliveryservices/{xml_id}/servers`

POST

Assigns *cache servers* to a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type Object

Request Structure

Table 480: Request Path Parameters

Name	Description
xml_id	The ‘xml_id’ of the <i>Delivery Service</i> whose server assignments are being edited

serverNames An array of hostname of *cache servers* to assign to this *Delivery Service*

1183: Request Example

```
POST /api/4.0/deliveryservices/test/servers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 24
Content-Type: application/json

{ "serverNames": [ "edge" ] }
```

Response Structure

xml_id The *xml_id* of the *Delivery Service* to which the servers in **serverNames** have been assigned

serverNames An array of hostnames of *cache servers* assigned to *Delivery Service* identified by **xml_id**

1184: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

¹ Users can only assign servers to *Delivery Services* that are visible to their *Tenant*.

(continued from previous page)

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳zTpLrWiLM4xRsm8mlBQFB5KzT478AjloSyXHgtyWhebCv1YIwWltnmkjr0HFgc3GMGZODt+fyzk0Yy5Zl/
    ↳yBtJw==
X-Server-Name: traffic_ops_golang/
Date: Tue, 20 Nov 2018 15:21:50 GMT
Content-Length: 52

{ "response": {
  "serverNames": [
    "edge"
  ],
  "xmlId": "test"
}}
```

`deliveryservices/{xml_id}/urisignkeys`

DELETE

Deletes URISigning objects for a *Delivery Service*.

Auth. Required Yes

Roles Required admin¹

Response Type undefined

Request Structure

Table 481: Request Path Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

¹ URI Signing Keys can only be created, viewed, deleted, or modified on *Delivery Services* that either match the requesting user's *Tenant* or are descendants thereof.

Response Structure

TBD

GET

Retrieves one or more URISigning objects for a delivery service.

Auth. Required Yes

Roles Required admin [Page 1730, 1](#)

Response Type undefined

Request Structure

Table 482: Request Route Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Response Structure

Issuer a string describing the issuer of the URI signing object. Multiple URISigning objects may be returned in a response, see example

renewal_kid a string naming the jwt key used for renewals

keys json array of jwt symmetric keys

alg this parameter repeats for each jwt key in the array and specifies the jwa encryption algorithm to use with this key, [RFC 7518](#)

kid this parameter repeats for each jwt key in the array and specifies the unique id for the key as defined in [RFC 7516](#)

kty this parameter repeats for each jwt key in the array and specifies the key type as defined in [RFC 7516](#)

k this parameter repeats for each jwt key in the array and specifies the base64 encoded symmetric key see [RFC 7516](#)

1185: Response Example

```
{ "Kabletown URI Authority": {
  "renewal_kid": "Second Key",
  "keys": [
    {
      "alg": "HS256",
```

(continues on next page)

(continued from previous page)

```

        "kid": "First Key",
        "kty": "oct",
        "k": "Kh_RkUMj-fzbD37qBnDf_3e_RvQ3RP9PaSmVEpE24AM"
    },
    {
        "alg": "HS256",
        "kid": "Second Key",
        "kty": "oct",
        "k": "fZBpDBNbk2GqhwoB_DGBAsBxqQZVix04rIoLJ7p_RlE"
    }
]
}}
```

POST

Assigns URISigning objects to a delivery service.

Auth. Required Yes

Roles Required admin Page 1730, 1

Response Type undefined

Request Structure

Table 483: Request Path Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Request Structure

Issuer a string describing the issuer of the URI signing object. Multiple URISigning objects may be returned in a response, see example

renewal_kid a string naming the jwt key used for renewals

keys json array of jwt symmetric keys

alg this parameter repeats for each jwt key in the array and specifies the jwa encryption algorithm to use with this key, [RFC 7518](#)

kid this parameter repeats for each jwt key in the array and specifies the unique id for the key as defined in [RFC 7516](#)

kty this parameter repeats for each jwt key in the array and specifies the key type as defined in [RFC 7516](#)

k this parameter repeats for each jwt key in the array and specifies the base64 encoded symmetric key see [RFC 7516](#)

1186: Request Example

```
{ "Kabletown URI Authority": {
  "renewal_kid": "Second Key",
  "keys": [
    {
      "alg": "HS256",
      "kid": "First Key",
      "kty": "oct",
      "k": "Kh_RkUMj-fzbD37qBnDf_3e_RvQ3RP9PaSmVEpE24AM"
    },
    {
      "alg": "HS256",
      "kid": "Second Key",
      "kty": "oct",
      "k": "fZBpDBNbk2GqhwoB_DGBAsBxqQZVix04rIoLJ7p_RlE"
    }
  ]
}}
```

PUT

updates URISigning objects on a delivery service.

Auth. Required Yes

Roles Required admin Page 1730, 1

Response Type undefined

Request Structure

Table 484: Request Path Parameters

Name	Required	Description
xml_id	yes	xml_id of the desired delivery service

Request Structure

Issuer a string describing the issuer of the URI signing object. Multiple URISigning objects may be returned in a response, see example

renewal_kid a string naming the jwt key used for renewals

keys json array of jwt symmetric keys

alg this parameter repeats for each jwt key in the array and specifies the jwa encryption algorithm to use with this key, [RFC 7518](#)

kid this parameter repeats for each jwt key in the array and specifies the unique id for the key as defined in [RFC 7516](#)

kty this parameter repeats for each jwt key in the array and specifies the key type as defined in [RFC 7516](#)

k this parameter repeats for each jwt key in the array and specifies the base64 encoded symmetric key see [RFC 7516](#)

1187: Request Example

```
{ "Kabletown URI Authority": {
  "renewal_kid": "Second Key",
  "keys": [
    {
      "alg": "HS256",
      "kid": "First Key",
      "kty": "oct",
      "k": "Kh_RkUMj-fzbD37qBnDf_3e_RvQ3RP9PaSmVEpE24AM"
    },
    {
      "alg": "HS256",
      "kid": "Second Key",
      "kty": "oct",
      "k": "fZBpDBNbk2GqhwoB_DGBAsBxqQZVix04rIoLJ7p_RlE"
    }
  ]
}}
```

`deliveryservices/xmlId/{{XMLID}}/sslkeys`

GET

Retrieves SSL keys for a *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 485: Request Path Parameters

Name	Description
XMLID	The ‘xml_id’ of the desired <i>Delivery Service</i>

Table 486: Request Query Parameters

Name	Re-quired	Description
ver-sion	no	The version number of the SSL keys to retrieve
de-code	no	If <code>true</code> , the returned keys will be decoded - if <code>false</code> , they will not be decoded

Caution: There’s almost certainly no good reason to request the private key! Even when “base 64-encoded” do not let **ANYONE** see this who would be unable to request it themselves!

Response Structure

businessUnit An optional field which, if present, contains the business unit entered by the user when generating the SSL certificate¹

certificate An object containing the actual generated key, certificate, and signature of the SSL keys

crt Base 64-encoded (or not if the decode query parameter was given and `true`) certificate for the *Delivery Service* identified by `deliveryservice`

¹ These optional fields will be present in the response if and only if they were specified during key generation; they are optional during key generation and thus cannot be guaranteed to exist or not exist.

csr Base 64-encoded (or not if the decode query parameter was given and true) csr file for the *Delivery Service* identified by deliveryservice

key Base 64-encoded (or not if the decode query parameter was given and true) private key for the *Delivery Service* identified by deliveryservice

Caution: There's almost certainly no good reason to request the private key! Even when "base 64-encoded" do not let **ANYONE** see this who would be unable to request it themselves!

cdn The CDN of the *Delivery Service* for which the certs were generated

city An optional field which, if present, contains the city entered by the user when generating the SSL certificate^{Page 1749, 1}

country An optional field which, if present, contains the country entered by the user when generating the SSL certificate^{Page 1749, 1}

deliveryservice The 'xml_id' of the *Delivery Service* for which the certificate was generated

hostname The hostname generated by Traffic Ops that is used as the common name when generating the certificate - this will be a FQDN for DNS *Delivery Services* and a wildcard URL for HTTP *Delivery Services*

organization An optional field which, if present, contains the organization entered by the user when generating certificate^{Page 1749, 1}

state An optional field which, if present, contains the state entered by the user when generating certificate^{Page 1749, 1}

version An integer that defines the "version" of the key - which may be thought of as the sequential generation; that is, the higher the number the more recent the key

expiration The expiration date of the certificate for the *Delivery Service* in **RFC 3339** format

1188: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": {
  "certificate": {
    "crt": "crt",
    "key": "key",
    "csr": "csr"
  },

```

(continues on next page)

(continued from previous page)

```
"deliveryservice": "my-ds",
"cdn": "qa",
"businessUnit": "CDN_Eng",
"city": "Denver",
"organization": "KableTown",
"hostname": "foober.com",
"country": "US",
"state": "Colorado",
"version": "1",
"expiration": "2020-08-18T13:53:06Z"
}}
```

DELETE

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 487: Request Path Parameters

Name	Required	Description
xmlId	yes	The <i>xml_id</i> of the desired <i>Delivery Service</i>

Table 488: Request Query Parameters

Name	Required	Description
version	no	The version number of the SSL keys that shall be retrieved

Response Structure

1189: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 18 Mar 2020 17:36:10 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Pj+zCoOXg19nGNxcSkjib2iDjG062Y3RcEEV+0YnwbGIsLcpa0BKZleY/qJOKT5DkSoX2qQkckUxUqdDxjVorQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 18 Mar 2020 16:36:10 GMT
Content-Length: 79

{
  "response": "Successfully deleted ssl keys for demo1"
}
```

`deliveryservices/xmlId/{xmlid}/urlkeys`

GET

See also:

deliveryservices/{ID}/urlkeys

Retrieves URL signing keys for a *Delivery Service*.

Caution: This method will return the *Delivery Service*'s **PRIVATE** URL signing keys! Be wary of using this endpoint and **NEVER** share the output with anyone who would be unable to see it on their own.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 489: Request Path Parameters

Name	Description
xmlid	The 'xml_id' of the desired <i>Delivery Service</i>

Response Structure

key<N> The private URL signing key for this *Delivery Service* as a base-64-encoded string, where <N> is the “generation” of the key e.g. the first key will always be named **key0**. Up to 16 concurrent generations are retained at any time (<N> is always on the interval [0,15])

1190: Response Example

```
{ "response": {
  "key9": "ZvVQNYpPVQWQV8tjQnUl6osm4y7xK4zD",
  "key6": "JhGdpw5X9o8TqHfgezCm0bqb9SQPASWL",
  "key8": "ySXdp1T8IeDEE10CMftzZb9EIw_20wwq",
  "key0": "D4AYzJ1AE2nYisA9MxMtY03TPDCHji9C",
  "key3": "W90YHlGc_kYlYw5_I0LrkpV9J0zSIneI",
  "key12": "ZbtMb3mrKqfS8hnx9_xWBIP_OPWlUpzc",
  "key2": "0qgEoD07sUsugIQemZbwmMt0tNCwB1sf",
  "key4": "aFJ2Gb7atmxVB8uv7T9S60aDml3ycpGf",
  "key1": "wnWNR1mCz104C7EFPtcqHd0xUMQyNFhA",
  "key11": "k6HMzlBH1x6htKkypRFfWQhAndQqe50e",
  "key10": "zYONfdD7fGYKj4kLvIj4U0918csuZ00d",
  "key15": "3360cGaIip_layZMc_0hI2teJbazxTQh",
  "key5": "SIwv3G0hWN7EE9wSwPFj18qE4M07sFxFN",
  "key13": "SqQKBR6LqE0zp8AewZUCVtBcW_8YFc1g",
  "key14": "DtXsu8nsw04YhT0kNoKBhu2G3P9WRpQJ",
  "key7": "cmKoIIxXGAxUMdCsWvnGLoIMGmNiuT5I"
}}
```

DELETE

See also:

deliveryservices/{ID}/urlkeys

Deletes URL signing keys for a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 490: Request Path Parameters

Name	Description
xmlid	The ‘xml_id’ of the desired <i>Delivery Service</i>

Response Structure

1191: Response Example

```
{
  "alerts": [{
    "level": "success",
    "text": "Successfully deleted URL Sig keys from Traffic Vault"
  }]
}
```

`deliveryservices/xmlId/{{xml_id}}/urlkeys/copyFromXmlId/
{{copyFrom_xml_id}}`

POST

Allows a user to copy URL signing keys from a specified *Delivery Service* to another *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 491: Request Path Parameters

Name	Description
xml_id	The <i>xml_id</i> of the <i>Delivery Service</i> to which keys will be copied
copyFrom_xml_id	The <i>xml_id</i> of the <i>Delivery Service</i> from which keys will be copied

Response Structure

1192: Response Example

```
{
  "response": "Successfully copied and stored keys"
}
```

`deliveryservices/xmlId/{xml_id}/urlkeys/generate`

POST

Generates URL signing keys for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object (string)

Request Structure

Table 492: Request Path Parameters

Name	Description
xml_id	The <i>xml_id</i> of the desired <i>Delivery Service</i>

Response Structure

1193: Response Example

```
{
  "response": "Successfully generated and stored keys"
}
```

`deliveryservicesserver`

GET

Retrieve information about the assignment of servers to *Delivery Services*

Auth. Required Yes

Roles Required None¹

¹ While no roles are required, this endpoint *does* respect tenancy permissions (pending [GitHub Issue #2978](#)).

Response Type Array

Request Structure

Table 493: Request Query Parameters

Name	Required	Default	Description
page	no	0	The page number for use in pagination - 0 means “no pagination”
limit	no	20	Limits the results to a maximum of this number - if pagination is used, this defines the number of results per page
orderby	no	“deliveryservice”	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array

1194: Request Example

```
GET /api/4.0/deliveryserviceserver?page=1&limit=2&orderby=lastUpdated_
→HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

Unlike most API endpoints, this will return a JSON response body containing both a “response” object as well as other, top-level fields (besides the optional “alerts” field). For this reason, this section contains a “response” key, which normally is implicit.

See also:

Response Structure

limit The maximum size of the response array, also indicative of the number of results per page using the pagination requested by the query parameters (if any) - this should be the same as the `limit` query parameter (if given)

orderby A string that names the field by which the elements of the response array are ordered - should be the same as the `orderby` request query parameter (if given)

response An array of objects, each of which represents a server’s *Delivery Service* assignment

deliveryService The integral, unique identifier of the *Delivery Service* to which the server identified by `server` is assigned

lastUpdated The date and time at which the server's assignment to a *Delivery Service* was last updated

server The integral, unique identifier of a server which is assigned to the *Delivery Service* identified by `deliveryService`

size The page number - if pagination was requested in the query parameters, else 0 to indicate no pagination - of the results represented by the response array. This is named "size" for legacy reasons

1195: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: J7sK8PohQWyTpTrMjJrWdlJwPj+Zyep/
    ↳xutM25uVosL6cHgi30nXa6VMYOC5Y3vd9r5KLES8rTgR+qUQcZcJ/A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 01 Nov 2018 14:27:45 GMT
Content-Length: 129

{ "orderBy": "lastUpdated",
  "response": [
    {
      "server": 8,
      "deliveryService": 1,
      "lastUpdated": "2018-11-01 14:10:38+00"
    }
  ],
  "size": 1,
  "limit": 2
}
```

POST

Assign a set of one or more servers to a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”²

Response Type Object

Request Structure

dsId The integral, unique identifier of the *Delivery Service* to which the servers identified in the `servers` array will be assigned

replace If `true`, any existing assignments for a server identified in the `servers` array will be overwritten by this request

servers An array of integral, unique identifiers for servers which are to be assigned to the *Delivery Service* identified by `deliveryService`

1196: Request Example

```
POST /api/4.0/deliveryserviceserver HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 46
Content-Type: application/x-www-form-urlencoded

dsId=1&replace=true&servers=12
```

Response Structure

dsId The integral, unique identifier of the *Delivery Service* to which the servers identified by the elements of the `servers` array have been assigned

replace If `true`, any existing assignments for a server identified in the `servers` array have been overwritten by this request

servers An array of integral, unique identifiers for servers which have been assigned to the *Delivery Service* identified by `deliveryService`

² Users with the “admin” or “operations” roles will be able to modify ALL server-to-Delivery-Service assignments, whereas all other users can only assign servers to the *Delivery Services* their Tenant has permissions to edit.

1197: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳D+HhGhoxzaxvka9vZIStoa0ZUpX23nz7zZnMbpFHNRO3MawyEaSb3GVUHQyCv6sDgwhpZZjRggDmctGCw
X-Server-Name: traffic_ops_golang/
Date: Thu, 01 Nov 2018 14:12:49 GMT
Content-Length: 123

{ "alerts": [
  {
    "text": "server assignments complete",
    "level": "success"
  }
],
"response": {
  "dsId": 1,
  "replace": false,
  "servers": [ 12 ]
}}
```

`deliveryserviceserver/{{DSID}}/{{serverID}}`

DELETE

Removes a *cache server* from a *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”¹

Response Type undefined

¹ Users with the “admin” or “operations” roles will be able to delete *any Delivery Service*, whereas other users will only be able to delete *Delivery Services* that their tenant has permissions to delete.

Request Structure

Table 494: Request Path Parameters

Name	Required	Description
dsId	yes	An integral, unique identifier for a <i>Delivery Service</i>
serverID	yes	An integral, unique identifier for a server

Note: The server identified by serverID must be a *cache server*, or the assignment will fail.

Response Structure

1198: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: rGD2sOMHYF0sga1zuTytyLHCUkkc3ZwQRKvZ/
    ↳HuPzObOP4WztKTOVXB4uhs3iJqBg9zRB2TucMxONHN+3/yShQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 01 Nov 2018 14:24:34 GMT
Content-Length: 80

{ "alerts": [
  {
    "text": "Server unlinked from delivery service.",
    "level": "success"
  }
]}
```


divisions

GET

Returns a JSON representation of all configured *Divisions*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 495: Request Query Parameters

Name	Description
id	Filter for <i>Divisions</i> having this integral, unique identifier
name	Filter for <i>Divisions</i> with this name
orderby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

Response Structure

id An integral, unique identifier for this Division

lastUpdated The date and time at which this Division was last modified, in *Traffic Ops’s Custom Date/Time Format*

name The Division name

1199: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→SLKi9RHa67sGoSz62IDcQsk7KZjTXKfonqMoCUFPXGcNUdhBssvUjc1G7KkWK8X1Ny16geMx2BN8Hm/
→3dQ75GA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 19:44:03 GMT
Content-Length: 139

{ "response": [
  {
    "id": 1,
    "lastUpdated": "2018-11-29 18:38:28+00",
    "name": "Quebec"
  },
  {
    "id": 2,
    "lastUpdated": "2018-11-29 18:38:28+00",
    "name": "USA"
  }
]}
```

POST

Creates a new Division.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the new Division

1200: Request Example

```
POST /api/4.0/divisions HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 16
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
{"name": "test"}
```

Response Structure

id An integral, unique identifier for this Division

lastUpdated The date and time at which this Division was last modified, in *Traffic Ops's Custom Date/Time Format*

name The Division name

1201: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +pJm4c30+JTaSXNt+LP+u240Ba/
    ↳SsvSSDOQ4rDc6hcyZ0FIL+iY/WWrMHhpLulRGKGY88bM4YPCMaxGn3FZ9yQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 19:52:06 GMT
Content-Length: 136

{ "alerts": [
  {
    "text": "division was created.",
    "level": "success"
  }
],
"response": {
  "id": 3,
  "lastUpdated": "2018-11-29 19:52:06+00",
  "name": "test"
}}
```

`divisions/{ID}`

PUT

Updates a specific Division

Auth. Required Yes

Roles Required “admin” or “operations”

Request Structure

Table 496: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the requested Division

name The new name of the Division

1202: Request Example

```
PUT /api/4.0/divisions/3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 17
Content-Type: application/json

{"name": "quest"}
```

Response Structure

id An integral, unique identifier for this Division

lastUpdated The date and time at which this Division was last modified, in *Traffic Ops’s Custom Date/Time Format*

name The Division name

1203: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: yBd8MzBR/Qbc/
→xTs44WEIFRTrqeMKZwUe2ufpm6JH6frh1UjFmYRs3/
→B7E5FTruFWRTuvEIlx5EpDmp3f9LjzA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 29 Nov 2018 20:10:36 GMT
Content-Length: 137

{ "alerts": [
  {
    "text": "division was updated.",
    "level": "success"
  }
],
"response": {
  "id": 3,
  "lastUpdated": "2018-11-29 20:10:36+00",
  "name": "quest"
}}
```

federation_resolvers

GET

Retrieves *Federation* Resolvers.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 497: Request Query Parameters

Name	Re-quired	Description
id	no	Return only the Federation Resolver identified by this integral, unique identifier
ipAd- dress	no	Return only the Federation Resolver(s) that has/have this IP Address
type	no	Return only the Federation Resolvers of this <i>Type</i>
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
off- set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1204: Request Example

```
GET /api/4.0/federation_resolvers?type=RESOLVE6 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.63.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

id The integral, unique identifier of the resolver

ipAddress The IP address or CIDR-notation subnet of the resolver - may be IPv4 or IPv6

lastUpdated The date and time at which this resolver was last updated, in *Traffic Ops’s Custom Date/Time Format*

type The *Type* of the resolver

1205: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→4TLkULAOAuap47H+hpwyf2lHjDbHbSNQHLMj7BCTHtps2CQxCuq7mwctbwqmPdmAjLOUXAIRsHmvSuAp4
X-Server-Name: traffic_ops_golang/
Date: Wed, 06 Nov 2019 00:03:56 GMT
Content-Length: 101

{ "response": [
  {
    "id": 1,
    "ipAddress": "::1/1",
    "lastUpdated": "2019-11-06 00:00:40+00",
    "type": "RESOLVE6"
  }
]}
```

POST

Creates a new federation resolver.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

ipAddress The IP address of the resolver - may be IPv4 or IPv6

typeId The integral, unique identifier of the *Type* of resolver being created

Caution: This field should only ever be an identifier for one of the *Types* “RESOLVE4” or “RESOLVE6”, but there is **no protection for this built into Traffic Ops** and therefore **any valid *Type* identifier will be silently accepted by Traffic Ops** and so care should be taken to ensure that these *Types* are properly identified. If any *Type* besides “RESOLVE4” or “RESOLVE6” is identified, the resulting resolver *will not work*.

See also:

types is the endpoint that can be used to determine the identifier for various

Types

1206: Request Example

```
POST /api/4.0/federation_resolvers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.63.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 36
Content-Type: application/json

{
  "ipAddress": "::1/1",
  "typeId": 37
}
```

Response Structure

id The integral, unique identifier of the resolver

ipAddress The IP address or CIDR-notation subnet of the resolver - may be IPv4 or IPv6

type The *Type* of the resolver

typeId The integral, unique identifier of the *Type* of the resolver

1207: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳e9D8JNrQb64xpuDwoBwbISSWUkDGCL2l37NuDXsXsPYof2EqmeHondD8NzxDSwWNJ8d9B9DXpZDbRUtgd
X-Server-Name: traffic_ops_golang/
Date: Wed, 06 Nov 2019 00:00:40 GMT
Content-Length: 153

{ "alerts": [
  {
    "text": "Federation Resolver created [ IP = ::1/1 ] with id: 1
  },
```

(continues on next page)

(continued from previous page)

```
        "level": "success"
      }
    ],
    "response": {
      "id": 1,
      "ipAddress": "::1/1",
      "type": "RESOLVE6",
      "typeId": 37
    }
  }
}
```

DELETE

Deletes a federation resolver.

- Auth. Required** Yes
- Roles Required** “admin”
- Response Type** Object

Request Structure

Table 498: Request Query Parameters

Name	Required	Description
id	yes	Integral, unique identifier for the federation resolver to be deleted

1208: Request Example

```
DELETE /api/4.0/federation_resolvers?id=4 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

id The integral, unique identifier of the resolver

ipAddress The IP address or CIDR-notation subnet of the resolver - may be IPv4 or IPv6

type The *Type* of the resolver

1209: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; HttpOnly
Whole-Content-Sha512:
  ↳2v4LYQdRVhaFJVd86Iv1BWVYzNPSlzpQ222bUB7Zz+Ss8A48FNyHZjPlq5a+a4g9KAQCTUIytWnIQk+L1
X-Server-Name: traffic_ops_golang/
Date: Fri, 08 Nov 2019 23:19:01 GMT
Content-Length: 161

{ "alerts": [
  {
    "text": "Federation resolver deleted [ IP = 1.2.6.4/22 ] with
    ↳id: 4",
    "level": "success"
  }
],
"response": {
  "id": 4,
  "ipAddress": "1.2.6.4/22",
```

(continues on next page)

(continued from previous page)

```
"type": "RESOLVE6"
}}
```

federations

GET

Retrieves a list of *Federation* mappings (i.e. *Federation* Resolvers) for the current user.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Array

Request Structure

No parameters available.

Response Structure

deliveryService The `xml_id` that uniquely identifies the *Delivery Service* that uses the federation mappings in mappings

mappings An array of objects that represent the mapping of a *Federation*’s CNAME to one or more Resolvers

cname The actual CNAME used by the *Federation*

resolve4 An array of IPv4 addresses (or subnets in CIDR notation) capable of resolving the *Federation*’s CNAME

resolve6 An array of IPv6 addresses (or subnets in CIDR notation) capable of resolving the *Federation*’s CNAME

ttl The TTL of the CNAME in hours

1210: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512:↵
↵d6Llm5qNc2sfgVH9IimW7hA4wvtBUq6EzUmpJf805kB0k6v2WysNgFEWK4hBXNdAYkr8hYuKPrwDy3tCx
X-Server-Name: traffic_ops_golang/
Date: Mon, 03 Dec 2018 17:19:13 GMT
Content-Length: 136

{ "response": [
  {
    "mappings": [
      {
        "ttl": 300,
        "cname": "blah.blah.",
        "resolve4": [
          "0.0.0.0/32"
        ],
        "resolve6": [
          "::/128"
        ]
      }
    ],
    "deliveryService": "demo1"
  }
]}
```

POST

Allows a user to create *Federation* Resolvers for *Delivery Services*, providing the *Delivery Service* is within a CDN that has some associated *Federation*.

Warning: Confusingly, this method of this endpoint does **not** create a new *Federation*; to do that, the *cdns/{{name}}/federations* endpoint must be used. Furthermore, the *Federation* must properly be assigned to a *Delivery Service* using the *federations/{{ID}}/deliveryservices* and assigned to the user creating Resolvers using *federations/{{ID}}/users*.

See also:

The *federations/{{ID}}/federation_resolvers* endpoint duplicates this functionality.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

The request payload is an array of objects that describe Delivery Service *Federation* Resolver mappings. Each object in the array must be in the following format.

deliveryService The *xml_id* of the *Delivery Service* which will use the *Federation* Resolvers specified in mappings

mappings An object containing two arrays of IP addresses (or subnets in CIDR notation) to use as *Federation* Resolvers

resolve4 An array of IPv4 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service's Federation*

resolve6 An array of IPv6 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service's Federation*

1211: Request Example

```
POST /api/4.0/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 118
Content-Type: application/json

[{"deliveryService": "demo1",
  "mappings": {
    "resolve4": ["127.0.0.1", "0.0.0.0/32"],
    "resolve6": [ "::1", "5efa::ff00/128"]
  }
}]
```

Response Structure

1212: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: B7TSUOYZPRPyi3mVy+CuxiXR5k/
↪d0s07w4i6kYzpWS+YL79juEfkusqfedayG/kMA809XbjkWRjcBAdxOVrdTQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 23 Oct 2019 22:28:02 GMT
Content-Length: 152

{ "alerts": [
  {
    "text": "admin successfully created federation resolvers.",
    "level": "success"
  }
],
"response": "admin successfully created federation resolvers."
}
```

DELETE

Deletes **all** *Federation* Resolvers associated with the logged-in user's *Federations*.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

No parameters available

1213: Request Example

```
DELETE /api/4.0/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1214: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳fd7P45mIiHuYqZZW6+8K+YjY1Pe504Aaw4J4Zp9AhrqLX72ERYtTqWtAp1msutzNSRUdUSC72+odNPtpv
X-Server-Name: traffic_ops_golang/
Date: Wed, 23 Oct 2019 23:34:53 GMT
Content-Length: 184

{ "alerts": [
  {
    "text": "admin successfully deleted all federation resolvers:
    ↳[ 8.8.8.8 ]",
    "level": "success"
  }
],
"response": "admin successfully deleted all federation resolvers: [ 8.
    ↳8.8.8 ]"
}
```

PUT

Replaces **all** *Federations* associated with a user's *Delivery Service*(s) with those defined inside the request payload.

Auth. Required Yes

Roles Required “admin”, “Federation”, “operations”, “Portal”, or “Steering”

Response Type Object (string)

Request Structure

The request payload is an array of objects that describe Delivery Service *Federation* Resolver mappings. Each object in the array must be in the following format.

deliveryService The *xml_id* of the *Delivery Service* which will use the *Federation* Resolvers specified in **mappings**

mappings An object containing two arrays of IP addresses (or subnets in CIDR notation) to use as *Federation* Resolvers

resolve4 An array of IPv4 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service*'s *Federation*

resolve6 An array of IPv6 addresses (or subnets in CIDR notation) that can resolve the *Delivery Service*'s *Federation*

1215: Request Example

```
PUT /api/4.0/federations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 95
Content-Type: application/json

[{"mappings": {
  "resolve4": ["8.8.8.8"],
  "resolve6": []
},
"deliveryService": "demo1"
}]
```

Response Structure

1216: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dQ5AvQULhc254zQwgUpBl1/CHbLr/
→clKtkbs0Ju9f1BM4xIfbb03puFNN9zaEaZ1iz0lBvHFp/PgfUqisD3QHA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 23 Oct 2019 23:22:03 GMT
Content-Length: 258
Content-Type: application/json

{ "alerts": [
  {
    "text": "admin successfully deleted all federation resolvers:
→[ 8.8.8.8 ]",
    "level": "success"
  },
  {
    "text": "admin successfully created federation resolvers.",
    "level": "success"
  }
]
```

(continues on next page)

(continued from previous page)

```
}
],
"response": "admin successfully created federation resolvers."
}
```

federations/all

GET

Retrieves a list of *Federation* mappings (also called *Federation* Resolvers) for the current user.

Auth. Required Yes

Roles Required “admin”

Response Type Array

Request Structure

No parameters available.

1217: Request Example

```
GET /api/4.0/federations/all HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

deliveryService The *xml_id* of the delivery service.

mappings An array of objects that represent the mapping of a *Federation*’s CNAME to one or more Resolvers

cname The actual CNAME used by the *Federation*

ttd The TTL of the CNAME in hours

1218: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Sun, 23 Feb 2020 21:38:06.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→UQBlGVPJytYMkv0V42EAIoJUnXjBTCXnOGp0berxte6TtnX63LTAKFfD2LejBVYXkKtnCdkBbs+SzhA0H.
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 20:38:06 GMT
Content-Length: 138

{
  "response": [
    {
      "mappings": [
        {
          "ttl": 60,
          "cname": "img1.mcdn.ciab.test."
        },
        {
          "ttl": 60,
          "cname": "img2.mycdn.ciab.test."
        }
      ],
      "deliveryService": "demo1"
    },
    {
      "mappings": [
        {
          "ttl": 60,
          "cname": "static.mycdn.ciab.test."
        }
      ],
      "deliveryService": "demo2"
    }
  ]
}
```

`federations/{{ID}}/deliveryservices`

GET

Retrieves *Delivery Services* assigned to a *Federation*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 499: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation to be inspected

Table 500: Request Query Parameters

Name	Re-quired	Description
dsID	no	Show only the <i>Delivery Service</i> identified by this integral, unique identifier
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1219: Request Example

```
GET /api/4.0/federations/1/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cdn** The CDN to which this *Delivery Service* Belongs
- id** The integral, unique identifier for the *Delivery Service*
- type** The routing type used by this *Delivery Service*
- xmlId** The 'xml_id' which uniquely identifies this *Delivery Service*

1220: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:44:13 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:44:13 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: 7Y9Q/
→qHeXfbjJduvucRCR85wf4VRfyYhlK59sNRkzIJuwnsMhFcEfYfNqrvELwfexOum/
→VEX2f/1oa+I/edGfw==
content-length: 74

{ "response": [
  {
    "xmlId": "demo1",
    "cdn": "CDN-in-a-Box",
    "type": "HTTP",
    "id": 1
  }
]}
```

POST

Assigns one or more *Delivery Services* to a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 501: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation to be inspected

dsIds An array of integral, unique identifiers for *Delivery Services* which will be assigned to this federation

replace An optional boolean (default: `false`) which, if `true`, will cause any conflicting assignments already in place to be overridden by this request

Note: If `replace` is not given (and/or not `true`), then any conflicts with existing assignments will cause the entire operation to fail.

1221: Request Example

```
POST /api/4.0/federations/1/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 32
Content-Type: application/json

{
  "dsIds": [1],
  "replace": true
}
```

Response Structure

dsIds An array of integral, unique identifiers for *Delivery Services* which are now assigned to this federation

replace An optional boolean (default: false) which, if true, means any conflicting assignments already in place were overridden by this request

1222: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
content-type: application/json
set-cookie: mojolicious=...; Path=/; HttpOnly
whole-content-sha512:
→rVd0nx8G3bRI8ub1zw6FTdmwQ7jer4zoqzOZf5tC1ckrR0HEIOH1Azdcmvv0FVE5I0omCHVnrYbzab7tU
x-server-name: traffic_ops_golang/
content-length: 137
date: Wed, 05 Dec 2018 00:34:06 GMT

{ "alerts": [
  {
    "text": "1 delivery service(s) were assigned to the federation",
    →1",
    "level": "success"
  }
],
```

(continues on next page)

(continued from previous page)

```
"response": {
  "dsIds": [
    1
  ],
  "replace": true
}}
```

`federations/{{ID}}/deliveryservices/{{dsID}}`

DELETE

Removes a *Delivery Service* from a federation. A *Delivery Service* cannot be removed from a federation if it is the only *Delivery Service* assigned to said federation

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 502: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the federation from which the <i>Delivery Service</i> identified by dsID will be removed
dsID	The integral, unique identifier of the <i>Delivery Service</i> which will be removed from the federation identified by ID

1223: Request Example

```
DELETE /api/4.0/federations/1/deliveryservices/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1224: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 01:06:51 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 05:06:51 GMT;
    ↳path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: NqAZuZYlF1UW0aazbj/
    ↳j4gWX7ye0kGGakRRFEkK6ShxqXvCxEOdCTyu75qiLPN2wSgr3FGQnp2Sq345sE7In9g==
content-length: 98

{ "alerts": [
  {
    "level": "success",
    "text": "federation deliveryservice was deleted."
  }
]}
```

federations/{{ID}}/federation_resolvers

GET

Retrieves federation resolvers assigned to a federation.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 503: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation for which resolvers will be retrieved

1225: Request Example

```
GET /api/4.0/federations/1/federation_resolvers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

id The integral, unique identifier of this federation resolver

ipAddress The IP address of the federation resolver - may be IPv4 or IPv6

type The type of resolver - one of:

RESOLVE4 This resolver is for IPv4 addresses (and **ipAddress** is IPv4)

RESOLVE6 This resolver is for IPv6 addresses (and **ipAddress** is IPv6)

1226: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:49:50 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:49:50 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: csC18kE3YjiILHP1wmJg7V4h/
→XWY8HUMKyPuZWnde2g7HJ4gTY51HfjCSqhyKvIJQ8Rl7uEqshF3Ey6xIMOX4A==
content-length: 63
```

(continues on next page)

(continued from previous page)

```
{ "response": [
  {
    "ipAddress": "0.0.0.0",
    "type": "RESOLVE4",
    "id": 1
  }
]}
```

POST

Assigns one or more resolvers to a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

Table 504: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the federation for which resolvers will be retrieved

fedResolverIds An array of integral, unique identifiers for federation resolvers

replace An optional boolean (default: `false`) which, if `true`, will cause any conflicting assignments already in place to be overridden by this request

Note: If `replace` is not given (and/or not `true`), then any conflicts with existing assignments will cause the entire operation to fail.

1227: Request Example

```
POST /api/4.0/federations/1/federation_resolvers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 41
Content-Type: application/json

{
```

(continues on next page)

(continued from previous page)

```
"fedResolverIds": [1],
"replace": true
}
```

Response Structure

fedResolverIds An array of integral, unique identifiers for federation resolvers

replace An optionally-present boolean (default: `false`) which, if `true`, any conflicting assignments already in place were overridden by this request

1228: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:47:47 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:47:47 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: +JDcRByS3H06pMg3Gzkvn0w7/
→v5oRu19e+RxyFIOKJKNH0kZILyQBS+PJpxDeCgwI19+0poW5dyHPPR9SwbNCA==
content-length: 148

{ "alerts": [
  {
    "level": "success",
    "text": "1 resolver(s) were assigned to the test.request.
→federation"
  }
],
"response": {
  "replace": true,
  "fedResolverIds": [
    1
  ]
}}
```

`federations/{{ID}}/users`

GET

Retrieves users assigned to a federation.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 505: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the federation for which users will be retrieved

Table 506: Request Query Parameters

Name	Re-quired	Description
userId	no	Show only the user that has this integral, unique identifier
role	no	Show only the users that have this role
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Response Structure

company The company to which the user belongs

email The user’s email address

fullName The user’s full name

id An integral, unique identifier for the user

role The user’s highest role

username The user’s short “username”

1229: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
→Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:31:34 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:31:34 GMT;
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512: eQQoF2xlbK2I2oTja7zrt/
→FlkLzCgwpU2zb2+rmIjHbHJ3MnmsSczSamIAAyTzs5gDaqcuUX1G35ZB8d7Bj82g==
content-length: 101

{ "response": [
  {
    "fullName": null,
    "email": null,
    "id": 2,
    "role": "admin",
    "company": null,
    "username": "admin"
  }
]}
```

POST

Assigns one or more users to a federation.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

userIds An array of integral, unique identifiers for users which will be assigned to this federation

replace An optional boolean (default: `false`) which, if `true`, will cause any conflicting assignments already in place to be overridden by this request

Note: If `replace` is not given (and/or not `true`), then any conflicts with existing assignments will cause the entire operation to fail.

1230: Request Example

```
POST /api/4.0/federations/1/users HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 34
Content-Type: application/json

{
  "userIds": [2],
  "replace": true
}
```

Response Structure

userIds An array of integral, unique identifiers for users which have been assigned to this federation

replace An optional boolean (default: `false`) which, if `true`, caused any conflicting assignments already in place to be overridden by this request

1231: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
➔Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 00:29:19 GMT
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

```
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 04:29:19 GMT;␣
→path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512:␣
→MvPmgOAs58aSOgVh+iEilflgOexbaexg+qE2IPrQZX0H4iSX4JvEys9adbGE9a9yaLj9uUMxg77N6ZyDhV
content-length: 137

{ "alerts": [
  {
    "level": "success",
    "text": "1 user(s) were assigned to the test.quest. federation"
  }
],
"response": {
  "userIds": [
    2
  ],
  "replace": true
}}
```

`federations/{{ID}}/users/{{userID}}`

DELETE

Removes a user from a federation.

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 507: Request Path Parameters

Name	Description
ID	An integral, unique identifier for the federation from which the user identified by <code>userID</code> will be removed
userID	An integral, unique identifier for the user who will be removed from the federation identified by ID

1232: Request Structure

```
DELETE /api/4.0/federations/1/users/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1233: Response Example

```
HTTP/1.1 200 OK
access-control-allow-credentials: true
access-control-allow-headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
access-control-allow-methods: POST,GET,OPTIONS,PUT,DELETE
access-control-allow-origin: *
cache-control: no-cache, no-store, max-age=0, must-revalidate
content-type: application/json
date: Wed, 05 Dec 2018 01:14:04 GMT
X-Server-Name: traffic_ops_golang/
set-cookie: mojolicious=...; expires=Wed, 05 Dec 2018 05:14:04 GMT;
    ↳path=/; HttpOnly
vary: Accept-Encoding
whole-content-sha512:
    ↳xdF6l7jdd2t8au6lh4pFtDqYxTfehZke2aDBuytL7I74hK9KCT7ssLuYbfvD8ejdqqF3+jiBiFk7neQ8c
content-length: 93

{ "alerts": [
  {
    "level": "success",
    "text": "Removed user [ admin ] from federation [ foo.bar. ]"
  }
]}
```

isos

POST

Generates an ISO from the requested ISO source.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined - ISO image as a streaming download

Request Structure

dhcp A string that specifies whether the generated system image will use DHCP IP address leasing; one of:

yes DHCP will be used, and other network configuration keys need not be present in the request (and are ignored if they are)

no DHCP will not be used, and the desired network configuration **must** be specified manually in the request body

disk An optional string that names the block device (under /dev/) used for the boot media, e.g. “sda”

domainName The domain part of the system image’s Fully Qualified Domain Name (FQDN)

hostName The host name part of the system image’s FQDN

interfaceMtu A number that specifies the Maximum Transmission Unit (MTU) for the system image’s network interface card - the only valid values of which I’m aware are 1500 or 9000, and this should almost always just be 1500

interfaceName An optional string naming the network interface to be used by the generated system image e.g. “bond0”, “eth0”, etc. If the special name “bond0” is used, an LACP binding configuration will be created and included in the system image

See also:

[The Link Aggregation Wikipedia page.](#)

ip6Address An optional string containing the IPv6 address of the generated system image

ip6Gateway An optional string specifying the IPv6 address of the generated system image’s network gateway - this will be ignored if **ipGateway** is specified

ipAddress An optional¹ string containing the IP address of the generated system image

ipGateway An optional¹ string specifying the IP address of the generated system image’s network gateway

ipNetmask An optional¹ string specifying the subnet mask of the generated system image

osversionDir The name of the directory containing the ISO source

See also:

[osversions](#)

¹ This optional key is required if and only if **dhcp** is “no”.

rootPass The password used by the generated system image's root user

1234: Request Example

```
POST /api/4.0/isos HTTP/1.1
Host: some.trafficops.host
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 334
Content-Type: application/json

{
  "osversionDir": "centos72",
  "hostName": "test",
  "domainName": "quest",
  "rootPass": "twelve",
  "dhcp": "no",
  "interfaceMtu": 1500,
  "ipAddress": "1.3.3.7",
  "ipNetmask": "255.255.255.255",
  "ipGateway": "8.0.0.8",
  "ip6Address": "1::3:3:7",
  "ip6Gateway": "8::8",
  "interfaceName": "eth0",
  "disk": "hda"
}
```

Response Structure

ISO image as a streaming download.

1235: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Connection: keep-alive
Content-Disposition: attachment; filename="test-centos72_centos72-
↳netinstall.iso"
Content-Encoding: gzip
Content-Type: application/download
Date: Wed, 05 Feb 2020 21:59:15 GMT
Set-Cookie: mojolicious=...; Path=/; Expires=Wed, 05 Feb 2020 22:59:11
↳GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Transfer-Encoding: chunked
Whole-Content-sha512: sLSVQGrLCQ4hGQhv2reragQHWNi2aKMcz2c/
↪HMAH45tLcZ1LenPy0zWRcRfHUNbV4PEEK0oiTfwE2H1A+WtRIQ==
X-Server-Name: traffic_ops_golang/
```

jobs

GET

Retrieve content invalidation jobs.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 508: Request Query Parameters

Name	Re- quired	Description
assetUrl	no	Return only invalidation jobs that operate on URLs by matching this regular expression
createdBy	no	Return only invalidation jobs that were created by the user with this username
delivery-Service	no	Return only invalidation jobs that operate on the <i>Delivery Service</i> with this <i>xml_id</i>
dsId	no	Return only invalidation jobs pending on the <i>Delivery Service</i> identified by this integral, unique identifier
id	no	Return only the single invalidation job identified by this integral, unique identifier
keyword	no	Return only invalidation jobs that have this “keyword” - only “PURGE” should exist
userId	no	Return only invalidation jobs created by the user identified by this integral, unique identifier

¹ When viewing content invalidation jobs, only those jobs that operate on a *Delivery Service* visible to the requesting user’s *Tenant* will be returned. Likewise, creating a new content invalidation job requires that the target *Delivery Service* is modifiable by the requesting user’s *Tenant*. However, when modifying or deleting an existing content invalidation job, the operation can be completed if and only if the requesting user’s *Tenant* is the same as the job’s *Delivery Service*’s *Tenant* or a descendant thereof, **and** if the requesting user’s *Tenant* is the same as the *Tenant* of the user who initially created the job or a descendant thereof.

1236: Request Example

```
GET /api/4.0/jobs?id=3&dsId=1&userId=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

1237: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: gH41oEi2zrd3y8yo+wfohn4/
→oHU098RpyPnqBzU7H1LUDkMOPKjAZnamcYqfdy7yDCFDUcgqkvbFAvnljxyb8w==
X-Server-Name: traffic_ops_golang/
Date: Tue, 18 Jun 2019 19:47:30 GMT
Content-Length: 186
```

(continues on next page)

(continued from previous page)

```
{ "response": [{
  "assetUrl": "http://origin.infra.ciab.test/.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
  "parameters": "TTL:2h",
  "startTime": "2019-06-18 21:28:31+00"
}]}
```

POST

Creates a new content invalidation job.

Caution: Creating a content invalidation job immediately triggers a CDN-wide revalidation update. In the case that the global *Parameter* `use_reval_pending` has a value of exactly "0", this will instead trigger a CDN-wide “Queue Updates”. This means that content invalidation jobs become active **immediately** at their `startTime` - unlike most other configuration changes they do not wait for a *Snapshot* or a “Queue Updates”. Furthermore, if the global *Parameter* `use_reval_pending` is "0", this will cause all pending configuration changes to propagate to all *cache servers* in the CDN. Take care when using this endpoint.

Auth. Required Yes

Roles Required “operations” or “admin”^{Page 1794, 1}

Response Type Object

Request Structure

deliveryService This should either be the integral, unique identifier of a *Delivery Service*, or a string containing an *xml_id*

startTime This can be a string in the legacy YYYY-MM-DD HH:MM:SS format, or a string in **RFC 3339** format, or a string representing a date in the same non-standard format as the `last_updated` fields common in other API responses, or finally it can be a number indicating the number of milliseconds since the Unix Epoch (January 1, 1970 UTC). This date must be in the future.

regex A regular expression that will be used to match the path part of URIs for content stored on *cache servers* that service traffic for the *Delivery Service* identified by `deliveryService`.

ttl Either the number of hours for which the content invalidation job should remain active, or a “duration” string, which is a sequence of numbers followed by units. The accepted units are:

- **h** gives a duration in hours
- **m** gives a duration in minutes
- **s** gives a duration in seconds
- **ms** gives a duration in milliseconds
- **us** (or **µs**) gives a duration in microseconds
- **ns** gives a duration in nanoseconds

These durations can be combined e.g. `2h45m` specifies a TTL of two hours and forty-five minutes - however note that durations are always rounded up to the nearest hour so that e.g. `121m` becomes three hours. TTLs cannot ever be negative, obviously.

1238: Request Example

```
POST /api/4.0/jobs HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 80
Content-Type: application/json

{
  "deliveryService": "demo1",
  "startTime": 1560893311219,
  "regex": "/.*",
  "ttl": "121m"
}
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

1239: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Location: https://trafficops.infra.ciab.test/api/4.0/jobs?id=3
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳nB2xg2IqO56rLT8dI4+KZgxOsTe5ShctG1U8epRsY9NyyMIpx8TZYt5MrO2QikuYh+NnyoR6V0VICCnGCI
X-Server-Name: traffic_ops_golang/
Date: Tue, 18 Jun 2019 19:37:06 GMT
Content-Length: 238

{
  "alerts": [
    {
      "text": "Invalidation Job creation was successful",
      "level": "success"
    }
  ],
  "response": {
    "assetUrl": "http://origin.infra.ciab.test/.*",
    "createdBy": "admin",
    "deliveryService": "demo1",
    "id": 3,
    "keyword": "PURGE",
    "parameters": "TTL:2h",
    "startTime": "2019-06-18 21:28:31+00"
  }
}
```


PUT

Replaces an existing content invalidation job with a new one provided in the request. This method of editing a content invalidation job does not prevent the requesting user from changing fields that normally only have one value. Use with care.

Caution: Modifying a content invalidation job immediately triggers a CDN-wide revalidation update. In the case that the global *Parameter* `use_reval_pending` has a value of exactly "0", this will instead trigger a CDN-wide “Queue Updates”. This means that content invalidation jobs become active **immediately** at their `startTime` - unlike most other configuration changes they do not wait for a *Snapshot* or a “Queue Updates”. Furthermore, if the global *Parameter* `use_reval_pending` is "0", this will cause all pending configuration changes to propagate to all *cache servers* in the CDN. Take care when using this endpoint.

Auth. Required Yes

Roles Required “operations” or “admin”^{Page 1794, 1}

Response Type Object

Request Structure

Table 509: Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the content invalidation job being modified

assetUrl A regular expression - matching URLs will be operated upon according to keyword

Note: Unlike in the payloads of *POST* requests to this endpoint, this must be a **full** URL regular expression, as it is **not** combined with the *Origin Server Base URL* of the *Delivery Service* identified by `deliveryService`.

createdBy The username of the user who initiated the job²

deliveryService The *xml_id* of the *Delivery Service* on which this job operates[?] - unlike *POST* request payloads, this cannot be an integral, unique identifier

id An integral, unique identifier for this job[?]

keyword A keyword that represents the operation being performed by the job. It can have any (string) value, but the only value with any meaning to Traffic

² This field must exist, but it must *not* be different than the same field of the existing job (i.e. as seen in a *GET* response)

Control is:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing space-separated key/value pairs - delimited by colons (`:`s) representing parameters associated with the job. In practice, any string can be passed as a job's `parameters`, but the only value with meaning is a single key/value pair indicated a TTL in hours in the format `TTL:hoursh`, and any other type of value may cause components of Traffic Control to work improperly or not at all.

startTime This can be a string in the legacy `YYYY-MM-DD HH:MM:SS` format, or a string in [RFC 3339](#) format, or a string representing a date in the same non-standard format as the `last_updated` fields common in other API responses, or finally it can be a number indicating the number of milliseconds since the Unix Epoch (January 1, 1970 UTC). This **must** be in the future, but only by no more than two days.

1240: Request Example

```
PUT /api/4.0/jobs?id=3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 188
Content-Type: application/json

{
  "assetUrl": "http://origin.infra.ciab.test/*.\"",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
  "parameters": "TTL:360h",
  "startTime": "2019-06-20 18:33:40+00"
}
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

1241: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→+P1PTav4ZBoiQcCqQnUqf+J0dCfQgVj8mzzKtUCA69mWYulya9Bjf6BUd8Aro2apmpgPBkCEA5sITJV1t
X-Server-Name: traffic_ops_golang/
Date: Wed, 19 Jun 2019 13:38:59 GMT
Content-Length: 234

{ "alerts": [{
  "text": "Content invalidation job updated",
  "level": "success"
}],
"response": {
  "assetUrl": "http://origin.infra.ciab.test/.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
  "parameters": "TTL:360h",
  "startTime": "2019-06-20 18:33:40+00"
```

(continues on next page)

(continued from previous page)

```
}}
```

DELETE

Deletes a content invalidation job.

Tip: Content invalidation jobs that have passed their TTL are not automatically deleted - for record-keeping purposes - so use this to clean up old jobs that are no longer useful.

Caution: Deleting a content invalidation job immediately triggers a CDN-wide revalidation update. In the case that the global *Parameter* `use_reval_pending` has a value of exactly `"0"`, this will instead trigger a CDN-wide “Queue Updates”. This means that content invalidation jobs become active **immediately** at their `startTime` - unlike most other configuration changes they do not wait for a *Snapshot* or a “Queue Updates”. Furthermore, if the global *Parameter* `use_reval_pending` is `"0"`, this will cause all pending configuration changes to propagate to all *cache servers* in the CDN. Take care when using this endpoint.

Auth. Required Yes

Roles Required “operations” or “admin”^{Page 1794, 1}

Response Type Object

Request Structure

Table 510: Query Parameters

Name	Re-quired	Description
id	yes	The integral, unique identifier of the content invalidation job being modified

1242: Request Example

```
DELETE /api/4.0/jobs?id=3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.20.1
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

assetUrl A regular expression - matching URLs will be operated upon according to keyword

createdBy The username of the user who initiated the job

deliveryService The *xml_id* of the *Delivery Service* on which this job operates

id An integral, unique identifier for this job

keyword A keyword that represents the operation being performed by the job:

PURGE This job will prevent caching of URLs matching the `assetUrl` until it is removed (or its Time to Live expires)

parameters A string containing key/value pairs representing parameters associated with the job - currently only uses Time to Live e.g. "TTL:48h"

startTime The date and time at which the job began, in a non-standard format

1243: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: FqfziXJYYwHb84Fac9+p4NEY3EsklYxe94wg/
→V0mlXk4R6l4SaPSh015CChPt/yT72MsWSETnIuRD9KtoK4I+w==
X-Server-Name: traffic_ops_golang/
Date: Tue, 18 Jun 2019 22:55:15 GMT
Content-Length: 234

{ "alerts": [
  {
    "text": "Content invalidation job was deleted",
    "level": "success"
  }
],
"response": {
  "assetUrl": "http://origin.infra.ciab.test/.*",
  "createdBy": "admin",
  "deliveryService": "demo1",
  "id": 3,
  "keyword": "PURGE",
```

(continues on next page)

(continued from previous page)

```
"parameters": "TTL:36h",
"startTime": "2019-06-20 18:33:40+00"
}}
```

letsencrypt/autorenew

POST

Generates an SSL certificate and private key using Let's Encrypt for a *Delivery Service*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

No parameters available

Response Structure

1244: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "alerts": [
  {
    "text": "This endpoint is deprecated, please use letsencrypt/
    ↳autorenew instead",
    "level": "warning"
  },
  {
    "text": "Beginning async call to renew certificates. This may
    ↳take a few minutes.",
    "level": "success"
  }
]}
```

letsencrypt/dnsrecords

GET

Gets DNS challenge records for Let's Encrypt DNS challenge for a specified FQDN.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

Table 511: Request Query Parameters

Name	Required	Description
fqdn	no	Return only DNS challenge records for the specified FQDN

1245: Request Example

```
GET /api/4.0/letsencrypt/dnsrecord?fqdn=_acme-challenge.demo1.example.
→com. HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

fqdn The FQDN for the TXT record location to complete the DNS challenge

record The record provided by Let's Encrypt to complete the DNS challenge

1246: Response Example

```
HTTP/1.1 200 OK
Content-Type: application/json

{ "response": [
  {
    "fqdn": "_acme-challenge.demo1.example.com.",
    "record": "testRecord"
  }
]}
```

logs

Note: This endpoint's responses will contain a cookie (`last_seen_log`) that is used by `logs/newcount` to determine the time of last access. Be sure your client uses cookies properly if you intend to use `logs/newcount` in concert with this endpoint!

GET

Fetches a list of changes that have been made to the Traffic Control system

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 512: Request Query Parameters

Name	Re-quired	Description
days	no	An integer number of days of change logs to return
limit	no	The number of records to which to limit the response, by default there is no limit applied
off-set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .
user-name	no	A name to which to limit the response too

New in version ATCv6: The username, page, offset query parameters were added to this in endpoint across across all API versions in ATC version 6.0.0.

1247: Request Example

```
GET /api/4.0/logs?days=1&limit=2&username=admin HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```


Response Structure

- id** Integral, unique identifier for the Log entry
- lastUpdated** Date and time at which the change was made, in *Traffic Ops's Custom Date/Time Format*
- level** Log categories for each entry, e.g. 'UICHANGE', 'OPER', 'APICHANGE'
- message** Log detail about what occurred
- ticketNum** Optional field to cross reference with any bug tracking systems
- user** Name of the user who made the change

1248: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 15:11:38 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: last_seen_log="2018-11-15% 15:11:38"; path=/; Max-
    ↳Age=604800
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳40dV+azaZ3b6F30y6YHVbV3H2a3ekZrdoxICupwaxQnj62pwYfb7YCM7Qhe30AItmB77Tbg9INy27ymaz
Content-Length: 357

{ "response": [
  {
    "ticketNum": null,
    "level": "APICHANGE",
    "lastUpdated": "2018-11-14 21:40:06.493975+00",
    "user": "admin",
    "id": 444,
    "message": "User [ test ] unlinked from deliveryservice [ 1 |
    ↳demo1 ]."
  },
  {
    "ticketNum": null,
    "level": "APICHANGE",
    "lastUpdated": "2018-11-14 21:37:30.707571+00",
```

(continues on next page)

(continued from previous page)

```
    "user": "admin",
    "id": 443,
    "message": "1 delivery services were assigned to test"
  }],
  "summary": {
    "count": 2
  }
}
```

Summary Fields

The `summary` object returned by this method of this endpoint uses only the `count` *standard property*.

logs/newcount

GET

Gets the number of new changes made to the Traffic Control system - “new” being defined as the last time the client requested either *logs*

Note: This endpoint’s functionality is implemented by the *logs* endpoint’s response setting cookies for the client to use when requesting `_this_` endpoint. Take care that your client respects cookies!

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available

Response Structure

newLogcount The integer number of new changes

1249: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 15 Nov 2018 15:17:35 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: Ugdqe8GXKSOExphwbDX/
    ↳Gli+2vBpubttbpfYMBJaCP7adox3MzmVRi2RxTDL5kwPewrcL1C088zGITskh0sc9g==
Content-Length: 30

{ "response": {
  "newLogcount": 4
}}
```

origins

GET

Gets all requested *Origins*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 513: Request Query Parameters

Name	Re- quired	Description
cacheGroup	no	Return only <i>Origins</i> within the <i>Cache Group</i> that has this <i>ID</i>
co- ordi- nate	no	Return only <i>Origins</i> located at the geographic coordinates identified by this integral, unique identifier
de- liv- ery- ser- vice	no	Return only <i>Origins</i> that belong to the <i>Delivery Service</i> identified by this integral, unique identifier
id	no	Return only the <i>Origin</i> that has this integral, unique identifier
name	no	Return only <i>Origins</i> by this name
profileId	no	Return only <i>Origins</i> which use the <i>Profile</i> that has this <i>ID</i>
pri- mary	no	If <code>true</code> , return only <i>Origins</i> which are the the primary <i>Origin</i> of the <i>Delivery Service</i> to which they belong - if <code>false</code> return only <i>Origins</i> which are <i>not</i> the primary <i>Origin</i> of the <i>Delivery Service</i> to which they belong
tenant	no	Return only <i>Origins</i> belonging to the tenant identified by this integral, unique identifier
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “ n ” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Note: Several fields of origin definitions which are filterable by Query Parameters are allowed to be `null`. `null` values in these fields will be filtered *out* appropriately by such Query Parameters, but do note that `null` is not a valid value accepted by any of these Query Parameters, and attempting to pass it will result in an error.

1250: Request Example

```
GET /api/4.0/origins?name=demo1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cachegroup** A string that is the *name of the Cache Group* to which the *Origin* belongs
- cachegroupId** An integer that is the *ID of the Cache Group* to which the *Origin* belongs
- coordinate** The name of a coordinate pair that defines the origin's geographic location
- coordinateId** An integral, unique identifier for the coordinate pair that defines the *Origin's* geographic location
- deliveryService** A string that is the *xml_id* of the *Delivery Service* to which the *Origin* belongs
- deliveryServiceId** An integral, unique identifier for the *Delivery Service* to which the *Origin* belongs
- fqdn** The FQDN of the *Origin*
- id** An integral, unique identifier for this *Origin*
- ip6Address** The IPv6 address of the *Origin*
- ipAddress** The IPv4 address of the *Origin*
- isPrimary** A boolean value which, when `true` specifies this *Origin* as the 'primary' *Origin* served by `deliveryService`
- lastUpdated** The date and time at which this *Origin* was last modified
- name** The name of the *Origin*
- port** The TCP port on which the *Origin* listens
- profile** The *Name* of the *Profile* used by this *Origin*
- profileId** The *ID* of the *Profile* used by this *Origin*
- protocol** The protocol used by this origin - will be one of 'http' or 'https'
- tenant** The name of the *Tenant* that owns this *Origin*
- tenantId** An integral, unique identifier for the *Tenant* that owns this *Origin*

1251: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→sm8DpvdvrfdSVLtmXTdfjsZbTlbc+pI40Gy0aj00XIURTPfFXuv/
→4LgHb6A3r92iybRHvFrH6qdB2g97U2sBg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 15:43:41 GMT
Content-Length: 376
```

```
{ "response": [
  {
    "cachegroup": null,
    "cachegroupId": null,
    "coordinate": null,
    "coordinateId": null,
    "deliveryService": "demo1",
    "deliveryServiceId": 1,
    "fqdn": "origin.infra.ciab.test",
    "id": 1,
    "ip6Address": null,
    "ipAddress": null,
    "isPrimary": true,
    "lastUpdated": "2018-12-10 19:11:32+00",
    "name": "demo1",
    "port": null,
    "profile": null,
    "profileId": null,
    "protocol": "http",
    "tenant": "root",
    "tenantId": 1
  }
]}
```

POST

Creates a new origin definition.

Warning: At the time of this writing it is possible to create and/or modify origin definitions assigned to STEERING and CLIENT_STEERING *Delivery Services* - despite that an origin has no meaning in those contexts. In these cases, the API responses may give incorrect output - see [GitHub Issue #3107](#) for details and updates.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cachegroupId An optional, integer which, if present, should be the *Cache Group ID* that identifies a *Cache Group* to which the new *Origin* shall belong

coordinateId An optional, integral, unique identifier of a coordinate pair that shall define the *Origin*’s geographic location

deliveryServiceId The integral, unique identifier of the *Delivery Service* to which the new *Origin* shall belong

fqdn The FQDN of the *Origin*

ip6Address An optional string containing the IPv6 address of the *Origin*

ipAddress An optional string containing the IPv4 address of the *Origin*

isPrimary An optional boolean which, if `true` will set this *Origin* as the ‘primary’ *Origin* served by the *Delivery Service* identified by `deliveryServiceID`

Note: Though not specifying this field in this request will leave it as `null` in the output, Traffic Ops will silently coerce that to its default value: `false`.

name A human-friendly name of the *Origin*

port An optional port number on which the *Origin* listens for incoming TCP connections

profileId An optional *ID* of a *Profile* that shall be used by this *Origin*

protocol The protocol used by the origin - must be one of ‘http’ or ‘https’

tenantId An optional¹, integral, unique identifier for the *Tenant* which shall own the new *Origin*

¹ The `tenantId` field is required if and only if tenancy is enabled within Traffic Ops.

1252: Request Example

```
POST /api/4.0/origins HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 114
Content-Type: application/json

{
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "name": "example",
  "port": 80,
  "protocol": "http",
  "tenantId": 1
}
```

Response Structure

- cachegroup** A string that is the *name of the Cache Group* to which the *Origin* belongs
- cachegroupId** An integer that is the *ID of the Cache Group* to which the *Origin* belongs
- coordinate** The name of a coordinate pair that defines the origin's geographic location
- coordinateId** An integral, unique identifier for the coordinate pair that defines the *Origin's* geographic location
- deliveryService** The 'xml_id' of the *Delivery Service* to which the *Origin* belongs
- deliveryServiceId** An integral, unique identifier for the *Delivery Service* to which the *Origin* belongs
- fqdn** The FQDN of the *Origin*
- id** An integral, unique identifier for this *Origin*
- ip6Address** The IPv6 address of the *Origin*
- ipAddress** The IPv4 address of the *Origin*
- isPrimary** A boolean value which, when `true` specifies this *Origin* as the 'primary' *Origin* served by *deliveryService*
- lastUpdated** The date and time at which this *Origin* was last modified
- name** The name of the *Origin*

- port** The TCP port on which the *Origin* listens
- profile** The *Name* of the *Profile* used by this *Origin*
- profileId** The *ID* the *Profile* used by this *Origin*
- protocol** The protocol used by this origin - will be one of 'http' or 'https'
- tenant** The name of the *Tenant* that owns this *Origin*
- tenantId** An integral, unique identifier for the *Tenant* that owns this *Origin*

1253: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳z4gp0MaqYu+gSRORhKT2e0bVBuVDVx1rdteRaN5kRL9uJ3hNzUCi4dSKIt0rgNgOEDt6x/
    ↳iTyrMvhr/TSHYtmA==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 15:14:27 GMT
Content-Length: 418

{ "alerts": [
  {
    "text": "origin was created.",
    "level": "success"
  }
],
"response": {
  "cachegroup": null,
  "cachegroupId": null,
  "coordinate": null,
  "coordinateId": null,
  "deliveryService": null,
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "id": 2,
  "ip6Address": null,
  "ipAddress": null,
  "isPrimary": null,
  "lastUpdated": "2018-12-11 15:14:27+00",
  "name": "example",
```

(continues on next page)

(continued from previous page)

```
"port": 80,
"profile": null,
"profileId": null,
"protocol": "http",
"tenant": null,
"tenantId": 1
}}
```

PUT

Updates an *Origin* definition.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 514: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Origin</i> definition being edited

cachegroupId An optional, integer which, if present, should be the *Cache Group ID* that identifies a *Cache Group* to which the new *Origin* shall belong

coordinateId An optional, integral, unique identifier of a coordinate pair that shall define the *Origin*’s geographic location

deliveryServiceId The integral, unique identifier of the *Delivery Service* to which the *Origin* shall belong

fqdn The FQDN of the *Origin*

ip6Address An optional string containing the IPv6 address of the *Origin*

ipAddress An optional string containing the IPv4 address of the *Origin*

isPrimary An optional boolean which, if `true` will set this *Origin* as the ‘primary’ origin served by the *Delivery Service* identified by `deliveryServiceID`

name A human-friendly name of the *Origin*

port An optional port number on which the *Origin* listens for incoming TCP connections

profileId An optional *ID* of the *Profile* that shall be used by this *Origin*

protocol The protocol used by the *Origin* - must be one of ‘http’ or ‘https’

tenantId An optional^{Page 1815, 1}, integral, unique identifier for the *Tenant* which shall own the new *Origin*

1254: Request Example

```
PUT /api/4.0/origins?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 135
Content-Type: application/json

{
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "isprimary": true,
  "name": "example",
  "port": 443,
  "protocol": "https",
  "tenantId": 1
}
```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the *Origin* belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the *Origin* belongs

coordinate The name of a coordinate pair that defines the origin's geographic location

coordinateId An integral, unique identifier for the coordinate pair that defines the *Origin's* geographic location

deliveryService The 'xml_id' of the *Delivery Service* to which the *Origin* belongs

deliveryServiceId An integral, unique identifier for the *Delivery Service* to which the *Origin* belongs

fqdn The FQDN of the *Origin*

id An integral, unique identifier for this *Origin*

ip6Address The IPv6 address of the *Origin*

ipAddress The IPv4 address of the *Origin*

isPrimary A boolean value which, when true specifies this *Origin* as the 'primary' *Origin* served by deliveryService

lastUpdated The date and time at which this *Origin* was last modified

name The name of the *Origin*

port The TCP port on which the *Origin* listens

profile The *Name* of the *Profile* used by this *Origin*

profileId The *ID* the *Profile* used by this *Origin*

protocol The protocol used by this origin - will be one of 'http' or 'https'

tenant The name of the *Tenant* that owns this *Origin*

tenantId An integral, unique identifier for the *Tenant* that owns this *Origin*

1255: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Zx7j0a7UAQxRtDenYodvGQSo0oPj4m0yY0AIEUpbdelmYMiNdPYtW82BCmMesFXkmP74nV4HbTUyDHVMu.
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 15:40:53 GMT
Content-Length: 420

{ "alerts": [
  {
    "text": "origin was updated.",
    "level": "success"
  }
],
"response": {
  "cachegroup": null,
  "cachegroupId": null,
  "coordinate": null,
  "coordinateId": null,
  "deliveryService": null,
  "deliveryServiceId": 2,
  "fqdn": "example.com",
  "id": 2,
  "ip6Address": null,
  "ipAddress": null,
  "isPrimary": true,
```

(continues on next page)

(continued from previous page)

```
"lastUpdated": "2018-12-11 15:40:53+00",
"name": "example",
"port": 443,
"profile": null,
"profileId": null,
"protocol": "https",
"tenant": null,
"tenantId": 1
}}
```

DELETE

Deletes an *Origin* definition.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 515: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Origin</i> definition being deleted

1256: Request Example

```
DELETE /api/4.0/origins?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1257: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: fLaY4/
→nh0yR38xq5weBKYg02+aQV6Z1Zro0q9UqUCHLMMrH1NMyhOHx+EphPq7JxkjmGY04WCt6VvDyjGWcgfQ==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 17:04:14 GMT
Content-Length: 61

{ "alerts": [
  {
    "text": "origin was deleted.",
    "level": "success"
  }
]}
```

osversions

See also:

Generate ISO

GET

Gets all available OS versions for ISO generation, as well as the name of the directory where the “kickstarter” files are found.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

This endpoint has no constant keys in its response. Instead, each key in the response object is the name of an OS, and the value is a string that names the directory where the ISO source can be found. These directories sit under `/var/www/files/` on the Traffic Ops host machine by default, or at the location defined by the `kickstart.files.location` *Parameter* of the Traffic Ops server's *Profile*, if it is defined.

1258: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→RxbRY2DZ+1Y0dTzzUETEZ3wtLBiD2BwXMVuaZjhe4a4cwgcZKRBWxZ6Qy5YYujFe1+UBiTG4sML/
→Amn27F4AVg==
X-Server-Name: traffic_ops_golang/
Date: Fri, 30 Nov 2018 19:14:36 GMT
Content-Length: 38

{ "response": {
  "CentOS 7.2": "centos72"
}}
```

Configuration File

The data returned from the endpoint comes directly from a configuration file. By default, the file is located at `/var/www/files/osversions.json`. The **directory** of the file can be changed by creating a specific *Parameter* named `kickstart.files.location` in configuration file `mkisofs`.

The format of the file is a JSON object as described in *Response Structure*.

1259: Example osversions.json file

```
{
  "CentOS 7.2": "centos72"
}
```

The legacy Perl Traffic Ops used a Perl configuration file located by default at `/var/www/files/osversions.cfg`. A Perl script is provided to convert the legacy configuration file to the new JSON format. The script is located within the Traffic Control repository at

traffic_ops/app/bin/osversions-convert.pl.

1260: Example usage of conversion script

```
./osversions-convert.pl < /var/www/files/osversions.cfg > /var/www/  
→files/osversions.json
```

parameterprofile

POST

Create one or more *Parameter/Profile* assignments.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

paramId The *ID* of the *Parameter* to be assigned to the *Profiles* identified within the *profileIds* array

profileIds An array of *Profile IDs* to which the *Parameter* identified by *paramId* shall be assigned

replace An optional boolean (default: false) which, if true, will cause any conflicting *Profile/Parameter* assignments to be overridden.

1261: Request Example

```
POST /api/4.0/parameterprofile HTTP/1.1  
Host: trafficops.infra.ciab.test  
User-Agent: curl/7.47.0  
Accept: */*  
Cookie: mojolicious=...  
Content-Length: 38  
Content-Type: application/json  
  
{  
  "paramId": 4,  
  "profileIds": [18]  
}
```


Response Structure

paramId The *ID* of the *Parameter* which has been assigned to the *Profiles* identified within the `profileIds` array

profileIds An array of *Profile IDs* to which the *Parameter* identified by `paramId` has been assigned

replace An optional boolean (default: false) which, if true, caused any conflicting *Profile/Parameter* assignments to be overridden.

1262: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳N2ahnhEnfZ0UqnjylN6Vu3HaOZk340YuiuyiqkhTbk0pENp+kwBPYu4Z/
    ↳sqBAloCfXSQaWlJzaeXw4uOD5heWw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 15:18:23 GMT
Content-Length: 147

{ "alerts": [
  {
    "text": "2 parameters were assigned to the 18 profile",
    "level": "success"
  }
],
"response": {
  "profileId": 18,
  "paramIds": [
    2,
    3
  ],
  "replace": false
}}
```

parameters

GET

Gets all *Parameters* configured in Traffic Ops

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 516: Request Query Parameters

Name	Re- quired	Description
con- fig- File	no	Filter <i>Parameters</i> by <i>Config File</i>
id	no	Filters <i>Parameters</i> by <i>ID</i>
name	no	Filter <i>Parameters</i> by <i>Name</i>
value	no	Filter <i>Parameters</i> by <i>Value</i>
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sort Order	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
off- set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit .
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page .

1263: Request Example

```
GET /api/4.0/parameters?configFile=records.config&name=location HTTP/1.
→1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- configFile** The *Parameter's Config File*
- id** The *Parameter's ID*
- lastUpdated** The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** *Name* of the *Parameter*
- profiles** An array of *Profile Names* that use this *Parameter*
- secure** A boolean value that describes whether or not the *Parameter* is *Secure*
- value** The *Parameter's Value*

1264: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
→jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
→DbBwhMAOJoeqDIImoDlrLnrVjQG04AooA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 18:23:39 GMT
Content-Length: 212

{ "response": [
  {
    "configFile": "records.config",
    "id": 29,
    "lastUpdated": "2018-12-05 17:51:02+00",
```

(continues on next page)

(continued from previous page)

```

    "name": "location",
    "profiles": [
        "ATS_EDGE_TIER_CACHE",
        "ATS_MID_TIER_CACHE"
    ],
    "secure": false,
    "value": "/etc/trafficserver/"
  }
}]

```

POST

Creates one or more new *Parameters*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

The request body may be in one of two formats, a single *Parameter* object or an array of *Parameter* objects. Each *Parameter* object shall have the following keys:

configFile The *Parameter*’s *Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*’s *Value*

1265: Request Example - Single Object Format

```

POST /api/4.0/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 84
Content-Type: application/json

{
  "name": "test",
  "value": "quest",
  "configFile": "records.config",

```

(continues on next page)

(continued from previous page)

```
"secure": false
}
```

1266: Request Example - Array Format

```
POST /api/4.0/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 180
Content-Type: application/json

[{"name": "test",
  "value": "quest",
  "configFile": "records.config",
  "secure": false
},
{
  "name": "foo",
  "value": "bar",
  "configFile": "records.config",
  "secure": false
}]
```

Response Structure

- configFile** The *Parameter's Config File*
- id** The *Parameter's ID*
- lastUpdated** The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** *Name* of the *Parameter*
- profiles** An array of *Profile Names* that use this *Parameter*
- secure** A boolean value that describes whether or not the *Parameter* is *Secure*
- value** The *Parameter's Value*

1267: Response Example - Single Object Format

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
→Cfh2X9i3G+MQ36eH95gukJq0BOGbQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:18:21 GMT
Content-Length: 212

{ "alerts": [
  {
    "text": "param was created.",
    "level": "success"
  }
],
"response": {
  "configFile": "records.config",
  "id": 124,
  "lastUpdated": "2018-12-05 19:18:21+00",
  "name": "test",
  "profiles": null,
  "secure": false,
  "value": "quest"
}}
```

parameters/{{ID}}

PUT

Replaces a *Parameter*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 517: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Parameter</i> which will be deleted

configFile The *Parameter*'s *Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*'s *Value*

1268: Request Example

```
PUT /api/4.0/parameters/124 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 81
Content-Type: application/json

{
  "name": "foo",
  "value": "bar",
  "configFile": "records.config",
  "secure": false
}
```

Response Structure

configFile The *Parameter*'s *Config File*

id The *Parameter*'s *ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name* of the *Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*'s *Value*

1269: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: DMxS2gKceFVKRtezON/
    ↳vsnrC+zI8onASSHaGv5i3wwvUvyt9KEe72gxQd6ZgVcSq3K8ZpkH6g3UI/WtEfdp5vA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 20:21:07 GMT
Content-Length: 209

{ "alerts": [
  {
    "text": "param was updated.",
    "level": "success"
  }
],
"response": {
  "configFile": "records.config",
  "id": 125,
  "lastUpdated": "2018-12-05 20:21:07+00",
  "name": "foo",
  "profiles": null,
  "secure": false,
  "value": "bar"
}}
```

DELETE

Deletes the specified *Parameter*. If, however, the *Parameter* is associated with one or more *Profiles*, deletion will fail.

Auth. Required Yes

Roles Required “admin” or “operations”

Response TType undefined

Request Structure

Table 518: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Parameter</i> which will be deleted

1270: Request Example

```
DELETE /api/4.0/parameters/124 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1271: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: hJjQq2Seg7sqWt+jKgp6gwRxUtoVU34PFoc9wEaweXdaIBTn/
    ↳BscoUuyw2/n+V8GZPqpeQcihZE50/0oQhdtHw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 19:20:30 GMT
Content-Length: 60

{ "alerts": [
  {
    "text": "param was deleted.",
    "level": "success"
  }
]}
```

phys_locations

GET

Retrieves *Physical Locations*

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 519: Request Query Parameters

Name	Description
id	Filter by integral, unique identifier
re-gion	Filter by integral, unique identifier of containing <i>Region</i>
name	Filter by name
or-derby	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
off-set	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

1272: Request Example

```
GET /api/4.0/phys_locations?name=CDN_in_a_Box HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- address** The physical location's street address
- city** The name of the city in which the physical location lies
- comments** Any and all human-readable comments
- email** The email address of the physical location's poc
- id** An integral, unique identifier for the physical location
- lastUpdated** The date and time at which the physical location was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the physical location
- phone** A phone number where the the physical location's poc might be reached
- poc** The name of a "point of contact" for the physical location
- region** The name of the region within which the physical location lies
- regionId** An integral, unique identifier for the region within which the physical location lies
- shortName** An abbreviation of the name
- state** An abbreviation of the name of the state or province within which this physical location lies
- zip** The zip code of the physical location

1273: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512:↵
↵0g4b3W1AwXytCnBo8TReQQij2v9oHA17MG9KuwMig5V4sFcMM5qP8dgPsFTunFr00DPI20c7BpUbZsvJt
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 22:19:52 GMT
Content-Length: 275

{ "response": [
  {
    "address": "1600 Pennsylvania Avenue NW",
    "city": "Washington",
    "comments": "",
    "email": "",
    "id": 2,
    "lastUpdated": "2018-12-05 17:50:58+00",
    "name": "CDN_in_a_Box",
    "phone": "",
    "poc": "",
    "regionId": 1,
    "region": "Washington, D.C",
    "shortName": "ciab",
    "state": "DC",
    "zip": "20500"
  }
]}
```

POST

Creates a new physical location

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

address The physical location’s street address

city The name of the city in which the physical location lies

comments An optional string for containing any and all human-readable comments

email An optional string containing email address of the physical location’s poc

name An optional name of the physical location

phone An optional string containing the phone number where the the physical location's poc might be reached

poc The name of a “point of contact” for the physical location

region An optional string naming the region that contains this physical location¹

regionId An integral, unique identifier for the region within which the physical location lies¹

shortName An abbreviation of the name

state An abbreviation of the name of the state or province within which this physical location lies

zip The zip code of the physical location

1274: Request Example

```
POST /api/4.0/phys_locations HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 326
Content-Type: application/json

{
  "address": "Buckingham Palace",
  "city": "London",
  "comments": "Buckingham Palace",
  "email": "steve.kingstone@royal.gsx.gov.uk",
  "name": "Great_Britain",
  "phone": "0-843-816-6276",
  "poc": "Her Majesty The Queen Elizabeth Alexandra Mary Windsor II",
  "regionId": 3,
  "shortName": "uk",
  "state": "Westminster",
  "zip": "SW1A 1AA"
}
```

¹ The only “region” key that actually matters in the request body is `regionId`; `region` is not validated and has no effect - particularly not the effect of re-naming the region - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the region. Note that if `region` is not present in the request body it will be `null` in the response, but again further requests will show the true region name.

Response Structure

- address** The physical location's street address
- city** The name of the city in which the physical location lies
- comments** Any and all human-readable comments
- email** The email address of the physical location's poc
- id** An integral, unique identifier for the physical location
- lastUpdated** The date and time at which the physical location was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the physical location
- phone** A phone number where the the physical location's poc might be reached
- poc** The name of a "point of contact" for the physical location
- region** The name of the region within which the physical location lies
- regionId** An integral, unique identifier for the region within which the physical location lies
- shortName** An abbreviation of the name
- state** An abbreviation of the name of the state or province within which this physical location lies
- zip** The zip code of the physical location

1275: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: GZ/
    ↳BC+AgGpOQNfd9oiZy19jtsD8MP0deyi7PVdz+9YSiLYP44gmn5K+Xi1yS0l59yjHf70+C1loVQPSlIeP9
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 00:14:47 GMT
Content-Length: 443

{ "alerts": [
  {
    "text": "physLocation was created.",
    "level": "success"
```

(continues on next page)

(continued from previous page)

```

    }
  ],
  "response": {
    "address": "Buckingham Palace",
    "city": "London",
    "comments": "Buckingham Palace",
    "email": "steve.kingstone@royal.gsx.gov.uk",
    "id": 3,
    "lastUpdated": "2018-12-06 00:14:47+00",
    "name": "Great_Britain",
    "phone": "0-843-816-6276",
    "poc": "Her Majesty The Queen Elizabeth Alexandra Mary Windsor II",
    "regionId": 3,
    "region": null,
    "shortName": "uk",
    "state": "Westminster",
    "zip": "SW1A 1AA"
  }
}
```

`phys_locations/{{ID}}`

PUT

Updates a *Physical Location*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Array

Request Structure

Table 520: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Physical Location</i> being modified

address The physical location’s street address

city The name of the city in which the physical location lies

comments An optional string for containing any and all human-readable comments

email An optional string containing email address of the physical location’s poc

name An optional name of the physical location

phone An optional string containing the phone number where the the physical location's poc might be reached

poc The name of a “point of contact” for the physical location

region An optional string naming the region that contains this physical location¹

regionId An integral, unique identifier for the region within which the physical location lies¹

shortName An abbreviation of the name

state An abbreviation of the name of the state or province within which this physical location lies

zip The zip code of the physical location

1276: Request Structure

```
PUT /api/4.0/phys_locations/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 268
Content-Type: application/json

{
  "address": "1600 Pennsylvania Avenue NW",
  "city": "Washington",
  "comments": "The White House",
  "email": "the@white.house",
  "name": "CDN_in_a_Box",
  "phone": "1-202-456-1414",
  "poc": "Donald J. Trump",
  "regionId": 2,
  "shortName": "ciab",
  "state": "DC",
  "zip": "20500"
}
```

¹ The only “region” key that actually matters in the request body is `regionId`; `region` is not validated and has no effect - particularly not the effect of re-naming the region - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the region. Note that if `region` is not present in the request body it will be `null` in the response, but again further requests will show the true region name.

Response Structure

- address** The physical location's street address
- city** The name of the city in which the physical location lies
- comments** Any and all human-readable comments
- email** The email address of the physical location's poc
- id** An integral, unique identifier for the physical location
- lastUpdated** The date and time at which the physical location was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the physical location
- phone** A phone number where the the physical location's poc might be reached
- poc** The name of a "point of contact" for the physical location
- region** The name of the region within which the physical location lies
- regionId** An integral, unique identifier for the region within which the physical location lies
- shortName** An abbreviation of the name
- state** An abbreviation of the name of the state or province within which this physical location lies
- zip** The zip code of the physical location

1277: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→qnMe60qxjSU8H1njlh00HWNr20YnVlOCufqCTdMBcdC1322jk2ICFQsQQ3Xu0OR0WSb7h70HCfXqDC1/
→jA1xjA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 23:39:17 GMT
Content-Length: 385

{ "alerts": [
  {
    "text": "physLocation was updated.",
```

(continues on next page)

(continued from previous page)

```

        "level": "success"
    }
],
"response": {
    "address": "1600 Pennsylvania Avenue NW",
    "city": "Washington",
    "comments": "The White House",
    "email": "the@white.house",
    "id": 2,
    "lastUpdated": "2018-12-05 23:39:17+00",
    "name": "CDN_in_a_Box",
    "phone": "1-202-456-1414",
    "poc": "Donald J. Trump",
    "regionId": 2,
    "region": null,
    "shortName": "ciab",
    "state": "DC",
    "zip": "20500"
}}

```

DELETE

Deletes a *Physical Location*

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 521: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the <i>Physical Location</i> being deleted

1278: Request Example

```

DELETE /api/4.0/phys_locations/3 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...

```

Response Structure

1279: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: KeW/tEmICwpCGC8F0YMTqHdeR9J6W6Z3w/
    ↳U+H0SbeCGyaEheCIhIsWlngT3dyfH1tiu8UyzaPB6QrJyXdybBkw==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 00:28:48 GMT
Content-Length: 67

{ "alerts": [
  {
    "text": "physLocation was deleted.",
    "level": "success"
  }
]}
```

ping

Checks whether Traffic Ops is online.

GET

Auth. Required No

Response Type undefined

Request Structure

No parameters available.

1280: Request Example

```
GET /api/4.0/ping HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

ping Returns an object containing only the "ping" property, which always has the value "pong".

1281: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Whole-Content-Sha512: 0HqcLcYHCB4AFYGFzcAsP2h+PCm1Yxk/
    ↳TqMajcy3fWCzY730Tv32k5trUaJLeSBbRx2FUi7z/sTAuzikdg0E4g==
X-Server-Name: traffic_ops_golang/
Date: Sun, 23 Feb 2020 20:52:01 GMT
Content-Length: 40
Content-Type: application/x-gzip

{
  "ping": "pong"
}
```

plugins

See also:

Go Plugins

GET

Retrieves the list of configured enabled Traffic Ops plugins.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

1282: Request Example

```
GET /api/4.0/plugins HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

description A short description of the plugin.

name The name of the plugin.

version A (hopefully) semantic version number describing the version of the plugin.

1283: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Tue, 11 Dec 2018 20:51:48 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: n73jg9XR4V5Cwqq56Rf3wuIi99k3mM5u2NAjcZ/
→gQBu8jvAFymDlnZqKeJ+wTl1lvjIsHpXCOVXV7+5UGakLgA==
Transfer-Encoding: chunked

{ "response": [
  {
    "name": "helloworld",
    "version": "1.0.0",
    "description": "configuration plugin to run at startup"
  }
]
}
```

profileparameter

See also:

profileparameters.

POST

Create one or more *Profile/Parameter* assignments.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

profileId The *ID* of the *Profile* to which the *Parameters* identified within the *parameterIds* array will be assigned

paramIds An array of *Parameter IDs* which shall be assigned to the *Profile* identified by *profileId*

replace An optional boolean (default: false) which, if true, will cause any conflicting *Profile/Parameter* assignments to be overridden.

1284: Request Example

```
POST /api/4.0/profileparameter HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 38
Content-Type: application/json

{
  "profileId": 18,
  "paramIds": [2, 3]
}
```

Response Structure

- profileId** The *ID* of the *Profile* to which the *Parameters* identified within the *parameterIds* array are assigned
- paramIds** An array of *Parameter IDs* which have been assigned to the *Profile* identified by *profileId*
- replace** An optional boolean (default: false) which, if true, indicates that any conflicting *Profile/Parameter* assignments have been overridden.

1285: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳N2ahnhEnfZ0UqnjylN6Vu3HaOZk340YuiuyiqkhTbk0pENp+kwBPYu4Z/
  ↳sqBAloCfXSQaWlJzaeXw4uOD5heWw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 15:18:23 GMT
Content-Length: 147

{ "alerts": [
  {
    "text": "2 parameters were assigned to the 18 profile",
```

(continues on next page)

(continued from previous page)

```

        "level": "success"
    }
],
"response": {
    "profileId": 18,
    "paramIds": [
        2,
        3
    ],
    "replace": false
}}

```

profileparameters

GET

Retrieves all *Parameter/Profile* assignments.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 522: Request Query Parameters

Name	Re- quired	Description
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

Response Structure

lastUpdated The date and time at which this *Profile/Parameter* association was last modified, in *Traffic Ops's Custom Date/Time Format*

parameter The *ID* of a *Parameter* assigned to profile

profile The *Name* of the *Profile* to which the *Parameter* identified by parameter is assigned

1286: Response Structure

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳+bnMkRgdx4bJoGGlr3mZl539obj3aQAP8e65FAXgywdRAUfXZCFM6VNDn7wScXBmvF2SFXo9F+MhuSwrtI
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 15:09:13 GMT
Transfer-Encoding: chunked

{ "response": [
  {
    "lastUpdated": "2018-12-05 17:50:49+00",
    "profile": "GLOBAL",
    "parameter": 4
  },
  {
    "lastUpdated": "2018-12-05 17:50:49+00",
    "profile": "GLOBAL",
    "parameter": 5
  }
]}
```

Note: The response example for this endpoint has been truncated to only the first two elements of the resulting array, as the output was hundreds of lines long.

POST

Associate a *Parameter* to a *Profile*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

This endpoint accepts two formats for the request payload:

Single Object Format For assigning a single *Parameter* to a single *Profile*

Array Format For making multiple assignments of *Parameters* to *Profiles* simultaneously

Single Object Format

parameterId The *ID* of a *Parameter* to assign to some *Profile*

profileId The *ID* of the *Profile* to which the *Parameter* identified by parameterId will be assigned

1287: Request Example - Single Object Format

```
POST /api/4.0/profileparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 36
Content-Type: application/json

{
  "profileId": 18,
  "parameterId": 1
}
```

Array Format

parameterId The *ID* of a *Parameter* to assign to some *Profile*

profileId The *ID* of the *Profile* to which the *Parameter* identified by parameterId will be assigned

1288: Request Example - Array Format

```
POST /api/4.0/profileparameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 88
Content-Type: application/json

[
  {
    "profileId": 18,
    "parameterId": 2
  },
  {
    "profileId": 18,
    "parameterId": 3
  }
]
```

Response Structure

lastUpdated The date and time at which the *Profile/Parameter* assignment was last modified, in *Traffic Ops's Custom Date/Time Format*

parameter *Name* of the *Parameter* which is assigned to profile

parameterId The *ID* of the assigned *Parameter*

profile *Name* of the *Profile* to which the *Parameter* is assigned

profileId The *ID* of the *Profile* to which the *Parameter* identified by parameterId is assigned

1289: Response Example - Single Object Format

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳eDmIwlzX44fZdxLRPHMNa8aoGAK5fQv9Y70A2eeQHfEkliU4evwcsQ4WeHcH0l3/
    ↳wPTGlpyC0gwLo8LQqpUxWQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 13:50:11 GMT
Content-Length: 166

{ "alerts": [
  {
    "text": "profileParameter was created.",
    "level": "success"
  }
],
"response": {
  "lastUpdated": null,
  "profile": null,
  "profileId": 18,
  "parameter": null,
  "parameterId": 1
}}
```

profileparameters/{{profileID}}/{{parameterID}}

DELETE

Deletes a *Profile/Parameter* association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 523: Request Path Parameters

Name	Description
profileID	The <i>ID</i> of the <i>Profile</i> from which a <i>Parameter</i> shall be removed
parameterID	The <i>ID</i> of the <i>Parameter</i> which shall be removed from the <i>Profile</i> identified by profileID

1290: Request Example

```
DELETE /api/4.0/profileparameters/18/129 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1291: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳JQuBqHyT9MnNw09NSIDVQhkRtXdeAJc95W1pF2dwQeoBFmf0Y8knXm3/0/
    ↳rbJDEoUC7DhUQN1aoYIsqqmz4qQQ==
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

```
Date: Mon, 10 Dec 2018 15:00:15 GMT
Content-Length: 71

{ "alerts": [
  {
    "text": "profileParameter was deleted.",
    "level": "success"
  }
]}
```

profiles

GET

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 524: Request Query Parameters

Name	Re- quired	Description
cdn	no	Used to filter <i>Profiles</i> by the integral, unique identifier of the CDN to which they belong
id	no	Filters <i>Profiles</i> by <i>ID</i>
name	no	Filters <i>Profiles</i> by <i>Name</i>
param	no	Used to filter <i>Profiles</i> by the <i>ID</i> of a <i>Parameter</i> associated with them

1292: Request Example

```
GET /api/4.0/profiles?name=ATS_EDGE_TIER_CACHE HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- cdn** The integral, unique identifier of the *CDN* to which this *Profile* belongs
- cdnName** The name of the *CDN* to which this *Profile* belongs
- description** The *Profile*'s *Description*
- id** The *Profile*'s *ID*
- lastUpdated** The date and time at which this *Profile* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The *Profile*'s *Name*
- routingDisabled** The *Profile*'s *Routing Disabled* setting
- type** The *Profile*'s *Type*

1293: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: QEpKM/
    ↳DwHBRvue9K7XKrpwKFKhW6yCMQ2vSQgxE7dWFGJaqC4KOU092bsJU/
    ↳5fjI9qlB+1uMT2kz6mFb1Wzp/w==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 20:40:31 GMT
Content-Length: 220

{ "response": [
  {
    "id": 9,
    "lastUpdated": "2018-12-05 17:51:00+00",
```

(continues on next page)

(continued from previous page)

```

    "name": "ATS_EDGE_TIER_CACHE",
    "description": "Edge Cache - Apache Traffic Server",
    "cdnName": "CDN-in-a-Box",
    "cdn": 2,
    "routingDisabled": false,
    "type": "ATS_PROFILE"
  }
}]

```

POST

Creates a new *Profile*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cdn The integral, unique identifier of the *CDN* to which this *Profile* shall belong

description The *Profile*’s *Description*

name The *Profile*’s *Name*

routingDisabled The *Profile*’s *Routing Disabled* setting

type The *Profile*’s *Type*

1294: Request Example

```

POST /api/4.0/profiles HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 125
Content-Type: application/json

{
  "name": "test",
  "description": "A test profile for API examples",
  "cdn": 2,
  "type": "UNK_PROFILE",
  "routingDisabled": true
}

```


Response Structure

- cdn** The integral, unique identifier of the *CDN* to which this *Profile* belongs
- cdnName** The name of the *CDN* to which this *Profile* belongs
- description** The *Profile's Description*
- id** The *Profile's ID*
- lastUpdated** The date and time at which this *Profile* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The *Profile's Name*
- routingDisabled** The *Profile's Routing Disabled* setting
- type** The *Profile's Type*

1295: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→UGV3PCnYBY0J3siICR0f9VVRNdUK1+9zsDDP6T9yt6t+AoHckHe6bvz0li9to/
→fGhC2zz5l9Nc1ro4taJUDD8g==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 21:24:49 GMT
Content-Length: 251

{ "alerts": [
  {
    "text": "profile was created.",
    "level": "success"
  }
],
"response": {
  "id": 16,
  "lastUpdated": "2018-12-07 21:24:49+00",
  "name": "test",
  "description": "A test profile for API examples",
  "cdnName": null,
  "cdn": 2,
  "routingDisabled": true,
```

(continues on next page)

(continued from previous page)

```
"type": "UNK_PROFILE"
}}
```

profiles/{{ID}}

PUT

Replaces the specified *Profile* with the one in the request payload

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 525: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> being modified

cdn The integral, unique identifier of the *CDN* to which this *Profile* will belong

description The *Profile*’s new *Description*

name The *Profile*’s new *Name*

routingDisabled The *Profile*’s new *Routing Disabled* setting

type The *Profile*’s new *Type*

Warning: Changing this will likely break something, be **VERY** careful when modifying this value

1296: Request Example

```
PUT /api/4.0/profiles/16 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 125
Content-Type: application/json

{
```

(continues on next page)

(continued from previous page)

```
"name": "test",
"description": "A test profile for API examples",
"cdn": 2,
"type": "UNK_PROFILE",
"routingDisabled": true
}
```

Response Structure

- cdn** The integral, unique identifier of the *CDN* to which this *Profile* belongs
- cdnName** The name of the *CDN* to which this *Profile* belongs
- description** The *Profile*'s *Description*
- id** The *Profile*'s *ID*
- lastUpdated** The date and time at which this *Profile* was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The *Profile*'s *Name*
- routingDisabled** The *Profile*'s *Routing Disabled* setting
- type** The *Profile*'s *Type*

1297: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Pnf+G9G3/
→+edt4b8PVsyGZHSNzaFEgphaGSminjRlRmMpWtuLAA20WZDUo3nX0Q081c2GCuFuEh9uMF2Vjeppg==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 21:45:06 GMT
Content-Length: 251

{ "alerts": [
  {
    "text": "profile was updated.",
    "level": "success"
  }
],
```

(continues on next page)

(continued from previous page)

```
"response": {
  "id": 16,
  "lastUpdated": "2018-12-07 21:45:06+00",
  "name": "test",
  "description": "A test profile for API examples",
  "cdnName": null,
  "cdn": 2,
  "routingDisabled": true,
  "type": "UNK_PROFILE"
}}
```

DELETE

Allows user to delete a *Profile*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 526: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> being deleted

1298: Request Example

```
DELETE /api/4.0/profiles/16 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1299: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: HNmJkZaNW9yil08/
→3TnqZ5FllH6Rp+jgp3KI46FZdojLYcu+8jEhDL1lokoirdrHyU4R1c3hjCI0urN7PVvWDA==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Dec 2018 21:55:33 GMT
Content-Length: 62

{ "alerts": [
  {
    "text": "profile was deleted.",
    "level": "success"
  }
]}
```

`profiles/{{ID}}/export`

GET

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 527: Request Path Parameters

Parameter	Description
id	The <i>ID</i> of the <i>Profile</i> to be exported

1300: Request Example

```
GET /api/4.0/profiles/3/export HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- profile** The exported *Profile*
 - cdn** The name of the *CDN* to which this *Profile* belongs
 - description** The *Profile's Description*
 - name** The *Profile's Name*
 - type** The *Profile's Type*
- parameters** An array of *Parameters* in use by this *Profile*
 - config_file** The *Parameter's Config File*
 - name** *Name* of the *Parameter*
 - value** The *Parameter's Value*

1301: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Disposition: attachment; filename="GLOBAL.json"
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mzP7DVxFAGhICxqagwDyBDRea7oBZPMAx7NCDeOBVCRqlcCFFe7XL3JP58b80aaVOW/
    ↳2ZGfg/jpYF70cdDfzQA==
X-Server-Name: traffic_ops_golang/
Date: Fri, 13 Sep 2019 20:14:42 GMT
Transfer-Encoding: gzip

{ "profile": {
  "name": "GLOBAL",
  "description": "Global Traffic Ops profile",
  "cdn": "ALL",
  "type": "UNK_PROFILE"
},
  "parameters": [
    {
      "config_file": "global",
      "name": "tm.instance_name",
      "value": "Traffic Ops CDN"
    }
  ]
}

```

(continues on next page)

(continued from previous page)

```

    },
    {
      "config_file": "global",
      "name": "tm.toolname",
      "value": "Traffic Ops"
    }
  ]}

```

profiles/{ID}/parameters

GET

Retrieves all *Parameters* assigned to the *Profile*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 528: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> for which <i>Parameters</i> will be listed

1302: Request Example

```

GET /api/4.0/parameters/profile/GLOBAL HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...

```

Response Structure

configFile The *Parameter*'s *Config File*

id The *Parameter*'s *ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops*'s *Custom Date/Time Format*

name *Name* of the *Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

1303: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: NudgZXUNyKNpmSFf856KEjyy+Pin/
→bFhG9NoRBDaxYbRKt2T5fF5Ze7sUNZfFI5n/ZZsgbx6Tsgtfd7oM6j+eg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 21:08:56 GMT
Content-Length: 542

{ "response": [
  {
    "configFile": "global",
    "id": 4,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.instance_name",
    "secure": false,
    "value": "Traffic Ops CDN"
  },
  {
    "configFile": "global",
    "id": 5,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.toolname",
    "secure": false,
    "value": "Traffic Ops"
  },
  {
    "configFile": "regex_revalidate.config",
    "id": 7,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "maxRevalDurationDays",
    "secure": false,
    "value": "90"
  }
]
}]}
```


POST

Associates *Parameters* to a *Profile*. If the *Parameter* does not exist, creates it and associates it to the *Profile*. If the *Parameter* already exists, associates it to the *Profile*. If the *Parameter* is already associated with the *Profile*, keep the association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 529: Request Path Parameters

Name	Description
ID	The <i>ID</i> of the <i>Profile</i> to which <i>Parameters</i> will be assigned

This endpoint accepts two formats for the request payload:

Single Object Format For assigning a single *Parameter* to a single *Profile*

Parameter Array Format For making multiple assignments of *Parameters* to *Profiles* simultaneously

Warning: Most API endpoints dealing with *Parameters* treat *Secure* as a boolean value, whereas this endpoint takes the legacy approach of treating it as an integer. Be careful when passing data back and forth, as boolean values will **not** be accepted by this endpoint!

Single Parameter Format

configFile The *Parameter*’s *Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*’s *Value*

1304: Response Example - Single Parameter Format

```
POST /api/4.0/profiles/18/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 99
```

(continues on next page)

(continued from previous page)

```
Content-Type: application/json

{
  "name": "test",
  "configFile": "quest",
  "value": "A test parameter for API examples",
  "secure": 0
}
```

Parameter Array Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

1305: Request Example - Parameter Array Format

```
POST /api/4.0/profiles/18/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 212
Content-Type: application/json

[
  {
    "name": "test",
    "configFile": "quest",
    "value": "A test parameter for API examples",
    "secure": 0
  },
  {
    "name": "foo",
    "configFile": "bar",
    "value": "Another test parameter for API examples",
    "secure": 0
  }
]
```

Response Structure

parameters An array of objects representing the *Parameters* which have been assigned

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

profileId The *ID* of the *Profile* to which the *Parameter(s)* have been assigned

profileName *Name* of the *Profile* to which the *Parameter(s)* have been assigned

1306: Response Example - Single Parameter Format

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: R2QUyCaNvKvVv/PNVNmEd/ma5h/iP1fMJlqhv+x2jE/
    ↳zNpHJ1KVXt6s3btB8nnHv6IDF/gt5kIzQ0mbW5U8bpg==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 14:45:28 GMT
Content-Length: 253

{ "alerts": [
  {
    "text": "Assign parameters successfully to profile test",
    "level": "success"
  }
],
"response": {
  "parameters": [
    {
      "configFile": "quest",
      "name": "test",
      "secure": 0,
      "value": "A test parameter for API examples",
      "id": 126
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```
],  
  "profileId": 18,  
  "profileName": "test"  
}}
```

Note: The format of the request does not affect the format of the response. `parameters` will be an array either way.

`profiles/import`

POST

Imports a *Profile* that was exported via *profiles/{{ID}}/export*

Note: On import of the *Profile Parameters* if a *Parameter* already exists with the same *Name*, *Config File* and *Value* it will link that to the *Profile* instead of creating it.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

profile The exported *Profile*

cdn The name of the *CDN* to which this *Profile* belongs

description The *Profile*’s *Description*

name The *Profile*’s *Name*

type The *Profile*’s *Type*

parameters An array of *Parameters* in use by this *Profile*

config_file The *Parameter*’s *Config File*

name *Name* of the *Parameter*

value The *Parameter*’s *Value*

1307: Request Example

```
POST /api/4.0/profiles/import HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
Content-Type: application/json

{ "profile": {
  "name": "GLOBAL",
  "description": "Global Traffic Ops profile",
  "cdn": "ALL",
  "type": "UNK_PROFILE"
},
"parameters": [
  {
    "config_file": "global",
    "name": "tm.instance_name",
    "value": "Traffic Ops CDN"
  },
  {
    "config_file": "global",
    "name": "tm.toolname",
    "value": "Traffic Ops"
  }
]}

```

Response Structure

cdn The name of the *CDN* to which this *Profile* belongs

description The *Profile's Description*

name The *Profile's Name*

type The *Profile's Type*

id The *Profile's ID*

1308: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json

```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54 GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  mzP7DVxFAGhICxqagwDyBDRea7oBZPMAx7NCDeOBVCRqlcCFFe7XL3JP58b80aaVOW/
  2ZGfg/jpYF70cdDfzQA==
X-Server-Name: traffic_ops_golang/
Date: Fri, 13 Sep 2019 20:14:42 GMT
Transfer-Encoding: gzip

{ "alerts": [
  {
    "level": "success",
    "text": "Profile imported [ Global ] with 2 new and 0 existing parameters"
  }
],
"response": {
  "cdn": "ALL",
  "name": "Global",
  "id": 18,
  "type": "UNK_PROFILE",
  "description": "Global Traffic Ops profile"
}}
```

`profiles/name/{name}/copy/{copy}`

POST

Copy *Profile* to a new *Profile*. The new *Profile*'s *Name* must not already exist.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 530: Request Path Parameters

Name	Description
name	The <i>Name</i> of the new <i>Profile</i>
copy	The <i>Name</i> of <i>Profile</i> from which the copy will be made

1309: Request Example

```
POST /api/4.0/profiles/name/GLOBAL_copy/copy/GLOBAL HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.62.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

description The new *Profile*'s *Description*

id The *ID* of the new *Profile*

idCopyFrom The *ID* of the *Profile* from which the copy was made

name The *Name* of the new *Profile*

profileCopyFrom The *Name* of the *Profile* from which the copy was made

1310: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Fri, 07 Dec 2018 22:03:54 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→r6V9viEZui1WCns0AUGEx1MtxjjXiU8SZV0tSQjeq7ZJDL15s8fMmjJdR/
→HRWduHn7Ax6GzYhoKwnIjMyc7ZWg==
Content-Length: 252

{ "alerts": [
  {
    "level": "success",
    "text": "Created new profile [ GLOBAL_copy ] from existing
→profile [ GLOBAL ]"
  }
],
"response": {
```

(continues on next page)

(continued from previous page)

```
"idCopyFrom": 1,
"name": "GLOBAL_copy",
"profileCopyFrom": "GLOBAL",
"id": 17,
"description": "Global Traffic Ops profile, DO NOT DELETE"
}}
```

`profiles/name/{name}/parameters`

GET

Retrieves all *Parameters* associated with a given *Profile*

Auth. Required Yes

Roles Required None

Response Type None

Request Structure

Table 531: Request Path Parameters

Name	Description
name	The <i>Name</i> of the <i>Profile</i> for which <i>Parameters</i> will be listed

1311: Request Example

```
GET /api/4.0/profiles/name/GLOBAL/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

configFile The *Parameter's Config File*

id The *Parameter's ID*

lastUpdated The date and time at which this *Parameter* was last updated, in *Traffic Ops's Custom Date/Time Format*

name *Name* of the *Parameter*

profiles An array of *Profile Names* that use this *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*'s *Value*

1312: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: NudgZXUNyKNpmSFf856KEjyy+Pin/
    ↳bFhG9NoRBDaxYbRKt2T5fF5Ze7sUNZfFI5n/ZZsgbx6Tsgtfd7oM6j+eg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 05 Dec 2018 21:52:08 GMT
Content-Length: 542

{ "response": [
  {
    "configFile": "global",
    "id": 4,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.instance_name",
    "secure": false,
    "value": "Traffic Ops CDN"
  },
  {
    "configFile": "global",
    "id": 5,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "tm.toolname",
    "secure": false,
    "value": "Traffic Ops"
  },
  {
    "configFile": "regex_revalidate.config",
    "id": 7,
    "lastUpdated": "2018-12-05 17:50:49+00",
    "name": "maxRevalDurationDays",
    "secure": false,
    "value": "90"
  }
]}
```

POST

Associates *Parameters* to a *Profile*. If the *Parameter* does not exist, creates it and associates it to the *Profile*. If the *Parameter* already exists, associates it to the *Profile*. If the *Parameter* is already associated with the *Profile*, keep the association.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 532: Request Path Parameters

Name	Description
name	The <i>Name</i> of the <i>Profile</i> to which <i>Parameters</i> will be assigned

This endpoint accepts two formats for the request payload:

Single Parameter Format Specify a single parameter to assign to the specified profile

Parameter Array Format Specify multiple parameters to assign to the specified profile

Warning: Most API endpoints dealing with parameters treat `secure` as a boolean value, whereas this endpoint takes the legacy approach of treating it as an integer. Be careful when passing data back and forth, as boolean values will **not** be accepted by this endpoint!

Single Parameter Format

configFile The *Parameter*’s *Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter*’s *Value*

1313: Request Example - Single Parameter Format

```
POST /api/4.0/profiles/name/test/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 99
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
{
  "name": "test",
  "configFile": "quest",
  "value": "A test parameter for API examples",
  "secure": 0
}
```

Parameter Array Format

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

1314: Request Example - Parameter Array Format

```
POST /api/4.0/profiles/name/test/parameters HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 212
Content-Type: application/json

[{"name": "test",
  "configFile": "quest",
  "value": "A test parameter for API examples",
  "secure": 0},
 {"name": "foo",
  "configFile": "bar",
  "value": "Another test parameter for API examples",
  "secure": 0}]
```

Response Structure

parameters An array of objects representing the *Parameters* which have been assigned

configFile The *Parameter's Config File*

name *Name* of the *Parameter*

secure A boolean value that describes whether or not the *Parameter* is *Secure*

value The *Parameter's Value*

profileId The *ID* of the *Profile* to which the *Parameter(s)* have been assigned

profileName *Name* of the *Profile* to which the *Parameter(s)* have been assigned

1315: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: HQWqOkOYHjvcxheWPrHOb0oZnUC+qLG1L040jtsLLnZYVUIu/
→qgJrzvziPnKq3FEHUWaZrnDCZM/iZD8AXOKBw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 14:20:22 GMT
Content-Length: 357

{ "alerts": [
  {
    "text": "Assign parameters successfully to profile test",
    "level": "success"
  }
],
"response": {
  "parameters": [
    {
      "configFile": "quest",
      "name": "test",
      "secure": 0,
      "value": "A test parameter for API examples",
      "id": 126
    },

```

(continues on next page)

(continued from previous page)

```
{
  "configFile": "bar",
  "name": "foo",
  "secure": 0,
  "value": "Another test parameter for API examples",
  "id": 129
},
{
  "profileId": 18,
  "profileName": "test"
}
}]
}}
```

Note: The format of the request does not affect the format of the response. `parameters` will be an array either way.

regions

GET

Retrieves information about *Regions*

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

Table 533: Request Query Parameters

Name	Required	Description
division	no	Filter <i>Regions</i> by the integral, unique identifier of the <i>Division</i> which contains them
id	no	Filter <i>Regions</i> by integral, unique identifier
name	no	Filter <i>Regions</i> by name
orderBy	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>n</i> th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1316: Request Example

```
GET /api/4.0/regions?division=1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

divisionName The name of the division which contains this region

divisionId The integral, unique identifier of the division which contains this region

id An integral, unique identifier for this region

lastUpdated The date and time at which this region was last updated, in *Traffic Ops's Custom Date/Time Format*

name The region name

1317: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→nSYbR+fRXaxhYl7dWgf0Udo2AsiXEnwvED1CPbk7ZNWK03I3TOhtmCQx9ABnJJ6xKYnl6EKMeopVTK0n
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 01:58:38 GMT
Content-Length: 117

{ "response": [
  {
    "divisionName": "Quebec",
    "division": 1,
    "id": 2,
    "lastUpdated": "2018-12-05 17:50:58+00",
    "name": "Montreal"
  }
]}
```

POST

Creates a new region

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

division The integral, unique identifier of the division which shall contain the new region¹

divisionName The name of the division which shall contain the new region¹

name The name of the region

¹ The only “division” key that actually matters in the request body is `division`; `divisionName` is not validated and has no effect - particularly not the effect of re-naming the division - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the division. Note that if `divisionName` is not present in the request body it will be `null` in the response, but again further requests will show the true division name (provided it has been assigned to a division).

1318: Request Example

```
POST /api/4.0/regions HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 65
Content-Type: application/json

{
  "name": "Manchester",
  "division": "4",
  "divisionName": "England"
}
```

Response Structure

- divisionName** The name of the division which contains this region
- divisionId** The integral, unique identifier of the division which contains this region
- id** An integral, unique identifier for this region
- lastUpdated** The date and time at which this region was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The region name

1319: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳ezxk+iP7o7KE7zpWmGc0j8nz5k+1wAzY0HiNiA2xswTQrt+N+6CgQqUV2r9G1HAsPNr0HF2PhYs/
  ↳Xr7DrYOW0A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 02:14:45 GMT
Content-Length: 178

{ "alerts": [
```

(continues on next page)

(continued from previous page)

```
{
  "text": "region was created.",
  "level": "success"
},
"response": {
  "divisionName": "England",
  "division": 3,
  "id": 5,
  "lastUpdated": "2018-12-06 02:14:45+00",
  "name": "Manchester"
}}
```

DELETE

Deletes a region. If no query parameter is specified, a 400 Bad Request response is returned.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 534: Request Query Parameters

Name	Required	Description
id	no	Delete <i>Region</i> by integral, unique identifier
name	no	Delete <i>Region</i> by name

1320: Request Example

```
DELETE /api/4.0/regions?name=Manchester HTTP/1.1
User-Agent: curl/7.29.0
Host: trafficops.infra.ciab.test
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1321: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Fri, 07 Feb 2020 13:56:24
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳yNqXKcoiohEbJrEkH8LD1zifh87dIusuvUqgQnYueyKqCXkfd5bQvQ00hQ2AAdSZa/
    ↳oe2SAqMjojGsUlxHtIQw==
X-Server-Name: traffic_ops_golang/
Date: Fri, 07 Feb 2020 12:56:24 GMT
Content-Length: 62

{
  "alerts": [
    {
      "text": "region was deleted.",
      "level": "success"
    }
  ]
}
```

regions/{{ID}}

PUT

Updates a *Region*.

Auth. Required Yes

Role(s) Required “admin” or “operator”

Response Type Object

Request Structure

Table 535: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the region to update

division The new integral, unique identifier of the division which shall contain the region¹

divisionName The new name of the division which shall contain the region¹

name The new name of the region

1322: Request Example

```
PUT /api/4.0/regions/5 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 60
Content-Type: application/json

{
  "name": "Leeds",
  "division": 3,
  "divisionName": "England"
}
```

¹ The only “division” key that actually matters in the request body is `division`; `divisionName` is not validated and has no effect - particularly not the effect of re-naming the division - beyond changing the name in the API response to this request. Subsequent requests will reveal the true name of the division. Note that if `divisionName` is not present in the request body it will be `null` in the response, but again further requests will show the true division name (provided it has been assigned to a division).

Response Structure

- divisionName** The name of the division which contains this region
- divisionId** The integral, unique identifier of the division which contains this region
- id** An integral, unique identifier for this region
- lastUpdated** The date and time at which this region was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The region name

1323: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳7SVj4q7dtSTNQEJlBApEwlad28WBVFnpdHaatoIpNfeLltfcpcdVTcOKB4JXQv7rlSD2p/
    ↳TxBQC6EXpxwYTnKQ==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 02:23:40 GMT
Content-Length: 173

{ "alerts": [
  {
    "text": "region was updated.",
    "level": "success"
  }
],
"response": {
  "divisionName": "England",
  "division": 3,
  "id": 5,
  "lastUpdated": "2018-12-06 02:23:40+00",
  "name": "Leeds"
}}
```

roles

GET

Retrieves all user *Roles*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 536: Request Query Parameters

Name	Re- quired	Description
id	no	Return only the <i>Role</i> identified by this integral, unique identifier
name	no	Return only the <i>Role</i> with this name
privLevel	no	Return only those <i>Roles</i> that have this privilege level
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page .

1324: Request Example

```
GET /api/4.0/roles?name=admin HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

capabilities An array of the names of the Capabilities given to this *Role*

description A description of the *Role*

id The integral, unique identifier for this *Role*

name The name of the *Role*

privLevel An integer that allows for comparison between *Roles*

1325: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳TEDXlQqWMSnJbL10JtFdbw0nqciNpjc4bd6m7iAB8aymakWeF+ghs1k5LayjdzHcjeDE8UNF/
    ↳HXSxOFvoLFEuA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 04 Sep 2019 17:15:36 GMT
Content-Length: 120

{ "response": [
  {
    "id": 4,
    "name": "admin",
    "description": "super-user",
    "privLevel": 30,
    "capabilities": [
      "all-write",
      "all-read"
    ]
  }
]
```

(continues on next page)

(continued from previous page)

```
}
[]}
```

POST

Creates a new *Role*.

Auth. Required Yes

Roles Required “admin”

Response Type Object

Request Structure

capabilities An optional array of capability names that will be granted to the new *Role*

description A helpful description of the *Role*’s purpose.

name The name of the new *Role*

privLevel The privilege level of the new *Role*¹

1326: Request Example

```
POST /api/4.0/roles HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "name": "test",
  "description": "quest",
  "privLevel": 30
}
```

¹ **privLevel** cannot exceed the privilege level of the requesting user. Which, of course, must be the privilege level of “admin”. Basically, this means that there can never exist a *Role* with a higher privilege level than “admin”.

Response Structure

capabilities An array of the names of the Capabilities given to this *Role*

Tip: This can be null *or* empty, depending on whether it was present in the request body, or merely empty. Obviously, it can also be a populated array.

description A description of the *Role*

id The integral, unique identifier for this *Role*

name The name of the *Role*

privLevel An integer that allows for comparison between *Roles*

1327: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: gzfc7m/
    ↳in5vVsVP+Y9h6JJfDhgpXKn9VAzoiPENhKbQfP8Q6jug08Rt2AK/
    ↳3Nz1cx5zZ8P9IjVxDdIg7mlC8bw==
X-Server-Name: traffic_ops_golang/
Date: Wed, 04 Sep 2019 17:44:42 GMT
Content-Length: 150

{ "alerts": [{
    "text": "role was created.",
    "level": "success"
}],
  "response": {
    "id": 5,
    "name": "test",
    "description": "quest",
    "privLevel": 30,
    "capabilities": null
  }
}
```


PUT

Replaces an existing *Role* with one provided by the request.

Auth. Required Yes

Roles Required “admin”

Response Type

Request Structure

Table 537: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Role</i> to be replaced

capabilities An optional array of capability names that will be granted to the new *Role*

Warning: When not present, the affected *Role*’s Capabilities will be unchanged - *not* removed, unlike when the array is empty.

description A helpful description of the *Role*’s purpose.

name The new name of the *Role*

privLevel The new privilege level of the new *Role*^{Page 1883, 1}

1328: Request Example

```
PUT /api/4.0/roles?id=5 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "name": "test",
  "privLevel": 29,
  "description": "quest"
}
```

Response Structure

capabilities An array of the names of the Capabilities given to this *Role*

Tip: This can be null *or* empty, depending on whether it was present in the request body, or merely empty. Obviously, it can also be a populated array.

Warning: If no **capabilities** array was given in the request, this will *always* be null, even if the *Role* has Capabilities that would have gone unchanged.

description A description of the *Role*

id The integral, unique identifier for this *Role*

name The name of the *Role*

privLevel An integer that allows for comparison between *Roles*

1329: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳mlHQenE1Q3gjrIK21C2hfueQOaTCpdYefboN0A9vYPUIwTiaF5ZaAMPQBdfGyiAhgHRxowITs3bR7s1L+
X-Server-Name: traffic_ops_golang/
Date: Thu, 05 Sep 2019 12:56:46 GMT
Content-Length: 150

{
  "alerts": [
    {
      "text": "role was updated.",
      "level": "success"
    }
  ],
  "response": {
    "id": 5,
    "name": "test",
```

(continues on next page)

(continued from previous page)

```

    "description": "quest",
    "privLevel": 29,
    "capabilities": null
  }
}

```

DELETE

Deletes a *Role*

Auth. Required Yes

Roles Required “admin”

Response Type undefined

Request Structure

Table 538: Request Query Parameters

Name	Required	Description
id	yes	The integral, unique identifier of the <i>Role</i> to be replaced

1330: Request Example

```

DELETE /api/4.0/roles?id=5 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...

```

Response Structure

1331: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
↪GMT; Max-Age=3600; HttpOnly

```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512: 10jeFZihtbvAus/XyHAW8rhgS9JBD+X/
→ezCp1iExYkEcHxN4gjr1L6x8zDFXORueBSlFldgtbWKT7QsmwCHUWA==
X-Server-Name: traffic_ops_golang/
Date: Thu, 05 Sep 2019 13:02:06 GMT
Content-Length: 59

{ "alerts": [{
  "text": "role was deleted.",
  "level": "success"
}]}
```

server_capabilities

GET

Retrieves *Server Capabilities*.

Auth. Required Yes

Roles Required “read-only”

Response Type Array

Request Structure

Table 539: Request Query Parameters

Name	Required	Description
name	no	Return the <i>Server Capability</i> with this name

1332: Request Structure

```
GET /api/4.0/server_capabilities?name=RAM HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

name The name of this *Server Capability*

lastUpdated The date and time at which this *Server Capability* was last updated, in ISO-like format

1333: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpGT3YRyKJ/
→p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 21:36:13 GMT
Content-Length: 68

{
  "response": [
    {
      "name": "RAM",
      "lastUpdated": "2019-10-07 20:38:24+00"
    }
  ]
}
```

POST

Create a new *Server Capability*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the *Server Capability*

1334: Request Example

```
POST /api/4.0/server_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 15
Content-Type: application/json

{
  "name": "RAM"
}
```

Response Structure

name The name of this *Server Capability*

lastUpdated The date and time at which this *Server Capability* was last updated, in ISO-like format

1335: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ysdopC//
→JQI79BRUa61s6M2HzHxYHpo5Rdcuau0oqCYxiV0oUhNZfOVydVkv8zDN2qA374XKnym4kWj3VzQIXg==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:10:00 GMT
Content-Length: 137

{
  "alerts": [
    {
      "text": "server capability was created.",
      "level": "success"
    }
  ],
  "response": {
    "name": "RAM",
    "lastUpdated": "2019-10-07 22:10:00+00"
  }
}
```

PUT

Update an existing *Server Capability*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name The name of the *Server Capability*

1336: Request Example

```
PUT /api/4.0/server_capabilities/edit?name=RAM HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 15
Content-Type: application/json

{
  "name": "HDD"
}
```

Response Structure

name The name of this *Server Capability*

lastUpdated The date and time at which this *Server Capability* was last updated, in ISO-like format

1337: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ysdopC//
→JQI79BRUa61s6M2HzHxYHpo5Rdcuau0oqCYxiV0oUhNZfOVydVkv8zDN2qA374XKnym4kWj3VzQIXg==
X-Server-Name: traffic_ops_golang/
Date: Wed, 03 March 2021 21:22:08 GMT
Content-Length: 137

{
  "alerts": [
    {
      "text": "server capability was updated.",
      "level": "success"
    }
  ],
  "response": {
    "name": "HDD",
    "lastUpdated": "2021-03-03 21:22:08+00"
  }
}
```

DELETE

Deletes a specific *Server Capability*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 540: Request Query Parameters

Name	Required	Description
name	yes	The name of the <i>Server Capability</i> to be deleted

1338: Request Example

```
DELETE /api/4.0/server_capabilities?name=RAM HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1339: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 8zCAATbCzcqiqigGVBy7WF1duDuXu1Wg2DBe9yfqTw/
    ↳c+yhE2eUk73hFTA/Oqt0kocaN7+1GkbFdPkQPvbnRaA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 20:44:40 GMT
Content-Length: 72

{
  "alerts": [
    {
      "text": "server capability was deleted.",
      "level": "success"
    }
  ]
}
```

server_server_capabilities

GET

Gets all associations of *Server Capabilities* to *cache servers*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 541: Request Query Parameters

Name	Re- quired	Description
serverId	no	Filter <i>Server Capability</i> associations by the integral, unique identifier of the server to which they are assigned
server-Host-Name	no	Filter <i>Server Capability</i> associations by the host name of the server to which they are assigned
server-Ca-pabil-ity	no	Filter <i>Server Capability</i> associations by <i>Server Capability</i> name
or-derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1340: Request Example

```
GET /api/4.0/server_server_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

serverHostName The server's host name

serverId The server's integral, unique identifier

lastUpdated The date and time at which this association between the server and the *Server Capability* was last updated, in *Traffic Ops's Custom Date/Time Format*

serverCapability The *Server Capability*'s name

1341: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
    ↳jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
    ↳DbBwhMAOJoeqDImoDlrLnrVjQG04AooA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 150

{
  "response": [
    {
      "lastUpdated": "2019-10-07 22:05:31+00",
      "serverHostName": "atlanta-org-1",
      "serverId": 260,
      "serverCapability": "ram"
    },
    {
      "lastUpdated": "2019-10-07 22:05:31+00",
      "serverHostName": "atlanta-org-2",
      "serverId": 261,
      "serverCapability": "disk"
    }
  ]
}
```

POST

Associates a *Server Capability* to a server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

serverId The integral, unique identifier of a server to be associated with a *Server Capability*

serverCapability The *Server Capability*’s name to associate

Note: The server referenced must be either an *Edge-tier* or *Mid-tier cache server*.

1342: Request Example

```
POST /api/4.0/server_server_capabilities HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 84
Content-Type: application/json

{
  "serverId": 1,
  "serverCapability": "disk"
}
```

Response Structure

serverId The integral, unique identifier of the newly associated server

lastUpdated The date and time at which this association between the server and the *Server Capability* was last updated, in *Traffic Ops’s Custom Date/Time Format*

serverCapability The *Server Capability*’s name

1343: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳eQrl48zWids0kDpfCYmmtYMpegjnFxf0VvlBYxxLSfp7P7p6oWX4uiC+/
    ↳Cfh2X9i3G+MQ36eH95gukJqOB0GbQ==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 157

{
  "alerts": [
    {
      "text": "server server_capability was created.",
      "level": "success"
    }
  ],
  "response": {
    "lastUpdated": "2019-10-07 22:15:11+00",
    "serverId": 1,
    "serverCapability": "disk"
  }
}
```

DELETE

Disassociate a server from a *Server Capability*.

Note: If the serverCapability is a *Server Capability* required by a *Delivery Service* that to which the server is assigned the DELETE will be blocked until either the server is unassigned from the *Delivery Service* or the *Server Capability* is no longer required by the *Delivery Service*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 542: Request Query Parameters

Name	Re-quired	Description
serverId	yes	The integral, unique identifier of the server to disassociate
serverCapabil-ity	yes	term: <i>Server Capability</i> name to disassociate from given server

1344: Request Example

```
DELETE /api/4.0/server_server_capabilities?serverId=1&
→serverCapability=disk HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1345: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: UF03/
→jcBFmFZM7CsrsIwTfPc5v8gUiXqJm6BNp1boPb4EQBnWNXZh/
→DbBwhMAOJoeqDImoDlrLnrVjQGO4AooA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 07 Oct 2019 22:15:11 GMT
Content-Length: 96

{
  "alerts": [
    {
      "text": "server server_capability was deleted.",
      "level": "success"
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```
]
}
```

servercheck

See also:

Check Extensions

GET

Fetches identifying and meta information as well as “check” values regarding all servers that have a *Type* with a name beginning with “EDGE” or “MID” (ostensibly this is equivalent to all *cache servers*).

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 543: Request Query Parameters

Name	Required	Description
id	no	Return only <i>cache servers</i> with this integral, unique identifier (id)
hostName	no	Return only <i>cache servers</i> with this host_name

1346: Request Example with hostName query param

```
GET /api/4.0/servercheck?hostName=edge HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

1347: Request Example with id query param

```
GET /api/4.0/servercheck?id=12 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- adminState** The name of the server's *Status* - called "adminState" for legacy reasons
- cacheGroup** The name of the *Cache Group* to which the server belongs
- checks** An optionally present map of the names of "checks" to their values. Only numeric and boolean checks are represented, and boolean checks are represented as integers with 0 meaning "false" and 1 meaning "true". Will not appear if the server in question has no valued "checks".
- hostName** The (short) hostname of the server
- id** The server's integral, unique identifier
- profile** The name of the *Profile* used by the server
- revalPending** A boolean that indicates whether or not the server has pending revalidations
- type** The name of the server's *Type*
- updPending** A boolean that indicates whether or not the server has pending updates

1348: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Thu, 18 Feb 2021 20:00:19
→GMT; Max-Age=3600; HttpOnly
X-Server-Name: traffic_ops_golang/
Date: Thu, 18 Feb 2021 19:00:19 GMT
Content-Length: 352

{ "response": [
  {
    "adminState": "REPORTED",
    "cacheGroup": "CDN_in_a_Box_Edge",
    "id": 12,
    "hostName": "edge",
    "revalPending": false,
    "profile": "ATS_EDGE_TIER_CACHE",
    "type": "EDGE",

```

(continues on next page)

(continued from previous page)

```

    "updPending": false
  }
}]

```

POST

Post a server check result to the “serverchecks” table. Updates the resulting value from running a given check extension on a server.

Auth. Required Yes

Roles Required None¹

Response Type Object

Request Structure

The request only requires to have either `host_name` or `id` defined.

host_name The hostname of the server to which this “servercheck” refers.

id The id of the server to which this “servercheck” refers.

servercheck_short_name The short name of the “servercheck”.

value The value of the “servercheck”

1349: Request Example

```

POST /api/4.0/servercheck HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 113
Content-Type: application/json

{
  "id": 1,
  "host_name": "edge",
  "servercheck_short_name": "test",
  "value": 1
}

```

¹ No roles are required to use this endpoint, however access is controlled by username. Only the reserved user extension is permitted the use of this endpoint.

Response Structure

1350: Response Example

```
{ "alerts": [  
  {  
    "level": "success",  
    "text": "Server Check was successfully updated."  
  }  
]}
```

servercheck/extensions

See also:

Managing Traffic Ops Extensions

GET

Retrieves the list of Traffic Ops extensions.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 544: Request Query Parameters

Name	Re-quired	Description
id	no	Filter TO Extensions by the integral, unique identifier of an Extension
name	no	Filter TO Extensions by the name of an Extension
script_file	no	Filter TO Extensions by the base filename of the script that runs for the Extension
is-active	no	Boolean used to return either only active (1) or inactive(0) TO Extensions
type	no	Filter TO Extensions by the type of Extension
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit.
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1351: Request Example

```
GET /api/4.0/servercheck/extensions HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

additional_config_json A string containing a JSON-encoded object with extra configuration options... inside a JSON object...

description A short description of the extension

Note: This is, unfortunately, null for all default extensions

id An integral, unique identifier for this extension definition

info_url A URL where info about this extension may be found

isactive An integer describing the boolean notion of whether or not the extension is active; one of:

0 disabled

1 enabled

name The name of the extension

script_file The base filename of the script that runs for the extension

servercheck_shortname The name of the column in the table at ‘Monitor’ -> ‘Cache Checks’ in Traffic Portal, where “Check Extension” output is displayed

type The Check *Type* of the extension. This will always be a CHECK_EXTENSION type with the naming convention of CHECK_EXTENSION_*.

version A (hopefully) semantic version number describing the version of the plugin

1352: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Tue, 11 Dec 2018 20:51:48 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: n73jg9XR4V5Cwqq56Rf3wuIi99k3mM5u2NAjcZ/
→gQB8jvAFymDlnZqKeJ+wTll1vjIsHpXCOVXV7+5UGakLgA==
Transfer-Encoding: chunked

{ "response": [
  {
    "script_file": "ToPingCheck.pl",
    "version": "1.0.0",
    "name": "ILO_PING",
    "description": null,
    "info_url": "-",
    "additional_config_json": "{ check_name: \"ILO\", \"base_url\
→\": \"https://localhost\", \"select\": \"ilo_ip_address\", \"cron\": \
→\"9 * * * *\" }",
    "isactive": 1,
    "type": "CHECK_EXTENSION_BOOL",
    "id": 1,
    "servercheck_short_name": "ILO"
```

(continues on next page)

(continued from previous page)

```

    },
    {
      "script_file": "ToPingCheck.pl",
      "version": "1.0.0",
      "name": "10G_PING",
      "description": null,
      "info_url": "-",
      "additional_config_json": "{ check_name: \"10G\", \"base_url\
→\": \"https://localhost\", \"select\": \"ip_address\", \"cron\": \"18_
→* * * *\" }",
      "isactive": 1,
      "type": "CHECK_EXTENSION_BOOL",
      "id": 2,
      "servercheck_short_name": "10G"
    }
  ]}

```

POST

Creates a new Traffic Ops check extension.

Auth. Required Yes

Roles Required None¹

Response Type undefined

Request Structure

additional_config_json An optional string containing a JSON-encoded object with extra configuration options... inside a JSON object...

description A short description of the extension

info_url A URL where info about this extension may be found

isactive An integer describing the boolean notion of whether or not the extension is active; one of:

0 disabled

1 enabled

name The name of the extension

script_file The base filename of the script that runs for the extension

¹ No roles are required to use this endpoint, however access is controlled by username. Only the reserved user extension is permitted the use of this endpoint.

See also:

Managing Traffic Ops Extensions for details on where the script should be located on the Traffic Ops server

servercheck_shortcode The name of the column in the table at ‘Monitor’ -> ‘Cache Checks’ in Traffic Portal, where “Check Extension” output is displayed

type The *Type* of extension. Must be CHECK_EXTENSION type with the naming convention of CHECK_EXTENSION_*.

version A (hopefully) semantic version number describing the version of the plugin

1353: Request Example

```
POST /api/4.0/servercheck/extensions HTTP/1.1
Host: ipcdn-cache-51.cdnlab.comcast.net:6443
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 208
Content-Type: application/json

{
  "name": "test",
  "version": "0.0.1-1",
  "info_url": "",
  "script_file": "",
  "isactive": 0,
  "description": "A test extension for API examples",
  "servercheck_shortcode": "test",
  "type": "CHECK_EXTENSION_NUM"
}
```

Response Structure

1354: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Date: Wed, 12 Dec 2018 16:37:44 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
    ↪GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 7M67PYnli6WzGQFS3g8Gh1SOyq6VENZMqm/
    ↪kUffOTLLFfuWSEuSLA65R5R+VyJiNjdqOG5Bp78mk+JYcqhtVGw==
Content-Length: 89

{ "supplemental":
  {
    "id": 5
  },
  "alerts": [{
    "level": "success",
    "text": "Check Extension Loaded."
  }]
}
```

`servercheck/extensions/{ID}`

DELETE

Deletes a Traffic Ops server check extension definition. This does **not** delete the actual extension file.

Auth. Required Yes

Roles Required None¹

Response Type undefined

Request Structure

Table 545: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the extension definition to be deleted

1355: Request Example

```
DELETE /api/4.0/servercheck/extensions/16 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

¹ No roles are required to use this endpoint, however access is controlled by username. Only the reserved user extension is permitted the use of this endpoint.

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1356: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Wed, 12 Dec 2018 16:33:52 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: EB0Nu85azbGzaehDTAODP3NPqWbByIza1XQhgwtS2WTXyK/
    ↳dxQtncp0YiJXy00tH9H+n+6BBfojB0b5h0dFPA==
Content-Length: 60

{ "alerts": [
  {
    "level": "success",
    "text": "Extension deleted."
  }
]}
```

servers

GET

Retrieves properties of all servers across all CDNs.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 546: Request Query Parameters

Name	Re- quired	Description
cache-group	no	Return only those servers within the <i>Cache Group</i> that has this <i>ID</i>
cache-group-Name	no	Return only those servers within the <i>Cache Group</i> that has this <i>Name</i>
dsId	no	Return only those servers assigned to the <i>Delivery Service</i> identified by this integral, unique identifier. If the Delivery Service has a <i>Topology</i> assigned to it, the <i>servers</i> endpoint will return each server whose <i>Cache Group</i> is associated with a <i>Topology Node</i> of that Topology and has the <i>Server Capabilities</i> that are <i>required by the Delivery Service</i> but excluding <i>Origin Servers</i> that are not assigned to the Delivery Service. For more information, see <i>Configure Multi-Site Origin</i> .
host-Name	no	Return only those servers that have this (short) hostname
id	no	Return only the server with this integral, unique identifier
profileId	no	Return only those servers that are using the <i>Profile</i> that has this <i>ID</i>
status	no	Return only those servers with this status - see <i>Health Protocol</i>
type	no	Return only servers of this <i>Type</i>
topology	no	Return only servers who belong to cachegroups assigned to the <i>Topology</i> identified by this name
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>nth</i> page of results, where “n” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

1357: Request Example

```
GET /api/4.0/servers?hostName=mid HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId The integral, unique identifier of the CDN to which the server belongs

cdnName Name of the CDN to which the server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be `null`

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service¹

iloIpGateway The IPv4 gateway address of the server's ILO service^{Page 1911, 1}

iloIpNetmask The IPv4 subnet mask of the server's ILO service^{Page 1911, 1}

iloPassword The password of the of the server's ILO service user^{Page 1911, 1} - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' *Role(s)*

iloUsername The user name for the server's ILO service^{Page 1911, 1}

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be present, but it is illegal for this set to be an empty collection.

¹ For more information see the [Wikipedia page on Lights-Out management](#).

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be present, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the "service interface" for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning "no limit". It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface's device name on the server, e.g. `eth0`.

routerPortName The human-readable name of the router responsible for reaching this server's interface.

routerPortName The human-readable name of the port used by the router responsible for reaching this server's interface.

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status

physLocation The name of the physical location where the server resides

physLocationId An integral, unique identifier for the physical location where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

profileId The *ID* the *Profile* used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack A string indicating "server rack" location

status The *Status* of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the *Type* of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

1358: Response Example

```
HTTP/1.1 200 OK
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 19 May 2020 17:06:25 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 19 May 2020 16:06:25 GMT
Content-Length: 538

{ "response": [{
  "cachegroup": "CDN_in_a_Box_Mid",
  "cachegroupId": 6,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "domainName": "infra.ciab.test",
  "guid": null,
  "hostName": "mid",
  "httpsPort": 443,
  "id": 12,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "lastUpdated": "2020-05-19 14:49:39+00",
  "mgmtIpAddress": "",
  "mgmtIpGateway": "",
```

(continues on next page)

(continued from previous page)

```
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_MID_TIER_CACHE",
"profileDesc": "Mid Cache - Apache Traffic Server",
"profileId": 10,
"rack": "",
"revalPending": false,
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "MID",
"typeId": 12,
"updPending": false,
"xmppId": "",
"xmppPasswd": "",
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "172.26.0.4/16",
        "gateway": "172.26.0.1",
        "serviceAddress": true
      }
    ],
    "maxBandwidth": null,
    "monitor": false,
    "mtu": 1500,
    "name": "eth0",
    "routerHostName": "",
    "routerPortName": ""
  }
],
}],
"summary": {
  "count": 13
}}
```

Summary Fields

The summary object returned by this method of this endpoint uses only the count *standard property*.

POST

Allows a user to create a new server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

cachegroupId An integer that is the *ID of the Cache Group* to which the server shall belong

cdnId The integral, unique identifier of the CDN to which the server shall belong

domainName The domain part of the server’s FQDN

hostName The (short) hostname of the server

httpsPort An optional port number on which the server listens for incoming HTTPS connections/requests

iloIpAddress An optional IPv4 address of the server’s ILO service^{Page 1911, 1}

iloIpGateway An optional IPv4 gateway address of the server’s ILO service^{Page 1911, 1}

iloIpNetmask An optional IPv4 subnet mask of the server’s ILO service^{Page 1911, 1}

iloPassword An optional string containing the password of the of the server’s ILO service user^{Page 1911, 1} - displays as simply ***** if the currently logged-in user does not have the ‘admin’ or ‘operations’ *Role(s)*

iloUsername An optional string containing the user name for the server’s ILO service^{Page 1911, 1}

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be necessary, but it is illegal for this set to be an empty collection.

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be necessary, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the "service interface" for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning "no limit". It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface's device name on the server, e.g. `eth0`.

routerPortName The human-readable name of the router responsible for reaching this server's interface.

routerPortName The human-readable name of the port used by the router responsible for reaching this server's interface.

mgmtIpAddress The IPv4 address of some network interface on the server used

for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

physLocationId An integral, unique identifier for the physical location where the server resides

profileId The *ID* the *Profile* that shall be used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack An optional string indicating “server rack” location

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort An optional port number on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd An optional password used in XMPP communications with the server

1359: Request Example

```
POST /api/4.0/servers HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 599
Content-Type: application/json

{
  "cachegroupId": 6,
  "cdnId": 2,
  "domainName": "infra.ciab.test",
  "hostName": "test",
  "httpsPort": 443,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "interfaces": [
    {
      "ipAddresses": [
        {
          "address": "::1",
          "gateway": "::2",
          "serviceAddress": true
        },
        {
          "address": "0.0.0.1/24",
          "gateway": "0.0.0.2",
          "serviceAddress": true
        }
      ],
      "maxBandwidth": null,
      "monitor": true,
      "mtu": 1500,
      "name": "eth0",
      "routerHostName": "",
      "routerPortName": ""
    }
  ],
  "interfaceMtu": 1500,
  "interfaceName": "eth0",
  "ip6Address": "::1",
```

(continues on next page)

(continued from previous page)

```

"ip6Gateway": "::2",
"ipAddress": "0.0.0.1",
"ipGateway": "0.0.0.2",
"ipNetmask": "255.255.255.0",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocationId": 1,
"profileId": 10,
"statusId": 3,
"tcpPort": 80,
"typeId": 12,
"updPending": false
}

```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId The integral, unique identifier of the CDN to which the server belongs

cdnName Name of the CDN to which the server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be null

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service [Page 1911, 1](#)

iloIpGateway The IPv4 gateway address of the server's ILO service [Page 1911, 1](#)

iloIpNetmask The IPv4 subnet mask of the server's ILO service [Page 1911, 1](#)

iloPassword The password of the of the server's ILO service user^{Page 1911, 1} - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' `ROLE(s) <ROLE>`

iloUsername The user name for the server's ILO service^{Page 1911, 1}

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be present, but it is illegal for this set to be an empty collection.

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be present, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the "service interface" for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning "no limit". It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface's device name on the server, e.g. `eth0`.

routerPortName The human-readable name of the router responsible for reaching this server's interface.

routerPortName The human-readable name of the port used by the router responsible for reaching this server's interface.

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

offlineReason A user-entered reason why the server is in `ADMIN_DOWN` or `OFFLINE` status

physLocation The name of the *Physical Location* where the server resides

physLocationId An integral, unique identifier for the *Physical Location* where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

profileId The *ID* the *Profile* used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack A string indicating "server rack" location

status The status of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by **httpsPort** may also be used for incoming TCP connections.

type The name of the ‘type’ of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if **true**, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server **hashId** for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

1360: Response Example

```
HTTP/1.1 201 Created
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 19 May 2020 17:34:40 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 19 May 2020 16:34:40 GMT
Content-Length: 562

{ "alerts": [
  {
    "text": "Server created",
    "level": "success"
  }
],
"response": {
  "cachegroup": "CDN_in_a_Box_Mid",
  "cachegroupId": 6,
  "cdnId": 2,
```

(continues on next page)

(continued from previous page)

```
"cdnName": "CDN-in-a-Box",
"domainName": "infra.ciab.test",
"guid": null,
"hostName": "test",
"httpsPort": 443,
"id": 14,
"iloIpAddress": "",
"iloIpGateway": "",
"iloIpNetmask": "",
"iloPassword": "",
"iloUsername": "",
"lastUpdated": "2020-05-19 16:34:40+00",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_MID_TIER_CACHE",
"profileDesc": "Mid Cache - Apache Traffic Server",
"profileId": 10,
"rack": null,
"revalPending": false,
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "MID",
"typeId": 12,
"updPending": false,
"xmppId": null,
"xmppPasswd": null,
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "::1",
        "gateway": "::2",
        "serviceAddress": true
      },
      {
        "address": "0.0.0.1/24",
        "gateway": "0.0.0.2",
        "serviceAddress": true
      }
    ]
  },
  {
    "maxBandwidth": null,

```

(continues on next page)

(continued from previous page)

```

        "monitor": true,
        "mtu": 1500,
        "name": "eth0",
        "routerHostName": "",
        "routerPortName": ""
    }
]
}}
```

servers/details

Retrieves details of *Servers*.

GET

Auth. Required Yes

Roles Required None

Response Type Array

Note: On top of the response including the response key that is of type array it will also include the keys `limit`, `orderby`, and `size`.

Request Structure

Table 547: Request Query Parameters

Name	Required	Description
host-Name	Required if no physLocationID provided	Return only the servers with this (short) hostname. Capitalization of “hostName” is important.
phys-LocationID	Required if no hostName provided	Return only servers with this integral, unique identifier for the physical location where the server resides. Capitalization of “physLocationID” is important.

1361: Request Example

```

GET /api/4.0/servers/details?hostName=edge HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
```

(continues on next page)

(continued from previous page)

Connection: keep-alive
Cookie: mojolicious=...

Response Structure

limit The maximum size of the `response` array, also indicative of the number of results per page using the pagination requested by the query parameters (if any) - this should be the same as the `limit` query parameter (if given)

orderby A string that names the field by which the elements of the `response` array are ordered - should be the same as the `orderby` request query parameter (if given)

response An array of objects, each of which represents the details of a given *Server*.

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cdnName Name of the CDN to which the server belongs

deliveryservices An array of integral, unique identifiers for *Delivery Services* to which this server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be `null`

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service¹

iloIpGateway The IPv4 gateway address of the server's ILO service¹

iloIpNetmask The IPv4 subnet mask of the server's ILO service¹

iloPassword The password of the of the server's ILO service user¹ - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' *Role(s)*

¹ For more information see the [Wikipedia page on Lights-Out management](#).

iloUsername The user name for the server's ILO service¹

interfaces An array of interface and IP address information

max_bandwidth The maximum allowed bandwidth for this interface to be considered “healthy” by Traffic Monitor. This has no effect if *monitor* is not true. Values are in kb/s. The value 0 means “no limit”.

monitor A boolean indicating if Traffic Monitor should monitor this interface

mtu The MTU to configure for `interfaceName`

See also:

[The Wikipedia article on Maximum Transmission Unit](#)

name The network interface name used by the server.

ipAddresses An array of the IP address information for the interface

address The IPv4 or IPv6 address and subnet mask of the server - applicable for the interface name

gateway The IPv4 or IPv6 gateway address of the server - applicable for the interface name

service_address A boolean determining if content will be routed to the IP address

routerHostName The human-readable name of the router responsible for reaching this server's interface.

routerPortName The human-readable name of the port used by the router responsible for reaching this server's interface.

mgmtIpAddress The IPv4 address of the server's management port

mgmtIpGateway The IPv4 gateway of the server’s management port

mgmtIpNetmask The IPv4 subnet mask of the server’s management port

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status

physLocation The name of the physical location where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

rack A string indicating “server rack” location

status The status of the server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the ‘type’ of this server

xmppId A system-generated UUID used to generate a server hashId for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

size The page number - if pagination was requested in the query parameters, else 0 to indicate no pagination - of the results represented by the response array. This is named “size” for legacy reasons

1362: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
```

(continues on next page)

(continued from previous page)

```
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 01:27:36.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→HW2F3CEpohNAvNlEDhUfXmtwpEka4dwUWfVUSSjW98aXiv10vI6ysRIcC2P9huabCz5fdHqY3tp0LR4ekv
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 00:27:36 GMT
Content-Length: 493
```

```
{
  "limit": 1000,
  "orderby": "hostName",
  "response": [
    {
      "cachegroup": "CDN_in_a_Box_Edge",
      "cdnName": "CDN-in-a-Box",
      "deliveryservices": [
        1
      ],
      "domainName": "infra.ciab.test",
      "guid": null,
      "hardwareInfo": null,
      "hostName": "edge",
      "httpsPort": 443,
      "id": 5,
      "iloIpAddress": "",
      "iloIpGateway": "",
      "iloIpNetmask": "",
      "iloPassword": "",
      "iloUsername": "",
      "mgmtIpAddress": "",
      "mgmtIpGateway": "",
      "mgmtIpNetmask": "",
      "offlineReason": "",
      "physLocation": "Apachecon North America 2018",
      "profile": "ATS_EDGE_TIER_CACHE",
      "profileDesc": "Edge Cache - Apache Traffic Server",
      "rack": "",
      "status": "REPORTED",
      "tcpPort": 80,
      "type": "EDGE",
      "xmppId": "edge",
      "xmppPasswd": "",
      "interfaces": [
        { "ipAddresses": [
```

(continues on next page)

(continued from previous page)

```

        {
            "address": "172.16.239.100",
            "gateway": "172.16.239.1",
            "service_address": true
        },
        {
            "address": "fc01:9400:1000:8::100",
            "gateway": "fc01:9400:1000:8::1",
            "service_address": true
        }
    ],
    "max_bandwidth": 0,
    "monitor": true,
    "mtu": 1500,
    "name": "eth0",
    "routerHostName": "",
    "routerPortName": ""
}

]
}

],
"size": 1
}

```

servers/{{HostName-Or-ID}}/update

POST

Queue or dequeue updates and revalidation updates for a specific server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 548: Request Path Parameters

Name	Description
HostName-OR-ID	The hostName or integral, unique identifier of the server on which updates are being queued or dequeued

Table 549: Request Query Parameters

Name	Re-quired	Description
updated	no	The value to set for the queue update flag on this server. May be 'true' or 'false'.
reval_updated	no	The value to set for the queue update flag on this server. May be 'true' or 'false'.

1363: Request Example

```
GET /api/4.0/servers/my-edge/update?updated=true&reval_updated=false_
→HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1364: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Mon, 10 Dec 2018 18:20:04 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54_
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 9Mmo9hIFZyF5gAvfdJD//
→VH9eNgiHVLinXt88H0GlJSHhwND8gMxaFyC+f9XZfiNAoGd1MKi1934ZJGmaIR6qQ==
Content-Length: 49

{
  "alerts" :
  [
    {
      "text" : "successfully set server 'my-edge'_
→updated=true reval_updated=false",
      "level" : "success"
```

(continues on next page)

(continued from previous page)

```

    }
  ]
}
```

servers/{{hostname}}/update_status

Note: This endpoint only truly has meaning for *cache servers*, though it will return a valid response for any server configured in Traffic Ops.

GET

Retrieves information regarding pending updates and revalidation jobs for a given server

Auth. Required Yes

Roles Required None

Response Type Array

Changed in version 4.0: Prior to API version 4.0, the response was a top-level array rather than the normal response object.

Request Structure

Table 550: Request Path Parameters

Name	Description
hostname	The (short) hostname of the server being inspected

1365: Request Example

```
GET /api/4.0/servers/edge/update_status HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

Each object in the returned array¹ will contain the following fields:

- host_id** The integral, unique identifier for the server for which the other fields in this object represent the pending updates and revalidation status
- host_name** The (short) hostname of the server for which the other fields in this object represent the pending updates and revalidation status
- parent_pending** A boolean telling whether or not any *Topology* ancestor or *parent* of this server has pending updates
- parent_reval_pending** A boolean telling whether or not any *Topology* ancestor or *parent* of this server has pending revalidation jobs
- reval_pending** true if the server has pending revalidation jobs, false otherwise
- status** The name of the status of this server

See also:

Health Protocol gives more information on how these statuses are used, and the GET method of the *statuses* endpoint can be used to retrieve information about all server statuses configured in Traffic Ops.

- upd_pending** true if the server has pending updates, false otherwise
- use_reval_pending** A boolean which tells *ORT* whether or not this version of Traffic Ops should use pending revalidation jobs

Note: This field was introduced to give *ORT* the ability to work with Traffic Control versions 1.x and 2.x seamlessly - as of Traffic Control v3.0 there is no reason for this field to ever be false.

1366: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
```

(continues on next page)

¹ The returned object is an array, and there is no guarantee that one server exists for a given hostname. However, for each server in the array, that server's update status will be accurate for the server with that particular server ID.

(continued from previous page)

```
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳R6BjNVrcecHGn3eGDqQ1yDiBnEDGQe7QtOMIsRwlpck9SZR8chRQznrkTF3YdROAZ1l8BxR3fXTIvKHIz
    ↳dA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 04 Feb 2019 16:24:01 GMT
Content-Length: 174

{ "response": [{
    "host_name": "edge",
    "upd_pending": false,
    "reval_pending": false,
    "use_reval_pending": true,
    "host_id": 10,
    "status": "REPORTED",
    "parent_pending": false,
    "parent_reval_pending": false
}]}
```

`servers/{ID}`

PUT

Allow user to edit a server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 551: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a server

cachegroupId An integer that is the *ID of the Cache Group* to which the server shall belong

cdnId The integral, unique identifier of the CDN to which the server shall belong

domainName The domain part of the server's FQDN

hostName The (short) hostname of the server

httpsPort An optional port number on which the server listens for incoming HTTPS connections/requests

iloIpAddress An optional IPv4 address of the server's ILO service¹

iloIpGateway An optional IPv4 gateway address of the server's ILO service^{Page 1929, 1}

iloIpNetmask An optional IPv4 subnet mask of the server's ILO service^{Page 1929, 1}

iloPassword An optional string containing the password of the of the server's ILO service user^{Page 1929, 1} - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' `ROLE(s) <ROLE>`

iloUsername An optional string containing the user name for the server's ILO service^{Page 1929, 1}

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be necessary, but it is illegal for this set to be an empty collection.

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be necessary, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface -

¹ For more information see the [Wikipedia page on Lights-Out management](#).

which is therefore sometimes referred to as the “service interface” for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning “no limit”. It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface. This unsigned integer must not be less than 1280.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface’s device name on the server, e.g. `eth0`.

routerPortName The human-readable name of the router responsible for reaching this server’s interface.

routerPortName The human-readable name of the port used by the router responsible for reaching this server’s interface.

mgmtIpAddress The IPv4 address of some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

physLocationId An integral, unique identifier for the physical location where the server resides

profileId The *ID* the *Profile* that shall be used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack An optional string indicating “server rack” location

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort An optional port number on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd An optional password used in XMPP communications with the server

1367: Request Example

```
PUT /api/4.0/servers/14 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 599
Content-Type: application/json

{
  "cachegroupId": 6,
  "cdnId": 2,
  "domainName": "infra.ciab.test",
  "hostName": "quest",
  "httpsPort": 443,
  "iloIpAddress": "",
```

(continues on next page)

(continued from previous page)

```

"iloIpGateway": "",
"iloIpNetmask": "",
"iloPassword": "",
"iloUsername": "",
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "::1",
        "gateway": "::2",
        "serviceAddress": true
      },
      {
        "address": "0.0.0.1/24",
        "gateway": "0.0.0.2",
        "serviceAddress": false
      }
    ],
    "maxBandwidth": null,
    "monitor": true,
    "mtu": 1500,
    "name": "bond0",
    "routerHostName": "",
    "routerPortName": ""
  }
],
"interfaceMtu": 1500,
"interfaceName": "eth0",
"ip6Address": "::1",
"ip6Gateway": "::2",
"ipAddress": "0.0.0.1",
"ipGateway": "0.0.0.2",
"ipNetmask": "255.255.255.0",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocationId": 1,
"profileId": 10,
"statusId": 3,
"tcpPort": 80,
"typeId": 12,
"updPending": false
}

```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belongs

cachegroupId An integer that is the *ID of the Cache Group* to which the server belongs

cdnId The integral, unique identifier of the CDN to which the server belongs

cdnName Name of the CDN to which the server belongs

domainName The domain part of the server's FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be `null`

hostName The (short) hostname of the server

httpsPort The port on which the server listens for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service Page 1929, 1

iloIpGateway The IPv4 gateway address of the server's ILO service Page 1929, 1

iloIpNetmask The IPv4 subnet mask of the server's ILO service Page 1929, 1

iloPassword The password of the of the server's ILO service user Page 1929, 1 - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' `ROLE(s) <ROLE>`

iloUsername The user name for the server's ILO service Page 1929, 1

interfaces A set of the network interfaces in use by the server. In most scenarios, only one will be present, but it is illegal for this set to be an empty collection.

ipAddresses A set of objects representing IP Addresses assigned to this network interface. In most scenarios, only one or two (usually one IPv4 address and one IPv6 address) will be present, but it is illegal for this set to be an empty collection.

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address". It is illegal for a server to not have at least one service address. It is also illegal for a server to have more than one service address of the same address family (i.e. more than one IPv4 service address and/or more than one IPv6 address). Finally, all service addresses for a server must be contained within one interface - which is therefore sometimes referred to as the "service interface" for the server.

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors will consider the entire server unhealthy - which includes *all* configured network interfaces. If this is `null`, it has the meaning "no limit". It has no effect if `monitor` is not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should be monitored by Traffic Monitor for statistics and health consideration.

mtu The MTU of this interface. If it is `null`, it may be assumed that the information is either not available or not applicable for this interface.

name The name of the interface. No two interfaces of the same server may share a name. It is the same as the network interface's device name on the server, e.g. `eth0`.

routerPortName The human-readable name of the router responsible for reaching this server's interface.

routerPortName The human-readable name of the port used by the router responsible for reaching this server's interface.

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server used for ‘management’

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

offlineReason A user-entered reason why the server is in ADMIN_DOWN or OFFLINE status

physLocation The name of the *Physical Location* where the server resides

physLocationId An integral, unique identifier for the *Physical Location* where the server resides

profile The *Name* of the *Profile* used by this server

profileDesc A *Description* of the *Profile* used by this server

profileId The *ID* the *Profile* used by this server

revalPending A boolean value which, if `true` indicates that this server has pending content invalidation/revalidation

rack A string indicating “server rack” location

status The status of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listens for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the ‘type’ of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server has updates of some kind pending, typically to be acted upon by Traffic Ops ORT

xmppId A system-generated UUID used to generate a server hashId for use in Traffic Router's consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

1368: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 19 May 2020 17:46:33
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 19 May 2020 16:46:33 GMT
Content-Length: 566

{ "alerts": [
  {
    "text": "Server updated",
    "level": "success"
  }
],
"response": {
  "cachegroup": "CDN_in_a_Box_Mid",
  "cachegroupId": 6,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "domainName": "infra.ciab.test",
  "guid": null,
  "hostName": "quest",
  "httpsPort": 443,
  "id": 14,
  "iloIpAddress": "",
  "iloIpGateway": "",
  "iloIpNetmask": "",
  "iloPassword": "",
  "iloUsername": "",
  "lastUpdated": "2020-05-19 16:46:33+00",
  "mgmtIpAddress": "",
  "mgmtIpGateway": "",
  "mgmtIpNetmask": "",
```

(continues on next page)

(continued from previous page)

```
"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_MID_TIER_CACHE",
"profileDesc": "Mid Cache - Apache Traffic Server",
"profileId": 10,
"rack": null,
"revalPending": false,
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "MID",
"typeId": 12,
"updPending": false,
"xmppId": null,
"xmppPasswd": null,
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "::1",
        "gateway": "::2",
        "serviceAddress": true
      },
      {
        "address": "0.0.0.1/24",
        "gateway": "0.0.0.2",
        "serviceAddress": false
      }
    ],
    "maxBandwidth": null,
    "monitor": true,
    "mtu": 1500,
    "name": "bond0",
    "routerHostName": "",
    "routerPortName": ""
  }
]
}}
```

DELETE

Allow user to delete server through api.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Changed in version 3.0: In older versions of the API, this endpoint did not return a response object. It now returns a representation of the deleted server.

Request Structure

Table 552: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a server

1369: Request Example

```
DELETE /api/4.0/servers/14 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

cachegroup A string that is the *name of the Cache Group* to which the server belonged

cachegroupId An integer that is the *ID of the Cache Group* to which the server belonged

cdnId The integral, unique identifier of the CDN to which the server belonged

cdnName Name of the CDN to which the server belonged

domainName The domain part of the server’s FQDN

guid An identifier used to uniquely identify the server

Note: This is a legacy key which only still exists for compatibility reasons - it should always be null

hostName The (short) hostname of the server

httpsPort The port on which the server listened for incoming HTTPS connections/requests

id An integral, unique identifier for this server

iloIpAddress The IPv4 address of the server's ILO service [Page 1929, 1](#)

iloIpGateway The IPv4 gateway address of the server's ILO service [Page 1929, 1](#)

iloIpNetmask The IPv4 subnet mask of the server's ILO service [Page 1929, 1](#)

iloPassword The password of the of the server's ILO service user [Page 1929, 1](#) - displays as simply `*****` if the currently logged-in user does not have the 'admin' or 'operations' *Role(s)*

iloUsername The user name for the server's ILO service [Page 1929, 1](#)

interfaces A set of the network interfaces that were in use by the server

ipAddresses A set of objects representing IP Addresses that were assigned to this network interface

address The actual IP address, including any mask as a CIDR-notation suffix

gateway Either the IP address of the network gateway for this address, or `null` to signify that no such gateway exists

serviceAddress A boolean that describes whether or not the server's main service is available at this IP address. When this property is `true`, the IP address is referred to as a "service address".

maxBandwidth The maximum healthy bandwidth allowed for this interface. If bandwidth exceeds this limit, Traffic Monitors would have considered the entire server unhealthy - which includes *all* configured network interfaces. If this was `null`, it has the meaning "no limit". It had no effect if `monitor` was not true for this interface.

See also:

Health Protocol

monitor A boolean which describes whether or not this interface should have been monitored by Traffic Monitor for statistics and health consideration

mtu The MTU of this interface. If it is `null`, it may be assumed that the information was either not available or not applicable for this interface.

name The name of the interface. It is the same as the network interface's device name on the server, e.g. `eth0`.

routerPortName The human-readable name of the router responsible for reaching this server's interface.

routerPortName The human-readable name of the port used by the router responsible for reaching this server's interface.

lastUpdated The date and time at which this server description was last modified

mgmtIpAddress The IPv4 address of some network interface on the server that was used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpGateway The IPv4 address of a gateway used by some network interface on the server that was used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

mgmtIpNetmask The IPv4 subnet mask used by some network interface on the server that was used for 'management'

Deprecated since version 3.0: This field is deprecated and will be removed in a future API version. Operators should migrate this data into the `interfaces` property of the server.

offlineReason A user-entered reason why the server was in ADMIN_DOWN or OFFLINE status

physLocation The name of the physical location where the server resided

physLocationId An integral, unique identifier for the physical location where the server resided

profile The *Name* of the *Profile* which was used by this server

profileDesc A *Description* of the *Profile* which was used by this server

profileId The *ID* the *Profile* which was used by this server

revalPending A boolean value which, if `true` indicates that this server had pending content invalidation/revalidation

rack A string indicating "server rack" location

status The *Status* of the server

See also:

Health Protocol

statusId The integral, unique identifier of the status of this server

See also:

Health Protocol

tcpPort The port on which this server listened for incoming TCP connections

Note: This is typically thought of as synonymous with “HTTP port”, as the port specified by `httpsPort` may also be used for incoming TCP connections.

type The name of the *Type* of this server

typeId The integral, unique identifier of the ‘type’ of this server

updPending A boolean value which, if `true`, indicates that the server had updates of some kind pending, typically to be acted upon by Traffic Ops *ORT*

xmppId A system-generated UUID used to generate a server `hashId` for use in Traffic Router’s consistent hashing algorithm. This value is set when a server is created and cannot be changed afterwards.

xmppPasswd The password used in XMPP communications with the server

1370: Response Example

```
HTTP/1.1 200 OK
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 19 May 2020 17:50:13 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
X-Server-Name: traffic_ops_golang/
Date: Tue, 19 May 2020 16:50:13 GMT
Content-Length: 568

{ "alerts": [
  {
    "text": "Server deleted",
    "level": "success"
  }
],
"response": {
  "cachegroup": "CDN_in_a_Box_Mid",
  "cachegroupId": 6,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "domainName": "infra.ciab.test",
  "guid": null,
  "hostName": "quest",
  "httpsPort": 443,
  "id": 14,
  "iloIpAddress": "",
  "iloIpGateway": "",
```

(continues on next page)

(continued from previous page)

```

"iloIpNetmask": "",
"iloPassword": "",
"iloUsername": "",
"lastUpdated": "2020-05-19 16:46:33+00",
"mgmtIpAddress": "",
"mgmtIpGateway": "",
"mgmtIpNetmask": "",
"offlineReason": "",
"physLocation": "Apachecon North America 2018",
"physLocationId": 1,
"profile": "ATS_MID_TIER_CACHE",
"profileDesc": "Mid Cache - Apache Traffic Server",
"profileId": 10,
"rack": null,
"revalPending": false,
"status": "REPORTED",
"statusId": 3,
"tcpPort": 80,
"type": "MID",
"typeId": 12,
"updPending": false,
"xmppId": null,
"xmppPasswd": null,
"interfaces": [
  {
    "ipAddresses": [
      {
        "address": "0.0.0.1/24",
        "gateway": "0.0.0.2",
        "serviceAddress": false
      },
      {
        "address": "::1",
        "gateway": "::2",
        "serviceAddress": true
      }
    ],
    "maxBandwidth": null,
    "monitor": true,
    "mtu": 1500,
    "name": "bond0",
    "routerHostName": "",
    "routerPortName": ""
  }
]
}
}

```

`servers/{{ID}}/deliveryservices`

GET

Retrieves all *Delivery Services* assigned to a specific server.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 553: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the server for which assigned <i>Delivery Services</i> shall be listed

Table 554: Request Query Parameters

Name	Re- quired	Description
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the ⁿ th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1371: Request Example

```
GET /api/4.0/servers/10/deliveryservices HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: python-requests/2.24.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

¹ Only the *Delivery Services* visible to the requesting user’s *Tenant* will appear, regardless of their *Role* or the *Delivery Services*’ actual ‘server assignment’ status.

Response Structure

active A boolean that defines *Active*.

anonymousBlockingEnabled A boolean that defines *Anonymous Blocking*

ccrDnsTtl The *DNS TTL* - named “ccrDnsTtl” for legacy reasons

cdnId The integral, unique identifier of the *CDN* to which the *Delivery Service* belongs

cdnName Name of the *CDN* to which the *Delivery Service* belongs

checkPath A *Check Path*

consistentHashRegex A *Consistent Hashing Regular Expression*

consistentHashQueryParams An array of *Consistent Hashing Query Parameters*

deepCachingType The *Deep Caching* setting for this *Delivery Service*

displayName The *Display Name*

dnsBypassCname A *DNS Bypass CNAME*

dnsBypassIp A *DNS Bypass IP*

dnsBypassIp6 A *DNS Bypass IPv6*

dnsBypassTtl The *DNS Bypass TTL*

dscp A *DSCP* to be used within the *Delivery Service*

ecsEnabled A boolean that defines the *EDNS0 Client Subnet Enabled* setting on this *Delivery Service*

edgeHeaderRewrite A set of *Edge Header Rewrite Rules*

exampleURLs An array of *Example URLs*

firstHeaderRewrite A set of *First Header Rewrite Rules*

fqPacingRate The *Fair-Queuing Pacing Rate Bps*

geoLimit An integer that defines the *Geo Limit*

geoLimitCountries A string containing a comma-separated list defining the *Geo Limit Countries*

geoLimitRedirectUrl A *Geo Limit Redirect URL*

geoProvider The *Geolocation Provider*

globalMaxMbps The *Global Max Mbps*

globalMaxTps The *Global Max TPS*

httpBypassFqdn A *HTTP Bypass FQDN*

id An integral, unique identifier for this *Delivery Service*

infoUrl An *Info URL*

- initialDispersion** The *Initial Dispersion*
- innerHeaderRewrite** A set of *Inner Header Rewrite Rules*
- ipv6RoutingEnabled** A boolean that defines the *IPv6 Routing Enabled* setting on this *Delivery Service*
- lastHeaderRewrite** A set of *Last Header Rewrite Rules*
- lastUpdated** The date and time at which this *Delivery Service* was last updated, in :rfc:3339 format
- Changed in version 4.0: Prior to API version 4.0, this property used *Traffic Ops's Custom Date/Time Format*.
- logsEnabled** A boolean that defines the *Logs Enabled* setting on this *Delivery Service*
- longDesc** The *Long Description* of this *Delivery Service*
- matchList** The *Delivery Service's Match List*
- pattern** A regular expression - the use of this pattern is dependent on the **type** field (backslashes are escaped)
 - setNumber** An integer that provides explicit ordering of *Match List* items - this is used as a priority ranking by Traffic Router, and is not guaranteed to correspond to the ordering of items in the array.
 - type** The type of match performed using pattern.
- maxDnsAnswers** The *Max DNS Answers* allowed for this *Delivery Service*
- maxOriginConnections** The *Max Origin Connections*
- midHeaderRewrite** A set of *Mid Header Rewrite Rules*
- missLat** The *Geo Miss Default Latitude* used by this *Delivery Service*
- missLong** The *Geo Miss Default Longitude* used by this *Delivery Service*
- multiSiteOrigin** A boolean that defines the use of *Use Multi-Site Origin Feature* by this *Delivery Service*
- orgServerFqdn** The *Origin Server Base URL*
- originShield** A *Origin Shield* string
- profileDescription** The *Description* of the *Profile* with which this *Delivery Service* is associated
- profileId** The *ID* of the *Profile* with which this *Delivery Service* is associated
- profileName** The *Name* of the *Profile* with which this *Delivery Service* is associated
- protocol** An integral, unique identifier that corresponds to the *Protocol* used by this *Delivery Service*

- qstringIgnore** An integral, unique identifier that corresponds to the *Query String Handling* setting on this *Delivery Service*
- rangeRequestHandling** An integral, unique identifier that corresponds to the *Range Request Handling* setting on this *Delivery Service*
- regexRemap** A *Regex Remap Expression*
- regionalGeoBlocking** A boolean defining the *Regional Geoblocking* setting on this *Delivery Service*
- remapText** *Raw Remap Text*
- signed** true if and only if *signingAlgorithm* is not null, false otherwise
- signingAlgorithm** Either a *Signing Algorithm* or null to indicate URL/URI signing is not implemented on this *Delivery Service*
- rangeSliceBlockSize** An integer that defines the byte block size for the ATS Slice Plugin. It can only and must be set if *rangeRequestHandling* is set to 3.
- sslKeyVersion** This integer indicates the *SSL Key Version*
- tenantId** The integral, unique identifier of the *Tenant* who owns this *Delivery Service*
- tlsVersions** A list of explicitly supported *TLS Versions*
- New in version 4.0.
- topology** The unique name of the *Topology* that this *Delivery Service* is assigned to
- trRequestHeaders** If defined, this defines the *Traffic Router Log Request Headers* used by Traffic Router for this *Delivery Service*
- trResponseHeaders** If defined, this defines the *Traffic Router Additional Response Headers* used by Traffic Router for this *Delivery Service*
- type** The *Type* of this *Delivery Service*
- typeId** The integral, unique identifier of the *Type* of this *Delivery Service*
- xmlId** This *Delivery Service*'s *xml_id*

1372: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Permissions-Policy: interest-cohort=()
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 08 Jun 2021 01:15:07 GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: R04tVfDdqx0rEU9BqlRmvsYXmVgVNkivqr6LhJlMulFR+1bLGivP8z93jy3N9bejcMdQwl1RwJojM3Mbw
X-Server-Name: traffic_ops_golang/
Date: Tue, 08 Jun 2021 00:15:07 GMT
Content-Length: 806
```

```
{ "response": [{
  "active": false,
  "anonymousBlockingEnabled": false,
  "ccrDnsTtl": 3600,
  "cdnId": 2,
  "cdnName": "CDN-in-a-Box",
  "checkPath": null,
  "consistentHashQueryParams": [],
  "consistentHashRegex": null,
  "deepCachingType": "NEVER",
  "displayName": "test",
  "dnsBypassCname": null,
  "dnsBypassIp": null,
  "dnsBypassIp6": null,
  "dnsBypassTtl": null,
  "dscp": 0,
  "ecsEnabled": false,
  "edgeHeaderRewrite": null,
  "exampleURLs": [
    "http://cdn.test.mycdn.ciab.test"
  ],
  "firstHeaderRewrite": null,
  "fqPacingRate": null,
  "geoLimit": 0,
  "geoLimitCountries": null,
  "geoLimitRedirectURL": null,
  "geoProvider": 0,
  "globalMaxMbps": null,
  "globalMaxTps": null,
  "httpBypassFqdn": null,
  "id": 7,
  "infoUrl": null,
  "initialDispersion": 1,
  "innerHeaderRewrite": null,
  "ipv6RoutingEnabled": true,
  "lastHeaderRewrite": null,
  "lastUpdated": "2021-06-08T00:14:04.959292Z",
```

(continues on next page)

(continued from previous page)

```
"logsEnabled": false,
"longDesc": "Apachecon North America 2018",
"matchList": [
  {
    "type": "HOST_REGEX",
    "setNumber": 0,
    "pattern": ".*\\.test\\.\\.\\.*"
  }
],
"maxDnsAnswers": null,
"maxOriginConnections": 0,
"maxRequestHeaderBytes": 0,
"midHeaderRewrite": null,
"missLat": 41.881944,
"missLong": -87.627778,
"multiSiteOrigin": false,
"originShield": null,
"orgServerFqdn": "http://origin.infra.ciab.test",
"profileDescription": null,
"profileId": null,
"profileName": null,
"protocol": 0,
"qstringIgnore": 0,
"rangeRequestHandling": 0,
"rangeSliceBlockSize": null,
"regexRemap": null,
"regionalGeoBlocking": false,
"remapText": null,
"routingName": "cdn",
"serviceCategory": null,
"signed": false,
"signingAlgorithm": null,
"sslKeyVersion": null,
"tenant": "root",
"tenantId": 1,
"tlsVersions": null,
"topology": null,
"trResponseHeaders": null,
"trRequestHeaders": null,
"type": "HTTP",
"typeId": 1,
"xmlId": "test"
}]}
```

POST

Assign an arbitrary number of *Delivery Services* to a single server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 555: Request Path Parameters

Name	Re- quired	Description
ID	Yes	The integral, unique identifier of the server that you want to assign delivery services to.

Table 556: Request Query Parameters

Name	Re- quired	Description
re- place	Yes	Whether the list of <i>Delivery Services</i> you provide should replace the existing list or be merged with the existing list. Must be a 1, or true, or 0, or false.

The request body is an array of IDs of *Delivery Services* that you want to assign to the server. The array can be empty, but it must be provided.

1373: Request Example

```
POST /api/4.0/servers/6/deliveryservices?replace=1 HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 3

[
  1
]
```

Response Structure

dsIds An array of integral, unique identifiers for *Delivery Services* which the request added to server. If `:replace:` is `false`, *Delivery Services* that are already assigned will remain, though they are not listed by `:dsIds:`.

replace The `:replace:` value you provided in the body of the request, or `null` if none was provided.

serverId The server's integral, unique identifier

1374: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 09:08:32
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳iV+JzAZSsmlxRZsNtIRg3oA9470hAwRMpq5xhcYVi0Y831Trx2YRlsyhYpOPqHg5+QPoXHGF0nx8uso0f
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 08:08:32 GMT
Content-Length: 129

{
  "alerts": [
    {
      "text": "successfully assigned dses to server",

```

(continues on next page)

(continued from previous page)

```

        "level": "success"
      }
    ],
    "response": {
      "serverId": 6,
      "dsIds": [
        1
      ],
      "replace": true
    }
  }
}

```

`servers/{{ID}}/queue_update`

Caution: In the vast majority of cases, it is advisable that the PUT method of the `servers/{{ID}}` endpoint be used instead.

POST

Queue or dequeue updates for a specific server.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 557: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the server on which updates are being queued or dequeued

action A string describing what action to take regarding server updates; one of:

queue *Queue Updates* for the server, propagating configuration changes to the actual server

dequeue Cancels any pending updates on the server

1375: Request Example

```
POST /api/4.0/servers/13/queue_update HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 22
Content-Type: application/json

{
  "action": "dequeue"
}
```

Response Structure

action The action processed, one of:

queue *Queue Updates* was performed on the server, propagating configuration changes to the actual server

dequeue Canceled any pending updates on the server

serverId The integral, unique identifier of the server on which action was taken

1376: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Mon, 10 Dec 2018 18:20:04 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 9Mmo9hIFZyF5gAvfdJD//
→VH9eNgiHVLinXt88H0GlJSHhwND8gMxaFyC+f9XZfiNAoGd1MKi1934ZJGmaIR6qQ==
Content-Length: 49

{
  "response": {
    "serverId": "13",
```

(continues on next page)

(continued from previous page)

```

    "action": "dequeue"
  }
}

```

servers/{ID}/status

PUT

Updates server status and queues updates on all descendant *Topology* nodes or child caches if server type is EDGE or MID. Also, captures offline reason if status is set to ADMIN_DOWN or OFFLINE and prepends offline reason with the user that initiated the status change.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 558: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the server whose status is being changed

offlineReason A string containing the reason for the status change

status The name or integral, unique identifier of the server’s new status

1377: Request Example

```

PUT /api/4.0/servers/13/status HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 56
Content-Type: application/json

{
  "status": "ADMIN_DOWN",
  "offlineReason": "Bad drives"
}

```

Response Structure

1378: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Mon, 10 Dec 2018 18:08:44 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳LS1jCo5eMVKxmeYDol0I2LgLYazocSggR5hynNoLcPmMov9u2s3ulksPdQtG1N3aS+VM9tdMsCrahFPra
Content-Length: 158

{ "alerts": [
  {
    "level": "success",
    "text": "Updated status [ ADMIN_DOWN ] for quest.infra.ciab.
    ↳test [ admin: Bad drives ] and queued updates on all child caches"
  }
]}
```

service_categories

GET

Get all requested *Service Categories*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 559: Request Query Parameters

Name	Description
name	Filter for <i>Service Categories</i> with this name
orderby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

1379: Request Example

```
GET /api/4.0/service_categories?name=SERVICE_CATEGORY_NAME HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

name This *Service Category*’s name

lastUpdated The date and time at which this *Service Category* was last modified, in *Traffic Ops’s Custom Date/Time Format*

1380: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Yzr6TfhxgpZ3pbrrr4TRG4wC3PlnHDDzgs2igtz/
  ↳1ppLSy2MzugqaGW4y5yzwzl5T3+7q6HWej7GQZt1XIVeZQ==
X-Server-Name: traffic_ops_golang/
```

(continues on next page)

(continued from previous page)

Date: Wed, 11 Mar 2020 20:02:47 GMT

Content-Length: 102

```
{
  "response": [
    {
      "lastUpdated": "2020-03-04 15:46:20-07",
      "name": "SERVICE_CATEGORY_NAME"
    }
  ]
}
```

POST

Create a new service category.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

name This *Service Category*’s name

1381: Request Example

```
POST /api/4.0/service_categories HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 48
Content-Type: application/json

{
  "name": "SERVICE_CATEGORY_NAME",
}
```

Response Structure

name This *Service Category*'s name

lastUpdated The date and time at which this *Service Category* was last modified,
in *Traffic Ops's Custom Date/Time Format*

1382: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: +pJm4c30+JTaSXNt+LP+u240Ba/
→SsvSSDQ4rDc6hcyZ0FIL+iY/WWrMHhpLulRGKGY88bM4YPCMaxGn3FZ9yQ==
X-Server-Name: traffic_ops_golang/
Date: Wed, 11 Mar 2020 20:12:20 GMT
Content-Length: 154

{
  "alerts": [
    {
      "text": "serviceCategory was created.",
      "level": "success"
    }
  ],
  "response": {
```

(continues on next page)

(continued from previous page)

```

    "lastUpdated": "2020-03-11 14:12:20-06",
    "name": "SERVICE_CATEGORY_NAME"
  }
}

```

DELETE

Deletes a specific *Service Category*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

1383: Request Example

```

DELETE /api/4.0/service_categories/my-service-category HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0

```

Response Structure

1384: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 17 Aug 2020 16:13:31.
↪GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: yErJobzG9IA0khvqZQK+Yi7X4pFVv0qxn6PjrdzN5DnKVm/
↪K8Kka3REul1XmKJnMXVRY8RayoEVGDm16mBF4Q==
X-Server-Name: traffic_ops_golang/

```

(continues on next page)

(continued from previous page)

Date: Mon, 17 Aug 2020 15:13:31 GMT

Content-Length: 93

```
{
  "alerts": [
    {
      "text": "serviceCategory was deleted.",
      "level": "success"
    }
  ]
}
```

snapshot

PUT

Performs a CDN *Snapshot*. Effectively, this propagates the new *configuration* of the CDN to its *operating state*, which replaces the output of the `cdns/{name}/snapshot` endpoint with the output of the `cdns/{name}/snapshot/new` endpoint. This also changes the output of the `cdns/{name}/configs/monitoring` endpoint since that endpoint returns the latest monitoring information from the *operating state*.

Note: Snapshotting the CDN also deletes all HTTPS certificates for every *Delivery Service* which has been deleted since the last *Snapshot*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 560: Request Query Parameters

Name	Description
cdn	The name of the CDN for which a <i>Snapshot</i> shall be taken
cdnID	The id of the CDN for which a <i>Snapshot</i> shall be taken

Note: At least one query parameter must be given.

1385: Request Example

```
PUT /api/4.0/snapshot?cdn=CDN-in-a-Box HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1386: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳gmaWI0tKgNFPY00zMrLCGDosBJkPbeIvW4BH9tEh96VjBqyWqzjgPySoMa3ViM1BQXA6VAUOGmc76VyhB
X-Server-Name: traffic_ops_golang/
Date: Wed, 18 Mar 2020 15:51:48 GMT
Content-Length: 47

{
  "response": "SUCCESS"
}
```

staticdnsentries

GET

Retrieve all static DNS entries configured within Traffic Control

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 561: Request Query Parameters

Name	Re- quired	Description
ad- dress	no	Return only static DNS entries that operate on this address/CNAME
cachegroup	no	Return only static DNS entries assigned to the <i>Cache Group</i> that has this <i>Name</i>
cachegroupId	no	Return only static DNS entries assigned to the <i>Cache Group</i> that has this <i>ID</i>
deliv- ery- ser- vice	no	Return only static DNS entries that apply within the domain of the <i>Delivery Service</i> with this <i>xml_id</i>
deliv- ery- servi- ceId	no	Return only static DNS entries that apply within the domain of the <i>Delivery Service</i> identified by this integral, unique identifier
host	no	Return only static DNS entries that resolve this FQDN
id	no	Return only the static DNS entry with this integral, unique identifier
ttl	no	Return only static DNS entries with this TTL
type	no	Return only static DNS entries of this type
typeId	no	Return only static DNS entries of the type identified by this integral, unique identifier
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1387: Request Example

```
GET /api/4.0/staticdnsentries?address=foo.bar HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

address If `typeId` identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which `host` shall be resolved

cachegroup An optional string containing the *Name of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryservice The name of a *Delivery Service* under the domain of which this static DNS entry shall be active

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If `typeId` identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the Fully Qualified Domain Name (FQDN) which shall resolve to `address`

id An integral, unique identifier for this static DNS entry

ttd The TTL of this static DNS entry in seconds

type The name of the type of this static DNS entry

typeId The integral, unique identifier of the *Type* of this static DNS entry

1388: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Px1zTH3ihg+hfmADGcap0Juuud39fGsX5Y3CzqaFNmRwFu1ZLMz0sy0EN2pb7vp0tpI6/
    ↳zeIUYAC3dbSbw0mA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:04:33 GMT
Content-Length: 226

{ "response": [
  {
    "address": "foo.bar.",
    "cachegroup": null,
    "cachegroupId": null,
    "deliveryservice": "demo1",
    "deliveryserviceId": 1,
    "host": "test",
    "id": 2,
    "lastUpdated": "2018-12-10 19:59:56+00",
    "ttl": 300,
    "type": "CNAME_RECORD",
    "typeId": 41
  }
]}

```

POST

Creates a new, static DNS entry.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

address If `typeId` identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which `host` shall be resolved

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If `typeId` identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the FQDN which shall resolve to `address`

ttl The TTL of this static DNS entry in seconds

typeId The integral, unique identifier of the *Type* of this static DNS entry

1389: Request Example

```
POST /api/4.0/staticdnsentries HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 92
Content-Type: application/json

{
  "address": "test.quest.",
  "deliveryserviceId": 1,
  "host": "test",
  "ttl": 300,
  "typeId": 41
}
```

Response Structure

address If `typeId` identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which `host` shall be resolved

cachegroup An optional string containing the *Name of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryservice The name of a *Delivery Service* under the domain of which this static DNS entry shall be active

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If `typeId` identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the Fully Qualified Domain Name (FQDN) which shall resolve to `address`

id An integral, unique identifier for this static DNS entry

ttl The TTL of this static DNS entry in seconds

type The name of the *Type* of this static DNS entry

typeId The integral, unique identifier of the *Type* of this static DNS entry

1390: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 8dcJyjw2NJZx0L90z16P7g/
→7j5A1jlpYiY6Y+rRVQ2wGcwYI3yiGPrz6ur0qKzgqEBBsh8aPF44WTHAR9jUJdg==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 19:54:19 GMT
Content-Length: 282

{ "alerts": [
  {
    "text": "staticDNSEntry was created.",
    "level": "success"
  }
],
"response": {
  "address": "test.quest.",
  "cachegroup": null,
  "cachegroupId": null,
  "deliveryservice": null,
  "deliveryserviceId": 1,
  "host": "test",
  "id": 2,
  "lastUpdated": "2018-12-10 19:54:19+00",
  "ttl": 300,
  "type": "CNAME_RECORD",
  "typeId": 41
}}
```

PUT

Updates a static DNS entry.

Auth. Required Yes

Role(s) Required “admin” or “operator”

Response Type Object

Request Structure

Table 562: Request Query Parameters

Name	Description
id	The integral, unique identifier of the static DNS entry to modify

address If typeId identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which host shall be resolved

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

deliveryserviceId The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active

host If typeId identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the Fully Qualified Domain Name (FQDN) which shall resolve to address

ttd The TTL of this static DNS entry in seconds

typeId The integral, unique identifier of the *Type* of this static DNS entry

1391: Request Example

```
PUT /api/4.0/staticdnsentries?id=2 HTTP/1.1
```

```
Host: trafficops.infra.ciab.test
```

```
User-Agent: curl/7.47.0
```

```
Accept: */*
```

```
Cookie: mojolicious=...
```

```
Content-Length: 89
```

```
Content-Type: application/json
```

```
{
  "address": "foo.bar.",
  "deliveryserviceId": 1,
  "host": "test",
  "ttl": 300,
  "typeId": 41
}
```

Response Structure

address If typeId identifies a CNAME type record, this is the Canonical Name (CNAME) of the server with a trailing period, otherwise it is the IP address to which host shall be resolved

cachegroup An optional string containing the *Name of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

cachegroupId An optional, integer that is the *ID of a Cache Group* which will service this static DNS entry

Note: This field has no effect, and is not used by any part of Traffic Control. It exists for legacy compatibility reasons.

- deliveryservice** The name of a *Delivery Service* under the domain of which this static DNS entry shall be active
- deliveryserviceId** The integral, unique identifier of a *Delivery Service* under the domain of which this static DNS entry shall be active
- host** If typeId identifies a CNAME type record, this is an alias for the CNAME of the server, otherwise it is the FQDN which shall resolve to address
- id** An integral, unique identifier for this static DNS entry
- ttl** The TTL of this static DNS entry in seconds
- type** The name of the *Type* of this static DNS entry
- typeId** The integral, unique identifier of the *Type* of this static DNS entry

1392: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳+FaYmpnlIIzVSBq0nosw29NZcV9xFhlVgWuUqXUyiDihVUSzX4jrdAlORDgzDvKsYQB8LSkPdGHwt1zjg
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 19:59:56 GMT
Content-Length: 279

{ "alerts": [
  {
    "text": "staticDNSEntry was updated.",
    "level": "success"
  }
],
"response": {
  "address": "foo.bar.",
  "cachegroup": null,
  "cachegroupId": null,
  "deliveryservice": null,
  "deliveryserviceId": 1,
```

(continues on next page)

(continued from previous page)

```
"host": "test",
"id": 2,
"lastUpdated": "2018-12-10 19:59:56+00",
"ttl": 300,
"type": "CNAME_RECORD",
"typeId": 41
}}
```

DELETE

Delete staticdnsentries.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 563: Request Query Parameters

Name	Description
id	The integral, unique identifier of the static DNS entry to delete

1393: Request Example

```
DELETE /api/4.0/staticdnsentries?id=2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1394: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→g6uqHPU44LuTtqU2ahtazrVCpcpNWVc9kWJQ0YRuiVLDnsm39KOB/xt3XM6j0/
→X3WYiIawnNspkxRC85LJHwFA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:05:52 GMT
Content-Length: 69

{ "alerts": [
  {
    "text": "staticDNSEntry was deleted.",
    "level": "success"
  }
]}

```

stats_summary

GET

Either retrieve a list of summary stats or the timestamp of the latest recorded stats summary.

What is returned is driven by the query parameter `lastSummaryDate`.

If the parameter is set it will return an object with the latest timestamp, else an array of summary stats will be returned.

Auth. Required Yes

Roles Required None

Response Type Array or Object

Request Structure

Summary Stats

Table 564: Request Query Parameters

Name	Required	Description
deliveryServiceName	no	Return only summary stats that were reported for <i>Delivery Service</i> with the given display name
cdnName	no	Return only summary stats that were reported for CDN with the given name
statName	no	Return only summary stats that were reported for given stat name
orderBy	no	Choose the ordering of the results - can only be one of deliveryServiceName, statName or cdnName
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the n^{th} page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1395: Request Example

```
GET /api/4.0/stats_summary HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Last Updated Summary Stat

Table 565: Request Query Parameters

Name	Required	Description
statName	no	Get latest updated date for the given stat
lastSummaryDate	yes	Tells route to get only latest updated timestamp

1396: Request Example

```
GET /api/4.0/stats_summary?lastSummaryDate=true HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

Summary Stats

cdnName The CDN name for which the summary stat was taken for

Note: If the `cdn` is equal to `all` it represents `summary_stats` across all delivery services across all CDNs

deliveryServiceName The *Delivery Service* display name for which the summary stat was taken for

Note: If the `deliveryServiceName` is equal to `all` it represents `summary_stats` across all delivery services within the given CDN

statName Stat name summary stat represents

statValue Summary stat value

summaryTime Timestamp of summary, in *Traffic Ops's Custom Date/Time Format*

statDate Date stat was taken, in YYYY-MM-DD format

1397: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dHNip9kpTGGS1w39/fWcFehNktgmXZus8XaufnmDpv0PyG/
→3fK/KfoC03Z0j9V74/CCffps7doEygWeL/xRtKA==
```

(continues on next page)

(continued from previous page)

```
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:56:59 GMT
Content-Length: 150

{ "response": [
  {
    "cdnName": "CDN-in-a-Box",
    "deliveryServiceName": "all",
    "statName": "daily_maxgbps",
    "statValue": 5,
    "summaryTime": "2019-11-19 00:04:06+00",
    "statDate": "2019-11-19"
  },
  {
    "cdnName": "CDN-in-a-Box",
    "deliveryServiceName": "all",
    "statName": "daily_maxgbps",
    "statValue": 3,
    "summaryTime": "2019-11-18 00:04:06+00",
    "statDate": "2019-11-18"
  },
  {
    "cdnName": "CDN-in-a-Box",
    "deliveryServiceName": "all",
    "statName": "daily_bytesserved",
    "statValue": 1000,
    "summaryTime": "2019-11-19 00:04:06+00",
    "statDate": "2019-11-19"
  }
]}

```

Last Updated Summary Stat

summaryTime Timestamp of the last updated summary, in *Traffic Ops's Custom Date/Time Format*

1398: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json

```

(continues on next page)

(continued from previous page)

```
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dHNip9kpTGGS1w39/fWcFehNktgmXZus8XaufnmDpv0PyG/
→3fK/KfoC03Z0j9V74/CCffps7doEygWeL/xRtKA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:56:59 GMT
Content-Length: 150

{ "response": {
  "summaryTime": "2019-11-19 00:04:06+00"
}}
```

POST

Post a stats summary for a given stat.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

cdnName The CDN name for which the summary stat was taken for

Note: If the `cdn` is equal to `all` it represents `summary_stats` across all delivery services across all CDNs

deliveryServiceName The *Delivery Service* display name for which the summary stat was taken for

Note: If the `deliveryServiceName` is equal to `all` it represents `summary_stats` across all delivery services within the given CDN

statName Stat name summary stat represents

statValue Summary stat value

summaryTime Timestamp of summary, in *Traffic Ops's Custom Date/Time Format*

statDate Date stat was taken, in YYYY-MM-DD format

Note: statName, statValue and summaryTime are required. If cdnName and deliveryServiceName are not given they will default to all.

1399: Request Example

```
POST /api/4.0/stats_summary HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 113
Content-Type: application/json

{
  "cdnName": "CDN-in-a-Box",
  "deliveryServiceName": "all",
  "statName": "daily_maxgbps",
  "statValue": 10,
  "summaryTime": "2019-12-05 00:03:57+00",
  "statDate": "2019-12-05"
}
```

Response Structure

1400: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↳ezxk+iP7o7KE7zpWmGc0j8nz5k+1wAzY0HiNiA2xswTQrt+N+6CgQqUV2r9G1HAsPNr0HF2PhYs/
  ↳Xr7DrY0w0A==
X-Server-Name: traffic_ops_golang/
Date: Thu, 06 Dec 2018 02:14:45 GMT
Content-Length: 97

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

    "text": "Stats Summary was successfully created",
    "level": "success"
  }
}
```

statuses

GET

Retrieves a list of all server *Statuses*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 566: Request Query Parameters

Name	Re- quired	Description
de- scrip- tion	no	Return only <i>Statuses</i> with this <i>exact</i> description
id	no	Return only the <i>Status</i> with this integral, unique identifier
name	no	Return only <i>Statuses</i> with this name
or- derby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
off- set	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the <i>n</i> th page of results, where “ <i>n</i> ” is the value of this parameter, pages are <i>limit</i> long and the first page is 1. If <i>offset</i> was defined, this query parameter has no effect. <i>limit</i> must be defined to make use of <i>page</i> .

1401: Request Example

```

GET /api/4.0/statuses?name=REPORTED HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- description** A short description of the status
- id** The integral, unique identifier of this status
- lastUpdated** The date and time at which this status was last modified, in *Traffic Ops's Custom Date/Time Format*
- name** The name of the status

1402: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: dHNip9kpTGGS1w39/fWcFehNktgmXZus8XaufnmDpv0PyG/
    ↳3fK/KfoC03Z0j9V74/CCffps7doEygWeL/xRtKA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 20:56:59 GMT
Content-Length: 150

{ "response": [
  {
    "description": "Server is online and reported in the health
    ↳protocol.",
    "id": 3,
    "lastUpdated": "2018-12-10 19:11:17+00",
    "name": "REPORTED"
  }
]}
```

steering

GET

Gets a list of all *Steering Targets* in the Traffic Ops database.

Auth. Required Yes

Roles Required “Portal”, “Steering”, “Federation”, “operations” or “admin”

Response Type Array

Request Structure

No parameters available.

1403: Request Example

```
GET /api/4.0/steering HTTP/1.1
User-Agent: python-requests/2.22.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

deliveryService A string that is the *xml_id* of the steering *Delivery Service*

clientSteering Whether this is a *client steering* Delivery Service.

targets The delivery services that the :ref:Steering Delivery Service <tr-steering>` targets.

order If this is a *STEERING_ORDER* target, this is the value of the order. Otherwise, 0.

weight If this is a *STEERING_WEIGHT* target, this is the value of the weight. Otherwise, 0.

deliveryService A string that is the *xml_id* of the steering *Delivery Service*

filters Filters of type *STEERING_REGEXP* that exist on either of the targets.

deliveryService A string that is the *xml_id* of the steering *Delivery Service*

pattern A regular expression - the use of this pattern is dependent on the *type* field (backslashes are escaped)

1404: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 24 Feb 2020 18:56:57
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳hcJa4xVLDx7bxBmoSjYo5YUwdSBWQr9GqlqRYrc6ZU7LeenjiV3go22YlIHt/
    ↳GtjLcHQjJ5DulKRhdsvFMq7Fng==
X-Server-Name: traffic_ops_golang/
Date: Mon, 24 Feb 2020 17:56:57 GMT
Content-Length: 167
```

```
{
  "response": [
    {
      "deliveryService": "steering1",
      "clientSteering": true,
      "targets": [
        {
          "order": 0,
          "weight": 1,
          "deliveryService": "demo1"
        },
        {
          "order": 0,
          "weight": 2,
          "deliveryService": "demo2"
        }
      ],
      "filters": [
        {
          "deliveryService": "demo1",
          "pattern": ".*\\.demo1\\.\\.*"
        },
        {
          "deliveryService": "demo2",
          "pattern": ".*\\.demo2\\.\\.*"
        }
      ]
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```
]
}
```

steering/{ID}/targets

GET

Get all targets for a steering *Delivery Service*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 567: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i> for which targets shall be listed

Table 568: Request Query Parameters

Name	Description
target	Return only the target mappings that target the <i>Delivery Service</i> identified by this integral, unique identifier
orderby	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

1405: Request Structure

```
GET /api/4.0/steering/2/targets?target=1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- deliveryService** A string that is the *xml_id* of the steering *Delivery Service*
- deliveryServiceId** An integral, unique identifier for the steering *Delivery Service*
- target** A string that is the *xml_id* of this target *Delivery Service*
- targetId** An integral, unique identifier for this target *Delivery Service*
- type** The steering type of this target *Delivery Service*. This should be one of STEERING_WEIGHT, STEERING_ORDER, STEERING_GEO_ORDER or STEERING_GEO_WEIGHT
- typeId** An integral, unique identifier for the *steering type* of this target *Delivery Service*
- value** The ‘weight’, ‘order’, ‘geo_order’ or ‘geo_weight’ attributed to this steering target as an integer

1406: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳utlJK4oYS2l6Ff7NzAqRuQeMEtaZyn3rM3Nlux2XgTLxvSyslHy0mJrwDExSU05gVMdrgYCLZrZEvPHlE
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 14:09:23 GMT
Content-Length: 130

{ "response": [
  {
    "deliveryService": "test",
    "deliveryServiceId": 2,
    "target": "demo1",
    "targetId": 1,
    "type": "STEERING_ORDER",
    "typeId": 44,
```

(continues on next page)

(continued from previous page)

```

    "value": 100
  }
}]

```

POST

Create a steering target.

Auth. Required Yes

Roles Required Portal, Steering, Federation, “operations” or “admin”

Response Type Object

Request Structure

Table 569: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i> to which a target shall be added

targetId The integral, unique identifier of a *Delivery Service* which shall be a new steering target for the *Delivery Service* identified by the ID path parameter

typeId The integral, unique identifier of the steering type of the new target *Delivery Service*. This should be corresponding to one of STEERING_WEIGHT, STEERING_ORDER, STEERING_GEO_ORDER or STEERING_GEO_WEIGHT

value The ‘weight’, ‘order’, ‘geo_order’ or ‘geo_weight’ which shall be attributed to the new target *Delivery Service*

1407: Request Example

```

POST /api/4.0/steering/2/targets HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 43
Content-Type: application/json

{
  "targetId": 1,
  "value": 100,
  "typeId": 43
}

```

Response Structure

- deliveryService** A string that is the *xml_id* of the steering *Delivery Service*
- deliveryServiceId** An integral, unique identifier for the steering *Delivery Service*
- target** A string that is the *xml_id* of this target *Delivery Service*
- targetId** An integral, unique identifier for this target *Delivery Service*
- type** The steering type of this target *Delivery Service*. This should be one of STEERING_WEIGHT, STEERING_ORDER, STEERING_GEO_ORDER or STEERING_GEO_WEIGHT
- typeId** An integral, unique identifier for the *steering type* of this target *Delivery Service*
- value** The ‘weight’, ‘order’, ‘geo_order’ or ‘geo_weight’ attributed to this steering target as an integer

1408: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳+dTvfzrnOhdWAOMmY28r0+gFV5z+3aABI2FfAMziTYcU+pZrDanrJzMXpKWIL5Q/
    ↳oCUBZpJDRt9hRCFkT4oGYw==
X-Server-Name: traffic_ops_golang/
Date: Mon, 10 Dec 2018 21:22:17 GMT
Content-Length: 196

{ "alerts": [
  {
    "text": "steeringtarget was created.",
    "level": "success"
  }
],
"response": {
  "deliveryService": "test",
  "deliveryServiceId": 2,
  "target": "demo1",
  "targetId": 1,
  "type": "HTTP",

```

(continues on next page)

(continued from previous page)

```
"typeId": 1,
"value": 100
}}
```

steering/{{ID}}/targets/{{targetID}}

PUT

Updates a steering target.

Auth. Required Yes

Roles Required Portal, Steering, Federation, “operations” or “admin”

Response Type Object

Request Structure

Table 570: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i>
targetID	The integral, unique identifier of a <i>Delivery Service</i> which is a target of the <i>Delivery Service</i> identified by ID

typeId The integral, unique identifier of the *steering type* of the target *Delivery Service*. This should be corresponding to one of STEERING_WEIGHT, STEERING_ORDER, STEERING_GEO_ORDER or STEERING_GEO_WEIGHT

value The ‘weight’, ‘order’, ‘geo_order’ or ‘geo_weight’ which shall be attributed to the target *Delivery Service*

1409: Request Example

```
PUT /api/4.0/steering/2/targets/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 26
Content-Type: application/json

{
  "value": 1,
  "typeId": 43
}
```

Response Structure

- deliveryService** A string that is the *xml_id* of the steering *Delivery Service*
- deliveryServiceId** An integral, unique identifier for the steering *Delivery Service*
- target** A string that is the *xml_id* of this target *Delivery Service*
- targetId** An integral, unique identifier for this target *Delivery Service*
- type** The steering type of this target *Delivery Service*
- typeId** An integral, unique identifier for the *steering type* of this target *Delivery Service*
- value** The ‘weight’ attributed to this steering target as an integer

1410: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
→AfXsIRzdtU3HZYkr93qBMVTZRJ5oTF2u5sKYnd+DSqxZ+RQxY6vXtCupnnXCf9dxMt5QXRW1EFOW/
→FBG6lFrTg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 14:34:22 GMT
Content-Length: 194

{ "alerts": [
  {
    "text": "steeringtarget was updated.",
    "level": "success"
  }
],
"response": {
  "deliveryService": "test",
  "deliveryServiceId": 2,
  "target": "demo1",
  "targetId": 1,
  "type": "HTTP",
  "typeId": 1,
  "value": 1
}}
```

DELETE

Removes a specific target mapping from a specific *Delivery Service*

Auth. Required Yes

Roles Required Portal, Steering, Federation, “operations” or “admin”

Response Type undefined

Request Structure

Table 571: Request Path Parameters

Name	Description
ID	The integral, unique identifier of a steering <i>Delivery Service</i> - a target of which shall be deleted
targetID	The integral, unique identifier of a <i>Delivery Service</i> which is a target to be removed of the <i>Delivery Service</i> identified by ID

1411: Request Example

```
DELETE /api/4.0/steering/2/targets/1 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1412: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳N6h8Kl7uQveqpTc3fmKXFDY2yYe5smApNcaTow4ab0DHGFdJfqQh89I4nvvaXvmVNhxVAqX3UE/
    ↳6blb08/9Xqg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 14:42:54 GMT
```

(continues on next page)

(continued from previous page)

Content-Length: 69

```
{ "alerts": [
  {
    "text": "steeringtarget was deleted.",
    "level": "success"
  }
]}
```

system/info

GET

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

parameters An object containing information about the Traffic Ops server

Note: These are all the *Parameters* in *The GLOBAL Profile*, so the keys below are merely those present by default required for Traffic Control to operate

default_geo_miss_latitude The default latitude used when geographic lookup of an IP address fails

default_geo_miss_longitude The default longitude used when geographic lookup of an IP address fails

tm.instance_name The name of the Traffic Ops instance; typically used when multiple instances are active

tm.toolname The name of the Traffic Ops tool (usually “Traffic Ops”) - used in several API endpoints and written in comment headers on most Apache Traffic Server (ATS) configuration files generated by Traffic Ops

tm.url The URL for this Traffic Ops instance) - used in several API endpoints and written in comment headers on most Apache Traffic Server (ATS) configuration files generated by Traffic Ops

use_reval_pending A string containing an integer which represents a boolean value (hold your applause); one of:

“0” Do not use pending revalidations - this effectively prohibits the use of “Content Invalidation Jobs”

“1” Use pending revalidations - this effectively enables the use of “Content Invalidation Jobs”

1413: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ObxOXk1jrC1/
→JtrqElUICceyx9iJKJxZydEIHvAU7khTTQwt0QGvS04ELDkdrbu3ctFo3pf3NAMaMM9tAkNokg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 19:06:01 GMT
Content-Length: 285

{ "response": {
  "parameters": {
    "default_geo_miss_latitude": "0",
    "default_geo_miss_longitude": "-1",
    "tm.instance_name": "CDN-In-A-Box",
    "tm.toolname": "Traffic Ops",
    "tm.url": "https://trafficops.infra.ciab.test:443/",
    "use_reval_pending": "0"
  }
}}
```

tenants

GET

Get all requested *Tenants*.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 572: Request Query Parameters

Name	Description
ac- tive	If <code>true</code> , return only active <i>Tenants</i> ; if <code>false</code> return only inactive <i>Tenants</i>
id	Return only <i>Tenants</i> with this integral, unique identifier
name	Return only <i>Tenants</i> with this name
or- derby	Choose the ordering of the results - must be the name of one of the fields of the objects in the <code>response</code> array
sortOrder	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	Choose the maximum number of results to return
offset	The number of results to skip before beginning to return results. Must use in conjunction with <code>limit</code>
page	Return the n^{th} page of results, where “n” is the value of this parameter, pages are <code>limit</code> long and the first page is 1. If <code>offset</code> was defined, this query parameter has no effect. <code>limit</code> must be defined to make use of <code>page</code> .

1414: Request Example

```
GET /api/4.0/tenants?name=root HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

active A boolean which indicates whether or not the *Tenant* is active

id The integral, unique identifier of this *Tenant*

name This *Tenant*'s name

parentId The integral, unique identifier of this *Tenant*'s parent

parentName The name of the parent of this *Tenant*

1415: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: Yzr6TfhxgpZ3pbbr4TRG4wC3PlnHDDzgs2igtz/
  ↳1ppLSy2MzugqaGW4y5yzwzl5T3+7q6HWej7GQZt1XIVeZQ==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 19:57:58 GMT
Content-Length: 106

{ "response": [
  {
    "id": 1,
    "name": "root",
    "active": true,
    "lastUpdated": "2018-12-10 19:11:17+00",
    "parentId": null
  }
]}
```

POST

Create a new tenant.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

active An optional boolean - default: false - which indicates whether or not the tenant shall be immediately active

name The name of the tenant

parentId The integral, unique identifier of the parent of this tenant

1416: Request Example

```
POST /api/4.0/tenants HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 48
Content-Type: application/json

{
  "active": true,
  "name": "test",
  "parentId": 1
}
```

Response Structure

active A boolean which indicates whether or not the tenant is active

id The integral, unique identifier of this tenant

name This tenant’s name

parentId The integral, unique identifier of this tenant’s parent

1417: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept, Set-Cookie, Cookie (continues on next page)
```


(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ysdopC//
→JQI79BRUa61s6M2HzHxYHpo5Rdcuau0oqCYxiV0oUhNZfOVydVkv8zDN2qA374XKnym4kWj3VzQIXg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 19:37:16 GMT
Content-Length: 162

{ "alerts": [
  {
    "text": "tenant was created.",
    "level": "success"
  }
],
"response": {
  "id": 9,
  "name": "test",
  "active": true,
  "lastUpdated": "2018-12-11 19:37:16+00",
  "parentId": 1
}}
```

`tenants/{ID}`

PUT

Updates a specific tenant.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 573: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the tenant being modified

active An optional boolean - default: `false` - which indicates whether or not the tenant shall be immediately active

name The name of the tenant

parentId The integral, unique identifier of the parent of this tenant

1418: Request Example

```
PUT /api/4.0/tenants/9 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 59
Content-Type: application/json

{
  "active": true,
  "name": "quest",
  "parentId": 3
}
```

Response Structure

active A boolean which indicates whether or not the tenant is active

id The integral, unique identifier of this tenant

name This tenant's name

parentId The integral, unique identifier of this tenant's parent

1419: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: 5soYQFrG2x5ZJ1e5UZIOLUv/
→928qyd2Bfgw21Wv85rqjLpyeT3djkrVD1/xpKConulNrZs2czJKrrwZA7X61w==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 20:30:54 GMT
Content-Length: 163

{ "alerts": [
  {
```

(continues on next page)

(continued from previous page)

```

        "text": "tenant was updated.",
        "level": "success"
    }
],
"response": {
    "id": 9,
    "name": "quest",
    "active": true,
    "lastUpdated": "2018-12-11 20:30:54+00",
    "parentId": 3
}}

```

DELETE

Deletes a specific tenant.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 574: Request Path Parameters

Name	Description
ID	The integral, unique identifier for the tenant being deleted

1420: Request Example

```
DELETE /api/4.0/tenants/9 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

1421: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: KU0XIbFoD0Cy06kzH2Gl59pBqie/
    ↳TEFJgh33mssGNwXJZlRkTLaSTHT8Df4X+pOs7UauZH10akGvaA0UTiN/vg==
X-Server-Name: traffic_ops_golang/
Date: Tue, 11 Dec 2018 20:40:31 GMT
Content-Length: 61

{ "alerts": [
  {
    "text": "tenant was deleted.",
    "level": "success"
  }
]}
```

topologies

GET

Retrieves *Topologies*.

Auth. Required Yes

Roles Required “read-only”

Response Type Array

Request Structure

Table 575: Request Query Parameters

Name	Required	Description
name	no	Return the <i>Topology</i> with this name

1422: Request Example

```
GET /api/4.0/topologies HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
```

Response Structure

description A short sentence that describes the *Topology*.

lastUpdated The date and time at which this *Topology* was last updated, in ISO-like format

name The name of the *Topology*. This can only be letters, numbers, and dashes.

nodes An array of nodes in the *Topology*

cachegroup The name of a *Cache Group*

parents The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

1423: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 13 Apr 2020 18:22:32
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳1F4MCJCinuQWz0f1LAAZBrzbuPVsHrNn2BtTozRZojEjGpm76IsXBQK5Q0wSwBoHac+D0C1Z3p7M8kdjc
X-Server-Name: traffic_ops_golang/
Date: Mon, 13 Apr 2020 17:22:32 GMT
```

(continues on next page)

(continued from previous page)

Content-Length: 205

```
{
  "response": [
    {
      "description": "This is my topology",
      "name": "my-topology",
      "nodes": [
        {
          "cachegroup": "edge1",
          "parents": [
            7
          ]
        },
        {
          "cachegroup": "edge2",
          "parents": [
            7,
            8
          ]
        },
        {
          "cachegroup": "edge3",
          "parents": [
            8,
            9
          ]
        },
        {
          "cachegroup": "edge4",
          "parents": [
            9
          ]
        },
        {
          "cachegroup": "mid1",
          "parents": []
        },
        {
          "cachegroup": "mid2",
          "parents": [
            4
          ]
        },
        {
          "cachegroup": "mid3",
```

(continues on next page)

(continued from previous page)

```

        "parents": [
            4
        ]
    },
    {
        "cachegroup": "mid4",
        "parents": [
            5
        ]
    },
    {
        "cachegroup": "mid5",
        "parents": [
            5,
            6
        ]
    },
    {
        "cachegroup": "mid6",
        "parents": [
            6
        ]
    }
],
"lastUpdated": "2020-04-13 17:12:34+00"
}
]
}

```

POST

Create a new *Topology*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

description A short sentence that describes the topology.

name The name of the topology. This can only be letters, numbers, and dashes.

nodes An array of nodes in the *Topology*

cachegroup The name of a *Cache Group* with at least 1 server in it

parents The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

1424: Request Example

```
POST /api/4.0/topologies HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 924
Content-Type: application/json

{
  "name": "my-topology",
  "description": "This is my topology",
  "nodes": [
    {
      "cachegroup": "edge1",
      "parents": [
        7
      ]
    },
    {
      "cachegroup": "edge2",
      "parents": [
        7,
        8
      ]
    },
    {
      "cachegroup": "edge3",
      "parents": [
        8,
        9
      ]
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```
{
  "cachegroup": "edge4",
  "parents": [
    9
  ]
},
{
  "cachegroup": "mid1",
  "parents": []
},
{
  "cachegroup": "mid2",
  "parents": [
    4
  ]
},
{
  "cachegroup": "mid3",
  "parents": [
    4
  ]
},
{
  "cachegroup": "mid4",
  "parents": [
    5
  ]
},
{
  "cachegroup": "mid5",
  "parents": [
    5,
    6
  ]
},
{
  "cachegroup": "mid6",
  "parents": [
    6
  ]
}
]
```

Response Structure

- description** A short sentence that describes the topology.
- lastUpdated** The date and time at which this *Topology* was last updated, in ISO-like format
- name** The name of the topology. This can only be letters, numbers, and dashes.
- nodes** An array of nodes in the *Topology*
 - cachegroup** The name of a *Cache Group*
 - parents** The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

1425: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 13 Apr 2020 18:12:34.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: ftNcDRjYCDMkQM+o/
→szayKZriQZHGpcT0vNY0HpKgy88i0pXeEEeLGbUPh6LXtK7TvL76EgGECTzvCkcm+2LVA==
X-Server-Name: traffic_ops_golang/
Date: Mon, 13 Apr 2020 17:12:34 GMT
Content-Length: 239

{
  "alerts": [
    {
      "text": "topology was created.",
      "level": "success"
    }
  ],
  "response": {
    "description": "This is my topology",
    "name": "my-topology",
    "nodes": [
      {
        "cachegroup": "edge1",
        "parents": [
          7
        ]
      }
    ]
  }
}
```

(continues on next page)

(continued from previous page)

```

    },
    {
      "cachegroup": "edge2",
      "parents": [
        7,
        8
      ]
    },
    {
      "cachegroup": "edge3",
      "parents": [
        8,
        9
      ]
    },
    {
      "cachegroup": "edge4",
      "parents": [
        9
      ]
    },
    {
      "cachegroup": "mid1",
      "parents": []
    },
    {
      "cachegroup": "mid2",
      "parents": [
        4
      ]
    },
    {
      "cachegroup": "mid3",
      "parents": [
        4
      ]
    },
    {
      "cachegroup": "mid4",
      "parents": [
        5
      ]
    },
    {
      "cachegroup": "mid5",
      "parents": [

```

(continues on next page)

(continued from previous page)

```

        5,
        6
    ]
},
{
    "cachegroup": "mid6",
    "parents": [
        6
    ]
},
],
"lastUpdated": "2020-04-13 17:12:34+00"
}
}

```

PUT

Updates a specific *Topology*

Request Structure

Table 576: Request Query Parameters

Name	Required	Description
name	yes	The name of the <i>Topology</i> to be updated

description A short sentence that describes the *Topology*.

name The name of the *Topology*. This can only be letters, numbers, and dashes.

nodes An array of nodes in the *Topology*

cachegroup The name of a *Cache Group* with at least 1 server in it

parents The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

1426: Request Example

```

PUT /api/4.0/topologies?name=my-topology HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...

```

(continues on next page)

(continued from previous page)

```
Content-Length: 853
Content-Type: application/json

{
  "name": "my-topology",
  "description": "The description is updated, too",
  "nodes": [
    {
      "cachegroup": "edge1",
      "parents": [
        6
      ]
    },
    {
      "cachegroup": "edge2",
      "parents": [
        6,
        7
      ]
    },
    {
      "cachegroup": "edge3",
      "parents": [
        7,
        8
      ]
    },
    {
      "cachegroup": "edge4",
      "parents": [
        8
      ]
    },
    {
      "cachegroup": "mid2",
      "parents": []
    },
    {
      "cachegroup": "mid3",
      "parents": []
    },
    {
      "cachegroup": "mid4",
      "parents": [
        4
      ]
    }
  ]
}
```

(continues on next page)

(continued from previous page)

```

    },
    {
      "cachegroup": "mid5",
      "parents": [
        4,
        5
      ]
    },
    {
      "cachegroup": "mid6",
      "parents": [
        5
      ]
    }
  ]
}

```

Response Structure

description A short sentence that describes the *Topology*.

lastUpdated The date and time at which this *Topology* was last updated, in ISO-like format

name The name of the *Topology*. This can only be letters, numbers, and dashes.

nodes An array of nodes in the *Topology*

cachegroup The name of a *Cache Group*

parents The indices of the parents of this node in the nodes array, 0-indexed. 2 parents max

1427: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 13 Apr 2020 18:33:13.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: WV0tsoOVrEWcVjWM2TmT5DXy/
→a5Q0ygTZEQRhbKHHUmz9dgVLK1F5Joc9jtKA8gZu8/eM5+Tqqguh3mzrhAy/Q==
X-Server-Name: traffic_ops_golang/

```

(continues on next page)

(continued from previous page)

Date: Mon, 13 Apr 2020 17:33:13 GMT

Content-Length: 237

```
{
  "alerts": [
    {
      "text": "topology was updated.",
      "level": "success"
    }
  ],
  "response": {
    "description": "The description is updated, too",
    "name": "my-topology",
    "nodes": [
      {
        "cachegroup": "edge1",
        "parents": [
          6
        ]
      },
      {
        "cachegroup": "edge2",
        "parents": [
          6,
          7
        ]
      },
      {
        "cachegroup": "edge3",
        "parents": [
          7,
          8
        ]
      },
      {
        "cachegroup": "edge4",
        "parents": [
          8
        ]
      },
      {
        "cachegroup": "mid2",
        "parents": []
      },
      {
        "cachegroup": "mid3",
```

(continues on next page)

(continued from previous page)

```

        "parents": []
    },
    {
        "cachegroup": "mid4",
        "parents": [
            4
        ]
    },
    {
        "cachegroup": "mid5",
        "parents": [
            4,
            5
        ]
    },
    {
        "cachegroup": "mid6",
        "parents": [
            5
        ]
    }
],
"lastUpdated": "2020-04-13 17:33:13+00"
}

```

DELETE

Deletes a specific *Topology*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

Table 577: Request Query Parameters

Name	Required	Description
name	yes	The name of the <i>Topology</i> to be deleted

1428: Request Example

```
DELETE /api/4.0/topologies?name=my-topology HTTP/1.1
User-Agent: python-requests/2.23.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

1429: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 13 Apr 2020 18:35:32
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: yErJobzG9IA0khvqZQK+Yi7X4pFVvOqxn6PjrdzN5DnKVm/
→K8Kka3REul1XmKJnMXVRY8RayoEVDm16mBFfe4Q==
X-Server-Name: traffic_ops_golang/
Date: Mon, 13 Apr 2020 17:35:32 GMT
Content-Length: 87

{
  "alerts": [
    {
      "text": "topology was deleted.",
      "level": "success"
    }
  ]
}
```

`topologies/{{name}}/queue_update`

POST

Queue or “dequeue” updates for all servers assigned to the *Cache Groups* in a specific *Topology*.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 578: Request Path Parameters

Name	Description
name	The name of the <i>Topology</i> on which to queue or dequeue updates.

action One of “queue” or “dequeue” as appropriate

cdnId The integral, unique identifier for the CDN on which to (de)queue updates

1430: Request Example

```
POST /api/4.0/topologies/demo1-top/queue_update HTTP/1.1
User-Agent: python-requests/2.24.0
Accept-Encoding: gzip, deflate
Accept: */*
Connection: keep-alive
Cookie: mojolicious=...
Content-Length: 28

{
  "action": "queue",
  "cdnId": 1
}
```

Response Structure

action The action processed, either “queue” or “dequeue”

cdnId The CDN ID on which *Queue Updates* was performed or cleared

topology The name of the *Topology* on which *Queue Updates* was performed or cleared

1431: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Encoding: gzip
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 08 Sep 2020 17:35:42
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
    ↳nmu3TMVmlcHeEstLuiqPsEypNV2jcs5PyrqsqJKkexxb8N7qk84AWzTJWUpsfdVWrj/
    ↳JzRiCPGJS4hw0phQ==
X-Server-Name: traffic_ops_golang/
Date: Tue, 08 Sep 2020 16:35:42 GMT
Content-Length: 79

{
  "response": {
    "action": "queue",
    "cdnId": 1,
    "topology": "demo1-top"
  }
}
```

types

GET

Retrieves all of the *Types* of things configured in Traffic Ops. Yes, that is as specific as a description of a ‘type’ can be.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 579: Request Query Parameters

Name	Re-quired	Description
id	no	Return only the type that is identified by this integral, unique identifier
name	no	Return only types with this name
useInTable	no	Return only types that are used to identify the type of the object stored in the Traffic Ops database table that has this name

1432: Request Structure

```
GET /api/4.0/types?name=TC_LOC HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- description** A short description of this type
- id** An integral, unique identifier for this type
- lastUpdated** The date and time at which this type was last updated, in *Traffic Ops's Custom Date/Time Format*
- name** The name of this type
- useInTable** The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type

1433: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
    ↳p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 12 Dec 2018 22:59:22 GMT
```

(continues on next page)

(continued from previous page)

Content-Length: 168

```
{ "response": [
  {
    "id": 48,
    "lastUpdated": "2018-12-12 16:26:41+00",
    "name": "TC_LOC",
    "description": "Location for Traffic Control Component Servers",
    "useInTable": "cachegroup"
  }
]}
```

POST

Creates a type

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

description A short description of this type

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type.

Note: The only useInTable value that is allowed to be created dynamically is ‘server’

1434: Request Structure

```
POST /api/4.0/type HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 67
Content-Type: application/json
```

(continues on next page)

(continued from previous page)

```
{
  "name": "Example01",
  "description": "Example",
  "useInTable": "server"
}
```

Response Structure

description A short description of this type

id An integral, unique identifier for this type

lastUpdated The date and time at which this type was last updated, in *Traffic Ops's Custom Date/Time Format*

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type

1435: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
  ↳p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 Feb 2020 18:58:41 GMT
Content-Length: 171

{
  "alerts": [
    {
      "text": "type was created.",
      "level": "success"
    }
  ],
  "response": [
    {
      "id": 3004,
      "lastUpdated": "2020-02-26 18:58:41+00",
```

(continues on next page)

(continued from previous page)

```

    "name": "Example01",
    "description": "Example"
    "useInTable": "server"
  }]
}
```

types/{{ID}}

PUT

Updates a type

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 580: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the type being updated

description A short description of this type

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type.

Note: Only types with useInTable set to ‘server’ are allowed to be updated.

1436: Request Structure

```

PUT /api/4.0/type/3004 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 68
Content-Type: application/json

{
```

(continues on next page)

(continued from previous page)

```
"name": "Example01",
"description": "Example2",
"useInTable": "server"
}
```

Response Structure

description A short description of this type

id An integral, unique identifier for this type

lastUpdated The date and time at which this type was last updated, in *Traffic Ops's Custom Date/Time Format*

name The name of this type

useInTable The name of the Traffic Ops database table that contains objects which are grouped, identified, or described by this type

1437: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo8OrCu79Tz9xpgT3YRyKJ/
→p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 Feb 2020 18:58:41 GMT
Content-Length: 172

{
  "alerts": [
    {
      "text": "type was updated.",
      "level": "success"
    }
  ],
  "response": [
    {
      "id": 3004,
      "lastUpdated": "2020-02-26 18:58:41+00",
      "name": "Example02",
```

(continues on next page)

(continued from previous page)

```

    "description": "Example"
    "useInTable": "server"
  }
}
```

DELETE

Deletes a type

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 581: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the type being deleted

Note: Only types with useInTable set to “server” are allowed to be deleted.

1438: Request Structure

```

DELETE /api/4.0/type/3004 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 0
```

Response Structure

1439: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: EH8jo80rCu79Tz9xpgT3YRyKJ/
→p2NcTmbS3huwtqRByHz9H6qZLQjA59RIPaVSq3ZxsU6QhTaox5nBkQ9LPSAA==
X-Server-Name: traffic_ops_golang/
Date: Wed, 26 Feb 2020 18:58:41 GMT
Content-Length: 84
```

```
{
  "alerts": [
    {
      "text": "type was deleted.",
      "level": "success"
    }
  ],
}
```

user/current

GET

Caution: As a username is needed to log in, any administrator or application must necessarily know the current username at any given time. Thus it's generally better to use the username query parameter of a GET request to *users* instead.

Retrieves the details of the authenticated user.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

No parameters available.

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user
- id** An integral, unique identifier for this user
- lastAuthenticated** The date and time at which the user was last authenticated, in **RFC 3339**
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege *Role* assigned to this user
- rolename** The name of the highest-privilege *Role* assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the *Tenant* to which this user belongs
- tenantId** The integral, unique identifier of the *Tenant* to which this user belongs
- uid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user
- username** The user's username

1440: Response Example

```

HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳HQwu9FxFyinxSVFK5+wpEhSxU60KbqXuokFbMZ30oerOoM5ZpWpglsHz7mRch8VAw0dzwsJzpPJivj07R
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 15:14:45 GMT
Content-Length: 382

{ "response": {
    "username": "admin",
    "localUser": true,
    "addressLine1": null,
    "addressLine2": null,
    "city": null,
    "company": null,
    "country": null,
    "email": null,
    "fullName": "admin",
    "gid": null,
    "id": 2,
    "newUser": false,
    "phoneNumber": null,
    "postalCode": null,
    "publicSshKey": null,
    "role": 1,
    "rolename": "admin",
    "stateOrProvince": null,
    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "lastUpdated": "2018-12-12 16:26:32+00",
    "lastAuthenticated": "2021-07-09T14:44:10.371708-06:00"
}}
```

PUT

Warning: Assuming the current user’s integral, unique identifier is known, it’s generally better to use the PUT method of the [users](#) instead.

Warning: Users that login via LDAP pass-back cannot be modified

Updates the date for the authenticated user.

Auth. Required Yes

Roles Required None

Response Type Object

Request Structure

user The entire request must be inside a top-level “user” key for legacy reasons

addressLine1 The user’s address - including street name and number

addressLine2 An additional address field for e.g. apartment number

city The name of the city wherein the user resides

company The name of the company for which the user works

confirmLocalPasswd An optional ‘confirm’ field in a new user’s password specification. This has no known effect and in fact *doesn’t even need to match localPasswd*

country The name of the country wherein the user resides

email The user’s email address - cannot be an empty string¹. The given email is validated (circuitously) by [GitHub user asaskevich’s regular expression](#) . Note that it can’t actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user’s full name, e.g. “John Quincy Adams”

gid A legacy field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - please don’t use this

¹ This field cannot be null.

id The user's integral, unique, identifier - this cannot be changed^{Page 1929, 1}

localPasswd Optionally, the user's password. This should never be given if it will not be changed. An empty string or null can be used to explicitly specify no change.

phoneNumber The user's phone number

postalCode The user's postal code

publicSshKey The user's public encryption key used for the SSH protocol

role The integral, unique identifier of the highest permission *Role* which will be permitted to the user - this cannot be altered from the user's current *Role*^{Page 1929, 1}

stateOrProvince The state or province in which the user resides

tenantId The integral, unique identifier of the *Tenant* to which the new user shall belong^{2Page 1929, 1}

uid A legacy field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - please don't use this

username The user's new username^{Page 1929, 1}

1441: Request Example

```
PUT /api/4.0/user/current HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 465
Content-Type: application/json

{ "user": {
  "addressLine1": null,
  "addressLine2": null,
  "city": null,
  "company": null,
  "country": null,
  "email": "admin@infra.trafficops.ciab.test",
  "fullName": "admin",
  "gid": null,
  "id": 2,
  "phoneNumber": null,
```

(continues on next page)

² This endpoint respects tenancy; a user cannot assign itself to a *Tenant* that is not the same *Tenant* to which it was previously assigned or a descendant thereof.

(continued from previous page)

```

"postalCode": null,
"publicSshKey": null,
"role": 1,
"stateOrProvince": null,
"tenantId": 1,
"uid": null,
"username": "admin"
}}
```

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address validated (circuitously) by [GitHub user asaskevich's regular expression](#) . Note that it can't actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A legacy field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the [users/register](#) endpoint, this will be the date and time at which the registration email was sent - otherwise it will be null
- role** The integral, unique identifier of the highest-privilege *Role* assigned to this user
- rolename** The name of the highest-privilege *Role* assigned to this user
- stateOrProvince** The name of the state or province where this user resides

- tenant** The name of the *Tenant* to which this user belongs
- tenantId** The integral, unique identifier of the *Tenant* to which this user belongs
- uid** A legacy field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user
- username** The user's username

1442: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Date: Thu, 13 Dec 2018 21:05:49 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: sHFqZQ4Cv7IIWaIejoAvM2Fr/HSupcX3D16KU/
    ↳etjw+4jcK9EME3Bq5ohLC+eQ52BDCKW2Ra+AC3TfFtworJww==
Content-Length: 478

{ "alerts": [
  {
    "text": "User profile was successfully updated",
    "level": "success"
  }
],
"response": {
  "addressLine1": null,
  "addressLine2": null,
  "city": null,
  "company": null,
  "country": null,
  "email": "admin@infra.trafficops.ciab.test",
  "fullName": null,
  "gid": null,
  "id": 2,
  "lastUpdated": "2019-10-08 20:14:25+00",
  "newUser": false,
  "phoneNumber": null,
  "postalCode": null,
  "publicSshKey": null,
  "registrationSent": null,
```

(continues on next page)

(continued from previous page)

```

    "role": 1,
    "roleName": "admin",
    "stateOrProvince": null,
    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "username": "admin"
  }}

```

user/login

POST

Authentication of a user using username and password. Traffic Ops will send back a session cookie.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

p Password

u Username

1443: Request Example

```

POST /api/4.0/user/login HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 26
Content-Type: application/json

{
  "u": "admin",
  "p": "twelve"
}

```

Response Structure

1444: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳Ud06T3tMNctnVusDXzRjVwwYOnD7jmnBzPEB9PvOt2bHajTv3SKTPiIZjDzvU6EX4p+JoG4fA5wlhgxp
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 15:21:33 GMT
Content-Length: 65

{ "alerts": [
  {
    "text": "Successfully logged in.",
    "level": "success"
  }
]}
```

user/login/oauth

POST

Authentication of a user by exchanging a code for an encrypted JSON Web Token from an OAuth service. Traffic Ops will POST to the `authCodeTokenUrl` to exchange the code for an encrypted JSON Web Token. It will then decode and validate the token, validate the key set domain, and send back a session cookie.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

authCodeTokenUrl URL for code-to-token conversion

code Code

clientId Client Id

redirectUri Redirect URI

1445: Request Example

```
POST /api/4.0/user/login/oauth HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 26
Content-Type: application/json

{
  "authCodeTokenUrl": "https://url-to-convert-code-to-token.example.
  ↪com",
  "code": "AbCd123",
  "clientId": "oauthClientId",
  "redirectUri": "https://traffic-portal.example.com/sso"
}
```

Response Structure

1446: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
  ↪Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
  ↪GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
  ↪Ud06T3tMNctnVusDXzRjVwwYOnD7jmnBzPEB9PvOt2bHajTv3SKTPiIZjDzvhU6EX4p+JoG4fA5wlhgxp
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 15:21:33 GMT
Content-Length: 65

{ "alerts": [
```

(continues on next page)

(continued from previous page)

```
{
  "text": "Successfully logged in.",
  "level": "success"
}
[]}
```

user/login/token

POST

Authentication of a user using a token. Normally, the token is obtained via a call to either *user/reset_password* or *users/register*.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

t A UUID generated for the user.

Implementation Detail

Though not strictly necessary for authentication provided direct database access, the tokens generated for use with this endpoint are compliant with [RFC 4122](#).

1447: Request Example

```
POST /api/4.0/user/login/token HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 44
Content-Type: application/json

{
  "t": "18EE200C-FF24-11E8-BF01-870C776752A3"
}
```

Response Structure

1448: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512: FuS3TkVosxHtpxRGMJ2on+WnFdYTNSPjxz/Gh1iT4UCJ2/
    ↳P0twUbAGQ3tTx9EfGiAzg9CNQiVUFGnYjJZ6NCpg==
X-Server-Name: traffic_ops_golang/
Date: Fri, 20 Sep 2019 15:02:43 GMT
Content-Length: 66

{ "alerts": [
  {
    "text": "Successfully logged in.",
    "level": "success"
  }
]}
```

user/logout

POST

User logout. Invalidates the session cookie of the currently logged-in user.

Auth. Required Yes

Roles Required None

Response Type undefined

Request Structure

No parameters available

Response Structure

1449: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 21:25:36 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: 6KEdr1ZC512zk0l03KwvQE0L7qrJ/
    ↳+ek6ztymkYy9p8gdPUyYyzGEAJ/Ldb8GY0UBFYmgqeZ3yWHvTcEsOQMiw==
Content-Length: 61

{ "alerts": [
  {
    "level": "success",
    "text": "You are logged out."
  }
]}
```

user/reset_password

POST

Sends an email to reset a user's password.

Auth. Required No

Roles Required None

Response Type undefined

Request Structure

email The email address of the user to initiate password reset

1450: Request Example

```
POST /api/4.0/user/reset_password HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 35
Content-Type: application/json

{
  "email": "test@example.com"
}
```

Response Structure

1451: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 22:11:53 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→lKWwVYbgKklk7bljnQJZwWV5bljIk+GkooD6SAC3CSexVKvfbL9dgL5iBc/
→BNNRk2pIU5I/1GglcdLrXsF1ZA==
Content-Length: 109

{ "alerts": [
  {
    "level": "success",
    "text": "Successfully sent password reset to email
→'test@example.com'"
  }
]
```

(continues on next page)

(continued from previous page)

```
  ]}
```

users

GET

Retrieves all requested users.

Auth. Required Yes

Roles Required None¹

Response Type Array

Request Structure

Table 582: Request Query Parameters

Name	Re-quired	Description
id	no	Return only the user identified by this integral, unique identifier
tenant	no	Return only users belonging to the <i>Tenant</i> identified by tenant name
role	no	Return only users belonging to the <i>Role</i> identified by role name
username	no	Return only the user with this username
orderby	no	Choose the ordering of the results - must be the name of one of the fields of the objects in the response array
sortOrder	no	Changes the order of sorting. Either ascending (default or “asc”) or descending (“desc”)
limit	no	Choose the maximum number of results to return
offset	no	The number of results to skip before beginning to return results. Must use in conjunction with limit
page	no	Return the ⁿ th page of results, where “n” is the value of this parameter, pages are limit long and the first page is 1. If offset was defined, this query parameter has no effect. limit must be defined to make use of page.

1452: Request Example

```
GET /api/4.0/users?username=admin HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
```

(continues on next page)

¹ While no roles are required, this endpoint does respect tenancy. A user will only be able to see, create, delete or modify other users belonging to the same tenant, or its descendants.

(continued from previous page)

```
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- changeLogCount** The number of change log entries created by the user
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`
- id** An integral, unique identifier for this user
- lastAuthenticated** The date and time at which the user was last authenticated, in **RFC 3339**
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege role assigned to this user
- rolename** The name of the highest-privilege role assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the tenant to which this user belongs
- tenantId** The integral, unique identifier of the tenant to which this user belongs

uid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always `null`

username The user's username

1453: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳YBJLN8NbOxOvECe1RGtcwCzIPDhyhLpW56nTJHQM5WI2WUDe2mAKREpaEE72nZrfBliq1GABwJlSxq2Odl
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 01:03:53 GMT
Content-Length: 391

{ "response": [
  {
    "username": "admin",
    "registrationSent": null,
    "addressLine1": null,
    "addressLine2": null,
    "city": null,
    "company": null,
    "country": null,
    "email": null,
    "fullName": null,
    "gid": null,
    "id": 2,
    "newUser": false,
    "phoneNumber": null,
    "postalCode": null,
    "publicSshKey": null,
    "role": 1,
    "rolename": "admin",
    "stateOrProvince": null,
    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "lastUpdated": "2018-12-12 16:26:32+00",
    "changeLogCount": 20,
    "lastAuthenticated": "2021-07-09T14:44:10.371708-06:00"
```

(continues on next page)

(continued from previous page)

```
}
[]}
```

POST

Creates a new user.

Auth. Required Yes

Roles Required “admin” or “operations”^{Page 2040, 1}

Response Type Object

Request Structure

addressLine1 An optional field which should contain the user’s address - including street name and number

addressLine2 An optional field which should contain an additional address field for e.g. apartment number

city An optional field which should contain the name of the city wherein the user resides

company An optional field which should contain the name of the company for which the user works

confirmLocalPasswd The ‘confirm’ field in a new user’s password specification - must match localPasswd

country An optional field which should contain the name of the country wherein the user resides

email The user’s email address The given email is validated (circuitously) by [GitHub user asaskevich’s regular expression](#) . Note that it can’t actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user’s full name, e.g. “John Quincy Adams”

localPasswd The user’s password

newUser An optional meta field with no apparent purpose - don’t use this

phoneNumber An optional field which should contain the user’s phone number

postalCode An optional field which should contain the user’s postal code

publicSshKey An optional field which should contain the user’s public encryption key used for the SSH protocol

role The number that corresponds to the highest permission role which will be permitted to the user

stateOrProvince An optional field which should contain the name of the state or province in which the user resides

tenantId The integral, unique identifier of the tenant to which the new user shall belong

Note: This field is optional if and only if tenancy is not enabled in Traffic Control

username The new user's username

1454: Request Example

```
POST /api/4.0/users HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 304
Content-Type: application/json

{
  "username": "mike",
  "addressLine1": "22 Mike Wazowski You've Got Your Life Back Lane",
  "city": "Monstropolis",
  "company": "Monsters Inc.",
  "email": "mwazowski@minc.biz",
  "fullName": "Mike Wazowski",
  "localPasswd": "BFFsully",
  "confirmLocalPasswd": "BFFsully",
  "newUser": true,
  "role": 1,
  "tenantId": 1
}
```

Response Structure

addressLine1 The user's address - including street name and number

addressLine2 An additional address field for e.g. apartment number

city The name of the city wherein the user resides

company The name of the company for which the user works

country The name of the country wherein the user resides

- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege role assigned to this user
- roleName** The name of the highest-privilege role assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the tenant to which this user belongs
- tenantId** The integral, unique identifier of the tenant to which this user belongs
- uid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always `null`
- username** The user's username

1455: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
➔Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 02:28:27 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
➔GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
```

(continues on next page)

(continued from previous page)

```
Whole-Content-Sha512:↵
↵vDqbaMvgeeoIds1czqvIWlyDG8WLnCCJdF14Ub05nsE+oJOakkyeZ8odf4d0Zjtqpk01hoVo14H2tjuWPo
Content-Length: 520

{ "alerts": [
  {
    "level": "success",
    "text": "User creation was successful."
  }
],
"response": {
  "registrationSent": null,
  "email": "mwazowski@minc.biz",
  "tenantId": 1,
  "city": "Monstropolis",
  "tenant": "root",
  "id": 8,
  "company": null,
  "roleName": "admin",
  "phoneNumber": null,
  "country": null,
  "fullName": "Mike Wazowski",
  "publicSshKey": null,
  "uid": null,
  "stateOrProvince": null,
  "lastUpdated": null,
  "username": "mike",
  "newUser": false,
  "addressLine2": null,
  "role": 1,
  "addressLine1": "22 Mike Wazowski You've Got Your Life Back Lane",
  "postalCode": null,
  "gid": null
}}
```

users/{{ID}}

GET

Retrieves a specific user.

Auth. Required Yes

Roles Required None

Response Type Array

Request Structure

Table 583: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the user to be retrieved

1456: Request Example

```
GET /api/4.0/users/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
```

Response Structure

- addressLine1** The user’s address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user’s email address
- fullName** The user’s full name, e.g. “John Quincy Adams”
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`
- id** An integral, unique identifier for this user
- lastAuthenticated** The date and time at which the user was last authenticated, in **RFC 3339**
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops’s Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user’s phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user’s public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`

role The integral, unique identifier of the highest-privilege role assigned to this user

rolename The name of the highest-privilege role assigned to this user

stateOrProvince The name of the state or province where this user resides

tenant The name of the tenant to which this user belongs

tenantId The integral, unique identifier of the tenant to which this user belongs

uid A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always null

username The user's username

1457: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳9vqUmt8fWEuDb+9LQJ4sGbbF4Z0a7uNyBNSWhyzAi3fBUZ5mGhd4Jx5IuSlEqiLZnYeViJJL8mpRortkH
X-Server-Name: traffic_ops_golang/
Date: Thu, 13 Dec 2018 17:46:00 GMT
Content-Length: 588

{ "response": [
  {
    "username": "admin",
    "registrationSent": null,
    "addressLine1": "not a real address",
    "addressLine2": "not a real address either",
    "city": "not a real city",
    "company": "not a real company",
    "country": "not a real country",
    "email": "not@real.email",
    "fullName": "Not a real Full Name",
    "gid": null,
    "id": 2,
    "newUser": false,
    "phoneNumber": "not a real phone number",
    "postalCode": "not a real postal code",
    "publicSshKey": "not a real ssh key",
    "role": 1,
```

(continues on next page)

(continued from previous page)

```

    "rolename": "admin",
    "stateOrProvince": "not a real state or province",
    "tenant": "root",
    "tenantId": 1,
    "uid": null,
    "lastUpdated": "2018-12-13 17:24:23+00",
    "lastAuthenticated": "2021-07-09T14:44:10.371708-06:00"
  }
}]

```

PUT

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type Object

Request Structure

Table 584: Request Path Parameters

Name	Description
ID	The integral, unique identifier of the user to be modified

addressLine1 An optional field which should contain the user’s address - including street name and number

addressLine2 An optional field which should contain an additional address field for e.g. apartment number

city An optional field which should contain the name of the city wherein the user resides

company An optional field which should contain the name of the company for which the user works

confirmLocalPasswd The ‘confirm’ field in a new user’s password specification - must match localPasswd

country An optional field which should contain the name of the country wherein the user resides

email The user’s email address The given email is validated (circuitously) by [GitHub user asaskevich’s regular expression](#) . Note that it can’t actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

fullName The user’s full name, e.g. “John Quincy Adams”

localPasswd The user's password

newUser An optional meta field with no apparent purpose - don't use this

phoneNumber An optional field which should contain the user's phone number

postalCode An optional field which should contain the user's postal code

publicSshKey An optional field which should contain the user's public encryption key used for the SSH protocol

role The number that corresponds to the highest permission role which will be permitted to the user

stateOrProvince An optional field which should contain the name of the state or province in which the user resides

tenantId The integral, unique identifier of the tenant to which the new user shall belong

Note: This field is optional if and only if tenancy is not enabled in Traffic Control

username The new user's username

1458: Request Structure

```
PUT /api/4.0/users/2 HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 458
Content-Type: application/json

{
  "addressLine1": "not a real address",
  "addressLine2": "not a real address either",
  "city": "not a real city",
  "company": "not a real company",
  "country": "not a real country",
  "email": "not@real.email",
  "fullName": "Not a real fullName",
  "phoneNumber": "not a real phone number",
  "postalCode": "not a real postal code",
  "publicSshKey": "not a real ssh key",
  "stateOrProvince": "not a real state or province",
  "tenantId": 1,
  "role": 1,
  "username": "admin"
}
```

Response Structure

- addressLine1** The user's address - including street name and number
- addressLine2** An additional address field for e.g. apartment number
- city** The name of the city wherein the user resides
- company** The name of the company for which the user works
- country** The name of the country wherein the user resides
- email** The user's email address
- fullName** The user's full name, e.g. "John Quincy Adams"
- gid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX group ID of the user - now it is always `null`
- id** An integral, unique identifier for this user
- lastUpdated** The date and time at which the user was last modified, in *Traffic Ops's Custom Date/Time Format*
- newUser** A meta field with no apparent purpose that is usually `null` unless explicitly set during creation or modification of a user via some API endpoint
- phoneNumber** The user's phone number
- postalCode** The postal code of the area in which the user resides
- publicSshKey** The user's public key used for the SSH protocol
- registrationSent** If the user was created using the *users/register* endpoint, this will be the date and time at which the registration email was sent - otherwise it will be `null`
- role** The integral, unique identifier of the highest-privilege role assigned to this user
- roleName** The name of the highest-privilege role assigned to this user
- stateOrProvince** The name of the state or province where this user resides
- tenant** The name of the tenant to which this user belongs
- tenantId** The integral, unique identifier of the tenant to which this user belongs
- uid** A deprecated field only kept for legacy compatibility reasons that used to contain the UNIX user ID of the user - now it is always `null`
- username** The user's username

1459: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
↪Accept
```

(continues on next page)

(continued from previous page)

```
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 17:24:23 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512: QKvGSIwSdreMI/OdgWv9WQfI/
→C1JbXSoQGospTGfCVUJ32XNWMhmREGzWojWsilW8os8b14TGYeyMLUWunf2Ug==
Content-Length: 661

{ "alerts": [
  {
    "level": "success",
    "text": "User update was successful."
  }
],
"response": {
  "registrationSent": null,
  "email": "not@real.email",
  "tenantId": 1,
  "city": "not a real city",
  "tenant": "root",
  "id": 2,
  "company": "not a real company",
  "roleName": "admin",
  "phoneNumber": "not a real phone number",
  "country": "not a real country",
  "fullName": "Not a real Full Name",
  "publicSshKey": "not a real ssh key",
  "uid": null,
  "stateOrProvince": "not a real state or province",
  "lastUpdated": "2018-12-12 16:26:32.821187+00",
  "username": "admin",
  "newUser": false,
  "addressLine2": "not a real address either",
  "role": 1,
  "addressLine1": "not a real address",
  "postalCode": "not a real postal code",
  "gid": null
}}
```

users/register

POST

Register a user and send registration email.

Auth. Required Yes

Roles Required “admin” or “operations”

Response Type undefined

Request Structure

email Email address of the new user The given email is validated (circuitously) by [GitHub user asaskevich’s regular expression](#) . Note that it can’t actually distinguish a valid, deliverable, email address but merely ensure the email is in a commonly-found format.

role The integral, unique identifier of the highest permissions *Role* which will be afforded to the new user. It restricts the allowed values to identifiers for *Roles* with at most the same permissions level as the requesting user.

tenantId A field containing the integral, unique identifier of the *Tenant* to which the new user will belong. It restricts the allowed values to identifiers for *Tenants* within the requesting user’s *Tenant*’s permissions.

1460: Request Example

```
POST /api/4.0/users/register HTTP/1.1
Host: trafficops.infra.ciab.test
User-Agent: curl/7.47.0
Accept: */*
Cookie: mojolicious=...
Content-Length: 59
Content-Type: application/json

{
  "email": "test@example.com",
  "role": 3,
  "tenantId": 1
}
```

Response Structure

1461: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
→Accept
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Content-Type: application/json
Date: Thu, 13 Dec 2018 22:03:22 GMT
X-Server-Name: traffic_ops_golang/
Set-Cookie: mojolicious=...; Path=/; Expires=Mon, 18 Nov 2019 17:40:54.
→GMT; Max-Age=3600; HttpOnly
Vary: Accept-Encoding
Whole-Content-Sha512:
→yvf++0qxvu3u0IAYbWLUgJKxZ4T60Mi5H9eGTxrKLxnRsHw0PdDIrThbTnWtATBkak4vU/
→dPHLLXKW85LUTEWg==
Content-Length: 160

{ "alerts": [
  {
    "level": "success",
    "text": "Sent user registration to test@example.com with the
→following permissions [ role: read-only | tenant: root ]"
  }
]}
```

vault/ping

GET

Pings Traffic Vault to retrieve status.

Auth. Required Yes

Roles Required “read-only”

Response Type Object

Request Structure

No parameters available.

Response Properties

status The status returned from the ping request to the Traffic Vault server

server The Traffic Vault server that was pinged

1462: Response Example

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Origin, X-Requested-With, Content-Type,
    ↳Accept, Set-Cookie, Cookie
Access-Control-Allow-Methods: POST,GET,OPTIONS,PUT,DELETE
Access-Control-Allow-Origin: *
Content-Type: application/json
Set-Cookie: mojolicious=...; Path=/; Expires=Tue, 25 Feb 2020 15:37:54
    ↳GMT; Max-Age=3600; HttpOnly
Whole-Content-Sha512:
    ↳z9P1NkxGebPncUhaChDHtYKYI+XVZfhE6Y84TuwoASZFIMfISELwADLpvpPTN+wnzBfREksLYn+0313Q
X-Server-Name: traffic_ops_golang/
Date: Tue, 25 Feb 2020 14:37:55 GMT
Content-Length: 90

{ "response":
  {
    "status": "OK",
    "server": "trafficvault.infra.ciab.test:8087"
  }
}
```


A living list of tools for testing, interacting with, and developing for the Traffic Control CDN

6.1 Tools

This is a living list of tools used to interact with, test, and develop for the Traffic Control CDN.

6.1.1 `atstccfg`

`atstccfg` is a tool for generating configuration files server-side on ATC cache servers.

Warning: **`atstccfg`** does not have a stable command-line interface, it can and will change without warning. Scripts should avoid calling it for the time being, as its only intended caller is *ORT*.

The source code for **`atstccfg`** may be found in `traffic_ops/ort/atstccfg`, and the Go module reference is github.com/apache/trafficcontrol/traffic_ops/ort/atstccfg.

Usage

- `atstccfg -h`
- `atstccfg -v`
- `atstccfg -l`
- `atstccfg [-e ERROR_LOCATION] [-i INFO_LOCATION] [-p] [-P TO_PASSWORD] [-r N] [-s] [-t TIMEOUT] [-u TO_URL] [-U TO_USER] [-w WARNING_LOCATION] [-y] [--dir TSROOT] -n CACHE_NAME`
- `atstccfg [-e ERROR_LOCATION] [-i INFO_LOCATION] [-p] [-P TO_PASSWORD] [-r N] [-s] [-t TIMEOUT] [-u TO_URL] [-U TO_USER] [-w WARNING_LOCATION] [--dir TSROOT] -n CACHE_NAME -d DATA`

- `atstccfg [-e ERROR_LOCATION] [-i INFO_LOCATION] [-p] [-P TO_PASSWORD] [-r N] [-s] [-t TIMEOUT] [-u TO_URL] [-U TO_USER] [-w WARNING_LOCATION] [--dir TSROOT] -n CACHE_NAME -a REVAL_STATUS -q QUEUE_STATUS`

When called using the fourth form, **atstccfg** provides its normal output. This is the entirety of all configuration files necessary for the server, all provided at once. The output is in *mixed/multipart* format, defined by **RFC 1521**. Each chunk of the message comes with the proprietary Path header, which specifies the exact location on disk of the file whose contents are contained in that chunk.

Options

- a REVAL_STATUS, **--set-reval-status** REVAL_STATUS
Sets the `reval_pending` property of the server in Traffic Ops. Must be ‘true’ or ‘false’. Requires **--set-queue-status** also be set. This disables normal output.
- e ERROR_LOCATION, **--log-location-error** ERROR_LOCATION
The file location to which to log errors. Respects the special string constants of github.com/apache/trafficcontrol/lib/go-log. Default: ‘stderr’
- d DATA, **--get-data** DATA
Specifies non-configuration-file data to retrieve from Traffic Ops. This disables normal output. Valid values are:
 - chkconfig** Retrieves information about the services which should be running on the *cache server*. The output will be in JSON-encoded format as an array of objects with these fields:
 - name** The name of the service. This should correspond to an existing systemd service unit file.
 - value** A “chkconfig” line describing on which “run-levels” the services should be running. See the *chkconfig(8)* manual pages for details on what this field means.
 - packages** Retrieves information about the packages which should exist on the *cache server*. The output will be in JSON-encoded format as an array of objects with these fields:
 - name** The name of the package. This should hopefully be a meaningful package name for the *cache server*’s package management system.
 - version** The version of the package which should be installed. This might also be an empty string which means “any version will do”.
 - statuses** Retrieves all statuses from Traffic Ops. This is defined to be exactly the response object from the response to a GET request made to the *statuses* Traffic Ops API endpoint.
 - system-info** Retrieves generic information about the Traffic Control system from the *system/info* API endpoint. The output is the `parameters` object of the responses from GET requests to that endpoint (still JSON-encoded).
 - update-status** Retrieves information about the current update status using *servers/{hostname}/update_status*. The response is in the same format as

the responses for that endpoint's GET method handler - except that that endpoint returns an array and this **atstccfg** call signature returns a single one of those elements. Which one is chosen is arbitrary (hence undefined behavior when more than one server with the same hostname exists).

--dir TSRROOT

Specifies a directory path in which to place Traffic Server configuration files, in the event that "location" *Parameters* are not found for them. If this is not given and location *Parameters* are not found for required files, then **atstccfg** will exit with an error.

The files that **atstccfg** considers "required" for these purposes are:

- cache.config
- hosting.config
- parent.config
- plugin.config
- records.config
- remap.config
- storage.config
- volume.config

-h, --help

Print usage information and exit.

-i INFO_LOCATION, **--log-location-info** INFO_LOCATION

The file location to which to log information messages. Respects the special string constants of github.com/apache/trafficcontrol/lib/go-log. Default: 'stderr'

-l, --list-plugins

List the loaded plug-ins and then exit.

-n NAME, **--cache-host-name** NAME

Required. Specifies the (short) hostname of the *cache server* for which output will be generated. Must be the server hostname in Traffic Ops, not a URL, or FQDN. Behavior when more than one server exists with the passed hostname is undefined.

-p, --traffic-ops-disable-proxy

Bypass the Traffic Ops caching proxy and make requests directly to Traffic Ops. Has no effect if no such proxy exists.

-P TO_PASSWORD, **--traffic-ops-password** TO_PASSWORD

Authenticate using this password - if not given, **atstccfg** will attempt to use the value of the *TO_PASSWORD* environment variable.

-q QUEUE_STATUS, **--set-queue-status** QUEUE_STATUS

Sets the *upd_pending* property of the server identified by *--cache-host-name* to the specified value, which must be 'true' or 'false'. Requires *--set-reval-status* to also be set.

-r N, **--num-retries** N

The number of times to retry getting a file if it fails. Default: 5

-s, --traffic-ops-insecure

If given, SSL certificate errors will be ignored when communicating with Traffic Ops.

Caution: The use of this option in production environments is discouraged.

- t TIMEOUT, --traffic-ops-timeout-milliseconds TIMEOUT**
Sets the timeout - in milliseconds - for requests made to Traffic Ops. Default: 30000
- u TO_URL, --traffic-ops-url TO_URL**
Request this URL, e.g. <https://trafficops.infra.ciab.test/servers/edge/configfiles/ats>. If not given, **atstccfg** will attempt to use the value of the [TO_URL](#) environment variable.
- U TO_USER, --traffic-ops-user TO_USER**
Authenticate as the user TO_USER - if not given, **atstccfg** will attempt to use the value of the [TO_USER](#) environment variable.
- v, --version**
Print version information and exit.
- w WARNING_LOCATION, --log-location-warning WARNING_LOCATION**
The file location to which to log warnings. Respects the special string constants of github.com/apache/trafficcontrol/lib/go-log. Default: 'stderr'
- y, --revalidate-only**
When given, **atstccfg** will only emit files relevant for updating content invalidation jobs. for Apache Traffic Server implementations, this limits the output to be only files named `regex_revalidate.config`. Has no effect if [--get-data](#) or [--set-queue-status/--set-reval-status](#) is/are used.

Environment Variables

atstccfg supports authentication with a Traffic Ops instance using the environment variables [TO_URL](#) (if [-u/--traffic-ops-url](#) is not given), [TO_USER](#) (if [-U/--traffic-ops-user](#) is not given), and [TO_PASSWORD](#) (if [-P/--traffic-ops-password](#) is not given).

6.1.2 Apache-TrafficControl Package

Contributing

When contributing Python code to Apache Traffic Control, please ensure that it passes the provided Pylint configuration file ([traffic_control/clients/python/pylint.rc](#)).

Package Contents

exception `trafficops.InvalidJSONError(*args, resp=None)`

Bases: `ValueError`

An error that occurs when an invalid JSON payload is passed to an endpoint.

resp = None

Contains the response object that generated the error

exception `trafficops.LoginError(*args)`

Bases: `OSError`

This represents an error that occurred during server login.

exception `trafficops.OperationError(*args, resp=None)`

Bases: `OSError`

This class represents a generic error, indicating something went wrong with the request or on the server.

resp = None

Contains the response object that generated the error

class `trafficops.RestApiSession(host_ip, api_version=None, api_base_path='api',
host_port=443, ssl=True, headers=None,
verify_cert=True, create_session=False,
max_retries=5)`

Bases: `object`

This class represents a login session with a generic REST API server. It provides base functionality inherited by [TOSession](#).

property `api_base_url`

Returns the base URL. (read-only)

Returns The base URL should match `'[w+-.]+://[w+-.]+(:d+)?'` e.g.
`'https://to.somedomain.net/api/0.1/'`

Return type `str`

property `api_version`

Returns the api version. (read-only)

Returns The api version from which this instance will request endpoints.

Return type `str`

close()

Close and cleanup the requests Session object.

Returns `None`

Return type `NoneType`

create()

Create the requests.Session to communicate with the RESTful API.

Returns `None`

Return type `NoneType`

delete(*api_path*, *args, **kwargs)

Perform HTTP DELETE requests

Parameters

- **api_path** (*str*) – The path to the API end-point that you want to call which does not include the base URL e.g. `user/login`, `servers`, etc. This string can contain substitution parameters as denoted by a valid `field_name` replacement field specification as per `str.format()` e.g. `cachegroups/{id}` or `cachegroups/{id:d}`
- **kwargs** (*Dict[str, Any]*) – Passed Keyword Parameters. If you need to send JSON data to the endpoint pass the keyword parameter data with the Python data structure. This method will convert it to JSON before sending it to the API endpoint. Use `query_params` to pass a dictionary of query parameters

Returns Python data structure distilled from JSON from the API request.

Return type `Tuple[Union[Dict[str, Any], List[Dict[str, Any]], munch.Munch, List[munch.Munch]], requests.Response]`

Raises `Union[LoginError, OperationError]`

get(*api_path*, *args, **kwargs)

Perform http get requests

Parameters

- **api_path** (*str*) – The path to the API end-point that you want to call which does not include the base url e.g. `user/login`, `servers`, etc. This string can contain substitution parameters as denoted by a valid `field_name` replacement field specification as per `str.format()` e.g. `cachegroups/{id}` or `cachegroups/{id:d}`
- **kwargs** (*Dict[str, Any]*) – Passed Keyword Parameters. If you need to send JSON data to the endpoint pass the keyword parameter data with the Python data structure. This method will convert it to JSON before sending it to the API endpoint. Use `query_params` to pass a dictionary of query parameters

Returns Python data structure distilled from JSON from the API request.

Return type `Tuple[Union[Dict[str, Any], List[Dict[str, Any]], munch.Munch, List[munch.Munch]], requests.Response]`

Raises `Union[LoginError, OperationError]`

head(*api_path*, *args, **kwargs)

Perform HTTP HEAD requests :param `api_path`: The path to the API end-point that you want to call which does not include the base URL e.g. `user/login`, `servers`, etc. This string can contain substitution parameters as denoted by a valid `field_name` replacement field specification as per `str.format()` e.g. `cachegroups/{id}` or `cachegroups/{id:d}` :type `api_path`: `str` :param `kwargs`: Passed Keyword Parameters. If you need to send JSON data to the endpoint pass the keyword param-

eter data with the Python data structure. This method will convert it to JSON before sending it to the API endpoint. Use `query_params` to pass a dictionary of query parameters :type kwargs: Dict[str, Any] :return: Python data structure distilled from JSON from the API request. :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]], munch.Munch, List[munch.Munch]], requests.Response] :raises: Union[LoginError, OperationError]

property is_open

Is the session open to the RESTful API? (Read-only Property)

Returns True if yes, otherwise, False

Return type bool

options(api_path, *args, **kwargs)

Perform HTTP OPTIONS requests :param api_path: The path to the API endpoint that you want to call which does not include the base URL e.g. `user/login`, `servers`, etc. This string can contain substitution parameters as denoted by a valid `field_name` replacement field specification as per `str.format()` e.g. `cachegroups/{id}` or `cachegroups/{id:d}` :type api_path: str :param kwargs: Passed Keyword Parameters. If you need to send JSON data to the endpoint pass the keyword parameter `data` with the Python data structure. This method will convert it to JSON before sending it to the API endpoint. Use `query_params` to pass a dictionary of query parameters :type kwargs: Dict[str, Any] :return: Python data structure distilled from JSON from the API request. :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]], munch.Munch, List[munch.Munch]], requests.Response] :raises: Union[LoginError, OperationError]

patch(api_path, *args, **kwargs)

Perform HTTP PATCH requests :param api_path: The path to the API endpoint that you want to call which does not include the base URL e.g. `user/login`, `servers`, etc. This string can contain substitution parameters as denoted by a valid `field_name` replacement field specification as per `str.format()` e.g. `cachegroups/{id}` or `cachegroups/{id:d}` :type api_path: str :param kwargs: Passed Keyword Parameters. If you need to send JSON data to the endpoint pass the keyword parameter `data` with the Python data structure. This method will convert it to JSON before sending it to the API endpoint. Use `query_params` to pass a dictionary of query parameters :type kwargs: Dict[str, Any] :return: Python data structure distilled from JSON from the API request. :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]], munch.Munch, List[munch.Munch]], requests.Response] :raises: Union[LoginError, OperationError]

post(api_path, *args, **kwargs)

Perform http post requests

Parameters

- **api_path** (*str*) – The path to the API end-point that you want to call which does not include the base URL e.g. `user/login`, `servers`, etc. This string can contain substitution parameters as denoted by a valid `field_name` replacement field specification as per `str.format()` e.g. `cachegroups/{id}` or `cachegroups/{id:d}`
- **kwargs** (*Dict[str, Any]*) – Passed Keyword Parameters

ters. If you need to send JSON data to the endpoint pass the keyword parameter `data` with the Python data structure. This method will convert it to JSON before sending it to the API endpoint. Use `query_params` to pass a dictionary of query parameters

Returns Python data structure distilled from JSON from the API request.

Return type Tuple[Union[Dict[str, Any], List[Dict[str, Any]], munch.Munch, List[munch.Munch]], requests.Response]

Raises Union[LoginError, OperationError]

put(*api_path*, *args, **kwargs)

Perform http put requests

Parameters

- **api_path** (*str*) – The path to the API end-point that you want to call which does not include the base URL e.g. `user/login`, `servers`, etc. This string can contain substitution parameters as denoted by a valid `field_name` replacement field specification as per `str.format()` e.g. `cachegroups/{id}` or `cachegroups/{id:d}`
- **kwargs** (*Dict[str, Any]*) – Passed Keyword Parameters. If you need to send JSON data to the endpoint pass the keyword parameter `data` with the Python data structure. This method will convert it to JSON before sending it to the API endpoint. Use `query_params` to pass a dictionary of query parameters

Returns Python data structure distilled from JSON from the API request.

Return type Tuple[Union[Dict[str, Any], List[Dict[str, Any]], munch.Munch, List[munch.Munch]], requests.Response]

Raises Union[LoginError, OperationError]

property server_url

The URL without the api portion. (read-only)

Returns The URL should match `'[w+-.]+://[w+-.]+(:d+)?'` e.g. `'https://to.somedomain.net'` or `'https://to.somedomain.net:443'`

Return type str

property session

The RESTful API session (Read-only Property)

Returns The requests session

Return type requests.Session

class `trafficops.TOSession`(*host_ip*, *host_port*=443, *api_version*='3.0', *ssl*=True, *headers*=None, *verify_cert*=True)

Bases: `trafficops.restapi.RestApiSession`

Traffic Ops Session Class Once you login to the Traffic Ops API via `login()`, you can call one or more of the methods to retrieve, POST, PUT, DELETE, etc. data to the API. If you are not logged in, an exception will be thrown if you try to call any of the endpoint

methods. This API client is simplistic and lightly structured on purpose but adding support for new endpoints routinely takes seconds. Another nice bit of convenience that result data is, by default, wrapped in `munch.Munch` objects, which provide attribute access to the returned dictionaries/hashtables - e.g. `a_dict['a_key']` with `munch` becomes `a_dict.a_key` or `a_dict['a_key']`. Also, the lack of rigid structure (loose coupling) means many changes to the Traffic Ops API, as it evolves, will probably go un-noticed (usually additions), which means fewer future problems to potentially fix in user applications.

An area of improvement for later is defining classes to represent request data instead of loading up dictionaries for request data.

Please see the [API documentation](#) for the details of the API endpoints.

Adding end-point methods

1463: Endpoint with no URL parameters and no query parameters

```
@api_request('get', 'cdns', ('3.0',))
def get_cdns(self):
    pass
```

1464: End-point with URL parameters and no query parameters

```
@api_request('get', 'cdns/{cdn_id:d}', ('3.0',))
def get_cdn_by_id(self, cdn_id=None):
    pass
```

1465: End-point with no URL parameters but with query parameters

```
@api_request('get', 'deliveryservices', ('3.0',))
def get_deliveryservices(self, query_params=None):
    pass
```

1466: End-point with URL parameters and query parameters

```
@api_request('get', 'deliveryservices/xmlId/{xml_id}/sslkeys', ('3.0',))
def get_deliveryservice_ssl_keys_by_xml_id(self, xml_id=None, query_params=None):
    pass
```

1467: End-point with request data

```
@api_request('post', 'cdns', ('3.0',))
def create_cdn(self, data=None):
    pass
```

1468: End-point with URL parameters and request data

```
@api_request('put', 'cdns', ('3.0',))
def update_cdn_by_id(self, cdn_id=None, data=None):
    pass
```

Calling end-point methods

get_cdns() calls endpoint *cdns* e.g. *t.get_cdns()*

get_types() calls endpoint *types*, optionally with query parameters e.g. *get_foo_data(id=45, query_params={'sort': 'asc'})* calls endpoint GET *api/2.x/foo/45?sort=asc* (presumably)

cdns_queue_update() calls endpoint *cdns/{{ID}}/queue_update*, with an ID path parameter and a JSON payload e.g. *cdns_queue_update(id=1, data={'action': 'queue'})*

Note: Only a small subset of the API endpoints are implemented. More can be implemented as needed.

add_ssl_keys_to_deliveryservice(*data=None*)

Add SSL keys to a Delivery Service. *deliveryservices/sslkeys/add* :param data: The parameter data to use for adding SSL keys to a Delivery Service. :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

assign_delivery_services_to_federations(*federation_id=None, data=None*)

Create one or more federation / delivery service assignments. *federations/{{ID}}/deliveryservices* :param federation_id: The federation id :type federation_id: int :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

assign_deliveryservice_servers_by_ids(*data=None*)

Assign servers by id to a Delivery Service. (New Method) *deliveryserviceserver* :param data: The required data to create server associations to a delivery service :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

assign_deliveryservice_servers_by_names(*xml_id=None, data=None*)

Assign servers by name to a Delivery Service by xmlId. *deliveryservices/{{xml_id}}/servers* :param xml_id: The XML Id of the delivery service :type xml_id: str :param data: The required data to assign servers to a delivery service :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

assign_federation_resolver_to_federations(*federation_id=None*,
data=None)

Create one or more federation / federation resolver assignments. [federations/{{ID}}/federation_resolvers](#) :param federation_id: The federation id :type federation_id: int :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

assign_parameter_to_profile_ids(*data=None*)

Create one or more parameter / profile assignments. [profileparameter](#) :param data: The data to assign :type data: Union[Dict[str, Any], List[Dict[str, Any]]] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

assign_profile_to_parameter_ids(*data=None*)

Create one or more profile / parameter assignments. [profileparameter](#) :param data: The data to assign :type data: Union[Dict[str, Any], List[Dict[str, Any]]] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

associate_paramater_to_profile(*data=None*)

Associate parameter to profile. [profileparameters](#) :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

associate_parameters_by_profile_id(*profile_id=None*, *data=None*)

Associate Parameters to a Profile by Id. [profiles/{{ID}}/parameters](#) :param profile_id: The profile id :type profile_id: int :param data: The parameter data to associate :type data: Union[Dict[str, Any], List[Dict[str, Any]]] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

associate_parameters_by_profile_name(*profile_name=None*, *data=None*)

Associate Parameters to a Profile by Name. [profiles/name/{{name}}/parameters](#) :param profile_name: The profile name :type profile_name: str :param data: The parameter data to associate :type data: Union[Dict[str, Any], List[Dict[str, Any]]] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

property base_url

Returns the base url. (read-only)

Returns The base url should match '[w+-.]+://[w+-.]+(:d+)?' e.g

<https://to.somedomain.net/api/2.0/>

Return type str

cachegroups_queue_update(*cache_group_id=None*, *data=None*)

Queue Updates by Cache Group ID [cachegroups/{{ID}}/queue_update](#) :param cache_group_id: The Cache Group Id :type cache_group_id: int :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

cdns_queue_update(*cdn_id=None*, *data=None*)

Queue Updates by CDN Id. [cdns/{{ID}}/queue_update](#) :param cdn_id: The CDN

Id :type cdn_id: int :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

copy_profile(*new_profile_name=None, copy_profile_name=None, data=None*)
Copy profile to a new profile. The new profile name must not exist *profiles/name/{{name}}/copy/{{copy}}* :param new_profile_name: The name of profile to copy to :type new_profile_name: String :param copy_profile_name: The name of profile copy from :type copy_profile_name: String :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_asn(*data=None*)
Create ASN *asns* :param data: The ASN data to use for ASN creation. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_cachegroups(*data=None*)
Create a Cache Group *cachegroups* :param data: The parameter data to use for cachegroup creation. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_cdn(*data=None*)
Create a new CDN. *cdns* :param data: The parameter data to use for cdn creation. :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

create_cdn_dns_sec_keys(*data=None*)
Generates ZSK and KSK keypairs for a CDN and all associated Delivery Services *cdns/dnsseckey/generate* :param data: The parameter data to use for cachegroup creation. :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

create_coordinates(*data=None*)
Create coordinates *coordinates* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_deliveryservice(*data=None*)
Allows user to create a delivery service. *deliveryservices* :param data: The request data structure for the API request :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

create_deliveryservice_regexes(*delivery_service_id=None, data=None*)
Create a regex for a delivery service *deliveryservices/{{ID}}/regexes* :param delivery_service_id: The delivery service Id :type delivery_service_id: int :param data: The required data to create delivery service regexes :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

create_division(data=None)

Create a division *divisions* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_federation(data=None)

Allows a user to add federations for their delivery service(s). *federations* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_federation_in_cdn(cdn_name=None, data=None)

Create a federation. *cdns/{{name}}/federations* :param cdn_name: The CDN name to find federation :type cdn_name: String :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_federation_resolver(data=None)

Create a federation resolver. :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_federation_user(federation_id=None, data=None)

Create one or more federation / user assignments. *federations/{{ID}}/users* :param federation_id: Federation ID :type federation_id: int :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_job(data=None)

Creates a new content-invalidation job sorted by start time. *jobs* :param data: The content-invalidation job object that will be created. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_origins(data=None)

Creates origins associated with a delivery service *origins* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_parameter(data=None)

Create Parameter *parameters* :param data: The parameter(s) data to use for parameter creation. :type data: Union[Dict[str, Any], List[Dict[str, Any]]] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

create_profile(data=None)

Create a profile *profiles* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises:

Union[LoginError, OperationError]

create_region(*query_params=None, data=None*)

Create a region *regions* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_role(*data=None*)

Create a new Role. *roles* :param data: A new Role object to be created. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_server(*data=None*)

Create a new Server. *servers* :param data: The parameter data to use for server creation :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_servercheck(*data=None*)

Post a server check result to the serverchecks table. *servercheck* :param data: The parameter data to use for server creation :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_staticdnsentries(*data=None*)

Create static DNS entries associated with the delivery service *staticdnsentries* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_tenant(*data=None*)

Create a tenant *tenants* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_to_extension(*data=None*)

Creates a Traffic Ops extension. *servercheck/extensions* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_topology(*data=None*)

Create a topology *topologies* :type data: Optional[Dict[str, Any]] :param data: The Topology data to use for Topology creation. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], Response] :raises: Union[LoginError, OperationError]

create_user(*data=None*)

Create a user. *users* :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str,

Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

create_user_with_registration(data=None)

Register a user and send registration email [users/register](#) :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_asn(query_params=None)

Delete ASN :to-api-asns-id: :param asn_id: The ID of the ASN to delete :type asn_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_cache_group_parameters(cache_group_id=None, parameter_id=None)

Delete a cache group parameter association. This endpoint has been deprecated and will no longer be available as of TO API v4. [cachegroupparameters/{ID}/{parameterID}](#) :param cache_group_id: The cache group id in which the parameter will be deleted :type cache_group_id: int :param parameter_id: The parameter id which will be disassociated :type parameter_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

delete_cachegroups(cache_group_id=None)

Delete a cache group [cachegroups/{ID}](#) :param cache_group_id: The cache group id to update :type cache_group_id: Integer :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_cdn_by_id(cdn_id=None)

Delete a CDN by Id. [cdns/{ID}](#) :param cdn_id: The CDN id :type cdn_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

delete_cdn_dns_sec_keys(cdn_name=None)

Delete dnssec keys for a cdn and all associated delivery services [cdns/name/{name}/dnsseckey](#) :param cdn_name: The CDN name to delete dnsseckey info for :type cdn_name: String :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

delete_coordinates(query_params=None)

Delete coordinates [coordinates](#) :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_deliveryservice_by_id(delivery_service_id=None)

Allows user to delete a delivery service. [deliveryservices/{ID}](#) :param delivery_service_id: The delivery service Id :type delivery_service_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

delete_deliveryservice_regex_by_regex_id(*delivery_service_id=None, delivery_service_regex_id=None*)

Delete a RegEx by Id for a Delivery Service by Id. [*deliveryservices/{ID}/regexes/{rID}*](#) :param delivery_service_id: The delivery service Id :type delivery_service_id: int :param delivery_service_regex_id: The delivery service regex Id :type delivery_service_regex_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

delete_deliveryservice_servers_by_id(*delivery_service_id=None, server_id=None*)

Removes a server (cache) from a delivery service. [*deliveryservice-server/{DSID}/{serverID}*](#) :param delivery_service_id: The delivery service id :type delivery_service_id: int :param server_id: The server id to remove from delivery service :type server_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_deliveryservice_ssl_keys_by_xml_id(*xml_id=None, query_params=None*)

Delete SSL keys for a Delivery Service by xmlId. [*deliveryservices/xmlId/{XMLID}/sslkeys*](#) :param xml_id: The Delivery Service xmlId :type xml_id: str :param query_params: The url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

delete_division(*division_id=None, query_params=None*)

Delete a division by division id [*divisions/{ID}*](#) :param division_id: The division id to delete :type division_id: int :param query_params: The required data to update delivery service regexes :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_federation_in_cdn(*cdn_name=None, federation_id=None*)

Delete a federation. [*cdns/{name}/federations/{ID}*](#) :param cdn_name: The CDN name to find federation :type cdn_name: String :param federation_id: The federation id :type federation_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_federation_resolver(*federation_resolver_id=None*)

Delete a federation resolver. :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_federation_user(*federation_id=None, user_id=None*)

Delete one or more federation / user assignments. [*federations/{ID}/users/{userID}*](#) :param federation_id: Federation ID :type federation_id: int :param user_id: Federation User ID :type user_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_job(*query_params=None*)

Deletes a content-invalidation job. *jobs* :param query_params: 'id' is a required parameter, identifying the job being deleted. :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_origins(*query_params=None*)

Updates origins associated with a delivery service *origins* :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_parameter(*parameter_id=None*)

Delete Parameter *parameters/{ID}* :param parameter_id: The parameter id to delete :type parameter_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

delete_physical_location(*physical_location_id=None, query_params=None*)

Delete Physical Location by id *phys_locations/{ID}* :param physical_location_id: The id to delete :type physical_location_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_profile_by_id(*profile_id=None*)

Delete Profile by Id. *profiles/{ID}* :param profile_id: The profile Id :type profile_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_profile_parameter_association_by_id(*profile_id=None, parameter_id=None*)

Delete Parameter association by Id for a Profile by Id. *profileparameters/{profileID}/{parameterID}* :param profile_id: The profile id :type profile_id: int :param parameter_id: The parameter id :type parameter_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

delete_region(*query_params=None*)

Delete a region by name or ID as a query parameter *regions/{ID}* :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_role(*query_params=None*)

Delete a Role. *roles* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_server_by_id(*server_id=None*)

Delete a Server by Id. *servers/{ID}* :param server_id: The server Id :type server_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

delete_staticdnsentries(*query_params=None*)

Delete static DNS entries associated with the delivery service *staticdnsentries*
: param query_params: The optional url query parameters for the call : type
query_params: Dict[str, Any] : rtype: Tuple[Union[Dict[str, Any], List[Dict[str,
Any]]], requests.Response] : raises: Union[LoginError, OperationError]

delete_to_extension(*extension_id=None*)

Deletes a Traffic Ops extension. *servercheck/extensions/{{ID}}* : param ex-
tension_id: The extension id to delete : type extension_id: int : rtype:
Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] : raises:
Union[LoginError, OperationError]

delete_topology(*name=None*)

Delete a Topology *topologies* : type name: Optional[str] : param name: The
name of the Topology to delete : type name: str : rtype: Tuple[Union[Dict[str, Any],
List[Dict[str, Any]]], Response] : raises: Union[LoginError, OperationError]

generate_deliveryservice_ssl_keys(*data=None*)

Generate an SSL certificate. (self-signed) *deliveryservices/sslkeys/generate* : param
data: The parameter data to use for Delivery Service SSL key generation. : type
data: Dict[str, Any] : rtype: Tuple[Dict[str, Any], requests.Response] : raises:
Union[LoginError, OperationError]

generate_deliveryservice_url_signature_keys(*xml_id=None*)

Generate URL Signature Keys for a Delivery Service by xmlId. *deliveryser-
vices/xmlId/{{xml_id}}/urlkeys/generate* : param xml_id: The Delivery Service xm-
lId : type xml_id: str : rtype: Tuple[Dict[str, Any], requests.Response] : raises:
Union[LoginError, OperationError]

generate_iso(*data=None*)

Generate an ISO *isos* : param data: The update action. QueueUpdateRequest()
can be used for this argument also. : type data: Dict[str, Any] : rtype:
Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] : raises:
Union[LoginError, OperationError]

get_all_cachegroup_parameters()

A collection of all cache group parameters. This endpoint has been deprecated and
will no longer be available as of TO API v4. *cachegroupparameters* : rtype: Tu-
ple[Dict[str, Any], requests.Response] : raises: Union[LoginError, OperationError]

get_all_deliveryservice_servers(*args, **kwargs)

Get all servers attached to all delivery services via the Traffic Ops API. : rtype:
Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] : raises:
Union[LoginError, OperationError]

get_api_capabilities(*query_params=None*)

Get all API-capability mappings *api_capabilities* : rtype: Tuple[Union[Dict[str,
Any], List[Dict[str, Any]]], requests.Response] : raises: Union[LoginError, Oper-
ationError]

get_asns(*query_params=None*)

Get ASNs. *asns* : rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], re-

quests.Response] :raises: Union[LoginError, OperationError]

get_authenticated_user()

Retrieves the profile for the authenticated user. [user/current](#) :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_cache_stats(query_params=None)

Retrieves statistics about the CDN. [cache_stats](#) :param query_params: See API page for more information on accepted params :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_cachegroup_parameters(cache_group_id=None)

Get a cache groups parameters. This endpoint has been deprecated and will no longer be available as of TO API v4. [cachegroups/{ID}/parameters](#) :param cache_group_id: The cache group Id :type cache_group_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_cachegroups(query_params=None)

Get Cache Groups. [cachegroups](#) :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_capabilities(query_params=None)

Retrieves capabilities [capabilities](#) :param query_params: See API page for more information on accepted parameters :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_cdn_dns_sec_keys(cdn_name=None)

Gets a list of dnsseckey for a CDN and all associated Delivery Services [cdns/name/{name}/dnsseckey](#) :param cdn_name: The CDN name to find dnsseckey info for :type cdn_name: String :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_cdn_health_by_name(cdn_name=None)

Retrieves the health of all locations (cache groups) for a given CDN [cdns/{name}/health](#) :param cdn_name: The CDN name to find health for :type cdn_name: String :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_cdn_monitoring_info(cdn_name=None)

Retrieves CDN monitoring information [cdns/{name}/configs/monitoring](#) :param cdn_name: The CDN name to find configs for :type cdn_name: String :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_cdn_ssl_keys(cdn_name=None)

Returns ssl certificates for all Delivery Services that are a part of the CDN. [cdns/name/{name}/sslkeys](#) :param cdn_name: The CDN name to find ssl keys for :type cdn_name: String :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_cdns(*query_params=None*)

Get all CDNs. *cdns* :param query_params: See API page for more information on accepted parameters :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_cdns_capacity()

Retrieves the aggregate capacity percentages of all locations (cache groups) for a given CDN. *cdns/capacity* :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_cdns_domains()

Retrieves the different CDN domains *cdns/domains* :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_cdns_health()

Retrieves the health of all locations (cache groups) for all CDNs *cdns/health* :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_cdns_routing()

Retrieves the aggregate routing percentages of all locations (cache groups) for a given CDN. *cdns/routing* :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_change_logs(*query_params=None*)

Retrieve all change logs from traffic ops *logs* :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_change_logs_newcount()

Get amount of new logs from traffic ops *logs/newcount* :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_coordinates(*query_params=None*)

Get all coordinates associated with the cdn *coordinates* :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_current_snapshot_crconfig(*cdn_name=None*)

Retrieves the CURRENT snapshot for a CDN which doesn't necessarily represent the current state of the CDN. The contents of this snapshot are currently used by Traffic Monitor and Traffic Router. *cdns/{name}/snapshot* :param cdn_name: The CDN name :type cdn_name: str :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_delivery_service_capacity(*delivery_service_id=None*)

Retrieves the capacity percentages of a delivery service. Delivery service must be assigned to user if user is not admin or operations. *deliveryservices/{ID}/capacity* :param delivery_service_id: The delivery service Id :type delivery_service_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_delivery_service_health(*delivery_service_id=None*)

Retrieves the health of all locations (cache groups) for a delivery service. Delivery service must be assigned to user if user is not admin or operations. [delivery-services/{ID}/health](#) :param delivery_service_id: The delivery service Id :type delivery_service_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_delivery_service_stats(*query_params=None*)

Retrieves statistics on the delivery services. [deliveryservice_stats](#) :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_deliveryservice_ineligible_servers(*delivery_service_id=None*)

Retrieves properties of CDN EDGE or ORG servers not eligible for assignment to a delivery service. [deliveryservices/{ID}/servers/eligible](#) :param delivery_service_id: The delivery service Id :type delivery_service_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_deliveryservice_regexes_by_id(*delivery_service_id=None,*
query_params=None)

Get RegExes for a Delivery Service by Id. [deliveryservices/{ID}/regexes](#) :param delivery_service_id: The delivery service Id :type delivery_service_id: int :param query_params: The url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_deliveryservice_servers(*delivery_service_id=None*)

Retrieves properties of CDN EDGE or ORG servers assigned to a delivery service. [deliveryservices/{ID}/servers](#) :param delivery_service_id: The delivery service Id :type delivery_service_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_deliveryservice_ssl_keys_by_xml_id(*xml_id=None,*
query_params=None)

Get SSL keys for a Delivery Service by xmlId. [deliveryservices/xmlId/{XMLID}/sslkeys](#) :param xml_id: The Delivery Service XML id :type xml_id: str :param query_params: The url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_deliveryservices(*query_params=None*)

Retrieves all delivery services (if admin or ops) or all delivery services assigned to user. [deliveryservices](#) :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_deliveryservices_regexes()

Get RegExes for all Delivery Services. [deliveryservices_regexes](#) :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_deliveryserviceserver(*query_params=None*)

Retrieves delivery service / server assignments. (Allows pagination and limits) *deliveryserviceserver* :param query_params: The required url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_divisions(*query_params=None*)

Get all divisions. *divisions* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_federation_delivery_services(*federation_id=None*)

Retrieves delivery services assigned to a federation *federations/{ID}/deliveryservices* :param federation_id: The federation id :type federation_id: int :param federation_id: The federation id :type federation_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_federation_resolvers(*query_params=None*)

Get federation resolvers. *federation_resolvers* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_federation_resolvers_by_id(*federation_id=None*)

federations/{ID}/federation_resolvers Retrieves federation resolvers assigned to a federation :param federation_id: The federation id :type federation_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_federation_users(*federation_id=None*)

Retrieves users assigned to a federation. *federations/{ID}/users* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_federations()

Retrieves a list of federation mappings (aka federation resolvers) for a the current user *federations* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_federations_for_cdn(*cdn_name=None, query_params=None*)

Retrieves a list of federations for a cdn. *cdns/{name}/federations* :param cdn_name: The CDN name to find federation :type cdn_name: String :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_jobs(*query_params=None*)

Get all content-invalidation jobs (tenancy permitting). *jobs* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_origins(*query_params=None*)

Get origins associated with the delivery service *origins* :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_osversions()

Get all OS versions for ISO generation and the directory where the kickstarter files are found. The values are retrieved from osversions.json found in either /var/www/files or in the location defined by the kickstart.files.location parameter (if defined). *osversions* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_parameters(*query_params=None*)

Get all Parameters. *parameters* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_parameters_by_profile_id(*profile_id=None*)

Get all Parameters associated with a Profile by Id. *profiles/{ID}/parameters* :param profile_id: The profile Id :type profile_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_parameters_by_profile_name(*profile_name=None*)

Get all Parameters associated with a Profile by Name. *profiles/name/{name}/parameters* :param profile_name: The profile name :type profile_name: str :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_pending_snapshot_crconfig(*cdn_name=None*)

Retrieves a PENDING snapshot for a CDN which represents the current state of the CDN. The contents of this snapshot are NOT currently used by Traffic Monitor and Traffic Router. Once a snapshot is performed, this snapshot will become the CURRENT snapshot and will be used by Traffic Monitor and Traffic Router. *cdns/{name}/snapshot/new* :param cdn_name: The CDN name :type cdn_name: str :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_physical_locations(*query_params=None*)

Get Physical Locations. *phys_locations* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_plugins()

Retrieves the list of plugins. *plugins* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_profiles(*query_params=None*)

Get Profiles. *profiles* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_regions(*query_params=None*)

Get Regions. *regions* :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_roles()

Get Roles. *roles* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_server_delivery_services(*server_id=None*)

Retrieves all delivery services assigned to the server *servers/{ID}/deliveryservices* :param server_id: The server id to retrieve :type server_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_server_details(*name=None*)

Get servers/details *servers/details* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_server_update_status(*server_name=None*)

Gets the current update status of a server named *server_name*. *servers/{hostname}/update_status* :param server_name: The (short) hostname of the server for which the update status will be fetched :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

get_servercheck_extensions()

Retrieves the list of extensions. *servercheck/extensions* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_servers(*query_params=None*)

Get Servers. *servers* :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_staticdnsentries(*query_params=None*)

Get static DNS entries associated with the delivery service *staticdnsentries* :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_statuses(*query_params=None*)

Retrieves a list of the server status codes available. *statuses* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_system_info()

Get information on the traffic ops system. *system/info* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_tenants(*query_params=None*)

Get all tenants. *tenants* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_topologies(*query_params=None*)

Get Topologies. *topologies* :type query_params: Optional[Dict[str, Any]] :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], Response] :raises: Union[LoginError, OperationError]

get_traffic_monitor_cache_stats()

Retrieves cache stats from Traffic Monitor. Also includes rows for aggregates *caches/stats* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_types(*query_params=None*)

Get Data Types. *types* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_user_by_id(*user_id=None*)

Retrieves user by ID. *users/{ID}* :param user_id: The user to retrieve :type user_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

get_users()

Retrieves all users. *users* :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

property logged_in

Read-only property of to determine if user is logged in to Traffic Ops. :return: True if connected and logged in, False otherwise :rtype: bool

login(*username, password*)

Login to the Traffic Ops API. :param username: Traffic Ops User Name :type username: str :param password: Traffic Ops User Password :type password: str :return: None :rtype: None :raises: LoginError

replace_authenticated_user(*data=None*)

Updates the currently authenticated user. *user/current* :param data: The new user information which will replace the current user's user information. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

servers_queue_update(*server_id=None, data=None*)

Queue Updates by Server Id. *servers/{ID}/queue_update* :param server_id: The server Id :type server_id: int :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

snapshot_crconfig(*query_params=None*)

Snapshot CRConfig by CDN Name or ID. *snapshot* :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any]

:rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

property to_url

The URL without the api portion. (read-only)

Returns The URL should match '[w+-.]+://[w+-.]+(:d+)?' e.g <https://to.somedomain.net> or <https://to.somedomain.net:443>

Return type str

topologies_queue_update(name=None, data=None)

Queue Updates by Topology name. [topologies/{name}/queue_update](#) :param name: The Topology name :param data: The update action. :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

update_asn(query_params=None)

Update ASN [asns/{id}](#) :param asn_id: The ID of the ASN to update :type asn_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_cachegroups(cache_group_id=None, data=None)

Update a cache group [cachegroups/{ID}](#) :param cache_group_id: The cache group id to update :type cache_group_id: Integer :param data: The parameter data to use for cachegroup creation. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_cdn_by_id(cdn_id=None, data=None)

Update a CDN by Id. [cdns/{ID}](#) :param cdn_id: The CDN id :type cdn_id: int :param data: The parameter data to use for cdn update. :type data: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

update_coordinates(query_params=None, data=None)

Update coordinates [coordinates](#) :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_deliveryservice_by_id(delivery_service_id=None, data=None)

Update a Delivery Service by Id. [deliveryservices/{ID}](#) :param delivery_service_id: The delivery service Id :type delivery_service_id: int :param data: The request data structure for the API request :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_deliveryservice_regexes(delivery_service_id=None, regex_id=None, query_params=None)

Update a regex for a delivery service [deliveryservices/{ID}/regexes/{rID}](#) :param delivery_service_id: The delivery service Id :type delivery_service_id: int :param regex_id: The delivery service regex id :type regex_id: int :param

query_params: The required data to update delivery service regexes :type query_params: Dict[str, Any] :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

update_deliveryservice_safe(*delivery_service_id=None, data=None*)

Allows a user to edit limited fields of a Delivery Service. [deliveryservices/{{ID}}/safe](#) :param delivery_service_id: The Delivery Service Id :type delivery_service_id: int :param data: The request data structure for the API request :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_division(*division_id=None, query_params=None*)

Update a division by division id [divisions/{{ID}}](#) :param division_id: The division id to update :type division_id: int :param query_params: The required data to update delivery service regexes :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_federation_in_cdn(*cdn_name=None, federation_id=None, query_params=None*)

Update a federation. [cdns/{{name}}/federations/{{ID}}](#) :param cdn_name: The CDN name to find federation :type cdn_name: String :param federation_id: The federation id :type federation_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_job(*data=None, query_params=None*)

Replaces a content-invalidation job with the one passed. :param data: The content-invalidation job with which the identified job will be replaced. :type data: Dict[str, Any] :param query_params: 'id' is a required parameter, identifying the job being updated. [jobs](#) :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_origins(*query_params=None*)

Updates origins associated with a delivery service [origins](#) :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_parameter(*parameter_id=None, query_params=None*)

Update Parameter [parameters/{{ID}}](#) :param parameter_id: The parameter id to update :type parameter_id: int :rtype: Tuple[Dict[str, Any], requests.Response] :raises: Union[LoginError, OperationError]

update_physical_location(*physical_location_id=None, query_params=None*)

Update Physical Location by id [phys_locations/{{ID}}](#) :param physical_location_id: The id to update :type physical_location_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_profile_by_id(*profile_id=None, data=None*)

Update Profile by Id. [profiles/{ID}](#) :param profile_id: The profile Id :type profile_id: int :param data: The parameter data to edit :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_region(*region_id=None*)

Update a region [regions/{ID}](#) :param region_id: The region to update :type region_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_role(*data=None, query_params=None*)

Get Roles. [roles](#) :param data: A new Role object which will replace the one identified. :type data: Dict[str, Any] :param query_params: 'id' is a required parameter, defining the Role to be replaced. :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_server_by_id(*server_id=None, data=None*)

Update a Server by Id. [servers/{ID}](#) :param server_id: The server Id :type server_id: int :param data: The parameter data to edit :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_server_status_by_id(*server_id=None, data=None*)

Update server_status by Id. [servers/{ID}/status](#) :param server_id: The server Id :type server_id: int :status: <https://traffic-control-cdn.readthedocs.io/en/latest/api/server.html> :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_staticdnsentries(*data=None, query_params=None*)

Update static DNS entries associated with the delivery service [staticdnsentries](#) :param data: The update action. QueueUpdateRequest() can be used for this argument also. :type data: Dict[str, Any] :param query_params: The optional url query parameters for the call :type query_params: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_tenant(*tenant_id=None*)

Update a tenant [tenants/{ID}](#) :param tenant_id: The tenant to update :type tenant_id: int :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response] :raises: Union[LoginError, OperationError]

update_topology(*name=None, data=None*)

Update a Topology [topologies](#) :type name: Optional[str] :param name: The name of the Topology :type name: str :type data: Optional[Dict[str, Any]] :param data: The new values for the Topology :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], Response] :raises: Union[LoginError, OperationError]

update_user_by_id(*user_id=None, data=None*)

Update a user. [users](#) :param data: The user update data payload. :type data: Dict[str, Any] :rtype: Tuple[Union[Dict[str, Any], List[Dict[str, Any]]], requests.Response]

:raises: Union[LoginError, OperationError]

trafficops.api_request(*method_name*, *api_path*, *supported_versions*)

This wrapper returns a decorator that routes the calls to the appropriate utility function that generates the RESTful API endpoint, performs the appropriate call to the endpoint and returns the data to the user.

Parameters

- **method_name** (*str*) – A method name defined on the Class, this decorator is decorating, that will be called to perform the operation. E.g. ‘GET’, ‘POST’, ‘PUT’, ‘DELETE’, etc. The method_name chosen must have the signature of <method>(self, api_path, **kwargs) e.g. def get(self, api_path, **kwargs): ...
- **api_path** (*str*) – The path to the API end-point that you want to call which does not include the base url e.g. user/login, servers, etc. This string can contain substitution parameters as denoted by a valid field_name replacement field specification as per str.format() e.g. cachegroups/{id} or cachegroups/{id:d}
- **supported_versions** (*Tuple[str]*) – A tuple of API versions that this route supports

Returns rtype int: A new function that replaces the original function with a boilerplate execution process.

Return type Callable[str, Dict[str, Any]]

utils

Useful utility methods

trafficops.utils.log_with_debug_info(*logging_level=20*, *msg=""*, *parent=False*, *separator=':'*)

Uses inspect module(reflection) to gather debugging information for the source file name, function name, and line number of the calling function/method.

Parameters

- **logging_level** (*int*) – The logging level from the logging module constants E.g. logging.INFO, logging.DEBUG, etc.
- **msg** (*Text*) – The message to log.
- **parent** (*bool*) – If True, use the caller’s parent information instead of the caller’s information in the message.
- **separator** (*Text*) – The string to use for the component separator

Returns ‘<file name>:<function name>:<line number>: <msg>’ e.g. ‘tosession.py:_build_endpoint:199: This is a message to log.’

Return type Text

Versioning

The `trafficops.__version__` module contains only the `__version__` “constant” which gives the version of this *Apache-TrafficControl* package and **not** the version of *Apache Traffic Control* for which it was made. The two are versioned separately, to allow the client to grow in a version-controlled manner without being tied to the release cadence of Apache Traffic Control as a whole.

Version 3.0 is supported for use with Apache Traffic Control versions 5.0 and 5.1 (release pending at the time of this writing). New functionality will be added as the *Traffic Ops API* evolves, but changes to this client will remain non-breaking for existing code using it until the next major version is released.

6.1.3 toaccess

toaccess

This module provides a set of functions meant to provide ease-of-use functionality for interacting with the Traffic Ops API. It provides scripts named `tomethod` where `method` is the name of an HTTP method (in lowercase). Collectively they are referred to as **toaccess**. Implemented methods thus far are:

- delete
- head
- get
- options
- patch
- post
- put

Arguments and Flags

PATH

This is the request path. By default, whatever is passed is considered to be relative to `/api/api-version/` where `api-version` is `--api-version`. This behavior can be disabled by using `--raw-path`.

DATA

An optional positional argument that is a data payload to pass to the Traffic Ops server in the request body. If this is the absolute or relative path to a file, the contents of the file will instead be read and used as the request payload.

`-h`, `--help`

Print usage information and exit

- a API_VERSION, --api-version API_VERSION**
Specifies the version of the Traffic Ops API that will be used for the request. Has no effect if `--raw-path` is used. (Default: 2.0)
- f, --full**
Output the full HTTP exchange including request method line, request headers, request body (if any), response status line, and response headers (as well as the response body, if any). This is equivalent to using `--request-headers`, `--request-payload`, and `--response-headers` at the same time, and those options will have no effect if given. (Default: false)
- k, --insecure**
Do not verify SSL certificates - typically useful for making requests to development or testing servers as they frequently have self-signed certificates. (Default: false)
- p, --pretty**
Pretty-print any payloads that are output as formatted JSON. Has no effect on plaintext payloads. Uses tab characters for indentation. (Default: false)
- r, --raw-path**
Request exactly `PATH`; do not preface the request path with `/api/api_version`. This effectively means that `--api-version` will have no effect. (Default: false)
- v, --version**
Print version information and exit.
- request-headers**
Output the request method line and any and all request headers. (Default: false)
- request-payload**
Output the request body if any was sent. Will attempt to pretty-print the body as JSON if `--pretty` is used. (Default: false)
- response-headers**
Output the response status line and any and all response headers. (Default: false)
- to-url URL**
The FQDN and optionally the port and scheme of the Traffic Ops server. This will override `TO_URL`. The format is the same as for `TO_URL`. (Default: uses the value of `TO_URL`)
- to-password PASSWORD**
The password to use when authenticating to Traffic Ops. Overrides `TO_PASSWORD`. (Default: uses the value of `TO_PASSWORD`)
- to-user USERNAME**
The username to use when connecting to Traffic Ops. Overrides `TO_USER`. (Default: uses the value of `TO_USER`)

Environment Variables

If defined, **toaccess** scripts will use the `TO_URL`, `TO_USER`, and `:envvar`TO_PASSWORD`` environment variables to define their connection to and authentication with the Traffic Ops server. Typically, setting these is easier than using the long options `--to-url`, `--to-user`, and `--to-password` on every invocation.

Exit Codes

The exit code of a **toaccess** script can sometimes be used by the caller to determine what the result of calling the script was without needing to parse the output. The exit codes used are:

- 0** The command executed successfully, and the result is on STDOUT.
- 1** Typically this exit code means that an error was encountered when parsing positional command line arguments. However, this is also the exit code used by most Python interpreters to signal an unhandled exception.
- 2** Signifies a runtime error that caused the request to fail - this is **not** generally indicative of an HTTP client or server error, but rather an underlying issue connecting to or authenticating with Traffic Ops. This is distinct from an exit code of 32 in that the *format* of the arguments was correct, but there was some problem with the *value*. For example, passing `https://test:` to `--to-url` will cause an exit code of 2, not 32.
- 4** An HTTP client error occurred. The HTTP stack will be printed to stdout as indicated by other options - meaning by default it will only print the response payload if one was given, but will respect options like e.g. `--request-payload` as well as `-p/--pretty`.
- 5** An HTTP server error occurred. The HTTP stack will be printed to stdout as indicated by other options - meaning by default it will only print the response payload if one was given, but will respect options like e.g. `--request-payload` as well as `-p/--pretty`.
- 32** This is the error code emitted by Python's `argparse` module when the passed arguments could not be parsed successfully.

Note: The way exit codes 4 and 5 are implemented is by returning the status code of the HTTP request divided by 100 whenever it is at least 400. This means that if the Traffic Ops server ever started returning e.g. 700 status codes, the exit code of the script would be 7.

Module Reference

`to_access.delete()`

Entry point for **todelete**

Returns The program's exit code

`to_access.get()`

Entry point for **toget**

Returns The program's exit code

`to_access.head()`

Entry point for **tohead**

Returns The program's exit code

`to_access.options()`

Entry point for **tooptions**

Returns The program's exit code

`to_access.output(r, pretty, request_header, response_header, request_payload,
indent='\t')`

Prints the passed response object in a format consistent with the other parameters.

Parameters

- **r** – The requests response object being printed
- **pretty** – If True, attempt to pretty-print payloads as JSON
- **request_header** – If True, print request line and request headers
- **response_header** – If True, print response line and response headers
- **request_payload** – If True, print the request payload
- **indent** – An optional number of spaces for pretty-printing indentation (default is the tab character)

`to_access.parse_arguments(program)`

A common-use function that parses the command line arguments.

Parameters **program** – The name of the program being run - used for usage informational output

Returns The Traffic Ops HTTP session object, the requested path, any data to be sent, an output format specification, whether or not the path is raw, and whether or not output should be prettified

`to_access.patch()`

Entry point for **topatch**

Returns The program's exit code

`to_access.post()`

Entry point for **topost**

Returns The program's exit code

`to_access.put()`

Entry point for **toput**

Returns The program's exit code

`to_access.request(method)`

All of the scripts wind up calling this function to handle their common functionality.

Parameters **method** – The name of the request method to use (case-insensitive)

Returns The program's exit code

6.1.4 Traffic Vault Util (Riak)

The `traffic_vault_util` tool - located at `tools/traffic_vault_util.go` in the [Apache Traffic Control repository](#) - is used to view and modify the contents of a Traffic Vault Riak cluster. The tool contains basic operations to display the buckets, keys and values stored within Riak.

Note: This tool does not apply to the PostgreSQL Traffic Vault backend.

`traffic_vault_util` also has a small converter utility to perform a one-off conversion of key formats within the SSL bucket. This conversion is useful when moving from an older version of Traffic Ops to the current version. In the older version, SSL records were indexed by *Delivery Service* database ID. Currently, SSL records are indexed by *Delivery Service* `xml_id`.

Usage

```
traffic_vault_util [--dry_run] --vault_ip IP --vault_action ACTION
[--vault_user USER] [--vault_password PASSWD] [--vault_port PORT]
```

--dry_run

An optional flag which, if given, will cause **traffic_vault_util** to not write changes, but merely print what *would* be done in a real run.

--vault_action ACTION

Defines the action to be performed. Available actions are:

list_buckets Lists the “buckets” in the Riak cluster used by Traffic Vault

list_keys Lists all the keys in all the buckets in the Riak cluster used by Traffic Vault

list_values Lists all the values of all the keys in all the buckets in the Riak cluster used by Traffic Vault

convert_ssl_to_xmlid Changes the key of all records in all buckets that start with “ds” into the `xml_id` of the *Delivery Service* for which we assume the record was created.

--vault_ip IP

Either the IP address or FQDN of the Traffic Vault instance with which **traffic_vault_util** will interact.

Warning: If this IP address or FQDN does not point to a real Riak cluster, **traffic_vault_util** will print an error message to STDOUT, but *will not terminate*. Instead, it will try forever to query the server to which it failed to connect, consuming large amounts of CPU usage all the while¹.

--vault_password PASSWD

An optional flag used to specify the password of the user defined by `--vault_user` when authenticating with Traffic Vault’s Riak cluster.

¹ These problems are all tracked by [GitHub Issue #3261](#).

Warning: Although this flag is optional, the utility will not work without it. It will try, but it will fail^{Page 2090, 1}.

--vault_port PORT

An optional flag which, if given, sets the port to which **traffic_vault_util** will try to connect to Riak. Default: 8087

--vault_user USER

An optional flag which, if given, specifies the name of the user as whom to connect to Riak.

Warning: Although this flag is optional, the utility will not work without it. It will try, but it will fail^{Page 2090, 1}.

7.1 FAQ

7.1.1 Who is using Traffic Control?

- [Comcast Cable](#) is the original developer of Traffic Control and is using it for all it's IP video delivery, delivering images and software to it's X1 platform, and for [delivering third party content](#) to it's footprint.
- [Cox Communications](#)
- [Cisco](#) has a product called [Open Media Distribution](#) that is based on Traffic Control.
- [Concurrent](#) has a product that uses Traffic Control, see their [github page](#) for more info.
- [Augere Pakistan / QUBEE](#)
- [Qwilt](#) has a product called [Open Edge CDN](#) that is based on Traffic Control.

7.1.2 How do I get help with Traffic Control?

Join us at [#traffic-control](#) on the [ASF Slack](#) or send your questions to our [mailing list](#). Slack is usually the best forum for quick Q&A type issues – like when you are getting a Traffic Control CDN up and running or if you have a question about configuration. Any discussions that could potentially lead to decisions being made about the project – like a new feature – should happen on [the developer mailing list](#).

7.1.3 How do I get involved with the development of Traffic Control?

See the [CONTRIBUTING.md](#) file.

7.1.4 What is Rascal?

Rascal was the original name for Traffic Monitor. You will sometimes still see this name in the source, or in older documents.

7.1.5 What is the CCR?

CCR (Comcast Content Router) was the original name for Traffic Router. You will sometimes still see this name in the source, or in older documents.

7.1.6 What is Twelve Monkeys?

Twelve Monkeys was the the original internal name for Traffic Ops. You will sometimes still see this name in the source, or in older documents. It's also a good movie.

7.1.7 What license is Traffic Control released under?

See the [LICENSE](#) file.

INDICES AND TABLES

8.1 Glossary

302 content routing *HTTP Content Routing*.

ACME Account An account previously created with an ACME provider.

astats (stats_over_http) An ATS plugin that allows you to monitor vitals of the ATS server.
See *Cache Monitoring*.

Cache Group

Cache Groups A group of caching HTTP proxy servers that together create a combined larger cache using consistent hashing. Traffic Router treats all servers in a *Cache Group* as though they are in the same geographic location, though they are in fact only in the same general area. A *Cache Group* has one single set of geographical coordinates even if the *cache servers* that make up the *Cache Group* are actually in *Physical Locations*. The *cache servers* in a *Cache Group* are not aware of the other *cache servers* in the group - there is no clustering software or communications between *cache servers* in a *Cache Group*.

There are two basic types of *Cache Groups*: EDGE_LOC and MID_LOC (“LOC” being short for “location” - a holdover from when *Cache Groups* were called “Cache Locations”). Traffic Control is a two-tiered system, where the clients get directed to the Edge-tier (EDGE_LOC) *Cache Group*. On cache miss, the *cache server* in the Edge-tier *Cache Group* obtains content from a Mid-tier (MID_LOC) *Cache Group*, rather than the origin, which is shared with multiple Edge-tier *Cache Groups*. Edge-tier *Cache Groups* are usually configured to have a single “parent” *Cache Group*, but in general Mid-tier *Cache Groups* have many “children”.

Note: Often the Edge-tier to Mid-tier relationship is based on network distance, and does not necessarily match the geographic distance.

See also:

A *Cache Group* serves a particular part of the network as defined in the *Coverage Zone File* (or *Deep Coverage Zone File*, when applicable).

See also:

For a more complete description of Cache Groups, see the [Cache Groups](#) overview section.

Cache Server

cache server

cache servers The main function of a CDN is to proxy requests from clients to [origin servers](#) and cache the results. To proxy, in the CDN context, is to obtain content using HTTP from an [origin server](#) on behalf of a client. To cache is to store the results so they can be reused when other clients are requesting the same content. There are three types of proxies in use on the Internet today:

- [reverse proxy](#): Used by Traffic Control for Edge-tier *cache servers*.
- [forward proxy](#): Used by Traffic Control for Mid-tier *cache servers*.
- transparent proxy: These are not used by Traffic Control. If you are interested you can learn more about transparent proxies on [wikipedia](#).

content routing Directing clients (or client systems) to a particular location or device in a location for optimal delivery of content See also [HTTP Content Routing](#) and [DNS Content Routing](#).

Coverage Zone File

Coverage Zone Map The CZM (Coverage Zone Map) or CZF is a file that maps network prefixes to [Cache Groups](#). Traffic Router uses the CZM to determine what [Cache Group](#) is closest to the client. If the client IP address is not in this CZM, it falls back to geographic mapping, using a [MaxMind GeoIP2 database](#) to find the client's location, and the geographic coordinates from Traffic Ops for the [Cache Group](#). Traffic Router is inserted into the HTTP retrieval process by making it the authoritative DNS server for the domain of the CDN [Delivery Service](#). In the example of the [reverse proxy](#), the client was given the `http://www-origin-cache.cdn.com/foo/bar/fun.html` URL. In a Traffic Control CDN, URLs start with a routing name, which is configurable per-[Delivery Service](#), e.g. `http://foo.mydeliveryservice.cdn.com/fun/example.html` with the chosen routing name `foo`.

1469: Example Coverage Zone File

```
{ "coverageZones": {  
  "cache-group-01": {  
    "network6": [  
      "1234:5678::/64",  
      "1234:5679::/64"  
    ],  
    "network": [  
      "192.168.8.0/24",  
      "192.168.9.0/24"  
    ]  
  }  
}
```

(continues on next page)

(continued from previous page)

```
}
}}
```

Deep Coverage Zone File

Deep Coverage Zone Map The DCZF or DCZM (Deep Coverage Zone Map) maps network prefixes to “locations” - almost like the *Coverage Zone File*. Location names must be unique, and within the file are simply used to group *Edge-tier cache servers*. When a mapping is performed by Traffic Router, it will only look in the DCZF if the *Delivery Service* to which a client is being directed makes use of *Deep Caching*. If the client’s IP address cannot be matched by entries in this file, Traffic Router will first fall back to the regular *Coverage Zone File*. Then, failing that, it will perform geographic mapping using a database provided by the *Delivery Service*’s *Geolocation Provider*.

1470: Example Deep Coverage Zone File

```
{ "deepCoverageZones": {
  "location-01": {
    "network6": [
      "1234:5678::/64",
      "1234:5679::/64"
    ],
    "network": [
      "192.168.8.0/24",
      "192.168.9.0/24"
    ],
    "caches": [
      "edge"
    ]
  }
}}
```

Delivery Service

Delivery Services *Delivery Services* are often referred to as a *reverse proxy* “remap rule” that exists on Edge-tier *cache servers*. In most cases, a *Delivery Service* is a one-to-one mapping to an FQDN that is used as a hostname to deliver the content. Many options and settings regarding how to optimize the content delivery exist, which are configurable on a *Delivery Service* basis. Some examples of these *Delivery Service* settings are:

- Cache in RAM, cache on disk, or do not cache at all.
- Use DNS or HTTP Content routing.
- Limits on transactions per second and bandwidth.
- Protocol (HTTP or HTTPS).
- Token-based authentication settings.
- Header rewrite rules.

Since Traffic Control version 2.1, *Delivery Services* can optionally be linked to a *Profile*, and have *Parameters* associated with them. One example of a feature that uses *Delivery Service Parameters* is the *Use Multi-Site Origin Feature* configuration. *Delivery Services* are also for use in allowing multiple *Tenants* to coexist in a Traffic Control CDN without interfering with each other, and to keep information about their content separated.

See also:

See *Delivery Services* for a more in-depth explanation of *Delivery Services*.

Delivery Service Request

Delivery Service Requests

DSR

DSRs A *Delivery Service Request* is the result of attempting to modify a *Delivery Service* when `dsRequests.enabled` is set to `true` in `traffic_portal_properties.json`. See *Delivery Service Requests* for more information.

See also:

See *Delivery Service Requests* for a more in-depth explanation of *Delivery Service Requests*, including their data model. See *Delivery Service Requests* for more information on how to use *Delivery Service Requests* in Traffic Portal.

Delivery Service required capabilities *Delivery Services required capabilities* are capabilities, which correlate to server capabilities, that are required in order to assign a server to a delivery service.`

Division

Divisions A group of *Regions*.

Edge

Edge-tier

Edge-Tier

Edge-tier cache

Edge-tier caches

Edge-tier cache server

Edge-tier cache servers Closest to the client or end-user. The edge tier is the tier that serves the client, edge caches are caches in the edge tier. In a Traffic Control CDN the basic function of the edge cache is that of a *reverse proxy*.

Federation

Federations *Federations* allow for other (“federated”) CDNs (e.g. at a different ISP (Internet Service Provider)) to add a list of DNS resolvers and an FQDN to be used in a DNS CNAME record for a *Delivery Service*. When a request is made from one of the federated CDN’s clients, Traffic Router will return the CNAME record configured from the federation mapping. This allows the federated CDN to serve the content without the content provider changing the URL, or having to manage multiple URLs. For example, if the

external CDN was actually another ATC-managed CDN, then a federation mapping to direct clients toward it should use the FQDN of a *Delivery Service* on the external CDN.

Federations only have meaning to DNS-routed *Delivery Services* - HTTP-routed Delivery services should instead treat the external FQDN as an *Origin* to achieve the same effect.

See also:

Federations are currently only manageable by directly using the *Traffic Ops API*. The endpoints related to federations are *federations*, *federation_resolvers*, *federations/{{ID}}/deliveryservices*, *federations/{{ID}}/deliveryservices/{{dsID}}*, *federations/{{ID}}/federation_resolvers*, *federations/{{ID}}/users*, and *federations/{{ID}}/users/{{userID}}*.

First-tier

First-tier cache

First-tier caches

First-tier cache server

First-tier cache servers Closest to the client or end-user. The first tier in a *Topology* is the tier that serves the client, similar to the *Edge-tier*.

forward proxy

forward proxies A forward proxy acts on behalf of the client such that the *origin server* is (potentially) unaware of the proxy's existence. All Mid-tier *cache servers* in a Traffic Control based CDN are *forward proxies*. In a *forward proxy* scenario, the client is explicitly configured to use the the proxy's IP address and port as a *forward proxy*. The client always connects to the *forward proxy* for content. The content provider does not have to change the URL the client obtains, and is (potentially) unaware of the proxy in the middle.

See also:

[ATS documentation on forward proxy](#).

If a client uses a *forward proxy* to request the URL `http://www.origin.com/foo/bar/fun.html` the resulting chain of events follows.

1. To retrieve `http://www.origin.com/foo/bar/fun.html`, the client sends an HTTP request to the *forward proxy*.

1471: Client Requests Content from its *Forward Proxy*

```
GET http://www.origin.com/foo/bar/fun.html HTTP/1.1
Host: www.origin.com
```

Note: In this case, the client requests the entire URL instead of just the path as is the case when using a *reverse proxy* or when requesting content directly from the *origin server*.

2. The proxy verifies whether the response for `http://www-origin-cache.cdn.com/foo/bar/fun.html` is already in the cache. If it is not in the cache:

1. The proxy sends the HTTP request to the *Origin*.

1472: The *Forward Proxy* Requests Content from the *origin server*

```
GET /foo/bar/fun.html HTTP/1.1
Host: www.origin.com
```

2. The *origin server* responds with the requested content.

1473: The *origin server*'s Response

```
HTTP/1.1 200 OK
Date: Sun, 14 Dec 2014 23:22:44 GMT
Server: Apache/2.2.15 (Red Hat)
Last-Modified: Sun, 14 Dec 2014
↳ 23:18:51 GMT
ETag: "1aa008f-2d-50a3559482cc0"
Content-Length: 45
Connection: close
Content-Type: text/html; charset=UTF-8

<!DOCTYPE html><html><body>This is a
↳ fun file</body></html>
```

3. The proxy sends this on to the client, optionally adding a *Via*: header to indicate that the request was serviced by proxy.

1474: The *Forward Proxy*'s Response to the Client

```
HTTP/1.1 200 OK
Date: Sun, 14 Dec 2014 23:22:44 GMT
Last-Modified: Sun, 14 Dec 2014
↳ 23:18:51 GMT
ETag: "1aa008f-2d-50a3559482cc0"
Content-Length: 45
Connection: close
Content-Type: text/html; charset=UTF-8
Age: 0
Via: http/1.1 cache01.cdn.kabletown.
↳ net (ApacheTrafficServer/4.2.1
↳ [uScSsSfUpSeN:t cCSi p sS])
Server: ATS/4.2.1

<!DOCTYPE html><html><body>This is a
↳ fun file</body></html>
```

If, however, the requested content *was* in the cache the proxy responds to the client with the previously retrieved result

1475: The *Forward Proxy* Sends the Cached Response

```
HTTP/1.1 200 OK
Date: Sun, 14 Dec 2014 23:22:44 GMT
Last-Modified: Sun, 14 Dec 2014 23:18:51 GMT
ETag: "1aa008f-2d-50a3559482cc0"
Content-Length: 45
Connection: close
Content-Type: text/html; charset=UTF-8
Age: 99711
Via: http/1.1 cache01.cdn.kabletown.net_
    ↪ (ApacheTrafficServer/4.2.1 [uScSsSfUpSeN:t cCSi p_
    ↪ sS])
Server: ATS/4.2.1

<!DOCTYPE html><html><body>This is a fun file</body>
    ↪ </html>
```

geo localization or geo routing Localizing clients to the nearest caches using a geo database like the one from Maxmind.

Health Protocol The protocol to monitor the health of all the caches. See [Health Protocol](#).

Inner-tier

Inner-tier cache

Inner-tier caches

Inner-tier cache server

Inner-tier cache servers The tier between the First tier and the Last tier. The inner tier in a [Topology](#) is the tier that forwards requests from other caches to other caches, i.e. caches in this tier do not directly serve the end-user and do not make requests to [Origins](#).

Last-tier

Last-tier cache

Last-tier caches

Last-tier cache server

Last-tier cache servers The tier above the First and Inner tiers. The last tier in a [Topology](#) is the tier that forwards requests from other caches to [Origins](#).

localization Finding location on the network, or on planet earth

Mid

Mid-tier

Mid-Tier

Mid-tier cache

Mid-tier caches

Mid-tier cache server

Mid-tier cache servers The tier above the edge tier. The mid tier does not directly serves the end-user and is used as an additional layer between the edge and the *Origin*. In a Traffic Control CDN the basic function of the mid cache is that of a *forward proxy*.

Origin

Origins

origin server

origin servers

Origin Servers The source of content for the CDN. Usually a redundant HTTP/1.1 webserver.

ORT The previous Traffic Control cache config app, replaced by *t3c*.

Parameter

Parameters Typically refers to a line in a configuration file, but in practice can represent any arbitrary configuration option.

See also:

The *Profiles and Parameters* overview section.

parent

parents The *parent(s)* of a *cache server* is/are the *cache server(s)* belonging to either the “parent” or “secondary parent” *Cache Group(s)* of the *Cache Group* to which the *cache server* belongs. For example, in general it is true that an *Edge-tier cache server* has one or more *parents* which are *Mid-tier cache servers*.

Physical Location

Physical Locations A pair of geographic coordinates (latitude and longitude) that is used by *Cache Groups* to define their location. This information is used by Traffic Router to route client traffic to the geographically nearest *Cache Group*.

Profile

Profiles A *Profile* is, most generally, a group of *Parameters* that will be applied to a server. *Profiles* are typically re-used by all *Edge-tier cache servers* within a CDN or *Cache Group*. A *Profile* will, in addition to configuration *Parameters*, define the CDN to which a server belongs and the “*Type*” of the Profile - which determines some behaviors of Traffic Control components. The allowed “*Types*” of *Profiles* are **not** the same as *Types*, and are maintained as a PostgreSQL “Enum” in `traffic_ops/app/db/create_tables.sql`.

Tip: A *Profile* of the wrong type assigned to a Traffic Control component *will* (in general) cause it to function incorrectly, regardless of the *Parameters* assigned to it.

See also:

The *Profiles and Parameters* overview section.

Queue

Queue Updates

Queue Server Updates *Queuing Updates* is an action that signals to various ATC components - most notably *cache servers* - that any configuration changes that are pending are to be applied now. Specifically, Traffic Monitor and Traffic Router are updated through a CDN *Snapshot*, and *not Queued Updates*. In particular, *ORT* will notice that the server on which it's running has new configuration, and will request the new configuration from Traffic Ops.

Updates may be queued on a server-by-server basis (in Traffic Portal's *Servers* view), a Cache Group-wide basis (in Traffic Portal's *Cache Groups* view), or on a CDN-wide basis (in Traffic Portal's *CDNs* view). Usually using the CDN-wide version is easiest, and unless there are special circumstances, and/or the user really knows what he or she is doing, it is recommended that the full CDN-wide *Queue Updates* be used.

This is similar to taking a CDN *Snapshot*, but this configuration change affects only servers, and not routing.

That seems like a vague difference because it is - in general the rule to follow is that changes to *Profiles* and *Parameters* requires only updates be queued, changes to the assignments of *cache servers* to *Delivery Services* requires both a *Snapshot* and a *Queue Updates*, and changes to only a *Delivery Service* itself (usually) entails a *Snapshot* only. These aren't exhaustive rules, and a grasp of what changes require which action(s) will take time to form. In general, when doing both *Queuing Updates* as well as taking a CDN *Snapshot*, it is advisable to first *Queue Updates* and *then* take the *Snapshot*, as otherwise Traffic Router may route clients to *Edge-tier cache servers* that are not equipped to service their request(s). However, when modifying the assignment(s) of *cache servers* to one or more *Delivery Services*, a *Snapshot* ought to be taken before updates are queued.

Warning: Updates to *Parameters* with certain *Config File* values may require running *ORT* in a different mode, occasionally manually. Though the server may appear to no longer have pending updates in these cases, until this manual intervention is performed the configuration *will not be correct*.

Region

Regions A group of *Physical Locations*.

reverse proxy

reverse proxies A *reverse proxy* acts on behalf of the *origin server* such that the client is (potentially) unaware it is not communicating directly with the *Origin*. All Edge-tier *cache servers* in a Traffic Control CDN are *reverse proxies*. To the end user a Traffic Control-based CDN appears as a *reverse proxy* since it retrieves content from the *origin server*, acting on behalf of that *origin server*. The client requests a URL that has a hostname which

resolves to the *reverse proxy*'s IP address and, in compliance with the HTTP 1.1 specification ([RFC 2616](#)), the client sends a `Host:` header to the *reverse proxy* that matches the hostname in the URL. The proxy looks up this hostname in a list of mappings to find the *Origin* hostname; if the hostname of the `Host:` header is not found in the list, the proxy will send an error (usually either `404 Not Found` or `503 Service Unavailable` as appropriate) to the client. If the supplied hostname is found in this list of mappings, the proxy checks its cache, and when the content is not already present, connects to the *Origin* to which the requested `Host:` maps requests the path of the original URL, providing the *Origin* hostname in the `Host` header. The proxy then stores the URL in its cache and serves the contents to the client. When there are subsequent requests for the same URL, a caching proxy serves the content out of its cache - provided [Cache Control Headers and Revalidation](#) are satisfied - thereby reducing latency and network traffic.

See also:

The [Apache Traffic Server documentation on reverse proxy](#).

To insert a *reverse proxy* into a typical HTTP 1.1 request and response flow, the *reverse proxy* needs to be told where the *origin server* can be reached (and which *Origin* to use for a given request when it's configured to proxy requests for multiple *Origins*). In ATS this is handled by adding rules to the [remap.config configuration file](#). The content owner must inform the clients, by updating the URL, to receive the content from the cache and not from the *origin server* directly. For example, clients might be instructed to request content from `http://www-origin-cache.cdn.com` which points to a *reverse proxy* for the actual *Origin* located at `http://www.origin.com`.

Now, if the client requests `/foo/bar/fun.html` from the *reverse proxy* the sequence of events is as follows. is given the URL `http://www-origin-cache.cdn.com/foo/bar/fun.html` (note the different hostname) and when attempting to obtain that URL, the following occurs:

1. The client sends a DNS request to the LDNS to resolve the name `www-origin-cache.cdn.com` to an IP address.
2. The LDNS finds an IP address for `www-origin-cache.cdn.com` e.g. `55.44.33.22`.
3. The client sends an HTTP request for `/foo/bar/fun.html` to the IP address.

1476: Client Requests Content from the *Reverse Proxy*

```
GET /foo/bar/fun.html HTTP/1.1
Host: www-origin-cache.cdn.com
```

4. The *reverse proxy* finds out the URL of the true *Origin* - in the case of ATS this is done by looking up `www-origin-cache.cdn.com` in its remap rules - and finds that it is `www.origin.com`.
5. The proxy checks its cache to see if the response for `GET /foo/bar/fun.html HTTP/1.1` from `www.origin.com` is already in the cache.
6. If the response is not in the cache:
 1. The proxy sends the request to the actual *Origin*

1477: *Reverse Proxy* Requests Content from the *origin server*

```
GET /foo/bar/fun.html HTTP/1.1
Host: www.origin.com
```

2. The *origin server* responds with the requested content

1478: Response from the *origin server*

```
HTTP/1.1 200 OK
Date: Sun, 14 Dec 2014 23:22:44 GMT
Server: Apache/2.2.15 (Red Hat)
Last-Modified: Sun, 14 Dec 2014
    ↪ 23:18:51 GMT
ETag: "1aa008f-2d-50a3559482cc0"
Content-Length: 45
Connection: close
Content-Type: text/html; charset=UTF-8

<!DOCTYPE html><html><body>This is a
    ↪ fun file</body></html>
```

3. The proxy sends the response on to the client, optionally adding a *Via:* header to indicate that the request was serviced by proxy.

1479: Resulting Response from the *Reverse Proxy* to the Client

```
HTTP/1.1 200 OK
Date: Sun, 14 Dec 2014 23:22:44 GMT
Last-Modified: Sun, 14 Dec 2014
    ↪ 23:18:51 GMT
ETag: "1aa008f-2d-50a3559482cc0"
Content-Length: 45
Connection: close
Content-Type: text/html; charset=UTF-8
Age: 0
Via: http/1.1 cache01.cdn.kabletown.
    ↪ net (ApacheTrafficServer/4.2.1
    ↪ [uScSsSfUpSeN:t cCSi p sS])
Server: ATS/4.2.1

<!DOCTYPE html><html><body>This is a
    ↪ fun file</body></html>
```

If, however, the response *was* already in the cache - and still valid according to the *Cache Control Headers and Revalidation* - the proxy responds to the client with the previously retrieved result.

1480: The *Reverse Proxy* Provides a Cached Response

```
HTTP/1.1 200 OK
Date: Sun, 14 Dec 2014 23:22:44 GMT
Last-Modified: Sun, 14 Dec 2014 23:18:51 GMT
ETag: "1aa008f-2d-50a3559482cc0"
Content-Length: 45
Connection: close
Content-Type: text/html; charset=UTF-8
Age: 39711
Via: http/1.1 cache01.cdn.kabletown.net_
    ↪(ApacheTrafficServer/4.2.1 [uScSsSfUpSeN:t cCSi p_
    ↪sS])
Server: ATS/4.2.1

<!DOCTYPE html><html><body>This is a fun file</body>
    ↪</html>
```

Role

Roles Permissions *Roles* define the operations a user is allowed to perform, and are currently an ordered list of permission levels.

Server Capability

Server Capabilities A *Server Capability* (not to be confused with a “Capability”) expresses the capacity of a *cache server* to serve a particular kind of traffic. For example, a *Server Capability* could be created named “RAM” to be assigned to *cache servers* that have RAM-disks allocated for content caching. *Server Capabilities* can also be required by *Delivery Services*, which will prevent *cache servers* without that *Server Capability* from being assigned to them. It also prevents *Mid-tier cache servers* without said *Server Capability* from being selected to serve upstream requests from those *Edge-tier cache servers* assigned to the requiring *Delivery Services*.

Service Category

Service Categories A *Service Category* defines the type of content being delivered by a *Delivery Service*. For example, a *Service Category* could be created named “linear” and assigned to a *Delivery Service* that delivers linear content.

Snapshot

Snapshots

CDN Snapshot

CDN Snapshots Previously called a “CRConfig” or “CRConfig.json” (and still called such in many places), this is a rather large set of routing information generated from a CDN’s configuration and topology.

Status

Statuses A *Status* represents the current operating state of a server. The default *Statuses* made available on initial startup of Traffic Ops are related to the *Health Protocol* and are explained in that section.

t3c The Traffic Control cache config app, used to generate and apply cache configuration files.

Tenant

Tenants

Tenancy

Tenancies Users are grouped into *Tenants* (or *Tenancies*) to segregate ownership of and permissions over *Delivery Services* and their resources. To be clear, the notion of *Tenancy* **only** applies within the context of *Delivery Services* and does **not** apply permissions restrictions to any other aspect of Traffic Control.

Topology

Topologies A structure composed of *Cache Groups* and parent relationships, which is assignable to one or more *Delivery Services*.

Topology Node

Topology Nodes

Parent Topology Node

Parent Topology Nodes

Child Topology Node

Child Topology Nodes Each *Topology Node* is associated with a particular *Cache Group*. In addition, the Topology Node has 0, 1, or 2 Parent Topology Nodes and has 0, 1, or 2 Child Topology Nodes, according to your configuration.

Type

Types A *Type* defines a type of some kind of object configured in Traffic Ops. Unfortunately, that is exactly as specific as this definition can be.

PYTHON MODULE INDEX

t

`to_access`, [2086](#)

`trafficops`, [2061](#)

`trafficops.__version__`, [2085](#)

`trafficops.utils`, [2085](#)

Symbols

- P TO_PASSWORD
command line option, 2059
- U TO_USER
command line option, 2060
- api-routes
traffic_ops command line option, 94
- api-version API_VERSION
toaccess command line option, 2086
- cache-host-name NAME
command line option, 2059
- cfg CONFIG
traffic_vault_migrate command line option, 327
- cfg CONFIG_FILE
reencrypt command line option, 210
- cfg CONFIG_PATH
traffic_ops command line option, 94
- compare
traffic_vault_migrate command line option, 323
- database database_name
sync_ts_databases command line option, 202
- days N
sync_ts_databases command line option, 202
- dbcfg DB_CONFIG_PATH
traffic_ops command line option, 94
- dir TSROOT
command line option, 2059
- dir directory
command line option, 127
- dry
traffic_vault_migrate command line option, 324
- dry_run
traffic_vault_util command line option, 2090
- dump
traffic_vault_migrate command line option, 323
- env ENVIRONMENT
admin command line option, 321
- fill DIR
traffic_vault_migrate command line option, 324
- fixtures FIXTURES
traffic_vault_migrate command line option, 327
- fromCfgPath=CFG
traffic_vault_migrate command line option, 324
- fromType=TYPE
traffic_vault_migrate command line option, 324
- full
toaccess command line option, 2087
- get-data DATA
command line option, 2058
- help
command line option, 2059
create_ts_databases command line option, 201
reencrypt command line option, 210
sync_ts_databases command line option, 202
toaccess command line option, 2086

```

    traffic_vault_migrate command
        line option, 324
--http port
    command line option, 127
--includeSystemTests ``no``/``yes``
    traffic_vault_migrate command
        line option, 327
--insecure
    toaccess command line option,
        2087
--list-plugins
    command line option, 2059
--logCfg CFG
    traffic_vault_migrate command
        line option, 324
--logLevel=LEVEL
    traffic_vault_migrate command
        line option, 323
--log-location-error ERROR_LOCATION
    command line option, 2058
--log-location-info INFO_LOCATION
    command line option, 2059
--log-location-warning
    WARNING_LOCATION
    command line option, 2060
--new-key NEW_KEY
    reencrypt command line option,
        210
--noConfirm
    traffic_vault_migrate command
        line option, 324
--num-retries N
    command line option, 2059
--password password
    create_ts_databases command
        line option, 201
--plugins
    traffic_ops command line option,
        94
--pretty
    toaccess command line option,
        2087
--previous-key PREVIOUS_KEY
    reencrypt command line option,
        210
--raw-path
    toaccess command line option,
        2087
--replication N
    create_ts_databases command
        line option, 201
--request-headers
    toaccess command line option,
        2087
--request-payload
    toaccess command line option,
        2087
--response-headers
    toaccess command line option,
        2087
--revalidate-only
    command line option, 2060
--riakcfg RIAK_CONFIG_PATH
    traffic_ops command line option,
        94
--set-queue-status QUEUE_STATUS
    command line option, 2059
--set-reval-status REVAL_STATUS
    command line option, 2058
--source-password password
    sync_ts_databases command line
        option, 202
--source-url URL
    sync_ts_databases command line
        option, 202
--source-user username
    sync_ts_databases command line
        option, 202
--started filename
    command line option, 127
--target-password password
    sync_ts_databases command line
        option, 202
--target-url URL
    sync_ts_databases command line
        option, 202
--target-user username
    sync_ts_databases command line
        option, 202
--toCfgPath=CFG
    traffic_vault_migrate command
        line option, 324
--toType=TYPE
    traffic_vault_migrate command
        line option, 324
--to-password PASSWORD

```


toaccess command line option, 2087	traffic_ops command line option, 95
--to-url URL toaccess command line option, 2087	-a API_VERSION toaccess command line option, 2086
--to-user USERNAME toaccess command line option, 2087	-a REVAL_STATUS command line option, 2058
--traffic-ops-disable-proxy command line option, 2059	-c traffic_vault_migrate command line option, 323
--traffic-ops-insecure command line option, 2059	-d traffic_vault_migrate command line option, 323
--traffic-ops-password TO_PASSWORD command line option, 2059	-d DATA command line option, 2058
--traffic-ops-timeout-milliseconds TIMEOUT command line option, 2060	-e ERROR_LOCATION command line option, 2058
--traffic-ops-url TO_URL command line option, 2060	-e LEVEL traffic_vault_migrate command line option, 323
--traffic-ops-user TO_USER command line option, 2060	-f toaccess command line option, 2087
--trafficvault admin command line option, 321	-f CFG traffic_vault_migrate command line option, 324
--url URL create_ts_databases command line option, 201	-g CFG traffic_vault_migrate command line option, 324
--user username create_ts_databases command line option, 201	-h command line option, 2059 toaccess command line option, 2086
--vault_action ACTION traffic_vault_util command line option, 2090	traffic_vault_migrate command line option, 324
--vault_ip IP traffic_vault_util command line option, 2090	-i DIR traffic_vault_migrate command line option, 324
--vault_password PASSWD traffic_vault_util command line option, 2090	-i INFO_LOCATION command line option, 2059
--vault_port PORT traffic_vault_util command line option, 2091	-k toaccess command line option, 2087
--vault_user USER traffic_vault_util command line option, 2091	-l command line option, 2059
--version command line option, 2060 toaccess command line option, 2087	-l CFG traffic_vault_migrate command line option, 324

-m traffic_vault_migrate command line option, [324](#)

-n NAME command line option, [2059](#)

-o TYPE traffic_vault_migrate command line option, [324](#)

-p command line option, [2059](#)
toaccess command line option, [2087](#)

-q QUEUE_STATUS command line option, [2059](#)

-r toaccess command line option, [2087](#)
traffic_vault_migrate command line option, [324](#)

-r N command line option, [2059](#)

-s command line option, [2059](#)

-t TIMEOUT command line option, [2060](#)

-t TYPE traffic_vault_migrate command line option, [324](#)

-u TO_URL command line option, [2060](#)

-v command line option, [2060](#)
toaccess command line option, [2087](#)

-w WARNING_LOCATION command line option, [2060](#)

-y command line option, [2060](#)

[302](#) content routing, [2095](#)

A

ACME Account, [2095](#)

add_ssl_keys_to_deliveryservice()
(*trafficops.TOSession* method), [2066](#)

admin command line option
--env ENVIRONMENT, [321](#)
--trafficvault, [321](#)
command, [321](#)

api_base_url (*trafficops.RestApiSession* property), [2061](#)

api_request() (in module *trafficops*), [2085](#)

api_version (*trafficops.RestApiSession* property), [2061](#)

assign_delivery_services_to_federations()
(*trafficops.TOSession* method), [2066](#)

assign_deliveryservice_servers_by_ids()
(*trafficops.TOSession* method), [2066](#)

assign_deliveryservice_servers_by_names()
(*trafficops.TOSession* method), [2066](#)

assign_federation_resolver_to_federations()
(*trafficops.TOSession* method), [2066](#)

assign_parameter_to_profile_ids()
(*trafficops.TOSession* method), [2067](#)

assign_profile_to_parameter_ids()
(*trafficops.TOSession* method), [2067](#)

associate_paramater_to_profile()
(*trafficops.TOSession* method), [2067](#)

associate_parameters_by_profile_id()
(*trafficops.TOSession* method), [2067](#)

associate_parameters_by_profile_name()
(*trafficops.TOSession* method), [2067](#)

astats (*stats_over_http*), [2095](#)

B

base_url (*trafficops.TOSession* property), [2067](#)

C

Cache Group, [2095](#)

Cache Groups, [2095](#)

Cache Server, [2096](#)

cache server, [2096](#)

cache servers, [2096](#)

cachegroups_queue_update() (*trafficops.TOSession* method), [2067](#)

CDN Snapshot, [2106](#)

CDN Snapshots, [2106](#)

cdns_queue_update() (*trafficops.TOSession* method), [2067](#)

Child Topology Node, [2107](#)

Child Topology Nodes, [2107](#)

close() (*trafficops.RestApiSession* method), [2061](#)

command
admin command line option, [321](#)
command line option

-P TO_PASSWORD, 2059
 -U TO_USER, 2060
 --cache-host-name NAME, 2059
 --dir TSROOT, 2059
 --dir directory, 127
 --get-data DATA, 2058
 --help, 2059
 --http port, 127
 --list-plugins, 2059
 --log-location-error
 ERROR_LOCATION, 2058
 --log-location-info
 INFO_LOCATION, 2059
 --log-location-warning
 WARNING_LOCATION, 2060
 --num-retries N, 2059
 --revalidate-only, 2060
 --set-queue-status QUEUE_STATUS,
 2059
 --set-reval-status REVAL_STATUS,
 2058
 --started filename, 127
 --traffic-ops-disable-proxy, 2059
 --traffic-ops-insecure, 2059
 --traffic-ops-password
 TO_PASSWORD, 2059
 --traffic-ops-timeout-milliseconds
 TIMEOUT, 2060
 --traffic-ops-url TO_URL, 2060
 --traffic-ops-user TO_USER, 2060
 --version, 2060
 -a REVAL_STATUS, 2058
 -d DATA, 2058
 -e ERROR_LOCATION, 2058
 -h, 2059
 -i INFO_LOCATION, 2059
 -l, 2059
 -n NAME, 2059
 -p, 2059
 -q QUEUE_STATUS, 2059
 -r N, 2059
 -s, 2059
 -t TIMEOUT, 2060
 -u TO_URL, 2060
 -v, 2060
 -w WARNING_LOCATION, 2060
 -y, 2060
 content routing, 2096
 copy_profile() (trafficops.TOSession
 method), 2068
 Coverage Zone File, 2096
 Coverage Zone Map, 2096
 create() (trafficops.RestApiSession
 method), 2061
 create_asn() (trafficops.TOSession
 method), 2068
 create_cachegroups() (traffi-
 cops.TOSession method), 2068
 create_cdn() (trafficops.TOSession
 method), 2068
 create_cdn_dns_sec_keys() (traffi-
 cops.TOSession method), 2068
 create_coordinates() (traffi-
 cops.TOSession method), 2068
 create_deliveryservice() (traffi-
 cops.TOSession method), 2068
 create_deliveryservice_regexes()
 (trafficops.TOSession method), 2068
 create_division() (trafficops.TOSession
 method), 2068
 create_federation() (traffi-
 cops.TOSession method), 2069
 create_federation_in_cdn() (traffi-
 cops.TOSession method), 2069
 create_federation_resolver() (traffi-
 cops.TOSession method), 2069
 create_federation_user() (traffi-
 cops.TOSession method), 2069
 create_job() (trafficops.TOSession
 method), 2069
 create_origins() (trafficops.TOSession
 method), 2069
 create_parameter() (trafficops.TOSession
 method), 2069
 create_profile() (trafficops.TOSession
 method), 2069
 create_region() (trafficops.TOSession
 method), 2070
 create_role() (trafficops.TOSession
 method), 2070
 create_server() (trafficops.TOSession
 method), 2070
 create_servercheck() (traffi-
 cops.TOSession method), 2070
 create_staticdnsentries() (traffi-
 cops.TOSession method), 2070

[create_tenant\(\)](#) (*trafficops.TOSession method*), 2070
[create_to_extension\(\)](#) (*trafficops.TOSession method*), 2070
[create_topology\(\)](#) (*trafficops.TOSession method*), 2070
[create_ts_databases](#) command line option
 --help, 201
 --password password, 201
 --replication N, 201
 --url URL, 201
 --user username, 201
[create_user\(\)](#) (*trafficops.TOSession method*), 2070
[create_user_with_registration\(\)](#) (*trafficops.TOSession method*), 2071

D

DATA
 toaccess command line option, 2086
Deep Coverage Zone File, 2097
Deep Coverage Zone Map, 2097
[delete\(\)](#) (*in module to_access*), 2088
[delete\(\)](#) (*trafficops.RestApiSession method*), 2061
[delete_asn\(\)](#) (*trafficops.TOSession method*), 2071
[delete_cache_group_parameters\(\)](#) (*trafficops.TOSession method*), 2071
[delete_cachegroups\(\)](#) (*trafficops.TOSession method*), 2071
[delete_cdn_by_id\(\)](#) (*trafficops.TOSession method*), 2071
[delete_cdn_dns_sec_keys\(\)](#) (*trafficops.TOSession method*), 2071
[delete_coordinates\(\)](#) (*trafficops.TOSession method*), 2071
[delete_deliveryservice_by_id\(\)](#) (*trafficops.TOSession method*), 2071
[delete_deliveryservice_regex_by_regex_id\(\)](#) (*trafficops.TOSession method*), 2071
[delete_deliveryservice_servers_by_id\(\)](#) (*trafficops.TOSession method*), 2072
[delete_deliveryservice_ssl_keys_by_xml_id\(\)](#) (*trafficops.TOSession method*), 2072
[delete_division\(\)](#) (*trafficops.TOSession method*), 2072
[delete_federation_in_cdn\(\)](#) (*trafficops.TOSession method*), 2072
[delete_federation_resolver\(\)](#) (*trafficops.TOSession method*), 2072
[delete_federation_user\(\)](#) (*trafficops.TOSession method*), 2072
[delete_job\(\)](#) (*trafficops.TOSession method*), 2072
[delete_origins\(\)](#) (*trafficops.TOSession method*), 2073
[delete_parameter\(\)](#) (*trafficops.TOSession method*), 2073
[delete_physical_location\(\)](#) (*trafficops.TOSession method*), 2073
[delete_profile_by_id\(\)](#) (*trafficops.TOSession method*), 2073
[delete_profile_parameter_association_by_id\(\)](#) (*trafficops.TOSession method*), 2073
[delete_region\(\)](#) (*trafficops.TOSession method*), 2073
[delete_role\(\)](#) (*trafficops.TOSession method*), 2073
[delete_server_by_id\(\)](#) (*trafficops.TOSession method*), 2073
[delete_staticdnsentries\(\)](#) (*trafficops.TOSession method*), 2073
[delete_to_extension\(\)](#) (*trafficops.TOSession method*), 2074
[delete_topology\(\)](#) (*trafficops.TOSession method*), 2074
Delivery Service, 2097
Delivery Service Request, 2098
Delivery Service Requests, 2098
Delivery Service required capabilities, 2098
Delivery Services, 2097
Division, 2098
Divisions, 2098
DSR, 2098
DSRs, 2098
E
Edge, 2098
Edge-Tier, 2098
Edge-tier, 2098
Edge-tier cache, 2098
Edge-tier cache server, 2098

Edge-tier cache servers, [2098](#)
 Edge-tier caches, [2098](#)
 environment variable
 MOJO_MODE, [97](#), [265](#), [321](#)
 SESSION_TIMEOUT_IN_SECS, [327](#), [329](#)
 TO_PASSWORD, [265](#), [266](#), [2059](#), [2060](#), [2087](#)
 TO_URL, [266](#), [327](#), [330](#), [2060](#), [2087](#), [2088](#)
 TO_USER, [265](#), [266](#), [2060](#), [2087](#), [2088](#)
 TO_USER_ADMIN, [328](#), [330](#)
 TO_USER_DISALLOWED, [328](#), [330](#)
 TO_USER_EXTENSION, [328](#), [330](#)
 TO_USER_FEDERATION, [328](#), [331](#)
 TO_USER_OPERATIONS, [328](#), [331](#)
 TO_USER_PASSWORD, [328](#), [330](#)
 TO_USER_PORTAL, [328](#), [331](#)
 TO_USER_READ_ONLY, [328](#), [331](#)
 TODB_DESCRIPTION, [327](#), [331](#)
 TODB_HOSTNAME, [327](#), [332](#)
 TODB_NAME, [327](#), [331](#)
 TODB_PASSWORD, [327](#), [332](#)
 TODB_PORT, [327](#), [332](#)
 TODB_SSL, [328](#), [332](#)
 TODB_TYPE, [328](#), [332](#)
 TODB_USER, [328](#), [332](#)

F

Federation, [2098](#)
 Federations, [2098](#)
 First-tier, [2099](#)
 First-tier cache, [2099](#)
 First-tier cache server, [2099](#)
 First-tier cache servers, [2099](#)
 First-tier caches, [2099](#)
 forward proxies, [2099](#)
 forward proxy, [2099](#)

G

generate_deliveryservice_ssl_keys() (trafficops.TOSession method), [2074](#)
 generate_deliveryservice_url_signature_keys() (trafficops.TOSession method), [2074](#)
 generate_iso() (trafficops.TOSession method), [2074](#)
 geo localization or geo routing, [2101](#)
 get() (in module to_access), [2088](#)
 get() (trafficops.RestApiSession method), [2062](#)
 get_all_cachegroup_parameters() (trafficops.TOSession method), [2074](#)
 get_all_deliveryservice_servers() (trafficops.TOSession method), [2074](#)
 get_api_capabilities() (trafficops.TOSession method), [2074](#)
 get_asns() (trafficops.TOSession method), [2074](#)
 get_authenticated_user() (trafficops.TOSession method), [2075](#)
 get_cache_stats() (trafficops.TOSession method), [2075](#)
 get_cachegroup_parameters() (trafficops.TOSession method), [2075](#)
 get_cachegroups() (trafficops.TOSession method), [2075](#)
 get_capabilities() (trafficops.TOSession method), [2075](#)
 get_cdn_dns_sec_keys() (trafficops.TOSession method), [2075](#)
 get_cdn_health_by_name() (trafficops.TOSession method), [2075](#)
 get_cdn_monitoring_info() (trafficops.TOSession method), [2075](#)
 get_cdn_ssl_keys() (trafficops.TOSession method), [2075](#)
 get_cdns() (trafficops.TOSession method), [2075](#)
 get_cdns_capacity() (trafficops.TOSession method), [2076](#)
 get_cdns_domains() (trafficops.TOSession method), [2076](#)
 get_cdns_health() (trafficops.TOSession method), [2076](#)
 get_cdns_routing() (trafficops.TOSession method), [2076](#)
 get_change_logs() (trafficops.TOSession method), [2076](#)
 get_change_logs_newcount() (trafficops.TOSession method), [2076](#)
 get_coordinates() (trafficops.TOSession method), [2076](#)
 get_current_snapshot_crconfig() (trafficops.TOSession method), [2076](#)
 get_delivery_service_capacity() (trafficops.TOSession method), [2076](#)
 get_delivery_service_health() (trafficops.TOSession method), [2076](#)

<code>get_delivery_service_stats()</code> (<i>trafficops.TOSession method</i>), 2077	<code>get_profiles()</code> (<i>trafficops.TOSession method</i>), 2079
<code>get_deliveryservice_ineligible_servers()</code> (<i>trafficops.TOSession method</i>), 2077	<code>get_regions()</code> (<i>trafficops.TOSession method</i>), 2079
<code>get_deliveryservice_regexes_by_id()</code> (<i>trafficops.TOSession method</i>), 2077	<code>get_roles()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_deliveryservice_servers()</code> (<i>trafficops.TOSession method</i>), 2077	<code>get_server_delivery_services()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_deliveryservice_ssl_keys_by_xml_id()</code> (<i>trafficops.TOSession method</i>), 2077	<code>get_server_details()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_deliveryservices()</code> (<i>trafficops.TOSession method</i>), 2077	<code>get_server_update_status()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_deliveryservices_regexes()</code> (<i>trafficops.TOSession method</i>), 2077	<code>get_servercheck_extensions()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_deliveryserviceserver()</code> (<i>trafficops.TOSession method</i>), 2077	<code>get_servers()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_divisions()</code> (<i>trafficops.TOSession method</i>), 2078	<code>get_staticdnsentries()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_federation_delivery_services()</code> (<i>trafficops.TOSession method</i>), 2078	<code>get_statuses()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_federation_resolvers()</code> (<i>trafficops.TOSession method</i>), 2078	<code>get_system_info()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_federation_resolvers_by_id()</code> (<i>trafficops.TOSession method</i>), 2078	<code>get_tenants()</code> (<i>trafficops.TOSession method</i>), 2080
<code>get_federation_users()</code> (<i>trafficops.TOSession method</i>), 2078	<code>get_topologies()</code> (<i>trafficops.TOSession method</i>), 2081
<code>get_federations()</code> (<i>trafficops.TOSession method</i>), 2078	<code>get_traffic_monitor_cache_stats()</code> (<i>trafficops.TOSession method</i>), 2081
<code>get_federations_for_cdn()</code> (<i>trafficops.TOSession method</i>), 2078	<code>get_types()</code> (<i>trafficops.TOSession method</i>), 2081
<code>get_jobs()</code> (<i>trafficops.TOSession method</i>), 2078	<code>get_user_by_id()</code> (<i>trafficops.TOSession method</i>), 2081
<code>get_origins()</code> (<i>trafficops.TOSession method</i>), 2078	<code>get_users()</code> (<i>trafficops.TOSession method</i>), 2081
<code>get_osversions()</code> (<i>trafficops.TOSession method</i>), 2079	
<code>get_parameters()</code> (<i>trafficops.TOSession method</i>), 2079	
<code>get_parameters_by_profile_id()</code> (<i>trafficops.TOSession method</i>), 2079	
<code>get_parameters_by_profile_name()</code> (<i>trafficops.TOSession method</i>), 2079	
<code>get_pending_snapshot_crconfig()</code> (<i>trafficops.TOSession method</i>), 2079	
<code>get_physical_locations()</code> (<i>trafficops.TOSession method</i>), 2079	
<code>get_plugins()</code> (<i>trafficops.TOSession method</i>), 2079	

H

`head()` (in module *to_access*), 2088
`head()` (*trafficops.RestApiSession method*), 2062

Health Protocol, 2101

I

Inner-tier, 2101
 Inner-tier cache, 2101
 Inner-tier cache server, 2101
 Inner-tier cache servers, 2101
 Inner-tier caches, 2101
 InvalidJSONError, 2061

`is_open` (*trafficops.RestApiSession* property), 2063

L

Last-tier, 2101

Last-tier cache, 2101

Last-tier cache server, 2101

Last-tier cache servers, 2101

Last-tier caches, 2101

localization, 2101

`log_with_debug_info`() (*in module trafficops.utils*), 2085

`logged_in` (*trafficops.TOSession* property), 2081

`login`() (*trafficops.TOSession* method), 2081

LoginError, 2061

M

Mid, 2101

Mid-Tier, 2101

Mid-tier, 2101

Mid-tier cache, 2102

Mid-tier cache server, 2102

Mid-tier cache servers, 2102

Mid-tier caches, 2102

module

 to_access, 2086

 trafficops, 2061

 trafficops.__version__, 2085

 trafficops.utils, 2085

MOJO_MODE, 97, 321

O

OperationError, 2061

`options`() (*in module to_access*), 2089

`options`() (*trafficops.RestApiSession* method), 2063

Origin, 2102

origin server, 2102

Origin Servers, 2102

origin servers, 2102

Origins, 2102

ORT, 2102

`output`() (*in module to_access*), 2089

P

Parameter, 2102

Parameters, 2102

parent, 2102

Parent Topology Node, 2107

Parent Topology Nodes, 2107

parents, 2102

`parse_arguments`() (*in module to_access*), 2089

`patch`() (*in module to_access*), 2089

`patch`() (*trafficops.RestApiSession* method), 2063

PATH

 toaccess command line option, 2086

Physical Location, 2102

Physical Locations, 2102

`post`() (*in module to_access*), 2089

`post`() (*trafficops.RestApiSession* method), 2063

Profile, 2102

Profiles, 2102

`put`() (*in module to_access*), 2089

`put`() (*trafficops.RestApiSession* method), 2064

Q

Queue, 2103

Queue Server Updates, 2103

Queue Updates, 2103

R

reencrypt command line option

 --cfg CONFIG_FILE, 210

 --help, 210

 --new-key NEW_KEY, 210

 --previous-key PREVIOUS_KEY, 210

Region, 2103

Regions, 2103

`replace_authenticated_user`() (*trafficops.TOSession* method), 2081

`request`() (*in module to_access*), 2089

`resp` (*trafficops.InvalidJSONError* attribute), 2061

`resp` (*trafficops.OperationError* attribute), 2061

RestApiSession (*class in trafficops*), 2061

reverse proxies, 2103

reverse proxy, 2103

RFC

 RFC 1035, 41, 456, 463, 473, 479, 996, 1002, 1013, 1019, 1580, 1587, 1597, 1604

RFC 1521, 2058
 RFC 2616, 4, 222, 256, 2104
 RFC 2616#section-14.9, 4
 RFC 2616#section-9.1.2, 256
 RFC 3339, 18, 262, 263, 389–391, 424, 439, 508, 556–558, 630, 677, 681, 926–928, 961, 978, 1049, 1099–1101, 1180, 1228, 1232, 1509–1511, 1545, 1562, 1634, 1666–1668, 1750, 1798, 1802, 2027, 2041, 2047
 RFC 4033, 175
 RFC 4044, 175
 RFC 4045, 175
 RFC 4122, 883, 1463, 2036
 RFC 4511, 109
 RFC 6781, 175
 RFC 6781#section-4.1.1.1, 176
 RFC 7129, 175
 RFC 7231#section-4, 256
 RFC 7516, 625, 627, 628, 1175, 1177, 1178, 1745–1748
 RFC 7518, 625, 627, 628, 1175, 1177, 1178, 1745, 1746, 1748

Role, [2106](#)

Roles, [2106](#)

S

Server Capabilities, [2106](#)

Server Capability, [2106](#)

`server_url` (*trafficops.RestApiSession* property), [2064](#)

`servers_queue_update()` (*trafficops.TOSession* method), [2081](#)

Service Categories, [2106](#)

Service Category, [2106](#)

`session` (*trafficops.RestApiSession* property), [2064](#)

`SESSION_TIMEOUT_IN_SECS`, [329](#)

Snapshot, [2106](#)

`snapshot_crconfig()` (*trafficops.TOSession* method), [2081](#)

Snapshots, [2106](#)

Status, [2106](#)

Statuses, [2107](#)

`sync_ts_databases` command line option
 --database *database_name*, [202](#)
 --days *N*, [202](#)

--help, [202](#)
 --source-password *password*, [202](#)
 --source-url *URL*, [202](#)
 --source-user *username*, [202](#)
 --target-password *password*, [202](#)
 --target-url *URL*, [202](#)
 --target-user *username*, [202](#)

T

`t3c`, [2107](#)

Tenancies, [2107](#)

Tenancy, [2107](#)

Tenant, [2107](#)

Tenants, [2107](#)

`to_access`
 module, [2086](#)

`TO_PASSWORD`, [265](#), [266](#), [2059](#), [2060](#), [2087](#)

`TO_URL`, [327](#), [330](#), [2060](#), [2087](#), [2088](#)

`to_url` (*trafficops.TOSession* property), [2082](#)

`TO_USER`, [265](#), [266](#), [2060](#), [2087](#), [2088](#)

`TO_USER_ADMIN`, [330](#)

`TO_USER_DISALLOWED`, [330](#)

`TO_USER_EXTENSION`, [330](#)

`TO_USER_FEDERATION`, [331](#)

`TO_USER_OPERATIONS`, [331](#)

`TO_USER_PASSWORD`, [330](#)

`TO_USER_PORTAL`, [331](#)

`TO_USER_READ_ONLY`, [331](#)

`toaccess` command line option
 --api-version *API_VERSION*, [2086](#)
 --full, [2087](#)
 --help, [2086](#)
 --insecure, [2087](#)
 --pretty, [2087](#)
 --raw-path, [2087](#)
 --request-headers, [2087](#)
 --request-payload, [2087](#)
 --response-headers, [2087](#)
 --to-password *PASSWORD*, [2087](#)
 --to-url *URL*, [2087](#)
 --to-user *USERNAME*, [2087](#)
 --version, [2087](#)
 -a *API_VERSION*, [2086](#)
 -f, [2087](#)
 -h, [2086](#)
 -k, [2087](#)
 -p, [2087](#)
 -r, [2087](#)

- v, 2087
 - DATA, 2086
 - PATH, 2086
 - TODB_DESCRIPTION, 331
 - TODB_HOSTNAME, 332
 - TODB_NAME, 331
 - TODB_PASSWORD, 332
 - TODB_PORT, 332
 - TODB_SSL, 332
 - TODB_TYPE, 332
 - TODB_USER, 332
 - Topologies, 2107
 - topologies_queue_update() (*trafficops.TOSession method*), 2082
 - Topology, 2107
 - Topology Node, 2107
 - Topology Nodes, 2107
 - TOSession (*class in trafficops*), 2064
 - traffic_ops command line option
 - api-routes, 94
 - cfg CONFIG_PATH, 94
 - dbcfg DB_CONFIG_PATH, 94
 - plugins, 94
 - riakcfg RIAK_CONFIG_PATH, 94
 - version, 95
 - traffic_vault_migrate command line option
 - cfg CONFIG, 327
 - compare, 323
 - dry, 324
 - dump, 323
 - fill DIR, 324
 - fixtures FIXTURES, 327
 - fromCfgPath=CFG, 324
 - fromType=TYPE, 324
 - help, 324
 - includeSystemTests
 - `no`/`yes`, 327
 - logCfg CFG, 324
 - logLevel=LEVEL, 323
 - noConfirm, 324
 - toCfgPath=CFG, 324
 - toType=TYPE, 324
 - c, 323
 - d, 323
 - e LEVEL, 323
 - f CFG, 324
 - g CFG, 324
 - h, 324
 - i DIR, 324
 - l CFG, 324
 - m, 324
 - o TYPE, 324
 - r, 324
 - t TYPE, 324
 - traffic_vault_util command line option
 - dry_run, 2090
 - vault_action ACTION, 2090
 - vault_ip IP, 2090
 - vault_password PASSWD, 2090
 - vault_port PORT, 2091
 - vault_user USER, 2091
 - trafficops
 - module, 2061
 - trafficops.__version__
 - module, 2085
 - trafficops.utils
 - module, 2085
 - Type, 2107
 - Types, 2107
- ## U
- update_asn() (*trafficops.TOSession method*), 2082
 - update_cachegroups() (*trafficops.TOSession method*), 2082
 - update_cdn_by_id() (*trafficops.TOSession method*), 2082
 - update_coordinates() (*trafficops.TOSession method*), 2082
 - update_deliveryservice_by_id() (*trafficops.TOSession method*), 2082
 - update_deliveryservice_regexes() (*trafficops.TOSession method*), 2082
 - update_deliveryservice_safe() (*trafficops.TOSession method*), 2083
 - update_division() (*trafficops.TOSession method*), 2083
 - update_federation_in_cdn() (*trafficops.TOSession method*), 2083
 - update_job() (*trafficops.TOSession method*), 2083
 - update_origins() (*trafficops.TOSession method*), 2083
 - update_parameter() (*trafficops.TOSession method*), 2083

method), [2083](#)
update_physical_location() (traffi-
cops.TOSession *method*), [2083](#)
update_profile_by_id() (traffi-
cops.TOSession *method*), [2083](#)
update_region() (trafficops.TOSession
method), [2084](#)
update_role() (trafficops.TOSession
method), [2084](#)
update_server_by_id() (traffi-
cops.TOSession *method*), [2084](#)
update_server_status_by_id() (traffi-
cops.TOSession *method*), [2084](#)
update_staticdnsentries() (traffi-
cops.TOSession *method*), [2084](#)
update_tenant() (trafficops.TOSession
method), [2084](#)
update_topology() (trafficops.TOSession
method), [2084](#)
update_user_by_id() (traffi-
cops.TOSession *method*), [2084](#)